คอมพิวเตอร์เกรดอุตสาหกรรม

K8-F17HI-3710

Industrial Mini PC

Key Benefit

- Factory Automation - HMI, SCADA, PLC Control
- Access Control - ระบบควบคุมการเข้าออก
- Point of Sale (POS) - ระบบขายหน้าร้าน
- IoT Gateway - รวบรวมข้อมูลจาก sensors
- Digital Signage - จอโฆษณาประหยัดไฟ

Industrial Mini PC ประหยัดสุดขั้น - พลัง 4 Core ในราคาที่จับต้องได้

การได้ Quad-Core ในระดับ TDP 6W ทำให้ได้ทั้งประสิทธิภาพและประหยัดไฟในเครื่องเดียว เหมาะสำหรับงานที่ต้องรันหลาย process พร้อมกันแต่ไม่ต้องการใช้ไฟเยอะ

Specification

CPU	Intel Pentium 3710
Clock Speed	1.6GHz~2.56GHz
Cores/Threads	4 Cores / 4 Threads
Cache	2 MB L2 Cache
TDP	6W
Architecture	Braswell
Intel Virtualization	Support VT-x, VT-d
Intel Hyper-Threading	Support
Memory	1×SO-DIMM DDR3 slot
Primary Storage	SSD (mSATA)
Secondary Storage	Optional HDD (supports expansion of a 2.5-inch hard drive)
Graphics	Intel HD Graphics
Audio Card	HD Audio ALC897

Display Mode	Dual Display (HDMI+VGA)
Max Resolution (VGA)	1920×1080
Max Resolution (HDMI)	3840×2160
Network	10/100/1000Mbps Adaptive, RTL 8111H / RTL8111GUS
WIFI+Bluetooth	Extendable WIFI+Bluetooth Module (M.2 PCIE)
OS Support	Windows 10 / Windows 11 / Linux
Serial Ports	4×RS232/RS485 COM
Video Ports	1×HDMI, 1×VGA
USB Ports	2×USB3.0, 2×USB2.0
Network Ports	2×RJ45
Other External Ports	1×RJ11, 1×PS2, 1×MIC&SPK
Power Input	1×DC_IN (Phoenix Connector)
Internal I/O Ports	4×COM, 1×F-PANEL, 1×PCIE GPIO, 1×CPU-FAN, 1×TPM Pin, 1×SATA HDD (SATA III), 1×LVDS, 1×SPEAKER(4pin), 1×SIM, 1×CMOS, AT_MODE(AUTO_PWR), 1×6pin, 1×USB2.0
Boot Mode	UEFI PXE / Auto-power-on / Wake-on-LAN / WDT / AMI 64M BIOS / Timed startup / Dynamic time startup

Working Temperature	-10~65°C
Working Humidity	0~95% (No Condensation)
Working Voltage	DC 12V - 5A
Static Electricity	Contact discharge 2K, Air discharge 6K
Storage Temperature	-10~60°C
Storage Humidity	0~95% (No Condensation)
Dimensions	L 197.4mm × W 126.3mm × H 47.5mm
Net Weight	1.2kg
Gross Weight	1.8kg
Features	Use aluminum alloy shell, industrial style, heavy and solid, unique appearance design
Heat Dissipation	Fanless Passive Cooling
Bracket	Dedicated bracket; Support VESA bracket
Packing List	Power Adapter×1, Power Cable×1, Bracket×1, User Manual×1, QA Card×1, Screws×1

I/O Port

01 PS2
02 RJ11
03 RS232 COM*4
04 MIC & SPK
05 USB2.0*4
06 RJ45 Gigabit LAN
07 USB3.0*2
08 HDMI
09 Indicator Light
10 VGA
11 DC_IN (Phoenix Connector)