คอมพิวเตอร์เกรดอุตสาหกรรม

K3-F18-6006

Industrial Mini PC

Key Benefit

- Factory Automation - ควบคุมเครื่องจักรผ่าน Serial ports
- HMI/SCADA Systems - แสดงผลข้อมูลระบบอุตสาหกรรม
- Edge Computing - ประมวลผลข้อมูล IoT
- Digital Signage - แสดงผล Dual monitor 4K
- Access Control - ระบบควบคุมการเข้าออก

Industrial Mini PC ตัวจริงสำหรับงานหนัก
ครบครันทุกการเชื่อมต่อ ทนทานทุกสภาพแวดล้อม

Specification

CPU	Intel Core i3-6006U @ 2.00GHz
Cores/Threads	2 Cores / 4 Threads
Cache	3MB Intel Smart Cache
TDP	15W
Architecture	Skylake
Memory	2×DDR4L slots, max support 32GB
Storage	SSD (M.2 2280) ×1, SATA3.0 ×1
Audio Card	HD Audio Realtek ALC 687
Graphics	Intel® HD Graphics 520
Network	Intel i211AT ×1, Intel i219 ×1
Extendable	M.2 PCIE ×1, miniPCIE ×1 (onboard SIM card slot)
OS Support	Windows & Linux
I/O Ports	6×Serial RS232/RS485 COM (Optional) 4×USB3.0, 4×USB2.0 2×HDMI, 2×RJ45 2×DC_IN (5525 + Phoenix Connector) 1×POW LED, 1×SDD LED
Internal I/O Ports	1×10pin GPIO, 1×4pin CPU_FAN 1×FP, 1×SPK, 1×SIM
Display Mode	4K Support, Dual Display (Duplicate/Extend mode)
HDMI Max Resolution	4096×2304@24Hz

Boot Mode	PXE / Auto-power-on / Wake-on-LAN
Intel Virtualization	Support
Intel Hyper-Threading	Support
Working Environment	Temperature: -20~50°C Relative Humidity: 50~90% (No Condensation)
Working Voltage	DC 12V - 5A
Static Electricity	Contact discharge 2K, Air discharge 6K
Storage Environment	Temperature: -20~50°C Relative Humidity: 50~90% (No Condensation)
Dimensions	L 133.8mm × W 126.6mm × H 54mm
Weight	Net: 1.25kg, Gross: 1.75kg
Heat Dissipation	Fanless Passive Cooling
Features	Aluminum alloy shell, industrial style Heavy and solid, unique appearance design
Bracket Options	VESA Mount, Din Rail, Embedded (Optional)
Packing	Kraft paper color box + Anti-fall corrugated outer box
Packing List	Power Adapter ×1, Power Cable ×1 VESA ×1 (optional), User Manual ×1 QA card ×1, Screws ×1

I/O Port

01 USB3.0*4
02 COM*6 (COM1 RS485 optional)
03 Indicator light (Power/Hard Disk)
04 Antenna hole
05 MIC/SPK
06 LAN*2
07 USB2.0*4
08 HDMI*2
09 DC 12V_IN
10 Phoenix Connector
(support wide voltage)
11 DC 12V_IN (5525)
12 Lock slot