GB4000 v1

คอมพิวเตอร์เกรดอุตสาหกรรม

Fanless Industrial Grade (4Lan+12COM)

6 x COM(4*RS485) + 6 x COM232(Phoenix)

2 x Intel i210/i219 + 2 x intel i226 2.5G

Product Highlights

- Fanless system without cooling fan, Brushed Full Aluminum Alloy shell for heat dissipation
- Industrial grade field operation, work continuously for 24 hours
- Less than 1% defective rate, super long lifetime and 1 years warranty
- 4 x RJ45 LANs, 12 COM ports (6 x DB9 COM with 4 ports supporting RS422/RS485 + 6 x RS232 Terminal)
- Built-in SIM card slot for 3G/4G Wi-Fi module
- Support VGA + HDMI dual display output synchronously
- Support Watchdog, AWAL, RTC, WOL, PXE, Reset functions

Technical Specifications

Feature	Specification
Processor Options	
Intel 4th Gen (Haswell)	Core i5-4278U (2.6GHz, Max 3.1GHz, 2C/4T, 3MB cache, TDP 28W)Core i7-4578U (3.0GHz, Max 3.5GHz, 2C/4T, 4MB cache, TDP 28W)
Intel 6th Gen (Skylake)	Core i3-6157U (2.4GHz, 2C/4T, 3MB cache, TDP 28W)
Intel 7th Gen (Kaby Lake)	Core i5-7267U (3.1GHz, Max 3.5GHz, 2C/4T, 4MB cache, TDP 28W)Core i7-7560U (2.4GHz, Max 3.8GHz, 2C/4T, 4MB cache, TDP 28W)
Intel 8th Gen	Core i5-8259U (2.3GHz, Max 3.8GHz, 4C/8T, 6MB cache, TDP 15W)Core i7-8560U (1.9GHz, Max 4.2GHz, 4C/8T, 8MB cache, TDP 15W)
Intel 10th Gen	Core i5-10210U (1.6GHz, Max 4.2GHz, 4C/8T, 6MB cache, TDP 15W)Core i7-10610U (1.8GHz, Max 4.9GHz, 4C/8T, 8MB cache, TDP 15W)
Intel 11th Gen	Core i5-1135G7 (2.4GHz, Max 4.2GHz, 4C/8T, 8MB cache, TDP 15W)Core i7-1195G7 (2.9GHz, Max 5.0GHz, 4C/8T, 12MB cache, TDP 15W)
Intel 12th Gen	Core i5-1235U (1.3GHz, Max 4.4GHz, 10C/12T, 12MB cache, TDP 15W)Core i7-1255U (1.7GHz, Max 4.7GHz, 10C/12T, 12MB cache, TDP 15W)Core i7-1260P (2.1GHz, Max 4.7GHz, 12C/16T, 18MB cache, TDP 28W)

Fanless Industrial Grade (4Lan+12COM)

Memory	1 x SO-DIMM DDR3L Slot (4th gen): up to 8GB2 x SO-DIMM DDR4 Slot (6-11th gen): up to 32GB2 x SO-DIMM DDR5 Slot (12-13th gen): up to 64GB
Storage	1 x M-SATA3.0 slot (4th gen only): 6Gb/s1 x M.2 slot for NVMe 2280 SSD (6-13th gen): 6Gb/s1 x SATA3.0 slot for HDD/SSD: 6Gb/s
Network	2 x Intel i210/i219 + 2 x Intel i226V 2.5G(11-13th CPU support 4 x Intel i226V)
I/O Ports	
Display	1 x VGA, 1 x HDMI (dual display supported)
COM Ports	6 x DB9 COM (4 ports support RS422/RS485)+ 6 x RS232 Terminal via Phoenix connector
USB	4 x USB 3.0, 2 x USB 2.0
LAN	4 x RJ45 Gigabit Ethernet
Audio	1 x MIC, 1 x SPK
Other	1 x PS/2 (keyboard and mouse 2-in-1)1 x GPIO (7-pin input, 7-pin output)1 x embedded SIM card slot
Expansion	1 x mini PCIe-half port (Wi-Fi/Bluetooth)1 x mini PCIe-full port (3G/4G/Wi-Fi/Bluetooth)1 x Extended I/O (LPC, USB, PCIe)
Physical	
Dimensions	248 × 150 × 83 mm
Weight	2.2 kg (net), 3.5 kg (gross)
Shell	Aluminum alloy body
Mounting	4 mounting holes on case
Cooling	Fanless design

Fanless Industrial Grade (4Lan+12COM)

Environmental	
Operating Temperature	-20°C to +60°C
Storage Temperature	-20°C to +70°C
Relative Humidity	10% ~ 90% @30°C (non-condensing)
Power	
Input	DC 9V ~ 36V
Recommended	12V/5A (4-8th gen), 19V-4.74A (10-13th gen)
OS Support	Windows 7/8/10/11, Linux, WES7/10
Package Contents	1 x Mini PC, 1 x Power Adapter, 1 x Power Cord 1 x Screws Bag, Wi-Fi antennas, 1 x HDMI cable 1 x User Manual, 1 x Long Screws Bag

Application Areas

Industrial Control Systems
- Factories with legacy machinery requiring multiple COM ports
- Automated manufacturing systems
- SCADA systems

Measurement & Testing Systems
- Scientific equipment requiring RS232/RS485 connections
- Laboratory testing apparatus
- Data acquisition systems

Building Management Systems (BMS)
- Environmental control systems
- Facility management systems
- Security and monitoring systems