



PRODUCT
DATASHEET '25

ADVANCE ANALYTIK

REVOLUTIONIZING ONLINE MONITORING SOLUTIONS



GAZ-AQMS-O3

Ozone Analyser

www.advanceanalytik.com

sales@advanceanalytik.com

Gaz-AQMS-03

Overview

Ozone analyzer adopts ultraviolet spectrometry principle and combines with advanced microprocessor technology. It provides accurate and reliable detection of O₃ at ppb* ppm level to meet the requirement of ambient gas monitoring.

UV absorption Ozone analyzer is developed based on Beer-Lambert technology. It is applied to monitor low concentration O₃ in ambient air.



254nm UV light passes through sample gas cell and is absorbed by ozone inside it. Adsorption value has a certain ratio with O₃ concentration. By cyclically alternating of magnetic valve and measuring sample gas and the sample without O₃, the true and reliable measured concentration of ozone is obtained at last.

This analyzer can completely control all functions and also provides online instruction for important work parameters. Real time auto compensation for temperature and pressure will be made during measurement.

Benefits:

- Measurement range: 0 - 20 ppm (autoranging)
- Dual measurement range and auto set range
- Ultraviolet spectrometry principle
- Multiple functional operations by microprocessor
- Task software is allowed to monitor task data during operation
- Continuous self-checking with alarm function
- Self-checking for intensity decaying of light source
- Bidirectional RS-232 port for remote control
- Digital output working parameter
- Response time optimized by signal filter technology of self-adaptation
- Compensation function for temperature and pressure
- USB and Ethernet interface
- Colorful display and screen touch operation
- Large memory and history data saved automatically

TECHNICAL SPECIFICATIONS

BASIC SPECIFICATION

Range	0 - 20 ppm (autoranging)
Concentration units	mg/m³, µg/m³, ng/m³, ppm, ppb or ppt
Lower detection limit	< 0.5 ppb
Linearity	< 1 % of full scale
Precision	0.1 ppm
Response time	30 seconds to 95 %
STP reference	0 °C, 20 °C, 25 °C at 101.3 kPa
Sample flow rate	500 cc/min
Temperature range	0 - 40 °C
Power	100 - 240 VAC, 50 - 60 Hz (autoranging)
Power consumption	260 VA (max at start-up); 150 VA (nominal);
Dimensions	429 × 175 × 638 mm
Rack spacing	3.5 RU
Weight	17.2 kg

**Note -**

This data sheet serves as general information about the Gaz-AQMS-03. For specific technical details, installation guidelines, and troubleshooting assistance, please refer to the official user manual provided with the product.

For inquiries and detailed technical information, please contact sales@advanceanalytik.com.



LET'S CONNECT !

Let's work together to find a solution that works for you



Contact Us :

+36 70328 6862

1132, Budapest Váci ut 16 Faz 12. ajto

<https://advanceanalytik.com>

sales@advanceanalytik.com

