




VizSens-EC(D)

Conductivity Sensor



www.advanceanalytik.com

 **ADVANCE
ANALYTIK**

VizSens-EC(D)

Conductivity Sensor

Introducing the VizSens-EC(D) Conductivity Sensor with a durable PPS Shell. This sensor offers precision, reliability, and versatility, making it an ideal solution for diverse applications. It features a wide measurement range with automatic range switching, ensuring accurate results even in challenging conditions. With an accuracy of $\pm 2\%$ F.S. and temperature compensation up to 60°C , this sensor delivers dependable conductivity measurements. Compact, IP68 rated, and supporting MODBUS RS485 communication, it offers easy installation with its $3/4$ mounting thread and standard 10-meter cable.



Product Features

- **Electrical Safety:** Equipped with power supply and output isolation design for enhanced electrical safety.
- **Anti-Interference:** Built-in protection circuit for power supply and communication chip, offering strong anti-interference ability.
- **Comprehensive Protection:** Features comprehensive protection circuit design, ensuring reliable operation without additional equipment.
- **Internal Circuit Design:** Circuit part integrated within the electrode, providing environmental tolerance and easy installation.
- **Communication Interface:** RS-485 transmission interface, MODBUS-RTU communication protocol, supporting two-way communication and remote command reception.
- **Advanced Diagnostics:** Offers additional electrode diagnostic information, enhancing intelligent monitoring capabilities.
- **Integrated Memory:** Internal memory stores calibration and setting information, even after power-off.



VizSens-EC(D)

Technical Specifications

Physical Specifications	
Main Material	PPS Shell
Dimensions	Dia26mm * Length 166mm
Cable Length	Standard: 10M, Max. extendable to 200M
Mounting Thread	3/4" thread
Measurement Specifications - Conductivity	
Measurement Range	0.0~200.0 us/cm
Communication Protocol	0-2000 us/cm
Power Supply	0.01-20.00 ms/cm (Automatic switch)
Accuracy	±2%F.S.
Resolution	Depending on the range: 0.01 ms/cm, 0.1 us/cm, 1 us/cm (Automatic switch)
Repeatability	±1%
Temperature Specifications	
Temperature Compensation	0-60°C
Electrode Temperature Resistance	0~60°C (Non-freezing)
Pressure Specifications	
Pressure Range	0-0.1 Mpa
Electrical Specifications	
Power Supply	12VDC
Communication Protocol	MODBUS RS485
Protection and Communication	
Protective Rate	IP68 (Protective casing)

Measurement Principle


The Conductivity Sensor employs a glass platinum electrode. Conductivity is determined through the ohmic formula based on voltage and current values. The sensor's precision and reliability make it a valuable tool for accurate conductivity measurements.



APPLICATIONS

**Wastewater Treatment**

Ensuring proper conductivity levels in wastewater treatment facilities.

**Water Plants**

Precise monitoring of conductivity levels for optimal water treatment processes.

**Swimming Pools**


Monitoring conductivity for maintaining safe and comfortable swimming pool conditions.

**Hydrological Monitoring**

Accurate measurement of conductivity in natural water bodies for environmental assessment.

**Fertilizers and Chemicals**

Monitoring conductivity in fertilizer and chemical solutions for quality control.

**Fish Ponds**

Controlling conductivity to create a suitable environment for aquatic life in fish ponds.

**Note -**

This data sheet serves as general information about the VizSens-EC(D) . For specific technical details, installation guidelines, and troubleshooting assistance, please refer to the official user manual provided with the product.

For inquiries and detailed technical information, please contact info@advanceanalytik.com .

ADVANCE ANALYTIK



Advance Analytik KFT
1132, Budapest Váci ut 16
Faz 12. ajtó
+36 70 328 6862
sales@advanceanalytik.com



www.advanceanalytik.com