



PRODUCT
DATASHEET '24

ADVANCE ANALYTIK

REVOLUTIONIZING ONLINE MONITORING SOLUTIONS



Viz Classic Conductivity/TDS

Single Channel Transmitter with HART

www.advanceanalytik.com
sales@advanceanalytik.com

Viz Classic

Single Channel Transmitter with HART

The Viz Classic Series features a high-performance two-wire transmitter for accurate conductivity and Total Dissolved Solids (TDS) measurements. This single-channel device ensures reliable data for water quality monitoring across various applications, making it ideal for both industrial and environmental use. With HART protocol support, it allows seamless integration with control systems, facilitating real-time data transmission and diagnostics. The compact and durable design simplifies installation while providing long-lasting performance in challenging conditions. The Viz Classic Series is ideal for use in water and wastewater treatment, industrial processes, aquaculture, desalination plants, and other industries where precise TDS and Conductivity control is vital.



Product Features

- **HART Protocol:** Supports HART communication for easy integration with existing control systems, enabling real-time data transmission and diagnostics.
- **Two-Wire Configuration:** Simplifies installation by using existing power lines for both power and signal, reducing installation complexity and costs.
- **Wide Measurement Range:** Ideal for diverse applications, ensuring accurate monitoring in various environmental and industrial settings.
- **User-Friendly Design:** Features a straightforward interface for quick setup and adjustments, enhancing operational efficiency.
- **Rugged Construction:** Built to withstand challenging conditions, ensuring durability and long-lasting performance.



Viz Classic (Conductivity/ TDS)	Single Channel Universal Controller Display: 16x2 Character display Mounting: 2 different models: Wall mount / Panel mount Output: 4 - 20 mA with HART protocol on the signal line Range: As per cell constant given below 0 : .01 0 - 50 uS/cm 0.1 : 0-500 us/cm 1 : 0-5000 us/cm 10 : 0-50000 us/cm Communication protocol: HART 7 Protocol Enclosure: IP65 for Wall mount, or Only front facia IP65 for Panel Mount Calibration: Dual/three Point Sensor Calibration, Current Loop Calibration Cable Connection: PG9 Polyurethane Glands: 2Nos Resolution: 0.01, 0.1, 1, 10 as per cell constant
--	--

Technical Specification of VIZ Classic Series Transmitter

Viz Classic - Single Channel Transmitter

INPUTS	Conductivity - Analog type TDS - Analog type Temperature - PT100 / PT1000 software Selectable
OUTPUTS	1 x 4 - 20 mA with HART protocol on the signal line
MOUNTING	2 different models: Wall mount / Panel mount
RANGE	As per cell constant given below 0.01 : 0 - 50 uS/cm 0.1 : 0-500 us/cm 1 : 0-5000 us/cm 10 : 0-50000 us/cm
POWER SUPPLY	12-32V DC, Loop Powered (Single line for Power and Output signal)
DISPLAY	16x2 Character display
COMMUNICATION INTERFACE	• HART Version: Compatible with HART 5, 6, and 7 • Device Diagnostics: Includes basic device and process diagnostics • Digital Communication: Two-way communication for calibration, configuration, and diagnostics • Protocol Support: Standard HART Protocol with 4-20 mA analog signal
TEMPERATURE	-20 to 200 deg C , Compensation : Integrated
ENCLOSURE	IP65 for Wall mount, or Only front facia IP65 for Panel Mount
CALIBRATION	Dual/three Point Sensor Calibration, Current Loop Calibration Two point Temperature Calibration
DIAGNOSTICS	Sensor Open / Short, Temp Sensor Open/ Short, Out of range Calibration error, Test output current
CABLE CONNECTIONS	PG9 Polyurethane Glands: 2Nos
DIMENSIONS	12.7 x 5.7 x 7.9 cm L*W*H <i>*Dimensions subject to change depending on configuration*</i>

APPLICATIONS



Water Treatment Plants

For monitoring water quality in treatment processes and ensuring compliance with regulatory standards.



Environmental Monitoring

For assessing water quality in natural ecosystems, identifying pollution sources, and protecting aquatic biodiversity.



Aquaculture Farms

To maintain optimal conditions for aquatic life, allowing for healthy growth and production.



Research Institutions

For conducting scientific studies related to water quality and environmental monitoring.



Industrial Process Control

For quality control in industrial processes that involve water usage.



Wastewater Treatment

To monitor and optimize the efficiency of wastewater treatment processes.



Food and Beverage Production

For ensuring the quality of water used in food and beverage production, meeting industry standards.



Note -

This data sheet serves as general information about the SINGLE CHANNEL CONTROLLER. For specific technical details, installation guidelines, and troubleshooting assistance, please refer to the official user manual provided with the product.

For inquiries and detailed technical information, please contact sales@advanceanalytik.com.



LET'S CONNECT !

Let's work together to find a solution that works for you



Contact Us :

+36 70328 6862

1132, Budapest Váci ut 16 Faz 12. ajto

<https://advanceanalytik.com>

sales@advanceanalytik.com

