



COMPANY
PROFILE '24-25

ADVANCE ANALYTIK

REVOLUTIONIZING ONLINE MONITORING SOLUTIONS



www.advanceanalytik.com
sales@advanceanalytik.com




We, Advance Analytik KFT are a Budapest Hungary based manufacturing company. Our company's long-standing presence in Budapest and our dedication to developing high-quality products our operation is a testament to our success and adaptability in the industry. With a strong commitment to precision and performance, we offer a comprehensive range of advanced analytical instruments, including analog & digital sensors, controllers and modular analyzers. We prioritize knowledge exchange and collaboration with our suppliers, customers, and sales partners. Such partnerships are essential for fostering innovation and staying up-to-date with the latest advancements in technology and processes.


SKILLS & STRENGTH

We have a diverse set of skills and resources that enable us to approach different situations with precision. Our ability to manufacture electronics and optical equipments, and develop software, gives us a wide range of tools to work with and allows us to create our own solutions to problems. The fact that we have developed our own software that is integrated with our analyzers and provides real-time measurements is particularly impressive.

This not only demonstrates our technical capabilities but also your ability to innovate and create customized solutions that meet your specific needs.



ELECTRONICS



OPTICS



FLUIDS



CHEMISTRY



THERMAL



**STRONG & RELIABLE
PARTNERSHIPS**



**QUALITY &
PERFORMANCE**



**RESEARCH &
DEVELOPMENT**



VIZ ECO SOLO
(Single Channel Transmitter)

The Advance Analytik Viz-Eco-Solo, a Single - channel transmitter, is an advanced instrument designed for comprehensive water quality monitoring. Compatible with multiple different sensors such as pH, DO, ORP, conductivity, turbidity, SS, COD, BOD, TOC, TSS, TDS, Nitrate, Nitrite, Color, Sludge Level, ISE, Residual Chlorine and others, this device offers versatility for a wide range of applications. Its plug-and-play sensor integration simplifies setup, while the flexible configuration allows users to adapt the system to their specific monitoring needs. The transmitter's user-friendly interface enables real-time data visualization and seamless integration with data logging systems, ensuring efficient data management.

Technical Specifications

INPUTS	Select any one Sensor (Digital/Analog/ISE) pH - Analog, Digital ORP - Analog, Digital Chlorine Sensor - Potentiometric/ISE Conductivity/Total Dissolved solids - Analog/Digital Dissolved Oxygen - Optical (Digital Type) Turbidity - Optical (Digital Type) Sludge Level - Optical (Digital Type) UV-VIS Sensor - Any One - COD,BOD,TOC,TSS,Nitrate,Nitrite,Color Total Suspended solids - IR Based Ion Selective Electrode - Analog
OUTPUTS	1 x 4-20mA active output (load of 500 ohm max)
RELAYS	1 x electromechanical SPDT (Form C) contact, 5 A Programmable individually for high or low alarm.
MEMORY	16 GB Memory Card Slot (Stores 1 Year measurement Data) Depending upon measurement cycle frequency. <i>*Memory card can be made available upon request*</i>
POWER SUPPLY	AC power supply: 80 - 265 VAC (50/60Hz); DC power supply: 9-36VDC
DISPLAY	128*64 dot matrix LCD with LED backlight
COMMUNICATION INTERFACE	Modbus RS485, 4-20mA
CERTIFICATIONS	IP65/NEMA4X
ENCLOSURE	Glass-filled nylon synthetic polyamide thermoplastic (top cover); Aluminum powder dusting (lower shell)
DIMENSIONS	145 x 125 x 162 mm L*W*H
WEIGHT	1.5Kg
OPERATING TEMPERATURE	-15 to 60°C



VIZ ECO DUO
(Dual Channel Transmitter)

The Viz-Eco-Duo Parameter Transmitter is an advanced solution for simultaneous monitoring of diverse parameters, catering to a wide range of customer requirements. Compatible with multiple different sensors and offers versatility for a wide range of applications. With support for up to 2 sensors, various data transmission options, and a user-friendly interface, the Viz-Eco-Duo ensures efficient integration, reduced operational costs, and reliable parameter monitoring.

Technical Specifications

INPUTS	Select any two Sensor (Digital/Analog/ISE) pH - Analog, Digital ORP - Analog, Digital Chlorine Sensor - Potentiometric/ISE Conductivity/Total Dissolved solids - Analog/Digital Dissolved Oxygen - Optical (Digital Type) Turbidity - Optical (Digital Type) Sludge Level - Optical (Digital Type) UV-VIS Sensor - Any One - COD,BOD,TOC,TSS,Nitrate,Nitrite,Color Total Suspended solids - IR Based Ion Selective Electrode - Analog
OUTPUTS	2 x 4-20mA active output (load of 500 ohm max)
RELAYS	2 x electromechanical SPDT (form C) contact, 5 A Programmable individually for high or low alarm.
MEMORY	16 GB Memory Card Slot (Stores 1 Year measurement Data) Depending upon measurement cycle frequency. <i>*Memory card can be made available upon request*</i>
POWER SUPPLY	AC power supply: 80 - 265 VAC (50/60Hz); DC power supply: 9-36VDC
DISPLAY	128*64 dot matrix LCD with LED backlight
COMMUNICATION INTERFACE	Modbus RS485, 4-20mA
CERTIFICATIONS	IP65/NEMA4X
ENCLOSURE	Glass-filled nylon synthetic polyamide thermoplastic (top cover); Aluminum powder dusting (lower shell)
DIMENSIONS	145 x 125 x 162 mm L*W*H
WEIGHT	1.5Kg
OPERATING TEMPERATURE	-15 to 60°C



VIZ ECO MULTI
(Multiple Channel Transmitter)

The Viz Eco Multi is a multi-channel transmitter that offers an advanced solution for monitoring multiple parameters simultaneously, meeting a variety of customer needs. Designed for applications in water quality monitoring across wastewater treatment plants, waterworks, water stations, surface water, and industrial settings, this versatile transmitter brings unparalleled flexibility and ease of use to the field. With support for up to 7 sensors, various data transmission options, and a user-friendly interface, the Viz Eco Multi ensures efficient integration, reduced operational costs, and reliable parameter monitoring.

Technical Specifications

Electrical Specifications	
Power Supply	AC: 85 - 265 VAC; DC: 9 - 36 VDC
Communication Protocol	MODBUS RS485 (standard), 4G: UDP/TCP, NB: UDP (optional)
Physical Specifications	
Main Material	(Glass-filled nylon synthetic polyamide thermoplastic) (top cover); Aluminum powder dusting (lower shell)
Protective Rate	IP65/ NEMA4X
Dimensions	260mm x 200mm x 123.3mm (L×W×H)
Weight	2.0KG
Environmental Specifications	
Operating temperature	-15 to 60°C
Supported Parameters and Sensors	
Supported Sensors	Up to 7 sensors
Display and Interface	
Screen	7-inch color touch screen
User Interface	Intuitive and user-friendly menu
Data Transmission	
Transmission Methods	4~20mA, MODBUS RS485, Wireless (optional)
Output	
Analog Output	8 x 4-20mA active output (load of 500 ohm max)
Relay	4 x electromechanical SPDT (form C) contact, 5 A Programmable individually for high or low alarm.



VIZ PRO SINGLE
(Single Channel Transmitter)

The Advance Analytik Viz Pro Single - channel transmitter is an advanced instrument designed for comprehensive water quality monitoring. Capable of measuring multiple parameters such as pH, DO, ORP, conductivity, turbidity, SS, and others, this device offers versatility for a wide range of applications. Its plug-and-play sensor integration simplifies setup, while the flexible configuration allows users to adapt the system to their specific monitoring needs. The transmitter's user-friendly interface enables realtime data visualization and seamless integration with data logging systems, ensuring efficient data management.

Technical Specifications

INPUTS	Select any one Sensor (Digital/Analog/4 to 20mA/ISE) pH - Analog pH - Digital ORP - Analog ORP - Digital Chlorine Sensor - Potentiometric Conductivity/Total Dissolved solids - Analog/Digital Dissolved Oxygen - Polarographic/Optical Turbidity - Digital Sludge Level - Optical/Digital UV-VIS Sensor - (COD,BOD,TOC,TSS,Color,UV 254) Total Suspended solids - IR Based Ion Selective Electrode - Analog/4 to 20 mA Temperature - PT100,PT1000, RTD, Thermocouple
OUTPUTS	1 x 4-20mA active output (load of 500 ohm max)
RELAYS	2 x electromechanical SPDT (Form C) contact, 5 A Programmable individually for high or low alarm.
FREE SOCKETS	2 x free sockets for additional modules among 4-20mA input module, 2-wire or 4-wire (15V DC source, 50 mA max) 4-20mA active output
MEASURING MODE	Continuous/Cyclic/Dynamic Mode
MEMORY	16 GB Memory Card (Stores 1 Year measurement Data) Depending upon measurement cycle frequency.
POWER SUPPLY	90 - 265 VAC 47/63 Hz or 24V DC 0.5 A
TOUCH SCREEN	5.0" Inch Color TFT LCD 800 x 480 pixels with Industrial projected capacitive touch screen.
COMMUNICATION INTERFACE	RS 232 and RS 485
CERTIFICATIONS	CE, EN 61010-1, EN 61326, IP66, IP68
ENCLOSURE	IP66, IP68 (24 Hours-2M Depth) Industrial Polycarbonate Housing Optional pipe mounting brackets/ Pole Mounting/Wall Mounting/Panel Mounting Brackets.
DIMENSIONS	296 x 225 x 185 mm
WEIGHT	3Kg approx. (Depending on Configuration)



VIZ PRO DUAL
(Dual Channel Transmitter)

Capable of measuring multiple parameters such as pH, DO, ORP, conductivity, turbidity, SS, and others, this device offers versatility for a wide range of applications. Its plug-and-play sensor integration simplifies setup, while the flexible configuration allows users to adapt the system to their specific monitoring needs. The transmitter's user-friendly interface enables real-time data visualization and seamless integration with data logging systems, ensuring efficient data management. This enables timely interventions, ensuring water safety and sustainability for the benefit of both ecosystems and human populations.

Technical Specifications

INPUTS	Select any two Sensor (Digital/Analog/4 to 20 mA/ISE) pH - Analog pH - Digital ORP - Analog ORP - Digital Chlorine Sensor - Potentiometric Conductivity/Total Dissolved solids - Analog/Digital Dissolved Oxygen - Polarographic/Optical Turbidity - Digital Sludge Level - Optical/Digital UV-VIS Sensor - (COD,BOD,TOC,TSS,Color,UV 254) Total Suspended solids - IR Based Ion Selective Electrode - Analog/4 to 20 mA Temperature - PT100,PT1000, RTD, Thermocouple
OUTPUTS	2 x 4-20mA active output (load of 500 ohm max)
RELAYS	2 x electromechanical SPDT (Form C) contact, 5 A Programmable individually for high or low alarm.
FREE SOCKETS	4 x free sockets for additional modules among 4-20mA input module, 2-wire or 4-wire (15V DC source, 50 mA max) 4-20mA active output
MEASURING MODE	Continuous/Cyclic/Dynamic Mode
MEMORY	16 GB Memory Card (Stores 1 Year measurement Data) Depending upon measurement cycle frequency.
POWER SUPPLY	90 - 265 VAC 47/63 Hz or 24V DC 0.5 A
TOUCH SCREEN	5.0" Inch Color TFT LCD 800 x 480 pixels with Industrial projected capacitive touch screen.
COMMUNICATION INTERFACE	RS 232 and RS 485
CERTIFICATIONS	CE, EN 61010-1, EN 61326,IP66,IP68
ENCLOSURE	IP66, IP68 (24 Hours-2M Depth) Industrial Polycarbonate Housing Optional pipe mounting brackets/ Pole Mounting/Wall Mounting/Panel Mounting Brackets.
DIMENSIONS	296 x 225 x 185 mm
WEIGHT	3Kg approx. (Depending on Configuration)



VIZ PRO MULTI
(Multiple Channel Transmitter)

The Viz Multi-Parameter Transmitter is an advanced solution for simultaneous monitoring of diverse parameters, catering to a wide range of customer requirements. Designed for applications in water quality monitoring across wastewater treatment plants, waterworks, water stations, surface water, and industrial settings, this versatile transmitter brings unparalleled flexibility and ease of use to the field. With support for up to 4 sensors, various data transmission options, and a user-friendly interface, the Viz Multi ensures efficient integration, reduced operational costs, and reliable parameter monitoring.

Technical Specifications

INPUTS	Select any four Sensor (Digital/Analog/4 to 20 mA/ISE) pH - Analog pH - Digital ORP - Analog ORP - Digital Chlorine Sensor - Potentiometric Conductivity/Total Dissolved solids - Analog/Digital Dissolved Oxygen - Polarographic/Optical Turbidity - Digital Sludge Level - Optical/Digital UV-VIS Sensor - (COD,BOD,TOC,TSS,Color,UV 254) Total Suspended solids - IR Based Ion Selective Electrode - Analog/4 to 20 mA Temperature - PT100,PT1000, RTD, Thermocouple
OUTPUTS	4 x 4-20mA active output (load of 500 ohm max)
RELAYS	4 x electromechanical SPDT (Form C) contact, 5 A Programmable individually for high or low alarm.
FREE SOCKETS	6 x free sockets for additional modules among 4-20mA input module, 2-wire or 4-wire (15V DC source, 50 mA max) 4-20mA active output
MEASURING MODE	Continuous/Cyclic/Dynamic Mode
MEMORY	16 GB Memory Card (Stores 1 Year measurement Data) Depending upon measurement cycle frequency.
POWER SUPPLY	90 - 265 VAC 47/63 Hz or 24V DC 0.5 A
TOUCH SCREEN	5.0" Inch Color TFT LCD 800 x 480 pixels with Industrial projected capacitive touch screen.
COMMUNICATION INTERFACE	RS 232 and RS 485
CERTIFICATIONS	CE, EN 61010-1, EN 61326,IP66,IP68
ENCLOSURE	IP66, IP68 (24 Hours-2M Depth) Industrial Polycarbonate Housing Optional pipe mounting brackets/ Pole Mounting/Wall Mounting/Panel Mounting Brackets.
DIMENSIONS	296 x 225 x 185 mm
WEIGHT	3Kg approx. (Depending on Configuration)

ANALOG SENSORS



VizSens-PH(Analog)

The pH Sensor is widely used in pH monitoring in water treatment, hydrological monitoring, wastewater treatment, swimming pools, fish ponds and fertilizers, chemicals, and biology. It uses a composite electrode in which a glass indicating electrode and a reference electrode are combined to measure the pH of the water.



VizSens-ORP(Analog)

The VizSens-ORP(A) ORP sensor is a combination electrode that includes a metals indicator electrode with a reference electrode. It measures the difference between the working battery composed of the measuring electrode and the reference electrode in a solution. By utilizing the linear relationship between the ORP value of the measuring solution and the potential of the working battery.



VizSens-EC(Analog)

The VizSens-EC(A) Conductivity Sensor, featuring a glass platinum electrode, is a reliable instrument for accurate conductivity monitoring. It utilizes voltage and current values to determine conductivity, making it an essential tool for applications in water treatment, hydrological monitoring, wastewater treatment, swimming pools, as well as in fertilizers, chemicals, and biology industries.

DIGITAL SENSORS



VizSens-PH(Digital)

The PPH-500B pH is a digital pH sensor with an RS485 communication interface and the standard Modbus protocol. Stainless steel corrosion resistant shell, IP68 protection grade, built-in PT1000 thermistor and compensation algorithm, with high precision, long life, small drift and other advantages, suitable for all kinds of harsh working environment.



VizSens-EC(Digital)

VizSens-EC(D) Conductivity Sensor with a durable PPS(polyphenylene) Shell. This sensor offers precision, reliability, and versatility, making it an ideal solution for diverse applications. It features a wide measurement range with automatic range switching, ensuring accurate results even in challenging conditions.



VizSens-ODO

The VizSens-ODO Optical Dissolved Oxygen Sensor utilizes fluorescence technology to accurately measure dissolved oxygen concentration. A luminescent material on the sensor's cap is excited by blue LED light, emitting red light. The intensity and time of the red light are indicative of oxygen molecule concentration, enabling precise calculations.



VizSens-RCL

A constant voltage principle to measure these components in water. The instrument utilizes stable electric potential and current signals to calculate concentrations, offering a simple structure, easy maintenance, and exceptional accuracy.



VizSens-UVCOD

The VizSens-UVCOD series COD/BOD/TSS/TOC sensor represents a new era in environmental protection sensors, offering reagent-free, pollution-free, economical, and eco-friendly water quality monitoring. This sensor is compact, easily installable, and enables online continuous monitoring.



VizSens-SS

The VizSens-SS Sensor is a highly capable solution designed for precise and reliable measurements in a variety of environments. This sensor employs advanced technology and robust construction to offer a wide measurement range and high accuracy. Consists of features like plug-and-play installation and versatile communication protocol.

D I G I T A L S E N S O R S



VizSens-Turb

The VizSens-Turb is a highly capable turbidity sensor known for its accurate and stable measurements. Equipped with advanced infrared scattered light technology, it offers excellent repeatability and reliability. With a built-in self-diagnosis function and optional automatic cleaning, it ensures data accuracy while reducing maintenance efforts.



VizSens-TurbLo

The VizSens-TurbLo is a highly reliable and robust turbidity sensor designed to provide accurate and consistent measurements within a range of 0.01 to 100 NTU. With its durable construction, easy installation, and user-friendly operation, this sensor is an excellent choice for environmental monitoring and water treatment applications.



VizSens-CPHL

The chlorophyll sensor uses the characteristic that chlorophyll A has an absorption peak and an emission peak in the spectrum, and emits monochromatic light of a specific wavelength to the water. The light intensity of chlorophyll A is proportional to the content of chlorophyll A in the water.



VizSens-BGA

The VizSens-BGA is an advanced sensor engineered for precise monitoring of Blue-Green Algae in water. With a wide measurement range of 0 to 300,000 cells/mL and an accuracy of $\pm 10\%$, it ensures reliable detection of algae levels. This compact sensor features a durable design, MODBUS RS485 communication, and various features to facilitate seamless integration with compatible controllers.



VizSens-OIW

The VizSens-OIW is an advanced oil in water sensor utilizing ultraviolet fluorescence technology. It excels in precision and versatility, with a wide detection range from 0 to 50ppm. Designed for efficient monitoring of oil levels in water, even in the presence of suspended solids, this sensor integrates seamlessly with compatible controllers.



VizSens-NH4N

The VizSens-NH4N is a highly accurate and reliable sensor designed for measuring Ammonia Nitrogen ($\text{NH}_4\text{-N}$) levels in water. With a pH range of 4-10 and a precision of ± 0.1 , it ensures precise and consistent readings. Operating up to 10 meters underwater with IP68 protection, it's suitable for various environmental applications. Compatible controllers, the VizSens-NH4N supports RS-485 and MODBUS protocol for seamless integration and data transmission.



VizSens-NO3N

The VizSens NO3N is a highly accurate and reliable sensor designed for measuring Nitrate nitrogen (NO_3N) levels in water. With a pH range of 4-10 and a precision of ± 0.1 , it ensures precise and consistent readings. The sensor features a digital RS-485 output with MODBUS protocol for seamless data transmission and integration with compatible controllers. Operating in harsh environments with IP68 protection, and offering optional measurement of Potassium and Sodium, the VizSens NO3N is an efficient and versatile solution for water quality monitoring and environmental applications.



OPTICS 1000
(Multiple Channel Transmitter)

The Optic 1000 Series is a high-performance online water analyser that provides accurate and reliable measurements for a wide range of water quality parameters such as Ammonium, Nitrates, Nitrites, Total Nitrogen, Phosphates, Total Phosphates, Organic Matter, Total Organic Carbon, Sulfides, Sulfites, Total Sulfur, Total Suspended Solids, Turbidity, Color, Chlorine, Chlorine Dioxide, Hydrocarbon, Aromatic Compounds, Phenol, Dissolved Oxygen, Conductivity, Ozone and pH. This device offers versatility for a wide range of applications also, the user-friendly interface enables user to pick any 4 modules and any 8 parameters of choice to be added in this modular analyser.

Technical Specifications

ENCLOSURE	
Type	Wall Mounted / Set / Portable (Optional handles)
Material	SS316L
Dimensions (HxWxD)	450x350x200 mm
Weight	± 15 kg
Protection class	IP65
Area Classification	Safe, Zone 1 or 2 <i>(Available on request)</i>
SAMPLE CONDITION	
Flow	0.2 L/min
Pressure	< 2 bars
Temperature	0... 50°C
CONTROLLER	
Display	8.5" TFT colour screen 16/9 (LED backlight)
Resolution	800 x 480 px
Touch screen	Glass to glass
Memory	16 GB SD card
Data transfer	USB type A
Operating temperature	0... 50°C
Operating humidity	< 90 % RH
COMMUNICATION OUTPUT	
Analog	4-20 mA isolated (Active or Passive) / 500 Ω max
Relay	Programmable limit or fault alarms / 5A (NO) 3A (NC) @ 277 VAC
Digital	RS485 / Modbus (Slave or Master) - Show value, calibration status, fault status...
POWER SUPPLY	
Voltage	100 ... 240 VAC (50 - 60 Hz) or 24 VDC (Universal)
Consumption	< 20 W (60 W max.)

LEVEL

FLOW

DATA LOGGER

male DB9

TxD-

RxD+

1

6

9

5

GND

do not use

do not use

do not use

do not use

do not use

© EKF
ukf.com

A short, straight Ethernet patch cable
may be used for connecting the
adapter to the CU4-SOPRANO

RJ45 jack

8

1

Adapter RS-485
full-duplex
EKF part no. 261.92.009.01

- www.advanceanalytik.com



LET'S CONNECT !

Let's work together to find a solution that works for you



Contact Us :

+36 70328 6862

1024, KeletiKarolyutca 48. fszt.

Budapest

<https://advanceanalytik.com>

sales@advanceanalytik.com

