




PRODUCT
DATASHEET '24

ADVANCE ANALYTIK

REVOLUTIONIZING ONLINE MONITORING SOLUTIONS



Viz Classic pH/ORP


Single Channel Transmitter with HART

www.advanceanalytik.com
sales@advanceanalytik.com

Viz Classic

Single Channel Transmitter with HART

The Viz Classic Series pH & ORP single-channel transmitter is engineered for precision measurement of pH (acidity/alkalinity) and ORP (oxidation-reduction potential) in various industrial processes. Operating on a two-wire 4-20 mA current loop, this transmitter is powered and transmits data through the same two wires, simplifying installation and reducing wiring costs. The integrated HART (Highway Addressable Remote Transducer) protocol allows for digital communication alongside the analog signal, enabling remote calibration, configuration, and diagnostics without disrupting measurement. The Viz Classic Series is ideal for use in water and wastewater treatment, chemical manufacturing, pulp and paper, food and beverage, and other industries where precise pH and ORP control is vital.



Product Features

- **Single-Channel Design:** Dedicated to pH or ORP measurement, delivering reliable, real-time monitoring of critical parameters.
- **HART Protocol Integration:** The HART protocol provides remote access to data, enabling calibration and diagnostic checks without manual intervention. It supports integration with HART-compatible systems for advanced control and monitoring.
- **Two-Wire Operation:** Powered by the 4-20 mA loop, the transmitter simplifies installation and reduces the need for separate power supplies.
- **Rugged and Durable:** Designed for tough industrial environments, ensuring long-term reliability and stable performance.



Ordering Information

Viz Classic (pH / ORP)	Single Channel Universal Controller Display: 16x2 Character display Mounting: 2 different models: Wall mount / Panel mount Output: 4 - 20 mA with HART protocol on the signal line Range: 0 -14pH, ORP -1500 to +1500 mV Communication protocol: HART 7 Protocol Enclosure: IP65 for Wall mount, or Only front facia IP65 for Panel Mount Calibration: Dual/three Point Sensor Calibration, Current Loop Calibration Cable Connection: PG9 Polyurethane Glands: 2Nos Resolution: +/-0.5% of Full scale
-----------------------------------	---

Technical Specification of VIZ Classic Series Transmitter

Viz Classic - Single Channel Transmitter

INPUTS	pH - Analog type ORP - Analog type Temperature - PT100 / PT1000 software Selectable
OUTPUTS	1 x 4 - 20 mA with HART protocol on the signal line
MOUNTING	2 different models: Wall mount / Panel mount
RANGE	pH 0 -14, ORP -1500 to +1500 mV
POWER SUPPLY	12-32V DC, Loop Powered (Single line for Power and Output signal)
DISPLAY	16x2 Character display
COMMUNICATION INTERFACE	• HART Version: Compatible with HART 5, 6, and 7 • Device Diagnostics: Includes basic device and process diagnostics • Digital Communication: Two-way communication for calibration, configuration, and diagnostics • Protocol Support: Standard HART Protocol with 4-20 mA analog signal
TEMPERATURE	-20 to 200 deg C , Compensation : Integrated
ENCLOSURE	IP65 for Wall mount, or Only front facia IP65 for Panel Mount
CALIBRATION	Dual/three Point Sensor Calibration, Current Loop Calibration Two point Temperature Calibration
DIAGNOSTICS	Sensor Open / Short, Temp Sensor Open/ Short, Out of range Calibration error, Test output current
CABLE CONNECTIONS	PG9 Polyurethane Glands: 2Nos
DIMENSIONS	12.7 x 5.7 x 7.9 cm L*W*H <i>*Dimensions subject to change depending on configuration*</i>



APPLICATIONS



Water Treatment Plants

For monitoring water quality in treatment processes and ensuring compliance with regulatory standards.



Environmental Monitoring

For assessing water quality in natural ecosystems, identifying pollution sources, and protecting aquatic biodiversity.



Aquaculture Farms

To maintain optimal conditions for aquatic life, allowing for healthy growth and production.



Research Institutions

For conducting scientific studies related to water quality and environmental monitoring.



Industrial Process Control

For quality control in industrial processes that involve water usage.



Wastewater Treatment

To monitor and optimize the efficiency of wastewater treatment processes.



Food and Beverage Production

For ensuring the quality of water used in food and beverage production, meeting industry standards.



Note -

This data sheet serves as general information about the SINGLE CHANNEL CONTROLLER. For specific technical details, installation guidelines, and troubleshooting assistance, please refer to the official user manual provided with the product.

For inquiries and detailed technical information, please contact sales@advanceanalytik.com.



LET'S CONNECT !

Let's work together to find a solution that works for you



Contact Us :

+36 70328 6862

1132, Budapest Váci ut 16 Faz 12. ajto

<https://advanceanalytik.com>

sales@advanceanalytik.com

