Report Date : 05.06.2024 Material : 10197528 Description : ACTUATOR, 2"-10K, 3000M, 718, SE/TP, ASSY Revision Level : 13;500000324132 Plant. Base Unit of Measure : EA Gross Weight : KG Net Weight : 243.8 KG Basic Material : See BoM for Materials Commodity Code Export Control Code : Manufacturer Manuf . Part No. MIR ID : 79001001 MIR Title : ACTUATOR ASSEMBLY, HYDRAULIC : Assembly, Test, MRB, ITP MIR Desc. Criticality Traceability type Serial No. Profile Batch Management

✓ Shelf life: 0 Day QM Control Key Inspection Setup Classification : MACS MCLASS; Subsea MACS 7000000; SUBSEA SUB-ASSEMBLIES 7900000; SHARED 7900100; Valve&Actuator #Kit, SubAss&Component 7900115; Actuator Attributes Related Drawings : Type:SWD,No:10002071807,Ver:03,Status:Re-issued Constr,Descr:ACTUATOR Type:SWD,No:10002152317,Ver:02,Status:Re-issued Constr,Descr:TOP ASSY, ACTUATOR W/ EXT STEM Type:SWD, No:10004335000, Ver:00, Status:IFC ,Descr:ACTUATOR, HYDRAULIC Other Related Docs : Type:PDC,No:10000854229,Ver:00,Status:IFC ,Descr:CALCULATION REPORT Type:PDC,No:10004342944,Ver:02,Status:Re-issued Constr,Descr:ASSEMBLY PROCEDURE Type:SWA,No:10002028436,Ver:03,Status:Temp. Release ,Descr:ASSY, ACTUATOR W/ EXT STEM Type:PDC,No:10002615521,Ver:11,Status:Re-issued Constr,Descr:FAT PROCEDURE Type:SWA,No:10004334990,Ver:00,Status:Temp. Release ,Descr:ACTUATOR, GENERIC, ASSY STEPS Type:PDC,No:10001366134,Ver:01,Status:Re-issued Constr,Descr:SDRL (STANDARD) Type:SWA,No:10004336572,Ver:00,Status:Temp. Release ,Descr:ACTUATOR, GENERIC, ASSY STEPS Type:PDC.No:10004342945.Ver:01.Status:Re-issued Constr.Descr:DISASSEMBLY PROCEDURE Type:PDC,No:10002802371,Ver:09,Status:Re-issued Constr,Descr:FLUSHING PROCEDURE Type:SWA,No:10004337381,Ver:00,Status:Temp. Release ,Descr:ACTUATOR, GENERIC, ASSY STEPS Basic Data Text : 1) PRIOR TO ASSEMBLY ALL PARTS SHALL BE THOROUGHLY CLEANED AND INSPECTED TO RULE OUT DAMAGE AND

DEFECTS.

2) ASSEMBLY SHALL BE PERFORMED IN A CLEAN ROOM OR CLEAN ENVIRONMENT SEPARATED FROM OTHER MANUFACTURING.

STAMP/ETCH THE FOLLOWING INFORMATION ON THE NAMEPLATE (ITEM 310):

NOM.SIZE: 2-1/16"
M/N: 10197528
S/N: _____
RATED WP: 690 BAR
RATED CP: 207/345 BAR
RATED WATER DEPTH: 3000 M

PSL: 3G

TEMP RATING: -18°C TO 150°C

MATR CLASS: 718 HH
MANUFACTURER: ____*
DATE: ____*

* Assembly facility

Characteristics:

Actuation Spring Type : Coil
Actuation Type : Hydraulic
Additional Features : Bonnet Test Port
Additional Features : Stem Extension

Application : XMT
Created By : 184789
Division : XMT
Hydraulic Operating Pressure : 207 (3 000)

Hydraulic Operating Pressure : 345 (5 000) Lab / Design Office : Curitiba MIR ID : 79001001 Material Group : 7900115 Material Trim : Inconel 718 Max. Rated Temperature (°C) : 150 °C Min. Rated Temperature (°C) : -18 °C Nominal Bore (inch) : 2 1/16 Rated Water Depth (m) : 3.000 m Rated Work Pressure (bar/psi): 690 (10 000) SDRL & QM OM: YES

Standard Material : Standard (Green)

Traceability Code : SN X Plant Status : PM

BoM :

Item No.	Material Number	Description	Quantity	UoM	Assembly	Criticality
0010	10197527	BONNET, 2-1/16"-10K, 718, SE/TP, ASSY	1,000	EA	V	1
0020	10080173	SPRING CANISTER ASSEMBLY, 2-1/16"	1,000	EA	✓	2
0030	10080181	CYLINDER 2 1/16", F/M	1,000	EA	✓	2
0040	10080180	PISTON, 2-1/16",F/M,OD=259MM, L=302MM	1,000	EA	V	2
0050	10080179	PISTON RETAINER RING, 2-1/16", OD=263, L=45	1,000	EA	V	2

0060	10080177	OVERRIDE STEM RETAINER, 31,75MM, F/M	1,000	EA	V	2
0070	10080176	ROV OVERRIDE INTERFACE, 2-1/16",F/M,L254	1,000	EA	V	2
0080	10080175	OVERRIDE STEM, 2 1/16", F/M	1,000	EA	V	2
0090	10080174	OVERRIDE STEM GUIDE, 31,75MM, F/M	1,000	EA	✓	3
0100	10291393	SPRING CHAMBER SEAL, CYL BORE, Ø120MM	1,000	EA		2
0110	10091809	SUPPORT RING, OR STEM 31,75MM, 718, F/M	3,000	EA	V	2
0120	10299012	ENVIRONMENTAL SEAL, CYL ROD, 31.75MM	1,000	EA		2
0130	10083706	INDICATOR RETAINER RING, OR STEM31,75, FM	1,000	EA	V	3
0140	10276504	INDICATOR, ACTUATOR, F/M	1,000	EA	V	3
0150	10133031	SHCS HEX, M10X35, A4-80	4,000	EA		2
0160	10091872	WEARBAND, 31,75x36,75x9,5, RTS	1,000	EA		2
0170	10082039	WEARBAND, 120x125x14,8, RTS	2,000	EA		2
0180	10082637	PLUG, 1/4", 56KPSI, PLAA2528020A	2,000	EA		3
0190	10094478	WIPER-I, 32,75X40,45X6,49, PEEK	1,000	EA		2
0200	10291395	HYDRAULIC SEAL, CYLINDER BORE, Ø120MM	2,000	EA		2
0210	10299014	HYDRAULIC SEAL, CYL ROD, 31,75MM	2,000	EA		2
0220	10091544	CIRCLIP, 1.625", CIRTEQ NJ-162	3,000	EA		3
0230	BS0000894	PLUG 3/8" MP(M) CPX60	6,000	EA		2
0240	BS0000821	GLAND 3/8 MP(M) CGLX60	6,000	EA		2
0250	10277497	SCREW HEX, M12 x 45, L7, ELZN	28,000	EA		1
0260	10093540	SCREW SET, CUP, M8 x 20, A4-80	2,000	EA		2
0270	10093557	O-RING, 221,62x5,33, HNBR85A	1,000	EA		1
0280	10093558	O-RING, 240,67x5,33, HNBR85A	1,000	EA		1
0290	10276008	BU-RING, 242,01x251,31x1,93, NBR90A	1,000	EA		2
0300	BB15-HS0005-63	VALVE, RELIEF, 1/4 CIRCLE SEAL 532T1-2M-50	1,000	EA		2
0310	10269234	NAMEPLATE, SMALL, ACTUATOR	1,000	EA		4
0320	BB7178042	NAIL, EASY-DRIVE, .116 DIA X 1/4 LG, #4,	2,000	EA		4
L	i	4				