

## Math 134: Cryptography

### Lecture 13: Choosing a prime $p$ and a primitive root $\alpha$

---

Eoin Mackall

February 7, 2025

University of California, Santa Cruz

Last time

---

# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

1. Bob chooses a large prime  $p$  and a primitive root  $\alpha$  for  $p$ .

# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

1. Bob chooses a large prime  $p$  and a primitive root  $\alpha$  for  $p$ .
2. Bob chooses a secret integer  $b$  with  $1 < b < p - 1$  and computes  $\beta \equiv \alpha^b \pmod{p}$ .

# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

1. Bob chooses a large prime  $p$  and a primitive root  $\alpha$  for  $p$ .
2. Bob chooses a secret integer  $b$  with  $1 < b < p - 1$  and computes  $\beta \equiv \alpha^b \pmod{p}$ .
3. Bob sends Alice the triple  $(p, \alpha, \beta)$ . This is Bob's *public* key.

# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

1. Bob chooses a large prime  $p$  and a primitive root  $\alpha$  for  $p$ .
2. Bob chooses a secret integer  $b$  with  $1 < b < p - 1$  and computes  $\beta \equiv \alpha^b \pmod{p}$ .
3. Bob sends Alice the triple  $(p, \alpha, \beta)$ . This is Bob's *public* key.
4. Alice will send her message in the form of an integer  $m \in \mathbb{Z}$ . If  $m > p$ , then Alice breaks  $m = m_1 m_2 m_3 \dots$  into blocks  $m_i$  of sizes less than  $p$ .

# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

1. Bob chooses a large prime  $p$  and a primitive root  $\alpha$  for  $p$ .
2. Bob chooses a secret integer  $b$  with  $1 < b < p - 1$  and computes  $\beta \equiv \alpha^b \pmod{p}$ .
3. Bob sends Alice the triple  $(p, \alpha, \beta)$ . This is Bob's *public* key.
4. Alice will send her message in the form of an integer  $m \in \mathbb{Z}$ . If  $m > p$ , then Alice breaks  $m = m_1 m_2 m_3 \dots$  into blocks  $m_i$  of sizes less than  $p$ .
5. For each block  $m_i$ , Alice will generate a random integer  $k_i$  and she will compute  $r_i \equiv \alpha^{k_i} \pmod{p}$  and  $t_i \equiv \beta^{k_i} \cdot m_i \pmod{p}$ .



# The ElGamal encryption algorithm

Alice wants to send a message to Bob. Bob has indicated that he wants to use the ElGamal public-key cryptosystem. What is the process for encryption?

1. Bob chooses a large prime  $p$  and a primitive root  $\alpha$  for  $p$ .
2. Bob chooses a secret integer  $b$  with  $1 < b < p - 1$  and computes  $\beta \equiv \alpha^b \pmod{p}$ .
3. Bob sends Alice the triple  $(p, \alpha, \beta)$ . This is Bob's *public* key.
4. Alice will send her message in the form of an integer  $m \in \mathbb{Z}$ . If  $m > p$ , then Alice breaks  $m = m_1 m_2 m_3 \dots$  into blocks  $m_i$  of sizes less than  $p$ .
5. For each block  $m_i$ , Alice will generate a random integer  $k_i$  and she will compute  $r_i \equiv \alpha^{k_i} \pmod{p}$  and  $t_i \equiv \beta^{k_i} \cdot m_i \pmod{p}$ .
6. Alice then sends all of the pairs  $(r_i, t_i)$  to Bob.

# The ElGamal decryption algorithm

Bob receives a message  $(r, t)$  from Alice. What is the process for decryption?

# The ElGamal decryption algorithm

Bob receives a message  $(r, t)$  from Alice. What is the process for decryption?

1. Bob computes a multiplicative inverse  $s$  to  $r$  modulo  $p$  (i.e. such that  $sr \equiv 1 \pmod{p}$ ) using, for example, the Euclidean Algorithm.

# The ElGamal decryption algorithm

Bob receives a message  $(r, t)$  from Alice. What is the process for decryption?

1. Bob computes a multiplicative inverse  $s$  to  $r$  modulo  $p$  (i.e. such that  $sr \equiv 1 \pmod{p}$ ) using, for example, the Euclidean Algorithm.
2. Bob uses the secret integer  $b$  that he chose earlier to compute the message as  $m \equiv ts^b \pmod{p}$ .

# The ElGamal decryption algorithm

Bob receives a message  $(r, t)$  from Alice. What is the process for decryption?

1. Bob computes a multiplicative inverse  $s$  to  $r$  modulo  $p$  (i.e. such that  $sr \equiv 1 \pmod{p}$ ) using, for example, the Euclidean Algorithm.
2. Bob uses the secret integer  $b$  that he chose earlier to compute the message as  $m \equiv ts^b \pmod{p}$ .
3. This works since

$$\begin{aligned} ts^b &\equiv (\beta^k m)s^b \equiv (\alpha^b)^k ms^b \\ &\equiv (\alpha^k)^b ms^b \\ &\equiv r^b ms^b \\ &\equiv (rs)^b m \equiv (1)^b m \equiv m \pmod{p}. \end{aligned}$$

# The ElGamal decryption algorithm

Bob receives a message  $(r, t)$  from Alice. What is the process for decryption?

1. Bob computes a multiplicative inverse  $s$  to  $r$  modulo  $p$  (i.e. such that  $sr \equiv 1 \pmod{p}$ ) using, for example, the Euclidean Algorithm.
2. Bob uses the secret integer  $b$  that he chose earlier to compute the message as  $m \equiv ts^b \pmod{p}$ .
3. This works since

$$\begin{aligned} ts^b &\equiv (\beta^k m)s^b \equiv (\alpha^b)^k ms^b \\ &\equiv (\alpha^k)^b ms^b \\ &\equiv r^b ms^b \\ &\equiv (rs)^b m \equiv (1)^b m \equiv m \pmod{p}. \end{aligned}$$

## Question

How should Bob choose his public key?

# Table of contents

## 1. Last time

The ElGamal encryption algorithm

The ElGamal decryption algorithm

## 2. Choosing a prime $p$

The Pohlig-Hellman Algorithm

## 3. Choosing a primitive root

Choosing a prime  $p$

---



# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

Let  $\alpha$  be a primitive root modulo  $p$ , and let  $\beta \equiv \alpha^x \pmod{p}$  be some power of  $\alpha$ .

# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

Let  $\alpha$  be a primitive root modulo  $p$ , and let  $\beta \equiv \alpha^x \pmod{p}$  be some power of  $\alpha$ .

Note that since  $2 \mid p - 1$ , we can assume  $q_1 = 2$ . Let  $t = (p - 1)/2 \in \mathbb{Z}$ .

# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

Let  $\alpha$  be a primitive root modulo  $p$ , and let  $\beta \equiv \alpha^x \pmod{p}$  be some power of  $\alpha$ .

Note that since  $2 \mid p - 1$ , we can assume  $q_1 = 2$ . Let  $t = (p - 1)/2 \in \mathbb{Z}$ . Then:

$$(\alpha^t)^2 \equiv \alpha^{t \cdot 2} \equiv \alpha^{p-1} \equiv 1 \pmod{p}.$$

Since  $t < (p - 1)$  and  $\alpha$  is primitive, we must have  $\alpha^t \equiv -1 \pmod{p}$ .

# The Pohlig-Hellman Algorithm

Note that since  $2 \mid p - 1$ , we can assume  $q_1 = 2$ . Let  $t = (p - 1)/2 \in \mathbb{Z}$ .  
Then:

$$(\alpha^t)^2 \equiv \alpha^{t \cdot 2} \equiv \alpha^{p-1} \equiv 1 \pmod{p}.$$

Since  $t < (p - 1)$  and  $\alpha$  is primitive, we must have  $\alpha^t \equiv -1 \pmod{p}$ .

# The Pohlig-Hellman Algorithm

Note that since  $2 \mid p - 1$ , we can assume  $q_1 = 2$ . Let  $t = (p - 1)/2 \in \mathbb{Z}$ . Then:

$$(\alpha^t)^2 \equiv \alpha^{t \cdot 2} \equiv \alpha^{p-1} \equiv 1 \pmod{p}.$$

Since  $t < (p - 1)$  and  $\alpha$  is primitive, we must have  $\alpha^t \equiv -1 \pmod{p}$ .

## Result

Now if we raise  $\beta \equiv \alpha^x \pmod{p}$  to the  $t$ th power we get:

$$\beta^t \equiv (\alpha^x)^t \equiv (\alpha^t)^x \equiv (-1)^x \pmod{p}.$$

If  $\beta^t \equiv 1 \pmod{p}$  then  $x \equiv 0 \pmod{2}$ , otherwise  $x \equiv 1 \pmod{2}$ .

# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

## The Pohlig-Hellman Algorithm

# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

## The Pohlig-Hellman Algorithm

Our goal is to find the discrete log  $x = \text{ind}_\alpha(\beta)$ .



# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

## The Pohlig-Hellman Algorithm

Our goal is to find the discrete log  $x = \text{ind}_\alpha(\beta)$ .

To do this we first find, by a successive procedure, the remainder of  $x \pmod{q_i^{t_i}}$  for all integers  $1 \leq i \leq s$  and for all  $1 \leq t_i \leq r_i$ .

# The Pohlig-Hellman Algorithm

Let  $p$  be an odd prime and write

$$p - 1 = q_1^{r_1} q_2^{r_2} \cdots q_s^{r_s}$$

for the prime factorization of  $p - 1$ , i.e. each  $q_i$  is prime and appears with power  $r_i > 0$  dividing  $p - 1$ .

## The Pohlig-Hellman Algorithm

Our goal is to find the discrete log  $x = \text{ind}_\alpha(\beta)$ .

To do this we first find, by a successive procedure, the remainder of  $x \pmod{q_i^{t_i}}$  for all integers  $1 \leq i \leq s$  and for all  $1 \leq t_i \leq r_i$ .

Then, we use our results and the Chinese Remainder Theorem to find the value of  $x \pmod{p - 1}$ .

# The Pohlig-Hellman Algorithm

Assume that  $q$  is prime and that  $q^r$  is the power of  $q$  dividing  $p - 1$ .

# The Pohlig-Hellman Algorithm

Assume that  $q$  is prime and that  $q^r$  is the power of  $q$  dividing  $p - 1$ .

We write  $x = \text{ind}_\alpha(\beta)$  in base  $q$  so that

$$x = x_0 + x_1q + x_2q^2 + x_3q^3 + \cdots$$

where  $x_0, x_1, x_2, \dots \in [0, q - 1]$  are integers.

# The Pohlig-Hellman Algorithm

Assume that  $q$  is prime and that  $q^r$  is the power of  $q$  dividing  $p - 1$ .

We write  $x = \text{ind}_\alpha(\beta)$  in base  $q$  so that

$$x = x_0 + x_1q + x_2q^2 + x_3q^3 + \cdots$$

where  $x_0, x_1, x_2, \dots \in [0, q - 1]$  are integers.

Let  $t_0 = (p - 1)/q \in \mathbb{Z}$ . Then:

# The Pohlig-Hellman Algorithm

Assume that  $q$  is prime and that  $q^r$  is the power of  $q$  dividing  $p - 1$ .

We write  $x = \text{ind}_\alpha(\beta)$  in base  $q$  so that

$$x = x_0 + x_1q + x_2q^2 + x_3q^3 + \cdots$$

where  $x_0, x_1, x_2, \dots \in [0, q - 1]$  are integers.

Let  $t_0 = (p - 1)/q \in \mathbb{Z}$ . Then:

$$\begin{aligned} t_0x &= t_0x_0 + qt_0(x_1 + x_2q + x_3q^2 + \cdots) \\ &= t_0x_0 + (p - 1)n \end{aligned}$$

where  $n = (x_1 + x_2q + x_3q^2 + \cdots) \in \mathbb{Z}$ .

# The Pohlig-Hellman Algorithm

Assume that  $q$  is prime and that  $q^r$  is the power of  $q$  dividing  $p - 1$ .

We write  $x = \text{ind}_\alpha(\beta)$  in base  $q$  so that

$$x = x_0 + x_1q + x_2q^2 + x_3q^3 + \cdots$$

where  $x_0, x_1, x_2, \dots \in [0, q - 1]$  are integers.

Let  $t_0 = (p - 1)/q \in \mathbb{Z}$ . Then:

$$\begin{aligned} t_0x &= t_0x_0 + qt_0(x_1 + x_2q + x_3q^2 + \cdots) \\ &= t_0x_0 + (p - 1)n \end{aligned}$$

where  $n = (x_1 + x_2q + x_3q^2 + \cdots) \in \mathbb{Z}$ . This implies

$$\beta^{t_0} \equiv \alpha^{xt_0} \equiv \alpha^{t_0x_0} \alpha^{(p-1)n} \equiv \alpha^{t_0x_0} \pmod{p}.$$

# The Pohlig-Hellman Algorithm

This implies

$$\beta^{t_0} \equiv \alpha^{xt_0} \equiv \alpha^{t_0 x_0} \alpha^{(p-1)n} \equiv \alpha^{t_0 x_0} \pmod{p}.$$

We can find the value of  $x_0$  by comparing  $\beta^{t_0}$  with the values

$$\alpha^{k(p-1)/q} \pmod{p} \quad k = 0, 1, \dots, q - 1.$$



# The Pohlig-Hellman Algorithm

This implies

$$\beta^{t_0} \equiv \alpha^{x t_0} \equiv \alpha^{t_0 x_0} \alpha^{(p-1)n} \equiv \alpha^{t_0 x_0} \pmod{p}.$$

We can find the value of  $x_0$  by comparing  $\beta^{t_0}$  with the values

$$\alpha^{k(p-1)/q} \pmod{p} \quad k = 0, 1, \dots, q-1.$$

If  $q^2 \mid p-1$  then we can find  $x_1$  by setting  $t_1 = (p-1)/q^2$  and  $\beta_1 \equiv \beta \alpha^{-x_0} \pmod{p}$ .

# The Pohlig-Hellman Algorithm

This implies

$$\beta^{t_0} \equiv \alpha^{xt_0} \equiv \alpha^{t_0 x_0} \alpha^{(p-1)n} \equiv \alpha^{t_0 x_0} \pmod{p}.$$

We can find the value of  $x_0$  by comparing  $\beta^{t_0}$  with the values

$$\alpha^{k(p-1)/q} \pmod{p} \quad k = 0, 1, \dots, q-1.$$

If  $q^2 \mid p-1$  then we can find  $x_1$  by setting  $t_1 = (p-1)/q^2$  and  $\beta_1 \equiv \beta \alpha^{-x_0} \pmod{p}$ .

A similar procedure gives

$$\beta_1^{t_1} \equiv (\beta \alpha^{-x_0})^{t_1} \equiv (\alpha^{x-x_0})^{t_1} \equiv (\alpha^{(x_1 q + x_2 q^2 + x_3 q^3 + \dots)})^{t_1} \equiv \alpha^{t_0 x_1} \pmod{p}.$$

# The Pohlig-Hellman Algorithm

This implies

$$\beta^{t_0} \equiv \alpha^{x t_0} \equiv \alpha^{t_0 x_0} \alpha^{(p-1)n} \equiv \alpha^{t_0 x_0} \pmod{p}.$$

We can find the value of  $x_0$  by comparing  $\beta^{t_0}$  with the values

$$\alpha^{k(p-1)/q} \pmod{p} \quad k = 0, 1, \dots, q-1.$$

If  $q^2 \mid p-1$  then we can find  $x_1$  by setting  $t_1 = (p-1)/q^2$  and  $\beta_1 \equiv \beta \alpha^{-x_0} \pmod{p}$ .

A similar procedure gives

$$\beta_1^{t_1} \equiv (\beta \alpha^{-x_0})^{t_1} \equiv (\alpha^{x-x_0})^{t_1} \equiv (\alpha^{(x_1 q + x_2 q^2 + x_3 q^3 + \dots)})^{t_1} \equiv \alpha^{t_0 x_1} \pmod{p}.$$

By comparing with the values  $\alpha^{k(p-1)/q} \pmod{p}$  again, we may find  $x_1$ .

# The Pohlig-Hellman Algorithm

In this way we find, for each prime  $q$  dividing  $p - 1$ , the value

$$x \equiv x_0 + x_1q + x_2q^2 + \cdots + x_{r-1}q^{r-1} \pmod{q^r}$$

where  $q^r$  is the power of  $q$  dividing  $p - 1$ .

# The Pohlig-Hellman Algorithm

In this way we find, for each prime  $q$  dividing  $p - 1$ , the value

$$x \equiv x_0 + x_1q + x_2q^2 + \cdots + x_{r-1}q^{r-1} \pmod{q^r}$$

where  $q^r$  is the power of  $q$  dividing  $p - 1$ .

Putting these together using the Chinese Remainder Theorem yields the value of  $x \pmod{p - 1}$ .

# The Pohlig-Hellman Algorithm

In this way we find, for each prime  $q$  dividing  $p - 1$ , the value

$$x \equiv x_0 + x_1q + x_2q^2 + \cdots + x_{r-1}q^{r-1} \pmod{q^r}$$

where  $q^r$  is the power of  $q$  dividing  $p - 1$ .

Putting these together using the Chinese Remainder Theorem yields the value of  $x \pmod{p - 1}$ .

## Take-away

If  $p - 1$  has only small(ish) prime factors, then using the Pohlig-Hellman algorithm, one can solve the discrete logarithm problem for  $p$ .

# The Pohlig-Hellman Algorithm

## Example

Let  $p = 257 = 2^8 + 1$ . This is prime. A primitive root for  $p$  is  $\alpha = 3$ .  
Let's find the discrete log  $x$  of 157 to base 3, so  $3^x \equiv 157 \pmod{257}$ .

# The Pohlig-Hellman Algorithm

## Example

Let  $p = 257 = 2^8 + 1$ . This is prime. A primitive root for  $p$  is  $\alpha = 3$ .  
Let's find the discrete log  $x$  of 157 to base 3, so  $3^x \equiv 157 \pmod{257}$ .

We write  $x = x_0 + x_1 \cdot 2 + x_2 \cdot 4 + x_3 \cdot 8 + \dots$ . A calculation shows that

$$157^{(257-1)/2} \equiv 1 \pmod{257}$$

so that  $x_0 = 0$ .



# The Pohlig-Hellman Algorithm

## Example

Let  $p = 257 = 2^8 + 1$ . This is prime. A primitive root for  $p$  is  $\alpha = 3$ . Let's find the discrete log  $x$  of 157 to base 3, so  $3^x \equiv 157 \pmod{257}$ .

We write  $x = x_0 + x_1 \cdot 2 + x_2 \cdot 4 + x_3 \cdot 8 + \dots$ . A calculation shows that

$$157^{(257-1)/2} \equiv 1 \pmod{257}$$

so that  $x_0 = 0$ .

Now

$$\beta_1 \equiv 157 \cdot 3^{-x_0} \equiv 157 \pmod{257}$$

so  $\beta_1^{(256)/4} \equiv (157)^{(256)/4} \equiv -1 \pmod{257}$ . So  $x_1 = 1$ .

# The Pohlig-Hellman Algorithm

## Example

Let  $p = 257 = 2^8 + 1$ . This is prime. A primitive root for  $p$  is  $\alpha = 3$ . Let's find the discrete log  $x$  of 157 to base 3, so  $3^x \equiv 157 \pmod{257}$ .

We write  $x = x_0 + x_1 \cdot 2 + x_2 \cdot 4 + x_3 \cdot 8 + \dots$ . A calculation shows that

$$157^{(257-1)/2} \equiv 1 \pmod{257}$$

so that  $x_0 = 0$ .

Now

$$\beta_1 \equiv 157 \cdot 3^{-x_0} \equiv 157 \pmod{257}$$

so  $\beta_1^{(256)/4} \equiv (157)^{(256)/4} \equiv -1 \pmod{257}$ . So  $x_1 = 1$ .

Continuing we eventually find  $x = 2 + 4 + 8 + 64 = 78$ .

## Choosing a primitive root

---

## The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Empirical evidence

Recall that for an integer  $n > 1$  we have

$$\phi(n) = n \cdot \prod_{q|n, q \text{ prime}} \left(1 - \frac{1}{q}\right).$$

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Empirical evidence

Recall that for an integer  $n > 1$  we have

$$\phi(n) = n \cdot \prod_{q|n, q \text{ prime}} \left(1 - \frac{1}{q}\right).$$

Also, we've seen that the number of primitive roots modulo an odd prime  $p$  is  $\phi(\phi(p)) = \phi(p - 1)$ .

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Empirical evidence

Recall that for an integer  $n > 1$  we have

$$\phi(n) = n \cdot \prod_{q|n, q \text{ prime}} \left(1 - \frac{1}{q}\right).$$

Also, we've seen that the number of primitive roots modulo an odd prime  $p$  is  $\phi(\phi(p)) = \phi(p-1)$ .

Since  $2 \mid (p-1)$  always, we have that  $\phi(p-1) \leq (1/2)(p-1)$  with equality if and only if  $p-1$  is a power of 2.

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Empirical evidence

Recall that for an integer  $n > 1$  we have

$$\phi(n) = n \cdot \prod_{q|n, q \text{ prime}} \left(1 - \frac{1}{q}\right).$$

Also, we've seen that the number of primitive roots modulo an odd prime  $p$  is  $\phi(\phi(p)) = \phi(p-1)$ .

Since  $2 \mid (p-1)$  always, we have that  $\phi(p-1) \leq (1/2)(p-1)$  with equality if and only if  $p-1$  is a power of 2.

If  $q$  is a large prime power then  $(1 - \frac{1}{q}) \approx 1$ .



# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Empirical evidence

Recall that for an integer  $n > 1$  we have

$$\phi(n) = n \cdot \prod_{q|n, q \text{ prime}} \left(1 - \frac{1}{q}\right).$$

Also, we've seen that the number of primitive roots modulo an odd prime  $p$  is  $\phi(\phi(p)) = \phi(p-1)$ .

Since  $2 \mid (p-1)$  always, we have that  $\phi(p-1) \leq (1/2)(p-1)$  with equality if and only if  $p-1$  is a power of 2.

If  $q$  is a large prime power then  $(1 - \frac{1}{q}) \approx 1$ .

If  $p-1$  has only a few prime factors, then this value should be close to  $(p-1)/2$ .

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

Empirical evidence

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Empirical evidence

By choosing  $p$  such that  $p - 1$  has few, large prime factors gives a good probability that any randomly chosen element from  $[2, p - 1)$  is a primitive root.

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

Example

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Example

Let  $p = 2003$ , which is prime. We have  $p - 1 = 2002 = 2 \cdot 7 \cdot 11 \cdot 13$ .

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Example

Let  $p = 2003$ , which is prime. We have  $p - 1 = 2002 = 2 \cdot 7 \cdot 11 \cdot 13$ .

For  $a$  to be a primitive root we need that

$$a^{(p-1)/2} \not\equiv 1 \pmod{2003}$$

$$a^{(p-1)/7} \not\equiv 1 \pmod{2003}$$

$$a^{(p-1)/11} \not\equiv 1 \pmod{2003}$$

$$a^{(p-1)/13} \not\equiv 1 \pmod{2003}$$

# The proportion of primitive roots mod $p$

Let  $p$  be an odd prime. How do we find a primitive root  $\alpha$  modulo  $p$ ?

## Example

Let  $p = 2003$ , which is prime. We have  $p - 1 = 2002 = 2 \cdot 7 \cdot 11 \cdot 13$ .

For  $a$  to be a primitive root we need that

$$a^{(p-1)/2} \not\equiv 1 \pmod{2003}$$

$$a^{(p-1)/7} \not\equiv 1 \pmod{2003}$$

$$a^{(p-1)/11} \not\equiv 1 \pmod{2003}$$

$$a^{(p-1)/13} \not\equiv 1 \pmod{2003}$$

Going through the first few values for  $a$ , we see

$$2^{(p-1)/7} \equiv 1 \pmod{2003} \quad \text{and} \quad 3^{(p-1)/2} \equiv 1 \pmod{2003},$$

but  $a = 5$  satisfies all of the above.