

Shadlen & Movshon (1999) — Synchrony Unbound: A Critical Evaluation of the Temporal Binding Hypothesis

ar060 · 25 June 2026

A reading of Shadlen & Movshon (1999), *Synchrony Unbound: A Critical Evaluation of the Temporal Binding Hypothesis* (Neuron 24:67–77). It is the rate-coding skeptic’s counterpart to the rhythm-and-synchrony story: where ar059 (Gerstner) and nb050 ask *when* a population locks into a gamma rhythm, this paper asks whether that synchrony could ever be a *code* — and argues, on a back-of-envelope count of cortical inputs, that it cannot. Its engine is the same flooded, balanced, high-input regime we simulate in nb058.

In plain English. The *binding problem*: your visual cortex represents an object’s pieces — edges, colours, motions — in scattered neurons, so how does the brain know they belong to one object? The *temporal binding hypothesis* answers: the neurons coding one object fire *in synchrony* (often riding a gamma rhythm), and that synchrony is the “we go together” tag. Shadlen & Movshon say this can’t work in real cortex, for one blunt reason — a cortical neuron is buried under input. It receives thousands of synapses and *hundreds of spikes for every spike it emits*, so in any few-millisecond window a flood of inputs always arrives “together.” If everything is synchronous, synchrony tags nothing: a neuron drowning in input integrates a *rate*, it cannot pick out a special coincident subset. They conclude cortex is a rate coder, and that binding is a higher-level, action-driven computation.

The binding problem and the temporal solution

A scene must be assembled from local features computed by neurons with small receptive fields. The **binding problem** is how the brain marks which features belong to the same object — without a combinatorial explosion of dedicated “this-red-vertical-bar-here” neurons. The **temporal binding hypothesis** (von der Malsburg, 1981; Gray et al., 1989; Singer & Gray, 1995) proposes a dynamic tag: neurons representing one object **synchronise** their spikes — typically within a gamma cycle — while neurons coding different objects fire out of phase. Synchrony is the binding label, transient and reassignable, sidestepping the need for cardinal neurons.

The paper’s first objections are conceptual: the hypothesis names a *signature* of binding (synchrony) without saying how binding is *computed*; and the perceptual and lesion evidence places object binding in high-level (parietal/frontal) cortex, not the early visual areas where the synchrony is recorded. But the argument that endures — and that ties to our work — is quantitative.

When synchrony could work: the sparse coincidence detector

For synchrony to *mean* something, a downstream neuron must act as a **coincidence detector** — fire when enough inputs arrive within a short window τ , and stay quiet otherwise. That requires chance coincidences to be rare. Take a neuron reading 10 inputs, each firing as a Poisson process at 10 spikes/s, so the ensemble rate is $R = 100$ spikes/s. The rate at which m inputs fall within τ of one another (an m -fold coincidence) is approximately

$$r_{\text{coinc}} \approx R \frac{(R\tau)^{m-1}}{(m-1)!}, \quad (1)$$

where:

- R — total spike rate of the input ensemble;

- τ — coincidence window;
- m — number of near-simultaneous spikes the detector demands.

For $m = 4$, $\tau = 5$ ms, $R = 100$ spikes/s this gives a chance rate of ≈ 1 spike/s — low enough that a spike from such a detector genuinely signals “ ≥ 4 of the 10 inputs were active together.” So coincidence detection *can* carry information — **but only in a sparse, low-rate regime**, where few inputs arrive between the neuron’s own spikes. And Shadlen & Movshon note the trap: in exactly that regime there is no binding problem to solve — with few effective inputs and low rates, there is nothing to tag, select among, or multiplex. The coincidence code works only where it is not needed.

The knockout: real cortex is flooded

What regime is a cortical neuron actually in? The anatomy answers. A pyramidal cell receives 3,000–10,000 synapses, $\approx 85\%$ excitatory; roughly 1,000 excitatory inputs come from the $\approx 1,000$ neurons in its own local column (neuron density $\approx 10^5/\text{mm}^3$, connection probability ≈ 0.09). The number that matters is the **effective excitatory input per output spike**,

$$n_{\text{in}} = N_{\text{eff}} \frac{r_{\text{in}}}{r_{\text{out}}}, \quad (2)$$

where N_{eff} is the effective count of excitatory inputs, r_{in} their mean rate, and r_{out} the cell’s own rate. With $N_{\text{eff}} \sim 10^3$ and comparable in/out rates, a neuron integrates **several hundred excitatory spikes between one output spike and the next** (Shadlen & Newsome, 1994, 1998).

Now the argument is immediate. With hundreds of input spikes per interspike interval, *any* 5–10 ms window during active cortex contains a flood of inputs arriving in apparent synchrony — not because anything special happened, but because that is what a recurrent, highly convergent network does. So what could “synchronous” spikes signify to such a neuron? In effect, **all spikes are synchronous with other spikes**; there is no quiet background against which a coincident subset stands out. A neuron in this regime is forced to be an **integrator** — it sums its drenched input and reports a rate — not a coincidence detector that reads timing.

The precision escape, and why it fails

One could rescue synchrony by demanding a much narrower window — sub-millisecond coincidences would be rare even in the flood (set $\tau \rightarrow 1$ ms in equation 1 and r_{coinc} collapses). Shadlen & Movshon close that door twice. First, **biophysics**: unlike specialised auditory-brainstem neurons, cortical cells lack the machinery for millisecond coincidence detection (Reyes et al.; Koch, 1999) — their membrane time constants and dendritic integration smear inputs over many milliseconds. Second, **the data**: reported “synchrony” is broad — correlogram peaks of 10–20 ms, sometimes 50 ms — far coarser than the precision a usable timing code would need. The window where synchrony is both rare-by-chance and biophysically readable does not coincide with the window where cortex actually correlates.

Their alternative: rate, and binding through action

The positive proposal is deflationary. Rate-modulated population activity already does the perceptual work; no new kind of signal is needed. And binding, properly construed, is a **high-level, action-oriented** operation: in parietal cortex (e.g. LIP), stimuli are co-represented to the extent they bear on a common action or saccade — a priority/saliency map. “Features are bound together to the extent that one feature can be viewed as an instruction to act in some way upon another.” This tames the combinatorial explosion (groupings are constrained by

possible actions) and fits the neurology of parietal damage. Their verdict: the temporal binding hypothesis *as proposed* is untenable — a signature without a mechanism, at the wrong level, biophysically undecodable, and weakly supported — though it productively forced the field to take neural timing seriously.

The tie to the balanced state

Here is why this 1999 polemic belongs next to our balanced-network work. **The knockout argument is the same physics as nb058.** “Several hundred balanced excitatory and inhibitory inputs per output spike, fluctuation-driven, irregular firing” is precisely the Vreeswijk–Sompolinsky asynchronous-irregular state — the regime where each cell’s net drive is a near-cancelling sum whose residual fluctuations decide its spikes ($CV \approx 1$). The two literatures read the *same* regime through different lenses:

- **V&S / nb058** asks *why* that state is self-consistent and finds it is deterministically chaotic — the network manufactures its own noise.
- **Shadlen & Movshon** take that flooded, irregular regime as given and draw the *coding* moral: a neuron there integrates a rate; it cannot read synchrony.

So nb058 supplies the mechanism beneath their argument. The same picture threads the rest of the reading list: London et al. (2010) shows a single spike perturbs cortical activity — high sensitivity, which they read as high noise and hence rate coding — and our nb058 chaos result (a positive Lyapunov exponent, a perturbation that amplifies) is the *source* of that sensitivity. Renart et al. (2010) is the asynchronous state measured directly.

And the debate is not settled by fiat. This paper is the **rate** pole; Fries’ Communication-through-Coherence is the modern **timing/rhythm** pole, where gamma coherence gates *which* signals get through. Our own pair of entries refuses the dichotomy: nb058 is the integrator/asynchronous regime Shadlen & Movshon favour, nb050 is PING gamma — the synchrony regime the binding camp favours — and they are the *same network* on either side of one control parameter (the correlation of the input). The interesting question our model poses is not “rate or timing?” but “what makes cortex sit on one side of that bifurcation, and can it switch?”

Honest caveats

It is a 1999 polemic, and worth reading as one. Its target is the *strong* binding-by-synchrony claim, and it lands; but precise spike timing does carry information in some systems and tasks, gamma coherence does modulate effective connectivity in later work, and “rate vs timing” is now understood as a spectrum rather than a verdict. The paper’s durable contribution is not “synchrony is dead” — it is the **integrator argument**: a quantitative, anatomy-grounded reason that a balanced, high-input cortical neuron reports rates. That is exactly the cortex we build in nb058, which is why the argument has outlived the debate that prompted it.

One-paragraph summary

Counting cortical inputs settles the matter: a pyramidal neuron integrates several hundred balanced spikes per output spike (equation 2), so in any few-millisecond window inputs are always “synchronous” by design — synchrony cannot stand out as a code. Coincidence detection works only in a sparse, low-rate regime (equation 1) where there is no binding problem to solve, and cortex lacks both the biophysics and the measured precision for a millisecond timing code anyway. The conclusion — cortex rate-codes, binding is high-level — rests on the same flooded, fluctuation-driven balanced state that nb058 simulates and V&S explains. Two lenses on one regime: V&S asks why it is chaotic; Shadlen & Movshon ask what it can compute.