

## pinglab — contents

|                                                                           |     |
|---------------------------------------------------------------------------|-----|
| COBANet .....                                                             | 3   |
| Parameters & Units .....                                                  | 5   |
| Metrics .....                                                             | 7   |
| Training .....                                                            | 14  |
| Manuscript .....                                                          | 17  |
| The SNN tool .....                                                        | 44  |
| Gradient Stabilisation .....                                              | 55  |
| Introduction .....                                                        | 60  |
| Bayesian and sampling-based cortical computation .....                    | 62  |
| SNNLANG developer documentation .....                                     | 67  |
| Compute options .....                                                     | 70  |
| Cloudflare R2 archive .....                                               | 75  |
| Networks, signals, and parameters .....                                   | 77  |
| Components, projections, and delays .....                                 | 80  |
| Compiling and executing bundles .....                                     | 83  |
| Inputs, outputs, and readouts .....                                       | 86  |
| Training recipes and graph-native learning .....                          | 90  |
| Runtime state, checkpoints, and provenance .....                          | 93  |
| Compatibility, status, and extension .....                                | 96  |
| Manuscript figures and captions .....                                     | 104 |
| Training-run guide .....                                                  | 115 |
| PING fundamentals .....                                                   | 129 |
| Accuracy converges, firing rate does not .....                            | 136 |
| PING locks E rate $\approx 10\times$ below COBA .....                     | 139 |
| DMFT model .....                                                          | 146 |
| PING tolerates 80% dropped spikes but collapses on added noise .....      | 160 |
| Switching the loop on at inference cuts E rate $\approx 15\times$ .....   | 165 |
| E rate is affine in gamma frequency .....                                 | 168 |
| Perturbations: gamma gates rates not just mean inhibition .....           | 171 |
| Rate floor stable across a $20\times \Delta t$ sweep .....                | 177 |
| Near-strict 1-spike-per-cycle ceiling: 98.9% of (cell, cycle) pairs ..... | 183 |
| Pool-size invariance requires inverse synaptic scaling .....              | 185 |
| Temporal and spatial evidence limits of trained PING .....                | 188 |
| Gradient descent does not preserve a trainable PING loop .....            | 197 |
| A PING rhythmicity metric .....                                           | 203 |
| What the Spiking Heidelberg Digits look like .....                        | 210 |
| Trying a cumulative-potential readout on matched SHD networks .....       | 213 |
| Adaptive conductance controls for matched SHD networks .....              | 231 |
| Plastic recurrent excitation reaches the old PING regime .....            | 257 |
| From Python graph to spikes .....                                         | 262 |
| A compiled graph learns .....                                             | 264 |
| A bundle checkpoint replays .....                                         | 266 |
| Arbitrary coupled graphs execute natively .....                           | 269 |
| Empirical input-rate calibration for variable-rate PING training .....    | 276 |
| Linear-filter analysis of sparse conductance-driven pixel features .....  | 280 |
| Spike-count streaming across input rates .....                            | 289 |

|                                                             |     |
|-------------------------------------------------------------|-----|
| When does the default PING circuit start to sing? .....     | 295 |
| Can inhibitory recovery tune default PING into gamma? ..... | 300 |
| Lowet 2015 .....                                            | 303 |
| Lowet 2017 .....                                            | 310 |
| Gold-star manuscript figure comparison .....                | 317 |
| Decoder transfer in frozen COBA and PING networks .....     | 322 |
| What does gamma timing buy? .....                           | 336 |
| Can a PING cycle be seen as a running engine? .....         | 342 |

# COBANet

14 May 2026

## 1. A conductance based neuron equation

The membrane is a capacitor ( $C_m$ ) pierced by ion channels in parallel. Conservation of charge (Kirchhoff) balances the capacitive current  $C_m dV/dt$  against the total ionic current:

$$C_m \frac{dV}{dt} = - \sum_{\text{ion}} I_{\text{ion}} \quad (1)$$

Each channel passes an ohmic current — its conductance  $g_{\text{ion}} \geq 0$  times the **driving force** ( $V - E_{\text{ion}}$ ), the distance of  $V$  from the reversal potential  $E_{\text{ion}}$  (where the channel's net current vanishes, set by the Nernst equilibrium):

$$I_{\text{ion}} = g_{\text{ion}}(V - E_{\text{ion}}) \quad (2)$$

Because  $g_{\text{ion}} \geq 0$ , the current's sign lives entirely in the driving force. Summing a leak ( $g_L$ ,  $E_L$ ) and synaptic conductances — excitatory ( $g_e$ ,  $E_e$ ), inhibitory ( $g_i$ ,  $E_i$ ) — gives the general conductance-based (COBA) neuron:

$$C_m \frac{dV}{dt} = -g_L(V - E_L) - g_e(V - E_e) - g_i(V - E_i) \quad (3)$$

## 2. The COBA model

COBANet specialises (3) to two populations — E driven by excitation and inhibition, I by excitation only:

$$C_m^E \frac{dV^E}{dt} = -g_L^E(V^E - E_L) - g_e^E(V^E - E_e) - g_i^E(V^E - E_i) \quad (4)$$

$$C_m^I \frac{dV^I}{dt} = -g_L^I(V^I - E_L) - g_e^I(V^I - E_e) \quad (5)$$

A neuron spikes at threshold  $V_{\text{th}}$  and resets to  $V_{\text{reset}}$  for a refractory period:

$$s_{t+1} = \mathbb{1}[V \geq V_{\text{th}}], \quad V \leftarrow V_{\text{reset}} \text{ if } s_{t+1} = 1 \text{ or refractory} \quad (6)$$

Each synaptic conductance is an exponential trace driven by presynaptic spikes — each spike adds its full weight as an instantaneous jump, then the conductance decays with the channel time constant; there is no E→E connection:

$$\frac{dg_e^E}{dt} = -\frac{g_e^E}{\tau_{\text{AMPA}}} + W_{\text{in}} \sum_k \delta(t - t_k^{\text{inp}}) \quad (7)$$

$$\frac{dg_i^E}{dt} = -\frac{g_i^E}{\tau_{\text{GABA}}} + W_{\text{ie}} \sum_k \delta(t - t_k^i) \quad (8)$$

$$\frac{dg_e^I}{dt} = -\frac{g_e^I}{\tau_{\text{AMPA}}} + W_{\text{ei}} \sum_k \delta(t - t_k^e) \quad (9)$$

(7) is E's excitation from the input  $W_{\text{in}}$ ; (8) its inhibition from I via  $W_{\text{ie}}$ ; (9) the I population's excitation from E via  $W_{\text{ei}}$ .

### 3. Discretization

The conductances (7)–(9) and membrane equations (4)–(5) are continuous ODEs. The delta-driven conductances integrate **exactly** over one step: between spikes they decay by  $e^{-\Delta t/\tau}$ , and any spike landing in the step adds its full weight — the decay-then-add recurrence  $g_{t+1} = e^{-\Delta t/\tau} g_t + W s_t$  (with the  $\tau$ ,  $W$  and spike train  $s$  of each of (7)–(9)). The membrane we integrate by **exponential Euler** — the same algebra for both populations (the I neuron drops  $g_i$ ).

Collecting on  $V$  makes it linear, with total conductance  $g_{\text{tot}} = g_L + g_e + g_i$ :

$$C_m \frac{dV}{dt} = -(g_L + g_e + g_i)V + (g_L E_L + g_e E_e + g_i E_i) \quad (10)$$

Dividing by  $g_{\text{tot}}$  gives decay-to-steady-state form, naming  $\tau_{\text{eff}} = C_m/g_{\text{tot}}$  (shorter than  $C_m/g_L$  when synapses are open) and the steady-state voltage  $V_\infty$  (the conductance-weighted mean of the reversals):

$$\frac{C_m}{g_{\text{tot}}} \frac{dV}{dt} = - \left( V - \frac{g_L E_L + g_e E_e + g_i E_i}{g_{\text{tot}}} \right) \quad (11)$$

A **zero-order hold** freezes the conductances over one step  $\Delta t$ , leaving (11) constant-coefficient with exact solution

$$V_{t+1} = V_\infty + (V_t - V_\infty)e^{-\Delta t/\tau_{\text{eff}}} \quad (12)$$

Per population — I has no  $g_i$ , so its  $g_{\text{tot}}$  and  $V_\infty$  drop those terms:

$$g_{\text{tot}}^E = g_L^E + g_e^E + g_i^E, \quad \tau_{\text{eff}}^E = \frac{C_m^E}{g_{\text{tot}}^E}, \quad V_\infty^E = \frac{g_L^E E_L + g_e^E E_e + g_i^E E_i}{g_{\text{tot}}^E} \quad (13)$$

$$g_{\text{tot}}^I = g_L^I + g_e^I, \quad \tau_{\text{eff}}^I = \frac{C_m^I}{g_{\text{tot}}^I}, \quad V_\infty^I = \frac{g_L^I E_L + g_e^I E_e}{g_{\text{tot}}^I} \quad (14)$$

with step (12) for each population  $p \in \{E, I\}$ :  $V_{t+1}^p = V_\infty^p + (V_t^p - V_\infty^p)e^{-\Delta t/\tau_{\text{eff}}^p}$ .

Being the *exact* frozen-conductance integral, (12) is **dt-invariant** —  $N$  small steps equal one big step, so firing rates and the gamma frequency are physical (Hz) properties, not timestep artifacts (exp044). A forward-Euler step  $V_{t+1} = V_t + (\Delta t/C_m)I_{\text{net}(V_t)}$  — not dt-invariant — is kept only as a parity toggle (*COBA\_INTEGRATOR*).

Each step runs in fixed order: conductances (7)–(9), then  $g_{\text{tot}}, \tau_{\text{eff}}, V_\infty$ , then the membrane step (12), then spike + reset (6). **The zero-order hold is this ordering** — the conductances advance once, then stay fixed while the membrane integrates across  $\Delta t$ . E and I advance synchronously, phase-locking the E→I→E gamma cycle to the grid.



## Parameters & Units

14 May 2026

All physical quantities in the codebase use the same unit system: **ms for time, mV for voltage, nF for capacitance,  $\mu$ S for conductance, nA for current, Hz for rates.**

Time fields carry an explicit *\_ms* suffix (*sim\_ms*, *ref\_ms\_E*, *tau\_gaba*); CLI flags follow the same convention (*-t-ms 600*). A  $\Delta t$  of 1 means 1 ms, not 1 s.

### Quantities

| Quantity                 | Unit    | Typical value                | Variable                           |
|--------------------------|---------|------------------------------|------------------------------------|
| Integration step         | ms      | 0.25                         | <i>dt</i> , <i>DT_MS</i>           |
| Simulation length        | ms      | 600                          | <i>sim_ms</i>                      |
| Membrane time constant   | ms      | 20 (E), 5 (I)                | <i>tau_m_E</i> , <i>tau_m_I</i>    |
| Refractory period        | ms      | 3 (E), 1.5 (I)               | <i>ref_ms_E</i> , <i>ref_ms_I</i>  |
| AMPA decay               | ms      | 2                            | <i>tau_ampa</i>                    |
| GABA decay               | ms      | 9                            | <i>tau_gaba</i>                    |
| Resting / leak potential | mV      | −65                          | <i>E_L</i>                         |
| Spike threshold          | mV      | −50                          | <i>V_th</i>                        |
| Reset potential          | mV      | −65                          | <i>V_reset</i>                     |
| AMPA reversal            | mV      | 0                            | <i>E_e</i>                         |
| GABA reversal            | mV      | −80                          | <i>E_i</i>                         |
| Membrane capacitance     | nF      | 1.0 (E), 0.5 (I)             | <i>C_m_E</i> , <i>C_m_I</i>        |
| Leak conductance         | $\mu$ S | 0.05 (E), 0.1 (I)            | <i>g_L_E</i> , <i>g_L_I</i>        |
| External drive           | $\mu$ S | 0.0006 (async), 0.003 (PING) | <i>t_e_async</i> , <i>t_e_ping</i> |
| Input current (CUBA)     | nA      | 20 per spike                 | <i>input_scale</i>                 |
| CUBA weight std          | nA      | 32                           | <i>W_STD_CUBA</i>                  |
| Max input rate           | Hz      | 25                           | <i>max_rate_hz</i>                 |
| Population firing rate   | Hz      | 20–80                        | <i>r_E</i> , <i>r_I</i>            |
| Gamma frequency          | Hz      | 30–80                        | <i>f_0</i>                         |

### COBA / PING biophysical constants

Used by COBA and PING. Values follow neuroscience conventions (cf. Dayan & Abbott, Gerstner *Neuronal Dynamics*); the E:I asymmetry in  $\tau_m$ ,  $C_m$ ,  $g_L$ ,  $\tau_{\text{ref}}$  produces the timescale separation that makes PING dynamics possible.

| Parameter                | E population | I population |
|--------------------------|--------------|--------------|
| $\tau_m$ (ms)            | 20           | 5            |
| $C_m$ (nF)               | 1.0          | 0.5          |
| $g_L$ ( $\mu$ S)         | 0.05         | 0.1          |
| $\tau_{\text{ref}}$ (ms) | 3            | 1.5          |
| $E_L$ (mV)               | −65          | −65          |
| $V_{\text{th}}$ (mV)     | −50          | −50          |

|                         |     |     |
|-------------------------|-----|-----|
| $V_{\text{reset}}$ (mV) | −65 | −65 |
| $E_e$ (mV, reversal)    | 0   | 0   |
| $E_i$ (mV, reversal)    | −80 | −80 |

Synapse time constants:  $\tau_{\text{AMPA}} = 2$  ms (excitation),  $\tau_{\text{GABA}} = 9$  ms (inhibition). These set the ceiling on PING’s  $\Delta t$ -stability: once  $\Delta t \gtrsim \tau_{\text{GABA}}$  the E→I→E loop cannot complete within one step.

## Internal consistency

The chosen units are self-consistent — no conversion factors appear in the integration code. Two equations carry the whole system.

The membrane time constant is  $\tau = C/g$ . With  $C$  in nF and  $g$  in  $\mu\text{S}$ ,

$$\tau_{[\text{ms}]} = \frac{C_{[\text{nF}]}}{g_{[\mu\text{S}]}}$$

so  $C_m = 1$  nF and  $g_L = 0.05$   $\mu\text{S}$  give  $\tau_m = 20$  ms directly.

The LIF voltage update is  $dv = (\Delta t/C)(-g_L(v - E_L) + I)$ . With  $\Delta t$  in ms,  $C$  in nF,  $v, E$  in mV,  $g$  in  $\mu\text{S}$ , and  $I$  in nA,

$$dv_{[\text{mV}]} = \frac{\Delta t_{[\text{ms}]}}{C_{[\text{nF}]}} \cdot I_{[\text{nA}]}$$

because  $\text{ms} \cdot \text{nA} / \text{nF} = \text{mV}$  exactly.

Conductance-current products share the same ledger:  $g(v - E)$  is  $\mu\text{S} \times \text{mV} = \text{nA}$ , so synaptic currents fold into  $I$  alongside any direct input current without a scale factor.

## Why not SI?

Pure SI (F, S, V, A, s) forces every value to a large negative exponent —  $C_m = 10^{-9}$  F,  $g_L = 5 \times 10^{-8}$  S,  $\Delta t = 2.5 \times 10^{-4}$  s. The neuroscience convention (ms, mV, nF,  $\mu\text{S}$ , nA) keeps every typical value between  $10^{-3}$  and  $10^2$ , which makes numerical debugging and human intuition faster. The tradeoff is that readers have to trust the unit consistency rather than verify it by plugging into SI formulas — this page is here so that trust is auditable.

# Metrics

14 May 2026

This page is the reference for every number and every panel the scope shows. It is written to stand on its own: if this is the first page you read, you should come away understanding what the scope is showing, what each metric measures, and what a “healthy” value looks like.

## model

*What it is:* The model variant driving the run. These sit on a ladder from simplest (snnTorch, a standard feedforward LIF network) to most biophysical (PING, with excitatory and inhibitory populations coupled into a gamma-producing loop). See COBANet for the conductance-based model.

*How it's calculated:* Read from the `-model` CLI flag. A spinner character prefixes the name on live runs so the eye can tell a frozen frame from one that's still updating.

*Common values:* `snnTorch`, `CUBA`, `COBA`, `PING`.

## dt

*What it is:* The integration timestep in ms — how much real time elapses per simulation step. Smaller  $\Delta t$  is more accurate but more expensive (more steps per trial).

*How it's calculated:* Read from `-dt`. Held fixed across a training run; can be varied at inference to probe  $\Delta t$ -stability.

*Common values:* 0.1 ms (fine), 0.25 ms (default), 1.0 ms (coarse). PING breaks down above about 1 ms because the excitatory-inhibitory feedback loop can't complete within a single step.

## N

*What it is:* Number of excitatory neurons in the hidden layer. For PING, the inhibitory population is sized at  $N_E/4$  (the classical 4:1 cortical ratio).

*How it's calculated:* Read from `-n-hidden`.

*Common values:* 256, 512, 1024.

## in

*What it is:* The peak firing rate of the input neurons, in Hz. An MNIST pixel with intensity 1.0 fires at this rate; a dark pixel fires at zero. Controls how strongly the network is driven.

*How it's calculated:* Each input neuron emits a Bernoulli spike at each step with probability

$$p = r \cdot \Delta t / 1000$$

where  $r$  is this per-pixel rate (Hz) scaled by pixel intensity. See Training § Input encoding for the full scheme.

*Common values:* 50 Hz for PING, 100 Hz for simpler models. - in the header when not set.

## E

*What it is:* Firing rate of the excitatory population, averaged over all E neurons and over the trial, in Hz. The single most important live readout of network activity.

*How it's calculated:* Let  $s_E \in \{0, 1\}^{T \times N_E}$  be the binary E spike array ( $T$  timesteps,  $N_E$  neurons; entry is 1 if neuron  $i$  spiked at step  $t$ ), and  $T_{\text{sec}} = T\Delta t/1000$  the trial length in seconds. Then

$$r_E = \frac{\sum_{t,i} s_{E[t,i]}}{N_E \cdot T_{\text{sec}}}$$

*Common values:* 1–30 Hz is sparse-coding territory (healthy for snnTorch when classifying MNIST); 40–80 Hz is the gamma-locked regime (PING target); over  $\sim 150$  Hz means the network has saturated; 0 Hz means it's silent.

## I

*What it is:* Firing rate of the inhibitory population, same definition as  $E$ . Only meaningful for models that have an I population (COBA, PING); shows - otherwise.

*How it's calculated:* Same as  $E$ , on the I spike array  $s_I$  and with  $N_I$  inhibitory neurons:

$$r_I = \frac{\sum_{t,i} s_{I[t,i]}}{N_I \cdot T_{\text{sec}}}$$

*Common values:* Typically 2–4 $\times$  the E rate under balanced PING operation — roughly 80–200 Hz.

## f<sub>0</sub>

*What it is:* A resolved dominant oscillation frequency of a recorded population, in Hz. A gamma-locked network should have a clear spectral peak, but a numerical maximum inside a search band is not by itself evidence of a rhythm.

*How it's calculated:* Generic simulator metrics do not currently emit  $f_0$ ; the earlier autocorrelation-lag shortcut was disabled because it selected a sub-cycle feature near 1 ms rather than the gamma period. Experiments use the shared gamma-frequency analysis helper on retained rasters or population traces. The experiment records its named configuration: source population, transient exclusion, binning and smoothing, Welch settings, search band, interpolation, activity and prominence gates, harmonic handling, and trial aggregation. New default-PING experiments use the recommended 30–80 Hz E-population configuration; historical experiments may retain explicit named variants when their scientific question requires a broader band or different preprocessing.

*Common values:* 30–80 Hz for a resolved gamma rhythm. Silence, inadequate prominence, insufficient duration, non-finite input, or a rejected band-edge maximum produces an unresolved result, not a fabricated 0 Hz frequency.

## CV

*What it is:* How bursty the E population's firing is. Takes the total E spike count in each 2 ms bin and computes the coefficient of variation (std / mean) of those counts across bins.

*How it's calculated:* Bin  $s_E$  at 2 ms; let  $n_b$  be the total E spike count in bin  $b$ . Then

$$\text{CV} = \frac{\sigma(n_b)}{\max(\mu(n_b), 10^{-9})}$$

*Common values:* Around 1 for Poisson-like asynchronous firing; well above 1 (often  $\gtrsim 2$ ) for gamma-locked PING, where spikes cluster into cycle peaks and leave the troughs empty; below  $\sim 0.3$  for a clock-like or saturated network.

## I/E

*What it is:* The ratio of inhibitory to excitatory population rates. A single number that summarises E–I balance.

*How it's calculated:*

$$I/E = \frac{r_I}{\max(r_E, 10^{-9})}$$

*Common values:* 2–4 under balanced PING operation. Much higher means inhibition has run away; much lower means inhibition is failing or E has saturated.

## act

*What it is:* The fraction of excitatory neurons that spiked at least once during the trial. Complements the population rate: a high  $E$  could come from a few neurons firing a lot, or many neurons firing a little — *act* tells you which.

*How it's calculated:*

$$\text{act} = \frac{\#\{i : \sum_t s_{E[t,i]} > 0\}}{N_E}$$

*Common values:* 1–3 % is healthy sparse coding (a classical snnTorch regime). 80 %+ with CV near 0.4 is healthy gamma-locked PING. Persistent values below 1 % or above 95 % alongside stalled accuracy are pathological.

## e\_raster

*What it is:* The excitatory spike raster over the trial. Each dot is one spike; the y-axis is E-neuron index, the x-axis is time. This is the primary dynamical read and occupies the largest cell in the grid.

*How to read it:* Vertical bands (near-synchronous firing across the population, at regular intervals) mean gamma-locked PING. A uniformly-speckled cloud means asynchronous firing — normal for CUBA or snnTorch. An empty raster means the network is silent; a solid block means it is saturated.

## i\_raster

*What it is:* Same idea as *e\_raster* but for the inhibitory population. Empty for models without an I population.

*How to read it:* Under balanced PING the I raster is denser and at higher rate than the E raster, matching the  $2\text{--}4\times$  I/E ratio.

## drive

*What it is:* The mean input current (conductance) reaching the membrane, overlaid with the voltage thresholds a neuron needs to reach to spike.

*How it's calculated:* The input conductance is passed through an exponential synapse with time constant  $\tau_{\text{AMPA}}$  to get the steady-state drive

$$g_{\text{ss}} = \frac{\bar{g}}{1 - e^{-\Delta t / \tau_{\text{AMPA}}}}$$

The bare spike threshold — the drive a neuron needs in the absence of inhibition — is

$$g_{\text{thresh}} = \frac{g_L(V_{\text{th}} - E_L)}{E_e - V_{\text{th}}}$$

The effective threshold adds an inhibition-proportional penalty  $g_i \cdot |E_i - V_{\text{th}}| / (E_e - V_{\text{th}})$ .

*How to read it:* The shaded region is where drive exceeds the effective threshold — that's when E neurons can fire. If drive never crosses threshold the network is dead by construction; if drive is always above, it is saturated.

## weights

*What it is:* Histograms of the current weight values, one sub-histogram per weight matrix (input-to-hidden, hidden-to-output, and any recurrent E-E / E-I / I-E matrices).

*How to read it:* Signed weights can span zero. Dale-constrained weights are initialized by lower-clamping a Gaussian and are projected back to the non-negative domain after updates. The initial histogram therefore has a point mass at zero from clamping and optional explicit zero initialization; those entries remain trainable. A later stack at zero may reflect the optimization boundary, so initial and final zero fractions must be compared before interpreting it as pruning.

## output

*What it is:* The readout logits for each output class, over the course of the trial.

*How it's calculated:* The readout accumulates hidden spikes across time and projects them through a trained linear layer:

$$\hat{y}_t = \left( \sum_{s \leq t} s_s^{\text{hid}} \right) W_{\text{out}} + b_{\text{out}}$$

The argmax at the final step is the model's prediction. See Training § Readout.

*How to read it:* For MNIST there are ten traces; if the network has learned, one trace pulls away from the pack as the trial progresses. If all traces stay flat, or one dominates from  $t=0$ , the run is pathological.

## psd

*What it is:* The power spectral density (frequency content) of the E population rate  $r_E(t)$ . The gamma band (30–80 Hz) is shaded.

*How it's calculated:* The experiment's named gamma-frequency configuration defines the population trace, transient exclusion, optional binning or smoothing, and spectral estimator. The shared helper returns the frequency axis, PSD, discrete and interpolated peaks, band-median power, prominence, and a resolved or unresolved reason. Figures may normalise the returned PSD for display, but peak resolution is applied to the unnormalised spectrum.

*How to read it:* A flat PSD means asynchronous firing. A peak inside the shaded band means gamma. A peak below 30 Hz means sub-gamma (beta). A peak above 80 Hz is rejected by the  $f_0$  search.

## participation

*What it is:* The distribution of per-neuron spike counts across the E population for this trial.

*How to read it:* A stack at zero indicates dead neurons; a stack at the per-neuron ceiling indicates saturated neurons. Both can be invisible from the population-level  $E$  token, which averages across the group.

## acc\_curve

*What it is:* Test accuracy, training loss, and learning rate as a function of epoch — the standard training-progress panel. All three are normalised to their running maximum and plotted on a single 0–100 % axis. Rendered only during training runs.

*How to read it:* A healthy run has accuracy climbing from  $\sim 10\%$  (chance on MNIST) toward 85–98 %, and loss dropping monotonically. A flat accuracy with drifting loss usually means the readout can't separate classes.

## rate\_curve

*What it is:* The E and I firing rates as a function of training epoch. Training-only.

*How to read it:* Stable rates within the healthy regime for the model (see *act* above) means the network is holding its operating point as it learns. Monotonic drift toward 0 or toward a ceiling usually means gradient pressure is pushing the network out of its regime.

## grad\_flow

*What it is:* For each weight matrix, the ratio of gradient norm to weight norm — how hard each layer is being updated relative to its current size. Training-only; log y-axis.

*How to read it:* The shaded band from  $10^{-3}$  to  $10^{-2}$  is the healthy window. Values below mean gradients are vanishing (that layer is not learning); above means they are exploding.

## digit\_image

*What it is:* The MNIST digit currently being presented to the network. A small greyscale inset that lets you sync the readout in *output* to the actual input class.

## sweep

*What it is:* A generic progress indicator for parameter-sweep runs. Shows the full sweep range faintly and the completed prefix solidly, with a dot on the current value.

## sweep\_rates

*What it is:* E and I firing rates accumulated across an inference sweep — one point per sweep frame, updated as the sweep progresses. Sweep-only.

*How to read it:* If the trace is flat across the swept variable, the network is stable under that variable. If it fans out by one to two orders of magnitude, it is not — this is the signature read off in a  $\Delta t$ -stability experiment.

## sweep\_f0

*What it is:* Resolved peak oscillation frequency  $f_0$  across the sweep under one recorded analysis configuration, with the gamma band (30–80 Hz) shaded. Sweep-only.

*How to read it:* A PING run with a robust E→I→E loop holds resolved  $f_0$  inside the shaded band across the whole sweep. Missing points are unresolved spectra and must retain their reason; they are not zeros. Drift out of band or loss of resolution indicates that the loop is changing or failing at that parameter value.

## Spectral radius

*What it is:* The largest-magnitude eigenvalue of the recurrent weight matrix  $J$ . A linear stability indicator: if  $\rho(J) > 1$ , the linearised network would explode;  $\rho(J) \approx 1$  sits at the edge of chaos.

*How it's calculated:* The recurrent matrix is reassembled post-training with E columns kept positive and I columns flipped to negative (so Dale's law appears as signs), then  $\rho(J) = \max_i |\lambda_i|$  via an eigendecomposition.

*Common values:*  $\rho < 1$  is quiescent (no sustained oscillation);  $\rho \approx 1$  is the gamma operating regime;  $\rho > 1$  is linearly unstable but the spiking nonlinearity can still stabilise it.

## Linear $f_0$ prediction

*What it is:* A continuous-rate prediction for the oscillation frequency, derived from the eigenvalue of  $J$  with the largest imaginary part.

*How it's calculated:* Pick  $\lambda^* = a + bi$  with largest  $|b|$ , then

$$f_0^{\text{lin}} = \frac{|b|}{2\pi} \cdot 1000 \text{ Hz}$$

*Common values:* Typically an upper bound on the measured  $f_0$  — the linear mode ignores the spiking nonlinearity and the refractory floor.

## Refractory-floor prediction

*What it is:* A lower bound on the oscillation frequency set by the biology: no spiking network can cycle faster than one excitatory refractory period plus one GABA-synapse decay.

*How it's calculated:*

$$f_0^{\text{cor}} = \frac{1000}{\tau_{\text{ref}}^E + \tau_{\text{GABA}}} \text{ Hz}$$

*Common values:* The measured  $f_0$  typically lies between  $f_0^{\text{cor}}$  and  $f_0^{\text{lin}}$ .

## loss

*What it is:* The training-set cross-entropy at the end of each epoch — the scalar the optimiser is minimising.

*Common values:* Starts near  $\ln(10) \approx 2.3$  for chance-level classification on MNIST and drops monotonically under healthy training. A flat or climbing loss means the gradient isn't reaching the readout.



**test\_loss**

*What it is:* Cross-entropy on the validation split, evaluated once per epoch. The `test_` prefix is a legacy artifact-field name; no official MNIST test images are used during training.

*Common values:* Tracks *loss* with a small gap. A widening gap usually means overfitting; a gap that collapses to zero often means data leakage between train and test.

**lr**

*What it is:* The current learning rate — the multiplier on each gradient step. Varies if `adaptive-lr` is set; constant otherwise.

*Common values:*  $10^{-2}$  for `snnTorch` / CUBA;  $10^{-4}$  for COBA / PING, whose conductance-based gradients are much steeper (see Gradient Stabilisation).

**grad\_norm**

*What it is:* The mean gradient norm across all parameters, taken after gradient clipping.

*Common values:* Stable to within an order of magnitude across a run. A sudden jump usually precedes an NaN loss.

**grad\_ratios**

*What it is:* A dictionary mapping each weight matrix to its  $\|\nabla\| / \|W\|$  — the quantity plotted by *grad\_flow*.

*Common values:* Healthy band  $10^{-3}$  to  $10^{-2}$  per layer; below is vanishing, above is exploding.

**acc**

*What it is:* Validation accuracy (%) at the end of each epoch. It selects the checkpoint but is not the final reported test accuracy.

*Common values:* 10 % is chance on MNIST; 85–90 % is typical at a small training tier; 95–98 % at medium or larger; anything above 98 % flags a leaked test split or a bug.

**best\_acc**

*What it is:* The maximum of *acc* over all epochs seen so far. Tracked alongside *best\_epoch* (the epoch that set it) and a *new\_best* flag (true on the epoch that set it).

*Common values:* This is the checkpoint-selection value. If *best\_epoch* is near the final epoch the run was still improving; if much earlier, it had plateaued.

On inference runs, *best\_acc* is just the single-shot test accuracy; the raw count *n\_correct* is saved alongside, and per-sample calls go to *test\_predictions.json* (one row per sample, carrying *idx*, *true*, *pred*, *correct*, *logits* for confusion-matrix and calibration downstream).

# Training

14 May 2026

This is the shared training recipe every model on the ladder uses. It runs, in order, through how gradients flow through time, the surrogate that lets them pass through spikes, the one flag that stops them exploding (its own article, Gradient Stabilisation), the loss and optimiser, the readout options, the firing-rate regulariser, weight initialisation, and the tasks the networks are trained on.

## Backpropagation through time

Every model here is a recurrent system run forward in time, so gradients come from Backpropagation Through Time (BPTT): unroll the recurrence into a deep feedforward graph — one layer per timestep, all sharing the same weights — and backpropagate through it.

Take a hidden state  $h^t$  that evolves as

$$h^t = f(h^{t-1}, x^t; \theta), \quad y^t = g(h^t; \theta)$$

with input  $x^t$ , output  $y^t$ , and parameters  $\theta$  shared across time. Running  $T$  steps gives a chain  $h^0 \rightarrow h^1 \rightarrow \dots \rightarrow h^T$ , which for gradients we treat as a depth- $T$  feedforward network with tied weights.

The gradient with respect to a parameter  $\theta_k$  then sums over every timestep it touched:

$$\frac{\partial \mathcal{L}}{\partial \theta_k} = \sum_{t=1}^T \frac{\partial \mathcal{L}}{\partial h^t} \cdot \frac{\partial h^t}{\partial \theta_k}$$

The catch is the product of per-step Jacobians  $\partial h^{t+1} / \partial h^t$  running through the chain: if their norms sit above 1 the product explodes in  $T$ , if below 1 it vanishes.

SNNs fit BPTT naturally — one simulation step is one step of the recursion, with the hidden state holding membrane potentials, synaptic conductances, and refractory counters. A 200 ms trial at  $\Delta t = 0.1$  ms unrolls to  $T = 2000$  steps. Because the state variables carry physical units (mV,  $\mu$ S), the per-step Jacobians are wildly scaled: voltage updates carry tiny factors like  $\Delta t / C_m$  while surrogate gradients through spikes are  $O(1)$ . That mismatch is exactly what the gradient-stabilisation flag exists to fix — derived in full in Gradient Stabilisation.

## Surrogate gradients

The spike function  $S = \mathbf{1}[U \geq \theta]$  has zero gradient almost everywhere, so the backward pass substitutes a smooth surrogate. Pinglab uses the fast-sigmoid surrogate everywhere. Forward is the hard step; backward is

$$\frac{\partial \tilde{S}}{\partial U} = \frac{k}{(1 + k |U - \theta|)^2}$$

This matches snntorch's *FastSigmoid*, so equal- $k$  comparisons against the snntorch reference test the update rule, not the surrogate.

It takes its slope from `SURROGATE_SLOPE = 5.0`, overridable per-run with `-surrogate-slope`.

## Gradient stabilisation

Conductance-based networks (COBA, PING) need one extra ingredient to train: the recurrent E $\leftrightarrow$ I loop makes the backpropagated gradient explode during BPTT, and a single flag, `--v-grad-dampen`, tames it. The full derivation — why the gradient diverges once per gamma cycle, and why per-step voltage damping fixes it without touching the forward pass — has its own article: **Gradient Stabilisation**.

## The training loop

Logits from the readout go into cross-entropy loss:

$$L_{\text{CE}} = -\frac{1}{B} \sum_{b=1}^B \log \frac{\exp(\hat{y}_{b,c_b})}{\sum_k \exp(\hat{y}_{b,k})}$$

with batch size  $B$ , logit vector  $\hat{y}_b$ , and true class  $c_b$ ; chance-level loss on a 10-class problem is  $\ln 10 \approx 2.30$ . The optimiser is Adam, with gradients clipped to unit norm (`GRAD_CLIP = 1.0`) before each step. The saved `weights.pth` is the *best-epoch* state by test accuracy, not the final epoch.

## Readout

The readout collapses the last hidden layer’s activity into class logits; `--readout` picks how.

Four modes:

- **spike-count** — sum last-hidden spikes over the trial and project linearly,  $\hat{y} = (\sum_t s_t^{\text{hid}})W_{\text{out}} + b_{\text{out}}$ . Equivalent to spike-rate up to a constant.
- **mem-mean** — pass spikes through a final spiking LIF with subtractive reset. At each timestep, the pre-reset output voltage is added to the trial accumulator; any output spike then subtracts the threshold before the next timestep. The class logit is the temporal mean of those pre-reset voltages. This is the default for the COBA/PING recipes and is used by exp025.
- **li** — leaky integrator: a non-spiking LIF whose final-step membrane potential is the logit.
- **rate** — softmax over per-trial spike rates.

The choice matters because it sets where the gradient enters the network: **mem-mean** lets it flow through the output LIF’s pre-reset voltage at every timestep, while **spike-count** only sees the aggregate. Although the reset is applied after the current voltage is accumulated, it changes the output state—and therefore the voltage statistic—at later timesteps.

## Firing-rate regularisation

Hidden activity can be limited with `--fr-reg-upper-target-hz` and `--fr-reg-upper-strength`:

$$r_b = \frac{1}{N_E T} \sum_{n \in E} z_{bn}, \quad \mathcal{L}_{\text{fr}} = \frac{s_u}{B} \sum_b \text{ReLU}(r_b - r_{\text{max}})^2$$

The ceiling is applied separately to each presentation’s population-mean hidden-E rate before averaging across the minibatch. The loss is normalised over neurons, presentation duration, samples, and hidden layers. This is the mechanism behind the activity sweep in exp025 and the rate-floor framing in ar009.

## Weight init

Dale-constrained magnitudes use a lower-clamped Gaussian, not a half-normal or truncated normal:

$$X_{ij} \sim \mathcal{N}(\mu, \sigma^2), \quad U_{ij} = \max(0, X_{ij}).$$

The configured  $\mu$  and  $\sigma$  are parent-Gaussian parameters on the summed-coupling scale, not moments of one stored edge. With initial-zero fraction  $s \in [0, 1)$  and Bernoulli indicator  $B_{ij}$ , the stored initialization is

$$W_{ij}^0 = B_{ij}U_{ij}/((1-s)N_{\text{pre}}).$$

The compensation keeps the expected column sum independent of  $s$ ; lower clamping means that expected sum is  $\mathcal{E}[\max(0, X)]$ , which is recorded alongside the configured parent parameters. Both lower-clamp zeros and explicitly zeroed entries remain trainable and may become positive. This is sparse initialization of a dense trainable matrix, not structural sparsity.

## Dale’s law under Adam

When Dale’s law is on, the feedforward matrices  $W_{\text{ff}}$  are clamped to  $W \geq 0$  when they are read by the forward pass and every trainable constrained matrix is projected back into the non-negative cone by `project_dales()` after each optimiser step. The recurrent conductance matrices  $W_{ee}$ ,  $W_{ei}$ ,  $W_{ie}$ , and  $W_{ii}$  are not forward-clamped: they are initialised non-negative and, when trainable, kept non-negative by the post-step projection. Their entries are conductance magnitudes; pathway-specific reversal potentials, rather than a negative stored  $W_{ie}$ , determine whether a synapse is excitatory or inhibitory.

# Manuscript

21 June 2026

## Abstract

Gamma oscillations are widespread in cortical activity but are largely absent from trained spiking neural networks, which typically operate in a current-based regime or impose oscillations as an external input. We train a spiking network with a fixed pyramidal–interneuron gamma (PING) loop on MNIST under surrogate-gradient descent, with the recurrent  $E \leftrightarrow I$  weights held at biophysical values. At matched test accuracy on the accuracy–rate frontier, the post-training excitatory firing rate is roughly an order of magnitude below a conductance-based control (3-fold by total population spike count once the higher-rate inhibitory pool is included), and the trained rate is well described by an affine relation  $r_E \approx -0.7 + 0.285f_\gamma$  with the measured gamma frequency ( $R^2 = 0.997$ ). When the loop weights are released for training under a Dale’s-law clamp, the rhythmicity collapses within one epoch and is not recovered from any initial condition tested. The trained network classifies a continuously concatenated digit stream without retraining or a segmentation cue; streaming accuracy is approximately governed by the product of presentation duration and input rate, remains below  $\approx 80\%$  for durations of 15 ms or less, and at 200 ms rises from chance below 0.5 Hz to clearly informative performance by 2 Hz. These results are consistent with an interpretation of gamma as a structural constraint on excitatory firing rates that does not require learned tuning of the inhibitory connectivity.

## 1. Introduction

Gamma oscillations in the 30–80 Hz band have been associated with attention, binding, and gating in cortical activity [1, 2, 3], with the original visual-cortex observation reported by [4]. Two generation mechanisms are commonly distinguished, ING and PING [5, 6] the present work focuses on PING. PING arises from the dynamics of a recurrent excitatory–inhibitory ( $E \leftrightarrow I$ ) loop [7]. Optogenetic activation of fast-spiking interneurons in intact cortical circuits drives gamma rhythms [8, 9, 10, 11]. Earlier in vitro recordings [12] and biophysical models [13] characterised interneuron-driven gamma in isolated inhibitory networks, and the synaptic mechanisms that synchronise the interneuron pool have been described [14].

PING has been studied extensively in biophysical [15, 16, 17] and neural-mass / mean-field models [18, 19, 20, 21], but these models are descriptive: they are not trained on a task. The parallel literature on trainable spiking neural networks uses surrogate-gradient descent for end-to-end optimisation [22, 23, 24] the resulting networks are typically current-based and non-rhythmic. The rhythmic variants either impose the oscillation as an external input [25] or obtain it as an emergent property of unconstrained surrogate-gradient training [26] in neither case is the rhythm carried by a fixed, biophysically-calibrated PING loop, and the present work is to our knowledge the first task-trained spiking network of that kind.

Cortical pyramidal cells fire at low rates (typically below 10 Hz) under strong recurrent input [27], and the cortical metabolic budget is dominated by excitatory spike generation, with inhibitory spikes substantially less costly per spike [28, 29]. The mechanism that constrains pyramidal firing rates under these conditions is not fully understood. We test the hypothesis that a fixed  $E \leftrightarrow I$  loop, by generating a gamma rhythm, constrains the post-training

excitatory firing rate. A spiking network with a fixed PING loop is trained on MNIST and the post-training firing rate is compared with a non-rhythmic baseline at matched accuracy. In the architecture studied here the measured rhythm and firing rate are tightly linked, so rate and timing are synergistic descriptions of a single dynamics rather than independent codes [30].

The remainder of the paper is organised as follows. §2.1 describes the model; §2.2 characterises the gamma onset in theory and simulation; §2.3 reports the trained accuracy–rate frontier; §2.4 reports two experiments that test whether the firing-rate reduction is acquired during training; §2.5 reports the relationship between the gamma frequency and the post-training firing rate; §2.6 reports robustness of the post-training firing rate to spike perturbations and to integration timestep; and §2.7 reports a streaming-classification protocol.

## 2. Results

### 2.1 The model: COBA baseline and the PING loop

The network is a two-population conductance-based spiking model with a single hidden layer of  $N_E$  excitatory (E) and  $N_I$  inhibitory (I) leaky integrate-and-fire (LIF) units, driven by feedforward input weights  $W_{in}$  and read out by a non-spiking leaky-integrator layer over the excitatory population (§5.2). Recurrence is confined to one excitatory–inhibitory (E↔I) loop: E projects to I through the weight  $W^{EI}$  and I back to E through  $W^{IE}$ , with no E→E or I→I connection. Throughout the paper we compare two configurations of this single architecture: with the loop disabled ( $W^{EI} = W^{IE} = 0$ ) it is a conductance-based (COBA) control in which input drives the excitatory population alone, and with the loop engaged it is the pyramidal–interneuron gamma (PING) configuration. The same network is trained on MNIST by surrogate-gradient descent from §2.3 onward (§5.4); in this section we characterise its free-running dynamics.

Free-running, the COBA configuration fires asynchronously: its power spectral density (PSD) has no peak in the gamma band, and the excitatory firing-rate–current ( $f$ – $I$ ) curve rises to  $\approx 485$  Hz under the strongest drive tested. Engaging the E→I→E loop instead produces synchronous inhibitory bursts and gamma-banded excitatory rasters with a PSD peak at  $f_\gamma \approx 41$  Hz, and holds the excitatory firing rate approximately an order of magnitude below the COBA baseline across two decades of input drive (Figure 1).




Figure 1: **A single recurrent  $E \rightarrow I \rightarrow E$  loop simultaneously generates a gamma rhythm and clamps the excitatory firing rate.** Free-running activity of the two-population conductance-based network (excitatory pool  $N_E = 1024$ , inhibitory pool  $N_I = 256$ ; canonical biophysical parameters, §5.1) under matched Poisson drive, in two configurations. Each column shows, from top: a wiring schematic, a single-trial spike raster, the excitatory power spectral density (PSD), and the excitatory  $f-I$  curve. **(A)** COBA baseline with the recurrent loop disabled ( $W^{EI} = W^{IE} = 0$ ): input projects to the excitatory (E) population only, with no inhibitory (I) population (schematic). The E spike raster is asynchronous, the Welch PSD of the summed E population shows no gamma-band peak, and the excitatory  $f-I$  curve rises to  $\approx 485$  Hz under the strongest drive tested. **(B)** PING configuration with the loop engaged (schematic:  $E \rightarrow I$  via  $W^{EI}$ ,  $I \rightarrow E$  via  $W^{IE}$ ; no  $I \rightarrow I$  or  $E \rightarrow E$  synapse): the inhibitory (I) population fires synchronous bursts, the E raster forms gamma bands, the PSD shows a discrete peak at  $f_\gamma \approx 41$  Hz, and on axes shared with (A) the E rate is held approximately an order of magnitude lower across two decades of input drive while the I rate rises to  $\approx 80$  Hz. Source: exp023.

## 2.2 Gamma onset across the $W^{EI} \times W^{IE}$ plane

Across the  $W^{EI} \times W^{IE}$  coupling plane the excitatory firing rate decreases, the inhibitory firing rate increases, and the lobe-trough rhythmicity score  $R$  (a normalised, dimensionless measure of periodicity in the population autocorrelation, bounded in  $[0, 1]$ ; §5.5) increases monotonically with coupling strength:  $R \approx 0$  along the COBA edges and  $R \approx 0.98$  at strong coupling. The four-dimensional mean-field reduction (§5.3) predicts a supercritical Hopf bifurcation at external drive  $I_{ext}^* = 0.6$  nA with crossing frequency  $f^* \approx 27.6$  Hz. The classification as supercritical is supported by quasi-static up/down ramps with peak hysteresis below  $10^{-5}$  in rate units and by the linear scaling of the squared steady-state oscillation amplitude  $A$ ,  $A^2 \propto (I_{ext} - I_{ext}^*)$  ( $R^2 = 0.999$ ). The predicted gamma frequency is in qualitative agreement with the spiking measurement across the GABA synaptic decay time constant  $\tau_{GABA} \in [4.5, 27]$  ms (Figure 2).




Figure 2: **Gamma emerges through a smooth, reversible onset across the coupling plane, consistent with a supercritical Hopf bifurcation of the mean-field reduction.** Nine panels (A–I). (A–C) Steady-state measurements across the  $11 \times 11$   $W^{EI} \times W^{IE}$  coupling plane: mean excitatory firing rate (A), mean inhibitory firing rate (B), and the lobe–trough rhythmicity contrast  $R$  (C, §5.5), which is  $\approx 0$  along the two COBA edges and rises to  $\approx 0.98$  toward strong coupling. (D–F) Single-trial E (black) and I (red) rasters at three points sampled along the  $W^{IE} = 2W^{EI}$  diagonal (circled in C): the loop-disabled origin (D, asynchronous), weak coupling ( $R < 0.5$ , E), and strong coupling (F, sharp gamma volleys). (G–I) The four-dimensional conductance mean-field reduction (§5.3): a complex-conjugate eigenvalue pair crosses into the right half-plane at external drive  $I^* = 0.6$  nA (G), locating a Hopf bifurcation at  $f^* \approx 27.6$  Hz; the steady-state oscillation amplitude grows continuously across the onset with coincident up- and down-ramp branches (H), the signature of a supercritical, reversible transition; and the predicted gamma frequency falls with  $\tau_{\text{GABA}}$  in qualitative agreement with the spiking measurement (I). Source: exp054 (coupling-plane maps and mean-field, incorporating exp033); spiking  $f_\gamma$  from exp041.

### 2.3 Trained PING attains COBA accuracy at $\approx 10 \times$ fewer spikes

Both architectures, trained on MNIST under surrogate-gradient descent (§5.4), converge to approximately 90% test accuracy. Sweeping the sample-wise hidden-E rate ceiling generates



an accuracy–rate frontier; at every ceiling tested, PING attains higher accuracy at lower mean hidden-E firing rate than COBA. At the unpenalised operating point, PING reaches  $\approx 90\%$  accuracy at  $\approx 16.6$  Hz mean hidden-E rate, against  $\approx 91\%$  at  $\approx 114$  Hz for COBA (Figure 3). Every frontier point is reported as the mean over three independent seeds (42, 43, 44), with standard errors across seeds. The PING rate does not decrease further as the ceiling is lowered, consistent with a structural lower bound on the rate.





Figure 3: **Trained PING matches COBA classification accuracy while operating at an order-of-magnitude lower excitatory firing rate.** Both configurations were trained on MNIST by surrogate-gradient descent (§5.4). Top: representative single-trial rasters of the trained networks: COBA fires densely and asynchronously with the inhibitory population silent, whereas PING fires in gamma bands with synchronous inhibitory bursts (red) above excitatory spikes (black). For visualisation, each raster is an extended 400 ms replay of one digit, twice the 200 ms presentation used for training and quantitative evaluation. Bottom left: test accuracy per epoch, both configurations converging to  $\approx 90\%$ . Bottom right: accuracy–rate frontier traced by sweeping the sample-wise hidden-E rate ceiling (§5.4); each marker shows mean hidden-E firing rate (abscissa) and test accuracy (ordinate) across three independent seeds, with standard-error bars. PING lies above and to the left of COBA across the sweep. At the unpenalised operating point (starred), PING reaches  $\approx 90\%$  at  $\approx 16.6$  Hz, against COBA’s  $\approx 91\%$  at  $\approx 114$  Hz. Source: exp025 rate-attractor analysis in exp024.

## 2.4 The firing-rate reduction does not require trained loop weights

Whether the firing-rate reduction in §2.3 is acquired during training or follows from the canonical loop weights is tested by two complementary experiments. We distinguish the two senses of “architectural”: (a) the reduction occurs without gradient-based tuning of the loop weights (which §2.4 establishes), as opposed to (b) the reduction emerges from generic  $E \leftrightarrow I$  structure without any hand-set values (which is not tested; the loop weights are held at the canonical biophysical values of [7]). The claim in this work is (a): the inductive bias is paid for at design time, not during training.


In the first, the recurrent loop is activated at inference on trained COBA networks from seeds 42–44, without retraining any weight. The illustrative seed-42 raster immediately becomes gamma-banded; across seeds, the mean excitatory rate falls by approximately a factor of 14 ( $\approx 112 \rightarrow \approx 8$  Hz), and mean test accuracy falls by  $\approx 48$  pp (Figure 4). The rate reduction therefore occurs without training. The accuracy loss is consistent with the absence of a learned compensation in the feedforward weights, which were optimised in the absence of the loop.



**Figure 4: Engaging the recurrent loop at inference reproduces the PING firing-rate reduction with no weight update.** COBA networks trained with seeds 42–44 are evaluated with recurrent E→I coupling scaled from  $ei = 0$  to  $ei = 1$ , without retraining. Top: illustrative seed-42 rasters at loop-off and full strength. Bottom left: across-seed mean excitatory (black) and inhibitory (red) rates; excitation falls approximately 14-fold (from  $\approx 112$  to  $\approx 8$  Hz) as inhibition rises to  $\approx 45$  Hz. Bottom right: mean accuracy falls from  $\approx 91\%$  to  $\approx 43\%$  (a  $\approx 48$  pp cost). Shaded bands show sample SD across seeds. The rate gating appears when the loop is wired in, whereas the accuracy loss reflects the absence of a feedforward compensation learned in the presence of the loop. Source: exp038.

In the second, the loop weights  $W^{EI}$ ,  $W^{IE}$  are released for training under the Dale’s-law clamp. Both matrices represent non-negative conductance magnitudes; pathway identity fixes their reversal potentials, and the negative GABA reversal potential makes the I→E pathway inhibitory (§5.4). After each optimiser step, the trained magnitudes are projected onto the non-negative cone. In all conditions tested, the rhythmicity score collapses within a single training epoch: the first logged metric, after epoch 1, shows  $R \approx 0.05$ , compared with the canonical initial value  $R \approx 1$  (Figure 5). The collapse is faster than the per-epoch logging interval, so no intermediate state is recorded. From every initial condition tested (canonical PING values, zero, and  $0.1 \times$  canonical), the inhibitory firing rate remains near zero,  $R$  stays in 0.02–0.11, and final test accuracy is approximately 90% at  $\approx 17$  Hz mean E rate for the frozen-PING control (Figure 5). These numbers differ from the §2.3 frontier endpoint ( $\approx 90\%$

at  $\approx 16.6$  Hz) because the §2.4 setup omits the activity regulariser and isolates the within-experiment contrast between frozen and trainable conditions rather than tracing the accuracy–rate frontier. Within this setup, gradient descent does not preserve or recover effective  $E \rightarrow I$  recruitment from any tested initial condition.



r001


**Figure 5: Releasing the loop weights to gradient descent prunes the rhythm within a single epoch, from every initialisation.** Per-epoch training metrics with the recurrent weights  $W^{EI}$ ,  $W^{IE}$  made trainable under the Dale’s-law clamp, over 50 epochs on MNIST. Lines are the mean of three seeds (42–44); shading is the across-seed range. Conditions differ only in initialisation of the loop weights: canonical PING values (black), zero (red), and  $0.1 \times$  canonical (amber), against a frozen-PING control (grey, dashed). **(A)** Test accuracy: all conditions overlap at  $\approx 84$ – $91\%$ . **(B)** Mean excitatory firing rate: the trainable conditions rise to  $\approx 49$ – $88$  Hz as the loop is dismantled, while the frozen control remains gated near 17 Hz. **(C)** Mean inhibitory firing rate: the trainable conditions collapse to  $\approx 0$  Hz within a few epochs, while the frozen control’s inhibitory rate rises to  $\approx 108$  Hz as its readout trains. **(D)** Lobe–trough rhythmicity contrast: the frozen control holds at  $\approx 1$  while every trainable initialisation drains to  $\approx 0.02$ – $0.11$ . Source: exp049.

The second result is conditional on the gradient-damping scheme that stabilises PING training (the gradient flowing through the loop is attenuated by a factor  $1/d$  on the backward pass, with  $d = 1000$ ; §5.4); a constrained-training scheme (§4 future directions) would test whether the loop’s pruning depends on the damping regime. The first experiment (inference-time activation) uses no gradients and is unaffected by this caveat, and carries most of the weight of the §2.4 conclusion.

## 2.5 Post-training $E$ rate covaries with gamma frequency

The post-training excitatory firing rate covaries approximately affinely with the measured gamma frequency. Across a sweep of  $\tau_{\text{GABA}}$ , which jointly changes the inhibitory decay kinetics, integrated inhibitory influence, and realised  $f_\gamma$ , the trained  $r_E$  is well fit by  $r_E =$

$-0.7 + 0.285f_\gamma$  ( $R^2 = 0.997$ , three seeds per point; Figure 6). Mean test accuracy declines from 91.2% at  $\tau_{\text{GABA}} = 4.5$  ms to 81.9% at 27 ms, a 9.3 percentage-point tradeoff across the sweep. The association has a cycle-resolved counterpart. Resolving spikes by (cell, cycle) pair, 98.85% contain at most one spike across the full  $\tau_{\text{GABA}}$  sweep:  $P(0) \approx 75\%$ ,  $P(1) \approx 24\%$ , and the multi-spike fraction ( $\geq 2$ ) is  $\approx 1\%$  (Figure 7). Because  $\tau_{\text{GABA}}$  changes more than frequency alone, these experiments do not identify  $f_\gamma$  as the sole causal variable.



r001

**Figure 6: Post-training excitatory rate covaries affinely with gamma frequency across a sweep of inhibitory decay kinetics.** Networks were trained from scratch at each of six values of the GABA decay constant  $\tau_{\text{GABA}} \in \{4.5, 6, 9, 12, 18, 27\}$  ms. Changing  $\tau_{\text{GABA}}$  alters both the realised gamma frequency and the duration and integrated influence of inhibition (§5.4). Top: mean post-training excitatory firing rate against measured  $f_\gamma$ ; markers are per-condition means over three seeds, with error bars ( $\pm$  SD) on both axes. The linear fit  $r_E = -0.7 + 0.285f_\gamma$  passes through every error bar ( $R^2 = 0.997$ ). Bottom: mean test accuracy declines from 91.2% at  $\tau_{\text{GABA}} = 4.5$  ms to 81.9% at 27 ms, a 9.3 percentage-point tradeoff. The sweep establishes covariance with realised frequency, not an independent causal effect of frequency alone. Source: exp041.




Figure 7: **The affine rate law follows from a near-binary per-cycle firing statistic: each excitatory cell contributes at most one spike per gamma cycle.** Excitatory spikes were resolved into (cell, cycle) pairs by assigning each spike to the gamma cycle inferred from peaks of the population inhibitory-burst rate (§5.5). Each panel shows the distribution of spikes per pair (0, 1, 2, or  $\geq 3$ ) at one value of  $\tau_{\text{GABA}}$ . Across the sweep,  $P(0) \approx 75\%$ ,  $P(1) \approx 24\%$ , and the multi-spike fraction ( $\geq 2$ ) stays near  $\approx 1\%$ ; pooled over all conditions, 98.85% of pairs contain at most one spike. Source: exp046.

## 2.6 Dynamics and robustness

The gating depends on the timing of inhibition, not its mean level. Perturbations of the trained PING network at inference reveal a deletion-versus-addition asymmetry. From an unperturbed baseline of approximately 90% accuracy, PING retains approximately 89% accuracy under deletion of 80% of emitted spikes (little degradation); addition of off-phase Poisson noise instead drives accuracy down to chance as the injected rate grows, because those spikes recruit the inhibitory pool at arbitrary phase and disrupt the rhythm [31]. COBA exhibits the opposite asymmetry (Figure 8). Two inference-time jitter perturbations of the inhibitory spike train, both holding the mean inhibitory rate fixed, produce opposite effects on the excitatory rate: per-cell jitter smears each burst into a continuous shunt and reduces the excitatory rate to zero, while cycle-coherent jitter preserves within-burst synchrony and raises the excitatory rate from  $\approx 17$  Hz to  $\approx 73$  Hz (Figure 9) [32].




Figure 8: **The gating is robust to spike deletion but fragile to spike addition, the expected signature of a phase-based code.** PING and COBA networks trained with seeds 42–44 are perturbed at inference without retraining. Left: deletion of a random fraction of emitted spikes. PING retains  $\approx 89\%$  mean accuracy through 80% deletion, close to its unperturbed value. Right: addition of Poisson spikes, expressed relative to each population’s baseline rate. PING falls toward chance as off-phase spikes disrupt the rhythm; COBA, having no rhythm to protect, is more tolerant to addition. Lines show across-seed means and shaded bands show sample SD. Source: exp037.




Figure 9: **Two inhibitory-jitter manipulations at the same magnitude that hold the mean inhibitory rate fixed drive the excitatory rate in opposite directions, isolating timing from level.** The trained PING inhibitory spike train is perturbed at inference while the mean per-cell inhibitory rate is held constant. Both arms use the same jitter magnitude,  $\sigma = 14$  ms — only the *kind* of jitter differs. Top: single-trial rasters (E black, I red). Bottom: mean excitatory rate (black) and accuracy (red) versus jitter magnitude  $\sigma$ , with the realised mean inhibitory rate overlaid (grey). Left: per-cell jitter smears each burst into a continuous shunt; the excitatory rate falls to  $\approx 0$  Hz (inhibitory rate  $\approx 105$  Hz) and accuracy falls to chance. Right: cycle-coherent jitter displaces whole bursts while preserving within-burst synchrony; the excitatory rate rises from  $\approx 17$  to  $\approx 73$  Hz (inhibitory rate  $\approx 103$  Hz, matched to the left arm) and accuracy holds high. Both arms are read where the realised inhibitory rate is matched to within a few percent; at larger  $\sigma$  the cycle-coherent excitatory rate climbs further, but the finite trial window truncates the most-displaced bursts and realised inhibition falls, so the strict comparison is anchored here. Identical mean inhibition, opposite excitatory outcome: the gate is the phase structure of inhibition, not its level. Source: exp042.

The post-training firing rate is also approximately invariant under change of integration timestep: across  $\Delta t \in [0.05, 1.0]$  ms (a  $20 \times$  range), the trained excitatory rate stays in 13.6–20.2 Hz and accuracy varies by less than 2.2 pp (Figure 10). The rate is therefore a property of the continuous dynamics, not an artefact of the discretisation.




Figure 10: **The firing-rate reduction is a physical-time property, invariant to the integration timestep over a twentyfold range.** The network was trained and evaluated at matched integration timestep  $\Delta t$  for each value across  $[0.05, 1.0]$  ms (logarithmic abscissa). Left ordinate (black diamonds): post-training mean excitatory rate, confined to a 13.6–20.2 Hz band and non-monotonic in  $\Delta t$ , so finer stepping does not buy a lower rate. Right ordinate (red squares): test accuracy, flat within 2.2 pp (88.2–90.4%). Because both training and inference use the same  $\Delta t$  at each point, the figure tests invariance of the training-plus-inference pipeline, not the generalisation of one trained network to a varied inference step. Source: exp044.


## 2.7 Streaming classification on continuous input

The preceding subsections evaluate the network on isolated single-digit presentations. The streaming protocol tests whether the firing-rate reduction is preserved under continuous input.

A PING network trained on single-digit MNIST classifies a continuously concatenated input stream without retraining and without a segmentation cue. The streaming protocol (§5.7) uses a time-averaged non-spiking LIF readout over a sliding window whose duration is matched exactly to each segment’s presentation duration. On a representative stream of five digits, each with its own duration (25–200 ms) and input rate (10–200 Hz), 3 of 5 are classified correctly (Figure 11). Across the  $(\tau, \text{input-rate})$  grid, accuracy is approximately a function of the product  $\tau \cdot \text{rate}$ . Accuracy does not exceed  $\approx 80\%$  for  $\tau \leq 15$  ms regardless of input rate (Figure 12A). For reference, 15 ms is approximately 0.7 times the canonical gamma period  $T_\gamma \approx 21$  ms. Accuracy saturates by  $\tau \approx 40$ –50 ms, and the trained operating point ( $\tau = 200$  ms, rate = 25 Hz) reaches 93% accuracy. Extending the 200 ms slice below the grid’s 5 Hz minimum locates a separate encoder floor: performance remains at chance through 0.5 Hz, becomes clearly informative by 2 Hz, and reaches 79.1% at 5 Hz (Figure



12B). The failed 200 ms, 10 Hz segment in Figure 11 occurs at a population-level accuracy of 87.3%, so it is a natural weak-evidence classification error rather than evidence that the encoding rate is intrinsically nonviable. Together the panels establish requirements for sufficient integration time and sufficient encoded input evidence; because gamma frequency is not independently varied, they do not identify the gamma cycle as the cause or temporal unit of either requirement.



exp048-replot

Figure 11: **A PING network trained on isolated digits classifies a continuous, unsegmented stream whose presentation timing varies from segment to segment.** A single input stream concatenates five MNIST digits, each with its own presentation duration (25–200 ms) and Poisson input rate (10–200 Hz); the network is given no segmentation cue and is not retrained. Top: the five digit thumbnails with their per-segment (duration, rate) and predicted labels; thumbnail opacity indicates input rate. Below: hidden excitatory and inhibitory rasters, showing gamma cycles maintained throughout (sparser under weak drive, denser under strong drive) and the sliding leaky-integrator readout traces. 3 of 5 digits are classified correctly; the two errors occur in the weakest-drive segments and are interpreted against the population curve in Figure 12B. Source: exp048.




Figure 12: **Streaming accuracy has distinct integration-time and encoding-rate evidence floors.** (A) Per-segment accuracy across presentation duration  $\tau$  and input rate, averaged over three seeds and 1,200 segments per grid cell. For  $\tau \leq 15$  ms, accuracy does not exceed  $\approx 80\%$  at any input rate; above that floor, diagonal iso-accuracy contours show an approximate dependence on  $\tau \cdot \text{rate}$ . The trained operating point ( $\tau = 200$  ms, 25 Hz) reaches 93%. (B) Probability of a correct classification versus encoding rate with both presentation duration and readout window fixed at 200 ms. All points belong to the same psychometric curve. Performance remains at chance through 0.5 Hz, is clearly informative by 2 Hz, and reaches 79.1% at 5 Hz; the dotted line marks the 25 Hz training rate. Thus the Figure 11 error at 200 ms and 10 Hz occurs in a condition with 87.3% population accuracy, above the nonviable encoder regime. For scale,  $\tau = 15$  ms is approximately 0.7 times the canonical gamma period  $T_\gamma \approx 21$  ms, but gamma frequency is not manipulated independently. Source: exp048.

### 3. Discussion

A recurrent  $E \leftrightarrow I$  loop, held fixed during training, generates a gamma rhythm and reduces the post-training excitatory firing rate by approximately an order of magnitude relative to the COBA baseline at matched accuracy (§2.3). The reduction does not require gradient-based learning of the loop weights: activating the loop at inference on a trained COBA network reduces the firing rate without retraining (§2.4), and gradient descent does not preserve the loop within a single epoch when its weights are released (§2.4, conditional on the §5.4 damping scheme). The inductive bias is paid for at design time, via the canonical biophysical loop weights [7], not during training. Within the mean-field reduction, the gamma onset is a supercritical Hopf bifurcation (§2.2), and the empirical data support this classification. Its continuous, reversible character fits the inference-time loop activation of §2.4, which produces a graded change in firing rate without hysteresis; a direct test would require an inference-time hysteresis sweep on the  $E \rightarrow I$  gain (§4).

The mechanism of the gate is the temporal structure of inhibition, not its mean level. The jitter perturbation experiment (Figure 9) is a direct test: holding the mean per-cell inhibitory rate fixed and varying its temporal structure produces opposite effects on the excitatory rate depending on whether within-burst synchrony is preserved, consistent with prior

characterisations of temporal-synchrony patterns within PING circuits [32]. The robustness asymmetry under spike addition versus deletion (Figure 8) follows from this dependence on phase: removal of spikes does not alter the phase structure of the population output, while addition of off-phase spikes does. The asymmetry constitutes a testable prediction for biological gamma circuits and would speak to long-standing rate-vs-timing debates [33, 34]. It echoes prior reports that oscillations sharpen spike-timing precision [31].

Across the  $\tau_{\text{GABA}}$  sweep, post-training rate covaries with the realised gamma frequency, and the majority of (cell, cycle) pairs contain at most one spike (Figures 6–7). This is consistent with cycle-structured rate control, but  $\tau_{\text{GABA}}$  simultaneously changes inhibitory decay, integrated conductance, and burst duty cycle; the experiment does not isolate frequency as the sole cause of the rate change. An independent manipulation of oscillation frequency at matched inhibitory influence would be needed for that attribution. The streaming experiment (Figure 12) instead separates two evidence bounds: panel A shows low accuracy at short presentation durations and an approximate dependence on  $\tau \cdot \text{rate}$ , whereas panel B locates the 200 ms encoder floor below 0.5 Hz. Errors above that floor are ordinary trial-level failures under weak evidence, not evidence that the rate is categorically unusable. The numerical proximity of the short-duration floor to the canonical gamma period is descriptive, not mechanistic, because gamma frequency is not independently varied. A gamma-frequency sweep or a cycle-aligned analysis showing discontinuities at integer multiples of  $T_\gamma$  would be required to test whether gamma defines a temporal unit for classification.

PING is a structured alternative to the asynchronous balanced state [36, 37]. The architectural treatment of the loop adopted here differs from the inhibitory-plasticity literature, in which the inhibitory connectivity is plastic and learns E/I balance [38, 39, 40, 41]. The §2.4 result, that gradient descent does not preserve the loop from any tested initial condition (under the §5.4 damping regime), provides empirical support for the architectural treatment in this setting. We propose a functional interpretation: gamma may act as a structural constraint on excitatory firing rates without requiring learned tuning of the inhibitory connectivity.

Relative to the two closest recent trainable-SNN precedents in the bibliography, the present work differs in how the rhythm is obtained rather than in claiming better performance. [25] imposes the oscillation as an external input to spiking neurons; [26] trains an adaptive-LIF network on speech, all parameters free, and reports that oscillatory synchronisation and cross-frequency coupling *emerge* from end-to-end optimisation, correlating with task performance. The §2.4 result that gradient descent does not preserve the loop is therefore not a claim that surrogate-gradient training cannot discover rhythm in general ([26] shows it can) but a narrower one: it does not maintain a *fixed, biophysically-calibrated PING loop* whose weights are released under the Dale’s-law clamp and the damping regime of §5.4. The two findings are complementary poles of the same question: rhythm acquired by training versus rhythm supplied by architecture. Neither [25] nor [26] uses a conductance-based  $E \leftrightarrow I$  loop, and neither attributes a firing-rate reduction to the rhythm via inference-time activation, frequency tuning, or jitter perturbation as §2.4–§2.6 do; their firing rates are roughly an order of magnitude higher than the rates reported here, and neither frames a per-spike economy. We do not provide a head-to-head numerical comparison: [25] and [26]

evaluate on temporally structured tasks (SHD; speech perception) where the present static-MNIST protocol is not directly comparable. The contribution is mechanistic, not benchmark-driven.

The reduction reported in §2.3 should be considered net of the inhibitory contribution. PING uses a smaller, higher-rate inhibitory population, so the reduction in total spike count ( $N_E \langle r_E \rangle + N_I \langle r_I \rangle$ ) is approximately a factor of 3 rather than a factor of 7. Excitatory glutamatergic signalling accounts for a larger share of the cortical energy budget than inhibitory transmission [28, 29] weighting spikes by metabolic cost recovers the order-of-magnitude figure. The argument is complicated by the substantial per-cell metabolic demands of fast-spiking interneurons, which sustain high firing rates and dense synaptic activity [42] for this reason we treat the uniform-spike-counting reduction (approximately 3-fold) as the more conservative claim. We do not attempt a quantitative metabolic comparison with cortex, given the architectural differences (no  $W_{ee}$  or  $W_{ii}$ , idealised synapse counts).

Several limitations apply. The evaluation uses a single dataset (MNIST), a single readout, and a fixed loop topology. MNIST is a simple, near-saturated benchmark on which many architectures reach comparable accuracy, so the classification results here should be read as evidence that the firing-rate reduction survives training to competence, not as a claim about task difficulty or about generalisation to harder problems; whether the mechanism holds on datasets with intrinsic temporal structure is left to future work (SHD, §4). The rhythmicity metric  $R$  is one of several available options. The mean-field reduction inherits biophysical cellular and synaptic parameters but contains a free effective-noise scale and remains a reduction of the full network. The architecture excludes  $W_{ee}$  and  $W_{ii}$ , conduction delays, and cell-type heterogeneity; the implications for cortical microcircuits with richer connectivity are open [15]. The streaming evaluation does not include temporally structured inputs in which classification depends on input timing. The capacity of a single gamma cycle and its scaling with assembly size are not characterised here [43]. Classification accuracy on MNIST is approximately 83–90%; the contribution of the present work concerns the mechanism by which the firing rate is reduced rather than the absolute accuracy. The §2.4 released-loop result depends on the gradient-damping scheme ( $d = 1000$ , §5.4) and the Dale clamp; whether the loop’s collapse persists under weaker damping is not addressed here. The paper does not benchmark against rhythmic-SNN baselines [25, 26] the PING-specific attribution rests on the within-architecture experiments of §2.4–§2.6 rather than on an external rhythmic-SNN comparison.

## 4. Conclusion and Future Directions

A recurrent  $E \leftrightarrow I$  loop held fixed during training reduces the post-training excitatory firing rate by approximately an order of magnitude relative to the COBA baseline at matched accuracy, and approximately 3-fold by total spike count when the higher-rate inhibitory pool is included (§3 para 5). The reduction is invariant to the integration timestep across a  $20 \times$  range (Figure 10, retrained at each  $\Delta t$ ) and is preserved under evaluation on continuously concatenated input streams (Figures 11–12).

Empirical extensions include evaluation on the SHD dataset [44], which tests the gating on a spiking benchmark with intrinsic temporal structure, and tasks in which classification accuracy depends on input timing, which could test whether the gamma cycle acts as a

temporal unit. This is the regime in which the emergent-oscillation route of [26] operates; a direct comparison there would set the imposed, biophysically-calibrated PING loop studied here against a network free to learn its own rhythmic structure, on the same temporally structured task. A more comprehensive characterisation of the  $W^{EI} \times W^{IE}$  plane would test the supercritical Hopf classification directly.

Theoretical extensions include multi-layer PING architectures, an independent two-dimensional sweep of the two loop-weight gains  $\alpha_{EI} \times \alpha_{IE}$ , multi-rhythm and theta-nested gamma models [19, 20], and characterisation of capacity limits for single cycles and minimal assemblies [43]. A constrained-training scheme, in which the loop weights are regularised toward biophysical values rather than held fixed, would connect the present result to the inhibitory-plasticity literature [38]. The rate law of §2.5 admits a testable biological prediction: perturbing the timing of inhibitory neurons in vivo (e.g. by optogenetic stimulation, as in [8, 9, 10]) should change the excitatory firing rate without altering the mean inhibitory rate, the in vivo analogue of Figure 9.

Gamma may act as a structural mechanism by which the cortical microcircuit maintains sparse excitatory firing rates at low metabolic cost. The present work provides one architecture in which this mechanism is realised explicitly.

## 5. Methods

### 5.1 Single-neuron and synapse dynamics

The model uses a conductance-based leaky integrate-and-fire (LIF) representation with two populations, excitatory (E) and inhibitory (I). The sub-threshold membrane potential of each population evolves as

$$\begin{aligned} C_m^E \frac{dV^E}{dt} &= -g_L^E(V^E - E_L) - g_e^E(V^E - E_e) - g_i^E(V^E - E_i) \\ C_m^I \frac{dV^I}{dt} &= -g_L^I(V^I - E_L) - g_e^I(V^I - E_e) \end{aligned}$$

where  $C_m$  is the membrane capacitance,  $g_L$  the leak conductance,  $E_L$  the leak reversal potential, and  $E_e$ ,  $E_i$  the excitatory and inhibitory synaptic reversal potentials. The I population has no inhibitory term because there is no I→I connection in this architecture (§5.2).

A neuron emits a spike when  $V$  crosses threshold  $V_{th}$  from below; the membrane potential is then reset to  $V_{reset}$  for a refractory period  $\tau_{ref}$ :

$$s_{t+1} = \mathbf{1}[V \geq V_{th}], \quad V \leftarrow V_{reset} \text{ if } s_{t+1} = 1 \text{ or refractory.}$$

Each synaptic conductance is an exponential trace driven by presynaptic spikes; a presynaptic spike adds its full weight  $W$  as an instantaneous jump in conductance, which then decays with the relevant channel time constant ( $\tau_{AMPA}$  for AMPA-like excitation,  $\tau_{GABA}$  for GABA-like inhibition):

$$\begin{aligned}\frac{dg_e^E}{dt} &= -\frac{g_e^E}{\tau_{\text{AMPA}}} + W_{\text{in}} \sum_k \delta(t - t_k^{\text{inp}}) \\ \frac{dg_i^E}{dt} &= -\frac{g_i^E}{\tau_{\text{GABA}}} + W^{IE} \sum_k \delta(t - t_k^i) \\ \frac{dg_e^I}{dt} &= -\frac{g_e^I}{\tau_{\text{AMPA}}} + W^{EI} \sum_k \delta(t - t_k^e)\end{aligned}$$

The first equation describes input-driven excitation onto E via feedforward weights  $W_{\text{in}}$ ; the second is inhibition onto E from I via  $W^{IE}$ ; the third is excitation onto I from E via  $W^{EI}$ . There is no equation for  $g_i^I$  (no I→I connection) and no recurrent contribution to  $g_e^E$  (no E→E connection). Canonical parameter values are listed in the parameters table; the E and I populations differ in membrane capacitance, leak conductance, membrane time constant, and refractory period.

Canonical parameter values for the spiking network are given below. Where E and I populations use different values they are listed as “E / I”; otherwise the value is shared. The  $\tau_{\text{GABA}} = 9$  ms value is the canonical PING value of [7].

| Symbol               | Description                 | Value                                |
|----------------------|-----------------------------|--------------------------------------|
| $C_m$                | Membrane capacitance        | 1.0 / 0.5 nF                         |
| $g_L$                | Leak conductance            | 0.05 / 0.1 $\mu\text{S}$             |
| $\tau_{\text{ref}}$  | Refractory period           | 3.0 / 1.5 ms                         |
| $E_L$                | Leak reversal potential     | −65 mV                               |
| $V_{\text{th}}$      | Spike threshold             | −50 mV                               |
| $V_{\text{reset}}$   | Reset potential             | −65 mV                               |
| $E_e$                | AMPA reversal potential     | 0 mV                                 |
| $E_i$                | GABA reversal potential     | −80 mV                               |
| $\tau_{\text{AMPA}}$ | AMPA decay time constant    | 2 ms                                 |
| $\tau_{\text{GABA}}$ | GABA decay time constant    | 9 ms                                 |
| $\Delta t$           | Integration timestep        | 0.1 ms (train) / 0.25 ms (inference) |
| $N_E$                | Hidden excitatory pool size | 1024                                 |
| $N_I$                | Inhibitory pool size        | 256                                  |

## 5.2 Network architecture

The network has one hidden layer with  $N_E$  excitatory and  $N_I$  inhibitory units, and a non-spiking leaky-integrator readout layer with weights  $W_{\text{out}}$  over the excitatory population. The readout units follow LIF membrane dynamics with no spike, reset, or refractory period; per-class logits are computed as the membrane potentials averaged over the presentation window. Input spikes drive the excitatory population via feedforward weights  $W_{\text{in}}$ . Recurrence is restricted to the E↔I loop: E projects to I via  $W^{EI}$ , and I projects back to E via  $W^{IE}$ . There is no  $W_{ee}$  and no  $W_{ii}$ .

The restriction to the E↔I loop is intended to make the rhythm unambiguously PING: excluding  $W_{ii}$  rules out ING, and excluding  $W_{ee}$  rules out recurrent-E driven oscillation [7,

**45]** The conductance-based (COBA) baseline used as a non-PING control is the loop-off limit of the same architecture, obtained by setting  $W^{EI} = W^{IE} = 0$ .

The loop weights  $W^{EI}$  and  $W^{IE}$  are held fixed (untrained) in the experiments reported in §2.3 and §2.5–§2.7. The loop is treated as a structural prior, consistent with the inhibitory-plasticity literature, in which inhibitory synapses serve an experience-dependent E/I balance role rather than carrying the feedforward computational features that the excitatory pathway acquires [38, 39]. The choice is also supported empirically by the result in §2.4 (Figures 4–5) that gradient descent does not preserve effective E→I recruitment when the recurrent conductances are released. A Dale’s-law clamp constrains all trained conductance magnitudes to remain non-negative throughout training (§5.4).

### 5.3 Mean-field reduction

To locate the gamma-onset bifurcation analytically (§2.2), the spiking network is reduced to a four-dimensional rate model in the state

$$\mathbf{x}(t) = (\bar{E}, \bar{I}, \bar{g}_e^I, \bar{g}_i^E),$$

where  $\bar{E}$  and  $\bar{I}$  are the population-mean firing rates of the E and I cells (in spikes per millisecond), and  $\bar{g}_e^I, \bar{g}_i^E$  are the population-mean cross-population synaptic conductances onto the I and E populations. The two cross-population conductances are sufficient because the architecture has no  $W_{ee}$  and no  $W_{ii}$  (§5.2); the within-population conductances vanish identically.

The reduction replaces the spike-driven conductance dynamics with rate-driven first-order filters, and replaces each cell’s stochastic spike output with the population-averaged firing rate of a noise-driven LIF cell at a given mean input current. The closed 4D system is

$$\begin{aligned}\tau_E \dot{\bar{E}} &= -\bar{E} + \Phi_E(I_{\text{ext}} - \bar{g}_i^E \Delta V_{\text{inh}}) \\ \tau_I \dot{\bar{I}} &= -\bar{I} + \Phi_I(\bar{g}_e^I \Delta V_{\text{exc}}) \\ \tau_{\text{AMPA}} \dot{\bar{g}}_e^I &= -\bar{g}_e^I + \tau_{\text{AMPA}} W^{EI} \bar{E} \\ \tau_{\text{GABA}} \dot{\bar{g}}_i^E &= -\bar{g}_i^E + \tau_{\text{GABA}} W^{IE} \bar{I}\end{aligned}$$

where  $I_{\text{ext}}$  is an external tonic drive to E (the bifurcation control parameter, below), and the driving forces are  $\Delta V_{\text{exc}} = E_e - E_L = 65$  mV and  $\Delta V_{\text{inh}} = E_L - E_i = 15$  mV evaluated at rest. The membrane time constants are the passive ratios  $\tau_E = C_m^E / g_L^E = 20$  ms and  $\tau_I = C_m^I / g_L^I = 5$  ms, computed from the capacitances and leak conductances in the §5.1 parameters table; the synaptic time constants  $\tau_{\text{AMPA}}, \tau_{\text{GABA}}$  are taken directly from that table. The fan-in-normalised coupling strengths are  $W^{EI} = 1.0$   $\mu\text{S}$  and  $W^{IE} = 2.0$   $\mu\text{S}$ , inherited from the spiking network.

The population gain functions  $\Phi_E$  and  $\Phi_I$  are the noise-driven LIF rate functions in Ricciardi–Siegert form [46]. For mean input current  $\mu$  delivered to a cell with leak conductance  $g_L$ , leak reversal  $E_L$ , threshold  $V_{\text{th}}$ , reset  $V_{\text{reset}}$ , membrane time constant  $\tau_m$ , and refractory period  $\tau_{\text{ref}}$ ,

$$\Phi(\mu) = \left[ \tau_{\text{ref}} + \tau_m \sqrt{\pi} \int_{(V_{\text{reset}} - \mu_V)/\sigma_V}^{(V_{\text{th}} - \mu_V)/\sigma_V} e^{u^2} (1 + \operatorname{erf} u) du \right]^{-1},$$

with mean membrane potential  $\mu_V = E_L + \mu/g_L$  and effective membrane-noise scale  $\sigma_V$ . The integral is evaluated by numerical quadrature. Cellular and synaptic parameters are inherited from the §5.1 model (with  $\tau_m = C_m/g_L$ ) separately for the E and I populations. The effective noise scale is not derived from the spiking model and is treated as a free sensitivity parameter; 4 mV is the reference value. Across  $\sigma_V \in \{3, 4, 5, 6\}$  mV, the Hopf and its supercritical classification persist and the crossing frequency remains stable, while the threshold, fixed point, and relative-onset amplitude vary quantitatively.

The silent (non-oscillating) fixed point is tracked as  $I_{\text{ext}}$  is swept from 0 to 4 nA in 10  $\mu$ A steps. At each  $I_{\text{ext}}$ , the fixed point is obtained by solving the algebraic system in  $(\bar{E}, \bar{I})$  (at steady state the two conductances are determined by the rates,  $\bar{g}_e^I = \tau_{\text{AMPA}} W^{EI} \bar{E}$  and  $\bar{g}_i^E = \tau_{\text{GABA}} W^{IE} \bar{I}$ ) using *scipy.optimize.fsolve*. The numerical Jacobian of the full 4D system at each fixed point is computed by central finite differences. The Hopf threshold  $I_{\text{ext}}^*$  is the smallest  $I_{\text{ext}}$  at which the eigenvalue  $\lambda^*$  with largest real part crosses zero with non-zero imaginary part; the crossing frequency is  $f^* = |\operatorname{Im} \lambda^*| / (2\pi)$ .

The onset is classified numerically by a quasi-static amplitude sweep.  $I_{\text{ext}}$  is ramped up across  $I_{\text{ext}}^*$  from a small perturbation of the silent fixed point and then ramped down; at each step the 4D system is integrated to its steady-state oscillation amplitude  $A$ . The onset is classified as supercritical when (i) the up- and down-ramp branches coincide within a peak hysteresis of  $10^{-4}$  in rate units, and (ii) the squared amplitude scales linearly with the bifurcation distance,

$$A^2 \propto (I_{\text{ext}} - I_{\text{ext}}^*),$$

with  $R^2 > 0.9$ . For the canonical parameter set the criterion is met with hysteresis below  $10^{-5}$  and  $R^2 = 0.999$ .

The mean-field prediction is compared with the gamma frequency measured in the spiking network, extracted as in §5.5, across a sweep of  $\tau_{\text{GABA}} \in \{4.5, 6, 9, 12, 18, 27\}$  ms (Figure 2). Both curves decrease monotonically with  $\tau_{\text{GABA}}$ ; the spiking measurement is consistently higher than the rate-equation prediction across the sweep. The reduction captures the qualitative dependence on the GABA decay time, which is the use to which it is put. The treatment follows the Wilson–Cowan tradition for cortical-rhythm modelling [18] and the broader population-dynamics and next-generation neural-mass literature [19, 47, 48].

## 5.4 Training

The network is trained on MNIST by surrogate-gradient descent through backpropagation in time [22, 23]. Each digit is rate-encoded as a Poisson spike train over a 200 ms presentation window at a peak rate of 25 Hz per active pixel (Bernoulli per timestep with  $p = r_{\text{max}} \Delta t$ ). The loss is cross-entropy on the time-averaged membrane potentials of the non-spiking LIF readout, with a sample-wise population-rate penalty active when hidden-E activity exceeds a soft ceiling  $r_{\text{ceil}}$ :



$$r_b = \frac{1}{N_E T} \sum_{i \in E} z_{bi}, \quad \mathcal{L} = \mathcal{L}_{\text{CE}} + \frac{s_u}{B} \sum_b \text{ReLU}(r_b - r_{\text{ceil}})^2,$$

where  $z_{bi}$  is the spike count of hidden-E neuron  $i$  during presentation  $b$ . The rate is normalised by population width and physical duration before the one-sided quadratic is applied to each presentation; the result is then averaged across the minibatch. Sweeping  $r_{\text{ceil}}$  over {off, 25, 10, 5, 2.5, 1} Hz generates the accuracy–rate frontier reported in §2.3.

The discrete spike nonlinearity has zero gradient almost everywhere; in the backward pass it is replaced by a fast-sigmoid surrogate of the distance to threshold  $u = V - V_{\text{th}}$ ,

$$\frac{\partial \mathbf{1}[V \geq V_{\text{th}}]}{\partial V} \equiv \frac{s}{(1 + s |u|)^2},$$

with slope  $s = 1$  [23, 49]. The forward pass evaluates the Heaviside exactly. Optimisation uses Adam [50] with learning rate  $4 \times 10^{-4}$ , batch size 256, and 50 epochs. Every activity-ceiling condition is repeated across three independent seeds (42, 43, 44); frontier points are their means and uncertainty bars show the standard error across seeds.

**Gradient damping for the PING configuration.** Surrogate-gradient training of the PING configuration is unstable without intervention on the gradient. A single loop weight ( $W^{EI}$  or  $W^{IE}$ ) contributes to the membrane-voltage update of every cell at every subsequent timestep within a trial; combined with the spike-driven impulse updates of the synaptic conductances and the non-zero surrogate gradient at the spike threshold, the gradient propagates through a tightly coupled feedback loop with millisecond-scale conductance dynamics. Over the 2,000-step backpropagation-through-time window of a single 200 ms trial at  $\Delta t = 0.1$  ms, multiplicative contributions across timesteps cause gradient norms to grow by many orders of magnitude, and training does not converge. The mechanism is the same multiplicative compounding through long unrolled recurrences that characterises the exploding-gradient pathology in standard recurrent networks [51].

We address this by attenuating the gradient flowing through the membrane-voltage increment  $dV$  on the backward pass by a factor of  $1/d$ , implemented as a straight-through identity that scales the gradient without modifying the forward value:

$$\text{damp}_d(x) = \frac{1}{d}x + \left(1 - \frac{1}{d}\right) \text{stopgrad}(x).$$

The operator is applied to  $dV$  at every integration step in every layer; the forward simulation is exact (the network still solves the same ODE), and the gradient flowing through that update is attenuated by a factor of  $1/d$  per step, eliminating the multiplicative compounding. All experiments reported here use  $d = 1000$ , applied identically to the PING and COBA training pipelines. The COBA configuration is trainable at the module default  $d = 80$ ; the PING configuration is not.

**Dale’s-law clamp.** The synaptic matrices store conductance magnitudes, not signed currents. After each optimiser step,  $W_{\text{in}}$ ,  $W^{EI}$ , and  $W^{IE}$  are therefore projected onto the non-negative cone [52, 53]. Excitatory or inhibitory action is set by the pathway-specific reversal potential in the membrane current: the I→E term  $g_I(E_I - V)$  is hyperpolarising for the GABA reversal potential  $E_I = -80$  mV. The projection permits either recurrent conductance

to grow while preventing an unphysical negative conductance. The §2.4 collapse primarily reflects weakened or absent E→I recruitment and loss of inhibitory firing, not  $W^{IE}$  crossing into a negative sign.

### 5.5 Measurement and analysis

Mean firing rates  $\langle r_E \rangle$  and  $\langle r_I \rangle$  are computed as time-averaged spike counts per neuron over the presentation window. The gamma frequency  $f_\gamma$  is extracted as the peak of the Welch power spectral density [54] of the summed population E spike train at sampling rate  $f_s = 1/\Delta t = 4000$  Hz, using a single segment of length equal to the trial, mean-centred (not z-scored) signal, no detrending, and a peak search restricted to the gamma band [5, 150] Hz; the peak frequency is refined by parabolic sub-bin interpolation.

The rhythmicity score  $R$  is the Michelson contrast between the first side lobe and the first trough of the autocorrelation of the binned population E spike count, computed via zero-padded FFT and normalised by the squared mean of the rate. After a 3-point smoothing kernel [0.25, 0.5, 0.25] is applied to the autocorrelogram, the first trough is identified as the first local minimum starting from lag 2, and the lobe as the maximum between lag 1 and the trough; then

$$R = \frac{\text{lobe} - \text{trough}}{\text{lobe} + \text{trough}} \in [0, 1).$$

$R$  is bounded and dimensionless. We use it in preference to spectral-peak measures because the latter become unreliable at the low firing rates encountered in some of the regimes of interest.  $R$  is qualitatively consistent with the spectral-peak and population-coherence measures used elsewhere in the gamma literature [55, 56].

The spikes-per-cycle distribution (Figure 7) is constructed by binning each cell’s spikes into gamma cycles inferred from peaks of the population I-burst rate (Gaussian-smoothed with  $\sigma = 1$  ms), detected with *scipy.signal.find\_peaks* using a minimum inter-peak separation of half the expected gamma period and a height threshold of 5% of the maximum. Cycle boundaries are placed at midpoints between consecutive I-burst peaks; each E spike is assigned to its enclosing cycle.

Spike-economy claims report both the mean E rate and the total population spike count  $N_E \langle r_E \rangle + N_I \langle r_I \rangle$ , so the reduction is stated net of the inhibitory contribution. The metabolic argument that excitatory spikes incur larger costs than inhibitory spikes [28, 29] is invoked where relevant but is not modelled quantitatively.

### 5.6 Integration and parameters

The membrane and synaptic-conductance ODEs are integrated by an exponential-Euler scheme [57] with zero-order hold on the synaptic conductances over each step. With  $g_{\text{tot}} = g_L + g_e + g_i$  the total instantaneous conductance, effective time constant  $\tau_{\text{eff}} = C_m/g_{\text{tot}}$ , and instantaneous steady state  $V_\infty = (g_L E_L + g_e E_e + g_i E_i)/g_{\text{tot}}$ , the closed-form update is

$$V_{t+1} = V_\infty + (V_t - V_\infty)e^{-\Delta t/\tau_{\text{eff}}}.$$

Training uses  $\Delta t = 0.1$  ms; smaller timesteps are required for numerical stability of the backpropagation through the recurrent E↔I dynamics. Inference uses  $\Delta t = 0.25$  ms. Firing rates and frequencies are reported in Hz. The §2.6 result (Figure 10) is obtained by retraining

the network at each  $\Delta t$  value in the swept range, and confirms invariance of training+inference at matched  $\Delta t$  within the range tested (not invariance of inference at a fixed- $\Delta t$ -trained network to a varied inference  $\Delta t$ ).

Default parameters used by all experiments are listed in the parameters table. Per-experiment values of the loop weights  $W^{EI}$ ,  $W^{IE}$  and the input rate, and ranges swept by experiment (e.g.  $\tau_{\text{GABA}}$ ,  $W^{IE}$ ), are stated in the corresponding figure captions.

### 5.7 Datasets and evaluation

The classification task is MNIST [58], rate-encoded as in §5.4 (200 ms presentation, 25 Hz peak Poisson rate per active pixel). The official 60,000-image training partition supplies optimizer-training and fixed stratified validation subsets; the official 10,000-image test partition remains sealed until evaluation of the selected checkpoint. For the streaming protocol used in §2.7, the trained network is presented with a continuously concatenated input stream. Ten spiking output LIF neurons accumulate class evidence; the total output spikes within each presentation are the dimensionless class logits, and their argmax gives the streaming label. For every segment, the readout window is matched exactly to the presentation duration,  $T_{\text{readout}} = T_{\text{presentation}} = \tau$ ; it is not varied independently. Output firing rates may be reported by dividing these counts by  $\tau$ , but rates are not used as cross-entropy logits. The duration–rate grid uses  $\tau \in \{10, 15, 25, 40, 50, 75, 100, 200\}$  ms and rates in  $\{5, 10, 25, 50, 100, 200\}$  Hz. Additional evaluations hold both durations fixed at 200 ms while sweeping below 5 Hz to locate the encoder’s chance floor, using the same three trained seeds. Reported metrics are official-test accuracy, mean E and I firing rates, and  $f_\gamma$ .

Training emits both a validation-selected checkpoint and a final-epoch checkpoint.

**Deployment-performance** analyses, including classifier robustness and streaming evaluation, use the validation-selected checkpoint. **Endpoint-dynamics** analyses of firing rates, gamma dynamics, integration timestep, recurrent weights, and training destinations use the final-epoch checkpoint. Every derived result records the analysis purpose, checkpoint role, resolved epoch, filename, and SHA-256 digest.

### 5.8 Reproducibility

Each reported result is produced by a standalone experiment script in the project repository (linked under §6). Each experiment hardcodes its own run scale (the sample count, seed set, and any parameter sweeps) and records those settings, together with the git commit and a run identifier, in the run’s provenance file; every run number quoted in this manuscript and its captions is interpolated from those files rather than typed by hand, so a figure and the text that describes it cannot drift apart. The figure-render pipeline regenerates every print-quality figure from the experiments, so a clean re-run of the repository reproduces the figures and numbers reported here.

### 5.9 Software and implementation

The model, training, and analysis are implemented in Python ( $\geq 3.10$ ). Spiking dynamics and surrogate-gradient training use PyTorch (2.11; with snnTorch 0.9 for baseline spiking primitives). Numerical analysis uses NumPy (2.2) and SciPy (1.15). All figures are produced with Matplotlib (3.10).

## 6. Code and data availability

Source code, per-notebook reproduction scripts, trained-weight artefacts, and the figure-render pipeline are available at <https://github.com/eoinmurray/pinglab>. MNIST is obtained from its standard public distributor. Library versions are listed in §5.9.

## 7. Declaration of generative-AI use

Claude Code (Anthropic; model Opus 4.8), an agentic large-language-model coding tool, was used extensively and interactively in the development of this work. Its use covers writing the simulation, training, analysis, and figure-rendering code in the project repository; debugging, refactoring, and code review; drafting, revising, and copy-editing the manuscript prose; and iteration on experimental design and presentation. No figure, illustration, table, or visualisation in this manuscript is produced by a generative AI model; all figures are rendered by Matplotlib from Python code in the project repository. The authors set the research questions, designed the experiments and analyses, ran the simulations, reviewed model-generated code prior to commit, and verified the reported results and the manuscript text. The authors are responsible for the content, accuracy, and claims of this work.

## References

1. Buzsáki & Wang — *Mechanisms of Gamma Oscillations*. 2012. doi:10.1146/annurev-neuro-062111-150444
2. Fries — *Rhythms for Cognition: Communication through Coherence*. 2015. doi:10.1016/j.neuron.2015.09.034
3. Fries, Reynolds, Rorie & Desimone — *Modulation of Oscillatory Neuronal Synchronization by Selective Visual Attention*. 2001. doi:10.1126/science.1055465
4. Gray, König, Engel & Singer — *Oscillatory Responses in Cat Visual Cortex Exhibit Inter-Columnar Synchronization Which Reflects Global Stimulus Properties*. 1989. doi:10.1038/338334a0
5. Whittington, Traub, Kopell, Ermentrout & Buhl — *Inhibition-Based Rhythms: Experimental and Mathematical Observations on Network Dynamics*. 2000. doi:10.1016/S0167-8760(00)00173-2
6. Williams et al. — *Fast Spiking Interneurons Autonomously Generate Fast Gamma Oscillations in the Medial Entorhinal Cortex with Excitation Strength Tuning ING-PING Transitions*. 2026. doi:10.1523/ENEURO.0452-25.2026
7. Börgers — *The PING Model of Gamma Rhythms*. 2017. doi:10.1007/978-3-319-51171-9\_30
8. Cardin, Carlén, Meletis, Knoblich, Zhang, Deisseroth, Tsai & Moore — *Driving Fast-Spiking Cells Induces Gamma Rhythm and Controls Sensory Responses*. 2009. doi:10.1038/nature08002
9. Sohal, Zhang, Yizhar & Deisseroth — *Parvalbumin Neurons and Gamma Rhythms Enhance Cortical Circuit Performance*. 2009. doi:10.1038/nature07991
10. Phensy et al. — *Prefrontal Gamma Oscillations Engage Dynamic Cell Type-Specific Configurations to Support Flexible Behavior*. 2026. doi:10.1016/j.neuron.2026.05.002
11. Offermanns, Pöppel & Hanganu-Opatz — *Developmental Embedding of Parvalbumin Interneurons Drives Local and Crosshemispheric Prefrontal Gamma Synchrony*. 2026.

12. Whittington, Traub & Jefferys — *Synchronized Oscillations in Interneuron Networks Driven by Metabotropic Glutamate Receptor Activation*. 1995. doi:10.1038/373612a0
13. Wang & Buzsáki — *Gamma Oscillation by Synaptic Inhibition in a Hippocampal Interneuron Network Model*. 1996. doi:10.1523/JNEUROSCI.16-20-06402.1996
14. Bartos, Vida & Jonas — *Synaptic Mechanisms of Synchronized Gamma Oscillations in Inhibitory Interneuron Networks*. 2007. doi:10.1038/nrn2044
15. Kopell, Börgers, Pervouchine, Malerba & Tort — *Gamma and Theta Rhythms in Biophysical Models of Hippocampal Circuits*. 2010. doi:10.1007/978-1-4419-0996-1\_15
16. Viriyopase, Memmesheimer & Gielen — *Cooperation and Competition of Gamma Oscillation Mechanisms*. 2016. doi:10.1152/jn.00493.2015
17. Brunel & Wang — *What Determines the Frequency of Fast Network Oscillations with Irregular Neural Discharges? I. Synaptic Dynamics and Excitation-Inhibition Balance*. 2003. doi:10.1152/jn.01095.2002
18. Wilson & Cowan — *Excitatory and Inhibitory Interactions in Localized Populations of Model Neurons*. 1972. doi:10.1016/S0006-3495(72)86068-5
19. Segneri, Bi, Olmi & Torcini — *Theta-Nested Gamma Oscillations in Next Generation Neural Mass Models*. 2020. doi:10.3389/fncom.2020.00047
20. Nandi, Valla & di Volo — *Bursting Gamma Oscillations in Neural Mass Models*. 2024. doi:10.3389/fncom.2024.1422159
21. Tahvili, Vinck & di Volo — *A Mean-Field Model of Neural Networks with PV and SOM Interneurons Reveals Connectivity-Based Mechanisms of Gamma Oscillations*. 2026. doi:10.1371/journal.pcbi.1014378
22. Eshraghian, Ward, Neftci, Wang, Lenz, Dwivedi, Bennamoun, Jeong & Lu — *Training Spiking Neural Networks Using Lessons From Deep Learning*. 2023. doi:10.1109/JPROC.2023.3308088
23. Neftci, Mostafa & Zenke — *Surrogate Gradient Learning in Spiking Neural Networks*. 2019. doi:10.1109/MSP.2019.2931595
24. Deckers et al. — *Advancing Spatio-Temporal Processing Through Adaptation in Spiking Neural Networks*. 2025. doi:10.1038/s41467-025-60878-z
25. Yan, Yang, Wu, Liu, Zhang, Li, Tan & Wu — *Efficient and Robust Temporal Processing with Neural Oscillations Modulated Spiking Neural Networks*. 2025. doi:10.1038/s41467-025-63771-x
26. Bittar & Garner — *Exploring Neural Oscillations During Speech Perception via Surrogate-Gradient Spiking Neural Networks*. 2024. doi:10.3389/fnins.2024.1449181
27. Barth & Poulet — *Experimental Evidence for Sparse Firing in the Neocortex*. 2012. doi:10.1016/j.tins.2012.03.008
28. Attwell & Laughlin — *An Energy Budget for Signaling in the Grey Matter of the Brain*. 2001. doi:10.1097/00004647-200110000-00001
29. Howarth, Gleeson & Attwell — *Updated Energy Budgets for Neural Computation in the Neocortex and Cerebellum*. 2012. doi:10.1038/jcbfm.2012.35
30. Ainsworth, Lee, Cunningham, Traub, Kopell & Whittington — *Rates and Rhythms: A Synergistic View of Frequency and Temporal Coding in Neuronal Networks*. 2012. doi:10.1016/j.neuron.2012.06.027

31. Schaefer, Angelo, Spors & Margrie — *Neuronal Oscillations Enhance Stimulus Discrimination by Ensuring Action Potential Precision*. 2006. doi:10.1371/journal.pbio.0040163
32. Nguyen & Rubchinsky — *Temporal Patterns of Synchrony in a Pyramidal-Interneuron Gamma (PING) Network*. 2021. doi:10.1063/5.0042451
33. Shadlen & Movshon — *Synchrony Unbound: A Critical Evaluation of the Temporal Binding Hypothesis*. 1999. doi:10.1016/S0896-6273(00)80822-3
34. London, Roth, Beeren, Häusser & Latham — *Sensitivity to Perturbations in vivo Implies High Noise and Suggests Rate Coding in Cortex*. 2010. doi:10.1038/nature09086
35. Akam & Kullmann — *Efficient “Communication through Coherence” Requires Oscillations Structured to Minimize Interference between Signals*. 2012. doi:10.1371/journal.pcbi.1002760
36. Renart, de la Rocha, Bartho, Hollender, Parga, Reyes & Harris — *The Asynchronous State in Cortical Circuits*. 2010. doi:10.1126/science.1179850
37. van Vreeswijk & Sompolinsky — *Chaos in Neuronal Networks with Balanced Excitatory and Inhibitory Activity*. 1996. doi:10.1126/science.274.5293.1724
38. Vogels, Sprekeler, Zenke, Clopath & Gerstner — *Inhibitory Plasticity Balances Excitation and Inhibition in Sensory Pathways and Memory Networks*. 2011. doi:10.1126/science.1211095
39. Hennequin, Agnes & Vogels — *Inhibitory Plasticity: Balance, Control, and Codependence*. 2017. doi:10.1146/annurev-neuro-072116-031005
40. Wu, Miehl & Gjorgjieva — *Regulation of Circuit Organization and Function Through Inhibitory Synaptic Plasticity*. 2022. doi:10.1016/j.tins.2022.10.006
41. Páscoa dos Santos & Verschure — *Excitatory-Inhibitory Homeostasis and Bifurcation Control in the Wilson-Cowan Model of Cortical Dynamics*. 2025. doi:10.1371/journal.pcbi.1012723
42. Kann — *The Interneuron Energy Hypothesis: Implications for Brain Disease*. 2016. doi:10.1177/0271678X16638956
43. Börgers, Talei Franzesi, LeBeau, Boyden & Kopell — *Minimal Size of Cell Assemblies Coordinated by Gamma Oscillations*. 2012. doi:10.1371/journal.pcbi.1002362
44. Cramer, Stradmann, Schemmel & Zenke — *The Heidelberg Spiking Data Sets for the Systematic Evaluation of Spiking Neural Networks*. 2022. doi:10.1109/TNNLS.2020.3044364
45. Tiesinga & Sejnowski — *Cortical Enlightenment: Are Attentional Gamma Oscillations Driven by ING or PING?*. 2009. doi:10.1016/j.neuron.2009.09.009
46. Brunel — *Dynamics of Sparsely Connected Networks of Excitatory and Inhibitory Spiking Neurons*. 2000. doi:10.1023/A:1008925309027
47. Gerstner — *Population Dynamics of Spiking Neurons: Fast Transients, Asynchronous States, and Locking*. 2000. doi:10.1162/089976600300015899
48. Montbrió, Pazó & Roxin — *Macroscopic Description for Networks of Spiking Neurons*. 2015. doi:10.1103/PhysRevX.5.021028
49. Zenke & Ganguli — *SuperSpike: Supervised Learning in Multilayer Spiking Neural Networks*. 2018. doi:10.1162/neco\_a\_01086
50. Kingma & Ba — *Adam: A Method for Stochastic Optimization*. 2015.

51. Pascanu, Mikolov & Bengio — *On the Difficulty of Training Recurrent Neural Networks*. 2013.
52. Cornford, Kalajdzievski, Leite, Lamarquette, Kullmann & Richards — *Learning to Live with Dale's Principle: ANNs with Separate Excitatory and Inhibitory Units*. 2021.
53. Zhu et al. — *Task Success in Trained Spiking Neural Network Models Coincides with Emergence of Cross-Stimulus-Modulated Inhibition*. 2026. doi:10.1007/s00422-025-01030-4
54. Welch — *The Use of Fast Fourier Transform for the Estimation of Power Spectra: A Method Based on Time Averaging Over Short, Modified Periodograms*. 1967. doi:10.1109/TAU.1967.1161901
55. Atallah & Scanziani — *Instantaneous Modulation of Gamma Oscillation Frequency by Balancing Excitation with Inhibition*. 2009. doi:10.1016/j.neuron.2009.04.027
56. Xing, Shen, Burns, Yeh, Shapley & Li — *Stochastic Generation of Gamma-Band Activity in Primary Visual Cortex of Awake and Anesthetized Monkeys*. 2012. doi:10.1523/JNEUROSCI.5644-11.2012
57. Rotter & Diesmann — *Exact Digital Simulation of Time-Invariant Linear Systems with Applications to Neuronal Modeling*. 1999. doi:10.1007/s004220050570
58. LeCun, Bottou, Bengio & Haffner — *Gradient-Based Learning Applied to Document Recognition*. 1998. doi:10.1109/5.726791

# The SNN tool

6 July 2026

One command-line tool, *tools/snn/tool.py*, drives every simulation, training run, and measurement in this project. Experiment runners never import the model code; they shell out to this tool, which writes data files (metrics, rasters, population traces, weight dumps) into an output directory, and then draw their own figures from those files. The tool is the engine; the plotting lives in the runners under *experiments/*.

This page is the reference for that engine. It is not a tutorial. It is the dictionary you reach for when an experiment mentions *-ei-strength 0.5* and you want to know exactly what that did.

## At a glance

- Run it with *uv run python tools/snn/tool.py* (never a bare *python*; the repo convention is *uv*).
- Three subcommands: *sim* (forward pass plus metrics), *train* (surrogate-gradient BPTT), *dump-weights* (emit weight matrices).
- Every parameter is a flag. There is no global config file; a saved run's *config.json* can be inherited with *-load-config*.
- Every run writes *config.json*, *run.sh*, *output.log*, and *run.jsonl* for reproducibility.
- The tool emits data, not figures. The runner draws the figure.

## The tool and the experiment

demolab draws a hard line between a **tool** and an **experiment**. A tool holds the reusable science and speaks only through files; an experiment (a runner in *experiments/expNNN.py*) chooses which tool commands to run, then reads their data files back and renders the figures. The runner reaches the tool by running its CLI as a subprocess, never by importing it. That firewall is what keeps *tools/snn/* generic and lets the same engine serve every writeup in the lab.

So a typical experiment does three things: it invokes *tool.py* (often many times, sweeping a parameter), it aggregates each run's config plus headline metrics into a single *numbers.json*, and it draws PNG or SVG figures from the run's data. The committed record lands in *artifacts/data/expNNN/*; the tool's own scratch output is disposable (see Artifacts).

## Quick start

Run a metrics-only forward pass of the canonical PING network:

```
uv run python tools/snn/tool.py sim --model ping --ei-strength 0.5
```

Train on MNIST for 50 epochs:

```
uv run python tools/snn/tool.py train --dataset mnist --epochs 50 --lr 0.0001
```

Evaluate a trained run on the test set, replaying it at a coarser timestep:



```
uv run python tools/snn/tool.py sim --infer \
  --load-config runs/foo/config.json \
  --load-weights runs/foo/weights.pth \
  --dt 0.5
```

Each subcommand has its own complete *-help*, and that per-subcommand help is authoritative. The top-level dispatcher’s group summary is hand-maintained and can lag the parser. When a flag here disagrees with reality, run *sim -help* and trust that.

## Commands

### sim

Run one forward pass and report firing-rate metrics. This is the cheapest mode (no training, no plots), used by the test suite, the dt-stability checks in ar003, and every experiment that needs a single inference pass over a trained or fresh network.

```
uv run python tools/snn/tool.py sim --model ping --dataset mnist --digit 3
```

On its own it prints metrics. The flags below make it load trained weights, evaluate a test set, emit extra data artifacts, or inject perturbations. There is no *-image* or *-video*: where those retired flags once produced panels and sweep MP4s, *sim* now emits raw data (via *-outputs*) that the calling runner plots, and sweep videos are assembled runner-side from many *sim* calls.

| flag                            | default | description                                                                                                                |
|---------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------|
| <i>-infer</i>                   | off     | Load trained weights and evaluate test-set accuracy; writes <i>results.json</i> (and <i>metrics.json</i> ).                |
| <i>-load-config PATH</i>        | —       | Load a saved <i>config.json</i> and inherit its model, dataset, and parameters. Explicit CLI flags override loaded values. |
| <i>-load-weights PATH</i>       | —       | Path to a <i>weights.pth</i> file for inference.                                                                           |
| <i>-max-samples INT</i>         | all     | [ <i>-infer</i> ] Cap the evaluation set to N samples.                                                                     |
| <i>-outputs OUTPUT [dots.c]</i> | —       | [ <i>-infer</i> ] Extra artifacts from the single forward pass ( <i>metrics.json</i>                                       |

|                                      |                 |                                                                                                                                                                                                                                                                                                          |
|--------------------------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                      |                 | always written):<br><i>per_cell_rates</i> (per-cell E/I Hz to <i>per_cell_rates.npz</i> ),<br><i>pop_traces</i> (per-trial population activity to <i>pop_traces.npz</i> , base signal for PSD / $f_\gamma$ ),<br><i>rasters</i> (sparse spike indices to <i>rasters.npz</i> , for cycle-level analysis). |
| <i>-tau-gaba FLOAT</i>               | inherited / 9.0 | [ <i>-infer</i> ] Override $\tau_{\text{GABA}}$ (ms) to replay a trained cell under specified inhibitory dynamics. Normally unset: <i>-load-config</i> inherits the trained value.                                                                                                                       |
| <i>-skip-load PREFIX [dots.c]</i>    | —               | [ <i>-infer</i> ] Drop <i>state_dict</i> keys with these prefixes before loading (e.g. <i>W_ei</i> . <i>W_ie</i> .) so a fresh sub-block survives. Transfer-load probes (exp038).                                                                                                                        |
| <i>-perturb-mode {drop, add}</i>     | —               | [ <i>-infer</i> ] Hidden-spike perturbation inside the forward loop: <i>drop</i> (Bernoulli mask), <i>add</i> (Poisson Hz). The exp037 drop/add asymmetry.                                                                                                                                               |
| <i>-perturb-level LEVEL [dots.c]</i> | —               | [ <i>-perturb-mode</i> ] One value: probability for <i>drop</i> , Hz for <i>add</i> .                                                                                                                                                                                                                    |
| <i>-i-override-file PATH</i>         | —               | [ <i>-infer</i> ] NPZ with a sparse per-trial I-spike stream to substitute for the inhibitory spikes each timestep. Injection dual of <i>-outputs rasters</i> (exp042).                                                                                                                                  |

|                                                      |                          |                                                                                                                                                  |
|------------------------------------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>-input-file PATH</i>                              | —                        | NPZ with <i>input_spikes</i> (T, B, N_IN) to forward instead of Poisson input. Arbitrary stimulus (exp048 digit streams).                        |
| <i>-scale-w-in / -scale-w-ei / -scale-w-ie FLOAT</i> | 1.0                      | [ <i>-infer</i> ] Multiply loaded input / E→I / I→E weights before the forward pass. Inference-time coupling sweeps without retraining (exp038). |
| <i>-sample-index INT</i>                             | —                        | Raw test-set index for a snapshot, overriding <i>-digit</i> / <i>-sample</i> .                                                                   |
| <i>-n-in / -n-inh / -n-batch INT</i>                 | 784 / — / 64             | [synthetic-spikes] Input channels, inhibitory pool size, Poisson trials averaged.                                                                |
| <i>-w-ei-mean / -w-ie-mean FLOAT</i>                 | from <i>-ei-strength</i> | [synthetic-spikes] Explicit W_EI / W_IE mean (std = $0.1 \cdot \text{mean}$ ).                                                                   |
| <i>-private-w-in</i>                                 | off                      | [synthetic-spikes] Identity W_in: one input channel per E cell.                                                                                  |

The block from *-skip-load* down is the **generic-primitive family**: small, experiment-agnostic hooks (perturb hidden spikes, inject an inhibitory stream, forward an arbitrary input file, scale a weight block at inference). Runners compose these instead of importing model code, and that is what keeps the tool/experiment boundary clean.

### train

Surrogate-gradient BPTT training loop. Writes *weights.pth*, *metrics.json*, a per-step *metrics.jsonl*, and *test\_predictions.json*.

```
uv run python tools/snn/tool.py train --model ping --dataset mnist \
  --epochs 50 --lr 0.0001 --v-grad-dampen 1000
```

*-epochs 0* runs the init snapshot only, useful as a probe.

| flag | default | description |
|------|---------|-------------|
|------|---------|-------------|

|                                            |        |                                                                                                                                                                                                                                                        |
|--------------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>-lr FLOAT</code>                     | 0.01   | Adam learning rate. Biophysical models (ping) typically need 0.0001; current-based models 0.01.                                                                                                                                                        |
| <code>-epochs INT</code>                   | 0      | Number of epochs. 0 = init-snapshot probe only.                                                                                                                                                                                                        |
| <code>-batch-size INT</code>               | 64     | DataLoader batch size.                                                                                                                                                                                                                                 |
| <code>-max-samples INT</code>              | all    | Cap dataset to N samples for smoke tests.                                                                                                                                                                                                              |
| <code>-v-grad-dampen FLOAT</code>          | 80.0   | Dampening factor $d$ on the COBA membrane-voltage gradient. PING needs a much larger value ( $d = 1000$ in the paper) to stabilise BPTT through the E $\leftrightarrow$ I loop; COBA trains at the default. Theory in ar006.                           |
| <code>-fr-reg-upper-target-hz FLOAT</code> | 0      | Population-mean hidden-E firing-rate ceiling per presentation, in Hz. The one-sided squared overshoot is averaged over presentations and hidden layers; active only when the strength is positive.                                                     |
| <code>-fr-reg-upper-strength FLOAT</code>  | 0      | Coefficient $s_u$ on the upper regulariser. Cramer et al.: 0.06.                                                                                                                                                                                       |
| <code>-tau-gaba FLOAT</code>               | 9.0 ms | Override $\tau_{\text{GABA}}$ . Default = <i>models.py</i> 's value (Börger / Buzsáki-Wang range). exp041 sweeps this across {4.5 ... 27} ms while training PING from scratch; the realised gamma frequency $f_\gamma$ tracks $1/\tau_{\text{GABA}}$ . |

### dump-weights

Build the network from a config and emit its weight matrices to *weights\_dump.npz*: the init state, plus (with *-load-weights*) the trained state. It runs no forward pass.

```
uv run python tools/snn/tool.py dump-weights \
  --load-config runs/foo/config.json \
  --load-weights runs/foo/weights.pth \
  --out-dir runs/foo/dump
```

Keys follow  $W_{ff\_N\_init}$  /  $W_{ff\_N\_trained}$  (feedforward, per layer N) plus the E-I blocks  $W_{ei}$  /  $W_{ie}$ . This is how a runner recovers the trained readout matrix ( $W_{out}$  = the last  $W_{ff}$ ) or compares init-vs-trained loop weights (the exp049 pruning analysis) without loading the model in-process. It takes the shared option groups plus *-load-config* / *-load-weights*.

### Shared options

These groups are attached to every subcommand. The grouping matches what each subcommand's *-help* prints.

#### Network

| flag | default | description |
|------|---------|-------------|
|------|---------|-------------|

|                                               |                   |                                                                                                                                                                                                                                                |
|-----------------------------------------------|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>-model {ping}</i>                          | <i>ping</i>       | Architecture. <i>ping</i> is the COBANet with E $\leftrightarrow$ I coupling; with <i>-ei-strength 0</i> the inhibitory loop is silenced for a no-rhythm control.                                                                              |
| <i>-n-hidden INT [INT dots.c]</i>             | dataset-dependent | Hidden layer sizes. One integer = single layer; multiple stacks layers. Default for mnist: 1024.                                                                                                                                               |
| <i>-readout {rate, mem-mean}</i>              | <i>rate</i>       | Output stage. <i>rate</i> sums last-hidden spikes and projects linearly at the final timestep. <i>mem-mean</i> averages the pre-reset voltage of a spiking, subtractively resetting output LIF over time (the trained classification readout). |
| <i>-dales-law / -no-dales-law</i>             | on                | Enforce Dale's law (non-negative weights) or allow signed weights. <i>-no-dales-law</i> is used for balanced-network experiments.                                                                                                              |
| <i>-ei-strength FLOAT</i>                     | 0.5               | E-I coupling strength <i>s</i> . Sets $W_{EI} = s$ and $W_{IE} = s \cdot \text{ratio}$ .                                                                                                                                                       |
| <i>-ei-ratio FLOAT</i>                        | 2.0               | $W_{IE} / W_{EI}$ .                                                                                                                                                                                                                            |
| <i>-w-in-initial-zero-fraction FLOAT</i>      | 0.95              | Fraction of input parameters set to zero at initialization. All remain trainable and may regrow.                                                                                                                                               |
| <i>-recurrent-initial-zero-fraction FLOAT</i> | 0.0               | Fraction of recurrent parameters set to zero at initialization; survivors are rescaled by $1/(1-s)$ . Trainable matrices may become dense.                                                                                                     |
| <i>-exact-k-initialization</i>                | off               | Choose exactly $K = \text{round}((1-s) \cdot N_{\text{pre}})$ initially non-zero recurrent entries per post cell instead of Bernoulli zeroing. This does not impose a persistent connectivity mask.                                            |
| <i>-dt FLOAT</i>                              | 0.25              | Integration timestep (ms).                                                                                                                                                                                                                     |

|                                   |     |                                                                                                                                                |
|-----------------------------------|-----|------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>-t-ms FLOAT</i>                | 200 | Total trial duration (ms). Metrics are measured over the full trace; runners strip any startup transient in post.                              |
| <i>-readout-w-out-scale FLOAT</i> | 1.0 | Scalar applied to the readout matrix after <i>build_net</i> , compensating for low hidden firing rate under <i>mem-mean</i> . Train-mode only. |
| <i>-surrogate-slope FLOAT</i>     | 1.0 | Fast-sigmoid surrogate-gradient slope $\beta$ . Larger = narrower active window. Cramer et al. use 40 for SHD RSNNs.                           |

The drive family below also lives in the Network group. It exists for the balanced-network (Brunel / van Vreeswijk-Sompolinsky) experiments and the Lyapunov chaos probe; canonical PING runs leave all of it off.

| flag                                         | default | description                                                                                                                                                                                                                            |
|----------------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>-independent-drive RATE G_PER_SPIKE</i>   | off     | Per-E-cell independent Poisson drive (bypasses <i>W_in</i> ): <i>N_E</i> uncorrelated streams at <i>RATE</i> Hz, each spike adding <i>G_PER_SPIKE</i> $\mu$ S of <i>g_E</i> . Zero cross-cell correlation.                             |
| <i>-independent-drive-i RATE G_PER_SPIKE</i> | off     | As above, targeting the I population directly. Needed for the full V&S asynchronous-irregular state.                                                                                                                                   |
| <i>-quenched-drive MEAN STD</i>              | off     | Per-E-cell DC conductance drawn once from <i>N</i> ( <i>MEAN</i> , <i>STD</i> ) $\mu$ S and frozen for the trial. V&S quenched input: no fluctuation, so it cannot pin spike times; the Lyapunov probe then measures autonomous chaos. |
| <i>-quenched-drive-i MEAN STD</i>            | off     | Per-I-cell frozen DC conductance.                                                                                                                                                                                                      |
| <i>-lyapunov-eps FLOAT</i>                   | 0 (off) | If $> 0$ (synthetic-spikes mode), rerun with all membranes $\epsilon$ -perturbed at $t=0$ and save the divergence $\ \Delta V(t)\ $ to <i>snapshot.npz</i> . Its growth rate is the max Lyapunov exponent:                             |

|  |  |                                                                           |
|--|--|---------------------------------------------------------------------------|
|  |  | positive for the chaotic V&S state,<br>$\approx 0$ for cycle-locked PING. |
|--|--|---------------------------------------------------------------------------|

## Input

| flag                                      | default                 | description                                                                                                             |
|-------------------------------------------|-------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <i>-input {synthetic-spikes, dataset}</i> | <i>synthetic-spikes</i> | Stimulus regime. <i>synthetic-spikes</i> is Poisson at <i>-input-rate</i> . <i>dataset</i> draws from <i>-dataset</i> . |
| <i>-input-rate FLOAT</i>                  | 25                      | Baseline input rate (Hz).                                                                                               |
| <i>-digit INT</i>                         | 0                       | Dataset class (0–9).                                                                                                    |
| <i>-sample INT</i>                        | 0                       | Sample index within the class.                                                                                          |
| <i>-sample-index INT</i>                  | —                       | Raw test-set index, overriding <i>-digit</i> / <i>-sample</i> .                                                         |
| <i>-dataset {mnist}</i>                   | <i>mnist</i>            | Dataset. <i>mnist</i> is the full 28×28 image encoded to spikes.                                                        |

## Weights (advanced)

| flag                    | default                                     | description                                                                                                                                                     |
|-------------------------|---------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>-w-in MEAN [STD]</i> | <i>0.3 0.06</i>                             | Input fan-in init. Single value sets STD = MEAN × 0.1.                                                                                                          |
| <i>-w-ei MEAN STD</i>   | from <i>-ei-strength</i>                    | Override the W_EI init.                                                                                                                                         |
| <i>-w-ie MEAN STD</i>   | from <i>-ei-strength</i> / <i>-ei-ratio</i> | Override the W_IE init.                                                                                                                                         |
| <i>-w-ii MEAN STD</i>   | <i>0 0</i>                                  | W_II (I→I) init. Off by default (canonical PING has no I→I). Enable for balanced-network experiments.                                                           |
| <i>-w-ee MEAN STD</i>   | <i>0 0</i>                                  | W_EE (E→E) init. Off by default. Enable for the full four-coupling balanced network, where recurrent excitation pins the E rate.                                |
| <i>-trainable-w-ei</i>  | frozen                                      | Promote E→I to gradient-carrying. Asks whether the optimiser will discover the PING-loop weights from scratch.                                                  |
| <i>-trainable-w-ie</i>  | frozen                                      | Promote I→E. The exp049 result <i>gradient descent dismantles PING</i> comes from flipping <i>-trainable-w-ei</i> and <i>-trainable-w-ie</i> on simultaneously. |

## Output

| flag                | default                  | description                                                                                  |
|---------------------|--------------------------|----------------------------------------------------------------------------------------------|
| <i>-out-dir DIR</i> | <i>temp/pinglab-cli/</i> | Output directory. The default is scratch (gitignored); runners always pass an explicit path. |

|                        |     |                                            |
|------------------------|-----|--------------------------------------------|
| <code>-wipe-dir</code> | off | Clear the output directory before the run. |
|------------------------|-----|--------------------------------------------|

## Execution

| flag                                                     | default   | description                                                                                                                   |
|----------------------------------------------------------|-----------|-------------------------------------------------------------------------------------------------------------------------------|
| <code>-seed INT</code>                                   | —         | RNG seed. Seeds Python, NumPy, torch (CPU + CUDA + MPS) before dataset load and model init. Persisted to <i>config.json</i> . |
| <code>-modal</code>                                      | off       | Re-dispatch to Modal.com. Artifacts sync back to <i>-out-dir</i> after completion.                                            |
| <code>-modal-gpu {none, T4, L4, A10G, A100, H100}</code> | <i>T4</i> | GPU type for Modal runs. <i>none</i> runs CPU-only.                                                                           |

`-modal` costs money. The project default is local; only pass it when explicitly instructed.

## Config inheritance

The trick that makes the experiment chain work is `-load-config`. Every *train* run writes a *config.json* alongside its *weights.pth*; a later *sim* or *dump-weights* run inherits from it:

```
uv run python tools/snn/tool.py sim --infer \
  --load-config runs/foo/config.json \
  --load-weights runs/foo/weights.pth \
  --dt 0.5
```

This inherits the model, hidden sizes, dataset, E-I parameters, input rate,  $\tau_{\text{GABA}}$ , and seed, while the explicitly-passed `-dt 0.5` overrides the trained value, replaying the network at a new timestep. Precedence is: explicit CLI flag, then loaded config, then default. The parser builds the set of CLI-explicit flags from *sys.argv* before applying inheritance.

Backwards compatibility: old configs that stored *n\_hidden* as a scalar are remapped to the *hidden\_sizes* list, legacy model names are aliased with a one-line stderr note, and configs missing *dales\_low* trigger a warning to pass it explicitly or retrain.

## Artifacts

Every subcommand calls *save\_run\_artifacts* on entry, writing four provenance files into *-out-dir*:

| file               | contents                                                                                                                                                                                                                                                                                                 |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>config.json</i> | The parsed argparse namespace plus a provenance block ( <i>git_sha</i> with a <i>dirty</i> suffix, <i>torch_version</i> , <i>device</i> , <i>python_env_hash</i> , <i>run_id</i> , <i>started_at</i> ) and the <i>mode</i> . Consumed by <code>-load-config</code> and the runner’s metadata extractors. |
| <i>run.sh</i>      | The literal <i>sys.argv</i> joined with spaces and prefixed with a shebang. Re-running reproduces the run (modulo seeded RNG state, also in <i>config.json</i> ).                                                                                                                                        |



|                   |                                                                                                                                                                                          |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>output.log</i> | The human run log. ANSI escapes are stripped from the file but preserved on stdout, so terminals see colour while the log stays grep-friendly.                                           |
| <i>run.jsonl</i>  | The machine-readable event spine: one typed JSON object per event (epoch rows, warnings, summary). This is what a runner parses when it wants structured progress, not scraped log text. |

Each command adds its own outputs: *train* writes *weights.pth*, *metrics.json*, *metrics.jsonl*, *test\_predictions.json*; *sim -infer* writes *metrics.json* (and *results.json*) plus whatever *-outputs* requested; *dump-weights* writes *weights\_dump.npz*.

These files are scratch. By default they land under *temp/pinglab-cli/*, which is gitignored and overwritten every run. The committed record is produced by the runner: it aggregates each command's config plus headline metrics into one *artifacts/data/expNNN/numbers.json* and renders its figures alongside. That folder, not the ephemeral tool output, is what the publisher reads and what reaches the site.

## Recipes

**Train, then measure the trained network.** Train writes a run directory; *sim -infer* reads it back and emits the population traces a runner needs for a PSD:

```
uv run python tools/snn/tool.py train --dataset mnist --epochs 50 \
    --lr 0.0001 --v-grad-dampen 1000 --out-dir runs/ping

uv run python tools/snn/tool.py sim --infer \
    --load-config runs/ping/config.json \
    --load-weights runs/ping/weights.pth \
    --outputs pop_traces per_cell_rates
```

**Loop-transfer at inference (exp038).** Take a network trained as COBA and scale its E→I coupling up at inference, with no retraining:

```
uv run python tools/snn/tool.py sim --infer \
    --load-config runs/coba/config.json \
    --load-weights runs/coba/weights.pth \
    --scale-w-ei 1.0 --scale-w-ie 1.0 --outputs rasters
```

**Perturbation sweep (exp037).** Drop a fraction of emitted spikes, or add off-phase Poisson noise, inside the forward loop:

```
uv run python tools/snn/tool.py sim --infer \
    --load-config runs/ping/config.json --load-weights runs/ping/weights.pth \
    --perturb-mode drop --perturb-level 0.8
```

**Recover the trained readout matrix.** Dump weights and read *W\_ff\_N\_trained* (the last layer is *W\_out*):

```
uv run python tools/snn/tool.py dump-weights \  
  --load-config runs/ping/config.json \  
  --load-weights runs/ping/weights.pth --out-dir runs/ping/dump
```

# Gradient Stabilisation

12 June 2026

Conductance-based spiking networks (COBA, PING) need one extra ingredient to train at all: a single flag, `--v-grad-dampen`. This article is the deep dive on why it is needed and what it does, derived from the discrete equations the code runs. For the surrounding recipe — BPTT, the spike surrogate, the loss, optimiser, readout, and regulariser — see the Training article; this one assumes that background.

**In plain English.** The E and I cells form a loop that makes the network oscillate at gamma ( $\approx 25$  Hz). Training sends the gradient backward around that same loop, and each time a neuron crosses its spike threshold the surrogate hands the gradient a large multiplier. The loop is traversed *once per gamma cycle* — only about five times in a 200 ms trial — but each pass multiplies by a factor well above one (the surrogate slope enters squared), so a handful of passes is enough to overflow to NaN. The forward simulation stays bounded because the spike reset clamps each cell every cycle; the gradient sidesteps that reset, so forward stability buys nothing backward. The fix, `--v-grad-dampen`, divides the voltage gradient by a constant  $\gamma$  at every step, shrinking the loop’s multiplier below one — and thanks to a straight-through trick it changes only the gradient, never the simulation. The rest of this article proves each of those claims from the discrete equations.

Naive BPTT through a 2000-step COBA/PING trial reaches NaN within a few batches. This article establishes the failure and its remedy from the discrete equations the code runs — no step omitted. The plan is: write the one-step map, differentiate it exactly (Lemma 1), propagate the gradient backward (the recursion), show the recurrent loop forces that gradient to diverge geometrically (Proposition 1), and show that scaling the per-step voltage gradient by  $1/\gamma$  makes the loop a contraction while leaving the forward trajectory untouched (Proposition 2).

## Setup: the discrete update

Index the timesteps  $t = 0, \dots, T$  at  $\Delta t = 0.1$  ms. Each cell holds a state  $(V^t, g_e^t, g_i^t)$ . With reversal potentials  $E_L, E_e, E_i$ , capacitance  $C_m$ , leak  $g_L$ , synaptic decays  $\beta_e = e^{-\Delta t/\tau_e}$  and  $\beta_i = e^{-\Delta t/\tau_i}$ , threshold  $\vartheta$  and reset  $V_r$ , the step is exactly (`lif_step_expeuler`, `exp_synapse`):

$$s^t = \Theta(V^t - \vartheta)\chi^t, \quad (\text{S})$$

$$g_e^{t+1} = \beta_e(g_e^t + W_e s_{\text{pre}}^t), \quad g_i^{t+1} = \beta_i(g_i^t + W_i s_{\text{pre}}^t), \quad (\text{C})$$

$$\tilde{V}^{t+1} = V_\infty^{t+1} + (V^t - V_\infty^{t+1})\alpha^{t+1}, \quad V^{t+1} = \begin{cases} V_r & \text{if } s^t = 1 \text{ or refractory} \\ \tilde{V}^{t+1} & \text{otherwise,} \end{cases} \quad (\text{V})$$

where  $\chi^t \in \{0, 1\}$  is the not-refractory gate, and the membrane decay and rest point are built from the *post*-update conductances  $g^{t+1}$ :

$$g_{\text{tot}} = g_L + g_e^{t+1} + g_i^{t+1}, \quad \alpha^{t+1} = e^{-\Delta t g_{\text{tot}}/C_m}, \quad V_\infty^{t+1} = \frac{g_L E_L + g_e^{t+1} E_e + g_i^{t+1} E_i}{g_{\text{tot}}}. \quad (\text{P})$$

The timing matters and is taken from the code: the spike  $s^t$  in (S) is read from the *current* voltage  $V^t$ , drives the conductance one step later in (C), and that conductance sets the

voltage in (V). So one synaptic edge — presynaptic voltage to postsynaptic voltage — spans one timestep.

### Lemma 1 — the one-step Jacobian

Differentiate (S), (C), (V) entry by entry. The spike surrogate gives the spike derivative

$$\frac{\partial s^t}{\partial V^t} = \sigma'(V^t - \vartheta)\chi^t, \quad \sigma'(u) = \frac{k}{(1 + k|u|)^2}, \quad \sigma'(0) = k. \quad (1)$$

From (C), the conductance partials are a self-decay and a *presynaptic-voltage* coupling obtained by chaining (1):

$$\frac{\partial g_e^{t+1}}{\partial g_e^t} = \beta_e, \quad \frac{\partial g_e^{t+1}}{\partial V_{\text{pre}}^t} = \beta_e W_e \sigma'(V_{\text{pre}}^t - \vartheta)\chi_{\text{pre}}^t. \quad (2)$$

From (V), with  $g$  held, the membrane self-term is the decay; and differentiating (P) gives the conductance-to-voltage term ( $\partial g_{\text{tot}}/\partial g_e = 1$ ,  $\partial V_{\infty}/\partial g_e = (E_e - V_{\infty})/g_{\text{tot}}$ ,  $\partial \alpha/\partial g_e = -(\Delta t/C_m)\alpha$ ):

$$\frac{\partial \tilde{V}^{t+1}}{\partial V^t} = \alpha^{t+1}, \quad \frac{\partial \tilde{V}^{t+1}}{\partial g_e^{t+1}} = \underbrace{(1 - \alpha) \frac{E_e - V_{\infty}}{g_{\text{tot}}}}_{\text{rest shifts}} - \underbrace{\frac{\Delta t}{C_m} \alpha (V^t - V_{\infty})}_{\text{decay shifts}} \equiv \kappa_e \approx \frac{\Delta t}{C_m} (E_e - V), \quad (3)$$

the last step being the leading order in  $\Delta t$  (using  $1 - \alpha \approx \Delta t g_{\text{tot}}/C_m$ ). Define  $\kappa_i$  identically with  $E_i$ . Collecting (1)–(3), the one-step Jacobian on  $(V, g_e, g_i)$ , with the cross-cell coupling in the lower-left block, is

$$J^t = \frac{\partial(V, g_e, g_i)^{t+1}}{\partial(V, g_e, g_i)^t} = \begin{pmatrix} \rho\alpha & \kappa_e & \kappa_i \\ \beta_e W_e \sigma'(V_{\text{pre}} - \vartheta)\chi_{\text{pre}} & \beta_e & 0 \\ \beta_i W_i \sigma'(V_{\text{pre}} - \vartheta)\chi_{\text{pre}} & 0 & \beta_i \end{pmatrix}. \quad (\text{J})$$

The single subtlety, and it is decisive below: the reset in (V) is a **torch.where**, so on any cell that spikes or is refractory the output is the constant  $V_r$  and the membrane self-term is gated to zero. We write this as the factor  $\rho \in \{0, 1\}$  on the  $\partial V^{t+1}/\partial V^t$  entry:  $\rho = 0$  at a spike (gradient through the cell's own membrane is cut),  $\rho = 1$  otherwise. Crucially  $\rho$  multiplies only the membrane self-term — it does **not** touch the spike output  $s^t$  in (1)–(2), which is evaluated at  $V^t$  *before* the reset.

### Backpropagation: the gradient recursion

Let  $\lambda^t \equiv \partial \mathcal{L}/\partial(V, g_e, g_i)^t$ . Reverse-mode autodiff is exactly the linear recursion

$$\lambda^t = (J^t)^\top \lambda^{t+1}, \quad \lambda^T = \nabla_{x^T} \mathcal{L} \implies \lambda^t = \left( \prod_{s=t}^{T-1} J^s \right)^\top \lambda^T. \quad (4)$$

So the gradient that reaches step  $t$  is governed by the product of one-step Jacobians, and  $\|\lambda^t\| \leq (\prod_s \|J^s\|) \|\lambda^T\|$ . Whether this is benign or catastrophic is decided by the voltage component of (J) chained through the recurrent wiring.

## Proposition 1 — the backpropagated gradient diverges (the problem)

*Claim.* In a network with a recurrent  $E \rightarrow I \rightarrow E$  loop, the voltage gradient grows geometrically in the number of gamma *cycles* traversed — not in the number of timesteps. A 200 ms trial holds only  $N \approx 5$  cycles against  $T = 2000$  steps; the danger is that each cycle multiplies by a large factor, not that there are many cycles.

*Proof.* Compose (2) and (3): the gradient carried from a postsynaptic voltage at  $t\{+\}1$  to a presynaptic voltage at  $t$  across one synapse is the product of the conductance-coupling and the membrane term,

$$a \equiv \frac{\partial V_{\text{post}}^{t+1}}{\partial V_{\text{pre}}^t} = \underbrace{\frac{\kappa}{C_m \Delta t (E_{\text{syn}} - V)}}_{\approx \frac{\Delta t}{C_m} (E_{\text{syn}} - V)} \cdot \underbrace{\beta W}_{\text{synapse}} \cdot \underbrace{\sigma'(V_{\text{pre}} - \vartheta)}_{\text{spike}}. \quad (5)$$

Traverse the loop once:  $V_E \rightarrow V_I$  across  $W_{ei}$  (edge gain  $a_{ei}$ ), then  $V_I \rightarrow V_E$  across  $W_{ie}$  (edge gain  $a_{ie}$ ). Over one round trip the  $E$ -voltage gradient maps to itself with the **loop gain**

$$\varrho = a_{ei}a_{ie} = \underbrace{k^2}_{\text{two } \sigma' \text{ at volley}} \cdot \beta_e \beta_i W_{ei} W_{ie} \kappa_I \kappa_E. \quad (6)$$

The factor  $k^2$  appears **once per gamma cycle**. Each population fires a single synchronous volley per cycle, so the two large kicks  $\sigma' \rightarrow \sigma'(0) = k$  (one for  $E$ , one for  $I$ ) occur together once per loop traversal and nowhere else; between volleys the per-step Jacobians are the mild sub-unit decays  $\alpha, \beta < 1$ , which merely carry the gradient along without amplifying it. So (4) collapses, across cycles, to the scalar recursion  $\lambda_{V,E}^{(n)} \approx \varrho \lambda_{V,E}^{(n+1)}$ , giving after  $N$  cycles

$$|\lambda_{V,E}| \geq |\varrho|^N |\lambda_{V,E}^T|. \quad (7)$$

**Worked example (default PING init).** Take the released constants:  $\Delta t = 0.1$  ms,  $k = 5$ ,  $C_m^E = 1.0$  nF,  $C_m^I = 0.5$  nF,  $E_e = 0$ ,  $E_i = -80$  mV,  $V \approx \vartheta = -50$  mV at the crossing,  $\tau_{\text{AMPA}} = 2$  ms ( $\beta_e = e^{-0.05} \approx 0.95$ ),  $\tau_{\text{GABA}} = 9$  ms ( $\beta_i \approx 0.99$ ), and order- $\mu\text{S}$  coupling  $W_{ei} \approx 1$ ,  $W_{ie} \approx 2$   $\mu\text{S}$ . The two edge gains (5) are

$$a_{ei} = \underbrace{\frac{0.1}{0.5}(0 - (-50))}_{\kappa_{\rightarrow I}=10} \cdot \underbrace{\frac{0.95 \cdot 1}{\beta_e W_{ei}}}_{\beta_e W_{ei}} \cdot \underbrace{5}_k \approx 48,$$

$$a_{ie} = \underbrace{\frac{0.1}{1.0}(-80 - (-50))}_{\kappa_{\rightarrow E}=-3} \cdot \underbrace{\frac{0.99 \cdot 2}{\beta_i W_{ie}}}_{\beta_i W_{ie}} \cdot \underbrace{5}_k \approx -30,$$

so the loop gain is  $\varrho = a_{ei}a_{ie} \approx -1.4 \times 10^3$ . Over the  $N \approx 5$  cycles of a 200 ms trial — not the  $T = 2000$  steps — the voltage gradient is amplified by

$$|\varrho|^N \approx (1.4 \times 10^3)^5 \approx 6 \times 10^{15}.$$

A unit gradient seeded at the readout thus returns to  $t = 0$  scaled by  $\sim 10^{16}$ ; summed over the batch and compounded across successive optimiser steps it crosses the fp32 ceiling ( $\approx 3.4 \times 10^{38}$ ) and the loss becomes NaN within a few batches. The blow-up is robust: even if threshold spread cuts the effective  $\sigma'$  tenfold (each edge  $\div 10$ , so  $\varrho \div 100$ ),  $|\varrho| \approx 14$  and  $|\varrho|^5 \approx 6 \times 10^5$  — still divergent. The compounding is per cycle, not per step. ■

*Why the forward pass does not blow up the same way.* The forward orbit is bounded because the reset (V) slams each spiking cell to  $V_r$  every cycle — that is the  $\rho = 0$  gate in (J), a strong per-cycle contraction. But  $\varrho$  in (6) is built only from the spike-output edges (5), i.e. from  $\sigma'$  evaluated *before* the reset; the gate  $\rho$  sits on the membrane self-term and never enters the loop product. So the backward loop bypasses precisely the contraction that bounds the forward orbit. Forward stability and backward divergence are not in contradiction: they travel different paths through (J), and the straight-through reset is what separates them.

## Proposition 2 — per-step voltage-gradient damping bounds it (the solution)

The flag `--v-grad-dampen` inserts, before the reset, the operation  $dv = \text{\_scale\_grad}(dv, 1/\gamma)$  where  $dv = (V_\infty - V)(1 - \alpha)$  is the membrane increment in (V). The primitive

$$\text{\_scale\_grad}(x, c) = cx + \text{detach}(x)(1 - c) \quad (8)$$

is the identity in the forward pass ( $cx + (1 - c)x = x$ ) but multiplies the backward gradient through  $x$  by  $c = 1/\gamma$ . Re-differentiating (V) with  $dv$  so scaled changes two partials of (J):

$$\frac{\partial V^{t+1}}{\partial V^t} = 1 - \frac{1 - \alpha}{\gamma} \in [\alpha, 1], \quad \frac{\partial V^{t+1}}{\partial g^{t+1}} = \frac{\kappa}{\gamma}. \quad (9)$$

The membrane self-term stays bounded by 1 (for  $\gamma \rightarrow \infty$  it tends to 1 — the slow integration pathway is *preserved*, not crushed), while every voltage $\leftarrow$ conductance edge — and therefore every loop edge (5) — is divided by  $\gamma$ . The loop gain (6) becomes

$$\varrho_\gamma = \frac{a_{ei}}{\gamma} \frac{a_{ie}}{\gamma} = \frac{\varrho}{\gamma^2}, \quad (10)$$

so the backward loop is a contraction,  $|\varrho_\gamma| \leq 1$ , as soon as

$$\gamma \geq \sqrt{|\varrho|}. \quad (11)$$

By (8) the forward trajectory  $x^t$  is bitwise identical with or without the flag, so this is a pure modification of the gradient, not of the dynamics. ■

In code this is the single line `\_scale\_grad(dv, 1.0 / v\_grad\_dampen)` in the LIF step. Since  $|\varrho| \sim k^2 c$  for an order-unity loop constant  $c$ , the threshold (11) scales like  $\sqrt{|\varrho|} \sim k\sqrt{c}$ , consistent with the recipes:  $\gamma \approx 80$  for the unitless standard SNN and  $\gamma \approx 1000$  for COBA/PING (used by exp025 and downstream), whose larger conductance-scale loop constant demands the larger  $\gamma$ .

## Corollary — the cost, and choosing $\gamma$

The  $1/\gamma$  in (9) lands on *every* voltage $\leftarrow$ conductance gradient, not only the recurrent loop. The feedforward input also enters through  $g_e$  (the term  $W_{\text{in}} s_{\text{in}}$  in (C)), so the input-weight gradient is suppressed by the same factor: damping trades a slice of the legitimate learning signal for stability. Hence the operating rule — take the smallest  $\gamma$  satisfying (11), i.e. the smallest value that prevents overflow. Too large a  $\gamma$  can therefore quietly cap achievable accuracy by starving the input layer of gradient. Distinct from gradient clipping, which rescales the assembled parameter gradient after the fact: damping reshapes the recursion (4)

term by term, before any parameter gradient is formed. Tightening (11) per-layer on long-trial tasks is open work.

**Prediction.** The mechanism implies the flag is load-bearing only when the loop exists: the same network should train with damping fully off when run as COBA ( $W_{ei} = 0$ , loop open), but fail as PING ( $W_{ei} > 0$ ) — every optimiser step’s gradient going non-finite and being skipped, leaving the network frozen at chance.

# Introduction

11 August 2026

This collection asks whether a pyramidal–interneuron network gamma (PING) loop can act as a structural sparsity constraint in a task-trained spiking network. The experiments separate three questions that are easy to muddle: what generates the rhythm, what sets the firing-rate floor, and whether the resulting sparse activity remains useful for classification. They also distinguish a genuine experimental dependency—one entry consuming another entry’s checkpoints or measurements—from a looser conceptual dependency.

## exp022 — Training-run guide

Link to exp022. The collection’s operational hub owns the canonical training registry and produces the shared COBA and PING checkpoint banks.

## Child experiments

### 1. exp024 — Accuracy converges, firing rate does not

Link to exp024. Audits exp022’s per-epoch baseline histories, comparing convergence of classification accuracy and firing rate. **Manuscript:** supports the rate-attractor interpretation of Figure 3; it is not the plotted image source.

### 2. exp025 — PING locks E rate $\approx 10\times$ below COBA

Link to exp025. Uses exp022’s trained cells for the central comparison between loop-free COBA and gamma-gated PING. **Manuscript:** Figure 3.

### 3. exp037 — PING tolerates 80% dropped spikes but collapses on added noise

Link to exp037. Applies spike-deletion and spike-addition perturbations to exp022’s trained cells. **Manuscript:** Figure 8.

### 4. exp038 — Switching the loop on at inference cuts E rate $\approx 15\times$

Link to exp038. Transfers a trained loop-free baseline into a fresh inhibitory architecture, separating the loop’s inference-time effect from training history. **Manuscript:** Figure 4.

### 5. exp041 — E rate is affine in gamma frequency

Link to exp041. Uses exp022’s  $\tau_{\text{GABA}}$  family to measure how inhibitory decay changes gamma frequency and excitatory rate. **Manuscript:** supplies the spiking comparison in Figure 2 and the complete Figure 6.

#### 1. exp033 — Mean-field PING

Link to exp033. Compares the measured sweep with the mean-field model.

**Manuscript:** mean-field panels in Figure 2.

#### 2. exp042 — Timing perturbations

Link to exp042. Uses exp022 baseline checkpoints and exp041 timing measurements to separate inhibitory timing from inhibitory level. **Manuscript:** Figure 9.

#### 3. exp046 — Per-cycle E-spike count

Link to exp046. Counts excitatory spikes within cycles measured by exp041.

**Manuscript:** Figure 7.

### 6. exp044 — Rate floor stable across a $20\times \Delta t$ sweep

Link to exp044. Reads exp022’s timestep-sweep cells to test whether the rate floor is physical rather than a step-count artefact. **Manuscript:** Figure 10.



## 7. **exp048 — Temporal and spatial evidence limits of trained PING**

Link to exp048. Loads the canonical trained PING checkpoint and varies presentation time, input rate, and evidence distribution. **Manuscript:** current source for Figures 11 and 12, pending replacement by exp082.

## 8. **exp049 — Gradient descent does not preserve a trainable PING loop**

Link to exp049. Uses exp022’s initialisation-family cells to test whether training retains or dismantles the recurrent loop. **Manuscript:** Figure 5.

## 9. **exp082 — Variable-rate streaming with a spike-rate readout**

Link to exp082. Consumes exp022’s variable-rate checkpoint bank. Exp080 and exp081 support its design conceptually but are not execution dependencies. **Manuscript:** planned replacement source for Figures 11 and 12 after results are complete.

## **exp023 — PING fundamentals**

Link to exp023. Establishes the free-running excitatory–inhibitory gamma mechanism without training. **Manuscript:** Figure 1.

## **exp047 — Pool-size invariance requires inverse synaptic scaling**

Link to exp047. Separates nominal total coupling from realised per-synapse strength while varying inhibitory-pool size.

## **exp054 — A PING rhythmicity metric**

Link to exp054. Calibrates a rhythmicity statistic and identifies its low-rate and shared-input failure modes using independent simulations. **Manuscript:** coupling-plane and spiking panels in the Figure 2 composite.

## **exp080 — Empirical input-rate calibration for variable-rate PING training**

Link to exp080. Calibrates transformations of sparse pixel intensities into variable Poisson input rates. It conceptually informs exp082 but supplies no runtime artifact.

## **exp081 — Linear-filter analysis of sparse conductance-driven pixel features**

Link to exp081. Analyses how sparse conductance-driven pixel streams are filtered before and within the PING network. It conceptually informs exp082 but supplies no runtime artifact.

# Bayesian and sampling-based cortical computation

28 June 2026

This guide connects the neural-Bayesian literature to our PING project. The central question is not merely whether cortical behaviour can look Bayesian. It is whether recurrent excitatory/inhibitory (E/I) dynamics can represent uncertainty by sampling, and whether the oscillatory and transient regimes we measure are computationally useful rather than incidental.

## 1. Papers and their relation to the project

1. **Pouget, Dayan & Zemel (2003), population-code foundations.** A broad account of inference with population activity [1]. It supplies the coding language needed to distinguish a distribution represented by a population from a single decoded estimate. For this project, it is the conceptual baseline: before asking whether PING dynamics sample a posterior, we need to state what information the population activity carries and what a downstream readout could recover.
2. **Ma, Beck, Latham & Pouget (2006), probabilistic population codes.** This is the canonical parametric alternative to neural sampling [2]. Instantaneous population rates encode the parameters of an exponential-family distribution, and cue combination becomes addition of population activity. It gives us a competing hypothesis: uncertainty may be encoded in population gain rather than in temporal variability. Any sampling claim from our network should make predictions that separate these accounts.
3. **Fiser, Berkes, Orbán & Lengyel (2010), the sampling hypothesis.** This review develops the proposal that spontaneous and evoked cortical activity are samples from an internal generative model [3]. It connects trial-to-trial variability to probabilistic representation. For our project, it motivates treating fluctuations as signal-bearing dynamics and asking whether the stationary activity distribution, rather than only the mean firing rate or oscillation frequency, matches a target distribution.
4. **Aitchison & Lengyel (2016), E/I circuits as Hamiltonian samplers.** This paper is the closest theoretical bridge to our model [4]. It assigns different computational roles to excitatory and inhibitory populations and argues that their coupled dynamics can accelerate sampling. It should inform which E/I variables we analyse, how phase-lagged activity might act like position and momentum, and why balanced oscillatory dynamics could improve exploration rather than simply stabilize the circuit.
5. **Orbán, Berkes, Fiser & Lengyel (2016), neural variability as sampling evidence.** This paper tests sampling-based predictions in visual cortex [5]. It is useful for translating the theory into empirical diagnostics, especially the relation between stimulus-dependent uncertainty, response variability, and the distribution of population activity. Our analogue is to test whether trained PING networks change their variability in the way the represented posterior requires.
6. **Echeveste, Aitchison, Hennequin & Lengyel (2020), optimized recurrent samplers.** Recurrent networks optimized for sampling develop cortical-like transients and variability [6]. This is the most direct precedent for training a recurrent circuit toward a sampling objective. It motivates comparing task performance with mixing, autocorrelation,

transient amplification, and stability, including our  $\Delta t$ -stability diagnostics. A network that fits the task but mixes poorly is not yet a convincing sampler.

7. **Padamsey, Katsanevaki, Dupuy & Rochefort (2022), precision under metabolic constraint.** Food scarcity reduces cortical coding precision and energy use [7]. This adds a cost axis to the project. If spike rate, inhibitory recruitment, or oscillatory precision has a metabolic price, the best circuit may trade posterior precision against energy rather than maximize accuracy without constraint.

## 2. Reading order and guide

Read the papers in four passes. The order below moves from representation, through the sampling hypothesis, to circuit implementation and finally energetic constraint.

1. **Establish the representational alternatives: Pouget et al. (2003), then Ma et al. (2006).** Ask what object neural activity represents, how uncertainty is encoded, and what operations a downstream circuit can perform. Keep the distinction between *encoding a distribution's parameters* and *producing samples from a distribution* explicit.
2. **Learn the sampling claim: Fiser et al. (2010), then Orbán et al. (2016).** Ask what counts as a neural sample, over what time or trial ensemble the distribution is defined, and which observations distinguish meaningful sampling variability from ordinary noise.
3. **Study the E/I mechanism: Aitchison & Lengyel (2016), then Echeveste et al. (2020).** Track the mapping from mathematical sampler variables to excitatory and inhibitory activity. Then look for measurable consequences in our networks: phase relations, autocorrelation time, mixing, transient amplification, stationary distributions, and sensitivity to the integration step  $\Delta t$ .
4. **Add the resource constraint: Padamsey et al. (2022).** Ask whether coding precision, firing cost, and inhibitory stabilization can be treated as a joint objective. This paper is best read last because it changes the optimization question from “what is the most accurate code?” to “what precision is worth its metabolic cost?”

On a first pass, read abstracts, figures, and discussion. On a second pass, reconstruct the representation and objective in equations. On a third pass, extract one table with four columns for each paper: represented quantity, circuit mechanism, observable prediction, and corresponding diagnostic in our PING model.

## 3. Terms and background to know

### Bayesian fundamentals

A **generative model** is a forward account of how an unobserved cause  $\theta$  produces an observation  $x$ . **Recognition** or **inference** reverses that account and estimates the cause from the observation. Bayes' rule is

$$p(\theta | x) = \frac{p(x | \theta)p(\theta)}{p(x)} \propto p(x | \theta)p(\theta).$$

- $\theta$  is the latent or unobserved cause.
- $x$  is the observation.

- $p(\theta)$  is the **prior**, the distribution before observing  $x$ .
- $p(x | \theta)$  is the **likelihood**, the probability of  $x$  under a proposed cause.
- $p(\theta | x)$  is the **posterior**, the updated distribution over causes.
- $p(x) = \int p(x | \theta)p(\theta) d\theta$  is the **evidence** or marginal likelihood, which normalizes the posterior.

**Marginalisation** integrates out variables that are not of interest. For a target  $\theta_1$  and nuisance variable  $\theta_2$ ,

$$p(\theta_1 | x) = \int p(\theta_1, \theta_2 | x) d\theta_2.$$

- $\theta_1$  is the quantity to retain.
- $\theta_2$  is the nuisance variable to integrate out.
- $x$  is the observation.

High-dimensional marginalisation is usually intractable, which is why approximate inference is needed.

### Probability representations

- **Probabilistic population code (PPC).** Population firing rates encode parameters of a probability distribution. In an exponential-family PPC,

$$p(\theta | x) \propto \exp(\mathbf{h}(\theta)^\top \mathbf{r}).$$

Here  $\theta$  is the latent variable,  $x$  is the observation,  $\mathbf{h}(\theta)$  is a vector of basis functions or sufficient statistics, and  $\mathbf{r}$  is the population response. Posterior uncertainty is commonly expressed through population gain.

- **Sampling-based code.** Instantaneous activity is treated as a draw from a distribution,

$$\mathbf{r}(t) \sim p(\mathbf{r} | x).$$

Here  $\mathbf{r}(t)$  is population activity at time  $t$ ,  $x$  is the observation, and  $p(\mathbf{r} | x)$  is the target activity distribution. Uncertainty is expressed by variability across time or trials. A decoder estimates expectations from multiple samples rather than reading distribution parameters from a single activity vector.

- **Variational inference (VI).** A tractable distribution  $q_{\varphi}(\theta)$  is fitted to the posterior by optimizing parameters  $\varphi$ . VI turns inference into optimization and is usually fast, but its approximation is limited by the chosen family for  $q_{\varphi}$ .

### Exponential families and approximate inference

An exponential-family distribution has the form

$$p(x | \eta) = h(x) \exp(\eta^\top T(x) - A(\eta)).$$

- $x$  is the random variable.
- $\eta$  is the vector of **natural parameters**.
- $T(x)$  is the vector of **sufficient statistics**.
- $A(\eta)$  is the log-partition function.
- $h(x)$  is the base measure.

A prior and likelihood are **conjugate** when the posterior belongs to the same parametric family as the prior. Conjugacy makes some Bayesian updates analytic. PPCs use exponential-family structure because multiplying compatible distributions can become addition of their natural parameters.

Three common approximation families are:

- **Laplace approximation.** Fit a Gaussian around the posterior mode using local curvature. It is cheap but poor for strongly non-Gaussian or multimodal posteriors.
- **Variational inference.** Optimize a tractable  $q_{\varphi(\theta)}$  to approximate the posterior.
- **Markov chain Monte Carlo (MCMC).** Construct a Markov chain whose stationary distribution is the posterior. It can be asymptotically exact, but finite runs can be biased by burn-in and autocorrelation.

The **Kullback–Leibler (KL) divergence** compares distributions:

$$\text{KL}(q \parallel p) = \int q(\theta) \log \frac{q(\theta)}{p(\theta)} d\theta \geq 0.$$

- $p(\theta)$  is the target distribution.
- $q(\theta)$  is the approximation.
- $\theta$  is the variable being integrated over.

The divergence is asymmetric. Minimizing  $\text{KL}(q \parallel p)$  is usually mode-seeking, while minimizing  $\text{KL}(p \parallel q)$  is usually mass-covering.

### Population coding and information

- **Tuning curve.** The mean response  $f_{i(\theta)}$  of neuron  $i$  as a function of stimulus  $\theta$ .
- **Fisher information.** A measure of how precisely responses identify  $\theta$ . Under regularity conditions, an unbiased estimator obeys the Cramér–Rao bound,  $\text{Var}(\hat{\theta}) \geq \frac{1}{I_{F(\theta)}}$ , where  $\hat{\theta}$  is the estimator and  $I_{F(\theta)}$  is Fisher information.
- **Linear Fisher information.** The information accessible to a linear decoder, which is a useful proxy for what a downstream neuron can extract through weighted synaptic input.
- **Noise correlations.** Trial-to-trial covariance between neurons at fixed stimulus. Correlations aligned with the tuning gradient can cap information even as the population grows.
- **Poisson variability.** A count model in which spike-count variance equals its mean. It is a common baseline rather than a universal biological law.

### Sampling dynamics and E/I circuits

- **Stationary distribution.** The distribution approached by a Markov process at long times. A neural-sampling claim requires the circuit’s stationary distribution to match the intended posterior, not merely to display irregular activity.
- **Langevin dynamics.** Noisy gradient dynamics designed to approach a target stationary distribution. They provide the simplest bridge from a log-posterior landscape to recurrent stochastic dynamics.
- **Hamiltonian Monte Carlo (HMC).** A sampler that augments the represented variable with momentum, allowing longer, less diffusive moves through the target distribution. The

Hamiltonian-brain account associates excitatory and inhibitory populations with complementary state variables.

- **Inhibition-stabilized network (ISN).** A recurrent E/I network whose excitatory subnetwork is unstable in isolation and stabilized by feedback inhibition.
- **Mixing time.** The time required for a chain to lose dependence on its initial state and explore the target distribution.
- **Autocorrelation time.** The time over which successive samples remain correlated. Shorter autocorrelation generally means more effective samples per unit time.
- **Transient amplification.** Temporary growth of selected activity patterns in an asymptotically stable recurrent network. It can accelerate movement through state space without requiring sustained instability.
- **$\Delta t$ -stability.** In this project, robustness of the simulated or trained dynamics to the numerical integration step  $\Delta t$ . A purported computational regime that disappears under a smaller step may be a discretization artefact rather than a property of the continuous-time circuit.

### Posterior readouts and metabolic cost

- **Maximum a posteriori (MAP) estimate.** The posterior mode,  $\theta_{\text{MAP}} = \arg \max_{\theta} p(\theta \mid x)$ .
- **Posterior mean.**  $\mathbb{E}[\theta \mid x]$ , the Bayes-optimal point estimate under squared-error loss.
- **Posterior variance or credible interval.** The width of the posterior, representing uncertainty rather than only a best estimate.
- **Bits per spike.** Mutual information between stimulus and response divided by spike count, used as a measure of coding efficiency.
- **Coding precision.** The inverse width of the represented distribution. A system can reduce precision to save energy while retaining a similar posterior mean.
- **Metabolic cost of a spike.** The energetic cost, largely paid by ion pumps, of restoring ionic gradients after an action potential.

## References

1. Pouget, Dayan & Zemel (2003), *Inference and computation with population codes* doi:10.1146/annurev.neuro.26.041002.131112
2. Ma, Beck, Latham & Pouget (2006), *Bayesian inference with probabilistic population codes* doi:10.1038/nrn1790
3. Fiser, Berkes, Orbán & Lengyel (2010), *Statistically optimal perception and learning: from behavior to neural representations* doi:10.1016/j.tics.2010.01.003
4. Aitchison & Lengyel (2016), *The Hamiltonian brain: efficient probabilistic inference with excitation-inhibition networks* doi:10.1371/journal.pcbi.1005186
5. Orbán, Berkes, Fiser & Lengyel (2016), *Neural variability and sampling-based probabilistic representations in the visual cortex* doi:10.1016/j.neuron.2016.09.038
6. Echeveste, Aitchison, Hennequin & Lengyel (2020), *Cortical-like dynamics in recurrent circuits optimized for sampling-based probabilistic inference* doi:10.1038/s41593-020-0671-1
7. Padamsey, Katsanevaki, Dupuy & Rochefort (2022), *Neocortex saves energy by reducing coding precision during food scarcity* doi:10.1016/j.neuron.2021.10.024

# SNNLANG developer documentation

30 July 2026

## Contents

1. Developer guide
2. Your first network
3. Run the graph
4. API reference
5. Collection reading path

## Developer guide

### What `snnlang` does

`snnlang` is the network-authoring layer for `tools/snn`. It provides a small Python API for describing populations, projections, inputs, outputs, and recordings. Compilation checks the description and writes a portable, data-only bundle. `tools/snn` loads that bundle and performs the simulation or training.

The system separates four concerns:

1. The **graph** describes reusable computation.
2. The optional **training recipe** describes standard learning choices.
3. The **execution protocol** supplies data, duration, seeds, device, checkpoints, and recordings for one run.
4. The **experiment** owns the scientific question, conditions, analysis, figures, and conclusions.

A saved bundle contains scientific structure rather than live Python objects. It can be inspected and replayed without importing the authoring package.

### Your first network

A network begins with an explicit timestep and a typed input. Components add reusable motifs. Outputs are values returned to a caller; observables are internal signals retained for inspection.

```
from tools import snnlang as snn

net = snn.Network("small_ping", dt=0.1 * snn.ms)
events = net.input(
    "events",
    shape=("time", "batch", 128),
    signal_type="spikes",
    unit="spike",
)

cell = snn.components.ping(
    net,
    name="cell",
    n_e=80,
```

```

        n_i=20,
        source=events,
    )
    net.expose(cell.E.spikes, cell.I.spikes, name="raster")

    bundle = snn.compile(net, target="tools/snn")
    bundle.write("small_ping.bundle", visualise=True)

```

Compilation produces `graph.json`, `manifest.json`, a readable report, and optional circuit diagrams.

## Run the graph

Provide one tensor for every declared input:

```

import torch
from tools.snn.execution import ExecutionSpec, simulate

spikes = torch.zeros(2_000, 1, 128)
result = simulate(ExecutionSpec(
    kind="simulate",
    executor="graph",
    bundle="small_ping.bundle",
    inputs={"events": spikes},
    seed=42,
    device="cpu",
    recording="observables",
))

e_spikes = result.recordings["raster_0"]
i_spikes = result.recordings["raster_1"]

```

Graph-native forward simulation supports this example today. Input generation remains the caller's responsibility.

## API reference

### Package surface

Import the public authoring API with `from tools import snnlang as snn`. The top-level package exports `Network`, graph specification constructors, `units`, `compile`, `load_bundle`, `validate_graph`, and the `components`, `ops`, `readouts`, and `training` modules.

### Minimal lifecycle

```

net = snn.Network(name, dt=0.1 * snn.ms)
bundle = snn.compile(net, training=None, target=None, assets=None)
root = bundle.write(path, visualise=False)
loaded = snn.load_bundle(root)

```

`Network` is mutable while authoring. `compile` returns a `Bundle` containing immutable graph data, optional training data, a manifest, diagnostics, and logical asset sources. `Bundle.write`



returns the bundle directory. `load_bundle` verifies digests and validates the stored graph before returning a `Bundle`.

### Execution boundary

Execution is deliberately separate from `tools.snnlang`. Import `ExecutionSpec`, `build`, `simulate`, `train`, or `infer` from `tools.snn.execution`. Graph execution is opt-in with `executor="graph"`; the legacy executor remains the default.

## Collection reading path

Read the collection in this order:

1. **SNNLANG developer documentation.** This page establishes the architecture, first graph, execution boundary, and package lifecycle.
2. **Networks, signals, and parameters.** Core authoring objects, shapes, units, populations, and parameters.
3. **Components, projections, and delays.** Reusable motifs, connectivity, scheduling, and causality.
4. **Compiling and executing bundles.** Validation, bundle I/O, typed requests, and result objects.
5. **Inputs, outputs, and readouts.** Public outputs, recordings, standard readouts, and dense bindings.
6. **Training recipes and graph-native learning.** Declarative learning vocabulary and current execution limits.
7. **Runtime state, checkpoints, and provenance.** Continuation, compatibility, save/load, and replay identity.
8. **Compatibility, status, and extension.** Current support, remaining gates, diagnostics, and extension points.

Each page begins with its own linked contents, presents the high-level developer guide, and ends with the API reference.

Next: Networks, signals, and parameters

# Compute options

11 August 2026

This is the operational map for pinglab compute. It separates the persistent control plane from the machines that perform numerical work, and records the authentication boundary for each provider. Prices, balances, queues, and GPU stock change. The commands below query those values when a decision is made instead of preserving a stale snapshot here.

Never place a password, TOTP seed, private SSH key, RunPod API key, or Modal token in this repository. Authentication commands either use an encrypted local key or open the provider's own interactive login flow.

## 1. Local Mac

**When to use.** Use the Mac for editing, Demolab preview, plotting, analysis of collected results, dry-run dispatch plans, and plumbing-scale tests. It is the shortest feedback loop. It is not a CUDA training machine.

**Provider overview.** This is the local development workstation. It has no scheduler and no marginal compute charge. The working checkout is `/Users/eoin/pinglab`.

**How to use.** Local access requires the macOS user session rather than a separate infrastructure login.

```
cd /Users/eoin/pinglab
uv sync --dev

# Run an experiment locally.
uv run python experiments/expNNN.py

# Preview the Demolab collection.
demolab dev
```

Keep cloud commands in dry-run mode until spending has been explicitly authorised.

## 2. Hetzner control plane

**When to use.** Use Hetzner for the persistent Codex session, orchestration, monitoring, result collection, and the public development preview. Do not use its small CPU and memory allocation for substantial numerical experiments.

**Provider overview.** Hetzner supplies the always-on Linux host named `pinglab-codex`. Caddy terminates HTTPS for `pl-hetzner.eoinmurray.info` and proxies to the Demolab development server on port `3000`. The server is a control plane, not a GPU worker.

**How to use.** The Mac alias `hetzner` authenticates as `eoin` with the dedicated `Ed25519` identity configured in `~/.ssh/config`. The private key remains on the Mac. The Hetzner host has its own dedicated key for Olorin.

```
ssh hetzner

# Inspect the persistent session and preview service.
tmux list-sessions
tmux attach -t shd-autoresearch
systemctl --user status demolab-dev.service

# Reach Olorin from the control plane.
ssh olorin 'hostname; whoami'
```

### 3. Olorin

**When to use.** Use Olorin for large single-GPU or multi-GPU work when a GPU is visibly idle and the Division F fair-use policy permits the allocation. Its large VRAM makes it the first choice for workloads that do not fit on consumer GPUs.

**Provider overview.** Olorin is a shared Division F machine with four NVIDIA RTX PRO 6000 Blackwell Server Edition GPUs, each with approximately 96 GB of VRAM. It currently has no Slurm scheduler. Availability is therefore manual and may change between inspection and launch.

**How to use.** The Mac alias `olorin` connects through `gate.eng.cam.ac.uk` using `~/.ssh/olorin_codex`. Hetzner has a separate dedicated key. Passwords are not stored. Check utilization immediately before every launch, select only an idle GPU, and keep heavy files under `/scratch/em586`.

```
ssh olorin
nvidia-smi

# Inspect utilization without opening an interactive shell.
ssh olorin \
  'nvidia-smi --query-gpu=index,utilization.gpu,memory.used,memory.total \
  --format=csv,noheader'

# On Olorin, after confirming that GPU N is idle:
cd /scratch/em586/pinglab
CUDA_VISIBLE_DEVICES=N uv run python experiments/expNNN.py
```

Never launch on all four GPUs merely because the machine accepts the command. Shared infrastructure without a scheduler requires more restraint, not less.

### 4. CSD3 Wilkes3, Service Level 2

**When to use.** Use SL2 for planned production runs where a queue of hours is acceptable. It is the default scheduled backend for long, reproducible A100 jobs and should consume the purchased allocation before commercial cloud credits.

**Provider overview.** Wilkes3 is Cambridge's Slurm-managed A100 cluster. The SL2 GPU account is `OLEARY-SL2-GPU`; the Ampere partition uses `QOS gpu1`. Account balance and scheduler estimates are live administrative state and must be queried at submission time.

**How to use.** Connect as Cambridge user `em586`. SSH requires the Raven/UIS password plus the six-digit token labelled **CSD3: SSH Login**. The `csd3` alias uses **ControlMaster** so subsequent commands reuse the authenticated connection. An SSH key can replace the password factor, but mandatory TOTP remains unless Research Computing Services arranges an automation-specific solution.

```
# Establish or reuse the multiplexed connection.
ssh csd3

# Inspect purchased hours and account associations.
ssh csd3 mybalance
ssh csd3 'sacctmgr show assoc user="$USER" format=Account,Partition,QOS'

# Submit one A100 job on SL2.
sbatch \
  --account=OLEARY-SL2-GPU \
  --partition=ampere \
  --qos=gpu1 \
  --gres=gpu:1 \
  job.slurm

# Ask Slurm for an estimate without submitting.
sbatch --test-only \
  --account=OLEARY-SL2-GPU --qos=gpu1 job.slurm
```

Command-line `sbatch` options override matching `#SBATCH` lines, so one job script can target either service level.

## 5. CSD3 Wilkes3, Service Level 3

**When to use.** Use SL3 for non-urgent work that can wait several days, for overflow, or for jobs submitted well before their results are needed. It is a poor interactive backend.

**Provider overview.** SL3 uses the same Wilkes3 A100 hardware and Ampere partition but a lower-priority service level. The GPU account is `OLEARY-SL3-GPU` and its QOS is `gpu2`.

**How to use.** Authentication is identical to SL2. Toggle the account and QOS at submission time:

```
sbatch \
  --account=OLEARY-SL3-GPU \
  --partition=ampere \
  --qos=gpu2 \
  --gres=gpu:1 \
  job.slurm

sbatch --test-only \
  --account=OLEARY-SL3-GPU --qos=gpu2 job.slurm

squeue -u "$USER"
```

The names are easy to invert: SL2 maps to `gpu1`, while SL3 maps to `gpu2`.

## 6. RunPod

**When to use.** Use RunPod for urgent burst capacity when Olorin is occupied and Wilkes3 is queued. Prefer a 4090 when the workload fits in 24 GB and stock exists; use a 5090 for additional VRAM or faster turnaround. Always run the smoke test before a fleet launch because allocation does not guarantee that the container will become usable promptly.

**Provider overview.** RunPod provides per-second GPU pods. Pinglab targets Secure Cloud in EU-R0-1, attaches the shared network volume, and uses `ghcr.io/eoinmurray/pinglab:cu128`, the same image used by experiment dispatch. GPU stock and regional prices are volatile. Pods must be reaped after failures because a rented but unusable pod can still bill.

**How to use.** `runpodctl doctor` stores the account API key in the user's RunPod configuration. Do not commit the key. The account also holds an SSH public key, optional S3 credentials for volume collection, and optional container-registry authentication for GHCR pulls.

```
# One-time interactive authentication.
runpodctl doctor

# Read-only inventory and account checks.
runpodctl gpu list
runpodctl datacenter list
runpodctl pod list -o json
runpodctl user -o json

# Free plan, then an explicitly paid capacity check.
uv run python experiments/helpers/runpod_smoke.py
uv run python experiments/helpers/runpod_smoke.py --live

# Experiment dispatch remains a dry-run without --live.
uv run python experiments/exp022.py --runpod --gpu 5090
uv run python experiments/exp022.py --runpod --gpu 5090 --live

# Kill switch for an exp022 fleet.
uv run python experiments/exp022.py --runpod --reap
```

Every pod-creating command spends money. Dry-run first, obtain explicit approval, launch, monitor, collect, and verify that `runpodctl pod list` is empty.

## 7. Modal

**When to use.** Use Modal when reliable serverless startup, automatic scaling, and reduced infrastructure management justify a higher GPU-hour price. It is useful as an escape hatch when RunPod image or SSH transport is unreliable. Only runners with an implemented Modal backend can use it.

**Provider overview.** Modal runs containerized functions and bills GPU, CPU, and memory by execution time. It provides managed scheduling rather than a persistent SSH host.

Pinglab's Modal integration is narrower than its RunPod integration, so backend support must be confirmed in the selected runner.

**How to use.** `modal setup` opens Modal's authentication flow and stores a local token. Never commit token values. As with RunPod, pinglab requires `--live` before a runner dispatches paid work.

```
# One-time interactive authentication.
uv run modal setup

# Confirm the runner's options before dispatch.
uv run python experiments/exp073.py --help

# Free plan, followed by an explicitly authorised live dispatch.
uv run python experiments/exp073.py --modal
uv run python experiments/exp073.py --modal --live
```

Modal is not a drop-in flag for every experiment. If a runner does not expose `--modal`, adding a backend is implementation work rather than a command-line choice.

## Decision order

Use the smallest adequate option. Develop locally; orchestrate from Hetzner; use an idle Olorin GPU for opportunistic free work; submit planned production to Wilkes3 SL2; use RunPod for urgent overflow; choose Modal when managed reliability is worth the premium; and leave SL3 for work that can wait.

# Cloudflare R2 archive

11 August 2026

Cloudflare R2 stores selected experiment scratch that is expensive to reproduce, especially trained checkpoint banks under `temp/experiments/`. Git remains the record for source code and published artifacts. R2 is a manual backup, not a live training filesystem.

The supported interface is `experiments/helpers/archive.py`. It stores snapshots at:

```
r2:pinglab/archive/<experiment-slug>/<producing-git-sha>/
```

## Access and authentication

The Mac currently has the `r2:` rclone remote. Hetzner does not. Credentials consist of an Access Key ID, Secret Access Key, and the EU R2 endpoint. Never commit or paste their values.

To configure a new machine, create an **Object Read & Write** token scoped to the `pinglab` bucket in the Cloudflare dashboard. Then configure rclone interactively:

```
rclone config
```

Use these choices:

1. Remote name: `r2`.
2. Storage: `s3`.
3. Provider: `Cloudflare`.
4. Enter the Access Key ID and Secret Access Key manually.
5. Endpoint: the EU endpoint shown by Cloudflare.
6. ACL: `private`.

Prefer a separate bucket-scoped token for each machine. See Cloudflare's token guide and rclone guide.

Verify access without writing:

```
rclone listremotes
rclone config redacted r2
rclone lsd r2:
rclone lsf --dirs-only r2:pinglab/archive
```

Do not print the unredacted rclone configuration.

## Archive a run

Check the local scratch, then archive it:

```
du -sh temp/experiments/exp022
uv run python experiments/helpers/archive.py archive exp022
```

The helper determines the producing Git commit, copies the tree, uploads `MANIFEST.json`, and verifies it with `rclone check`. It uses `copy`, never `sync`, so a partial local tree cannot delete existing remote objects.

## List snapshots

```
uv run python experiments/helpers/archive.py list exp022

rclone tree r2:pinglab/archive/exp022 --max-depth 2
rclone size r2:pinglab/archive/exp022
rclone cat r2:pinglab/archive/exp022/<sha>/MANIFEST.json
```

## Restore a snapshot

Restore the latest snapshot:

```
uv run python experiments/helpers/archive.py restore exp022
```

Or restore a specific producing commit:

```
uv run python experiments/helpers/archive.py restore exp022 <sha>
```

Restore copies into `temp/experiments/exp022/` without deleting unrelated local files. Validate configuration files and load representative checkpoints before using the restored bank.

## Safety rules

- Never run `rclone sync` against an archive prefix.
- Archive only completed runs worth preserving.
- Do not use R2 as mutable training storage.
- Keep snapshots from different producing commits separate.
- Revoke and replace a token immediately if it may have leaked.
- Do not confuse R2 credentials with `RUNPOD_S3_ACCESS_KEY_ID` and `RUNPOD_S3_SECRET_ACCESS_KEY`; those access RunPod storage.

The helper deliberately has no delete command. Remote deletion should remain a separate, explicit administrative action.



# Networks, signals, and parameters

14 August 2026

## Contents

1. Developer guide
2. Networks
3. Signals and inputs
4. Populations
5. Parameters
6. API reference

## Developer guide

### Networks

**Network** is the mutable authoring object. Compilation turns it into immutable graph data. Every graph has a name and timestep.

```
net = snn.Network("example", dt=0.1 * snn.ms)
```

Names must be unique and contain no whitespace. They become stable identifiers in graphs, recordings, and checkpoints.

### Signals and inputs

Signals carry an identifier, shape, physical unit, and signal type. Time-varying inputs use the canonical (time, batch, channels) axis order.

```
image = net.input(
    "image",
    shape=("time", "batch", 784),
    signal_type="spikes",
    unit="spike",
)
```

This declares what the graph accepts. It does not decide whether the spikes came from MNIST, SHD, a Poisson encoder, or a recorded event stream.

### Populations

A population contains equally configured neurons and exposes named ports such as **spikes**, **voltage**, **excitatory**, and **inhibitory**.

```

excitatory = net.population(
    "E",
    size=80,
    neuron=snn.COBA_LIF(
        capacitance_nf=1.0,
        leak_us=0.05,
        resting_mv=-65.0,
        threshold_mv=-50.0,
        reset_mv=-65.0,
        refractory_steps=12,
    ),
)

```

The authoring API describes COBA-LIF, LIF, and non-spiking leaky-integrator populations. The graph executor currently supports COBA-LIF and leaky integrators. General current-based LIF execution is not implemented.

### Parameters

Parameters have stable names, shapes, units, initializers, and optional constraints.

Projections normally create their own dense weight parameter, but a named `ParameterRef` may be supplied explicitly.

Initializers explicitly distinguish lower-clamped normal, signed normal, uniform, constant, and zero distributions. Lower-clamped normal may request Bernoulli or exact-fan-in initial zeroing; those zeros remain ordinary parameters rather than a permanent connectivity mask. Projection weights record fan-in normalization, while direct readout parameters record direct storage. The execution result reports each parameter's initializer, constraint, unit, runtime shape, scaling rule, and realized count, zero fraction, mean, standard deviation, minimum, and maximum.

## API reference

### Network

```

Network(name: str, *, dt: Quantity = 0.1 * ms)

```

`name` becomes the graph identifier. `dt` is a time `Quantity`. Names claimed inside one network must be non-empty, unique, and contain no whitespace.

### Network.input

```

net.input(name, *, shape, signal_type, unit="1") -> Signal

```

`shape` is a tuple of integers and symbolic axes. Time-varying dense inputs begin with ("time", "batch", ...). The returned signal identifier is `<name>.value`.

### Network.population

```

net.population(name, *, size, neuron, spiking=True) -> Population

```

size must be positive. A spiking population exposes `.spikes` and `.voltage`; a non-spiking population exposes `.voltage`. Target ports are `.excitatory`, `.inhibitory`, and `.modulatory`.

#### **Network.parameter and Network.constant**

```
net.parameter(name, *, shape, initializer, unit="1", constraint=None) ->
ParameterRef
net.constant(name, value, *, unit="1") -> str
```

Parameter constructors are `LowerClampedNormal(mean, std, initial_zero_fraction=0, zeroing="bernoulli")`, its compatibility spelling `Normal(mean, std)`, `SignedNormal(mean, std)`, `Uniform(low, high)`, `Constant(value)`, and `Zeros()`. Exact fan-in zeroing uses `zeroing="exact_k"`. `NonNegative()` is the implemented constraint. Neuron constructors are `COBA_LIF(**values)`, `LIF(**values)`, and `LeakyIntegrator(**values)`. Unit helpers are `ms`, `mV`, `nS`, and `Hz`.

#### **Core return types**

`Signal` exposes `id`, `shape`, `unit`, `signal_type`, `owner`, and `port`. `Population` exposes `id`, `size`, `neuron`, `spiking`, `group`, and its signal or target-port properties. `ParameterRef` contains the stable parameter `id`.

Next: Components, projections, and delays

# Components, projections, and delays

14 August 2026

## Contents

1. Developer guide
2. Components
3. Projections
4. Scheduling and causality
5. API reference

## Developer guide

### Components

Components are Python functions that add a reusable motif to a network. They disappear during compilation, leaving ordinary populations, projections, parameters, and groups.

`snn.components.ping` creates excitatory and inhibitory COBA-LIF populations with reciprocal E-to-I and I-to-E projections. Its defaults preserve established *tools/snn* numerical conventions. They are compatibility defaults, not a universal biological model.

```
cell = snn.components.ping(
    net,
    name="sensory",
    n_e=256,
    n_i=64,
    source=events,
)
```

A component may be instantiated several times. Larger circuits should be constructed by connecting named components rather than creating a new simulator class.

### Projections

A projection declares its source, target port, synapse, weights, constraint, connection role, and optional delay.

```
net.connect(
    source.spikes,
    target.excitatory,
    name="source_to_target",
    synapse=snn.AMPA(tau=2 * snn.ms),
    weight=snn.Normal(0.2, 0.03),
    constraint=snn.NonNegative(),
    connection="feedforward",
    delay=0.2 * snn.ms,
)
```

The graph backend supports dense AMPA and GABA feedforward, recurrent, and feedback projections. Sparse matrices, structured connectivity, fractional-step delays, and modulatory synapses are not implemented.

A projection may set `enabled: false`. Disabled projections remain structural: their parameter names, shapes, initializers, and construction positions are unchanged, while execution contributes exactly zero conductance. This is the appropriate representation for controlled recurrent-loop ablations because later tensors retain the same identities and random draws.

### Scheduling and causality

Feedforward edges with no delay follow a deterministic topological order. Recurrent and feedback spikes are causal: zero additional delay still means that a spike affects another population no earlier than the next simulation step. Positive delays must be exact multiples of the network timestep.

Zero-delay cycles, projection dimension errors, polarity mismatches, and invalid delays fail during planning rather than during simulation.

## API reference

### `components.ping`

```
snn.components.ping(
    net, *, name, n_e, n_i, source=None,
    tau_gaba=9 * snn.ms,
    include_silent_recurrence=False,
) -> PING
```

Returns a `PING` object with `.E` and `.I` populations. When `source` is supplied, the component adds a feedforward AMPA projection to `E`. The optional silent recurrent paths retain zero-valued `E→E` and `I→I` parameter shapes.

### `Network.connect`

```
net.connect(
    source, target, *, name, synapse,
    weight=Constant(1.0), constraint=None,
    connection="feedforward", delay=None,
    enabled=True,
) -> Projection
```

`source` is a `Signal`; `target` is a population target-port string. Implemented connection values are "feedforward", "recurrent", and "feedback". The authoring vocabulary also accepts "modulatory", which the graph executor does not support. Synapse constructors are `AMPA(**values)`, `GABA(**values)`, `LeakyIntegrator(**values)`, and `Modulatory(**values)`.

`weight` accepts an initializer `Spec` or an existing `ParameterRef`. A new dense projection parameter has graph shape `[target, source]` and unit `nS`. `delay` is a time `Quantity` and must resolve to an integral number of graph timesteps for execution.

### `Network.group`

```
with net.group(name, parent=None) as component:
    ...
```

The context records subsequently claimed members under one component. **parent** must name an existing group. Groups organize reports and diagrams; they do not change execution.

**Projection**

A **Projection** exposes **id**, **source**, **target**, **synapse**, **connection**, **delay**, **parameter\_ids**, **group**, and **.weight**, which returns the first projection parameter as a **ParameterRef**.

Next: Compiling and executing bundles

# Compiling and executing bundles

14 August 2026

## Contents

1. Developer guide
2. Compilation
3. Execution requests
4. Recordings and results
5. API reference

## Developer guide

### Compilation

`snn.compile` validates a network, validates an optional training recipe, reports target capabilities, and returns a `Bundle`. A target asks for diagnostics but never changes the graph.

```
bundle = snn.compile(net, target="tools/snn")
root = bundle.write("network.bundle", visualise=True)
```

A bundle contains canonical `graph.json`, optional `training.json`, a digest-bearing `manifest.json`, copied logical assets, a readable summary, and optional diagrams. Loading verifies hashes and rejects missing or altered files.

Dataset paths, output directories, accelerator caches, and experiment-specific analysis do not belong in the bundle.

### Execution requests

`ExecutionSpec` selects the legacy or graph executor explicitly and supplies inputs, seed, device, recording profile, checkpoint, runtime state, and execution options.

The graph executor plans the complete topology before stepping. It validates dimensions, scheduling, polarity, delays, supplied inputs, outputs, and backend capabilities. Historical CLI commands continue to select the legacy executor by default.

### Recordings and results

Recording profiles are:

- `full`, retaining every supported population trace;
- `observables`, retaining only explicitly exposed signals; and
- `none`, minimizing recording overhead.

Results contain named outputs, recordings, parameters, final voltages, runtime state, timing, device, and recording metadata.

Forward graph execution is implemented for dense COBA-LIF and leaky-integrator graphs with AMPA and GABA projections. Unsupported capabilities fail explicitly before execution.

## API reference

### Compile and load

```
snn.compile(network, *, training=None, target=None, assets=None) -> Bundle
snn.load_bundle(path) -> Bundle
snn.validate_graph(graph) -> ValidationResult
```

`target="tools/snn"` adds capability diagnostics without rewriting the graph. `assets` maps declared logical asset identifiers to physical paths. `load_bundle` verifies every manifest entry and graph digest before returning data.

### Bundle

```
bundle.write(path, *, visualise=False) -> Path
bundle.visualise(path, *, view="circuit", scale=1) -> Path
```

Bundle fields are `graph`, `training`, `manifest`, `diagnostics`, and `asset_sources`. Visualization views are "circuit", "training", and "expanded".

### ExecutionSpec

```
ExecutionSpec(
    kind,
    executor="legacy",
    bundle=None,
    graph=None,
    inputs={},
    input_bindings=(),
    protocol={},
    seed=0,
    device="auto",
    recording="full",
    checkpoint=None,
    runtime_state=None,
    options={},
)
```

`kind` is "build", "simulate", "train", or "infer". `executor` is "legacy" or "graph". Recording profiles are "full", "observables", and "none". Device values are "auto", "cpu", "cuda", "cuda:N", or "mps".

### Dispatch and results

```
build(spec) -> ExecutionResult
simulate(spec, *, runtime_state=None) -> ExecutionResult
train(spec) -> ExecutionResult
infer(spec) -> ExecutionResult
execute_request(spec, *, legacy=None) -> ExecutionResult
```



`ExecutionResult` exposes `executor`, `outputs`, `recordings`, `parameters`, `final_state`, `runtime_state`, `metrics`, and `model`. Graph-native `train` is not implemented; it fails with the missing training capability instead of using the legacy trainer silently.

Next: Inputs, outputs, and readouts

# Inputs, outputs, and readouts

14 August 2026

## Contents

1. Developer guide
2. Outputs and observables
3. Standard readouts
4. Input bindings
5. API reference

## Developer guide

### Outputs and observables

An output is a named value returned by the graph. An observable exposes an internal signal for recording without changing the computation.

```
readout = snn.readouts.MeanVoltage(
    source=cell.E.spikes,
    classes=10,
    name="classifier",
)
net.output("class_logits", readout)
net.expose(cell.E.spikes, cell.I.spikes, name="hidden")
```

### Standard readouts

The standard readouts are mean voltage, final voltage, spike count, duration-normalized spike rate, and cumulative potential. Spike-rate logits divide spike count by valid presentation duration, so changing duration does not silently rescale the classifier.

All five standard readouts execute in the graph executor. Spike rate reports spikes per second from either an explicit duration in seconds or a `(time, batch)` valid-time mask; masked reductions reject empty windows rather than silently returning arbitrary values. The compiler infers shapes and units, checks linear readout parameter shapes, rejects malformed masks and ambiguous durations, and records operation requirements in the bundle capability manifest.

### Input bindings

The execution layer binds concrete data to graph inputs without placing datasets or stimuli in graph structure. Dense arrays and sparse event streams are implemented as separate named, data-only representations. Dense NPY replay binds to a graph with one input; dense NPZ arrays bind by input identifier.

Before execution, the resolver requires exact input coverage, common time and batch axes, declared feature dimensions, finite numeric values, binary spike values, and boolean or zero/one masks. A mismatch names the offending input and fails before simulation.

Event replay stores zero-based integer step, batch, and channel coordinates plus explicit step and batch counts. Coordinates must be ordered by step, batch, and channel. The resolver rejects duplicates, invalid graph input types, inconsistent durations, and out-of-bounds coordinates before materializing binary spikes.

Every replay emits a versioned execution protocol containing the representation, source-file digest and array keys, resolved shape and data type, signal type and unit, dataset identity and split when supplied, sample cap, batch size, shuffle behavior, timestep, duration, masks, seeds, and representation-specific resolution semantics. The command-line contract accepts `--input-file` or `--event-file`, dataset metadata, and the explicit `--input-shuffle` or `--no-input-shuffle` pair.

Fixed-rate and categorical variable-rate Poisson encoding belong to execution protocol rather than graph topology. Both are implemented as seeded bindings. The categorical protocol samples one rate uniformly and independently per presentation, records the realized rate vector, and then generates graph-shaped spikes using the declared timestep.

Dense-array, valid-time-mask, sparse event-stream, generated Poisson, and portable dataset-snapshot bindings work today. A snapshot remains an external immutable NPZ file identified by its content digest and caller-supplied dataset/split identity. The standard encoder vocabulary covers feature-scaled rate-Poisson samples, already binned spikes, and timestamped event samples binned at the graph timestep.

## API reference

### Outputs and observables

```
net.output(name, signal) -> SignalLike
net.expose(*signals, name=None) -> None
```

An output maps a public name to one graph signal. `expose` records one or more internal signals. A single exposed signal uses `name` directly; multiple signals use `<name>_0`, `<name>_1`, and subsequent indices.

### Standard readouts

```
snn.readouts.MeanVoltage(*, source, classes, name, tau=2 * snn.ms,
weight=Normal(1.0, 0.1))
snn.readouts.FinalVoltage(*, source, classes, name)
snn.readouts.SpikeCount(*, source, classes, name)
snn.readouts.SpikeRate(*, source, classes, name, duration=None, mask=None,
window="full")
snn.readouts.CumulativePotential(*, source, classes, name)
```

Every constructor returns a `Readout`, which delegates signal attributes and exposes its parameter identifiers. `classes` is the output width. `MeanVoltage` defaults to the legacy COBANet output membrane's 2 ms time constant; alternatives remain explicit authoring choices. `SpikeRate` requires either `duration` in seconds or a `(time, batch)` mask. The only implemented window is `"full"`.

## Dense bindings

```
DenseArrayBinding(input_id, value, source={})
load_dense_array_bindings(path, graph) -> tuple[DenseArrayBinding, ...]
resolve_dense_array_bindings(
    graph, *, bindings=(), inputs=None,
    device="cpu", seed=0, protocol=None,
) -> ResolvedDenseInputs
```

value is a PyTorch tensor. source is JSON-serializable provenance. NPY binds only to a graph with one input; NPZ keys bind by graph input identifier. Direct `ExecutionSpec.inputs` values are converted to in-memory bindings and validated through the same resolver.

The resolved protocol uses schemas `tools/snn.dense-array-binding/v1` and `tools/snn.execution-protocol/v1`. Reserved protocol fields cannot be overridden by caller metadata.

## Event-stream bindings

```
EventStreamBinding(
    input_id, steps, batches, channels,
    steps_count, batch_size, source={},
)
load_event_stream_bindings(path, graph) -> tuple[EventStreamBinding, ...]
resolve_event_stream_bindings(
    graph, *, bindings,
    device="cpu", seed=0, protocol=None,
) -> ResolvedDenseInputs
resolve_input_bindings(
    graph, *, dense_bindings=(), event_bindings=(), inputs=None,
    device="cpu", seed=0, protocol=None,
) -> ResolvedDenseInputs
```

Event bindings support graph inputs with shape `("time", "batch", channels)` and signal type `"spikes"`. Coordinate arrays are one-dimensional integer tensors of equal length. Step coordinates lie in `[0, steps_count)`, batch coordinates in `[0, batch_size)`, and channel coordinates in the declared graph width.

A single-input NPZ uses `steps`, `batches`, `channels`, `steps_count`, and `batch_size`. Multi-input files prefix each key with the input identifier and a period. Typed requests may combine event-stream spike inputs with dense masks or continuous inputs when their time and batch axes agree.

The event schema is `tools/snn.event-stream-binding/v1`; a mixed request uses `tools/snn.mixed-input-bindings/v1`. The protocol records ordering, duplicate rejection, binary materialization, event counts, masks, and file provenance.

## Dataset snapshots and encoders

```
DatasetEncoder(
    kind, duration_ms=None, max_rate_hz=None, seed=0,
)
DatasetSnapshotBinding(
    path, input_id, dataset_id, split, encoder,
    target_id=None,
    feature_key="features", label_key="labels",
    sample_cap=None, shuffle=False, order_seed=0,
)
resolve_dataset_snapshot_binding(
    graph, binding, device="cpu", execution_seed=0,
) -> tuple[ResolvedDenseInputs, tuple[TargetArrayBinding, ...]]
```

The binding uses `schema tools/snn.dataset-snapshot-binding/v1` and currently requires a single spike input shaped (time, batch, channels). Every snapshot contains one-dimensional integer labels. A target id turns the selected labels into a digest-bearing training target; simulation may omit the target id.

`rate_poisson` expects floating features shaped (samples, channels) with finite values in [0, 1]. Each value scales `max_rate_hz`; seeded Bernoulli discretization produces the declared physical duration at graph dt. The maximum rate must keep per-step probability at most one.

`prebinned_spikes` expects binary features shaped (time, samples, channels) and preserves the exact time axis. `event_bin` expects equal-length `event_sample` and `event_channel` integer arrays plus floating `event_time_ms`. It applies left-closed, right-open floor bins, unions collisions into binary spikes, and records retained-event and collision counts.

Selection starts from snapshot sample indices, applies a seed-derived permutation when requested, and then applies the cap. The execution protocol records the snapshot path and SHA-256, dataset identity, split, total and selected sample indices, label/feature keys, batch size, shuffle flag, order seed, encoder parameters and seed, graph timestep, physical duration, and resolved target provenance.

The CLI selects this route with `--dataset-file`, `--dataset-encoder`, `--input-dataset-id`, and `--input-split`. Training also supplies `--dataset-target-id`; `--max-samples`, `--input-shuffle`, `--seed`, `--t-ms`, and `--input-rate` define selection and encoding where applicable. Dataset snapshots cannot be combined with replay or generated-input bindings.

Next: Training recipes and graph-native learning

# Training recipes and graph-native learning

14 August 2026

## Contents

1. Developer guide
2. Training is separate from the graph
3. Current boundary
4. API reference

## Developer guide

### Training is separate from the graph

`TrainSpec` describes standard learning choices without embedding a training loop in graph structure. It refers to named outputs and parameters in one network.

```
from tools.snnlang import training

recipe = training.TrainSpec(
    objectives=[training.CrossEntropy(
        prediction=readout,
        target="digit",
    )],
    parameter_groups=[training.ParameterGroup(
        name="feedforward",
        parameters=readout.parameters,
        lr=1e-3,
    )],
    optimizer=training.AdamW(weight_decay=1e-4),
    epochs=20,
)

bundle = snn.compile(net, training=recipe)
```

The recipe vocabulary includes objectives, named parameter groups, learning rates, frozen parameters, optimizer settings, regularizers, stop-gradient boundaries, epoch count, gradient clipping, and surrogate configuration. Every graph parameter must belong to exactly one group. Trainable groups require a positive finite learning rate; frozen groups require zero. Compilation records canonical resolved trainable and frozen sets plus a per-parameter learning-rate map so backends never infer ownership from naming conventions.

### Current boundary

Training recipes compile, and a narrow one-layer MNIST PING recipe can be translated into the legacy trainer. The typed graph API executes deterministic minibatch AdamW trajectories for cross-entropy and spike-budget objectives through named trainable/frozen groups. Named input and target files retain their digests in the execution protocol; seed-derived epoch permutations and checkpointed batch position support exact mid-epoch CPU resume. Requests never fall back silently to legacy execution.

Deterministic initialization, differentiable-reachability checks, recurrent trainability, variable-rate protocols, spike-budget regularization, selected and final checkpoints, optimizer-state replay, and exact CPU resume are implemented. Accelerator stochastic-state support and layered legacy-versus-graph conformance tests remain.

## API reference

### TrainSpec

```
training.TrainSpec(
    objectives,
    parameter_groups,
    optimizer,
    regularizers=(),
    stop_gradients=(),
    epochs=1,
    gradient_clip=None,
    surrogate=training.FastSigmoid(slope=1.0),
    presentation_duration=200 * snn.ms,
)
```

The specification is data only. `compile` verifies referenced outputs, parameters, regularizer signals, stop-gradient signals, and differentiable routes before writing `training.json`.

The collection's supported surrogate is `training.FastSigmoid(slope=1.0)`. Its slope must be positive and finite. Voltage-gradient dampening is declared per spiking population as `voltage_grad_dampen`; it is also resolved into `training.json` so training provenance contains the complete backward contract. Dampening factors must be positive and finite. The narrow legacy adapter accepts fast-sigmoid slopes and a single shared dampening factor, and rejects richer unsupported combinations explicitly.

Presentation duration is a positive millisecond quantity independent of graph timestep, but it must resolve to an integer number of steps. `SpikeBudgetPenalty` implements the exp022 one-sided quadratic firing-rate ceiling. It converts each population's spike count to a per-presentation population-mean rate in Hz, applies the squared hinge above the ceiling, then averages presentations and layers. This makes the term invariant to batch size, population width, hidden-layer count, and equivalent changes in presentation duration.

Compilation proves a gradient route for every objective and regularizer by walking backward through operations and enabled projections. It intersects the reachable named parameters with the resolved trainable set and respects `StopGradient` boundaries. Frozen-only paths, disabled trainable projections, and barriers with no downstream trainable parameter fail with the exact reachable and trainable sets. Recurrent parameters are treated structurally, so frozen, trainable initialized, trainable zero-initialized, and trainable small-initialized loop variants use the same vocabulary without name-based exceptions.

### Objectives and parameter groups

```
training.CrossEntropy(*, prediction, target, weight=1.0) -> Objective
training.ParameterGroup(parameters, name, lr, frozen=False)
```

`prediction` accepts a signal-like object or identifier. It must resolve to a named graph output. `target` is the external target identifier. Group identifiers are non-empty and unique; groups are non-empty; and every parameter appears exactly once across the groups. Frozen groups use `lr=0`, while trainable groups use a positive finite rate.

### Optimizer and regularization

```
training.AdamW(**config) -> Optimizer
training.UpperRatePenalty(*, signal, threshold, strength) -> Regularizer
training.SpikeBudgetPenalty(*, signals, ceiling_hz, strength) -> Regularizer
training.StopGradient.at(signal) -> StopGradient
training.FastSigmoid(*, slope=1.0) -> Spec
```

Optimizer configuration is serialized without running an optimizer. `SpikeBudgetPenalty` is the canonical multi-layer form; `UpperRatePenalty` is its single-signal compatibility spelling. `StopGradient.at` records a graph boundary by signal identifier.

### Execution support

`snn.compile(net, training=recipe)` validates and serializes the recipe. `tools.snn.execution.train(ExecutionSpec(executor="graph", training=..., inputs=..., targets=...))` performs one update by default; `options={"updates": n}` repeats the same resolved batch for focused trajectory checks. Setting `options={"epochs": n, "batch_size": b, "shuffle": true}` iterates the sample axis with a deterministic permutation per epoch. `TargetArrayBinding` and `load_target_array_bindings` provide named NPY/NPZ targets with source digests. A training bundle authenticates and supplies its own recipe. The result exposes named gradients, optimizer state, selected/final checkpoints, and exact next-batch state without tensor-position mapping.

Next: Runtime state, checkpoints, and provenance



# Runtime state, checkpoints, and provenance

14 August 2026

## Contents

1. Developer guide
2. Runtime state
3. Checkpoints
4. Provenance
5. API reference

## Developer guide

### Runtime state

Runtime state contains the dynamic values required to continue one trajectory: voltages, refractory counters, conductances, projection and input histories, and completed step count. It excludes static parameter values.

A runtime-state signature covers timestep, populations, input shapes, projections, delays, synapses, and state layout. Incompatible state is rejected rather than partially loaded. This supports burn-in followed by a compatible intervention without restarting the circuit.

Runtime-state save, load, validation, and continuation are implemented.

### Checkpoints

Parameter checkpoints and runtime state serve different purposes. A parameter checkpoint describes learned or initialized weights. Runtime state describes where one simulation trajectory currently is. A graph-training checkpoint additionally carries named optimizer state, the completed-update count, CPU stochastic state, exact named accelerator generator states when applicable, the resolved execution protocol, initializer metadata, and graph and training digests.

The graph trainer can write both the final update and the lowest-loss update selected during an invocation. Resume validates the complete named parameter set, shapes, dtypes, recipe identity, protocol, initializer provenance, random backend, and accelerator device topology before restoring parameters, AdamW state, random-number streams, and the next dataset epoch and batch. A partial or positional mapping is rejected. CPU, CUDA, and MPS checkpoints resume only on the same random backend; CUDA requires the exact contiguous device set captured from `cuda:0` onward.

### Provenance

A run should retain the bundle digest, resolved execution protocol, seeds, backend and version, realized initializer statistics, checkpoint identity, and produced artifacts. Dense-array graph runs now emit a versioned execution protocol in `metrics.json`, including source digests, resolved input contracts, dataset metadata, timing, masks, and execution seed. A resumed run must preserve optimizer state, data order, and stochastic streams when exact continuation is claimed.

The bundle is network provenance, not the complete experiment record. Experiment runners still own conditions, orchestration, analysis, figures, and publication.

## API reference

### GraphRuntimeState

```
GraphRuntimeState(
    signature,
    compatibility,
    completed_steps,
    voltages,
    refractory,
    conductances,
    population_histories,
    input_histories,
)
```

Every tensor group is keyed by stable graph identifier. `.detached(device="cpu")` returns a cloned, detached state on the requested device. Static parameters are not included.

### Save, load, and compatibility

```
save_runtime_state(path, state) -> Path
load_runtime_state(path, *, device="cpu") -> GraphRuntimeState
runtime_state_compatibility(plan) -> dict
runtime_state_signature(plan) -> str
```

Runtime state uses schema `tools/snn.graph-runtime-state/v1`. Loading verifies the manifest and tensor payload. Simulation compares the stored signature and compatibility structure with the current graph plan before restoring any state.

### Resume execution

```
result = simulate(spec, runtime_state=previous.runtime_state)
```

A resume request must preserve graph structure, timestep, population sizes, projections, delays, synapses, parameter shapes, batch shape, and state dtypes.

`result.runtime_state.completed_steps` reports the cumulative trajectory length.

### Training checkpoints

```
save_training_checkpoint(path, checkpoint) -> Path
load_training_checkpoint(path, *, device="cpu") -> TrainingCheckpoint
capture_training_rng_state(device) -> tuple[str, dict[str, Tensor]]
restore_training_rng_state(checkpoint, device) -> None
legacy_parameter_map_v1(graph) -> dict[str, str]
import_legacy_parameters_v1(graph, state_dict) -> ParameterInterchange
export_legacy_parameters_v1(graph, parameters) -> ParameterInterchange
```

Training checkpoints use schema `tools/snn.training-checkpoint/v1` and store a JSON manifest beside a digest-verified compressed tensor payload. Manifest version 2 adds `rng_backend`, an exact accelerator-device inventory, and one authenticated uint8 generator state per device while retaining the CPU generator. Parameters and optimizer tensors are

keyed by stable graph parameter id. The manifest authenticates the graph and training recipes, completed update, resolved execution protocol, realized initialization metadata, optimizer scalars, selected loss, tensor layout, dataset iterator position, and stochastic topology. CPU-only manifest version 1 remains loadable.

CUDA capture uses every state returned by `torch.cuda.get_rng_state_all`; resume requires the available device count to reproduce the exact `cuda:0 ... cuda:N` inventory before any generator is changed. MPS stores exactly one `mps` state. Cross-backend resume, missing or extra states, non-contiguous CUDA ids, malformed RNG tensors, and unavailable MPS restoration fail closed. Training metrics report the checkpoint RNG backend and device names.

Mocked topology fixtures prove schema, inventory, validation, and restore dispatch without allocating hardware. They do **not** prove accelerator numerical determinism or legacy-versus-graph parity; those claims require the publication-device cases in the final conformance campaign.

`ExecutionSpec.checkpoint` resumes graph training from a checkpoint directory. The `save_final_checkpoint` and `save_selected_checkpoint` options persist the final and invocation-selected states. `legacy_parameter_map_v1` provides the explicit one-layer legacy adapter map and fails closed for graphs that cannot be represented without omissions or ambiguity.

Simulation and inference requests also accept a graph training-checkpoint directory. They authenticate the payload and graph digest, require exact parameter names, shapes, and dtypes, and load parameters without restoring optimizer, random-stream, or data-order state. Inference metrics retain the checkpoint format, path, graph and training digests, completed update, and selected loss. A non-directory checkpoint remains the explicit legacy PyTorch state-file route.

Parameter interchange uses schema `tools/snn.legacy-parameter-interchange/v1`. Import and export require the exact six supported one-layer keys, runtime shapes, floating dtypes, and complete graph coverage. The returned provenance records direction, mapping version, and the full semantic map. This is parameter-only interchange: legacy optimizer objects are not relabelled as portable graph-training checkpoints.

### Provenance fields

Graph simulation metrics include device, recording profile, build and simulation timing, runtime-state schema and signature, completed steps, and the resolved execution protocol. Dense file bindings add source paths, SHA-256 digests, array keys, shapes, dtypes, dataset metadata, timing, masks, and execution seed.

Next: Compatibility, status, and extension

# Compatibility, status, and extension

14 August 2026

## Contents

1. Developer guide
2. Compatibility
3. Current support
4. What remains
5. Extending snnlang
6. API reference

## Developer guide

### Compatibility

*snnlang* is additive. Historical commands and experiments use the legacy executor unless they explicitly select the graph executor. Bundles remain data-only, and *tools/snn* does not import the authoring package when replaying them.

Migration requires layered comparisons of structure, parameters, initialization, forward state, gradients, optimizer updates, checkpoints, resumed trajectories, learning curves, downstream measurements, and publication outputs. A successful smoke test does not establish equivalence.

Issue 73 is the active implementation and migration checklist. The independent exp022 gold-star campaign remains outside this documentation work.

### Current support

| Area                 | Status      | Current boundary                                                                                                                   |
|----------------------|-------------|------------------------------------------------------------------------------------------------------------------------------------|
| Graph authoring      | Implemented | Typed populations, inputs, parameters, projections, groups, outputs, and observables.                                              |
| Bundles              | Implemented | Canonical JSON, hashes, manifests, assets, reports, and diagrams.                                                                  |
| Graph simulation     | Implemented | Dense COBA-LIF and leaky-integrator graphs with AMPA/GABA projections.                                                             |
| Arbitrary topology   | Implemented | Named feedforward, recurrent, and feedback projections with integral delays.                                                       |
| Runtime continuation | Implemented | Validated save, load, and continuation of dynamic graph state.                                                                     |
| Readouts             | Implemented | Mean voltage, final voltage, spike count, spike rate, cumulative potential, and valid-time masks execute through graph operations. |
| Input bindings       | Implemented | Dense arrays, valid-time masks, sparse event streams, fixed/categorical Poisson, and portable dense/prebinned/                     |

|                      |                  |                                                                                                                                                                                       |
|----------------------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                      |                  | timestamped-event dataset snapshots emit versioned execution protocols.                                                                                                               |
| Training recipes     | Implemented      | Validated objectives, regularizers, groups, gradient choices, duration, and reachability compile to canonical data.                                                                   |
| Native training      | Core implemented | Deterministic epoch/minibatch AdamW training and versioned named checkpoints support exact CPU resume and accelerator random-state topology; hardware parity remains a campaign gate. |
| Collection migration | Not implemented  | Requires the complete issue 73 equivalence process.                                                                                                                                   |

### What remains

The following work is **not implemented**. Issue 73 tracks it as an active checklist.

### Complete graph and protocol vocabulary

Portable immutable NPZ dataset snapshots now cover feature-scaled rate-Poisson encoding, exact prebinned spikes, and graph-timestep binning of timestamped events. Deterministic selection and target binding support MNIST-like dense and SHD-like event data without a hidden dataset registry or download side effect. The complete collection training vocabulary is implemented: disabled and trainable recurrent variants, initializer metadata, constraints and units, exhaustive parameter groups, gradient choices, spike-budget regularization, variable graph timesteps and presentation durations, differentiable-route validation, and element-level rejection are explicit. Dataset identity, split, source digest and keys, total/selected indices, sample cap, batch size, shuffle behavior, duration, encoder configuration, and execution/order/encoder seeds are recorded in the execution protocol.

### Graph-native training and checkpoints

Deterministic dataset iteration, named digest-bearing target bindings, versioned graph-training checkpoints, selected and final persistence, strict named loading, the one-layer legacy parameter map, and exact mid-epoch CPU optimizer/random-stream/data-order resume are implemented. Checkpoint manifest version 2 also stores the random backend and exact CUDA-device or MPS generator inventory, rejects cross-backend/topology resume, and remains backward-compatible with CPU-only version 1 checkpoints. Mocked topology tests validate this contract; publication-accelerator numerical resume and parity remain unproven until hardware execution. A compact local production matrix now executes MNIST-shaped one-layer PING and SHD-shaped three-layer PING graphs, trains every named parameter in the deep recurrent SHD recipe, and combines categorical variable-rate input with fine-timestep inference. It verifies public output/recording shapes and complete recurrent gradient coverage without downloading datasets. Full dataset trajectories, accelerator parity, and campaign-scale resource/job shapes remain campaign gates.

## Inference and interventions

Portable selected/final graph checkpoint loading for simulation and inference is implemented with exact graph/name/shape/dtype validation and checkpoint provenance in metrics. A versioned, request-local override contract supports Poisson duration and rate plus scaling of named projections. It rejects ambiguous input modes, invalid values, and unknown projections. Timestep replacement recompiles an immutable graph copy rather than mutating runtime state. Inference timestep changes now recompile an immutable graph copy and rebuild physical decay and delay planning. Only generated Poisson bindings are resampled; their physical presentation duration is preserved unless separately overridden. Checkpoints authenticate against the source graph before their same-shaped named parameters load into the effective graph. Dense/event replay, incompatible delays, and runtime-state conversion fail closed. Named hidden-population spike deletion and Poisson-addition interventions are implemented as an ordered, seeded, request-local contract. Intervened spikes feed later zero-delay populations, delayed histories, recordings, and readouts through the ordinary graph schedule without backend callbacks. Graph CLI inference now writes a versioned manifest that inventories the stable names, shapes, and data types in output, recording, and parameter payloads. It binds their content digests to graph, seed, execution protocol, checkpoint, override, intervention, recording, and device provenance; validation fails closed on identity drift or corruption. A derived-inference contract resolves exact public logits and population-spike names into labels, predictions, accuracy, per-presentation per-cell rates, and sparse time/batch/cell rasters while retaining the authenticated source-artifact digest.

## Artifacts and campaigns

Metrics, checkpoints, inference artifacts, and runstore provenance now use versioned schemas. Every newly initialized run stores an explicit **legacy** or **graph** executor. Graph runs require a prefixed graph digest and may record the training digest; legacy runs reject graph identities. Inventory, archive, verification, and restore retain the manifest, while promotion carries executor and graph/training identities into reverse provenance without changing campaign ownership.

- Wire the collection orchestrator’s future graph campaign plan to the explicit runstore fields after the independent legacy campaign is complete.
- Validate resumption and promotion through a complete graph campaign worktree without changing the active publication view prematurely.

## Conformance and migration

The first hand-checkable CPU cases prove exact named parameter tensors and complete E/I spike, membrane, AMPA, and GABA traces for both feedforward-isolated and actively recurrent one-layer PING networks built from one parameter set. Mean-voltage logits agree under the predeclared  $10^{-6}$  absolute and relative CPU tolerance. The first case also fixed the legacy recurrent layer map to its actual one-based names and aligned the **MeanVoltage** default with the legacy 2 ms output membrane.

A four-update backward case makes all six feedforward and recurrent tensors trainable and compares the complete loss trajectory, every final named gradient, the constrained final parameters, and all named AdamW tensors under the same predeclared tolerance. A two-update checkpoint followed by two resumed updates is bit-identical to the uninterrupted

graph trajectory. The fixture applies the legacy trainer’s non-negative projection after each optimizer step, separating optimizer state from the constrained stored parameter value.

Bidirectional parameter interchange now imports and exports the supported legacy state keys with exact coverage, shape, dtype, and mapping-version provenance. Forward conformance is rerun after a graph  $\rightarrow$  legacy  $\rightarrow$  graph round trip. Optimizer interchange remains deliberately excluded because a legacy optimizer object does not satisfy the portable graph checkpoint contract.

A five-sample, two-epoch shuffled dataset case independently reconstructs each seed-derived permutation and uneven minibatch in direct PyTorch. All six update coordinates and losses, plus the final gradient, parameter, and AdamW tensors, conform under the frozen CPU policy. Mid-epoch resume rejects a changed shuffle protocol before restoring state.

The representative production-shaped fixtures add the 784-channel/10-class MNIST contract and the 700-channel/20-class SHD contract. The SHD example is a trainable three-PING hierarchy with exhaustive parameter coverage and a six-population spike budget. Its focused CPU update confirms gradients for feedforward, all recurrent  $E \rightarrow I/I \rightarrow E$  tensors, and the readout. A separate PING fixture recompiles from 0.1 ms to 0.05 ms while preserving presentation duration and sampling categorical rates across three presentations. These are interface and numerical-path gates, not claims about dataset accuracy.

The checked-in `tools/snn.equivalence-policy/v1` freezes the final comparison before campaign evidence is inspected. Topology, parameter identity and initialization, discrete state, checkpoint coordinates and provenance, labels, predictions, rasters, and campaign identity are exact. Only named floating results use the predeclared  $10^{-6}$  absolute and relative tolerance. Learning trajectories, interventions, aggregations, downstream measurements, uncertainty bands, claims, and figures are all in review scope. Changing a tolerance requires a new policy identity rather than editing the frozen decision after seeing results.

A read-only `tools/snn.migration-preflight/v1` report now fails closed unless an immutable legacy campaign, a complete graph campaign with the expected graph and training digests, and passing CUDA or MPS conformance evidence all authenticate against that policy. It neither executes nor activates campaigns. The repository is therefore explicit about missing external evidence instead of treating local fixtures as migration readiness.

- Run the publication-accelerator conformance case and record any limits on numerical determinism.
- After the independent legacy gold-star campaign is complete, run the full `snnlang` campaign under the frozen scientific protocol and compare every result, uncertainty band, claim, and figure.
- Retain both immutable campaigns and require deliberate review before changing the default executor or migrating the publication collection.

## Extending `snnlang`

Add a feature when it represents reusable computation or execution. Keep it in an experiment runner when its meaning depends on one hypothesis or figure.

A capability should include a clear authoring API, versioned serialization, compiler validation, precise diagnostics, a hand-checkable execution fixture, explicit state and

provenance semantics, and compatibility tests. Add an executable example once the feature is mature enough to teach.

Avoid opaque callbacks, access to backend internals, positional checkpoint guesses, and silent fallbacks.

## API reference

### Validation and diagnostics

```
snn.validate_graph(graph) -> ValidationResult
result.raise_for_errors() -> None
```

`ValidationResult` exposes `.diagnostics`, `.errors`, and `.warnings`. Each `Diagnostic` contains severity, code, message, and optional subject; `.line()` renders a stable one-line form.

Compilation raises graph and training errors. Target capability gaps remain diagnostics so a bundle can still describe computation unsupported by the selected backend.

### Executor capability inspection

```
graph_capability_issues(graph) -> list[CapabilityIssue]
plan_graph(graph) -> GraphPlan
```

`CapabilityIssue` identifies the graph element, missing capability, and message. `plan_graph` performs execution-specific topology, shape, polarity, scheduling, and integral-delay validation before constructing a `GraphPlan`.

`GRAPH_CAPABILITIES_V1` is the current machine-readable executor boundary. It lists supported neuron, synapse, operation, connection, recording, delay, and training capabilities.

### Conformance reports

```
policy = ComparisonPolicy(mode="numeric", atol=1e-6, rtol=1e-5)
report = compare_conformance_layers(
    case_id,
    reference,
    candidate,
    policies={"forward": {"logits": policy}},
)
report.require_passed()
write_conformance_report(path, report)
```

Reports use schema `tools/snn.conformance-report/v1`. Each layer and field is named explicitly. Missing fields, extra fields, shapes, dtypes, values, maximum absolute and relative errors, and the applied policy are recorded. Exact comparison is the default; numerical tolerance must be declared for a specific field, and an unused rule is rejected.

`canonical_json_tensor` encodes topology and provenance structures for exact comparison beside numerical tensors.



The final migration contract is stored in `tools/snn/equivalence-policy-v1.json`.

`load_equivalence_policy` authenticates its canonical digest, and `migration_preflight` returns named readiness gates and failures without changing campaign or publication state.

### Inference overrides

```
simulate(ExecutionSpec(
  kind="simulate",
  executor="graph",
  bundle="trained.bundle",
  checkpoint="selected.checkpoint",
  poisson_bindings=(binding,),
  options={"inference_overrides": {
    "duration_ms": 400.0,
    "input_rate_hz": 25.0,
    "projection_scales": {"sensory_ping_I_to_E": 0.5},
  }},
))
```

The contract uses schema `tools/snn.inference-overrides/v1`. Overrides apply after checkpoint loading to one built model only; the graph bundle and checkpoint are not modified. Duration must be a positive integral number of graph timesteps. Rate must be finite and non-negative. Projection scales use exact graph projection identifiers and finite non-negative factors. Duration and rate overrides require generated Poisson bindings, while projection scaling also works with replay bindings. Metrics retain both the requested mapping and its resolved duration, rate, and projection factors.

The command line exposes named scaling with repeatable `--scale-projection ID=FACTOR`. Existing `--t-ms` and `--input-rate` arguments define generated Poisson execution at request construction. `--inference-timestep-ms` recompiles a request-local graph copy, preserving the original Poisson duration while changing its step count. Metrics record source and effective graph digests and the resolved timestep.

### Inference interventions

```
options={"inference_interventions": [
  {
    "kind": "drop_spikes",
    "population_id": "sensory_ping_E",
    "probability": 0.25,
    "seed": 17,
  },
  {
    "kind": "add_poisson_spikes",
    "population_id": "sensory_ping_E",
    "rate_hz": 5.0,
    "seed": 18,
  },
]}
```

The ordered contract uses schema `tools/snn.inference-interventions/v1`. Deletion independently removes each emitted spike with the declared probability. Addition takes the union with a Bernoulli-discretized homogeneous Poisson stream whose probability is `rate_hz * dt_seconds`. Exact population identifiers are required; duplicate kind/target pairs, unknown fields, non-spiking populations, invalid probabilities, and rates above the timestep probability boundary are rejected.

Each intervention uses a seed-derived stream keyed by its list position, kind, population, and absolute execution step. A continued runtime therefore consumes the same intervention samples as one uninterrupted run. The modified spikes enter normal downstream propagation, delay histories, recordings, and readouts. Metrics retain the requested list and resolved per-step probabilities. The CLI preserves list order through repeatable `--intervention drop:POPULATION=PROBABILITY` and `--intervention add:POPULATION=RATE_HZ` arguments.

### Inference artifacts and cache validation

```
manifest = write_inference_artifacts(
    "inference-run", result, graph=graph, seed=17,
)
validate_inference_artifacts(
    "inference-run", graph=graph, seed=17,
)
```

Graph CLI runs persist `recordings.npz`, `outputs.npz`, `parameters.npz`, and `metrics.json` beside `inference-manifest.json`. Schema `tools/snn.inference-artifacts/v1` inventories every NPZ array name, shape, and data type and authenticates each payload by SHA-256. Its graph digest prevents reuse against a different source graph. Its request digest covers the seed, execution protocol, checkpoint, overrides, interventions, recording profile, resolved device, and source/effective graph identities.

`validate_inference_artifacts` verifies the manifest identity, exact file set, payload digests, NPZ inventories, request digest, and optional expected graph and seed. A cache consumer must validate before reuse; paths or directory names are not identities. The standard `accuracy/rate/raster` conversion below consumes these stable named payloads; scientific interpretation remains at the experiment or campaign layer.

## Derived inference products

```
summary = derive_inference_products(
    "inference-run",
    "derived-run",
    logits_id="class_logits",
    labels=labels,
    spike_recordings=("sensory_ping_E.spikes", "sensory_ping_I.spikes"),
)
validate_derived_inference_products(
    "derived-run",
    source_artifact_digest=source_manifest["artifact_digest"],
)
```

Schema `tools/snn.derived-inference/v1` writes exact integer labels and predictions, JSON accuracy and timing, per-presentation per-cell rates in Hz, and sparse raster coordinates for each requested public spike recording. Raster arrays explicitly store zero-based `steps`, `batches`, `cells`, and the original `[time, batch, cells]` shape. Rates divide each presentation's cell counts by the resolved physical duration.

Derivation first validates the source inference cache, then requires floating `[batch, classes]` logits, integral in-range `[batch]` labels, positive protocol duration, and binary `[time, batch, cells]` recordings with the same batch axis. Its own manifest authenticates every derived payload and links it to the source artifact digest. Scientific thresholds and campaign acceptance decisions remain outside this generic conversion.

## Code map

- `tools/snnlang/core.py`: authoring objects and primitive specifications.
- `components.py`: reusable graph-building components.
- `readouts.py` and `ops.py`: standard operations.
- `training.py`: training recipes.
- `compiler.py`: validation and bundle writing.
- `visualize.py`: bundle reports.
- `tools/snn/execution.py`: graph planning and execution.
- `tools/snn/conformance.py`: versioned layered comparison reports.
- `tools/snn/bundle.py`: the narrow legacy adapter.
- `tools/snnlang/tests` and `tools/snn/tests/test_execution.py`: focused conformance fixtures.

# Manuscript figures and captions

20 August 2026






Figure 13: **A** single recurrent  $E \rightarrow I \rightarrow E$  loop simultaneously generates a gamma rhythm and clamps the excitatory firing rate. Free-running activity of the two-population conductance-based network (excitatory pool  $N_E = 1024$ , inhibitory pool  $N_I = 256$ ; canonical biophysical parameters, §5.1) under matched Poisson drive, in two configurations. Each column shows, from top: a wiring schematic, a single-trial spike raster, the excitatory power spectral density (PSD), and the excitatory  $f$ - $I$  curve. **(A)** COBA baseline with the recurrent loop disabled ( $W^{EI} = W^{IE} = 0$ ): input projects to the excitatory (E) population only, with no inhibitory (I) population (schematic). The E spike raster is asynchronous, the Welch PSD of the summed E population shows no gamma-band peak, and the excitatory  $f$ - $I$  curve rises to  $\approx 485$  Hz under the strongest drive tested. **(B)** PING configuration with the loop engaged (schematic:  $E \rightarrow I$  via  $W^{EI}$ ,  $I \rightarrow E$  via  $W^{IE}$ ; no  $I \rightarrow I$  or  $E \rightarrow E$  synapse): the inhibitory (I) population fires synchronous bursts, the E raster forms gamma bands, the PSD shows a discrete peak at  $f_\gamma \approx 41$  Hz, and on axes shared with (A) the E rate is held approximately an order of magnitude lower across two decades of input drive while the I rate rises to  $\approx 80$  Hz. Source: exp023.





**Figure 15: Trained PING matches COBA classification accuracy while operating at an order-of-magnitude lower excitatory firing rate.** Both configurations were trained on MNIST by surrogate-gradient descent (§5.4). Top: representative single-trial rasters of the trained networks: COBA fires densely and asynchronously with the inhibitory population silent, whereas PING fires in gamma bands with synchronous inhibitory bursts (red) above excitatory spikes (black). For visualisation, each raster is an extended 400 ms replay of one digit, twice the 200 ms presentation used for training and quantitative evaluation. Bottom left: test accuracy per epoch, both configurations converging to  $\approx 90\%$ . Bottom right: accuracy–rate frontier traced by sweeping the sample-wise hidden-E rate ceiling (§5.4); each marker shows mean hidden-E firing rate (abscissa) and test accuracy (ordinate) across three independent seeds, with standard-error bars. PING lies above and to the left of COBA across the sweep. At the unpenalised operating point (starred), PING reaches  $\approx 90\%$  at  $\approx 16.6$  Hz, against COBA’s  $\approx 91\%$  at  $\approx 114$  Hz. Source: exp025 rate-attractor analysis in exp024.






Figure 16: **Engaging the recurrent loop at inference reproduces the PING firing-rate reduction with no weight update.** COBA networks trained with seeds 42–44 are evaluated with recurrent E→I coupling scaled from  $ei = 0$  to  $ei = 1$ , without retraining. Top: illustrative seed-42 rasters at loop-off and full strength. Bottom left: across-seed mean excitatory (black) and inhibitory (red) rates; excitation falls approximately 14-fold (from  $\approx 112$  to  $\approx 8$  Hz) as inhibition rises to  $\approx 45$  Hz. Bottom right: mean accuracy falls from  $\approx 91\%$  to  $\approx 43\%$  (a  $\approx 48$  pp cost). Shaded bands show sample SD across seeds. The rate gating appears when the loop is wired in, whereas the accuracy loss reflects the absence of a feedforward compensation learned in the presence of the loop. Source: exp038.



r001


**Figure 17: Releasing the loop weights to gradient descent prunes the rhythm within a single epoch, from every initialisation.** Per-epoch training metrics with the recurrent weights  $W^{EI}$ ,  $W^{IE}$  made trainable under the Dale’s-law clamp, over 50 epochs on MNIST. Lines are the mean of three seeds (42–44); shading is the across-seed range. Conditions differ only in initialisation of the loop weights: canonical PING values (black), zero (red), and  $0.1 \times$  canonical (amber), against a frozen-PING control (grey, dashed). **(A)** Test accuracy: all conditions overlap at  $\approx 84$ – $91\%$ . **(B)** Mean excitatory firing rate: the trainable conditions rise to  $\approx 49$ – $88$  Hz as the loop is dismantled, while the frozen control remains gated near 17 Hz. **(C)** Mean inhibitory firing rate: the trainable conditions collapse to  $\approx 0$  Hz within a few epochs, while the frozen control’s inhibitory rate rises to  $\approx 108$  Hz as its readout trains. **(D)** Lobe–trough rhythmicity contrast: the frozen control holds at  $\approx 1$  while every trainable initialisation drains to  $\approx 0.02$ – $0.11$ . Source: exp049.





r001

Figure 18: **Post-training excitatory rate covaries affinely with gamma frequency across a sweep of inhibitory decay kinetics.** Networks were trained from scratch at each of six values of the GABA decay constant  $\tau_{\text{GABA}} \in \{4.5, 6, 9, 12, 18, 27\}$  ms. Changing  $\tau_{\text{GABA}}$  alters both the realised gamma frequency and the duration and integrated influence of inhibition (§5.4). Top: mean post-training excitatory firing rate against measured  $f_\gamma$ ; markers are per-condition means over three seeds, with error bars ( $\pm$  SD) on both axes. The linear fit  $r_E = -0.7 + 0.285f_\gamma$  passes through every error bar ( $R^2 = 0.997$ ). Bottom: mean test accuracy declines from 91.2% at  $\tau_{\text{GABA}} = 4.5$  ms to 81.9% at 27 ms, a 9.3 percentage-point tradeoff. The sweep establishes covariance with realised frequency, not an independent causal effect of frequency alone. Source: exp041.



r001

Figure 19: **The affine rate law follows from a near-binary per-cycle firing statistic: each excitatory cell contributes at most one spike per gamma cycle.** Excitatory spikes were resolved into (cell, cycle) pairs by assigning each spike to the gamma cycle inferred from peaks of the population inhibitory-burst rate (§5.5). Each panel shows the distribution of spikes per pair (0, 1, 2, or  $\geq 3$ ) at one value of  $\tau_{\text{GABA}}$ . Across the sweep,  $P(0) \approx 75\%$ ,  $P(1) \approx 24\%$ , and the multi-spike fraction ( $\geq 2$ ) stays near  $\approx 1\%$ ; pooled over all conditions, 98.85% of pairs contain at most one spike. Source: exp046.





Figure 20: **The gating is robust to spike deletion but fragile to spike addition, the expected signature of a phase-based code.** PING and COBA networks trained with seeds 42–44 are perturbed at inference without retraining. Left: deletion of a random fraction of emitted spikes. PING retains  $\approx 89\%$  mean accuracy through 80% deletion, close to its unperturbed value. Right: addition of Poisson spikes, expressed relative to each population's baseline rate. PING falls toward chance as off-phase spikes disrupt the rhythm; COBA, having no rhythm to protect, is more tolerant to addition. Lines show across-seed means and shaded bands show sample SD. Source: exp037.



r001

**Figure 21: Two inhibitory-jitter manipulations at the same magnitude that hold the mean inhibitory rate fixed drive the excitatory rate in opposite directions, isolating timing from level.** The trained PING inhibitory spike train is perturbed at inference while the mean per-cell inhibitory rate is held constant. Both arms use the same jitter magnitude,  $\sigma = 14$  ms — only the *kind* of jitter differs. Top: single-trial rasters (E black, I red). Bottom: mean excitatory rate (black) and accuracy (red) versus jitter magnitude  $\sigma$ , with the realised mean inhibitory rate overlaid (grey). Left: per-cell jitter smears each burst into a continuous shunt; the excitatory rate falls to  $\approx 0$  Hz (inhibitory rate  $\approx 105$  Hz) and accuracy falls to chance. Right: cycle-coherent jitter displaces whole bursts while preserving within-burst synchrony; the excitatory rate rises from  $\approx 17$  to  $\approx 73$  Hz (inhibitory rate  $\approx 103$  Hz, matched to the left arm) and accuracy holds high. Both arms are read where the realised inhibitory rate is matched to within a few percent; at larger  $\sigma$  the cycle-coherent excitatory rate climbs further, but the finite trial window truncates the most-displaced bursts and realised inhibition falls, so the strict comparison is anchored here. Identical mean inhibition, opposite excitatory outcome: the gate is the phase structure of inhibition, not its level. Source: exp042.





Figure 22: **The firing-rate reduction is a physical-time property, invariant to the integration timestep over a twentyfold range.** The network was trained and evaluated at matched integration timestep  $\Delta t$  for each value across  $[0.05, 1.0]$  ms (logarithmic abscissa). Left ordinate (black diamonds): post-training mean excitatory rate, confined to a 13.6–20.2 Hz band and non-monotonic in  $\Delta t$ , so finer stepping does not buy a lower rate. Right ordinate (red squares): test accuracy, flat within 2.2 pp (88.2–90.4%). Because both training and inference use the same  $\Delta t$  at each point, the figure tests invariance of the training-plus-inference pipeline, not the generalisation of one trained network to a varied inference step. Source: exp044.



exp048-replot

**Figure 23: A PING network trained on isolated digits classifies a continuous, unsegmented stream whose presentation timing varies from segment to segment.** A single input stream concatenates five MNIST digits, each with its own presentation duration (25–200 ms) and Poisson input rate (10–200 Hz); the network is given no segmentation cue and is not retrained. Top: the five digit thumbnails with their per-segment (duration, rate) and predicted labels; thumbnail opacity indicates input rate. Below: hidden excitatory and inhibitory rasters, showing gamma cycles maintained throughout (sparser under weak drive, denser under strong drive) and the sliding leaky-integrator readout traces. 3 of 5 digits are classified correctly; the two errors occur in the weakest-drive segments and are interpreted against the population curve in Figure 12B. Source: exp048.




Figure 24: **Streaming accuracy has distinct integration-time and encoding-rate evidence floors.** **(A)** Per-segment accuracy across presentation duration  $\tau$  and input rate, averaged over three seeds and 1,200 segments per grid cell. For  $\tau \leq 15$  ms, accuracy does not exceed  $\approx 80\%$  at any input rate; above that floor, diagonal iso-accuracy contours show an approximate dependence on  $\tau \cdot \text{rate}$ . The trained operating point ( $\tau = 200$  ms, 25 Hz) reaches 93%. **(B)** Probability of a correct classification versus encoding rate with both presentation duration and readout window fixed at 200 ms. All points belong to the same psychometric curve. Performance remains at chance through 0.5 Hz, is clearly informative by 2 Hz, and reaches 79.1% at 5 Hz; the dotted line marks the 25 Hz training rate. Thus the Figure 11 error at 200 ms and 10 Hz occurs in a condition with 87.3% population accuracy, above the nonviable encoder regime. For scale,  $\tau = 15$  ms is approximately 0.7 times the canonical gamma period  $T_\gamma \approx 21$  ms, but gamma frequency is not manipulated independently. Source: exp048.

# Training-run guide

11 August 2026

## Contents

1. Abstract
2. Summary
3. Training-run guide
  1. TR-01 — Canonical full-data reference
  2. TR-02 — Activity-ceiling sweep
  3. TR-03 — Inhibitory-timescale sweep
  4. TR-04 — Integration-timestep sweep
  5. TR-05 — Recurrent-initialization sweep
  6. TR-06 — Variable-rate streaming bank
  7. TR-07 — Low-input recruitment sweep
4. Results by training run
  1. TR-01 — Canonical full-data reference
  2. TR-02 — Activity-ceiling sweep
  3. TR-03 — Inhibitory-timescale sweep
  4. TR-04 — Integration-timestep sweep
  5. TR-05 — Recurrent-initialization sweep
  6. TR-06 — Variable-rate streaming bank
  7. TR-07 — Low-input recruitment sweep

---

## Abstract

Exp022 defines the collection’s shared training runs and checkpoint bank. It specifies the motivation, parameterization, output-layer shape, and downstream consumers for seven training-run types comprising 102 cells. The runs span reference models and controlled sweeps over activity ceiling, inhibitory timescale, integration timestep, recurrent initialization, input rate, and feedforward input coupling. Together, they provide the checkpoints used by the collection’s training-dependent experiments.

Every cell saves two identified checkpoints. For MNIST, each epoch is evaluated over three fixed, independently seeded Poisson encodings of the validation split. The best-validation checkpoint minimizes mean validation cross-entropy across those draws, with mean accuracy as a tie-breaker; the final-epoch checkpoint represents the dynamical and parameter state at the end of training. The result rasters in this entry use the final-epoch checkpoint.

---

## Summary

All runs map Poisson-encoded pixels through 1,024 excitatory neurons to ten spiking output LIF neurons. COBA and PING use the same input-weight and readout-weight initialization distributions. COBA disables recurrent E/I coupling; PING adds a  $1024 \rightarrow 256 \rightarrow 1024$  E/I feedback loop and uses stronger backward-pass gradient damping to stabilize training through that recurrent path.

Unless a run-specific table says otherwise, every cell uses the following contract.

| Parameter                         | Default                                  | Meaning                                                                                                                    |
|-----------------------------------|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Dataset                           | MNIST                                    | 784 normalized pixels encoded as independent Poisson channels                                                              |
| Presentation duration             | 200 ms                                   | One static digit per training presentation                                                                                 |
| Integration timestep              | 0.1 ms                                   | 2,000 recurrent updates per presentation                                                                                   |
| Epochs                            | 50                                       | Training horizon for every production cell                                                                                 |
| Seeds                             | 42, 43, 44                               | Three independently initialized cells per configuration                                                                    |
| Minibatch                         | 256                                      | Presentations per optimization step                                                                                        |
| Optimizer learning rate           | $4 \times 10^{-4}$                       | Shared learning rate                                                                                                       |
| Input population                  | 784                                      | One channel per image pixel                                                                                                |
| Excitatory population             | 1,024                                    | Learned stimulus representation                                                                                            |
| Inhibitory population             | 256                                      | PING feedback population; silent when E/I coupling is disabled                                                             |
| $\tau_{\text{AMPA}}$              | 2 ms                                     | Fixed excitatory synaptic decay                                                                                            |
| $\tau_{\text{GABA}}$              | 6 ms                                     | Default inhibitory decay at the gamma operating point                                                                      |
| Input initial-zero fraction       | 0.95                                     | Fraction set to zero at initialization; every entry remains trainable and may regrow                                       |
| Input summed-coupling parent mean | 0.9                                      | Parent-Gaussian mean before lower clamping and fan-in normalization; shared by COBA and PING                               |
| Readout-weight initialization     | $\max(0, \mathcal{N}(1.1206, 0.8350^2))$ | A directly stored lower-clamped Gaussian. Its zero-valued entries remain trainable; COBA and PING use the same initializer |
| E/I loop strength                 | COBA: 0; PING: 1                         | The forward architectural difference under comparison                                                                      |
| Gradient damping                  | COBA: 1; PING: 1,000                     | Backward-pass stabilization for the recurrent PING loop; it does not change forward dynamics                               |



| Parameter                | Default                                                                         | Meaning                                                                                                                                                                                                                                          |
|--------------------------|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Surrogate slope          | 1                                                                               | Spike-gradient surrogate parameter                                                                                                                                                                                                               |
| Default readout          | mem-mean                                                                        | A <b>spiking</b> $1024 \rightarrow 10$ output-LIF layer. At each timestep its pre-reset voltages enter the temporal mean, then emitted spikes subtract the threshold before the next update. These mean voltages—not spike counts—are the logits |
| Stored projection shapes | $784 \times 1024$ ; $1024 \times 256$ ;<br>$256 \times 1024$ ; $1024 \times 10$ | Input $\rightarrow$ E, E $\rightarrow$ I, I $\rightarrow$ E, and E $\rightarrow$ class, in source-to-destination orientation                                                                                                                     |

## Training-run guide

### TR-01 — Canonical full-data reference

The full-data COBA and PING cells are used for headline accuracy. They use the official MNIST training partition with no spike-budget penalty, so the comparison is not affected by the smaller dataset or regularization used in the sweeps. Ten percent of that partition is reserved for checkpoint selection; the official test partition remains untouched during training. This experiment uses these cells directly.

| Key parameter | Value                                     | Why it differs                                         |
|---------------|-------------------------------------------|--------------------------------------------------------|
| Architectures | COBA and PING                             | Provides a feedforward control and recurrent E/I model |
| Training pool | 60,000 official training samples          | 54,000 optimizer-training and 6,000 validation samples |
| Input rate    | 25 Hz maximum-pixel rate                  | Fixed-rate collection baseline                         |
| Spike budget  | Off                                       | Measures unconstrained capacity                        |
| Cells         | 2 architectures $\times$ 3 seeds<br>= 6   | Across-seed comparison for both models                 |
| Readout shape | $1024 \rightarrow 10$ spiking LIF outputs | mem-mean: mean membrane voltage supplies the logits    |

### TR-02 — Activity-ceiling sweep

This run measures the trade-off between accuracy and firing rate as the activity ceiling is tightened. For each presentation, the loss computes the population-mean hidden-E firing rate, applies a one-sided quadratic penalty above the target, then averages the penalties across the minibatch. Quiet presentations therefore cannot offset active presentations. Expressing the

target in hertz and normalising over samples, neurons, duration, and hidden layers makes the intervention comparable across those dimensions. A smaller training pool keeps the multi-seed sweep manageable; only the activity target changes across conditions. Its absolute rates should therefore not be compared directly with the full-data cells. The resulting checkpoints are used by exp024, exp025, exp037, exp038.

| Key parameter                   | Value                                       | Why it differs                                                     |
|---------------------------------|---------------------------------------------|--------------------------------------------------------------------|
| Architectures                   | COBA and PING                               | Direct architecture comparison                                     |
| Training pool                   | 7,000 official training samples             | 6,300 optimizer-training and 700 validation samples                |
| Hidden-E rate target $r_{\max}$ | off, 25, 10, 5, 2.5, 1 Hz                   | Spans unconstrained through severe sparsity                        |
| Penalty strength                | 0.041 when enabled                          | Calibrated for the sample-wise, population-normalized Hz objective |
| Cells                           | $2 \times 6$ settings $\times$ 3 seeds = 36 | Error bars at every frontier point                                 |
| Readout shape                   | 1024 $\rightarrow$ 10 spiking LIF outputs   | mem-mean: mean membrane voltage supplies the logits                |

### TR-03 — Inhibitory-timescale sweep

This run changes  $\tau_{\text{GABA}}$  to test how the inhibitory timescale affects gamma frequency, firing rate, and accuracy. All other scientific settings are held fixed, with 6 ms as the standard condition. The resulting checkpoints are used by exp041, exp042, exp046.

| Key parameter        | Value                                     | Why it differs                                                    |
|----------------------|-------------------------------------------|-------------------------------------------------------------------|
| Architecture         | PING                                      | The manipulated quantity belongs to the recurrent inhibitory loop |
| Training pool        | 7,000 samples                             | Sweep-scale default                                               |
| $\tau_{\text{GABA}}$ | 4.5, 6, 9, 12, 18, 27 ms                  | Moves the inhibitory rhythm across a broad timescale range        |
| Cells                | 6 settings $\times$ 3 seeds = 18          | Across-seed estimate at each decay                                |
| Readout shape        | 1024 $\rightarrow$ 10 spiking LIF outputs | mem-mean: mean membrane voltage supplies the logits               |

### TR-04 — Integration-timestep sweep

This run changes the integration timestep while keeping each presentation at 200 ms. It tests whether the observed dynamics depend on numerical resolution and measures the extra compute required by finer timesteps. The 0.05 ms cells need the large-memory Cambridge request. The resulting checkpoints are used by exp044.

| Key parameter      | Value                                     | Why it differs                                                        |
|--------------------|-------------------------------------------|-----------------------------------------------------------------------|
| Architecture       | PING                                      | Tests the recurrent reference model                                   |
| Training pool      | 7,000 samples                             | Sweep-scale default                                                   |
| $\Delta t$         | 0.05, 0.1, 0.25, 0.5, 1 ms                | Changes numerical resolution while holding 200 ms physical time fixed |
| Steps/presentation | 4,000; 2,000; 800; 400; 200               | Compute and activation memory scale inversely with $\Delta t$         |
| Cells              | 5 settings $\times$ 3 seeds = 15          | Across-seed stability check                                           |
| Readout shape      | 1024 $\rightarrow$ 10 spiking LIF outputs | <b>mem-mean</b> : mean membrane voltage supplies the logits           |

### TR-05 — Recurrent-initialization sweep

This run tests whether training preserves the PING loop or learns a useful loop from weaker initial conditions. Recurrent initialization and trainability change together, while the feedforward network and classifier remain fixed to the PING recipe. The resulting checkpoints are used by exp049.

| Key parameter         | Value                                                                     | Why it differs                                                           |
|-----------------------|---------------------------------------------------------------------------|--------------------------------------------------------------------------|
| Architecture          | PING                                                                      | Manipulates the recurrent loop directly                                  |
| Training pool         | 7,000 samples                                                             | Sweep-scale default                                                      |
| Loop conditions       | frozen PING; trainable PING init; trainable zero init; trainable 0.1 init | Separates built-in dynamics from recurrence learned during task training |
| Trainable projections | $W_{EI}$ and $W_{IE}$ only in trainable conditions                        | The frozen condition is the mechanistic control                          |
| Cells                 | 4 conditions $\times$ 3 seeds = 12                                        | Across-seed comparison                                                   |
| Readout shape         | 1024 $\rightarrow$ 10 spiking LIF outputs                                 | <b>mem-mean</b> : mean membrane voltage supplies the logits              |

### TR-06 — Variable-rate streaming bank

This run trains PING across the input rates used by exp082. One rate is sampled uniformly for each presentation, and the ten output LIF neurons produce class logits from their total spike counts rather than their mean membrane voltages. This keeps the cross-entropy logits dimensionless and gives one additional output spike the same logit increment. The readout weights use a small Gaussian initialization,  $\mathcal{N}(0.05, 0.04^2)$ , lower-clamped at zero and governed by the shared non-negative constraint.

This smaller initialization is required because the decision rule differs from the other runs. Applying their `mem-mean` readout initialization to `spike-count` caused all ten output neurons to fire heavily and almost uniformly whenever the hidden population was active, producing thousands of output spikes at 25 Hz without useful class separation. The generic fan-in-normalized initialization produced the opposite failure: a silent output layer. Bounded full-architecture trials placed  $\mathcal{N}(0.05, 0.04^2)$  between these regimes, with output neurons near threshold at the upper training rates, finite gradients, and no gross initial class imbalance. The value is therefore calibrated for spike-count decoding rather than transferred from the membrane-voltage classifier.

Output firing rates may still be reported as activity measurements. During streaming inference, the output neurons reset at digit boundaries while the hidden PING state continues. The resulting checkpoints are used by `exp082`.

| Key parameter          | Value                                                  | Why it differs                                                                                                                           |
|------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| Architecture           | PING                                                   | Target model for streaming inference                                                                                                     |
| Training pool          | 7,000 samples                                          | Uses the shared sweep-scale training set                                                                                                 |
| Input-rate set         | 0.5, 0.75, 1, 1.5, 2, 3, 5, 7.5, 10, 15, 25 Hz         | Denser sampling within the interval selected by <code>exp080</code>                                                                      |
| Sampling rule          | Uniform categorical, independently per presentation    | Makes rate variation part of the training distribution                                                                                   |
| Readout                | <code>spike-count</code>                               | Hidden E spikes drive ten spiking LIF class neurons; each logit is that class neuron's total spikes over the presentation                |
| Readout initialization | $\mathcal{N}(0.05, 0.04^2)$ , constrained non-negative | Keeps the spiking outputs near threshold at high training rates without the saturation caused by the default <code>mem-mean</code> scale |
| Readout shape          | $1024 \rightarrow 10$ spiking LIF outputs              | Ten class neurons emit and reset throughout the presentation                                                                             |
| Cells                  | 1 recipe $\times$ 3 seeds = 3                          | Checkpoint bank expected by <code>exp082</code>                                                                                          |

## TR-07 — Low-input recruitment sweep

TR-02 asks how changing the activity ceiling affects networks initialized at the standard input coupling. TR-07 asks the complementary question: with the strictest TR-02 ceiling fixed at 1 Hz from the first epoch, can PING recruit its inhibitory loop when the feedforward projection starts weak? It varies the parent mean used to initialize expected summed input

coupling, before lower clamping and fan-in normalization; it does not directly set the mean of the stored synaptic matrix. The training pool, optimizer, recurrent loop, and **mem-mean** readout remain at the reduced-sweep defaults. Exp022 owns all twelve checkpoints, and exp025 aggregates the three seeds at each setting to test recruitment and path dependence.


| Key parameter                     | Value                                                            | Why it differs                                                                                                          |
|-----------------------------------|------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Architecture                      | PING                                                             | Tests recruitment of the recurrent inhibitory loop                                                                      |
| Training pool                     | 7,000 samples                                                    | 6,300 optimizer-training and 700 validation samples                                                                     |
| Epochs                            | 50                                                               | Matches the reduced production standard                                                                                 |
| Input summed-coupling parent mean | 0.05, 0.1, 0.3, 0.9                                              | Varies initial feedforward drive from weak coupling to the shared 0.9 standard before clamping and fan-in normalization |
| Hidden-E rate target              | 1 Hz                                                             | Applies the strictest TR-02 activity ceiling from epoch 0                                                               |
| Parameters held fixed             | PING loop, optimizer, dataset split, and <b>mem-mean</b> readout | Isolates initial feedforward recruitment from the activity-ceiling sweep                                                |
| Cells                             | 4 settings $\times$ 3 seeds = 12                                 | Across-seed estimate for every condition                                                                                |
| Readout shape                     | 1024 $\rightarrow$ 10 spiking LIF outputs                        | <b>mem-mean</b> : mean membrane voltage supplies the logits                                                             |

## Results by training run

Each completed run reports one training-curve figure and one representative seed-42 raster. The figures summarize all configurations and seeds; the raster is a diagnostic example, not an across-seed statistic.

### TR-01 results — Canonical full-data reference

**Run status:** complete · 6/6 cells represented



r001

Figure 25: Training curves for the six full-data reference cells.





Figure 26: Sample raster: canonical PING, seed 42, held-out digit-0 probe.

**TR-02 results — Activity-ceiling sweep**

Run status: complete · 36/36 cells represented



r001

Figure 27: Training curves across both architectures, six spike budgets, and three seeds.




Figure 28: Sample raster: PING with spike budget off, seed 42.


**TR-03 results — Inhibitory-timescale sweep****Run status:** complete · 18/18 cells represented

Figure 29: Training curves across six  $\tau_{\text{GABA}}$  values and three seeds.






Figure 30: Sample raster: PING at  $\tau_{\text{GABA}} = 6$  ms, seed 42.

#### TR-04 results — Integration-timestep sweep

Run status: complete · 15/15 cells represented






Figure 31: Training curves across five integration timesteps and three seeds.

Figure 32: Sample raster: PING at  $\Delta t = 0.1$  ms, seed 42.

**TR-05 results — Recurrent-initialization sweep****Run status:** complete · 12/12 cells represented

r001

Figure 33: Training curves across four recurrent-loop conditions and three seeds.




Figure 34: Sample raster: frozen PING recurrent loop, seed 42.

**TR-06 results — Variable-rate streaming bank**

**Run status:** pending · 0/3 cells trained

**TODO — training curves.** Add the three variable-rate learning curves after the Cambridge jobs complete.

**TODO — sample raster.** Add a seed-42 E/I/output raster at a declared held-out rate, plus low- and high-rate diagnostics if one raster hides a rate-dependent failure.

---

**TR-07 results — Low-input recruitment sweep**

**Run status:** pending · 0/12 cells trained

**TODO — training curves.** Add across-seed mean accuracy and E/I-rate curves for all four input initializations after the Cambridge jobs complete.

**TODO — sample raster.** Add a representative seed-42 raster for each input initialization at a declared held-out MNIST example.

# PING fundamentals

13 May 2026

## Abstract

Strips PING down to its biophysical fundamentals and characterises it *in isolation from any task* — no training, no readout, no loss, just a free-running network driven by Poisson input. The  $E \rightarrow I \rightarrow E$  loop produces gamma at  $\approx 30$  Hz with the standard  $\tau_{\text{AMPA}} + \tau_{\text{GABA}}$  cycle period, and the f-I curves show the loop is dynamic-range compression: PING holds E an order of magnitude below COBA across two orders of magnitude of drive, while COBA saturates near its refractory ceiling.

## Method

The architecture characterised here is sketched atop Figure 1. An input layer drives the excitatory population through  $W_{\text{in}}$ ; the  $E \rightarrow I \rightarrow E$  loop is formed by  $W_{\text{ei}}$  (E to I) and  $W_{\text{ie}}$  (I back to E), with no I→I synapse. Disabling the I→E loop (*ei-strength 0*) recovers the COBA reference; engaging it (*ei-strength 1.5*) produces the gamma rhythm.

The full conductance-based model that produces PING is documented in COBANet this notebook is the empirical companion. Two conditions run on the same network — *ei-strength 0* (loop disabled, the COBA reference) and *ei-strength 1.5* (loop engaged, the PING regime) — each driven by uniform Poisson input fed through  $W_{\text{in}}$  (untrained network). Because PING’s loop clamps the E rate while COBA’s is unclamped, a single input rate can’t show both legibly: the two rasters therefore use **per-condition input rates** — COBA at 5 Hz (a legible  $\approx 24$  Hz async raster), PING at 45 Hz (into gamma,  $f_{\gamma} \approx 40$  Hz). Population spectra are Welch PSDs on the population-mean E trace (one window per trial of length  $T$ , parabolic-interpolated peak; same recipe as exp041 and exp049).

The run scale reports the geometry that actually produced the figures. The two loop conditions (COBA, *ei-strength 0*; PING, *ei-strength 1.5*) are the grid; the raster/PSD input rates are per-condition (COBA 5 Hz, PING 45 Hz) and the free-running f-I panels sweep uniform Poisson drive (2–100 Hz,  $T = 400$  ms).

**Rate response.** The f-I panels of Figure 1 sweep spatially **uniform** Poisson input (all channels at the same rate, no digit structure) on the *untrained, free-running* network, comparing COBA against PING on a shared rate axis — the bare dynamic-range compression of the architecture.

## Results




Figure 35: The architecture and its behaviour, off and on, on the same network. Each column carries its schematic on top — **A** COBA (input→E→output, no I population) and **B** PING (the same plus the recurrent E↔I loop,  $W_{ei}$  down and  $W_{ie}$  up) — directly above the plots it produces. Below each schematic is one combined raster (E black in the lower portion, I red in the upper portion — same axes, no gap) above a bottom row pairing the Welch PSD of the population-mean E trace with the free-running f-I curve (mean per-cell rate vs input rate, E black / I red; each column has its own y-axis — COBA runs to its  $\approx 400+$  Hz ceiling, PING is on a smaller scale so its loop-clamped E and climbing I are legible). Rasters and spectra are on uniform Poisson input (400 ms) at per-condition rates (COBA 5 Hz, PING 45 Hz — see Methods); the f-I curves sweep that drive on the untrained network. All runs are at  $\Delta t = 0.1$  ms. **A** — **COBA** (*ei-strength* 0, loop off): asynchronous E firing, no I activity, no recurrent gamma peak, and an E f-I curve that climbs steeply with input rate and saturates toward the refractory ceiling. **B** — **PING** (*ei-strength* 1.5, loop on): the I population fires a synchronous burst once per cycle and the E raster breaks into vertical bands (the I volley trails each E volley by the AMPA delay); the PSD carries a clean gamma peak (dashed red line;  $f_\gamma$  measured from this raster’s E-population PSD, marked on the plot); and its f-I shows the E rate held to single digits across the whole sweep (note the much smaller y-axis than COBA’s) while inhibition climbs — the loop’s dynamic-range compression. The single E→I→E loop is the only change: it converts asynchronous firing into a gamma rhythm *and* clamps the E rate.




Figure 36: Membrane voltage  $V_E$  (black) of the most active E cell, recurrent loop **off** (COBA, *ei-strength* 0). Driven only by feedforward input, the cell charges toward threshold ( $V_{th} = -50$  mV, faint dashed) and hard-resets to  $V_{reset} = -65$  mV each time it fires — irregular, input-paced spiking with no rhythmic structure. The rhythm-free control for Figure 3a.




Figure 37: Synaptic and leak conductances on the same E cell, COBA mode. Only the excitatory conductance  $g_E$  (black) is active — it steps up with each input spike and decays with  $\tau_{AMPA}$  — while the leak  $g_L$  (faint dotted) is fixed. There is no inhibitory  $g_I$  because the  $I \rightarrow E$  loop is off. All conductances are **non-negative**: they count open channels, not current direction or sign.




Figure 38: Signed synaptic currents into the E cell, COBA mode, with  $I_X^{\text{in}} = -g_X(V - E_X)$  (positive = depolarising). With no inhibition, the only synaptic current is the depolarising excitatory current  $I_E^{\text{in}}$  (black); the leak current (faint) hovers near zero. Compare Figure 3c, where the loop introduces an inhibitory current of the *opposite* sign.




Figure 39: Membrane voltage  $V_E$  (black) of the most active E cell, recurrent loop **on** (PING, *ei-strength 1.5*), same input as 2a. Rhythmic inhibitory bursts now hold the cell below threshold most of the time: each I-burst drags  $V_E$  toward  $E_i = -80$  mV, and the membrane recovers — and can fire — only as the inhibition decays between bursts. The loop has turned the irregular firing of 2a into cycle-gated firing.






Figure 40: Conductances on the same E cell, PING mode. The inhibitory conductance  $g_I$  (red) now dominates — it spikes once per gamma cycle as the synchronous I-burst arrives through  $W_{ie}$ , then decays with  $\tau_{\text{GABA}}$  — while  $g_E$  (black) carries the smaller feedforward input and  $g_L$  (faint) is fixed. All three traces are **non-negative**:  $g_I$  is large and positive, and that is what shunts the cell — it carries no sign of its own.




Figure 41: The load-bearing panel. Signed currents into the E cell, PING mode. The excitatory current  $I_E^{\text{in}} = -g_E(V - E_E)$  (black) is depolarising; the inhibitory current  $I_I^{\text{in}} = -g_I(V - E_I)$  (red) is **negative (hyperpolarising) even though  $g_I$  is positive** (Figure 3b) — the minus sign comes entirely from the driving force ( $V - E_I > 0$ ) whenever  $V$  sits above  $E_i = -80$  mV. The COBA principle made literal: *the sign lives in the driving force, never in the conductance*. The sharp negative pulses are the per-cycle inhibitory kicks that gate the rhythm.




Figure 42: Membrane voltage  $V_I$  (red) of the most active I cell, PING mode. The I cell integrates the excitatory volley from the E population and fires once per gamma cycle, so  $V_I$  tracks the E-burst envelope — ramping up as E cells fire, crossing threshold ( $V_{th} = -50$  mV, faint dashed), resetting, and waiting for the next volley. This single I-spike per cycle delivers the inhibitory burst seen on the E cell in 3b–3c.




Figure 43: Conductances on the I cell, PING mode. The I cell receives **only excitation**:  $g_E$  (black) is the arriving E-spike envelope (delivered via  $W_{ei}$ ) and  $g_L$  (faint) is the fixed leak. There is no inhibitory conductance — the architecture has no I→I synapse — which is exactly why the I population can synchronise into the sharp once-per-cycle bursts that clock the loop.




Figure 44: Signed currents into the I cell, PING mode. With no inhibitory input, only the depolarising excitatory current  $I_E^{\text{in}}$  (black) and a small leak current contribute — the I cell is driven purely up to threshold. Read 3a–3f together and the loop is in cross-section: E spikes ramp  $g_E$  on I (3e–3f) → I fires once per cycle (3d) → that spike delivers the inhibitory burst  $g_I$  on E (3b) → its negative current shuts E down (3c, 3a) →  $g_I$  decays → E refires. That delayed E→I→E loop is PING.

# Accuracy converges, firing rate does not

2 June 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained.

## Abstract

Reads exp022's PING and COBA  $\theta_u = \text{off}$  baselines (three seeds each, 50 epochs) and asks whether the firing rate converges once the accuracy has. It does not, not for COBA. Test accuracy plateaus by  $\approx 15$  epochs in both architectures, but PING's E rate locks to a tight  $\approx 10$  Hz attractor (cross-seed to 0.1 Hz) while COBA's keeps climbing through epoch 50. Accuracy is a point; for COBA, the rate is a manifold the optimiser drifts along at constant accuracy.

## Method

Reads the shared  $\theta_u = \text{off}$  baselines (coba and ping, three seeds each) from the training hub, exp022 (Training), which fixes the recipe (50 epochs, mem-mean readout, no rate regulariser), and plots their per-epoch training history. The question, following exp041 / exp044: once test accuracy has plateaued, does the firing rate also settle? **Converged** means a last-10-epoch slope below 0.1 pp/ep (accuracy) or 0.05 Hz/ep (rate).

## Results




Figure 45: COBA, three seeds. Loss (train solid, test dashed) and **accuracy plateau by  $\approx 15$  epochs**, but the **E rate keeps climbing to  $\approx 143$  Hz and is still rising at epoch 50**. Accuracy has converged, the rate has not.




Figure 46: PING, three seeds. Loss and accuracy plateau by  $\approx 15$  epochs as in COBA, but here the **E rate settles into a tight band near  $\approx 10$  Hz**, converged. (The I rate, dashed, keeps climbing to  $\approx 61$  Hz, driven by the still-growing input weights, the same force that drives COBA's E rate up.) The loop pins the excitatory rate; without it, COBA's drifts.




Figure 47: Test accuracy (left), test cross-entropy on a log axis (middle), and E firing rate (right) vs epoch; three seeds each, COBA red / PING black. Dotted verticals mark each model's accuracy-convergence epoch (first epoch within 1% of final accuracy). Accuracy is flat past  $\approx$  epoch 20, yet **cross-entropy keeps falling well to its right**: COBA's is still dropping at epoch 50. COBA's E rate climbs  $\approx 45 \rightarrow 143$  Hz in lockstep; PING reaches the same low loss early and **stays pinned near  $\approx 10$  Hz**.

## Discussion

The rate climb is what the loss spends to keep gaining confidence. Cross-entropy stops at *certain*, not *correct*:

$$\text{CE} = -\log p_y = \log \left( 1 + \sum_{k \neq y} e^{z_k - z_y} \right)$$

- $z_y, z_k$ : logits for the true class and class  $k$
- $p_y$ : softmax probability of the true class
- $m = z_y - \max_{k \neq y} z_k$ : decision margin

Accuracy needs only the *sign* of  $m$ ; cross-entropy keeps shrinking with the *size* of the gaps. So past the convergence line the argmax is fixed but the loss still falls on validation data by

widening margins, which means scaling logits up. With a mem-mean readout,  $z \approx W_{\text{out}} \cdot$  (E activity), so wider margins cost either weight or spikes. COBA takes the spike route (rate  $\approx 45 \rightarrow 143$  Hz, still climbing); PING sharpens its readout through the loop and holds  $\approx 10$  Hz. The loop buys confidence without the same activity increase; without it, confidence costs spikes.

So the rate doesn't fail to converge: it tracks a loss that never stops rewarding margin. Each cell's per-epoch metrics already record *test\_margin*, *test\_confidence* and *test\_logit\_scale*, so the prediction that COBA's margin rises with its rate while PING's plateaus can be read straight from them.

## Next steps

Figure 3 infers confidence from the rate. The margin, confidence and logit scale that exp022 already logs on the validation split per epoch let us measure it directly:

- Plot per-epoch **margin**  $\langle m \rangle$ , **confidence**  $\langle p_y \rangle$  and **logit scale** vs epoch, COBA vs PING: the direct version of Figure 3's middle panel.
- Overlay each against the E rate to test the lockstep: confidence up with rate for COBA, both flat for PING.
- Confirm the split quantitatively: does COBA's margin keep rising at epoch 50 (slope  $> 0$ ) while PING's plateaus (slope  $\approx 0$ ), matching the cross-entropy and rate slopes here.

# PING locks E rate $\approx 10\times$ below COBA

30 May 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained.

## Abstract

Head-to-head comparison of COBA (recurrent inhibitory loop disabled) against PING (loop active) on MNIST under matched architecture and training recipe. PING locks the hidden E rate to  $\approx 17$  Hz while COBA runs at  $\approx 114$  Hz; accuracy is within a few points across the two, so the loop buys better than an order-of-magnitude per-spike economy. The rate-vs-accuracy frontier traced by sweeping the hidden-E rate ceiling regulariser shows the floor is structural, not a trade-off the optimiser can navigate away.

## Method

**Training recipe (canonical / medium tier):**

| Parameter                                             | Value                                                                                                                          |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Integration timestep $\Delta t$                       | 0.1 ms                                                                                                                         |
| Trial duration $T$                                    | 200 ms                                                                                                                         |
| MNIST training pool (7,000 official-training samples) | 6,300 optimizer-training / 700 validation; downstream inference uses a fixed 1,000-image subset of the official test partition |
| Epochs                                                | 50                                                                                                                             |

Checkpoint-backed rates, rasters, and input-scaling interventions use the final-epoch checkpoint because this experiment characterizes the trained network’s endpoint dynamics, rather than deployment performance of the validation-selected classifier.

Two configurations of the same COBANet architecture, differing only in whether the  $E \rightarrow I \rightarrow E$  inhibitory loop is active. **COBA** (*-ei-strength 0*) disables the loop; excitatory cells drive each other but receive no structured inhibition. **PING** (*-ei-strength 1*) enables the loop, producing pyramidal-interneuron gamma (PING) oscillations at a cadence set by  $\tau_{\text{AMPA}}$  and  $\tau_{\text{GABA}}$ .

**Architecture.**  $N_E = 1024$  excitatory cells,  $N_I = 256$  inhibitory cells, single hidden layer. Input: 784 channels (MNIST pixels), Poisson-encoded at 25 Hz peak rate. Readout: mem-mean (time-averaged E spike vector projected through a trained linear layer  $W_{\text{out}}$ ; see ar006 for the full readout specification). Dale’s law enforced.

**What is trainable.** Only the input weights  $W_{\text{in}}$  ( $784 \times 1024$ , 95% sparse) and the readout  $W_{\text{out}}$  ( $1024 \times 10$ ). The recurrent weights  $W_{ee}$  (fixed at zero, since Börgers-style PING needs no  $E \rightarrow E$  coupling),  $W_{ei}$ , and  $W_{ie}$  are initialised once and held *requires\_grad = False*. The synaptic time constants  $\tau_{\text{AMPA}}$ ,  $\tau_{\text{GABA}}$  are module-level constants. 813k trainable parameters out of 2.4M total.

**Training.** Adam,  $\text{lr} = 4 \times 10^{-4}$ , batch size 256, gradient norm clipped to 1.0. Cross-entropy loss on 10-class MNIST (definition in ar006). The voltage-gradient damping is 1 for COBA and 1000 for PING, where recurrent backpropagation requires stabilisation. Every frontier

condition is trained with three independent seeds (42, 43, 44); plotted points are across-seed means with standard errors.

**Recipe difference.** COBA and PING share  $W_{\text{in}} \sim \mathcal{N}(0.9, 0.09)$  at 95% sparsity and the same directly specified readout initializer. COBA disables the recurrent loop; PING enables it and uses the loop-specific gradient damping.

**Activity regulariser.** To probe the rate axis, the training loss adds a soft upper bound on each presentation’s population-mean hidden-E firing rate:

$$r_b = \frac{1}{N_E T} \sum_{n \in E} z_{bn}, \quad L_{\text{rate}} = \frac{\lambda}{B} \sum_b \text{ReLU}(r_b - r_{\text{max}})^2,$$

with  $r_b$  the population-mean hidden-E firing rate for presentation  $b$  and  $r_{\text{max}}$  its ceiling in hertz. Presentations at or below the ceiling contribute zero. The normalized penalty uses  $\lambda = 0.041$ . We sweep off, 25, 10, 5, 2.5, and 1 Hz, giving twelve  $(\text{model}, r_{\text{max}})$  conditions and 36 trained cells across seeds.

**Rate-floor decomposition.** The affine law  $r_E = p \cdot f_\gamma$  (exp041, exp046) factors the E rate into per-cycle participation  $p$  and gamma frequency  $f_\gamma$ . Both are measured at one explicitly representative final-epoch checkpoint (seed 42) per condition:  $f_\gamma$  from the Welch PSD peak of the E-population trace,  $p$  via I-burst peak detection and per-(cell, cycle) spike counting (style of exp046).

**Basin and landscape probes.** To test basin attractivity, four input-coupling conditions are each trained with seeds 42, 43, and 44 (12 PING networks total), using parent means of 0.05, 0.1, 0.3, and 0.9 for the expected summed  $W_{\text{in}}$  initialization before lower clamping and fan-in normalization ( $r_{\text{max}} = 1$  Hz from epoch 0; Figure 3). Exp022 owns these TR-07 trainings; this experiment aggregates their checkpoints. To map the loss landscape around the operating point, each network trained at the tightest ceiling ( $r_{\text{max}} = 1$  Hz) has its  $W_{\text{in}}$  scaled by a common scalar  $s \in [0.05, 3]$  at inference with all other weights frozen, metrics averaged over the same fixed 1,000-image held-out subset at 24 values of  $s$  (Figures 4–5).



## Results




Figure 48: The headline comparison in one 2x2 frame (rasters, learning, and the accuracy-rate frontier together). **Top:** trained-baseline single-trial rasters on the same MNIST digit 0 input. COBA (*-ei-strength 0*) fires densely and asynchronously at  $\approx 114$  Hz (I silent, loop off); PING (*-ei-strength 1*) fires in gamma bands at  $\approx 17$  ms cadence ( $\approx 17$  Hz per E cell) with synchronous I bursts (red) above E (black), on the same architecture, parameter count, and recipe, with only PING’s recurrent E $\leftrightarrow$ I matrices non-zero. **Bottom left:** validation accuracy per epoch (mean over three seeds); both reach  $\approx 90\%$ , so both learn the task. **Bottom right:** the accuracy-rate frontier across hidden-E rate ceilings (mean  $\pm$  SEM across three seeds at every point). PING sits up-and-left of COBA, the same accuracy at a fraction of the hidden-E rate, with the unpenalised operating points starred and labelled (PING 90% at  $\approx 17$  Hz, COBA 91% at  $\approx 114$  Hz). COBA red, PING black; E black and I red in the rasters. *The headline of this entry: gamma gating buys an order-of-magnitude per-spike economy at matched accuracy.*




Figure 49: Five representative seed-42 PING rate-target checkpoints, 256 test trials each.  $p$  stays in 0.16–0.26 across the entire sweep (the architecture protects the participation gate), while  $f_\gamma$  slides from  $\approx 60$  Hz to  $\approx 18$  Hz as the penalty tightens. The grey dashed  $p \cdot f_\gamma$  curve overlays the measured E rate within 27%; the rate change is entirely in  $f_\gamma$ . PING accuracy holds at 81–90% the whole way; COBA’s collapses from 90% to 63%.




Figure 50: Across-seed mean per-epoch training traces for four input summed-coupling parent means (seeds 42–44,  $r_{\max} = 1$  Hz from epoch 0), one condition per column; shaded bands are SEM. Top: test accuracy. Bottom: test-set E (black) and I (red) firing rates. The comparison tests whether lower initial input drive delays or prevents recruitment of the inhibitory loop. Final mean accuracies: 76.5% / 76.6% / 76.8% / 76.6%; final I rates: 5.6 / 5.8 / 5.6 / 5.6 Hz.




Figure 51: Inference-time  $W_{in}$  scale sweep on the two networks trained under the tightest ceiling ( $r_{max} = 1$  Hz); every  $W_{in}$  weight multiplied by a common scalar  $s$ , all other weights frozen, 24 values of  $s \in [0.05, 3]$ . Top row: CE loss, activity penalty  $L_{rate}$ , total objective CE +  $L_{rate}$ . Bottom row: test accuracy (chance dotted), E rate, I rate. PING black, COBA red. Vertical dashed line at  $s = 1$  marks the trained operating point; dotted line marks  $\approx f^*$ , PING's recruitment cliff. Loss panels clipped at 4; COBA's penalty reaches  $\approx 3$  at  $s = 3$  (rate<sup>2</sup> scaling).




Figure 52: The same 24-point sweep as Figure 4, re-projected with hidden E rate on the x-axis. Filled stars mark each cell's trained operating point ( $s = 1$ ): PING at  $E \approx 4.7$  Hz, COBA at  $E \approx 2.1$  Hz. PING's accuracy reaches its plateau ( $\approx 83\%$ ) just past its trained operating point; COBA climbs slowly and only reaches  $\approx 63\%$  even at  $E \approx 8$  Hz.

# DMFT model

28 May 2026

## Abstract

A mean-field account of exp025's recruitment cliff. In the 4D conductance DMFT the cliff is a Hopf bifurcation of the silent fixed point. With COBANet's cellular and synaptic parameters define the population gain and couplings, while the effective membrane-noise scale is treated as a free sensitivity parameter. At the 4 mV reference value, the Jacobian eigenvalues place the threshold at  $I_{\text{ext}}^* = 0.6$  nA, the crossing pair's imaginary part gives a gamma rhythm at  $f^* \approx 27.6$  Hz set by the synaptic timescales, and a hysteresis sweep shows the onset is supercritical: continuous and reversible.

## Methods

### 1. The 4D DMFT model

#### 1.1 Summary of COBA model.

We start from the COBANet model (ar003 §2): conductance-based E and I membranes, a threshold-reset rule, and three exponential synapses (no E→E; I receives no inhibition):

$$C_m^E \dot{V}^E = -g_L^E(V^E - E_L) - g_e^E(V^E - E_e) - g_i^E(V^E - E_i) \quad (1)$$

$$C_m^I \dot{V}^I = -g_L^I(V^I - E_L) - g_e^I(V^I - E_e) \quad (2)$$

$$s_{t+1} = \mathbb{1}[V \geq V_{\text{th}}], \quad V \leftarrow V_{\text{reset}} \text{ if } s_{t+1} = 1 \text{ or refractory} \quad (3)$$

$$g_{e,t+1}^E = e^{-\Delta t / \tau_{\text{AMPA}}} g_{e,t}^E + W_{\text{in}} s_t^{\text{inp}} \quad (4)$$

$$g_{i,t+1}^E = e^{-\Delta t / \tau_{\text{GABA}}} g_{i,t}^E + W_{\text{ie}} s_t^i \quad (5)$$

$$g_{e,t+1}^I = e^{-\Delta t / \tau_{\text{AMPA}}} g_{e,t}^I + W_{\text{ei}} s_t^e \quad (6)$$

#### 1.2. Continuous-time form with tonic drive.

Recast in continuous time. The synapses (4)–(6) are the exp-Euler form of first-order filters  $\tau \dot{g} = -g + \tau \sum W s$ , used here as ODEs. At a constant input rate  $g_e^E$  (4) settles to a steady mean, so its excitatory current into the E membrane (1) is a near-constant depolarising drive; we replace it by a tonic current  $I_{\text{ext}}$ , the swept control parameter. The E membrane then carries  $I_{\text{ext}}$  in place of  $g_e^E$ :

$$C_m^E \dot{V}^E = -g_L^E(V^E - E_L) - g_i^E(V^E - E_i) + I_{\text{ext}} \quad (7)$$

$$C_m^I \dot{V}^I = -g_L^I(V^I - E_L) - g_e^I(V^I - E_e) \quad (8)$$

Here  $g_i^E$  is the inhibition onto E and  $g_e^I$  the excitation onto I, each a continuous-time exponential filter of the presynaptic spikes:

$$\tau_{\text{AMPA}} \dot{g}_e^I = -g_e^I + \tau_{\text{AMPA}} W^{EI} s^E(t) \quad (9)$$

$$\tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} W^{IE} s^I(t) \quad (10)$$

with  $s^E(t), s^I(t)$  the population spike trains and  $W^{EI}, W^{IE}$  the recurrent weight matrices; (9)–(10) are the continuous forms of (5)–(6).

### 1.3. Homogeneous coupling and population means.

Now resolve the populations: index E cells by  $j \in \{1, \dots, N_E\}$  and I cells by  $k \in \{1, \dots, N_I\}$ . The recurrent drive in (9)–(10) is the presynaptic sum  $W^{EI}s^E = \sum_j W_{kj}^{EI}s_j^E$  (and  $W^{IE}s^I = \sum_k W_{jk}^{IE}s_k^I$ ). Replace each random weight by its population mean,  $W_{kj}^{EI} \rightarrow w^{EI}$  and  $W_{jk}^{IE} \rightarrow w^{IE}$ ; the sums become

$$\sum_j W_{kj}^{EI}s_j^E \rightarrow w^{EI} \sum_j s_j^E = w^{EI}N_E E(t) \quad (11)$$

$$\sum_k W_{jk}^{IE}s_k^I \rightarrow w^{IE} \sum_k s_k^I = w^{IE}N_I I(t) \quad (12)$$

introducing the *population-mean firing rates*

$$E(t) \equiv \frac{1}{N_E} \sum_{j=1}^{N_E} s_j^E(t), \quad I(t) \equiv \frac{1}{N_I} \sum_{k=1}^{N_I} s_k^I(t). \quad (13)$$

A *smooth-rate ansatz* (short-window averaging) treats  $E(t), I(t)$  as continuous, dropping weight heterogeneity and finite-size noise, the shot noise  $\text{Var}[E(t)] \propto E(t)/N_E$  that vanishes only as  $N_E, N_I \rightarrow \infty$ . At finite  $N_E = 1024, N_I = 256$  the residual  $O(N^{-1/2})$  fluctuations smear the Hopf onset and sustain a weak noisy gamma below threshold, both seen in the spiking simulations.

With no cell index left, every E cell sees the same  $g_e^E$  and every I cell the same  $g_e^I$ , collapsing the per-cell conductances to population means. Defining lumped couplings

$$\tilde{W}^{EI} \equiv w^{EI}N_E, \quad \tilde{W}^{IE} \equiv w^{IE}N_I \quad (14)$$

the conductance dynamics become

$$\tau_{\text{AMPA}} \dot{g}_e^I = -g_e^I + \tau_{\text{AMPA}} \tilde{W}^{EI} E \quad (15)$$

$$\tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} \tilde{W}^{IE} I \quad (16)$$

Two equations, down from  $N_E + N_I$ . (The fan-in scale  $\tilde{W}$  folds into  $W^{EI}, W^{IE}$  in 1.6.)

*Running system, end of 1.3: conductances are now two population means; the membrane is still per-cell but sees those means:*

$$C_m^E \dot{V}_j^E = -g_L^E (V_j^E - E_L) - g_i^E (V_j^E - E_i) + I_{\text{ext}}$$

$$C_m^I \dot{V}_k^I = -g_L^I (V_k^I - E_L) - g_e^I (V_k^I - E_e)$$

$$\tau_{\text{AMPA}} \dot{g}_e^I = -g_e^I + \tau_{\text{AMPA}} \tilde{W}^{EI} E$$

$$\tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} \tilde{W}^{IE} I$$

### 1.4. Driving-force linearisation.

The synaptic current is conductance times a *driving force*,  $-g(V - E_{\text{rev}})$ , a  $g$ – $V$  product, hence nonlinear. Freeze  $V$  at rest,  $V_{\text{rest}} = E_L = -65$  mV, *in the driving force only* (leak and

threshold keep their full  $V$ -dependence, handled by the f-I curve in 1.5). Each driving force becomes a fixed voltage gap:

$$\Delta V_{\text{inh}} \equiv V_{\text{rest}} - E_i = -65 - (-80) = 15 \text{ mV} \quad (17)$$

$$\Delta V_{\text{exc}} \equiv V_{\text{rest}} - E_e = -65 - 0 = -65 \text{ mV}$$

The synaptic currents in (7)–(8) then lose their  $V$ -dependence and become proportional to conductance alone:

$$-g_i^E (V_j^E - E_i) \approx -g_i^E \Delta V_{\text{inh}} \quad (18)$$

$$-g_e^I (V_k^I - E_e) \approx -g_e^I \Delta V_{\text{exc}} = +g_e^I \cdot |E_e - V_{\text{rest}}| \quad (19)$$

(inhibition pulls  $V$  down,  $\Delta V_{\text{inh}} = +15$  mV; excitation pushes it up,  $|\Delta V_{\text{exc}}| = 65$  mV). Removing the  $g$ - $V$  coupling reduces COBA to a current-based (CUBA) form; the cost is shunting: with  $V$  fixed we ignore that conductance also lowers the effective time constant ( $\tau_{\text{eff}} = C_m/g_{\text{tot}}$ ).

*Running system, end of 1.4: the synaptic currents are now linear in conductance (no  $V$  left in the driving force):*

$$\begin{aligned} C_m^E \dot{V}_j^E &= -g_L^E (V_j^E - E_L) - g_i^E \Delta V_{\text{inh}} + I_{\text{ext}} \\ C_m^I \dot{V}_k^I &= -g_L^I (V_k^I - E_L) + g_e^I |\Delta V_{\text{exc}}| \\ \tau_{\text{AMPA}} \dot{g}_e^I &= -g_e^I + \tau_{\text{AMPA}} \tilde{W}^{EI} E \\ \tau_{\text{GABA}} \dot{g}_i^E &= -g_i^E + \tau_{\text{GABA}} \tilde{W}^{IE} I \end{aligned}$$

### 1.5. Population rate from an f-I curve.

Under (17)–(19) the membrane equations (7)–(8) read  $C_m \dot{V} = -g_L(V - E_L) + I_{\text{syn}}$ , LIF with a synaptic current. A LIF cell under constant net current  $I$  fires at its f-I rate  $\varphi(I)$ ; replacing each cell's spikes by that rate gives

$$E(t) \approx \varphi_E(I_{\text{eff}}^E(t)), \quad I(t) \approx \varphi_I(I_{\text{eff}}^I(t)) \quad (20)$$

with effective input currents (from (7)–(8) with (17)–(19) substituted)

$$I_{\text{eff}}^E(t) = I_{\text{ext}}(t) - g_i^E(t) \Delta V_{\text{inh}} \quad (21)$$

$$I_{\text{eff}}^I(t) = g_e^I(t) |\Delta V_{\text{exc}}| \quad (22)$$

(I receives only excitation; E receives the drive minus the GABA shunt.) The instantaneous-rate replacement (20) holds only for slow inputs; in reality  $E(t)$  relaxes toward the f-I fixed point on  $\tau_E$ , which we encode explicitly:

$$\tau_E \dot{E} = -E + \Phi_E(I_{\text{ext}} - g_i^E \Delta V_{\text{inh}}) \quad (23)$$

$$\tau_I \dot{I} = -I + \Phi_I(g_e^I |\Delta V_{\text{exc}}|) \quad (24)$$

where  $\Phi_E, \Phi_I$  are the smooth steady-state gain functions (COBANet's LIF f-I curve in the numerics; see Locating the Hopf). Two more equations down, together with (15)–(16), four equations in  $(E, I, g_e^I, g_i^E)$ .



Running system, end of 1.5: a closed 4D rate model in  $(E, I, g_e^I, g_i^E)$ , constants not yet absorbed:

$$\begin{aligned}\tau_E \dot{E} &= -E + \Phi_E(I_{\text{ext}} - g_e^E \Delta V_{\text{inh}}) \\ \tau_I \dot{I} &= -I + \Phi_I(g_e^I |\Delta V_{\text{exc}}|) \\ \tau_{\text{AMPA}} \dot{g}_e^I &= -g_e^I + \tau_{\text{AMPA}} \tilde{W}^{EI} E \\ \tau_{\text{GABA}} \dot{g}_i^E &= -g_i^E + \tau_{\text{GABA}} \tilde{W}^{IE} I\end{aligned}$$

### 1.6. Absorb the driving-force constants.

The prefactors  $\Delta V_{\text{inh}}, |\Delta V_{\text{exc}}|$  in (23)–(24) and the fan-in scalings in (15)–(16) are constants carrying no dynamics; fold them into the couplings:

$$W^{EI} \equiv \tilde{W}^{EI} \cdot |\Delta V_{\text{exc}}|, \quad W^{IE} \equiv \tilde{W}^{IE} \cdot \Delta V_{\text{inh}} \quad (25)$$

and absorb  $|\Delta V_{\text{exc}}|$  into the I-cell argument by redefining  $g_e^I \mapsto g_e^I \cdot |\Delta V_{\text{exc}}|$  (similarly  $g_i^E$ ). The conductances now carry current units and the f-I curves take their argument directly: a change of variables, no dynamics lost.

### 1.7 The 4D system

After 1.1–1.6, the mean-field equations are

$$\tau_E \dot{E} = -E + \Phi_E(I_{\text{ext}} - g_e^E), \quad \tau_I \dot{I} = -I + \Phi_I(g_e^I) \quad (26)$$

$$\tau_{\text{AMPA}} \dot{g}_e^I = -g_e^I + \tau_{\text{AMPA}} W^{EI} E, \quad \tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} W^{IE} I \quad (27)$$

in state  $(E, I, g_e^I, g_i^E)$ . Whether 4D is minimal, or a 2D reduction would do, is settled in the appendix, Is it really 4D?

### 1.8 4D Jacobian

At a fixed point  $(E^*, I^*, g_e^{I^*}, g_i^{E^*})$ :

$$J = \begin{pmatrix} -1/\tau_E & 0 & 0 & -\Phi_E'/\tau_E \\ 0 & -1/\tau_I & \Phi_I'/\tau_I & 0 \\ W^{EI} & 0 & -1/\tau_{\text{AMPA}} & 0 \\ 0 & W^{IE} & 0 & -1/\tau_{\text{GABA}} \end{pmatrix} \quad (28)$$

with  $\Phi_E', \Phi_I'$  evaluated at the fixed-point arguments.

## 2. Locating the Hopf

### 2.1 The Hopf condition and sweep

Below the cliff the network is silent: nudge it and the perturbation dies away. Above the cliff the same nudge grows into a sustained rhythm. The switch is a Hopf bifurcation of the silent fixed point: the smallest drive  $I_{\text{ext}}^*$  at which the fixed point stops damping oscillations and starts amplifying them.

Linear stability makes this precise. Each mode of the linearised system evolves as  $e^{\lambda t}$ , where  $\lambda$  is an eigenvalue of the Jacobian (28): a negative real part decays, a positive one grows. The Hopf is the instant an oscillating mode (a complex-conjugate pair) crosses from the left half-plane to the right ( $\text{Re } \lambda = 0, \text{Im } \lambda \neq 0$ ), so the silent state gives way to a growing oscillation

rather than a static shift. To find it we sweep  $I_{\text{ext}}$ , track the fixed point, and diagonalise  $J$  at each step;  $I_{\text{ext}}^*$  is the first drive where the leading pair reaches the axis (Figure 2). The local analysis holds only if a single pair crosses while the rest stay damped (a simple Hopf); two pairs crossing at once (a double-Hopf) would seed tori the linearisation cannot see.

Timescales:  $\tau_E = 20$ ,  $\tau_I = 5$ ,  $\tau_{\text{AMPA}} = 2$ ,  $\tau_{\text{GABA}} = 6$  ms.

## 2.2 Gain and couplings from COBANet

The cellular parameters and couplings come from COBANet. For  $\Phi$  we use the LIF f-I curve: a cell under white-noise input of mean  $\mu$  and standard deviation  $\sigma_V$  fires at the Siegert rate

$$\varphi(\mu) = \left[ \tau_{\text{ref}} + \tau_m \sqrt{\pi} \int_{(V_{\text{reset}} - \mu_V)/\sigma_V}^{(V_{\text{th}} - \mu_V)/\sigma_V} e^{u^2} (1 + \text{erf } u) du \right]^{-1}, \quad \mu_V = E_L + \mu/g_L \quad (29)$$

with COBANet's  $\tau_m, g_L, V_{\text{th}}, V_{\text{reset}}, \tau_{\text{ref}}$  per population. The couplings are  $W^{EI} = w^{EI} N_E |\Delta V_{\text{exc}}|$  and  $W^{IE} = w^{IE} N_I \Delta V_{\text{inh}}$  (eqs 14, 25): the fan-in normalisation ( $w \mapsto w/N$ ) makes  $w^{EI} N_E, w^{IE} N_I$  the ei-strength values  $s$  and  $rs$  ( $\approx 1$  and  $2$   $\mu\text{S}$ ), times the driving forces (17). With  $\Phi$  in physical units  $I_{\text{ext}}$  is a current in nanoamps. The effective membrane-noise standard deviation  $\sigma_V$  is not derived from the spiking model and is therefore a free sensitivity parameter; 4 mV is the reference value. We rerun the fixed-point, Jacobian, criticality, and relative-onset amplitude analyses at  $\sigma_V \in \{3, 4, 5, 6\}$  mV rather than treating that reference as calibrated.

## 3. Calculating its frequency

At the crossing  $\lambda = \pm i\omega^*$ , so  $f^* = \omega^*/2\pi$  is read from the Jacobian at threshold. To test whether inhibitory decay sets the period, we re-find the Hopf at each  $\tau_{\text{GABA}}$  of exp041's retrained sweep and compare  $f^*$  to the spiking  $f_\gamma$  (Figure 3).

## 4. Classifying sub- or supercritical

### 4.1 The hysteresis sweep

Above the Hopf a limit cycle exists; whether it appears gently or abruptly decides whether exp025's recruitment cliff is the graded, reversible onset that picture assumes. We test it with a hysteresis sweep: step  $I_{\text{ext}}$  quasi-statically up through  $I_{\text{ext}}^*$  and back down, at each step integrating (26)–(27) to steady state from the previous step's end state (so any coexisting cycle is carried along), and record the peak-to-peak amplitude  $A = \max_t E - \min_t E$ .

A *stable* cycle born at threshold makes the rising and falling branches coincide, with  $A$  returning to zero at  $I_{\text{ext}}^*$ : a reversible, supercritical onset. An *unstable* cycle sitting below threshold instead acts as a basin boundary: the silent state jumps to a distant large-amplitude cycle that survives as the drive is lowered back, so the branches split into a hysteresis loop with a bistable window: subcritical (Figure 4).

### 4.2 The cycle waveform

The same integration gives the cycle's shape above onset:  $E$  and  $I$  are near-sinusoidal, with the  $E$  burst leading the  $I$  burst by the round-trip synaptic delay:  $E$  recruits  $I$ ,  $I$  shunts  $E$  a few milliseconds later (Figure 5).

## Results




Figure 53: Summary of the analysis; the detailed panels follow. **A**, the Hopf: one eigenvalue pair crosses into the right half-plane at  $I^* = 0.6$  nA, fixing a gamma rhythm at  $f^* \approx 27.6$  Hz (full plot, Figure 2). **B**, the onset is supercritical and reversible, the up/down branches coinciding (Figure 4). **C**, the predicted frequency falls with  $\tau_{\text{GABA}}$ , tracking the spiking measurement (Figure 3). exp025's recruitment cliff is a supercritical Hopf, set by the synaptic time constants, in a reduction whose inherited cellular and coupling parameters are biophysically grounded and whose free effective-noise scale is sensitivity-tested below.

### Frequency

Sweeping  $I_{\text{ext}}$  and diagonalising  $J$  at each step locates the Hopf at

$$I_{\text{ext}}^* = 0.6 \text{ nA}, \quad \omega^* = 0.173 \text{ rad/ms}, \quad f^* = \frac{\omega^*}{2\pi} \approx 27.6 \text{ Hz},$$

in the PING gamma band at the 4 mV reference value. One complex pair crosses the imaginary axis while the others stay damped, a simple Hopf (Figure 2). The predictive content is the *dependence* on the synaptic timescales: across a  $\tau_{\text{GABA}}$  sweep  $f^*$  tracks the spiking network's gamma qualitatively, not quantitatively (Figure 3).




Figure 54: **The topology is robust, but its quantitative operating point depends on the free effective-noise scale.** Across  $\sigma_V \in \{3, 4, 5, 6\}$  mV, a Hopf is found and classified as supercritical at every value. The crossing frequency remains  $\approx 27.6$  Hz, while  $I_{\text{ext}}^*$  spans 0.6–0.76 nA, the onset fixed point shifts, and the E peak-to-peak amplitude measured at  $I_{\text{ext}}^* + 0.4$  nA falls from 8.3 to 3.7 Hz. The vertical dotted line marks the 4 mV reference analysis used by the detailed figures.




Figure 55: **How to read it.** Each dot is one eigenvalue  $\lambda$  of the Jacobian (28). Its horizontal position is the growth rate  $\text{Re } \lambda$  (negative means that mode decays, positive means it grows), and the dotted line at  $\text{Re } \lambda = 0$  is the stability boundary: everything to its left is damped. Its vertical position is the oscillation frequency  $\text{Im } \lambda$  (zero = a non-oscillating mode, on the real axis). The Jacobian is  $4 \times 4$ , so each drive contributes four dots; sweeping  $I_{\text{ext}}$  (colour, dark→bright) drags them along the curves shown. Follow the upper and lower arms: one complex-conjugate pair lifts off the real axis and marches rightward, touching the boundary at  $\pm i\omega^*$  (cyan circles) when  $I_{\text{ext}}^* = 0.6$  nA. That crossing is the Hopf, where the network tips from damping to amplifying, and the height of the crossing sets the rhythm,  $f^* = \omega^*/2\pi \approx 27.6$  Hz. The other two eigenvalues stay left of the line throughout, so a single oscillation goes unstable: a simple Hopf. (A second pair reaches the axis only at far higher drive, above the recruitment cliff.)




Figure 56: Both fall monotonically with  $\tau_{\text{GABA}}$ : the inhibitory decay is the clock in both. The match is qualitative, not quantitative. The reference mean-field is *flatter* and runs below the spiking network across the sweep, the gap largest at short  $\tau_{\text{GABA}}$  (27.6 vs 59.1 Hz at the canonical 6 ms) and narrowing as  $\tau_{\text{GABA}}$  grows. The reduction captures the mechanism but not the full sensitivity, expected since it drops the spike-synchrony of the E-volley that sharpens the cycle most at short  $\tau_{\text{GABA}}$ .

### Super or subcritical

The rising and falling sweeps coincide (Figure 4): the amplitude grows continuously from zero at  $I_{\text{ext}}^*$  and retraces exactly on the way down, with no hysteresis (loop width 0 nA, branch gap  $2 \times 10^{-6}$ ) and no cycle coexisting with the silent state. This is a supercritical Hopf, the recruitment cliff of exp025. The rising branch obeys the predicted  $A^2 \propto (I_{\text{ext}} - I_{\text{ext}}^*)$  (slope  $1.1 \times 10^{-4}$ ,  $R^2 = 0.999$ ), so  $A \propto \sqrt{I_{\text{ext}} - I_{\text{ext}}^*}$  and  $dA/dI_{\text{ext}}$  diverges at threshold: most of the amplitude appears in a narrow band of drive above  $I_{\text{ext}}^*$ .




Figure 57: Quasi-static up/down ramp of the drive across  $I_{\text{ext}}^*$ . The rising branch (black, drive increasing) and falling branch (red, drive decreasing) coincide: the cycle turns on and off at the same drive, with amplitude growing continuously from zero. No loop, no bistable window: the reversible onset of a supercritical Hopf. (A subcritical onset would show the two branches separating into a hysteresis loop.)

Above onset,  $E$  leads  $I$  by  $\approx 5.2$  ms, the loop delay the 2D reduction omits.




Figure 58:  $E$  (black) and  $I$  (red) over the limit cycle at  $I_{\text{ext}} = I^* + 0.4$  nA. The  $E$  burst leads the  $I$  burst by  $\approx 5.2$  ms:  $E$  recruits  $I$ ,  $I$  shunts  $E$  a few milliseconds later, and the cycle repeats, the loop delay the 2D reduction omits.

## Appendix

### Is it really 4D?

A Hopf gives a closed-loop trajectory, so the long-run motion is planar, so there should be a 2D description. This appendix collects the attempts. Verdict: a 2D *description* exists (a centre manifold), but the *vector field* does not reduce below three.

1. **A Hopf gives planar (two-dimensional) dynamics, so 4D looks suspect.** A limit cycle is a closed loop, traversed with two coordinates (amplitude and phase), so the motion lies in a plane. If it is 2D, a 2D model should exist; steps 3–5 hunt for it.
2. **The geometry confirms the motion is 2D (Figures 6–7).** The four variables cycle in loop order ( $E$ , then  $g_e^I$ , then  $I$ , then  $g_i^E$ , each lagging the last, Figure 6). Projected onto every variable pair (Figure 7), the cycle is one closed loop on a thin 2D sheet, a *centre manifold* (the loop is a 1D curve on it). Only  $(E, g_e^I)$  nearly collapses to a line (AMPA trails the E rate); the rest enclose real area, so no variable pair can stand in for the sheet.
3. **Route A: the textbook Wilson-Cowan model (slave the conductances).** The standard 2D tool is two rates with instantaneous coupling, the 4D model with infinitely fast synapses. Slave each conductance to its filter's steady value (15)–(16),  $g_e^I = \tau_{\text{AMPA}} W^{EI} E$  and  $g_i^E = \tau_{\text{GABA}} W^{IE} I$ , and substitute into (26):

$$\tau_E \dot{E} = -E + \Phi_E(I_{\text{ext}} - \tau_{\text{GABA}} W^{IE} I), \quad (30)$$

$$\tau_I \dot{I} = -I + \Phi_I(\tau_{\text{AMPA}} W^{EI} E). \quad (31)$$

Its divergence (the Jacobian trace),

$$\frac{\partial \dot{E}}{\partial E} + \frac{\partial \dot{I}}{\partial I} = -\frac{1}{\tau_E} - \frac{1}{\tau_I} < 0, \quad (32)$$

is a negative constant, so Bendixson–Dulac forbids a periodic orbit: no Hopf, for any drive or coupling. It has dropped the round-trip delay (E excites I after  $\tau_{\text{AMPA}}$ , I shunts E after  $\tau_{\text{GABA}}$ ): zero-lag inhibition damps but cannot overshoot. The reduction is valid only if synapses are fast relative to the rhythm, which they are not ( $\tau_{\text{GABA}} \approx 6$  ms is the gamma period's order).

4. **Route B: quasi-steady-state the rates instead.** The dual move: slave the rates,  $E = \Phi_E(I_{\text{ext}} - g_i^E)$  and  $I = \Phi_I(g_e^I)$ , into the conductance equations (27), giving a 2D system in  $(g_e^I, g_i^E)$ :

$$\tau_{\text{AMPA}} \dot{g}_e^I = -g_e^I + \tau_{\text{AMPA}} W^{EI} \Phi_E(I_{\text{ext}} - g_i^E), \quad (33)$$

$$\tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} W^{IE} \Phi_I(g_e^I), \quad (34)$$

with the same negative-constant divergence,

$$\frac{\partial \dot{g}_e^I}{\partial g_e^I} + \frac{\partial \dot{g}_i^E}{\partial g_i^E} = -\frac{1}{\tau_{\text{AMPA}}} - \frac{1}{\tau_{\text{GABA}}} < 0, \quad (35)$$

so no cycle: it rings down (Figure 8). (These rates are the membrane variables, already reduced to an f-I rate.)



5. **Route C: lump into fast and slow timescales.** Slave the two fastest variables, the AMPA conductance ( $\tau_{\text{AMPA}} = 2$  ms) and the I rate ( $\tau_I = 5$  ms), keeping the two slowest  $\{E, g_i^E\}$  ( $\tau_{\text{GABA}} = 6$ ,  $\tau_E = 20$  ms):

$$\tau_E \dot{E} = -E + \Phi_E(I_{\text{ext}} - g_i^E), \quad (36)$$

$$\tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} W^{IE} \Phi_I(\tau_{\text{AMPA}} W^{EI} E). \quad (37)$$

Trace  $-1/\tau_E - 1/\tau_{\text{GABA}} < 0$ : no cycle. The split is forced anyway: the constants interleave,  $\tau_{\text{AMPA}} = 2 < \tau_I = 5 < \tau_{\text{GABA}} = 6 < \tau_E = 20$  ms, so “fast” and “slow” each mix a conductance with a rate.

6. **All three fail for one structural reason.** The network is a pure ring: the single loop  $E \rightarrow g_e^I \rightarrow I \rightarrow g_i^E \rightarrow E$ , no recurrent  $E \rightarrow E$  or  $I \rightarrow I$  and no self-drive, so each variable’s only diagonal Jacobian term is its own decay and every gain  $\Phi'$  sits off-diagonal. Eliminate *any* two variables and the 2D trace is  $-1/\tau_a - 1/\tau_b < 0$ ; Bendixson–Dulac then rules out a cycle. Routes A–C are three of the  $\binom{4}{2} = 6$  ways to pick the kept pair; the runner sweeps all six and none crosses. A 2D model that *does* oscillate has added a destabiliser PING lacks: recurrent excitation or a cubic self-gain, i.e. a positive diagonal term. We do not add one: PING has no  $W^{EE}$  to supply it, and bolting one on would make a self-excitation oscillator (van der Pol / FitzHugh–Nagumo), not PING: a different mechanism for the gamma, not this network’s.

7. **Three dimensions survive.** Slave only the fastest lag, the AMPA conductance  $g_e^I = \tau_{\text{AMPA}} W^{EI} E$  (step 2’s near-degenerate pair), leaving a three-lag ring:

$$\tau_E \dot{E} = -E + \Phi_E(I_{\text{ext}} - g_i^E), \quad (38)$$


$$\tau_I \dot{I} = -I + \Phi_I(\tau_{\text{AMPA}} W^{EI} E), \quad (39)$$

$$\tau_{\text{GABA}} \dot{g}_i^E = -g_i^E + \tau_{\text{GABA}} W^{IE} I, \quad (40)$$

This still Hopfs. Located like the 4D bifurcation (sweep  $I_{\text{ext}}$ , diagonalise the  $3 \times 3$  Jacobian, find the complex-pair crossing), it gives  $I_{\text{ext}}^* = 0.7$  nA and  $f^* = 37$  Hz, both above the 4D values, since dropping the AMPA lag stiffens the loop. The same sweep finds no crossing for either 2D reduction. Figure 8: 4D and 3D sustain the rhythm; all three 2D reductions ring down.

8. **Resolution: the 2D description is the centre manifold, not a coordinate pair.**

The 2D description that exists is the centre manifold, the plane of the two critical, oscillatory eigenvectors, tilted across all of  $(E, I, g_e^I, g_i^E)$ : a plane in the *eigenbasis*, not any coordinate pair. So it is genuinely 2D yet unreachable by dropping two physical variables: a coordinate projection lands on the wrong plane, where the gains go off-diagonal and Bendixson–Dulac kills the cycle (steps 3–6). The *attractor* is a 1D loop on a 2D manifold; the *vector field* does not reduce below three, since a Hopf needs three first-order lags in the  $E \rightarrow I \rightarrow E$  ring to build the destabilising phase. 4D is the natural model, 3D the floor, and the 2D centre manifold where the cycle lives, not a model in the original variables.



exp033-numerics

Figure 59: The four state variables over the limit cycle ( $I_{\text{ext}} = I^* + 0.4$  nA), in loop order  $E \rightarrow g_e^I \rightarrow I \rightarrow g_i^E$ . Each peaks after the one above it:  $g_e^I$  tracks the  $E$  rate almost rigidly (the near-degenerate pair of step 2), then drives  $I$ , which fills  $g_i^E$ , which shunts  $E$ : one round trip of the ring per gamma cycle.




Figure 60: The 4D limit cycle ( $I_{\text{ext}} = I^* + 0.4$  nA) projected onto all six variable pairs. Every projection is one closed loop: the trajectory lives on a 2D centre manifold. The  $(E, g_e^I)$  panel collapses almost to a line: the fast AMPA conductance tracks the E rate, which is why slaving it (the 3D reduction) preserves the dynamics, while the other pairs enclose genuine area and cannot be collapsed.




Figure 61: The reductions tested by simulation:  $g_e^F$  after a small kick at a common drive ( $I_{\text{ext}} = 1$  nA, above every threshold). The 4D model (black,  $f^* = 28$  Hz) and the 3D AMPA-slaved reduction (black dashed,  $f^* = 37$  Hz) both sustain the limit cycle; the 2D rate-slaved reduction (red) rings down to its fixed point: no Hopf, as eq (35) requires.

# PING tolerates 80% dropped spikes but collapses on added noise

30 May 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained. Its complete TR-02 activity frontier contains seeds 42–44 at every COBA and PING rate target. The machine-readable results retain each checkpoint row and report the across-seed mean and SEM for every frontier point.

## Abstract

Perturbs the hidden spike stream of trained PING and COBA networks at inference (drop spikes, add spikes) to ask whether the PING rate floor is dynamical or informational. PING tolerates dropping  $\approx 80\%$  of its emitted spikes (accuracy 89% at that level, from 90% unperturbed) yet collapses once added Poisson noise passes  $\approx 70\%$  of its own baseline rate. COBA is roughly flat to both, holding 90% across the whole add sweep (which reaches only  $\approx 26\%$  of its far higher baseline). The asymmetry, drops forgiven while adds break the gating, is the gamma cycle made visible: a structural feature of the architecture, not a readout-side trade-off.

## Method

All perturbations are applied to the checkpoint selected by validation accuracy. This measures robustness of the selected classifier rather than the final dynamical state reached at epoch 50.

| Parameter                            | Value                                        |
|--------------------------------------|----------------------------------------------|
| Integration timestep $\Delta t$      | 0.1 ms                                       |
| Trial duration $T$                   | 200 ms                                       |
| Evaluation corpus                    | Official MNIST test partition (1000 samples) |
| Evaluated held-out samples per seed  | 1000                                         |
| Baseline training epochs (in exp022) | 50                                           |

The PING and COBA baseline definitions and training recipe are in exp025, where the rate-floor mechanism is also worked out. This entry tests whether the floor is **dynamical** (locked by the cycle period) or **informational** (locked by the readout’s spike-count requirement) by perturbing the hidden spike stream of the trained networks at inference.

**The perturbation.** A per-step callback on the COBANet’s `_hidden_perturb_fn` slot fires every timestep of every trial, with no warm-up, schedule, or exclusion. Trials are  $T = 200$  ms at  $\Delta t = 0.1$  ms  $\rightarrow$  2000 fires per trial, applied across a fixed 1,000-image subset of the official test partition for independently trained seeds 42, 43, and 44. At each timestep  $t$ :

1. *update conductances* from the previous step’s spikes:  $g_e^{(t)} \leftarrow g_e^{(t-1)} \cdot d_{\text{AMPA}} + \tilde{s}^{E,(t-1)} W_{ee} + \text{input}^{(t)} W_{in}$ , with the analogous update for  $g_i^{(t)}$  from  $\tilde{s}^{I,(t-1)} W_{ie}$  and the E $\rightarrow$ I conductance from  $\tilde{s}^{E,(t-1)} W_{ei}$ ;
2. *LIF step* integrates  $V^{(t)}$  and emits raw spike vectors  $\mathbf{s}^{E,(t)} \in \{0, 1\}^{B \times N_E}$ ,  $\mathbf{s}^{I,(t)} \in \{0, 1\}^{B \times N_I}$ ;

3. *perturbation callback* rewrites the raw vectors  $\rightarrow \tilde{\mathbf{s}}^{E,(t)}, \tilde{\mathbf{s}}^{I,(t)}$ ;
4. *record* the perturbed vectors into the spike buffer;
5. *readout accumulator* adds  $\tilde{\mathbf{s}}^{E,(t)}W_{\text{out}}$  to the mem-mean integrator.

Step 1 of timestep  $t + 1$  consumes the perturbed spikes through  $W_{ee}, W_{ei}, W_{ie}$ : a dropped E spike fails to drive I next step and contributes nothing to the readout; an injected I spike adds inhibition next step and counts in the rate metric. E and I get the same mode and level with independent draws.

**Drop mode.** For each (batch, neuron, timestep) slot  $i$ , draw  $u_i \sim \text{Uniform}(0, 1)$  i.i.d. and keep each emitted spike with probability  $1 - p_{\text{drop}}$ :

$$\tilde{s}_i = s_i \cdot \mathbb{1}[u_i \geq p_{\text{drop}}].$$

Drop thins the count fed to both the readout and the next-step conductance update while leaving the E $\rightarrow$ I $\rightarrow$ E loop intact. Sweep  $p_{\text{drop}} \in \{0.0, 0.1, \dots, 1.0\}$ , 11 levels.

**Add mode.** For each slot draw  $u_i \sim \text{Uniform}(0, 1)$  i.i.d. and flip silent slots on at Poisson statistics, phase-independent:

$$\tilde{s}_i = \min(s_i + \mathbb{1}[u_i < r_{\text{add}} \cdot \Delta t / 1000], 1).$$

Sweep  $r_{\text{add}} \in \{0, 2, \dots, 40\}$  Hz per neuron, 21 levels, applied equally to E and I. Because the two architectures sit at very different baselines (COBA  $\approx 155$  Hz per E cell versus PING  $\approx 20$  Hz, a factor of  $\approx 8$ ), a fixed added rate is a much larger relative insult to PING than to COBA, so the right panel of Figure 1 expresses the added rate as a percentage of each model’s own baseline E rate (the architecture-fair view). The per-step RNG is seeded separately from the input encoder, so the Poisson input stream matches the unperturbed baseline. Every seed uses the same 11-point drop and 21-point add grids and the same held-out sample count:  $2 \text{ models} \times 3 \text{ seeds} \times (11 + 21) = 192$  quantitative forward passes. Curves report the across-seed mean and shaded sample SD. Rasters are illustrative seed-42 trials and are not treated as replicated quantitative evidence.

## Results




Figure 62: **Left (drop):** Bernoulli mask, percent of emitted spikes dropped. **Right (add):** Poisson injection as a percent of each model’s own baseline E rate, so the two architectures are insult-matched. The asymmetry is direct: PING (black) holds accuracy to  $\approx 89\%$  at 80% drop but collapses once added noise passes  $\approx 70\%$  of its baseline, while COBA (red) stays at 90% across its whole sweep, which reaches only  $\approx 26\%$  of its far higher baseline. Lines are means across independently trained seeds 42–44; shaded bands show sample SD. The dashed line marks chance.




Figure 63: Illustrative seed-42 PING replayed on the same MNIST digit 0 trial across three drop levels (0, 50, 100%); E (black) above I (red). The gamma cadence persists as spikes are thinned and only vanishes at total drop: dropping spikes thins the train without injecting phase-incoherent activity.




Figure 64: Illustrative seed-42 PING replayed across three added-noise levels (0, 20, 40 Hz per neuron). The gamma banding dissolves into asynchronous firing as the added rate rises, matching the accuracy cliff in the previous figure.





Figure 65: Illustrative seed-42 COBA replayed across the same drop sweep. With no cycle to preserve, dropping spikes just thins a uniform asynchronous mean.



r001

Figure 66: Illustrative seed-42 COBA replayed across the same add sweep. Added spikes blend into COBA's asynchronous mean: no temporal structure to corrupt, just a higher mean rate.



## Switching the loop on at inference cuts E rate $\approx 15\times$

30 May 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained. Its complete TR-02 activity frontier contains seeds 42–44 at every COBA and PING rate target. The machine-readable results retain each checkpoint row and report the across-seed mean and SEM for every frontier point.

### Abstract

Loads a trained COBA network and switches the I-loop on at inference by sweeping *ei\_strength* from 0 to 1. Across independently trained seeds 42–44, the same feedforward weights that fire at  $\approx 112$  Hz without the loop fire at  $\approx 8$  Hz with it engaged, a  $\approx 14\times$  drop with no weight update. Accuracy, though, falls  $\approx 48$  pp (from  $\approx 91\%$  to  $\approx 43\%$ ) as the loop engages, because the readout was never trained with it. PING gating is a post-hoc sparsity knob: the architecture, not the training, supplies the gamma dynamics, but using it well still needs training *with* the loop.

### Method

Each inference intervention starts from the checkpoint selected by validation accuracy. The recurrent-loop replacements and input-rate sweeps therefore probe the selected classifier, not the final-epoch training state.

| Parameter                           | Value                                         |
|-------------------------------------|-----------------------------------------------|
| Integration timestep $\Delta t$     | 0.1 ms                                        |
| Trial duration $T$                  | 200 ms                                        |
| Evaluation corpus                   | Official MNIST test partition (10000 samples) |
| Evaluated held-out samples per seed | 1000                                          |
| Epochs                              | 50                                            |

The PING and COBA baseline definitions and the training recipe are in exp025 this entry runs the COBA  $\rightarrow$  PING I-loop transfer probe at eval time on the trained baselines. (The input-rate sweep / f-I curve material that previously lived here has moved to exp023, the natural home for “architectural response to drive”.)

**Inference-time probe.** The trained COBA baselines (seeds 42–44, activity regulariser off) are loaded and *ei\_strength* (the I-loop gain) is overridden at eval time across 11 values from 0 to 1. Each seed uses the same grid and held-out sample count.  $W_{\text{in}}$  and  $W_{\text{out}}$  load from its COBA checkpoint;  $W^{EI}$  and  $W^{IE}$  are freshly initialised (the COBA checkpoint stores these at zero, so skipping the load leaves a functional I-loop). No retraining. The quantitative curves report the across-seed mean and shaded sample SD. The raster panels show seed 42 as an explicitly illustrative example.

## Results




Figure 67: Switching the recurrent I-loop on *at inference* on a trained COBA network (no retraining;  $W^{EI}/W^{IE}$  freshly wired, since the COBA checkpoint stores them at zero). **Top:** the same feedforward weights fire densely and asynchronously at  $ei = 0$  (COBA) and in gamma bands at  $ei = 1$  (PING); the gamma dynamics come from the inhibitory architecture, not from training. **Bottom left:** across-seed mean E rate falls  $\approx 14\times$  ( $\approx 112 \rightarrow 8$  Hz) as the loop engages while I rises to  $\approx 45$  Hz; the suppression is continuous in loop strength. **Bottom right:** mean accuracy *degrades* without retraining, from the  $\approx 91\%$  COBA baseline to  $\approx 43\%$  at full strength (a  $\approx 48$  pp cost). Shaded bands show sample SD across seeds 42–44. So the architecture supplies the rate-gating for free, but using it well needs training *with* the loop (exp025): the sparsity is architectural, the accuracy is learned.




Figure 68: The illustrative seed-42 transition: trained COBA replayed at six inference-time  $ei\_strength$  values (same trial, same feedforward weights, a fresh I-loop each row). At  $ei = 0$  the asynchronous-dense COBA pattern persists; by  $ei \approx 0.4$  the same weights produce gamma cycles, sharpening toward  $ei = 1$ . The rhythm appears continuously as the loop is wired in, with no retraining at any point.

# E rate is affine in gamma frequency

2 June 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained.

## Abstract

exp037 varied  $\tau_{\text{GABA}}$  at inference and the per-cell E rate tracked the gamma cycle. Does that survive *re-training* at each  $\tau_{\text{GABA}}$ ? Yes. Across  $\tau_{\text{GABA}} \in \{4.5, 6, 9, 12, 18, 27\}$  ms  $\times$  3 seeds,  $r_E = -0.7 + 0.285 \cdot f_\gamma$  with  $R^2 = 0.997$ . The slope is per-cycle E-cell participation; the intercept is a non-rhythmic baseline; accuracy stays at  $\approx 81\text{--}92\%$  across the sweep. The cycle clock constrains what the network can become.

## Method

**Sweep.** Six  $\tau_{\text{GABA}}$  values  $\{4.5, 6, 9, 12, 18, 27\}$  ms  $\times$  three seeds = 18 networks, trained in the shared hub to the gamma standard (50 epochs on MNIST, Adam at  $4 \times 10^{-4}$ , batch 256, mem-mean readout, no spike budget,  $\Delta t = 0.1$  ms,  $T = 200$  ms); only  $\tau_{\text{GABA}}$  varies.

Checkpoint-backed accuracy, rate, and spectral measurements use the same fixed 1,000-image subset of the official MNIST test partition for every cell.

**Measuring  $f_\gamma$ .** For each cell,  $f_\gamma$  is the parabolic-interpolated peak of the Welch PSD on the per-trial population E trace; the fit (Figure 4) uses per-trial peak medians, which avoid the centroid bias of trial-mean PSD peaks. Parabolic interpolation with peak-bin values  $(y_0, y_1, y_2)$ :

$$f_\gamma = \text{freq}[\text{peak}] + \frac{1}{2} \frac{y_0 - y_2}{y_0 - 2y_1 + y_2} \cdot \Delta f, \quad \Delta f = 5 \text{ Hz}.$$

It is needed because the bare 5 Hz bin quantisation would coarsen  $f_\gamma$  across the six conditions; on a well-isolated peak the interpolation error is  $O((\Delta f)^3)$ .

**The predicted law.** The shape  $r_E = a + p \cdot f_\gamma$  is predicted by cycle dynamics, not curve-fitted. Within one cycle of duration  $1/f_\gamma$ , a fraction  $p$  of E cells emits exactly one spike (those nearest threshold when the I shunt drops); the rest are still recovering, so the cyclic per-cell rate is  $p \cdot f_\gamma$ . At long  $\tau_{\text{GABA}}$  the I conductance never fully decays and the cycle dissolves into a tonic bath, leaving a feedforward baseline  $a$  independent of  $f_\gamma$ :


$$r_E = \underbrace{a}_{\text{feedforward baseline}} + \underbrace{p \cdot f_\gamma}_{\text{cyclic contribution}}.$$

We fit this across the 18 cells.

**Convergence.** Accuracy plateaus by  $\approx$  epoch 15 while the E rate keeps climbing through training (Figure 1), so the fit uses the explicitly recorded final-epoch checkpoints and rates. Fitting  $r_E = a + p \cdot f_\gamma$  across the 18 cells is tight, and forcing the intercept through zero barely loosens it, so the law is not an artefact of the free intercept:


| fit            | $a$ (Hz) | $p$ (Hz/Hz) | $R^2$ |
|----------------|----------|-------------|-------|
| affine         | −0.7     | 0.285       | 0.997 |
| through origin | 0        | 0.271       | 0.995 |

## Results




r001

Figure 69: Per-cell accuracy (top) and E rate (bottom) over training, one line per cell. Accuracy plateaus by  $\approx$  epoch 15; the E rate keeps climbing through the 50 epochs, so the final-epoch rates are the ones fit.




r001

Figure 70: Trial-mean Welch PSDs by  $\tau_{\text{GABA}}$ ; dots mark the parabolic-interpolated peak. The peak shifts cleanly from  $\approx 8$  Hz at  $\tau_{\text{GABA}} = 27$  ms to  $\approx 68$  Hz at  $\tau_{\text{GABA}} = 4.5$  ms, with no overlap between adjacent conditions.



r001

Figure 71: One MNIST trial through each network. The cycle period stretches from  $\approx 20$  ms ( $f_\gamma \approx 68$  Hz) at short  $\tau_{\text{GABA}}$  to  $\approx 50$  ms ( $f_\gamma \approx 8$  Hz) at long, the eye and the spectrum agreeing.



r001

Figure 72: The law itself. Top: mean post-training E rate vs  $f_\gamma$ , six clusters  $\times$  three seeds, error bars from seed variance; the affine fit passes through every error bar. Bottom: per-cluster accuracy is flat, so the rate change is not paid in classification.

# Perturbations: gamma gates rates not just mean inhibition

2 June 2026

## Abstract

exp025’s rate gap admits a cheap reading: PING fires less because the I-loop delivers more inhibition. This entry forecloses that reading and identifies *what* about the I-stream is doing the suppressing: qualitatively (rhythm vs mean), and quantitatively (which temporal precision is required). Scaffolded by ar009 §Leg 1 item 2.

## Methods

The interventions use final-epoch checkpoints because they test the endpoint dynamics characterized by exp041, rather than deployment performance of the validation-selected classifier. The source training horizon is read from those checkpoint configurations and retained in the generated provenance.

Each point in the dense intervention sweeps uses the same fixed 1,000-image subset of the official MNIST test partition. The complete condition grids and all three trained seeds are retained; the subset bounds repeated inference while leaving headline checkpoint accuracy to the full official test evaluation reported by exp022.

Pure inference on the exp022-owned TR-02 PING baseline (seed 42,  $\theta_u = \text{off}$ ). exp025 provides the scientific COBA–PING rate-gap comparison; it does not own this checkpoint. For each batch the I-population spike tensor  $\mathbf{s}_{\text{base}}^I \in \{0, 1\}^{T \times B \times N_I}$  is recorded from a baseline forward pass, then an override tensor replaces it in a second pass via the exp037 hidden-perturbation hook. The E-population experiences only the override I-stream through  $W^{IE}$ ; the readout consumes the perturbed E spikes.

Every perturbation only *moves* spikes in time (or, for Poisson, redraws at the matched count) — none adds or removes them — so the mean per-cell I rate is matched to baseline by construction: exactly for phase-shuffle, and to within  $\approx 5\%$  for the jitter families across the range where each result is read. The one exception is cycle-coherent jitter at the largest  $\sigma$ : a Gaussian block offset with  $\sigma = 100$  ms displaces part of each burst past the ends of the fixed presentation window, where it is clamped and lost, so the *realised* I rate falls to 73.9 Hz (32% below the 108.3 Hz baseline). Realised I is therefore plotted on every sweep, and the strict same-mean-inhibition comparison (the compound figure below) is anchored at  $\sigma = 14$  ms, where realised I is still within 5% of baseline on both arms.

Five perturbation families:

1. **Baseline**: no override; trained PING dynamics.
2. **Cycle-coherent jitter**: partition the trial into blocks of length  $1/f_\gamma$  ( $\approx 22.8$  ms at the trained operating point from exp041). For each (trial, block), draw a single Gaussian offset  $\Delta \sim \mathcal{N}(0, \sigma^2)$  and shift every I-spike in that block by  $\Delta$ . Within-burst cross-cell synchrony is preserved exactly; only the *placement* of each burst is perturbed. Sweep  $\sigma \in \{0, 1, 3, 7, 14, 21, 28, 42, 60, 100\}$  ms.
3. **Per-I-cell jitter**: draw an independent Gaussian offset  $\Delta_{b,n,k} \sim \mathcal{N}(0, \sigma^2)$  for *every* I-spike and shift each spike by its own offset. Destroys within-burst cross-cell synchrony while

- keeping the mean per-cell rate; the within-burst counterpart of cycle-coherent jitter. Sweep  $\sigma \in \{0, 0.5, 1, 2, 5, 9, 14, 21, 50\}$  ms.
4. **Phase-shuffle**: per-trial permutation  $\pi_b$  of the time axis applied to all I-cells together:  $\mathbf{s}_{\text{shuf}}^I[t, b, n] = \mathbf{s}_{\text{base}[\pi_b(t), b, n]}^I$ . Preserves cross-cell co-firing within a timestep; destroys all phase structure.
  5. **Rate-matched Poisson**: per-(trial, cell) Bernoulli with  $p = \text{count}_{b,n}/T$ . Destroys both temporal and cross-cell structure; tests the  $g_i$  variance limit.

## Results




Figure 73: Two inference-time perturbations of the trained-PING I-stream, **both holding the mean per-cell I rate fixed at  $\approx 108.3$  Hz**, push the E rate in *opposite* directions, which a mean-inhibition account cannot produce. **Both columns use the same jitter magnitude,  $\sigma = 14$  ms** — only the *kind* of jitter differs. **Left column, smear the bursts**: per-I-cell jitter (realised I 105.2 Hz) scatters the spikes within each burst, destroying synchrony while leaving the mean untouched; the burst dissolves into a continuous shunt, the E rate falls to zero, and accuracy collapses toward chance (18.2% at the Poisson limit). **Right column, move the bursts**: cycle-coherent jitter (realised I 103.2 Hz — within 5% of the left column) displaces each gamma burst bodily but keeps its within-burst synchrony; the I-stream opens gaps and the E rate *rises* from 16.6 Hz at baseline to 73.1 Hz, accuracy holding near 82.4%. Same jitter magnitude, same mean inhibition (both  $\approx 108.3$  Hz), opposite outcome: what gates the E rate is the *timing* of inhibition, the rhythm, not its average level. The cycle-coherent rise continues past the full phase-shuffle level to 146.1 Hz by  $\sigma = 100$  ms (bottom-right sweep), but there the finite trial window truncates the most-displaced bursts and realised I falls 32%, so the strict rate-matched reading is taken at  $\sigma = 14$  ms; see Methods.



## Per-I-cell jitter






Figure 74: Per-I-cell jitter sweep, three seeds. Each spike receives an independent Gaussian offset; mean per-cell I rate is preserved exactly. **E rate (black diamonds, left axis) falls monotonically from baseline** (16.6 Hz), already more than halved to 5.3 Hz by  $\sigma = 0.5$  ms and essentially zero (0 Hz) by  $\sigma \approx 5$  ms, below  $\tau_{\text{GABA}} = 6$  ms. **Accuracy (red squares, right axis) holds at  $\approx 87.5\%$  up to  $\sigma = 0.5$  ms**, then collapses through 73.7% ( $\sigma = 1$ ), 40.8% ( $\sigma = 2$ ) and 13.1% ( $\sigma = 5$ ), bottoming at chance (13.1%) by  $\sigma = 9$  ms. The grey trace is the realised mean I rate, held flat near 108.3 Hz across the sweep: the E collapse happens under matched inhibition. The  $\sigma \rightarrow \infty$  asymptote is the rate-matched Poisson regime: E silent, accuracy at chance.



r001

Figure 75: Single trial replayed at five per-cell jitter levels. At  $\sigma = 0$  the I-bursts are crisp vertical bands. At  $\sigma = 1$  ms the bursts visibly smear into a few-ms-wide cluster and E firing already collapses to the low single digits (per-trial E annotated on each panel; sweep mean 1.2 Hz). At  $\sigma \geq 5$  ms the I-stream looks indistinguishable from a continuous low-variance shunt, and E is silenced. Per-cell jitter doesn't release E; it destroys the bursty structure that gave E its recovery troughs in the first place.

## Cycle-coherent jitter



r001

Figure 76: E rate (black diamonds) and accuracy (red squares) vs cycle-coherent jitter  $\sigma$ , three seeds. As  $\sigma$  grows the displaced bursts open wider gaps and the E rate climbs from baseline (16.6 Hz) *past* the full phase-shuffle level (42.9 Hz, the reference with within-burst structure destroyed) to 146.1 Hz by  $\sigma = 100$  ms, with the sharpest rise near the predicted transition timescale  $\sigma = 1/f_\gamma \approx 22.8$  ms; accuracy declines only gently, holding near 71.7%. The grey trace is the realised mean I rate: it holds within 5% of baseline through  $\sigma \approx 14$  ms — where the E rate has already risen to 73.1 Hz — then droops to 73.9 Hz (32% below baseline) by  $\sigma = 100$  ms, as the finite trial window truncates the most-displaced bursts. The strict same-mean-inhibition comparison is read at the smaller  $\sigma$ , where the rate is matched and the E rise is already unambiguous.




Figure 77: Single trial replayed at five jitter levels ( $\sigma = 0, 7, 14, 28, 100$  ms; seed 42, MNIST digit 0 sample 0). Per-trial E rate annotated on each panel. **The I-bands stay vertical and crisp at every  $\sigma$ :** within-burst synchrony is preserved exactly. What changes is *where* each burst lands: at larger  $\sigma$  the bursts are displaced bodily from their phase-locked positions, opening longer gaps in the I-stream that E fires through, and the E rate climbs accordingly.

## Next steps

**Toroidal (wrapped) jitter, to extend the rate-matched range and disentangle release from truncation.** The strict same-mean-inhibition claim is now anchored at  $\sigma = 14$  ms, where realised I holds within 5% of baseline on both arms and the E rate has already risen to 73.1 Hz — the qualitative result stands on rate-matched ground. Beyond  $\sigma \approx 30$  ms, though, the cycle-coherent E-rate rise and the realised-I droop become confounded: some of the extra E firing is genuine gap-opening, and some is simply less inhibition delivered, because the finite window clamps and loses the most-displaced bursts. Wrapping each block offset modulo the trial length would restore exact spike-count preservation at every  $\sigma$  and separate the two, at the cost of re-injecting a wrapped burst at the opposite trial edge — a phase artifact of its own, so the wrapped sweep is a robustness check, not a replacement. The prediction: if the wrapped E rate still climbs past the phase-shuffle level (42.9 Hz), the release at large  $\sigma$  is real; if it flattens there, part of the 146.1 Hz overshoot at  $\sigma = 100$  ms was the truncation. Either way the anchored rhythm-vs-mean conclusion is unaffected.

# Rate floor stable across a $20\times \Delta t$ sweep

2 June 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained.

## Abstract

The  $\Delta t$  audit asks whether the exp025 headline E rate is a physical (Hz) property of the trained network or an artefact of the integration timestep. The rate stays within a 9–14 Hz band across a  $20\times \Delta t$  sweep, accuracy holds at 90.4–91.4%, and the gamma cycle period in physical ms is invariant. The rate is not fully  $\Delta t$ -independent, though: it rises monotonically with the timestep, from  $\approx 9.2$  Hz at  $\Delta t = 0.05$  ms to  $\approx 13.4$  Hz at  $\Delta t = 1$  ms, so a coarser step inflates the rate while leaving accuracy and cycle period intact.

## Method

Checkpoint-backed rates and rasters use the final-epoch checkpoint, matching the epoch-50 endpoint shown in the training histories.

| Parameter                                             | Value                                                                                                                          |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Integration timestep $\Delta t$                       | 0.05–1.0 ms (swept)                                                                                                            |
| Trial duration $T$                                    | 200 ms                                                                                                                         |
| MNIST training pool (7,000 official-training samples) | 6,300 optimizer-training / 700 validation; downstream inference uses a fixed 1,000-image subset of the official test partition |
| Epochs                                                | 50                                                                                                                             |

The exp022 hub trains one PING per  $\Delta t \in \{0.05, 0.1, 0.25, 0.5, 1.0\}$  ms  $\times$  seed  $\in \{42, 43, 44\}$  = 15 cells; this entry loads them and evaluates. Total physical time  $T = 200$  ms is held constant (step count varies 4000  $\rightarrow$  200). Batch size (

```
cells: (  
  (  
    cell_name: "ping_dt0p05__seed42",  
    dt_ms: 0.05,  
    seed: 42,  
  ),  
  (  
    cell_name: "ping_dt0p05__seed43",  
    dt_ms: 0.05,  
    seed: 43,  
  ),  
  (  
    cell_name: "ping_dt0p05__seed44",  
    dt_ms: 0.05,  
    seed: 44,  
  ),  
  (  
    cell_name: "ping_dt0p1__seed42",
```

```

    dt_ms: 0.1,
    seed: 42,
),
(
    cell_name: "ping_dt0p1__seed43",
    dt_ms: 0.1,
    seed: 43,
),
(
    cell_name: "ping_dt0p1__seed44",
    dt_ms: 0.1,
    seed: 44,
),
(
    cell_name: "ping_dt0p25__seed42",
    dt_ms: 0.25,
    seed: 42,
),
(
    cell_name: "ping_dt0p25__seed43",
    dt_ms: 0.25,
    seed: 43,
),
(
    cell_name: "ping_dt0p25__seed44",
    dt_ms: 0.25,
    seed: 44,
),
(
    cell_name: "ping_dt0p5__seed42",
    dt_ms: 0.5,
    seed: 42,
),
(
    cell_name: "ping_dt0p5__seed43",
    dt_ms: 0.5,
    seed: 43,
),
(
    cell_name: "ping_dt0p5__seed44",
    dt_ms: 0.5,
    seed: 44,
),
(
    cell_name: "ping_dt1__seed42",
    dt_ms: 1.0,
    seed: 42,

```

```

    ),
    (
        cell_name: "ping__dt1__seed43",
        dt_ms: 1.0,
        seed: 43,
    ),
    (
        cell_name: "ping__dt1__seed44",
        dt_ms: 1.0,
        seed: 44,
    ),
),
common: (
    batch_size: 256,
    dales_law: true,
    dataset: "mnist",
    ei_strength: 1.0,
    epochs: 50,
    grad_clip: 1.0,
    hidden_sizes: (1024,),
    input_rate: 25.0,
    input_rate_sampling: "fixed",
    lr: 0.0004,
    max_samples: 7000,
    model: "ping",
    n_hidden: 1024,
    n_in: 784,
    n_inh: 256,
    n_out: 10,
    readout_mode: "mem-mean",
    readout_w_init_mean: 1.12060546875,
    readout_w_init_std: 0.8349609375,
    surrogate_slope: 1.0,
    t_ms: 200.0,
    tau_ampa_ms: 2.0,
    tau_gaba_ms: 6.0,
    trainable_w_ei: false,
    trainable_w_ie: false,
    v_grad_dampen: 1000.0,
    w_in: (0.9, 0.09000000000000001),
    w_in_initial_zero_fraction: 0.95,
    weight_decay: 0.0,
),
registered_differences: (
    dt_ms: (0.05, 0.1, 0.25, 0.5, 1.0),
    seeds: (42, 43, 44),
),

```

) is read from and verified across the consumed checkpoint configs. All other PING training parameters are likewise checked for equality; only integration timestep and seed may differ between cells.

Run inference on that held-out subset; report mean E rate (Hz), accuracy, and a single-trial raster from seed 42 per  $\Delta t$  for visual cycle-period inspection.

## Results






Figure 78: Hidden E rate (black) and test accuracy (red) as  $\Delta t$  varies  $20\times$ ; markers are per- $\Delta t$  means over three seeds. Accuracy holds near 91% while the E rate rises monotonically from  $\approx 9.2$  Hz at  $\Delta t = 0.05$  ms to  $\approx 13.4$  Hz at  $\Delta t = 1$  ms.





r001

Figure 79: Single-trial rasters at each  $\Delta t$ , x-axis in *physical* ms (not steps). All five panels show E (black) and I (red) bursts locked to the same gamma cadence. The cycle physics is  $\Delta t$ -invariant.



r001

Figure 80: Top: test accuracy converges by epoch  $\approx 10$ –15 across all  $\Delta t$ . Bottom: test E rate has *not* converged at epoch 50; every curve is still rising, ordered by  $\Delta t$ . The  $\Delta t$ -dependent rate is a snapshot at epoch 50, not a fixed-point ceiling.

# Near-strict 1-spike-per-cycle ceiling: 98.9% of (cell, cycle) pairs

4 June 2026

## Abstract

exp041's slope  $p \approx 0.20$  was interpreted as “each E cell joins a cycle with  $\approx 20\%$  probability”. That reading assumes the per-cycle spike count is bounded by 1 (an E cell either participates in this cycle or not). This notebook measures that directly: walking through every gamma cycle in the shared 1,000-image held-out evaluation subset and counting how many spikes each E cell actually emits, on all 18 trained checkpoints in exp041's  $\tau_{\text{GABA}}$  sweep.

## Methods

Cycle statistics are evaluated from the final-epoch checkpoints used by exp041, so this experiment audits the same endpoint gamma dynamics. The source training horizon is read from those checkpoint configurations and retained in the generated provenance.

For each of exp041's 18 trained cells ( $6 \tau_{\text{GABA}} \times 3$  seeds):

1. Run inference on the fixed 1,000-image subset of the official MNIST test partition; capture per-trial  $(T, B, N_E)$  and  $(T, B, N_I)$  spike tensors.
2. Detect I-burst times per trial: smooth the population I rate with a 1-ms Gaussian, run scipy peak detection with min-distance set to half the cell's own  $1/f_\gamma$ .
3. Cycle boundaries are the midpoints between consecutive I-burst peaks (first cycle starts at  $t = 0$ , last ends at trial end).
4. For each (cell, cycle, trial), count the number of E spikes within the cycle window.
5. Bucket counts globally into  $\{0, 1, 2, \geq 3\}$  and aggregate by  $\tau_{\text{GABA}}$ .

The cycle anchor is the I-burst: this is the right anchor because the cycle is operationally defined as “the time between one inhibitory blanket and the next”, not as the time between E bursts (which can be silent on a given cycle).

## Results




Figure 81: Distribution of E spike count per gamma cycle per cell, by  $\tau_{\text{GABA}}$ , three seeds aggregated. Across **179 million (cell, cycle) pairs**, the architecture is overwhelmingly bimodal: each cell either emits zero spikes in a given cycle ( $\approx 79\%$  of the time) or exactly one ( $\approx 20\%$  of the time). Two-or-more events occur in  $\approx 1.1\%$  of cycles; three-or-more in  $\approx 0.14\%$ . Pooled over the sweep, 98.9% of pairs carry at most one spike.




Figure 82: Per-cell E rate versus measured gamma frequency  $f_\gamma$  across the  $\tau_{\text{GABA}}$  sweep. The busiest cell in each network tracks the one-spike-per-cycle ceiling  $r = f_\gamma$  (max-cell fit  $r = 0.97f_\gamma$ ,  $R^2 = 0.88$ ), while the median cell sits on exp041's shallower  $r \approx 0.20f_\gamma$  participation slope. The ceiling is near-strict: even the most active cell rarely exceeds one spike per cycle.

# Pool-size invariance requires inverse synaptic scaling

14 July 2026

## Abstract

The apparent invariance of pyramidal–interneuron network gamma (PING) firing rate to inhibitory-pool size is a consequence of the simulator’s fan-in normalization, not independence from interneuron count. Excitatory cells are denoted E and inhibitory cells I. Let  $G_{IE}$  denote the expected summed I→E coupling after lower clamping. Dividing by the presynaptic pool size gives realised mean synaptic conductance  $j_{IE} = \frac{G_{IE}}{N_I}$ . We vary  $N_I$  under paired controls. Rates remain flat when  $G_{IE}$  is fixed and  $j_{IE} \propto \frac{1}{N_I}$ ; when the realised synapse  $j_{IE}$  is fixed, rates change strongly with  $N_I$ . Pool-size invariance therefore requires compensatory inverse scaling of individual synapses.

## Methods

**1. Weight convention.** For a dense I→E matrix with shape  $N_I \times N_E$ , the simulator draws  $X \sim \mathcal{N}(\mu, \sigma^2)$ , lower-clamps it as  $U = \max(0, X)$ , and divides by  $N_I$ . The CLI values are the parent-Gaussian parameters on the summed-coupling scale; the expected summed coupling is  $G_{IE} = \mathcal{E}[U]$ . Thus

$$\mathcal{E}[W_{kj}^{IE}] \approx j_{IE} = \frac{G_{IE}}{N_I}, \quad \mathcal{E}\left[\sum_{k=1}^{N_I} W_{kj}^{IE}\right] \approx G_{IE}. \quad (1)$$

$G_{IE}$  is consequently an expected *summed coupling*, not the conductance of one synapse. An inhibitory volley with active set  $\mathcal{A}$  gives E cell  $j$  the conductance increment

$$\Delta g_j^I = \sum_{k \in \mathcal{A}} W_{kj}^{IE}, \quad (2)$$

where:

- $\mathcal{E}$  denotes expectation over random weight initialization;
- $W_{kj}^{IE}$  is the realised conductance from inhibitory cell  $k$  to excitatory cell  $j$ ;
- $j_{IE}$  is the mean realised conductance of one I→E synapse;
- $G_{IE}$  is the expected sum of all I→E weights arriving at one E cell;
- $N_I$  and  $N_E$  are the inhibitory and excitatory pool sizes;
- $\mathcal{A}$  is the set of inhibitory cells active in a volley; and
- $\Delta g_j^I$  is the resulting inhibitory-conductance increment at excitatory cell  $j$ .

Equation 2 therefore depends on both the realised synapses and the number of participating inhibitory cells.

**2. Paired controls.** We sweep  $N_I \in \{16, 64, 256\}$  under two conventions. In the fixed-summed-coupling arm,  $G_{IE} \in \{1, 2, 4\}$   $\mu\text{S}$  is held fixed, forcing  $j_{IE} \propto \frac{1}{N_I}$ . In the fixed-synapse arm,  $j_{IE} \in \{3.91, 7.81, 15.63\}$  nS is held fixed and the nominal parameter is set to  $G_{IE} = N_I j_{IE}$ . The two arms coincide at the reference pool  $N_I = 256$ .

**3. Simulation.** Untrained dense PING network,  $N_E = 1024$ ,  $\Delta t = 0.1$  ms,  $T = 500$  ms, 8 independent Poisson-input trials per network and 3 network/input seeds per condition. E→I summed coupling is fixed at 1  $\mu\text{S}$ ; input comprises 784 independent 25 Hz Poisson channels. Markers show seed means and error bars  $\pm 1$  standard deviation (SD).

## Results

Fixed summed coupling produces overlapping rate curves. At  $G_{IE} = 2 \mu\text{S}$ , the E rate is 6.01 Hz for  $N_I = 16$  and 6 Hz for  $N_I = 256$ . This is the expected consequence of holding the summed I→E coupling fixed while shrinking each realised synapse as  $\frac{1}{N_I}$ .

Fixed realised synaptic strength gives the opposite result. At  $j_{IE} = 7.81 \text{ nS}$ , increasing  $N_I$  from 16 to 256 changes the E rate from 16.62 to 6 Hz and the I rate from 120.41 to 34.41 Hz. Every tested synaptic strength shows the same pool-size dependence. The direction is mechanistically consistent: more inhibitory cells at unchanged individual strength produce greater population-level inhibition, while the recurrent feedback reduces both E activity and the I activity it recruits.




Figure 83: **Excitatory and inhibitory firing rates across inhibitory-pool size under two I→E scaling controls.** Top: excitatory-cell rate in Hz per cell. Bottom: inhibitory-cell rate in Hz per cell. **(a)** Holding the expected summed I→E coupling  $G_{IE}$  fixed makes the realised synapse  $j_{IE} = \frac{G_{IE}}{N_I}$  shrink as the pool grows. **(b)** Holding  $j_{IE}$  fixed makes summed coupling grow with  $N_I$ . Each curve is one coupling level; markers are means and error bars  $\pm 1$  standard deviation (SD) over 3 seeds, with 8 trials per seed. The controls coincide at the reference pool  $N_I = 256$ . Rates are invariant to pool size only under inverse scaling of individual synapses.

## Conclusion

The network is not intrinsically insensitive to inhibitory-pool size. It is insensitive only along a specific normalization path: individual I→E synapses must scale approximately as  $\frac{1}{N_I}$  so

that expected summed coupling stays fixed. The operative control variable in this dense model is population-level inhibitory drive, jointly determined by pool size, realised synaptic strength, and volley participation. This experiment does not establish that the same inverse scaling holds biologically; it identifies the compensation required for invariance in the model.

# Temporal and spatial evidence limits of trained PING

8 June 2026

## Abstract

A frozen pyramidal-interneuron gamma (PING) network, whose trained weights remain fixed during evaluation, is tested under complementary temporal and spatial reductions of Modified National Institute of Standards and Technology (MNIST) digit evidence. It classifies continuously streamed digits without retraining, but a duration  $\times$  input-rate sweep reveals a failure floor below 15 ms. At fixed 200 ms presentation and readout windows, performance remains at 10-class chance through 0.5 Hz and becomes clearly informative by 2 Hz. Separately, foreground pixels are permanently removed from binarized images and presented to both PING and a width-matched artificial neural network (ANN). PING is competitive at intermediate deletion but reaches chance by retention  $q = 0.02$ . Together, the curves delimit temporal, event-rate, and spatial evidence regimes for a future variable-rate training experiment.

## Methods

### Streaming duration and encoding rate

The trained baseline from the canonical PING experiment contains 1024 excitatory (E) and 256 inhibitory (I) cells. It was trained on one MNIST digit per 200 ms trial using random seeds 42, 43, 44. Each seed identifies an independent training run with a reproducible random initialization and data order. Everything here is **inference-only** at the trained timestep  $\Delta t = 0.1$  ms; the weights are never updated. The two-dimensional sweep averages over all 3 seeds; the single-stream examples use seed 42.

A stream of digits, each shown for  $\tau$  ms, is classified in one forward pass. The *only* change from training is a sliding readout window:

1. **Encode** each digit as a Poisson spike train over  $\tau$  ms across 784 input channels, one per pixel. Each channel generates independent random spikes. The stated encoding rate is the expected number of spikes per second for a full-intensity pixel; lower pixel intensities reduce that rate proportionally.
2. **Concatenate** the per-digit trains into one input stream. At segment index  $k$ , the Poisson rate switches instantaneously at the boundary

$$t_k = k\tau. \quad (1)$$

Here  $t_k$  is the boundary time of segment  $k$ ,  $k$  is the segment index, and  $\tau$  is the duration of each segment.

3. **Run once** through the trained network at the trained  $\Delta t$ , without retraining.
4. **Integrate evidence** in a non-spiking output leaky integrator, one unit per class. A leaky integrator accumulates incoming spikes while gradually discounting older input:

$$v_{\text{out}}(t) = \beta_{\text{out}} v_{\text{out}}(t-1) + \frac{1 - \beta_{\text{out}}}{\Delta t} \mathbf{s}^E(t-1) W_{\text{out}}. \quad (2)$$



Here  $t$  is the discrete timestep;  $\mathbf{v}_{\text{out}}(t)$  is the vector of output-unit states;  $\beta_{\text{out}}$  is their leak factor, the fraction of the previous output state retained for one timestep;  $\Delta t$  is the simulation timestep;  $\mathbf{s}^E(t-1)$  is the E-cell spike vector at the preceding timestep; and  $\mathbf{W}_{\text{out}}$  is the trained E-to-output weight matrix.

5. **Read a sliding window.** Average  $\mathbf{v}_{\text{out}}$  over the trailing  $\tau$ -window and apply a softmax:

$$\text{logits}(t) = \frac{\Delta t}{\tau} \sum_{u=t-w+1}^t \mathbf{v}_{\text{out}}(u). \quad (3)$$

$$p(\text{class}, t) = \text{softmax}(\text{logits}(t)). \quad (4)$$

Here  $\text{logits}(t)$  is the class-evidence vector;  $u$  indexes timesteps in the window;  $\tau$  is the presentation duration;  $w$  is its number of timesteps; and  $p(\text{class}, t)$  is the softmax-normalized class-probability vector. Softmax converts the logits into non-negative class probabilities that sum to one. The readout-window duration is matched exactly to the current digit's presentation duration:

$$T_{\text{readout}} = T_{\text{presentation}} = \tau. \quad (5)$$

Here  $T_{\text{readout}}$  is the duration over which output evidence is averaged,  $T_{\text{presentation}}$  is the time for which the digit is shown, and  $\tau$  is that common duration.

The corresponding window length is

$$w = \frac{\tau}{\Delta t}. \quad (6)$$

Every digit is therefore read over exactly its own presentation duration; readout duration is not varied independently. At training the average ran over the *whole* trial; the trailing matched-duration window is the single change.

6. **Predict per segment** at the end of the digit's  $\tau$ -window according to

$$\hat{c}(t) = \arg \max_c p(\text{class} = c, t). \quad (7)$$

Here  $c$  indexes the 10 digit classes, and  $\arg \max$  selects the class with the largest probability.

The output leak is

$$\beta_{\text{out}} = \exp(-\Delta t / \tau_{\text{out}}). \quad (8)$$

Here  $\tau_{\text{out}}$  is the output-unit time constant, which controls how quickly accumulated output evidence decays, and  $\exp$  denotes the exponential function. The probability trace  $p(\text{class}, t)$  is the network's online class confidence.

The grid uses presentation durations 10 ms, 15 ms, 25 ms, 40 ms, 50 ms, 75 ms, 100 ms, 200 ms and input rates 5 Hz, 10 Hz, 25 Hz, 50 Hz, 100 Hz, 200 Hz per channel. This gives 48 cells with 1200 classified segments per cell.

To resolve the encoding-rate floor below the grid, additional evaluations use rates 0.01 Hz, 0.025 Hz, 0.05 Hz, 0.1 Hz, 0.25 Hz, 0.5 Hz, 1 Hz, 2 Hz, 3 Hz while holding both presentation and readout at 200 ms. Each cell contains 10 streams of 10 digits for every trained seed. The

5 Hz, 10 Hz, 25 Hz, 50 Hz, 100 Hz, 200 Hz points use the same fixed-duration protocol and come from the corresponding grid row.


### **Foreground-retention calibration**

The spatial protocol uses the same MNIST split and has two parts:

1. Train 3 seeds of a width-matched artificial neural network (ANN) with 784 inputs, one rectified-linear hidden layer of 1024 units, and 10 outputs. The hidden width matches the PING E population, not its recurrent E/I architecture. A rectified-linear unit outputs zero for a negative input and otherwise passes the input unchanged. Training uses 15 epochs, or complete passes through the training set, batches of 256 images per weight update, and learning rate 0.001, the step size of each update.
2. Binarize each held-out image, meaning an image excluded from training, at intensity 0: pixels above the threshold become unit-valued foreground and all others become zero-valued background. Retain every foreground pixel independently with probability  $q$ . Retention  $q = 1$  leaves the foreground intact and  $q = 0$  removes it. The ANN calibration uses 10 independent mask realizations per image. The matched comparison uses 100 fixed held-out examples and identical masks for every ANN and PING seed; PING encodes them at 25 Hz for 200 ms.

## Results

### Streaming classification and temporal evidence



exp048-replot

Figure 84: Classification when presentation duration and encoding rate vary between segments. The segment conditions are 200 ms at 10 Hz; 50 ms at 100 Hz; 100 ms at 25 Hz; 25 ms at 200 Hz; 75 ms at 15 Hz. Thumbnail opacity increases with encoding rate. The middle panels plot E- and I-cell spike rasters against time (ms); the lower panel plots class probability against time (ms), with the true class emphasized in red. The label-to-prediction pairs are 5→0, 3→3, 4→4, 1→1, 7→8, giving 3 of 5 correct segments.




Figure 85: Temporal and encoding-rate limits of the frozen PING classifier. **(A)** Per-segment accuracy (%) is shown for presentation duration (ms, horizontal) and Poisson encoding rate (Hz per channel, vertical), using 1200 segments per cell. **(B)** Probability of a correct classification (%) is plotted against encoding rate (Hz) with presentation and readout fixed at 200 ms. The inset enlarges the linear 0.01–10 Hz interval without changing the axis scale. The dashed line marks 10-class chance and the dotted line the 25 Hz training rate. Accuracy stays at its empty-input floor, the accuracy obtained when almost no input spikes arrive, through 0.5 Hz, becomes informative by 2 Hz, and reaches 79.1% at 5 Hz.

The fixed-duration rate curve distinguishes a nonviable encoder regime from ordinary classification errors under weak evidence. In the variable-condition stream, the first failed segment received 10 Hz for 200 ms, yet that condition reaches 87.3% across the population. Its error is therefore natural trial-level variation, not evidence that 10 Hz is intrinsically too low. The other failed segment, presented at 15 Hz for 75 ms, is likewise above the empty-input rate floor, although its shorter window supplies less total evidence. Rates below 0.5 Hz are not useful operating points; 2 Hz is the lowest clearly informative tested rate and 5 Hz is a practical lower bound for future sweeps.

### Spatial evidence calibration

The architecture-matched ANN remains above chance until foreground retention falls to  $q = 0.005$ , fewer than one visible foreground pixel per image on average.




Figure 86: Held-out ANN accuracy as foreground evidence is removed. Probability of a correct classification (%) is plotted against foreground retention  $q$ , the independent probability that a foreground pixel remains visible. Points are means across 3 ANN seeds and the band is one standard error, the estimated uncertainty of that mean across seeds. The dashed line marks 10-class chance; the dotted line marks the measured chance-region bound at  $q = 0.005$ , the highest tested retention whose 95% confidence interval across seeds still contains chance accuracy.

Under identical masks, neither classifier is uniformly better. With 29.5 visible pixels on average ( $q = 0.2$ ), PING reaches 68.7% against the ANN's 60.7%. They coincide near 45% at  $q = 0.1$ . PING still leads at  $q = 0.05$ , then reaches chance at  $q = 0.02$  while the ANN remains above it.




Figure 87: Width-matched ANN and frozen PING accuracy under identical spatial deletion. Probability of a correct classification (%) is plotted against foreground retention  $q$ . Black circles denote ANN and red squares PING; bands show one standard error across trained seeds. Each point uses 100 fixed held-out examples and identical independently sampled foreground masks. PING runs at 25 Hz for 200 ms. Neither classifier dominates across the full retention range.




Figure 88: Stimulus and error structure across the matched masking curve. Rows progress from intact input through intermediate masking to the blank control. Left panels show five binarized examples and their mean visible foreground-pixel count. The ANN and PING panels show confusion matrices with true digit on the vertical axis and predicted digit on the horizontal axis; each row is normalized to show the distribution of predictions for one true class. The lowest-retention rows reveal collapse toward model-specific default classes rather than structured digit confusions.

Binarization maps every nonzero antialiased MNIST pixel, including intermediate-intensity pixels introduced to smooth digit edges, to full intensity, so spatial retention is not a second measurement of grayscale contrast. Nevertheless, expected input-event count gives a useful first-order bridge. For an otherwise identical binary image encoded at the masking experiment’s 25 Hz ceiling, retaining fraction  $q$  gives the same expected event count as retaining the full foreground and using

$$r_{\text{equiv}} = q \cdot 25 \text{ Hz}. \quad (9)$$

Here  $r_{\text{equiv}}$  is the full-foreground Poisson rate with the same expected event count, meaning the expected total number of input spikes across the image and presentation;  $q$  is foreground retention; and 25 Hz is the masking experiment’s reference encoding rate.

Thus  $q = 0.1$  maps to  $r_{\text{equiv}} = 2.5$  Hz, within the 2–3 Hz transition of the fixed-duration rate curve. At that retention, PING reaches 45%, compared with 49.7% at 2 Hz in the grayscale rate sweep. This numerical alignment supports including a rate near 2.5 Hz in variable-rate training, but it is not an equivalence of corruptions: spatial masking permanently removes locations, whereas lowering Poisson rate preserves all locations in expectation and changes temporal sampling noise.



# Gradient descent does not preserve a trainable PING loop

9 June 2026

The trained networks this entry uses are produced once in the shared training hub, exp022 (Training), and reused here rather than retrained.

## Abstract

exp025 freezes the recurrent conductances  $W^{EI}, W^{IE}$  at biophysical values. When they are trainable, Adam does *not* preserve or recover effective PING from any tested initialisation (canonical, zero, or 10% of canonical): E→I recruitment weakens or remains absent, inhibitory firing collapses, and the network moves toward dense E firing at  $\approx 90\%$  accuracy, close to the frozen PING control ( $\approx 91\%$ ). The matrices store non-negative conductance magnitudes; inhibition is produced by the GABA reversal potential, not by a negative  $W^{IE}$ . PING is therefore a structural prior imposed by the frozen loop in this setup, not one gradient descent recovers on its own.

## Method

All checkpoint-backed rhythmicity, raster, and recurrent-weight summaries use the final-epoch checkpoint. Per-epoch trajectories continue to come directly from the training history.

Quantitative checkpoint-backed inference uses the same fixed 1,000-image subset of the official MNIST test partition for every condition and seed. Single-trial raster panels remain illustrative and do not define that evaluation corpus.

**Architecture.**  $N_E = 1024$  excitatory,  $N_I = 256$  inhibitory, mem-mean readout, Dale’s law enforced. Hyperparameters match the shared exp022 PING recipe: Adam at  $\text{lr } 4 \times 10^{-4}$ , batch 256, surrogate slope 1, lower-clamped-Gaussian  $W_{\text{in}}$  with parent parameters (0.9, 0.09) and a 95% initial-zero fraction, directly specified readout initialization, gradient norm clipped to 1.0,  $\Delta t = 0.1$  ms,  $T = 200$  ms, no firing-rate regulariser. The zero-initialized input parameters remain trainable and may regrow.

Both recurrent matrices are non-negative conductance magnitudes. After each optimiser step they are projected onto the non-negative cone. Their physiological sign is supplied by the pathway reversal potential: I→E contributes  $g_I(E_I - V)$  with  $E_I = -80$  mV and is therefore inhibitory despite  $W^{IE} \geq 0$ .

**Sweep.** Four conditions  $\times$  three seeds (42, 43, 44) on the 10% MNIST subset (5600 train / 1400 test), 50 epochs. Only the initial ( $W^{EI}, W^{IE}$ ) and the trainable-or-not flag vary:

| Condition                    | $W^{EI}, W^{IE}$ init     | Trainable? |
|------------------------------|---------------------------|------------|
| <i>frozen_ping</i> (control) | canonical biophysical     | no         |
| <i>trainable_ping_init</i>   | canonical biophysical     | <b>yes</b> |
| <i>trainable_zero_init</i>   | 0 (COBA-equivalent start) | <b>yes</b> |
| <i>trainable_small_init</i>  | $0.1 \times$ canonical    | <b>yes</b> |

Canonical biophysical means  $W^{EI} \sim \mathcal{N}(1.0, 0.1)$   $\mu\text{S}$ ,  $W^{IE} \sim \mathcal{N}(2.0, 0.2)$   $\mu\text{S}$  at  $N_I = 256$ , fan-in-normalised, so the trainer reports per-edge means of  $\approx 0.0010$  and  $\approx 0.0078$ . “PING is on”

means the inhibitory loop is active: E recruits I, and I paces a gamma rhythm through GABA conductance. “The loop is lost” means E→I recruitment is too weak to sustain that regime, I activity is low or absent, and E fires densely. The firing rates and rhythmicity are the cleanest read of which regime a trained network reaches.

## Results

The whole sweep collapses to one picture. In the (E firing rate, I firing rate) plane, a network “found PING” if it sits in the low-E / high-I corner, and “lost the loop” if it sits in the dense-E / silent-I corner.





Figure 89: Each point is one trained network (4 conditions  $\times$  3 seeds). The **frozen control** (grey) sits in the PING corner,  $E \approx 10$  Hz and  $I \approx 57$  Hz, the inhibitory loop alive. **Every trainable condition** (started at canonical PING, at zero, or at  $0.1 \times$  canonical) collapses to the dense-E / silent-I floor,  $E \approx 40\text{--}75$  Hz and  $I \approx 0\text{--}7$  Hz, at  $\approx 90\%$  accuracy, essentially matching the  $\approx 91\%$  control. Where the loop *starts* makes no difference; only whether it is allowed to train. Gradient descent never reaches PING, and dropping it costs no accuracy.

## Training curves — functional loop collapse, epoch by epoch



r001

Figure 90: Per-epoch metrics from the runs themselves, coloured by init: PING init (black), zero init (red), small-seed init (amber), frozen-PING control (grey dashed); 10% of MNIST, 50 epochs, 3 seeds each. **Accuracy:** all reach  $\approx 85\text{--}90\%$  and track each other; losing effective PING costs nothing. **E rate:** the trainable runs climb to  $\approx 37\text{--}75$  Hz as inhibition releases the excitatory population, while the frozen control stays gated near 10 Hz. **I rate:** every trainable run drops to  $\approx 0$  within a few epochs as effective  $E \rightarrow I$  recruitment weakens or remains absent, while the frozen control's I rate *rises* to  $\approx 57$  Hz as its readout trains. **Pingness:** the exp054 lobe–trough contrast holds near  $\approx 0.99$  for the frozen control while every trainable init collapses to  $\approx 0.1\text{--}0.2$ . The residual floor is the metric's known low-rate inflation under shared input (exp054), not a surviving rhythm: the frozen-vs-trainable gap is the signal. Functional loop activity dies early, from every start, with no accuracy penalty.

The saved matrices identify which side of the recurrent loop changes. In the canonical-initialisation seed-42 checkpoint, 84.5% of  $E \rightarrow I$  entries are zero after training, compared with 1.1% of  $I \rightarrow E$  entries; their final means are 0.000536 and 0.00943, respectively. Thus the silent inhibitory population is associated chiefly with sparse  $E \rightarrow I$  recruitment, while the  $I \rightarrow E$  conductance remains predominantly positive.




Figure 91: **The two recurrent matrices do not collapse symmetrically.** Initial and trained conductance distributions for the canonical-initialisation condition, pooled across seeds 42–44; each panel reports its own mean and zero fraction. The checkpoint-level distinction is already clear in seed 42: 84.5% of  $W^{EI}$  entries are zero after training, versus 1.1% of  $W^{IE}$  entries. The loss of PING therefore tracks weakened E→I recruitment and near-silent I activity, not I→E weights crossing into a negative sign cone.

## Phase portrait — there is only one attractor under training

The four per-epoch panels above tell the story but separate the two state variables that matter. Putting *E rate* and *pingness* on perpendicular axes shows the trajectories of training directly, and the geometry rules out a misreading: it is *not* the case that PING and COBA are two attractors of the same dynamics, with the architecture deciding the basin. Under training there is **one** attractor (the COBA corner), and the PING state only persists because freezing the loop zeroes its gradients.




Figure 92: Each trainable trajectory is the per-epoch mean across 3 seeds, alpha-ramped along the epoch axis so the direction of flow reads off the line itself; open markers are epoch 1 (the first logged epoch), filled markers are epoch 50. **Frozen PING (grey)**: sits in the upper PING basin from start to finish at pingness  $\approx 0.98$ ; drifts a little in E rate ( $\approx 4 \rightarrow 10$  Hz) as the feedforward and readout weights train, but the loop weights themselves can't move by construction. **Trainable PING init (black)**: was initialised with canonical biophysical loop weights, but by the time the first metric is logged (after epoch 1) rhythmicity has already collapsed to  $\approx 0.17$ . The trajectory then walks rightward along the COBA floor with the others. **Trainable zero init (red)** and **small-seed init (amber)**: start at the floor and stay there, E rate climbing as the feedforward layer learns the task. Every legend entry lands at 83–91% accuracy, so the move costs nothing. The reading is sharper than the time-series panels suggest: the empty band between pingness  $\approx 0.2$  and  $\approx 0.85$  is the *whole story*, because gradient descent flies through it within one epoch and the metric never catches it mid-flight. There is no separatrix between PING and COBA under training because there is no slow trajectory through the gap. The freeze isn't preventing slow erosion; it's preventing instant collapse.

## Accuracy–rate trajectory — same destination, different spike economy

Figure 4 puts pingness on its own axis. Putting pingness on the *colour* axis instead and replaying training as (E rate, accuracy) trajectories (the exp025 accuracy–rate frontier given a time axis) gives another reading of the same data: every condition reaches the same final test accuracy, but along very different routes, and only one of them is doing PING while it gets there.




Figure 93: Each trajectory is the per-epoch mean across 3 seeds; per-segment colour is that epoch’s pingness on a viridis 0→1 scale (colourbar at right). Open markers are epoch 1, filled markers are epoch 50. The frontier *with time* tells three things at once. **Same destination:** all four conditions land at  $\approx 83\text{--}91\%$  accuracy by epoch 50, regardless of init or whether the loop trains. **Different routes:** the frozen control climbs accuracy almost vertically with little change in E rate ( $\approx 4 \rightarrow 10$  Hz); the trainable conditions all bend right and up, the biggest one (zero init) reaching final accuracy at  $E \approx 75$  Hz,  $\approx 8\times$  the frozen control’s rate. **Only one of them is still PING:** the frozen control’s line is bright yellow because pingness stays high ( $\approx 1.0$ ) the whole way; every trainable line is dark purple because rhythmicity had already collapsed to  $\approx 0.1$  by the first logged epoch. Reading the colour bar: most of pingness 0.2–0.85 is unused space, because no trajectory crosses it slowly enough to be logged. Reading the geometry: this is the manuscript’s accuracy–rate frontier (exp025, §2.3) animated, and the architecture is the only thing keeping a trained network on the sparse, rhythmic side of it. The dashed divider at  $\approx 17$  Hz marks the two basins explicitly: frozen PING holds the left, every trainable run ends in the right, at the same accuracy.

# A PING rhythmicity metric

15 June 2026

## Abstract

A single bounded scalar for how rhythmic a spiking network is: the **lobe–trough contrast** of its spike-time autocorrelation,  $(\text{lobe} - \text{trough})/(\text{lobe} + \text{trough}) \in [0, 1)$ . Driving each excitatory cell with its own private Poisson input makes the metric rate-invariant by construction; across untrained PING networks it reads 0 along the COBA edges and rises smoothly to 0.98 through the PING interior, a rankable gradient that tracks the gamma-gated collapse of the E firing rate from 95 to 3 Hz.

## Methods

The networks here are untrained PING populations driven by external input; the rhythmicity metric is read off the resulting excitatory raster. Write  $r(t)$  for the binned population spike count ( $n$  bins of width  $\Delta t$ ) and  $\ell$  for the lag. The metric is read off in a fixed sequence of steps:

1. **Drive each E cell with its own private Poisson channel.** Every excitatory cell receives an independent homogeneous Poisson spike train at 100 Hz through a one-to-one identity input weight: there is no shared, dense  $W_{\text{in}}$  projection, so no two cells share an input channel. Private input removes the input-driven spike coincidence that would otherwise inflate the metric at low firing, which is what makes the contrast rate-invariant by construction (Figures 4–5) with no post-hoc correction.
2. **Bin to a population count.** Sum spikes across cells into one count per  $\Delta t$  bin, giving the population trace  $r(t)$  of length  $n$ .
3. **Raw autocorrelation.** Form the lag product  $\sum_t r(t)r(t + \ell)$ , which counts spike pairs separated by lag  $\ell$ . All lags are computed at once in  $O(n \log n)$  via the Wiener–Khinchin route (zero-pad  $r$ , take its FFT, multiply by the conjugate, inverse-transform) rather than the  $O(n^2)$  direct sum.
4. **Correct for finite overlap.** Only  $n - \ell$  bin-pairs exist at lag  $\ell$  (the last  $\ell$  samples have no partner), so the raw sum tapers toward zero with lag simply from running out of overlap; dividing by that per-lag overlap  $n - \ell$  converts it to the *average* product per available pair and flattens the taper.
5. **Set the chance level.** Divide by the mean rate squared  $\langle r \rangle^2$  so rate-matched independent firing sits at  $A = 1$ , and drop the self-paired zero lag. The result is the normalised autocorrelogram

$$A(\ell) = \frac{1}{\langle r \rangle^2} \frac{1}{n - \ell} \sum_t r(t)r(t + \ell).$$

6. **Locate the Mexican hat.** A rhythmic  $A(\ell)$  has a “Mexican-hat” profile: a central lobe above 1 (spikes recur a cycle apart) flanked by a dip below 1 where firing is suppressed between volleys. Scanning out from zero lag, take the trough as the first local minimum of a lightly smoothed  $A(\ell)$  (it falls near the half-period) and the lobe as the highest point at a shorter lag. Both searches start one bin past zero, so the self-paired zero-lag value

dropped in step 5 is excluded from the lobe height: the lobe is read from the first real lag onward, never the trivial self-correlation.

**7. Read the contrast.** The metric is the **lobe–trough contrast**

$$\text{contrast} = \frac{\text{lobe} - \text{trough}}{\text{lobe} + \text{trough}} \in [0, 1),$$

zero when lobe equals trough (no structure) and approaching 1 as the trough goes silent.

It is bounded by construction, with no trough floor needed.

In words:  $A(\ell)$  is how much more (or less) likely a spike is to be followed by another one  $\ell$  ms later than under independent firing, with  $A = 1$  the chance floor. A central lobe above 1 says spikes *cluster* in volleys; a trough below 1 near the half-period says firing is *suppressed between* them. The contrast is **0** when the spikes carry no such structure (asynchronous) and approaches **1** as sharp volleys separate against near-silence; because it reads the *shape* of  $A(\ell)$ , it registers a rhythm whether or not its frequency holds still.



## Results




Figure 94: The anchor result: gamma switches on smoothly across the recurrent-weight plane, read as scalar maps over the  $W_{EI} \times W_{IE}$  grid (untrained networks, private per-cell Poisson input) with example rasters beneath. **Top:** three per-cell summaries, every cell labelled. **E rate** is high along both zero edges (the loop is broken, E fires at the input-driven  $\approx 95$  Hz) and gated down through the interior; **I rate** is silent where  $W_{EI} = 0$ , runs away along  $W_{IE} = 0$  (clipped so the interior is legible), and is controlled once the loop closes; **lobe-trough contrast** (the rhythm scored 0–1) reads exactly 0 along both COBA edges and rises smoothly toward strong coupling, with three points marked along the  $W_{IE} = 2W_{EI}$  diagonal. **Bottom:** E/I rasters (E black, I red above) at those points: **A** the fully-off origin ( $W_{EI} = W_{IE} = 0$ ), asynchronous with no I; **B** weak coupling, emerging volleys (contrast 0.27, below the half-way mark); **C** strong coupling, sharp volleys (contrast 0.98). E rate falling, I rate rising, and contrast rising are three readings of the same loop engaging. The full per-cell detail (every raster and autocorrelogram) is in the figures below; the rate-fairness behind the contrast metric is in Figures 4–5.




Figure 95: E/I rasters for a  $6 \times 6$  subset of the grid (every other cell; the heatmaps below use all 121). The two zero edges are the controls:  $W_{EI} = 0$  (left column) leaves I silent and E asynchronous;  $W_{IE} = 0$  (bottom row) lets I fire but not inhibit E, so both stay dense; neither is rhythmic. The interior shows clear gamma volleys (E black, I red) that sharpen as either weight grows, the rhythm the contrast (Figure 1) scores.




Figure 96: The E-population autocorrelogram  $A(\ell)$  for a  $6 \times 6$  subset of the grid (lag 0–50 ms; dotted line = chance,  $A = 1$ ), with the located lobe ( $\blacktriangle$ ) and trough ( $\blacktriangledown$ ) marked. The two zero edges are flat at 1: asynchronous firing, no structure. Through the interior the Mexican hat emerges: a sharp central lobe at  $\approx 1$  ms over a trough near the half-period, with a secondary peak at the full period further out. The contrast in Figure 1 is exactly this lobe-versus-trough read off as one number.




Figure 97: The rate-invariance test that justifies the private-input choice. Each line is a **non-rhythmic null network** (no inhibitory loop, no rhythm at any drive) scanned over input rate; a rate-invariant metric should read  $\approx 0$  everywhere. With **private input** (black) it does: flat at  $\leq 0.07$  across all firing rates. With **shared input** (grey dashed) it instead **climbs to  $\approx 0.50$  as firing thins**: cells sharing input channels fire coincidentally, and the metric reads that as rhythm. The real PING cells (red) sit well above the private-input null, so their contrast is genuine, with no correction needed.




Figure 98: Why shared input fails and private input does not, at matched low firing rates.

**Top (shared input):** coincident spikes from shared channels leave a central peak over a shallow dip (a spurious hat with no inhibitory loop behind it), and the metric marks a lobe (▲) and trough (▼) and reports a non-zero contrast. **Bottom (private input):** the same firing rates, but with one channel per cell the central peak is gone;  $A(l)$  is flat shot-noise around chance and the contrast collapses to  $\approx 0$ . Same rate, same spike counts; the only difference is whether cells share input.

## The onset over its mean-field bifurcation

The turn-on above is *what* the network does; the exp033 4D conductance mean-field is *why*. This final section stacks the two into one manuscript figure: the empirical maps and example rasters directly over the mean-field bifurcation that predicts them. It recomputes the exp033 numerics (Hopf crossing, hysteresis sweep, gamma-vs- $\tau_{\text{GABA}}$ ) and reuses this notebook's own map and raster rendering, so restyling Figure 1 propagates here automatically, and no figures are copied. (This is the anchor that was formerly its own entry.)




Figure 99: Panels are lettered **A–I** in reading order. **Top (empirics, A–C)**. Across the  $W_{EI} \times W_{IE}$  plane the E rate falls (**A**), the I rate rises (**B**), and the lobe–trough contrast rises (**C**): three readings of one loop engaging, 0 along both COBA edges and smoothly up toward strong coupling. The contrast map circles three points along the  $W_{IE} = 2W_{EI}$  diagonal, shown as rasters **D/E/F**: the fully-off origin (**D**), emerging volleys (**E**), and sharp gamma volleys (**F**). **Bottom (theory, G–I, exp033)**. The same onset from the 4 mV reference of a 4D conductance mean-field with inherited biophysical parameters and a sensitivity-tested effective-noise scale: a complex-conjugate eigenvalue pair crosses into the right half-plane at  $I^* \approx 0.60$  nA (a Hopf, **G**), the amplitude rises continuously with coinciding up/down branches (supercritical and reversible, not a hard switch, **H**), and the predicted gamma frequency falls with  $\tau_{GABA}$  in step with the exp041 spiking measurement (**I**). The smooth empirical turn-on is exactly what a supercritical Hopf predicts.

# What the Spiking Heidelberg Digits look like

11 July 2026

## Abstract

The Spiking Heidelberg Digits (SHD) [1] benchmark delivers spoken digits as cochlear spikes. Unlike the static MNIST images the gamma-gated-sparsity collection Poisson-encodes into spike trains before its conductance-based spiking network (COBANet) ever sees them, SHD arrives *already* as events, with no image and no dense array anywhere: each sample is a spoken digit passed through a model of the inner ear, so it is a list of events, each an event time and the cochlear channel that fired. Before training a network on it, this entry looks at the raw data: one utterance per class, then several utterances of a single digit. Different classes paint visibly distinct time–frequency signatures and repeated utterances of one digit share a family resemblance, so the data is well-behaved and separable enough to be worth training on.

## Methods

Nothing here runs the network: every raster is drawn straight from the raw SHD event lists, with no binning and no model.

1. Load the SHD train split as raw events:  $N = 8156$  training utterances (a held-out test split adds more), each a spoken digit recorded from several speakers and converted to spikes by a Cramer et al. [1] cochlea model, a computational model of the inner ear that maps sound onto firing across an array of frequency-tuned channels.
2. Draw the class gallery: the first utterance of each of the 20 classes (the digits 0–9 spoken in German, labels 0–9, then English, labels 10–19), each as a spike raster.
3. Draw the within-class spread: the first 4 utterances of class 0, *null*, side by side.

Every utterance is a set of events  $\{(t_k, u_k)\}$ , where:

- $t_k$ , the **spike time** of event  $k$ , in seconds (utterances run  $\approx 0.2$ – $1.4$  s, median  $\approx 0.7$  s);
- $u_k \in \{0, \dots, 699\}$ , the **cochlear channel** that fired: a place code for frequency, where a low channel  $\approx$  low pitch and a high channel  $\approx$  high pitch.

So an utterance carries  $C = 700$  input channels and a median of  $\approx 7605$  events per utterance (range  $\approx 2410$ – $14917$ ).

## Results




Figure 100: One utterance per class (German 0–9, then English 0–9), each a raster of time (ms) against cochlear channel. **What we expect.** If SHD is learnable, different words should paint different time–frequency signatures. **What we see.** They do: a compact high-channel onset for *zwei*, a long two-lobe sweep for *sieben/seven*, a low-channel tail on *sechs*. A diffuse haze of isolated events sits under every panel: the cochlea model’s spontaneous background firing, which the classifier has to see past.




Figure 101: 4 different utterances of class 0, *null*, each a raster of time (ms) against cochlear channel: the within-class spread. **What we expect.** Different speakers saying the same word should share a family resemblance while differing in the particulars. **What we see.** Exactly that: all 4 carry the same broad high-channel onset falling into a mid-channel body, but they differ in duration, event density, and the fine structure of the low-channel tail. This speaker variability is what a classifier trained on SHD must generalise over.

## Next steps

The data is well-behaved and visibly class-separable, so it is worth training on. The trainer accepts SHD directly: it bins these events onto the model’s integration grid (a spike tensor of shape  $T_{\text{steps}} \times 700$  at the integration timestep  $\Delta t$ ) and feeds them to the PING (pyramidal–interneuron gamma) network, the excitatory and inhibitory populations of the COBANet, where:

- $T_{\text{steps}}$ , the number of time bins on the integration grid;
- $\Delta t$ , the integration timestep, in seconds.

The next entries take that path: a first PING network trained on SHD, then the firing-rate regulariser (the upper firing-rate bound from Cramer et al. [1], with target  $\theta_u = 100$  and weight  $s_u = 0.06$ ) that event-based benchmarks need to keep the hidden-layer rates in check, where:

- $\theta_u$ , the target upper bound on a unit’s firing rate;
- $s_u$ , the strength of the penalty applied above that bound.

## References

1. Cramer, Stradmann, Schemmel & Zenke — *The Heidelberg Spiking Data Sets for the Systematic Evaluation of Spiking Neural Networks*. IEEE Transactions on Neural Networks and Learning Systems, 2020. doi:10.1109/TNNLS.2020.3044364



# Trying a cumulative-potential readout on matched SHD networks

19 July 2026

## Abstract

This one-seed exploratory experiment tests whether the newly merged `tools/snn` cumulative-potential decoder can move matched Dale-constrained COBA and PING networks above the exp068–exp070 validation plateau on SHD. The screening ladder uses the same deterministic development-training / held-out-validation split as exp069 and exp070; the official SHD test remains sealed. Candidate one keeps the baseline 256-cell architecture and changes the classifier to `--readout cumulative-potential --signed-readout`

`--readout-bias`. If that is finite, active, and promising, candidate two keeps the same decoder and tests two 256-cell hidden layers. Only the best short candidate may be promoted to forty epochs.

## Goal prompt

```
/goal Design and execute the next exploratory SHD experiment on branch night/spiking-heidelberg-digits/ar071, using the newly merged tools/snn cumulative-potential readout additions to try to raise validation accuracy while keeping the comparison between matched Dale-constrained COBA and PING networks scientifically clean.
```

```
Start from updated main at merge commit
9527162d7a0ef80deac0e3f606ce513b9280ba6c. Do not modify main. Open a new
draft PR for this experiment when the first meaningful commit is ready.
```

Scientific objective:

Run a one-seed exploratory validation-only ladder on SHD to identify whether stronger temporal readout and modest capacity changes materially improve matched COBA/PING learning beyond exp068-exp070.

Constraints:

- Use one seed only.
- Do not use the official SHD test set during exploratory screening.
- Use a held-out validation split from the training set for all selection decisions.
- Keep COBA and PING matched except for their registered cell-specific voltage-gradient dampening.
- Preserve matched input, readout, training split, optimizer, batch, and preprocessing settings across COBA and PING within each candidate.
- Use short runs first for iteration speed, targeting about 8-10 epochs per candidate.
- Promote only the most promising candidate to a 40-epoch validation run.
- Do not run multiple seeds unless a later claim is worth defending and I explicitly authorize it.
- RunPod spending requires explicit approval before pod creation; use at most one pod at a time unless separately authorized.

- Reap any pod when finished.
- Do not merge the PR.
- Avoid the full local test suite on the 4 GB Hetzner host; use focused checks and demolab build.

#### Candidate ladder:

1. Baseline architecture with the new signed cumulative-potential readout:  
--readout cumulative-potential --signed-readout --readout-bias
2. If candidate 1 is finite, active, and improves validation learning, try modest increased capacity with two hidden layers, e.g. --n-hidden 256 256, keeping the same readout.
3. Optionally test one conservative recurrence/readout-adjacent setting if supported by existing tools/snn CLI and scientifically justified before seeing final results.
4. Promote the best candidate, if any, to a matched 40-epoch COBA/PING validation run.

#### Deliverables:

- Create the next numbered experiment, likely exp071, with artifacts under artifacts/data/exp071.
- Produce numbers.json, provenance, reproducer, training curves, firing-rate diagnostics, and matched input/E/I rasters where relevant.
- Write writings/exp071.typ as the canonical cold-readable experiment report.
- Include the goal prompt below the abstract and append timestamped activity-log/thread checkpoints in the experiment appendix, following the simplified SHD organization.
- Record scientific decisions, failures, anomalies, costs, commits, results, and pending work in the experiment article.
- Sanitize any publishable transcript/log content before committing.
- Build and validate with focused checks plus demolab build.
- Commit meaningful attempts, including killed attempts, with clear messages.
- Push branch night/spiking-heidelberg-digits/ar071 and update the new PR with evidence.
- Finish at the human review gate with a concise evidence summary, exact compute spend, validation performed, and links to the rendered exp071 file and PR.

## Methods

### Locked comparison

Both cells use seed 42, the exp069/exp070 development split (7340 training utterances and 816 validation utterances), batch size 32, Adam learning rate 0.0004, 1 ms simulation steps, 1000 ms utterance windows, fixed Dale-constrained feed-forward/recurrent conductances, and identical input preprocessing. COBA disables the inhibitory loop and uses the engine's no-dampening value; PING enables the inhibitory loop and uses voltage-gradient dampening 1000. These cell-specific settings are the only intended COBA/PING difference inside each candidate.

The readout is the new cumulative-potential decoder with signed abstract classifier weights and a trainable readout bias. The readout initialisation scale is one, not the old membrane-readout scale of 225, because that scale belonged to the prior output-LIF membrane recipe. COBA and PING are still matched exactly within each candidate.


### Ordered exploratory ladder



| Order | Candidate                                                        | Short epochs | Status      |
|-------|------------------------------------------------------------------|--------------|-------------|
| 1     | Baseline 256-cell architecture plus cumulative-potential readout | 40           | registered  |
| 2     | Two hidden layers, 256 cells each, same readout                  | 40           | conditional |

Candidate selection uses held-out validation accuracy and cross-entropy only. Training must remain finite, active, non-saturated, and free of skipped or non-finite updates. The official test file is not staged or loaded by the runner.

### Current evidence

The current published attempt is `#r.attempt` at stage `#r.stage`. COBA selected 68.38% validation accuracy; PING selected 69.49%. Exact spend was 3.956 USD , with 0 active pods after collection.





This final forty-epoch promotion keeps the candidate-one architecture and readout. COBA selected epoch 36 at 68.38%, while PING selected epoch 38 at 69.49%. Both final cells were finite, active, clean, and produced matched rasters. In this one-seed validation run PING is

ahead of COBA by 1.1 percentage points; this is exploratory validation evidence, not a defended multi-seed claim.

## Activity appendix

### Checkpoint cp001

Timestamp: `#trace.checkpoint_time_utc`. Sanitized source hash prefix: `#trace.sanitized_sha256_prefix`. The log excludes hidden reasoning, tool payloads, credentials, private paths, environment values, addresses, and sensitive infrastructure details.

### Decisions, actions, and pending work

1. The experiment is registered as exp071 on branch `night/spiking-heidelberg-digits/ar071` from main merge commit `9527162d7a0ef80deac0e3f606ce513b9280ba6c`.
2. Candidate one is fixed before results as the baseline 256-cell architecture with cumulative-potential readout, signed abstract classifier weights, and readout bias.
3. The old membrane-readout initialisation scale of 225 is not carried into the cumulative decoder; readout scale is one for the new decoder, matched across COBA and PING.
4. Candidate two is conditional on candidate-one viability and keeps the same readout while using two 256-cell hidden layers.
5. Selection remains one-seed and validation-only on the exp069/exp070 split. The official SHD test remains unavailable to the runner.
6. No RunPod pod has been created in this checkpoint and spend remains 0 USD.

### Visible messages

#### User

2026-07-19T11:18:05.855Z

Role: user · Checkpoint: cp001 · Session: exp071-continuation-redacted

<codex\_internal\_context source="goal"> Continue working toward the active thread goal: design and execute the next exploratory SHD experiment on branch `night/spiking-heidelberg-digits/ar071` using the newly merged cumulative-potential readout additions, with one seed, validation-only selection, local short runs before any promoted forty-epoch run, no official test use, explicit RunPod approval before spending, focused checks, artifacts under `artifacts/data/exp071`, `writings/exp071.typ`, timestamped activity checkpoints, commits, push, PR update, and no merge. </codex\_internal\_context>

#### Assistant

2026-07-19T11:18:05.855Z

Role: assistant · Checkpoint: cp001 · Session: exp071-continuation-redacted

I'll pick this up from the actual repo state, keep the dirty article-consolidation work isolated, and start by setting up the exp071 branch/work area cleanly. First I'm running the lab manual hook, then I'll inspect what's already in place.

#### Assistant

2026-07-19T11:18:05.855Z

Role: assistant · Checkpoint: cp001 · Session: exp071-continuation-redacted

Because this goal includes opening/updating a PR, I'm using the GitHub workflow skill now; it'll keep the GitHub side tidy and bounded.

**Assistant**

2026-07-19T11:18:05.855Z

Role: assistant · Checkpoint: cp001 · Session: exp071-continuation-redacted

The main checkout has the older article-consolidation changes restored and dirty, so I'm not touching it. I'm making a separate Git worktree for night/spiking-heidelberg-digits/ar071; that gives exp071 a clean branch without risking those staged/unstaged edits.

**Assistant**

2026-07-19T11:18:05.855Z

Role: assistant · Checkpoint: cp001 · Session: exp071-continuation-redacted

I've got the design shape now: exp071 can inherit exp069's split, selection, validation-only test seal, rasters, and RunPod plumbing, while overriding only the candidate-specific readout/hidden sizes/epochs. I'm going to add the initial scaffold plus a pre-result artifact so the report builds before paid compute.

**Assistant**

2026-07-19T11:18:05.855Z

Role: assistant · Checkpoint: cp001 · Session: exp071-continuation-redacted

One design decision I'm making explicit before results: candidate 1 uses the cumulative decoder with `-signed-readout -readout-bias` and a readout init scale of 1.0, not the old membrane-readout scale of 225. That scale was specific to the previous output-LIF membrane recipe; keeping it would be an unregistered hybrid rather than the clean new readout test. COBA/PING remain matched within each candidate.

**Checkpoint cp002**

Timestamp: `#trace-two.checkpoint_time_utc`. Sanitized source hash prefix: `#trace-two.sanitized_sha256_prefix`.

**Decisions, actions, and pending work**

1. Focused Python compilation passed for `experiments/exp071.py`.
2. Focused Ruff initially caught an unused import in `experiments/exp071.py`; the import was removed and Ruff then passed.
3. RunPod dispatch was dry-run only. It planned two 5090 pods, one for COBA and one for PING, and explicitly created nothing.
4. The first local smoke trained both cells finite and active, but the runner failed its own added hidden-size validation because `hidden_sizes` is stored in `config.json` while `metrics.config` keeps only legacy `n_hidden`.
5. The validation check was fixed to read `config.json` for `hidden_sizes`, falling back to `n_hidden` only when needed.
6. The second local 128/128 two-epoch smoke passed for both cells with the cumulative-potential readout. COBA selected 5.46875% validation accuracy and ended at 24.25390625 Hz E; PING selected 10.15625% and ended at 2.9765625 Hz E / 15.046875 Hz I.
7. The smoke accuracies are plumbing diagnostics only, not registered screening evidence.
8. No paid compute has started and spend remains 0 USD.

**Visible messages added****Assistant**

2026-07-19T11:28:51.466Z

Role: assistant · Checkpoint: cp002 · Session: exp071-continuation-redacted

Pre-result artifacts published locally. I'm doing the light checks in increasing cost: Python compile, dry-run RunPod dispatch (no –live), then the local 128/128 two-epoch smoke if the cheap checks pass.

**Assistant**

2026-07-19T11:28:51.466Z

Role: assistant · Checkpoint: cp002 · Session: exp071-continuation-redacted

Cheap checks found one real scaffold nit—an unused import—while the RunPod path correctly dry-ran two pods and created nothing. I'm cleaning that import and then running the local smoke.

**Assistant**

2026-07-19T11:28:51.466Z

Role: assistant · Checkpoint: cp002 · Session: exp071-continuation-redacted

The smoke exposed a useful plumbing bug, not a science failure: both cells trained finite/active, but my extra validation looked for hidden\_sizes inside metrics.config, where this engine build stores only the legacy n\_hidden. I'm tightening that check against config.json instead and recording this as a killed/debugging attempt before moving on.

**Assistant**

2026-07-19T11:28:51.466Z

Role: assistant · Checkpoint: cp002 · Session: exp071-continuation-redacted

Ruff and compile are clean now. Starting the second local smoke; still no cloud spend.

**Assistant**

2026-07-19T11:28:51.466Z

Role: assistant · Checkpoint: cp002 · Session: exp071-continuation-redacted

Local smoke passed: COBA and PING were both finite and active on the 128/128, 2-epoch gate. I'm promoting that from temp into the publishable pre-result artifact and adding a second timestamped checkpoint before build/commit.

**Assistant**

2026-07-19T11:28:51.466Z

Role: assistant · Checkpoint: cp002 · Session: exp071-continuation-redacted

Build caught a subtle artifact-publishing issue: my pre-result publish swapped the exp071 artifact directory and dropped the activity JSON files I'd just written. The site build protected itself by stubbing exp071. I'm fixing the artifact layout by restoring those JSON logs after publish and then rebuilding.

**Checkpoint cp003**

Timestamp: #trace-three.checkpoint\_time\_utc. Sanitized source hash prefix: #trace-three.sanitized\_sha256\_prefix.

**Decisions, actions, and pending work**

1. The scientist explicitly authorized paid RunPod compute for exp071 after the local smoke gate.
2. Before live dispatch, exp071 was patched to honor –only-cells so the registered one-pod-at-a-time constraint can be enforced.
3. Focused validation passed after that patch: Ruff, Python compilation, exp071-only ty, and a COBA-only RunPod dry-run that planned exactly one pod.
4. Commit 11b0cdb7a7e1dc01b8aa3d3af7a41bdf90d1f2b was pushed before live dispatch so pods would fetch a pinned committed SHA.
5. Two COBA-only live cloud attempts were started and then killed as infrastructure/monitoring attempts before any artifact was collected. These are not scientific COBA training failures.
6. The first attempt was stopped after remaining provider-running without collected artifacts; the manual SSH probe used the wrong local key, so the attempt is recorded as a monitoring/cloud-plumbing kill.
7. The second attempt used the corrected monitoring assumption but the provider SSH endpoint stayed not-ready during the observation window; it was stopped and deleted as a startup kill.
8. The active pod list was empty after reaping.
9. Exact provider billing for these short pod IDs had not reconciled at checkpoint time. Timestamp-based estimated exposure is 0.149054 USD total at 0.99 USD/hour. Exact spend remains pending.
10. No PING pod was started, preserving one pod at a time. Pending work is to fix or work around the cloud startup/observability issue before any further live screening.

**Visible messages added****User**

2026-07-19T11:46:40.467Z

Role: user · Checkpoint: cp003 · Session: exp071-continuation-redacted

you have permission

**Assistant**

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Got it — I'll treat that as explicit permission to start paid RunPod compute for the next registered short-screening step. I'll still enforce the experiment's one-pod-at-a-time constraint, so first I'm checking whether the current runner can dispatch only COBA or whether I need a tiny orchestration fix before spending.

**Assistant**

2026-07-19T11:46:40.467Z



Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Good catch from CI: exp071 added several ty diagnostics of its own, alongside the known old repo-wide ones. I'm fixing only the exp071-scoped issues and adding `-only-cells` support so live dispatch can obey the one-pod-at-a-time constraint.

## Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Patch is in. I'm running focused validation now: `ruff`, `py_compile`, `exp071-only ty`, and `dry-run dispatch` for just COBA to prove it plans one pod.

## Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Focused checks pass and the dry-run now plans exactly one pod for COBA. I'm committing/pushing this orchestration fix before live dispatch, because the pod will fetch from GitHub by pinned SHA.

## Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Committed/pushed 11b0cdb. Now I'm starting the authorized live short-screening COBA pod only. After it fires, I'll monitor/collect/reap before starting PING, preserving the one-pod rule.

## Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

COBA live pod fired at pinned SHA 11b0cdb; one pod only. I'm logging that on PR #55, then I'll monitor until it self-terminates before collecting and moving to PING.

## Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Pod details show it was created at 11:36 UTC and is still desired-running; I'm not going to echo the raw detail payload because it contains sensitive provider fields. The runtime/cost is still small, but I'm treating this as a watch item now rather than passive waiting.

## Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

No progress signal after the extra window, and SSH wasn't available, so I'm stopping this COBA pod as a killed infrastructure attempt rather than burning more time/money. Then I'll check billing and record the failed live attempt.

### Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

The pod is stopped. The stop response includes sensitive provider env fields, so I'll sanitize it out of all publishable records. I'm deleting the stopped pod now to fully reap it.

### Assistant

2026-07-19T11:46:40.467Z

Role: assistant · Checkpoint: cp003 · Session: exp071-continuation-redacted

Both pods are deleted; active pod list is empty. Estimated exposure from timestamps is about \$0.15 total, but RunPod's per-pod billing endpoint has not reconciled those pod IDs yet, so I'm recording provider exact pending rather than pretending the estimate is exact.

## Checkpoint cp004

Timestamp: #trace-four.checkpoint\_time\_utc. Sanitized source hash prefix: #trace-four.sanitized\_sha256\_prefix.

### Decisions, actions, and pending work

1. An existing authenticated container-registry entry was used for the next live attempts, fixing the earlier anonymous image-pull/startup problem without changing the registered scientific design.
2. Candidate one, cumulative\_baseline, completed the 8-epoch short stage for COBA and PING with one live pod at a time.
3. COBA selected epoch 8 with validation accuracy 60.049019607843135%, validation cross-entropy 1.5872331674282367, final E rate 28.346392463235293 Hz, no skipped steps, and no non-finite batches.
4. PING selected epoch 8 with validation accuracy 57.96568627450981%, validation cross-entropy 1.4047367160136883, final E/I rates 7.494308172487745 / 36.273169424019606 Hz, no skipped steps, and no non-finite batches.
5. Matched validation curves, activity curves, and input/E/I rasters were published under artifacts/data/exp071.
6. The active pod list was empty after both collections.
7. Exact provider billing had not reconciled at checkpoint time. The temporary timestamp-based estimate is 0.77 USD total across killed startup attempts, productive COBA/PING runs, and collector pods; exact spend remains pending.
8. Candidate one clears the finite-active-above-chance short viability gate. The next registered step is candidate two, cumulative\_256\_256, before any forty-epoch promotion decision.

## Visible messages added

**Assistant**

2026-07-19T12:34:00.000Z

Role: assistant · Checkpoint: cp004 · Session: exp071-continuation-redacted

The earlier hangup is pinned down: anonymous GHCR pulls were the likely culprit. I found the existing registry auth entry, confirmed the active pod list is empty, and I'm re-running the COBA short screen with authenticated image pull — still one pod only.

**Assistant**

2026-07-19T12:34:00.000Z

Role: assistant · Checkpoint: cp004 · Session: exp071-continuation-redacted

Much better: the authenticated COBA pod is running and visible. I'm polling it in short windows; if it finishes normally I'll collect/reap and then start PING.

**Assistant**

2026-07-19T12:34:00.000Z

Role: assistant · Checkpoint: cp004 · Session: exp071-continuation-redacted

COBA finished and self-terminated. I'm collecting the artifacts now; the collector itself is transient cloud compute, so I'll also verify it reaps before launching PING.

**Assistant**

2026-07-19T12:34:00.000Z

Role: assistant · Checkpoint: cp004 · Session: exp071-continuation-redacted

COBA short is collected: selected epoch 8 at 60.05% validation accuracy, finite/active, no skipped or non-finite updates, matched rasters present. Active pods are empty again, so I'm starting PING short now under the same authenticated path.

**Assistant**

2026-07-19T12:34:00.000Z

Role: assistant · Checkpoint: cp004 · Session: exp071-continuation-redacted

PING is running cleanly now. I've also logged the COBA→PING handoff on PR #55. Next step is collection, then I'll publish both curves/rasters into exp071 before moving to candidate two.

**Assistant**

2026-07-19T12:34:00.000Z

Role: assistant · Checkpoint: cp004 · Session: exp071-continuation-redacted

PING finished and collected. Candidate one is now a real short-screen result: COBA 60.05%, PING 57.97%, both finite/active, both with rasters, no skipped/non-finite updates. I'm publishing those artifacts into the report and recording the spend as exact-provider-pending with the conservative timestamp estimate.

**Checkpoint cp005**

Timestamp: #trace-five.checkpoint\_time\_utc. Sanitized source hash prefix: #trace-five.sanitized\_sha256\_prefix.

**Decisions, actions, and pending work**

1. Candidate two, cumulative\_256\_256, completed the 8-epoch short stage for COBA and PING with one live pod at a time and separate collector pods.
2. COBA selected epoch 5 with validation accuracy 32.84313725490196%, validation cross-entropy 2.159944314223069, selected E rate 71.34302236519608 Hz, no skipped steps, and no non-finite batches.
3. PING selected epoch 7 with validation accuracy 42.76960784313726%, validation cross-entropy 1.8651616527484014, selected E/I rates 11.079091988357844 / 39.40600107230392 Hz, no skipped steps, and no non-finite batches.
4. Matched validation curves, activity curves, and input/E/I rasters for candidate two were published under artifacts/data/exp071 while preserving the candidate-one artifact record.
5. Candidate two is finite, active, and clean, but it underperforms candidate one on both cells: candidate one selected COBA 60.049019607843135% and PING 57.96568627450981%.
6. The registered short-screen promotion target is therefore candidate one, cumulative\_baseline, not the two-hidden-layer candidate.
7. The active pod list was empty after both candidate-two collections.
8. Exact provider billing had not reconciled at checkpoint time. The temporary cumulative timestamp-based estimate is 1.76 USD total, well below the 40 USD ceiling.
9. Pending work is to run the registered 40-epoch promotion for candidate one, COBA and PING one pod at a time, unless stopped by the scientist.

**Visible messages added****Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

COBA candidate-two artifacts are collected and the collector reaped; active pod list is empty. I'm validating the collected COBA result before deciding whether to spend on PING for this candidate.

**Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

COBA candidate two completed cleanly but weakly: best epoch 5 at 32.84% validation, E active around 71 Hz, no skipped/non-finite updates. Because the registered candidate comparison is matched COBA/PING, I'm still running PING candidate two before making the promotion decision; otherwise we'd be peeking on one cell and stopping asymmetrically.

**Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

PING is healthy and actually a bit faster: epoch 2/8 is at 26.84% validation, E/I active, clean. ETA for PING completion is roughly 14–16 minutes.

**Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

PING epoch 5/8 has reached 41.05%, clean and active. Better than COBA candidate two, still below candidate-one PING's 57.97%. Three epochs to go.

**Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

PING self-terminated and the active pod list is empty. Collecting candidate-two artifacts now.

**Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

PING candidate two is collected and collector reaped; active pod list empty. I'm validating both candidate-two cells and then I'll publish the short result into exp071.

**Assistant**

2026-07-19T13:39:00.000Z

Role: assistant · Checkpoint: cp005 · Session: exp071-continuation-redacted

Candidate two is published locally. I'm making the report compare both short candidates directly so the promotion decision is explicit rather than buried in raw JSON.

**Checkpoint cp006**

Timestamp: #trace-six.checkpoint\_time\_utc. Sanitized source hash prefix: #trace-six.sanitized\_sha256\_prefix.

**Decisions, actions, and pending work**

1. The scientist explicitly authorized relaxing the earlier one-pod-at-a-time operational constraint so the final40 COBA and PING cells could overlap. This did not change the registered scientific design.
2. Final40 candidate one, cumulative\_baseline, completed for COBA and PING. COBA self-terminated before PING and was collected while PING continued; PING then self-terminated and was collected. The active pod list was empty after final collection.
3. COBA selected epoch 36 with validation accuracy 68.38235294117646%, validation cross-entropy 1.1455509593853583, selected E rate 30.165441176470587 Hz, no skipped steps, and no non-finite batches. Final epoch 40 accuracy was 65.93137254901961%.
4. PING selected epoch 38 with validation accuracy 69.48529411764706%, validation cross-entropy 0.9843250490151919, selected E/I rates 9.563893037683824 / 44.886220894607845

Hz, no skipped steps, and no non-finite batches. Final epoch 40 accuracy was 68.25980392156863%.

5. Both final40 cells were finite, active, clean, and produced matched validation curves, firing-rate diagnostics, and input/E/I rasters.
6. In this one-seed validation-only exploratory run, PING finished 1.1029411764706083 percentage points ahead of COBA on the registered selected-validation rule. This is exploratory evidence, not a defended multi-seed claim.
7. Exact provider billing had not reconciled at checkpoint time. The temporary cumulative timestamp-based estimate is 4.15 USD total, well below the 40 USD ceiling.
8. Pending work is to build, commit, push, update PR #55, and finish at the human review gate without merging.

### Visible messages added

**User**

2026-07-19T15:52:00.000Z

Role: user · Checkpoint: cp006 · Session: exp071-continuation-redacted

status and eta?

**Assistant**

2026-07-19T15:52:00.000Z

Role: assistant · Checkpoint: cp006 · Session: exp071-continuation-redacted

Status: COBA final40 is still running cleanly, one pod only. Latest sampled metrics were epoch 32/40: best validation 66.67% at epoch 29, no skipped/non-finite updates, active E rate. ETA for COBA training finish is roughly 13–15 minutes, then collection/reap probably another 2–4 minutes. After that I'll start PING final40, likely ~60–70 minutes plus collection based on the short PING timing.

**User**

2026-07-19T15:52:00.000Z

Role: user · Checkpoint: cp006 · Session: exp071-continuation-redacted

why didn't you run them in parallel?

**Assistant**

2026-07-19T15:52:00.000Z

Role: assistant · Checkpoint: cp006 · Session: exp071-continuation-redacted

Because the active exp071 mandate explicitly says “at most one pod at a time” / “one-pod-at-a-time constraint,” and PR comments/logs are written around that constraint. I only launched PING after COBA completion for the short candidates, and I'm doing the same for final40. If you want to change that for future runs, I'd treat it as new authority/design change and log it before launching a second pod.

**User**

2026-07-19T15:52:00.000Z

Role: user · Checkpoint: cp006 · Session: exp071-continuation-redacted

its okay to do them in parallel you have my permission

### Assistant

2026-07-19T15:52:00.000Z

Role: assistant · Checkpoint: cp006 · Session: exp071-continuation-redacted

Got it — I'll treat that as explicit updated authority to run COBA and PING final40 concurrently from here. That changes the operational constraint, not the scientific design, so I'll log the authorization on PR #55 and launch PING final40 while COBA continues, keeping total spend well below the \$40 ceiling.

### Assistant

2026-07-19T15:52:00.000Z

Role: assistant · Checkpoint: cp006 · Session: exp071-continuation-redacted

COBA final40 is collected and valid: selected epoch 36 at 68.38%, final epoch 40 at 65.93%, clean, active, rasters present. PING is the only active pod now.

### Assistant

2026-07-19T15:52:00.000Z

Role: assistant · Checkpoint: cp006 · Session: exp071-continuation-redacted

PING has now edged ahead: epoch 36 best is 69.24%, clean/active. COBA selected 68.38%, so PING is +0.86 percentage points at this moment. Three epochs left.

### Assistant

2026-07-19T15:52:00.000Z

Role: assistant · Checkpoint: cp006 · Session: exp071-continuation-redacted

Final40 validation is clean and collected: COBA selected 68.38% at epoch 36; PING selected 69.49% at epoch 38. Both final runs are finite/active/clean with rasters, and active pods are empty. I'm preparing the final artifact publish/report update now.

## Checkpoint cp007

Timestamp: #trace-seven.checkpoint\_time\_utc. Sanitized source hash prefix: #trace-seven.sanitized\_sha256\_prefix.

## Decisions, actions, and pending work

1. After the previous blocked checkpoint, the scientist explicitly instructed Codex to keep going and confirmed permission to continue the review-gate work.
2. RunPod active-pod state was rechecked and remained empty.
3. RunPod by-pod billing had reconciled for all exp071 pod events. The exact provider total for the experiment is 3.956481664587045 USD.
4. The final40 PING training charge reconciled to 1.1461867298930883 USD over 4150275 billed milliseconds, and the final40 PING collector charge reconciled to 0.00804237462580204 USD over 29245 billed milliseconds.

5. The publishable compute ledger was updated from the temporary timestamp estimate to exact provider billing. Pod identifiers remain omitted from the committed ledger and article.
6. The final40 numbers were regenerated with `exact_provider_billing=true`. No scientific result values changed.
7. Pending work is focused validation, rebuild, commit, push, PR evidence update, and the final human-review summary.

### Visible messages added

#### Assistant

2026-07-19T16:00:00.000Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

Blocked on the one remaining external requirement: exact RunPod spend.

Fresh check:

- Active pods: ``
- Worktree/branch: clean on `night/spiking-heidelberg-digits/ar071`
- PR #55: open draft, green checks
- Latest by-pod billing:
  - final40 COBA: ``\$1.1224509432`
  - final40 COBA collector: ``\$0.0055998252`
  - final40 PING: ``\$0.4491335023` and still changing
  - final40 PING collector: still no billing row
  - visible by-pod subtotal: ``\$3.2513860624`

Because the final PING billing is still moving and its collector is missing, I can't honestly replace the conservative committed estimate (``\$4.15`, `exact\_provider\_billing=false`) with an exact spend. Since this same provider-reconciliation blocker has repeated across the required goal continuations, I marked the goal `blocked`.

Everything scientific remains done/review-ready; the blocker is purely RunPod's delayed billing reconciliation.

#### User

2026-07-19T17:37:43.751Z

Role: user · Checkpoint: cp007 · Session: exp071-continuation-redacted

keep going you have permission

#### Assistant

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

Got it — I'll resume from the billing gate and keep pushing until either RunPod reconciles or there's another concrete in-scope move. First I'm refreshing the lab docs requirement, repo/PR state, active pods, and by-pod billing again.



**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

Repo and PR are still clean/green. Now checking the provider billing again; if the final PING row has stopped advancing and collector appears, I'll turn this into an exact ledger update.

**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

Nice, the billing rows have finally landed. The exp071 by-pod total is now ``$3.9564816646`` with no missing rows, and no active pods. I'm going to convert the experiment ledger/report from conservative estimate to exact provider billing and add the final timestamped checkpoint.

**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

I've got the exact spend source. Next I'm making the publication-side changes only: exact compute ledger, regenerated ``numbers.json``, CP007 activity checkpoint, and the report wiring. No scientific result values should change.

**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

I'm keeping pod IDs out of the committed ledger and article; the exact dollar amounts and billed milliseconds are enough provenance without publishing infrastructure identifiers.

**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

The exact ledger publish step succeeded. I'm checking the artifact diff now because the runner republishes the current final40 view and may leave older short-screen/activity artifacts untouched or missing depending on the published-run helper.

**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

As expected, the publish helper replaced the artifact tree with the final40-only view. I'm restoring the previously committed short-screen/activity assets, then I'll add the new CP007 file.

**Assistant**

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

I'm adding CP007 as a narrow, sanitized activity checkpoint: it records the user-visible continuation around the billing gate, the exact spend evidence, and the remaining actions. I'll avoid publishing pod IDs/endpoints/paths.

## Assistant

2026-07-19T17:37:43.751Z

Role: assistant · Checkpoint: cp007 · Session: exp071-continuation-redacted

I'm going to put the private raw checkpoint copy under `temp/`, which is not part of the publishable artifacts. Then I'll use its SHA-256 prefix in CP007 and commit only the sanitized checkpoint.

# Adaptive conductance controls for matched SHD networks

19 July 2026

## Abstract

This one-seed exploratory experiment tests whether two newly added conductance-neuron controls move matched Dale-constrained COBA and PING networks beyond the exp071 roughly 70% validation plateau on SHD. The control is the exp071 cumulative-potential readout recipe: `--readout cumulative-potential --signed-readout --readout-bias`. The ladder then tests bounded trainable leak/membrane time constants, bounded adaptive E-cell thresholds, and their combination. All selection decisions use the held-out validation split from the official SHD training set; the official test set remains sealed.

## Goal prompt

```
/goal Design and execute the next exploratory SHD experiment from updated
main at f32299bb1b48d18ba9dfe6328097d2147bcc6286, using the newly merged
tools/snn adaptive conductance controls to test whether COBA/PING validation
accuracy can move meaningfully beyond the exp071 ~70% plateau toward
canonical SHD RSSN performance.
```

Create the next numbered experiment, likely exp072, on a new branch. Do not modify main directly after branching. Open a draft PR after the first meaningful commit.

Scientific objective:

Run a one-seed exploratory validation-only ladder on SHD comparing matched Dale-constrained COBA and PING networks while testing two new neuron-dynamics paths:

1. trainable conductance leak / membrane time constants via `--train-leak`;
2. adaptive E-cell thresholds via `--adaptive-threshold`;
3. the combination of both.

Use the exp071 cumulative-potential readout baseline as the control:

```
--readout cumulative-potential --signed-readout --readout-bias
```

Constraints:

- Use one seed only.
- Do not use the official SHD test set.
- Use a held-out validation split from the training set for all selection decisions.
- Keep COBA and PING matched except for registered cell-specific voltage-gradient dampening and PING E/I coupling.
- Preserve matched input, readout, training split, optimizer, batch, preprocessing, and candidate flags across COBA/PING within each candidate.
- COBA should use the no-inhibitory-loop setting; PING should use the registered inhibitory-loop setting and dampening 1000.
- Use short runs first for iteration speed, about 8-10 epochs per candidate.
- Promote only the most promising candidate to a matched 40-epoch validation

```
run.
- Do not run multiple seeds unless I explicitly authorize it later.
- RunPod spending requires explicit approval before pod creation.
- Use at most one pod at a time unless I explicitly authorize parallelism.
- Reap any pod when finished.
- Do not merge the PR.
- Avoid the full local test suite on the 4 GB Hetzner host; use focused
checks and demolab build.
```

Candidate ladder:

0. Control: exp071 architecture/readout without new adaptive controls.

1. Trainable leak only:

```
--train-leak
```

2. Adaptive threshold only:

```
--adaptive-threshold
```

3. Combined:

```
--train-leak --adaptive-threshold
```

Suggested default bounds:

- E membrane tau: [5, 50] ms
- I membrane tau: [2, 20] ms
- adaptive threshold tau: [50, 500] ms
- adaptive threshold initial strength: 1.0 mV
- adaptive threshold max strength: 20.0 mV

Deliverables:

- Produce artifacts/data/exp072 with numbers.json, provenance, reproducer, training curves, firing-rate diagnostics, parameter diagnostics for learned tau/adaptation values, and matched input/E/I rasters.
- Write writings/exp072.typ as the canonical cold-readable experiment report.
- Include this goal prompt below the abstract.
- Append timestamped activity-log/thread checkpoints in the experiment appendix.
- Record scientific decisions, failures, anomalies, costs, commits, results, and pending work.
- Sanitize any publishable logs before committing.
- Build and validate with focused checks plus demolab build.
- Commit meaningful attempts, including killed attempts, with clear messages.
- Push the branch and update the PR with evidence.
- Finish at the human review gate with a concise evidence summary, exact compute spend, validation performed, links to the rendered exp072 file and PR, and a recommendation for the next move toward 90% SHD.

## Methods

### Locked comparison

Both cells use seed 42, the established SHD development split (7340 training utterances and 816 validation utterances), batch size 32, Adam learning rate 0.0004, 1 ms simulation steps, 1000 ms utterance windows, matched input preprocessing, and the same cumulative-potential

readout. COBA uses the no-inhibitory-loop setting and no voltage-gradient dampening; PING uses the registered inhibitory loop and dampening 1000. Those cell-specific settings are the only intended COBA/PING differences within a candidate.

### Candidate ladder

| Order | Candidate                                               | Extra flags                           | Short epochs |
|-------|---------------------------------------------------------|---------------------------------------|--------------|
| 0     | Control: exp071 architecture/<br>readout                | none                                  | 8            |
| 1     | Trainable conductance leak /<br>membrane time constants | --train-leak                          | 8            |
| 2     | Adaptive E-cell thresholds                              | --adaptive-threshold                  | 8            |
| 3     | Combined leak plus adaptation                           | --train-leak --adaptive-<br>threshold | 8            |

The default bounds are E membrane tau [5, 50] ms, I membrane tau [2, 20] ms, adaptive-threshold tau [50, 500] ms, initial adaptive strength 1.0 mV, and maximum adaptive strength 20.0 mV. Candidate selection uses held-out validation accuracy and cross-entropy only.

Training must remain finite, active, non-saturated, and free of skipped or non-finite updates.

## Results

The eight-epoch ladder completed for all four candidates. Control had the best paired average, but trainable leak was the only modification that improved the target PING cell while keeping COBA close, so `train_leak` was promoted to forty epochs.


| Candidate          | COBA acc. | COBA CE | PING acc. | PING CE |
|--------------------|-----------|---------|-----------|---------|
| control            | 60.17%    | 1.5905  | 56.86%    | 1.4221  |
| train_leak         | 58.95%    | 1.6838  | 57.72%    | 1.4365  |
| adaptive_threshold | 50.61%    | 1.9109  | 53.68%    | 1.532   |
| combined           | 50.37%    | 1.8996  | 50.98%    | 1.5616  |


The promoted forty-epoch `train_leak` run selected 69.49% for COBA and 71.08% for PING. As a later sensitivity check, the initially weak `combined` candidate was also run for eighty epochs.

| Long run              | COBA acc. | COBA epoch | PING acc. | PING epoch |
|-----------------------|-----------|------------|-----------|------------|
| train_leak, 40 epochs | 69.49%    | 37         | 71.08%    | 40         |
| combined, 80 epochs   | 64.58%    | 77         | 71.69%    | 73         |

The eighty-epoch combined follow-up nudged PING to 71.69%, but only after twice as many epochs and with stuck-dynamics warnings; COBA remained lower at 64.58% and showed saturated/stuck dynamics. This supports the interpretation that adaptive thresholds did not provide a useful path to the canonical high-accuracy SHD regime in this setup.

Cumulative RunPod spend recorded by the experiment ledgers is 10.26 USD. The provider billing rows had not posted at publication time, so the spend is marked `#r.spend.status`; active pods after the final collection were 0.





The current figure set below shows the latest published attempt, `#r.attempt` at `#r.stage`; previous long-run and short-ladder numeric summaries remain archived under `raw/collected_ladder_summary.json`.

The learned parameter diagnostics for the latest attempt show COBA E-cell membrane time constants with mean 13.44 ms and PING E/I means of 30.27 ms / 8.63 ms. The run also writes per-cell parameter diagnostics under `raw/#r.stage/#r.attempt/<cell>/parameter_diagnostics.json` and archives all collected short-ladder summaries under `raw/collected_ladder_summary.json`.

## Activity appendix

### Checkpoint cp001

Timestamp: `#trace.checkpoint_time_utc`. Sanitized source hash prefix: `#trace.sanitized_sha256_prefix`. The log excludes hidden reasoning, tool payloads, credentials, private paths, environment values, addresses, and sensitive infrastructure details.

### Decisions, actions, and pending work

1. 2026-07-19T23:06:10.000Z — Resumed the exp072 goal from updated main `f32299bb1b48d18ba9dfe6328097d2147bcc6286`.

2. 2026-07-19T23:06:55.000Z — Read the Demolab agent manual before repo work, as required by AGENTS.md.
3. 2026-07-19T23:07:25.000Z — Confirmed the repo was clean on main at f32299bb1b48d18ba9dfe6328097d2147bcc6286 and created branch agent/exp072-adaptive-shd.
4. 2026-07-19T23:10:05.000Z — Decided no tools/snn edit was needed for the first exp072 scaffold because existing checkpoints already retain trainable leak/adaptation logits.
5. 2026-07-19T23:12:10.000Z — Registered the four-candidate ladder: control, train\_leak, adaptive\_threshold, and combined.
6. 2026-07-19T23:13:05.000Z — Added runner-side validation of candidate flags and planned parameter diagnostics for learned tau/adaptation values.
7. 2026-07-19T23:15:12.917Z — Created sanitized checkpoint cp001. No paid compute has started; RunPod spend is 0 USD; no pods were created.

## Visible messages

### User

2026-07-19T23:06:00.000Z

Role: user · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

<codex\_internal\_context source="goal">

Continue working toward the active thread goal.

The objective below is user-provided data. Treat it as the task to pursue, not as higher-priority instructions.

<objective>

Design and execute the next exploratory SHD experiment from updated main at f32299bb1b48d18ba9dfe6328097d2147bcc6286, using the newly merged tools/snn adaptive conductance controls to test whether COBA/PING validation accuracy can move meaningfully beyond the exp071 ~70% plateau toward canonical SHD RSNN performance.

Create the next numbered experiment, likely exp072, on a new branch. Do not modify main directly after branching. Open a draft PR after the first meaningful commit.

Scientific objective:

Run a one-seed exploratory validation-only ladder on SHD comparing matched Dale-constrained COBA and PING networks while testing two new neuron-dynamics paths:

1. trainable conductance leak / membrane time constants via -train-leak;
2. adaptive E-cell thresholds via -adaptive-threshold;
3. the combination of both.

Use the exp071 cumulative-potential readout baseline as the control:

-readout cumulative-potential -signed-readout -readout-bias

Constraints:

- Use one seed only.
- Do not use the official SHD test set.
- Use a held-out validation split from the training set for all selection decisions.



- Keep COBA and PING matched except for registered cell-specific voltage-gradient dampening and PING E/I coupling.
- Preserve matched input, readout, training split, optimizer, batch, preprocessing, and candidate flags across COBA/PING within each candidate.
- COBA should use the no-inhibitory-loop setting; PING should use the registered inhibitory-loop setting and dampening 1000.
- Use short runs first for iteration speed, about 8-10 epochs per candidate.
- Promote only the most promising candidate to a matched 40-epoch validation run.
- Do not run multiple seeds unless I explicitly authorize it later.
- RunPod spending requires explicit approval before pod creation.
- Use at most one pod at a time unless I explicitly authorize parallelism.
- Reap any pod when finished.
- Do not merge the PR.
- Avoid the full local test suite on the 4 GB Hetzner host; use focused checks and demolab build.

Candidate ladder:

0. Control: exp071 architecture/readout without new adaptive controls.
1. Trainable leak only:
  - train-leak
2. Adaptive threshold only:
  - adaptive-threshold
3. Combined:
  - train-leak -adaptive-threshold

Suggested default bounds:

- E membrane tau: [5, 50] ms
- I membrane tau: [2, 20] ms
- adaptive threshold tau: [50, 500] ms
- adaptive threshold initial strength: 1.0 mV
- adaptive threshold max strength: 20.0 mV

Deliverables:

- Produce artifacts/data/exp072 with numbers.json, provenance, reproducer, training curves, firing-rate diagnostics, parameter diagnostics for learned tau/adaptation values, and matched input/E/I rasters.
  - Write writings/exp072.typ as the canonical cold-readable experiment report.
  - Include this goal prompt below the abstract.
  - Append timestamped activity-log/thread checkpoints in the experiment appendix.
  - Record scientific decisions, failures, anomalies, costs, commits, results, and pending work.
  - Sanitize any publishable logs before committing.
  - Build and validate with focused checks plus demolab build.
  - Commit meaningful attempts, including killed attempts, with clear messages.
  - Push the branch and update the PR with evidence.
  - Finish at the human review gate with a concise evidence summary, exact compute spend, validation performed, links to the rendered exp072 file and PR, and a recommendation for the next move toward 90% SHD.
- </objective>

Continuation behavior:

- This goal persists across turns. Ending this turn does not require shrinking the objective to what fits now.

- Keep the full objective intact. If it cannot be finished now, make concrete progress toward the real requested end state, leave the goal active, and do not redefine success around a smaller or easier task.
- Temporary rough edges are acceptable while the work is moving in the right direction. Completion still requires the requested end state to be true and verified.

#### Budget:

- Tokens used: 0
- Token budget: none
- Tokens remaining: unbounded

#### Work from evidence:

Use the current worktree and external state as authoritative. Previous conversation context can help locate relevant work, but inspect the current state before relying on it. Improve, replace, or remove existing work as needed to satisfy the actual objective.

#### Progress visibility:

If `update_plan` is available and the next work is meaningfully multi-step, use it to show a concise plan tied to the real objective. Keep the plan current as steps complete or the next best action changes. Skip planning overhead for trivial one-step progress, and do not treat a plan update as a substitute for doing the work.

#### Fidelity:

- Optimize each turn for movement toward the requested end state, not for the smallest stable-looking subset or easiest passing change.
- Do not substitute a narrower, safer, smaller, merely compatible, or easier-to-test solution because it is more likely to pass current tests.
- Treat alignment as movement toward the requested end state. An edit is aligned only if it makes the requested final state more true; useful-looking behavior that preserves a different end state is misaligned.

#### Completion audit:

Before deciding that the goal is achieved, treat completion as unproven and verify it against the actual current state:

- Derive concrete requirements from the objective and any referenced files, plans, specifications, issues, or user instructions.
- Preserve the original scope; do not redefine success around the work that already exists.
- For every explicit requirement, numbered item, named artifact, command, test, gate, invariant, and deliverable, identify the authoritative evidence that would prove it, then inspect the relevant current-state sources: files, command output, test results, PR state, rendered artifacts, runtime behavior, or other authoritative evidence.
- For each item, determine whether the evidence proves completion, contradicts completion, shows incomplete work, is too weak or indirect to verify completion, or is missing.
- Match the verification scope to the requirement's scope; do not use a narrow check to support a broad claim.
- Treat tests, manifests, verifiers, green checks, and search results as evidence only after confirming they cover the relevant requirement.
- Treat uncertain or indirect evidence as not achieved; gather stronger evidence or continue the work.

Do not rely on intent, partial progress, memory of earlier work, or a plausible final answer as proof of completion. Marking the goal complete is a claim that the full objective has been finished and can withstand requirement-by-requirement scrutiny. Only mark the goal achieved when current evidence proves every requirement has been

satisfied and no required work remains. If the evidence is incomplete, weak, indirect, merely consistent with completion, or leaves any requirement missing, incomplete, or unverified, keep working instead of marking the goal complete. If the objective is achieved, call `update_goal` with status "complete" so usage accounting is preserved. If the achieved goal has a token budget, report the final consumed token budget to the user after `update_goal` succeeds.

Blocked audit:

- Do not call `update_goal` with status "blocked" the first time a blocker appears.
- Only use status "blocked" when the same blocking condition has repeated for at least three consecutive goal turns, counting the original/user-triggered turn and any automatic goal continuations.
- If the user resumes a goal that was previously marked "blocked", treat the resumed run as a fresh blocked audit. If the same blocking condition then repeats for at least three consecutive resumed goal turns, call `update_goal` with status "blocked" again.
- Use status "blocked" only when you are truly at an impasse and cannot make meaningful progress without user input or an external-state change.
- Once the blocked threshold is satisfied, do not keep reporting that you are still blocked while leaving the goal active; call `update_goal` with status "blocked".
- Never use status "blocked" merely because the work is hard, slow, uncertain, incomplete, or would benefit from clarification.

Do not call `update_goal` unless the goal is complete or the strict blocked audit above is satisfied. Do not mark a goal complete merely because the budget is nearly exhausted or because you are stopping work.

</codex\_internal\_context>

## Assistant

2026-07-19T23:06:10.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

I'll pick this up from the actual repo state first: confirm we're on updated `main`, read the Demolab runbook as required, then branch exp072 and build the smallest useful implementation/checkpoint before any compute.

## Assistant

2026-07-19T23:06:25.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

I'm going to use the GitHub publishing skill when we get to branch/PR work, since this task explicitly includes pushing and opening/updating a PR. First I'm doing the local repo/runbook checks.

## Assistant

2026-07-19T23:06:55.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

Runbook check is done. Next I'm reading the repo's current state and the GitHub publishing instructions before touching branches/PRs.

**Assistant**

2026-07-19T23:07:25.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

State is clean on `main` at the intended merge commit. I'm going to branch now, then scaffold exp072 against the existing exp071 runner/report rather than inventing a new pathway.

**Assistant**

2026-07-19T23:08:30.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

The experiment runner can mostly reuse exp069/071. One thing I'm adding deliberately is parameter diagnostics: exp072 needs learned leak/adaptation values in artifacts, so I'm checking what the SNN engine already records before deciding whether the runner can extract them without touching `tools/snn`.

**Assistant**

2026-07-19T23:09:10.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

I'm going to create exp072 as an exp071-derived runner/report, then patch the scientific ladder from “readout/capacity” to “control/leak/adaptation/combined”. No `tools/snn` edits should be needed for this first stage.

**Assistant**

2026-07-19T23:10:05.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

Good: the engine already stores the trainable logits in checkpoints/weight dumps, so exp072 can extract diagnostics from saved weights in the experiment runner. I'm patching that into the runner now.

**Assistant**

2026-07-19T23:11:10.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

Small correction in-flight: the first broad patch tried to move too much at once. I'm splitting it into boring little patches now—the reliable way, less heroic, fewer gremlins.

**Assistant**

2026-07-19T23:12:10.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

Candidate registry is now the four planned conditions: control, trainable leak, adaptive threshold, combined. Next patch wires the flags and validation gates.

**Assistant**

2026-07-19T23:13:05.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

The runner now validates the new flags and will export learned parameter summaries from trained checkpoints. I'm updating the report so it's exp072-specific and doesn't expect old exp071 checkpoint JSONs.

**Assistant**

2026-07-19T23:14:50.000Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

I'm creating the first activity checkpoint now. I'll keep the committed log sanitized and compact, and store the raw visible transcript copy outside the published artifact path with only its hash prefix referenced in the article metadata.

**Assistant**

2026-07-19T23:15:12.917Z

Role: assistant · Checkpoint: cp001 · Session: 2026-07-19-exp072-codex

Sanitization check: no credentials, tokens, SSH material, IP addresses, environment dumps, or private infra details have appeared in the visible text I'm about to publish. The private raw copy will still stay out of the article and out of git; only a SHA-256 prefix goes into metadata.

**Checkpoint cp002**

Timestamp: `#trace-two.checkpoint_time_utc`. Sanitized source hash prefix: `#trace-two.sanitized_sha256_prefix`.

**Decisions, actions, and pending work**

1. 2026-07-19T23:16:40.000Z — Focused validation passed: python compile and Ruff for experiments/exp072.py.
2. 2026-07-19T23:17:40.000Z — Demolab build initially stubbed exp072 because artifact regeneration removed the activity checkpoint; fixed by restoring activity after publication and recording the failure.
3. 2026-07-19T23:18:35.000Z — Demolab build then passed with exp072 included.
4. 2026-07-19T23:23:35.000Z — Control local smoke passed: COBA 5.47%, PING 10.16%, both finite and active.
5. 2026-07-19T23:28:05.000Z — Trainable-leak local smoke passed: COBA 5.47%, PING 11.72%, both finite and active.
6. 2026-07-19T23:32:55.000Z — Adaptive-threshold local smoke passed: COBA 5.47%, PING 10.94%, both finite and active.
7. 2026-07-19T23:36:55.000Z — Combined local smoke passed: COBA 3.91%, PING 10.16%, both finite and active.
8. 2026-07-19T23:37:35.000Z — Refreshed pre-result artifacts so numbers.json records the all-candidate smoke ladder.
9. 2026-07-19T23:37:57.083Z — No paid compute has started; RunPod spend remains 0 USD; no pods were created.

**Visible messages added****Assistant**

2026-07-19T23:15:30.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Private raw checkpoint copy is written outside the repo. I'm hashing it now, then I'll add the sanitized JSON checkpoint under `artifacts/data/exp072/activity/` so the article can render.

**Assistant**

2026-07-19T23:15:45.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Checkpoint hash prefix is `a313f4e2bed6`. I'm committing only sanitized visible messages and a ledger of decisions/actions—not the private raw file or any tool payloads.

**Assistant**

2026-07-19T23:16:10.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Sanitized checkpoint JSON is in place. Next: focused code validation and generation of the pre-result `artifacts/data/exp072/numbers.json` so the report can build.

**Assistant**

2026-07-19T23:16:40.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Python compile and Ruff passed for the new runner. I'm publishing the pre-result artifact now; this is local/no paid compute.

**Assistant**

2026-07-19T23:17:10.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Pre-result artifacts are published under `artifacts/data/exp072`. I'm building the Demolab site/PDFs now to catch Typst/data-contract issues before the checkpoint commit.

**Assistant**

2026-07-19T23:17:40.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Build found the expected snag: `publish\_pre\_result()` regenerated `artifacts/data/exp072` and wiped the activity file I'd just added. That's useful evidence; I'll make the runner preserve/copy activity checkpoints during publication so this doesn't recur.

**Assistant**

2026-07-19T23:18:05.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

I'm treating that as a failed validation attempt and fixing forward. The checkpoint itself stays cp001; the build failure and fix will be recorded in the next meaningful activity checkpoint after the scaffold is stable.

**Assistant**

2026-07-19T23:18:35.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Activity checkpoint restored into the generated artifact. I'm rebuilding now; if this passes, I'll move on to the lightweight local smoke stage.

**Assistant**

2026-07-19T23:19:05.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Demolab build now passes with exp072 included. I'm starting the local 128/128 two-epoch smoke ladder next, one candidate at a time and still zero paid compute.

**Assistant**

2026-07-19T23:19:50.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Control smoke is running; first COBA-style cell is finite so far. I'll let this one finish before starting the adaptive candidates so any failure is easy to attribute.

**Assistant**

2026-07-19T23:20:20.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Still in the first local smoke, evaluation phase. This host is predictably slow for 1000 ms SHD even at 128 samples, but we're making progress and not spending cloud money.

**Assistant**

2026-07-19T23:20:50.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Control COBA-style smoke epoch 1 finished at finite loss and nonzero E activity; epoch 2 is underway. After this runner will do PING for the same candidate.

**Assistant**

2026-07-19T23:21:50.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

COBA-style control smoke completed cleanly in about 2 minutes with active firing. PING-style control is now training and also active at initialization.

**Assistant**

2026-07-19T23:22:20.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

PING control smoke is finite through epoch 1, with low-but-nonzero E and active I firing. Good enough for plumbing so far; waiting for epoch 2/rasters.

**Assistant**

2026-07-19T23:23:35.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Control local smoke passed: COBA 5.47%, PING 10.16%, both finite and active. The runner printed the full split provenance noisily, but that's just stdout; committed artifacts keep the provenance in JSON. I'm going to smoke the three new-control candidates too before the first PR checkpoint, because that is the best early guard against a bad ladder.

**Assistant**

2026-07-19T23:24:20.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Trainable-leak smoke is underway. Parameter count increased as expected, so the flag is reaching the model.

**Assistant**

2026-07-19T23:25:25.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Trainable-leak COBA-style cell is finite and active; it's near the end of epoch 2.

**Assistant**

2026-07-19T23:26:00.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Trainable-leak COBA-style smoke passed. PING-style trainable-leak smoke has started, also with the expected larger parameter count.

**Assistant**

2026-07-19T23:26:30.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

PING trainable-leak is finite through the training batches of epoch 1; waiting on validation/epoch 2.

**Assistant**

2026-07-19T23:27:00.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

PING trainable-leak epoch 1 passed: finite, active E/I, no obvious smoke failure.

**Assistant**

2026-07-19T23:27:30.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Trainable-leak PING is at final validation; this candidate is almost done.



**Assistant**

2026-07-19T23:28:05.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Trainable-leak smoke passed too: COBA 5.47%, PING 11.72%, both finite/active. Next is adaptive-threshold smoke.

**Assistant**

2026-07-19T23:28:45.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold smoke is running; parameter count increased as expected and initial E activity is a bit lower than control, which is plausible for adaptation.

**Assistant**

2026-07-19T23:29:15.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold COBA-style epoch 1 is finite; validation completed, epoch summary imminent.

**Assistant**

2026-07-19T23:29:45.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold COBA-style is finite/active through epoch 1, training epoch 2 now.

**Assistant**

2026-07-19T23:30:45.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold COBA-style completed its epochs finite/active; waiting for the runner to finish checkpointing and start PING.

**Assistant**

2026-07-19T23:31:15.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold COBA-style passed; PING-style adaptive threshold is now training and active.

**Assistant**

2026-07-19T23:31:45.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold PING epoch 1 passed finite with active E/I.

**Assistant**

2026-07-19T23:32:15.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold PING is in epoch 2. Still finite; no smoke kill signal.

## Assistant

2026-07-19T23:32:55.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Adaptive-threshold smoke passed: COBA 5.47%, PING 10.94%, finite/active. Last local smoke is the combined candidate.

## Assistant

2026-07-19T23:33:25.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined smoke started. Parameter count is higher again, matching both flag families being present.

## Assistant

2026-07-19T23:33:55.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined COBA-style epoch 1 is finite; validation is underway.

## Assistant

2026-07-19T23:34:25.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined COBA-style is active and finite through epoch 1; epoch 2 is almost through training.

## Assistant

2026-07-19T23:34:55.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined COBA-style completed finite/active; waiting for checkpointing and then PING.

## Assistant

2026-07-19T23:35:25.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined COBA-style passed; PING-style combined is now training.

## Assistant

2026-07-19T23:35:55.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined PING epoch 1 passed finite with active E/I; final epoch underway.

**Assistant**

2026-07-19T23:36:25.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Combined PING is at final validation. After it exits I'll refresh the pre-result artifact to record the latest local smoke state and rebuild.

**Assistant**

2026-07-19T23:36:55.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

All four local smokes passed. I'm patching the pre-result publisher to record the whole local smoke ladder, not just whichever `EXP072\_ATTEMPT` was selected last.

**Assistant**

2026-07-19T23:37:15.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

The publisher now collects all four local smoke summaries. I'm adjusting the article wording to recognize the full-ladder smoke state.

**Assistant**

2026-07-19T23:37:35.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Now I'll refresh `artifacts/data/exp072` with the all-smoke pre-result state. This will regenerate the artifact directory, so I'll restore the activity checkpoint afterward before building.

**Assistant**

2026-07-19T23:37:50.000Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Pre-result artifact refreshed. I'm adding cp002 now to record the smoke-ladder milestone and the one validation hiccup/fix, then the article will include both cp001 and cp002.

**Assistant**

2026-07-19T23:37:57.083Z

Role: assistant · Checkpoint: cp002 · Session: 2026-07-19-exp072-codex

Sanitization for cp002: again, no credentials/tokens/SSH material/IPs/environment dumps/private infra details in the visible text I'm publishing; tool payloads stay out.

**Checkpoint cp003**

Timestamp: `#trace-three.checkpoint_time_utc`. Sanitized source hash prefix: `#trace-three.sanitized_sha256_prefix`.

**Decisions, actions, and pending work**

1. 2026-07-19T23:38:45.000Z — Rebuilt successfully after adding cp002 to the article.

2. 2026-07-19T23:39:25.000Z — Restored tracked PDF rebuild noise and quarantined unrelated untracked generated PDFs outside the repo; retained exp072.pdf.
3. 2026-07-19T23:41:20.000Z — Committed first exp072 checkpoint as c580b7c: Add exp072 adaptive SHD scaffold.
4. 2026-07-19T23:41:45.000Z — Pushed branch agent/exp072-adaptive-shd to origin.
5. 2026-07-19T23:42:00.000Z — Opened draft PR #57: <https://github.com/eoinmurray/pinglab/pull/57>.
6. 2026-07-19T23:42:15.000Z — gh pr edit failed because of a deprecated Projects GraphQL field, leaving the body empty; fixed by patching the PR through the REST API.
7. 2026-07-19T23:42:30.000Z — PR #57 body now records validation evidence, zero spend, and the next RunPod approval gate.

### Visible messages added

#### Assistant

2026-07-19T23:38:20.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

cp002 is written with hash prefix `bec9f91c83e2`. I'm wiring it into the article and rebuilding.

#### Assistant

2026-07-19T23:39:00.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Focused validation is green: compile, Ruff, and Demolab build all pass. I'm cleaning the generated PDF noise now so the first commit contains only exp072's intended files/artifacts.

#### Assistant

2026-07-19T23:39:25.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

The build rewrote many existing PDFs, which is normal here but not part of this PR. I'm restoring tracked PDFs and keeping only the new exp072 PDF plus exp072 data/report/runner.

#### Assistant

2026-07-19T23:39:45.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

The shell guard blocked my explicit `rm -f` cleanup, fair enough. I'll use a safer move-to-quarantine approach for the unrelated untracked PDFs.

#### Assistant

2026-07-19T23:40:05.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Tracked PDFs are restored. Now I'm moving the unrelated untracked build PDFs out of the repo, leaving `exp072.pdf` intact.

**Assistant**

2026-07-19T23:40:30.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Worktree scope is clean: only new exp072 runner, article, data, and PDF are untracked. I'm doing a quick artifact sanity read before committing.

**Assistant**

2026-07-19T23:41:00.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Artifact provenance looks sane: local host, dirty patch capturing the new exp072 scaffold, zero spend, all-smoke ladder recorded. I'm staging only the exp072 files now and making the first checkpoint commit.

**Assistant**

2026-07-19T23:41:20.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

First checkpoint commit is in: `c580b7c` ("Add exp072 adaptive SHD scaffold"). Next I'm pushing the branch and opening the draft PR, per the goal.

**Assistant**

2026-07-19T23:41:45.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Branch is pushed. I'm opening a draft PR now with the validation evidence and zero-spend status.

**Assistant**

2026-07-19T23:42:00.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Draft PR opened as #57. Minor process wart: my first body-file helper tried plain `python` (not allowed/available here), so I'm checking/updating the PR body with `uv run python` now.

**Assistant**

2026-07-19T23:42:15.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

`gh pr edit` hit GitHub's deprecated Projects GraphQL field bug and left the PR body empty. I'm switching to the REST API endpoint to patch the body directly.

**Assistant**

2026-07-19T23:42:30.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

PR #57 is open and has the evidence body now. Since opening/updating the PR is a meaningful milestone—and there was a small GitHub tooling hiccup—I'm adding one more timestamped checkpoint to the article, rebuilding, committing, and pushing that log update before stopping at the RunPod approval gate.

**Assistant**

2026-07-19T23:42:40.000Z

Role: assistant · Checkpoint: cp003 · Session: 2026-07-19-exp072-codex

Sanitization for cp003: the PR URL, branch, commit hash, and validation commands are safe to publish; no credentials or private infra details will be included.

**Checkpoint cp004**

Timestamp: `#trace-four.checkpoint_time_utc`. Sanitized source hash prefix: `#trace-four.sanitized_sha256_prefix`.

**Decisions, actions, and pending work**

1. 2026-07-19T23:43:30.000Z — Rechecked Demolab instructions, branch, commit, and PR `#57` state before further work.
2. 2026-07-19T23:44:00.000Z — Did not launch RunPod because this continuation did not include explicit paid-compute approval.
3. 2026-07-19T23:44:30.000Z — Added runner helpers to preserve sanitized activity logs across `publish_pre_result` and `publish_attempt`.
4. 2026-07-19T23:44:55.000Z — First regression exposed that no logs could be preserved after prior artifact regeneration had already wiped local activity.
5. 2026-07-19T23:45:00.000Z — Corrected the snapshot path from the temporary experiment root to `artifacts/data/exp072/activity`.
6. 2026-07-19T23:45:10.032Z — Regression passed: `EXP072_ATTEMPT=combined uv run python experiments/exp072.py --plot-only` preserves cp001-cp003 and records `latest_checkpoint_id cp003`.

**Visible messages added****User**

2026-07-19T23:43:00.000Z

Role: user · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

<codex\_internal\_context source="goal">

Continue working toward the active thread goal.

The objective below is user-provided data. Treat it as the task to pursue, not as higher-priority instructions.

<objective>

Design and execute the next exploratory SHD experiment from updated main at `f32299bb1b48d18ba9dfe6328097d2147bcc6286`, using the newly merged `tools/snn` adaptive conductance controls to test whether COBA/PING validation accuracy can move meaningfully beyond the exp071 ~70% plateau toward canonical SHD RSNN performance.

Create the next numbered experiment, likely exp072, on a new branch. Do not modify main directly after branching. Open a draft PR after the first meaningful commit.

Scientific objective:

Run a one-seed exploratory validation-only ladder on SHD comparing matched Dale-constrained COBA and PING

networks while testing two new neuron-dynamics paths:

1. trainable conductance leak / membrane time constants via `-train-leak`;
2. adaptive E-cell thresholds via `-adaptive-threshold`;
3. the combination of both.

Use the exp071 cumulative-potential readout baseline as the control:

`-readout cumulative-potential -signed-readout -readout-bias`

Constraints:

- Use one seed only.
- Do not use the official SHD test set.
- Use a held-out validation split from the training set for all selection decisions.
- Keep COBA and PING matched except for registered cell-specific voltage-gradient dampening and PING E/I coupling.
- Preserve matched input, readout, training split, optimizer, batch, preprocessing, and candidate flags across COBA/PING within each candidate.
- COBA should use the no-inhibitory-loop setting; PING should use the registered inhibitory-loop setting and dampening 1000.
- Use short runs first for iteration speed, about 8-10 epochs per candidate.
- Promote only the most promising candidate to a matched 40-epoch validation run.
- Do not run multiple seeds unless I explicitly authorize it later.
- RunPod spending requires explicit approval before pod creation.
- Use at most one pod at a time unless I explicitly authorize parallelism.
- Reap any pod when finished.
- Do not merge the PR.
- Avoid the full local test suite on the 4 GB Hetzner host; use focused checks and demolab build.

Candidate ladder:

0. Control: exp071 architecture/readout without new adaptive controls.

1. Trainable leak only:

`-train-leak`

2. Adaptive threshold only:

`-adaptive-threshold`

3. Combined:

`-train-leak -adaptive-threshold`

Suggested default bounds:

- E membrane tau: [5, 50] ms
- I membrane tau: [2, 20] ms
- adaptive threshold tau: [50, 500] ms
- adaptive threshold initial strength: 1.0 mV
- adaptive threshold max strength: 20.0 mV

Deliverables:

- Produce artifacts/data/exp072 with numbers.json, provenance, reproducer, training curves, firing-rate diagnostics, parameter diagnostics for learned tau/adaptation values, and matched input/E/I rasters.
- Write writings/exp072.typ as the canonical cold-readable experiment report.

- Include this goal prompt below the abstract.
- Append timestamped activity-log/thread checkpoints in the experiment appendix.
- Record scientific decisions, failures, anomalies, costs, commits, results, and pending work.
- Sanitize any publishable logs before committing.
- Build and validate with focused checks plus demolab build.
- Commit meaningful attempts, including killed attempts, with clear messages.
- Push the branch and update the PR with evidence.
- Finish at the human review gate with a concise evidence summary, exact compute spend, validation performed, links to the rendered exp072 file and PR, and a recommendation for the next move toward 90% SHD.

</objective>

</codex\_internal\_context>

**Assistant**

2026-07-19T23:43:10.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

I'm resuming from the branch/PR state and will re-run the Demolab manual check first. The next scientific step is the paid RunPod short ladder, but I'll verify local/PR state before deciding whether I have enough authority to launch it.

**Assistant**

2026-07-19T23:43:30.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

I'll use the GitHub publishing workflow only for PR updates/comments after I've generated new evidence; first I'm checking the current local state.

**Assistant**

2026-07-19T23:44:00.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

State is clean on PR #57 at `49a684e`. I don't have explicit paid RunPod approval in this turn, so I'm going to use this turn to harden the runner/report around activity checkpoints and RunPod collection before spending anything.

**Assistant**

2026-07-19T23:44:15.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

One issue from the previous checkpoint is worth fixing properly: `--plot-only` regenerates `artifacts/data/exp072`, so activity logs need to survive publication rather than being hand-restored. I'm patching that into exp072 now.

**Assistant**

2026-07-19T23:44:30.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex



I found the exact weak point: `publish_pre_result()` and `publish_attempt()` don't preserve existing `activity/messages_cp*.json`. I'm adding a small helper that snapshots those files before the Demolab publish context and copies them back into the new artifact.

**Assistant**

2026-07-19T23:44:45.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

The preservation helper is patched. I'm testing it by running `-plot-only` locally; this is the same path that previously wiped the checkpoint files, so it's the right regression check.

**Assistant**

2026-07-19T23:44:55.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

Regression caught a second nuance: because the previous publish had already wiped local activity before this test started, there were no files for the helper to preserve. I'm restoring the committed checkpoints from git, then rerunning the same regression.

**Assistant**

2026-07-19T23:45:00.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

Aha, `ARTIFACTS` in this runner points at the temp experiment root, not the committed published artifact directory. That's why the helper saw nothing. I'm correcting it to snapshot from `artifacts/data/exp072/activity`.

**Assistant**

2026-07-19T23:45:05.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

Path fixed. I'm restoring the three checkpoint files from the last commit and rerunning the preservation regression.

**Assistant**

2026-07-19T23:45:10.032Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

The regression now passes: `-plot-only` preserves cp001–cp003 and records `latest_checkpoint_id: cp003` in `numbers.json`. I'm adding cp004 for this hardening fix, then I'll rebuild, commit, push, and leave the goal at the paid-compute approval gate.

**Assistant**

2026-07-19T23:45:15.000Z

Role: assistant · Checkpoint: cp004 · Session: 2026-07-19-exp072-codex

Sanitization for cp004: it will include repo state, PR number, validation commands, and the runner fix; no credentials, tokens, SSH material, IPs, environment dumps, private paths, or tool payloads.

**Checkpoint cp005**

Timestamp: #trace-five.checkpoint\_time\_utc. Sanitized source hash prefix: #trace-five.sanitized\_sha256\_prefix.

Note: this checkpoint records the scientific ledger for the long RunPod monitoring turn, but does not claim a complete verbatim transcript because no raw transcript export was available in the workspace.

**Decisions, actions, and pending work**

1. 2026-07-20T00:00:00.000Z — User authorized RunPod spending for the whole exp072 execution, including 40-epoch runs if needed, while preserving the one-pod-at-a-time constraint.
2. 2026-07-20T02:20:07.957Z — Completed and published the short control rung: COBA selected 60.17% validation accuracy; PING selected 56.86%. Both were finite and active.
3. 2026-07-20T02:59:09.000Z — Completed and published the short train\_leak rung: COBA selected 58.95%; PING selected 57.72%. This was the only modified candidate that improved PING over control in the short ladder.
4. 2026-07-20T03:36:28.000Z — Completed and published the short adaptive\_threshold rung: COBA selected 50.61%; PING selected 53.68%. Both were active but weaker than control/train\_leak.
5. 2026-07-20T04:08:53.000Z — Completed and published the short combined rung: COBA selected 50.37%; PING selected 50.98%. Both were active but weaker than train\_leak.
6. 2026-07-20T04:10:00.000Z — Promoted train\_leak to the matched 40-epoch stage because it was the only modification that improved PING while keeping COBA close.
7. 2026-07-20T05:17:12.000Z — Final40 train\_leak COBA completed and was collected with no active pod remaining before the next cell launched.
8. 2026-07-20T06:29:29.000Z — Final40 train\_leak PING completed, was collected, and the final40 attempt was published. No active pods remained after collection.
9. 2026-07-20T06:30:00.000Z — Final40 train\_leak selected 69.49% validation accuracy for COBA at epoch 37 and 71.08% for PING at epoch 40. PING had a small 1.59 percentage-point edge.
10. 2026-07-20T06:33:34.862Z — Cumulative experiment spend ledgers total 4.66 USD, marked timestamp-estimated pending provider billing reconciliation.

**Visible milestone messages added****User**

2026-07-20T00:00:00.000Z

Role: user · Checkpoint: cp005 · Session: 2026-07-20-exp072-codex

you have runpod permission for whole thing, 40 epoch runs if needed

**Assistant**

2026-07-20T04:10:00.000Z

Role: assistant · Checkpoint: cp005 · Session: 2026-07-20-exp072-codex

Short ladder readout: control is best by paired average, but `train\_leak` is the only modification that improves the target PING cell while keeping COBA close. I'm going to promote `train\_leak` to 40 epochs: it's the best scientific bet for "can trainable leak move PING upward?" rather than just re-running the control.

### Assistant

2026-07-20T06:30:00.000Z

Role: assistant · Checkpoint: cp005 · Session: 2026-07-20-exp072-codex

No active pods. Final40 result: `train\_leak` COBA selected 69.49% at epoch 37; PING selected 71.08% at epoch 40. That's a real small PING edge, but still far below SOTA territory.

### Checkpoint cp006

Timestamp: `#trace-six.checkpoint_time_utc`. Sanitized source hash prefix: `#trace-six.sanitized_sha256_prefix`.

### Decisions, actions, and pending work

1. 2026-07-20T08:01:22.000Z — Launched exp072 combined final80 COBA after adding and pushing a registered final80 stage.
2. 2026-07-20T08:03:42.000Z — User requested COBA and PING run in parallel; stopped the local sequential monitor without stopping COBA and launched combined final80 PING as a second pod.
3. 2026-07-20T10:22:06.000Z — PING final80 self-terminated while COBA continued.
4. 2026-07-20T11:22:09.000Z — COBA final80 self-terminated; collection fetched both cells and no active pods remained.
5. 2026-07-20T11:23:31.000Z — Collected final80 combined artifacts.
6. 2026-07-20T11:24:00.000Z — Selected final80 combined results: COBA 64.58% at epoch 77; PING 71.69% at epoch 73.
7. 2026-07-20T11:24:30.000Z — Dynamics warnings: COBA saturated/stuck; PING stuck. Combined PING only slightly exceeded train\_leak final40 while taking twice the epochs; combined COBA remained worse than train\_leak final40.
8. 2026-07-20T11:25:02.841Z — Published final80 combined locally with estimated cumulative spend pending final provider billing reconciliation.

### Visible milestone messages added

#### User

2026-07-20T08:02:00.000Z

Role: user · Checkpoint: cp006 · Session: 2026-07-20-exp072-codex

do ping and cobra in paralell on two pods

#### Assistant

2026-07-20T11:24:00.000Z

Role: assistant · Checkpoint: cp006 · Session: 2026-07-20-exp072-codex

Result: final80 combined selected COBA 64.58% (epoch 77) and PING 71.69% (epoch 73). PING is only +0.61 pp above leak-only final40, but with stuck warnings and twice the epochs; COBA is worse and saturated/stuck. No active pods.

# Plastic recurrent excitation reaches the old PING regime

20 July 2026

## Abstract

This exploratory experiment tested the next biologically plausible path after exp071/exp072: keep the cumulative-potential readout, keep the historical one-seed validation-only SHD split, and make recurrent  $E \rightarrow E$  excitation both nonzero and plastic while preserving Dale signs. The original matched COBA/PING design still failed at the required local smoke gate: PING remained finite and active, but the matched COBA cell repeatedly produced skipped/non-finite updates even after reducing the requested  $W_{EE}$  scale from 0.3 0.01 through 0.03 0.01, 0.003 0.001, and finally 0.0003 0.0001. After that gate failure, an explicitly authorized PING-only continuation ran the surviving cell on Modal. The first eight-epoch short stage reached 58.33% validation accuracy; after reviewing that trajectory, the user authorized the forty-epoch continuation. The final40 run selected 71.32% held-out validation accuracy at epoch 39 and finished at 68.38%.  $W_{EE}$  remained nonnegative and trained away from its tiny initialization. The result is a modest PING-only recovery to the old 70% regime, not a matched COBA/PING result and not a clear jump to a new high-accuracy regime.

## Goal prompt

```
/goal Design and execute a new exploratory SHD experiment on a new branch/PR,
testing whether nonzero Dale-constrained trainable recurrent excitation moves
the matched COBA/PING models beyond the current ~70% regime.
```

```
Use current main as the base. Build exp073 around the best surviving SHD
recipe from exp071/exp072, especially the cumulative-potential readout. Do
not rerun the old baseline unless needed for debugging; use exp071/exp072 as
the historical baseline.
```

```
Experiment:
```

- run matched COBA and PING cells with nonzero  $W_{EE}$  initialization and --trainable-w-ee;
- keep  $W_{in}$  and  $W_{out}$  trainable as in the current training path;
- keep Dale signs enforced; do not use free signed recurrence;
- start with a modest nonzero  $W_{EE}$  initialization, e.g. --w-ee 0.03 0.01, unless local inspection of current parameter scales suggests a safer nearby value;
- keep input preprocessing, dataset split, readout, optimizer, batch size, and evaluation protocol matched across COBA and PING;
- keep the comparison exploratory and single-seed unless I explicitly ask for replication.

```
Protocol:
```

- implement through experiments/exp073.py and existing tools/snn CLI capabilities if possible;
- do not edit tools/snn unless the current CLI cannot express nonzero trainable  $W_{EE}$  cleanly; if a tools/snn change is required, stop and explain exactly why before editing;

- run a local smoke/scout stage first with few epochs/samples to confirm finite loss, active spiking, and  $W_{EE}$  actually changes during training;
- if both cells are finite and active, run a short RunPod exploratory stage, fewer than 40 epochs for iteration speed;
- if accuracy looks meaningfully better than the exp071/exp072 historical ~70% regime without pathological firing or NaNs, run a 40-epoch confirmation for the promising cell(s);
- COBA and PING may run in parallel on separate RunPod pods when useful;
- RunPod spending is authorized up to \$40 total; reap all pods when finished.

#### Deliverables:

- artifacts/data/exp073 with provenance, numbers.json, reproducer, training curves, firing-rate diagnostics,  $W_{EE}$  diagnostics, and matched rasters where relevant;
- writings/exp073.typ as a cold-readable Demolab experiment report comparing exp073 to the historical exp071/exp072 baseline;
- update the Spiking Heidelberg Digits collection so exp073 is the next canonical experiment;
- build successfully;
- commit focused implementation/results changes, push the branch, and open a new PR;
- do not merge unless I explicitly ask.

#### End at the review gate with:

- best/selected COBA and PING accuracies;
- whether trainable nonzero  $W_{EE}$  appears to move us beyond the ~70% regime;
- $W_{EE}$  diagnostics showing it was nonzero and trained;
- firing-rate/pathology summary;
- exact compute spend;
- validation performed;
- PR link and rendered exp073 link.

## Methods

The intended comparison inherited the exp071/exp072 SHD recipe: seed 42, 7340 development-training utterances, 816 held-out validation utterances, batch size 32, Adam learning rate 0.0004, 1 ms simulation steps, 1000 ms windows, matched input preprocessing, and the cumulative-potential readout with signed abstract readout weights and a trainable bias. The official SHD test set remained sealed and inaccessible to the runner.

The only intended new scientific ingredient was `--trainable-w-ee` with nonzero `--w-ee`.

Dale's law stayed enabled;  $W_{EI}$ ,  $W_{IE}$ , and  $W_{II}$  stayed frozen. COBA kept the no-inhibitory-loop recipe and no voltage-gradient dampening; PING kept the registered inhibitory loop and dampening 1000.

During implementation, the local CLI accepted `--w-ee` but training did not pass it into model construction. Commit 247e186 fixed that plumbing and added a focused regression test before this experiment ran. A later transport fix moved exp073's Modal worker function to module scope and aligned its Python image with the host, without changing any scientific parameter.

## Local gate


The final registered local scout used the same nonzero  $W_{EE}$  initialization now recorded in the PING-only configuration: `--w-ee #r.config.w_ee_init.at(0) #r.config.w_ee_init.at(1)`.


The gate required both matched cells to be finite, active, non-saturated, and free of skipped or non-finite updates before any paid matched run. COBA failed that finite-update criterion while PING passed, so the locked matched COBA/PING result could not be promoted. The cloud result below is therefore the later authorized PING-only continuation, not a matched-network claim.

## Authorized PING-only continuation

After the matched local gate failed, the user authorized a design pivot: continue with the surviving PING cell only, without recasting it as a matched COBA/PING result. This continuation uses the same one seed, development-training/validation split, input preprocessing, cumulative potential readout, nonzero trainable  $W_{EE}$ , and PING dampening 1000. The eight-epoch short run reached 58.33%; after trajectory review, the user authorized the forty-epoch continuation recorded here.

| Cell | Selected acc. | Final acc. | Epoch | Final E rate | Final I rate |
|------|---------------|------------|-------|--------------|--------------|
| PING | 71.32%        | 68.38%     | 39    | 19.52 Hz     | 55.54 Hz     |





The PING-only  $W_{EE}$  diagnostics show selected mean 0.01463611 and mean absolute movement from initialization 0.0146355.

The selected checkpoint's  $W_{EE}$  norm grew without violating Dale's nonnegativity constraint. The run was dispatched on modal with GPU A10G. The timestamped compute ledger records 2026-07-23T12:30:20.490Z to 2026-07-23T15:22:25.613Z UTC, estimated billable GPU time 10291.6 s, and estimated spend 3.149 USD. This is a timestamp estimate pending provider-billing reconciliation, not an exact invoice.

### Timestamped result checkpoint

At 2026-07-23T15:22:25.613Z UTC, the user-authorized final40 result selected 71.32% validation accuracy at epoch 39 and finished at 68.38%. The run was finite and clean in the runner's summary, but the activity curves and live log show high activity with saturation warnings during training, so the result should be read as accuracy recovery with a dynamical caveat rather than a free improvement.



## Conclusion

The locked matched experiment still failed at the local gate: COBA could not be honestly promoted. The later PING-only run is therefore exploratory continuation evidence for the stable PING recipe, not matched COBA/PING evidence. Its 71.32% selected validation accuracy reaches the exp071/exp072 historical 70% PING regime and slightly edges over it on this one seed, but the final epoch falls back to 68.38% and the high-activity/saturation diagnostics make this a cautious exploratory signal, not a defensible high-accuracy claim.

Paid compute spend: 3.915 USD. Provider billing exact: **false**. Active RunPod pods after this checkpoint: 0.

# From Python graph to spikes

31 July 2026

## Abstract

This is the smallest useful end-to-end demonstration of `snnlang`. The experiment runner defines a PING circuit using the Python authoring API, compiles it into a deterministic data-only bundle, and invokes `tools/snn` through its command-line interface. The simulator receives an explicit, saved Poisson spike tensor rather than an implicit constant drive. The published record retains the graph, compiler reports, exact input, simulator rasters, and summary numbers. This entry tests plumbing, not a neuroscientific hypothesis.


## The compiled network



The graph contains 3 populations, 4 projections, 1 graph operations, and 4 parameter tensors. Its canonical graph digest is sha256:22ea86531342.... The simulator consumes this compiled description; the Python objects used to author it do not cross the process boundary.

## Exact spiking input and response

The saved input tensor has shape  $2000 \times 4 \times 784$  and contains 62629 spikes. Its requested uniform Poisson rate was 100 Hz and its realised rate was 99.85 Hz. The aligned raster below shows trial 0: the exact input events, then the excitatory and inhibitory events produced by the compiled network.



Across all 4 trials and 200 ms, the simulator measured mean E and I rates of 20.92 Hz and 62.5 Hz respectively. The displayed trial contains 15632 input, 1012 E, and 768 I spikes.

### What this establishes

The useful result is architectural: one short Python definition can be statically checked, visualised, serialised, handed to the existing optimised PyTorch simulator, and inspected as ordinary Demolab evidence. Execution settings remain with the experiment runner, while graph structure remains in the bundle. The next experiments can change the authored network without growing another pile of bespoke simulator flags—a small victory over configuration archaeology.

# A compiled graph learns

31 July 2026

## Abstract

This is an integration gate, not an MNIST benchmark. A Python `snnlang` program defines a 128-E/32-I PING network and a standard training recipe. The compiler writes the graph and recipe into a portable bundle; `tools/snn train --bundle` authenticates both, maps the supported subset onto the existing optimised PyTorch trainer, and trains on only 1000 MNIST examples for 4 epochs. The experiment asks one intentionally unglamorous question: does the compiled network actually learn?


## Graph and training scope



The graph fixes the PING topology, 0.5 ms simulation step, mean-voltage classifier, initialisers, and trainable/frozen parameter scope. The recipe fixes unit-weight cross-entropy, AdamW with learning rate 0.001 and weight decay 0.0001, gradient clipping, and epoch count. The runner owns execution choices: the deterministic MNIST subset, batch size 64, 100 ms presentation window, seed 75, and artifact locations.

The current backend is deliberately strict. It accepts trainable input and readout projections with frozen E↔I recurrence; unsupported objectives, parameter scopes, optimisers, or graph structures fail before training.

## Training trajectory



The 800-example training split and 200-example held-out split are tiny. Across the short run, training cross-entropy changed by  $-0.035$ , held-out cross-entropy by  $-0.027$ , and held-out accuracy by 1.5 percentage points. Best held-out accuracy was 64.5% at epoch 2. The trainer wrote both selected and final checkpoints in 14.3 seconds.

## Conclusion

The compiled graph trained: optimisation reduced the training objective and emitted ordinary `tools/snn` checkpoints and metrics. This does not establish competitive accuracy or good generalisation. It establishes the more basic vertical slice needed before migrating real experiments: Python graph  $\rightarrow$  authenticated bundle  $\rightarrow$  existing PyTorch training loop  $\rightarrow$  inspectable evidence.

# A bundle checkpoint replays


2 August 2026

## Abstract

This is an integration and equivalence experiment, not an accuracy benchmark. A Python `snnlang` program authors the current supported backend subset: MNIST input spikes, one 64-E/16-I PING cell, and a mean-voltage classifier. The compiled bundle owns the graph topology, initialisers, unit-weight cross-entropy objective, AdamW optimiser, epoch count, and trainable/frozen parameter scope. The runner owns execution choices: 160 deterministic MNIST examples, batch size 32, 40 ms presentation duration, 0.5 ms timestep, and seed 76.


The selected bundle-trained checkpoint replayed through `tools/snn sim --bundle --infer --load-weights` at 50%, exactly matching the trainer’s recorded best accuracy. The final checkpoint also replayed exactly. A focused deterministic unit gate separately shows exact bundle-vs-legacy equality for initial state dictionaries, forward logits, cross-entropy loss, gradients, and one AdamW step. This validates only the current MNIST PING + MeanVoltage adapter, not arbitrary `snnlang` graphs.

## Lifecycle checked



The experiment stores the complete executable bundle at `artifacts/data/exp076/network.bundle`, including `graph.json`, `training.json`, and the manifest that authenticates both. Training writes a selected checkpoint and a final checkpoint. Replay then exercises four load paths: bundle checkpoint through bundle inference, final bundle checkpoint through bundle inference, selected bundle checkpoint through the equivalent explicit legacy route, and a separately trained legacy checkpoint through the bundle route.

## Short training trajectory



The run used 128 training examples and 32 held-out examples from the deterministic split. Best held-out accuracy was 50% at epoch 2 the final epoch was 50%. The point is not that this tiny model is good at MNIST. The point is that an ordinary bundle-trained checkpoint is reloadable and produces reproducible held-out evaluation.

## Replay and checkpoint compatibility

| Check               | Reference | Fresh replay |
|---------------------|-----------|--------------|
| Selected checkpoint | 50%       | 50%          |
| Final checkpoint    | 50%       | 50%          |

Selected replay differed from the trainer by 0 pp, and final replay differed by 0 pp. The exact match is expected here because training-time evaluation and fresh inference use the same held-out split, presentation duration, seed, and deterministic Poisson evaluation generator.

Structurally, every checked checkpoint loaded with no missing keys, no unexpected keys, and no shape mismatches. The state dictionary keys were `W_ff.0`, `W_ff.1`, `W_ee.1`, `W_ei.1`, `W_ie.1`, and `W_ii.1`. The equivalent legacy route loaded the bundle-produced selected checkpoint and reached 50%. The bundle route loaded a checkpoint produced by a separate one-epoch legacy run and reached 15.625%, matching that legacy checkpoint's own selected accuracy.

## Deterministic one-step parity gate

| Stage                    | Result         |
|--------------------------|----------------|
| Initial state dictionary | exact          |
| Forward logits           | exact          |
| Cross-entropy loss       | exact          |
| Gradients                | exact          |
| One AdamW step           | exact          |
| Tolerance                | rtol 0, atol 0 |

The automated gate constructs the bundle and equivalent legacy configurations from their public descriptions, seeds both initialisations identically, feeds the exact same already-

encoded spike tensor and labels, and compares tensors in order. If a future edit breaks parity, the test reports the first divergent stage and tensor name rather than a generic failure.

The trainable parameter set is `W_ff.0` and `W_ff.1`: input and readout projections. The recurrent E/I matrices `W_ee.1`, `W_ei.1`, `W_ie.1`, and `W_ii.1` are frozen under the current bundle-training design. Unsupported objectives, parameter scopes, optimiser variants, graph shapes, and structural CLI overrides remain capability errors rather than silent fallbacks.

## Runtime and scope

The complete local experiment took 57.07 s, including bundle training, selected/final replay, legacy checkpoint loading, a tiny legacy checkpoint-production run, and bundle loading of that legacy checkpoint. Bundle training itself reported 8.44 s.

This establishes a small but useful invariant: for the currently supported MNIST PING + MeanVoltage subset, `snnlang` bundle execution is not merely shape-compatible with the legacy route; it is numerically identical for the deterministic one-step training calculation and checkpoint-compatible across the bundle and legacy inference routes. It says nothing about unsupported graph topologies, objectives, recurrent plasticity scopes, custom readouts, or accelerator-specific execution.



# Arbitrary coupled graphs execute natively

5 August 2026

## Abstract

This validation completes the cumulative architecture gates through ar063 Milestone 3. The new graph executor matches the active legacy single-PING reference exactly: seeded parameters, E and I spikes, mean-voltage output, and checkpoint replay all have zero recorded discrepancy. Its matched local steady-state runtime is below the legacy runtime, so the declared overhead gate passes without an exception. The arbitrary-graph fixture then executes two independently driven PING circuits in uncoupled, unidirectional, reciprocal, and explicitly delayed reciprocal forms. Every variant changes graph data only. This is an execution and causality result, not a scientific claim about inhibitory coupling.

## Registered goal

/goal Implement ar063 cumulatively through Appendix B.6 Milestone 3 on a new branch and PR from current main.

### Outcome:

Complete every unmet requirement in ar063 Appendix B from Milestone 1 through Milestone 3, culminating in graph-native execution of arbitrary coupled forward graphs. Demonstrate two independently driven PING circuits with reciprocal delayed inhibitory coupling, while preserving the legacy executor and all existing behaviour.

### Authority:

- You may make the additions and careful modifications required in tools/snn, tools/snnlang, schemas, focused tests, experiment runners, and Demolab writings.
- Do not change historical experiment runners merely to adopt snnlang.
- Do not change legacy defaults, CLI routing, checkpoint formats, parameter names, numerical behaviour, or artifact contracts.
- Do not begin Milestone 4 or run its scientific coupling sweep.
- No paid compute is authorized. Stop and ask if a required acceptance gate cannot reasonably run locally.
- Do not merge the PR; finish at the human review gate.

### Protocol:

1. Read writings/ar063.typ in full, treating Appendix B as normative. Inspect the repository and establish the actual status of Milestones 0–3 rather than assuming the status labels are current.
2. Preserve or safely stash unrelated generated-PDF drift before branching. Create a focused branch from current origin/main.
3. Complete Milestone 1 – freeze the compatibility seam:
  - add the versioned backend capability vocabulary and precise element-level diagnostics;

- introduce typed ExecutionSpec and ExecutionResult objects;
  - provide internal build, simulate, train, and infer request APIs;
  - make the existing CLI a thin caller of that API where required by B.4;
  - keep legacy as the default executor;
  - ensure bundle loading remains data-only and does not import snnlang;
  - prove representative MNIST, SHD, untrained, checkpoint, and recording compatibility.
4. Complete Milestone 2 – graph-native single-PING forward execution:
- make snnlang emit all state, scheduling, delay, initialization, constraint, output, and observable information without backend guesses;
  - implement a graph planner and coarse, vectorized PyTorch executor for the complete B.5 topology;
  - lower the complete graph before the timestep loop—do not dynamically interpret graph nodes each timestep;
  - keep torch.compile behind the existing internal boundary;
  - compare legacy and graph paths for parameter identities and shapes, seeded initialization, CPU state trajectories, spikes, outputs, recordings, and checkpoint round trips;
  - measure warm compiled steady-state runtime, compilation time, and peak memory independently;
  - require the stated 5–10% steady-state overhead target, or stop for review if a measured exception would need acceptance.
5. Complete Milestone 3 – arbitrary coupled forward graphs:
- support independently named components, arbitrary E/I population sizes, independent inputs, feedforward/recurrent/feedback projections, and explicit positive delays;
  - validate temporal causality, dimensions, polarity, and delayed feedback;
  - execute arbitrary named populations and projections, multiple incoming conductance streams, deterministic recurrent/feedback scheduling, delay buffers, and recordings from every population;
  - dense support is sufficient; do not expand into sparse or structured lowering.
6. Add a new Demolab validation experiment, using the next available experiment ID, whose acceptance fixture contains two independently driven PING circuits with GABA projections from each inhibitory population to the other circuit’s excitatory population. Include:
- uncoupled;
  - unidirectional;
  - reciprocal with zero additional coupling delay where valid under the declared scheduling semantics;
  - reciprocal with explicit positive delay.
7. Add exact micro-tests proving which timestep receives every delayed pulse, including boundary and recurrent-feedback cases. The experiment runner may calculate compact phase/synchrony diagnostics only to establish that named recordings are usable; do not perform the Milestone 4 scientific parameter

sweep or make a scientific coupling claim.

8. Require every coupling variant to be expressible by graph changes alone after the executor is implemented. Any variant requiring simulator-specific edits fails the Milestone 3 exit criterion.

9. Produce committed artifacts for the validation experiment:

- numbers.json;
- provenance and reproducer;
- canonical graph and bundle manifests;
- deterministic circuit diagrams;
- named input/E/I recordings for both circuits;
- exact delay-timing evidence;
- compatibility and performance measurements.

10. Write a cold-readable writings/expNNN.typ report. Put the full goal prompt immediately below the abstract and append a timestamped activity-log appendix recording decisions, implementation events, failures, anomalies, commits, validation, and conclusions. All reported numbers and figures must come from recorded artifacts.

11. Update the status ledger and relevant documentation in writings/ar063.typ with links to the experiment evidence and implementation commits. Mark a milestone demonstrated only after its complete gate passes.

Validation:

- Run focused lint, type, schema, and unit checks.
- Run all milestone-0 acceptance tests, including exp074–exp076.
- Run representative lightweight legacy MNIST, SHD, untrained, checkpoint, and recording smoke tests.
- Run Milestone 2 numerical parity and performance gates.
- Run Milestone 3 scheduling, delay-buffer, multi-input, polarity, dimension, recording, and fixture tests.
- Do not run the full repository test suite on this host.
- Run demolab build and visually inspect every page of the new experiment PDF and the updated ar063 PDF.

Git and publication:

- Record architecture, executor implementation, fixture/debugging, evidence, and writing work in focused commits with clear messages.
- Commit meaningful failed or killed attempts when they affect interpretation.
- Push the branch and open a draft PR against main.
- Add timestamped PR comments at meaningful implementation and validation milestones.
- Do not merge or modify main.

Stop and ask before:

- weakening or changing an ar063 acceptance or compatibility criterion;

- accepting Milestone 2 performance outside its declared threshold;
- changing legacy defaults or historical behaviour;
- starting Milestone 4;
- using paid compute;
- or taking an action outside the authority above.

Finish at the human review gate with:

- the demonstrated status of Milestones 1, 2, and 3;
- exact compatibility, numerical-parity, delay-timing, and performance evidence;
- validation performed;
- known limitations and remaining work;
- exact compute spend;
- links to the rendered ar063 and experiment files, commits, artifacts, and PR.

## Methods

1. The compatibility adapter converts legacy flags and bundles into typed execution requests. Legacy remains the default executor.
2. The graph planner validates capabilities, dimensions, polarity, temporal causality, and integral delays before lowering named populations and dense projections into a fixed schedule.
3. The single-PING gate uses the same authored bundle, seed, input tensor, and initial parameters in legacy and graph-native execution. It compares active spikes and outputs, then reloads a graph checkpoint.
4. The coupled fixture authors two different-sized PING circuits with separate spike inputs. GABA projections connect each inhibitory population to the other circuit's excitatory population as required by each variant.
5. The runner calculates only compact cross-correlation diagnostics to show that named recordings are usable. It does not sweep coupling parameters.

## Exact single-PING compatibility

| Gate                                                 | Recorded result |
|------------------------------------------------------|-----------------|
| Seeded parameter maximum absolute error              | 0               |
| E/I spike mismatch count                             | 0               |
| Named output maximum absolute error                  | 0               |
| Checkpoint replay maximum absolute error             | 0               |
| Legacy median runtime                                | 0.313 s         |
| Graph median runtime                                 | 0.272 s         |
| Graph overhead                                       | −13.2%          |
| Allowed overhead                                     | 10%             |
| CPU Inductor first invocation (20 steps × 2 samples) | 19.226 s        |
| CPU Inductor warm median (same bounded shape)        | 0.022 s         |

|                                        |              |
|----------------------------------------|--------------|
| Compiled replay maximum absolute error | 0            |
| Legacy peak traced Python memory       | 199746 bytes |
| Graph peak traced Python memory        | 9897 bytes   |

The active parity result is exact at the recorded precision. The graph path is 13.2% faster on this matched CPU reference. Matched steady state is measured eager for both paths because the established legacy boundary disables `torch.compile` on CPU. A separate bounded CPU Inductor probe records compilation and warm execution with exact compiled replay. The larger compile attempt was killed after five minutes, so accelerator compilation and large-shape CPU compile scaling remain limitations. The compilation boundary remains an internal backend concern rather than graph data.

### Coupled acceptance fixture




Figure 102: Reciprocal delayed acceptance graph. Two separately named PING components receive independent inputs. Each cross-circuit red projection carries spikes from one inhibitory population to the other excitatory population. The topology is compiled, planned, and archived as data.

| Variant                           | Cross edges | Delay steps | Graph digest           |
|-----------------------------------|-------------|-------------|------------------------|
| Uncoupled                         | 0           | none        | sha256:e4e440c3f4a2... |
| Unidirectional                    | 1           | 1           | sha256:a4c9c87b7ab3... |
| Reciprocal, zero additional delay | 2           | 1           | sha256:36f49c2dac29... |

|                            |   |   |                      |
|----------------------------|---|---|----------------------|
| Reciprocal, explicit delay | 2 | 5 | sha256:114d50072c91. |
|----------------------------|---|---|----------------------|

A zero-additional-delay recurrent or feedback edge still receives its source spike on the next causal step. The explicitly delayed fixture receives it after 5 steps. Non-integral delays and zero-delay algebraic cycles fail during planning.

Named population recordings




Figure 103: Matched excitatory recordings from the four graph variants. Time in milliseconds is horizontal and cell index is vertical; the left and right columns show circuits A and B. Strong inhibition silences circuit B in two fixtures, which is a useful execution stress case but not evidence for a coupling mechanism. The retained input, E, I, voltage, and projection-conductance arrays permit later analysis without simulator access.

The phase and synchrony calculations are deliberately not interpreted. Circuit B has no spikes in the unidirectional and reciprocal zero-additional-delay fixtures, so a scientific phase comparison would be meaningless. Milestone 4 remains unstarted.

## Exit decision

Milestones 1, 2, and 3 pass this local validation. Legacy routing remains the default, bundle loading remains independent of the authoring package, and the arbitrary coupling variants require no simulator edit. The committed record includes authenticated bundles, canonical diagrams, independent inputs, named recordings from both E/I circuits, delay evidence, parity evidence, performance timings, provenance, and a reproducer. Paid compute cost is \$0.

## Activity log

**2026-08-05T11:26:22Z**

Committed the typed compatibility seam as 5be1cdb.

**2026-08-05T11:34:00Z**

Committed the first graph-native executor as f6d1a86.

**2026-08-05T11:35:00Z**

Killed the first fixture attempt before simulation because Graphviz dot was absent; atomic publication retained the previous state.

**2026-08-05T11:38:00Z**

Installed Graphviz after explicit user approval and restored canonical snnlang diagrams.

**2026-08-05T11:39:00Z**

Rejected the first active parity result: 1,536 spike mismatches and 0.348 maximum output error exposed implicit refractory and readout-reset semantics.

**2026-08-05T11:42:00Z**

Made refractory counts, membrane constants, within-step feedforward order, and readout reset explicit; active parity became exact.

**2026-08-05T11:43:00Z**

Published the corrected exp077 acceptance run locally with four graph-only variants, delay evidence, named recordings, and a passing performance gate.

**2026-08-05T12:13:00Z**

Killed a five-minute CPU Inductor attempt on the full performance shape; retained that shape for matched eager performance and bounded compilation measurement to 20 steps by 2 samples.

**2026-08-05T12:14:00Z**

Completed the bounded CPU Inductor gate with exact replay; reran exp074, exp075, and exp076 successfully through historical interfaces.

**2026-08-05T12:15:33Z**

Committed the corrected arbitrary graph executor, explicit numerical semantics, CLI request routing, documentation, and focused tests as cf11906.

**2026-08-05T12:15:45Z**

Focused architecture gate passed: 43 tests, zero failures; the broader artifact-schema selection passed 49 tests, zero failures.

# Empirical input-rate calibration for variable-rate PING training

10 August 2026

## Abstract

This experiment asks which input-rate interval preserves enough digit information after synaptic and membrane filtering to justify using it in a variable-rate PING training run. We trained a nonlinear decoder on freshly simulated MNIST features spanning eight rates, then evaluated the frozen decoder on held-out images at each rate. The selected interval is 0.5 to 25 Hz. Its lower edge is the first tested rate at which all three decoders meet or exceed 50% held-out accuracy. The result calibrates this feature representation and decoder; it does not measure PING-network accuracy.

## Methods

1. **Partition the MNIST dataset.** The official MNIST training partition contains 60000 images. We assigned its first 20000 images to decoder training and the next 5000 images to checkpoint selection. The remaining 35000 images were not used. Final evaluation used the first 5000 images from the separate official test partition. Training, validation, and test images therefore did not overlap.
2. **Simulate filtered image features.**

Each normalized pixel intensity  $x_i$  generated an independent binary event at every  $\Delta t = 0.1$  ms timestep,

$$S_i(t) \sim \text{Bernoulli}\left(rx_i\Delta\frac{t}{1000}\right). \quad (1)$$

Here  $r$  is the maximum-pixel encoding rate in spikes/s. Conductance followed

$$g_i(t) = \exp\left(-\Delta\frac{t}{\tau_{\text{AMPA}}}\right)g_i(t - \Delta t) + wS_i(t), \quad (2)$$

with  $\tau_{\text{AMPA}} = 2$  ms and  $w = 1.2$   $\mu\text{S}$ . The non-spiking conductance-based membrane obeyed

$$C_E \frac{dv_i}{dt} = g_{\text{L,E}}(E_L - v_i) + g_i(t)(E_e - v_i), \quad (3)$$

with  $C_E = 1$  nF,  $g_{\text{L,E}} = 0.05$   $\mu\text{S}$ ,  $E_L = -65$  mV, and  $E_e = 0$  mV. Conductance began at zero and voltage at  $E_L$ . The decoder feature was the baseline-subtracted voltage averaged over the complete 200 ms presentation,

$$z_i = \frac{1}{T} \int_0^T (v_i(t) - E_L) dt. \quad (4)$$

Every training, validation, illustration, and test feature used a newly drawn spike train and direct evaluation of Equations 1–4. The random spikes form *shot noise*: each spike produces a discrete jump in conductance, followed by the exponential AMPA decay in Equation 2. These conductance pulses alter both the voltage toward which the membrane moves and the speed at which it moves there. The effect of a spike therefore depends on



the voltage and conductance left by earlier spikes, rather than adding a fixed voltage increment.

Direct simulation is particularly important at low input rates. A finite presentation may contain no spikes, one spike, or a few spikes arriving at different times. The response statistics can consequently change during the presentation (*nonstationary*) and the distribution across presentations can be asymmetric or concentrated around a few distinct outcomes (*non-Gaussian*) [1]. Evaluating Equations 1–4 for each presentation preserves these effects instead of replacing them with a steady, bell-shaped approximation.

### 3. Train a mixed-rate decoder.

The official MNIST training partition supplied the first 20000 images for training and the next 5000 for validation. Every presentation sampled one of the eight rates 0.1, 0.25, 0.5, 1, 2, 5, 10, 25 Hz uniformly and independently. A 784–1024–10 ReLU decoder was trained with cross-entropy and Adam for 50 epochs. Seeds 42, 43, 44 defined independent initializations, rate assignments, and spike trains. Validation accuracy selected one checkpoint per seed.

### 4. Evaluate held-out accuracy and select the interval.

1. **Select the held-out images.** We took the first 5000 images from the official MNIST test partition. These images were not used for training or checkpoint selection.
2. **Simulate shared test features.** We simulated every held-out image once at each registered input rate. All three validation-selected decoders received the same simulated feature for a given image and rate, so differences among decoders were not caused by different spike realizations.
3. **Measure each decoder’s accuracy.** For each input rate and decoder, we divided the number of correctly classified test images by 5000. This produced one held-out accuracy per decoder at each rate.
4. **Select the interval.**

The practical floor was the lowest tested rate at which every decoder met or exceeded 50% accuracy,

$$r_{\text{train}} = \min \left\{ r \in \mathcal{R} : \min_{s \in \mathcal{S}} A_s(r) \geq 0.5 \right\}. \quad (5)$$

Here  $\mathcal{R}$  is the set of tested rates,  $\mathcal{S}$  is the set of decoder seeds,  $A_{s(r)}$  is held-out accuracy for decoder  $s$  at rate  $r$ , and  $r_{\text{train}}$  is the selected training floor. The upper edge was the highest tested rate. We did not interpolate between tested rates.

## Results

### Decoder training

Validation accuracy improved across training for all three decoder seeds.




Figure 104: Mixed-rate validation accuracy across training. The horizontal axis is epoch and the vertical axis is validation accuracy. Each curve is one independently trained nonlinear decoder, and every epoch uses fresh direct feature simulations. All three decoders improve before checkpoint selection.

#### What the decoder saw




Figure 105: An MNIST input image and its directly simulated filtered features. The left panel shows the normalized input. The remaining panels show independent spike realizations at maximum-pixel encoding rates of 0.5 Hz, 5 Hz, and 25 Hz. Each simulation uses a  $1.2 \mu\text{S}$  synaptic conductance and a 200 ms presentation. Greater input rate preserves more of the digit's spatial structure.

Sparse presentations retained fragments of the digit rather than a uniformly attenuated image. Increasing rate filled in the spatial pattern and reduced the importance of individual event times.

## Empirical rate selection




Figure 106: Held-out nonlinear-decoder accuracy against maximum-pixel encoding rate. Points average the official test images and three independently trained decoders. The band spans the lowest and highest decoder accuracy at each rate. Horizontal rules mark chance and the 50% practical criterion. The red vertical rule, when present, marks the first tested rate at which all three decoders meet that criterion.

All three decoders first met the practical 50% criterion at 0.5 Hz. Mean accuracy at that condition was 62.9%. We therefore select 0.5 to 25 Hz for later variable-rate PING training.

## Conclusion

The filtered MNIST representation retained usable digit information from 0.5 Hz upward. All three independently trained decoders met the 50% held-out accuracy criterion at the selected lower bound. We therefore carry 0.5 to 25 Hz forward as the empirical input-rate interval. This is a decoder-based calibration, not a measurement of PING-network performance, so the interval must still be checked in the network for which it was selected.

## Relation to prior work

Neural decoding measures information accessible to a specified readout, not an absolute information content or a mechanistic account of the encoded population [2]. We therefore interpret the ANN psychometric curve only as a decoder-relative calibration. Nonstationary filtered-shot-noise theory motivates direct simulation of the conductance and membrane dynamics [1].

## References

1. Brigham & Destexhe: *Nonstationary Filtered Shot-Noise Processes and Applications to Neuronal Membranes*. Physical Review E, 2015. doi:10.1103/PhysRevE.91.062102
2. Quian Quiroga & Panzeri: *Extracting Information from Neuronal Populations: Information Theory and Decoding Approaches*. Nature Reviews Neuroscience, 2009. doi:10.1038/nrn2578

# Linear-filter analysis of sparse conductance-driven pixel features

10 August 2026

## Abstract

We tested what stationary linear-filter theory explains about a sparse conductance-driven pixel feature, and where the approximation fails. We simulated how an AMPA synapse, a conductance-based membrane, and finite-time averaging transform a fully active pixel driven from 0 to 25 Hz. The model explains the flat response to slow input fluctuations, attenuation of fast fluctuations, and lobes caused by temporal averaging.

The model does not accurately predict feature magnitude: it overpredicts the mean, and its standard deviation peaks too early and has the wrong shape. Sparse responses depend strongly on the discrete number and timing of spikes, violating the model’s assumption of small, stationary fluctuations. The theory explains the filtering, but direct simulation remains necessary for quantitative predictions.

## Methods

### 1. Simulate the finite-window feature.

We fixed the normalized pixel intensity at  $x = 1$  and varied only its input rate  $r$  from 0 to 25 spikes/s. At each timestep, the pixel generated an event with probability

$$p_{\text{event}} = \frac{r\Delta t}{1000}. \quad (1)$$

Here  $r$  is the input rate in spikes/s and  $\Delta t = 0.1$  ms. During a presentation of duration  $T = 200$  ms, the expected number of events is  $r\frac{T}{1000}$ . Expected event count is therefore a consequence of the chosen rate, not a separate experimental variable.

Conductance and membrane voltage followed

$$g(t) = \beta g(t - \Delta t) + wS(t), \quad (2)$$

$$\beta = \exp\left(-\Delta \frac{t}{\tau_{\text{AMPA}}}\right), \quad (3)$$

$$C \frac{dv}{dt} = g_L(E_L - v) + g(t)(E_e - v). \quad (4)$$

Here  $S(t)$  is one when an event occurs and zero otherwise,  $g(t)$  is AMPA conductance,  $w$  is the conductance increment per event,  $\beta$  is the per-timestep decay factor, and  $\tau_{\text{AMPA}}$  is the AMPA decay time constant. The membrane voltage is  $v(t)$ ,  $C$  is membrane capacitance,  $g_L$  is leak conductance,  $E_L$  is the leak reversal potential, and  $E_e$  is the excitatory reversal potential.

We used  $C = 1$  nF,  $g_L = 0.05$   $\mu\text{S}$ ,  $E_L = -65$  mV,  $E_e = 0$  mV,  $\tau_{\text{AMPA}} = 2$  ms, and independent probe conductances  $w \in \{0.6, 1.2, 2.4\}$   $\mu\text{S}$ . Every presentation began from  $g(0) = 0$  and  $v(0) = E_L$ . Its scalar feature was

$$z = \frac{1}{T} \int_0^T (v(t) - E_L) dt. \quad (5)$$

Here  $z$  is the baseline-subtracted mean voltage and  $T$  is presentation duration.

For the mean and SD estimates in Figure 1, we generated 512 new presentations at each of 101 input rates and each conductance. For the full response distributions in Figure 2, we generated 4096 new presentations at each selected rate. Direct simulation retains the nonstationary finite-window behaviour of filtered conductance shot noise [2].

## 2. Calculate the stationary operating point.

For stationary Poisson rate  $r$ , filtered-shot-noise theory [1] gives the mean AMPA conductance

$$\bar{g}_r = rw \frac{\tau_{\text{AMPA}}}{1000}. \quad (6)$$

Replacing the fluctuating conductance by this mean gives the operating-point voltage

$$\bar{v}_r = \frac{g_L E_L + \bar{g}_r E_e}{g_L + \bar{g}_r}. \quad (7)$$

Because this operating point is constant across the window, its predicted mean feature is

$$\mu_{\text{linear}}(z) = \bar{v}_r - E_L. \quad (8)$$

An overbar denotes a stationary mean,  $\bar{g}_r$  is mean conductance at rate  $r$ ,  $\bar{v}_r$  is the corresponding mean voltage, and  $\mu_{\text{linear}}(z)$  is the resulting linear prediction for mean feature value. Appendix A.1 derives Equations 6–8 from the continuous conductance and membrane equations.

## 3. Derive the local frequency response.

Linearizing Equations 2–4 around the operating point gives the response from input-rate fluctuation to voltage fluctuation,

$$G_r(\omega) = \frac{w}{i\omega + \frac{1}{\tau_{\text{AMPA}}}} \cdot \frac{E_e - \bar{v}_r}{i\omega C + g_L + \bar{g}_r}. \quad (9)$$

Here  $\omega$  is angular frequency in rad/ms and  $i$  is the imaginary unit. The transfer function  $G_{r(\omega)}$  maps a small input-rate fluctuation to its voltage response around the operating point. Appendix A.2 derives Equation 9 by linearizing the synaptic and membrane equations.

Averaging voltage over the finite presentation contributes

$$A_T(\omega) = \frac{1 - \exp(-i\omega T)}{i\omega T}, \quad (10)$$

so the complete input-to-feature response is

$$H_r(\omega) = A_T(\omega)G_r(\omega). \quad (11)$$

Here  $A_{T(\omega)}$  is the transfer function of averaging over duration  $T$ , and  $H_{r(\omega)}$  is the complete input-to-feature transfer function. Appendix A.3 derives Equations 10 and 11.

To generate Figure 3, we evaluated Equations 9 and 11 from 0.1 to 200 Hz at 0.25, 3, 25 spikes/s for the nominal 1.2  $\mu\text{S}$  probe. Frequency in Hz was converted using  $\omega = 2\pi \frac{f}{1000}$ . The Bode magnitude was reported relative to the low-drive DC response,

$$M_X(f) = 20 \log_{10} \left( \frac{|X_r(2\pi \frac{f}{1000})|}{|X_{r_{\text{low}}}(0)|} \right). \quad (12)$$

Here  $M_{X(f)}$  is Bode magnitude in dB,  $X_r = G_r$  for Figure 3A,  $X_r = H_r$  for Figure 3B,  $f$  is modulation frequency in Hz, and  $r_{\text{low}}$  is the lowest operating rate used as the DC reference.

#### 4. Calculate the linearized feature variance.

The centred ideal Poisson input has a white two-sided spectrum on the millisecond time base,

$$S_{\text{in}}(\omega) = \frac{r}{1000}. \quad (13)$$

The feature spectrum and variance are therefore

$$S_z(\omega) = |H_r(\omega)|^2 S_{\text{in}}(\omega), \quad (14)$$

$$\text{Var}_{\text{linear}}(z) = \frac{1}{2\pi} \int_{-\infty}^{\infty} |H_r(\omega)|^2 S_{\text{in}}(\omega) d\omega. \quad (15)$$

Here  $S_{\text{in}(\omega)}$  is the two-sided input power spectrum,  $S_{z(\omega)}$  is the feature power spectrum, and  $\text{Var}_{\text{linear}(z)}$  is the predicted feature variance. Appendix A.4 derives Equations 13–15 from the Poisson spectrum and the linear-filter variance identity.

We integrated Equation 15 numerically on a logarithmic frequency grid. A second calculation with half as many points measured quadrature refinement.

## Results

### Empirical finite-window response

Mean response increased with input rate and event strength. Variability first increased as spike count and timing diversified, then flattened or declined as relative count fluctuations, shunting, and voltage saturation became more important.




Figure 107: Empirical finite-window response of a fully active pixel over the input-rate grid. Both horizontal axes show input rate in spikes/s. Panel A shows mean feature in mV; Panel B shows feature SD in mV. Each coloured curve contains 101 rate conditions. At every rate, the plotted mean or SD summarizes 512 independently simulated presentations; the figure does not display those individual presentations as points. Black, red, and cyan denote 0.6, 1.2, 2.4  $\mu\text{S}$  conductance increments. Mean response rises with rate, while variability reaches a broad maximum or plateau.




Figure 108: Empirical feature distributions at 0.25, 3, 25 spikes/s for the nominal 1.2  $\mu\text{S}$  probe. Each panel contains 4096 new presentations. The horizontal axes show feature value in mV. Bars report probability per common fixed-width bin on a shared logarithmic vertical axis. Sparse input produces an atom at rest and separated timing-dependent responses; increasing rate produces a smoother distribution.

Input rate fixes only the average number of events. Individual presentations can still contain no events, one event, or several events. Even when two presentations contain the same number, different event times change the finite-window average.

### Analytical Bode-magnitude response

The synapse and membrane passed slow modulation but attenuated fast modulation. Finite-window averaging superimposed regularly spaced zeros and lobes on that falling response.




Figure 109: Analytical Bode-magnitude plots at the nominal  $1.2 \mu\text{S}$  probe. Black, red, and cyan denote operating rates 0.25, 3, 25 spikes/s. The horizontal axis is modulation frequency in Hz and the vertical axis is gain relative to the low-drive direct-current response in decibels. Panel A shows Equation 9; Panel B shows the complete 200 ms window-averaged response from Equation 11.

In Panel A, each curve is flat at low frequency because the AMPA conductance and membrane voltage can follow a slowly varying input quasi-statically. Greater drive lowers that plateau by shunting the membrane and reducing the excitatory driving force. The curves bend downward once modulation becomes too fast for the synaptic and membrane timescales to follow.

Panel B is the same synapse-plus-membrane response multiplied by the rectangular-window response. With  $T_s = \frac{T}{1000}$  s,

$$\left| A_T \left( 2\pi \frac{f}{1000} \right) \right| = \left| \frac{\sin(\pi f T_s)}{\pi f T_s} \right|. \quad (16)$$

Its zeros at  $f = \frac{n}{T_s}$  cancel modulation containing an integer number of cycles within the presentation. Here  $n$  is any nonzero integer. The absolute sinc response creates the lobes, while the Panel A low-pass response supplies their falling envelope. Appendix A.3 derives Equation 16 from the finite-window averaging kernel.

### Analytical and empirical moments

The stationary model reproduced the mean curve's broad shape but not its magnitude, and it failed to reproduce the shape of the empirical standard deviation.






Figure 110: Analytical and empirical moments over input rate for a fully active pixel. The horizontal axis is input rate in spikes/s. Solid curves are stationary predictions from Equations 8 and 15; faint points are independently simulated finite-window estimates. Panel A shows mean feature in mV and Panel B feature SD in mV. The stationary theory overpredicts the mean and places the SD maximum too early.

The analytical mean preserved the broad curvature and conductance ordering but exceeded the empirical magnitude. Its median predicted-to-empirical ratio was 1.986. The stationary calculation evaluates the response at mean conductance,  $z(E[g])$ , whereas simulation estimates the response over random conductance paths,  $E[z(g)]$ . Saturation makes these unequal, approximately

$$E[z(g)] < z(E[g]).$$

The stationary input also acts throughout the window; a real late event contributes only briefly to Equation 5.

The SD mismatch is more fundamental. The empirical distribution is a spike-count and spike-time mixture,

$$p_Z(z) = \sum_{n=0}^{\infty} P(N = n) p_{Z|N}(z|n). \quad (17)$$

Here  $Z$  is the random feature value,  $N$  is the event count,  $P(N = n)$  is the probability of observing  $n$  events, and  $p_{Z|N}(z|n)$  is the feature distribution conditional on that count.

Equation 15 instead treats input as a small stationary fluctuation around one operating point. At low rates, zero-event trials remain exactly at rest, one large event produces a timing-dependent response, and multiple events interact through shunting and saturation. That non-Gaussian mixture explains why the analytical SD rises too sharply and peaks too early, especially for the largest conductance increment.

## Conclusion

Stationary linear-filter theory correctly explains the low-frequency plateau, high-frequency roll-off, averaging-window zeros, and qualitative operating-point dependence. It does not quantitatively predict finite-window moments in the sparse, large-jump regime. Direct simulation is therefore required for empirical rate selection, while the analytical model remains useful for explaining the filter’s structure.

## Limitations

The empirical moment grid used 512 presentations per condition; it was designed to resolve the qualitative theoretical comparison, not to estimate extreme distribution tails. The analytical variance assumes ideal continuous-time Poisson drive and a local stationary linearization, whereas simulation uses discrete Bernoulli events and begins from rest.

## Reproducibility

uv run python experiments/exp081.py regenerates every sample, summary, and figure. The runner contains a complete independent physical specification and consumes no artifacts or code from another experiment.

## Appendix A: derivation of the analytical filter

### A.1 Stationary conductance and voltage

Write the continuous AMPA equation driven by an event train  $s(t) = \sum_k \delta(t - t_k)$  as

$$\frac{dg}{dt} = -\frac{g}{\tau_{\text{AMPA}}} + ws(t). \quad (\text{A1})$$

Here  $s(t)$  is the impulse train,  $t_k$  is the time of event  $k$ , and  $\delta(t - t_k)$  is a Dirac impulse at that time.

For stationary input rate  $r$  spikes/s, the rate on the millisecond time base is  $\frac{r}{1000}$ . Taking expectations of Equation A1 and setting the stationary derivative to zero gives

$$0 = -\frac{\bar{g}_r}{\tau_{\text{AMPA}}} + w\frac{r}{1000},$$

hence Equation 6. The stationary membrane equation is

$$0 = g_L(E_L - \bar{v}_r) + \bar{g}_r(E_e - \bar{v}_r), \quad (\text{A2})$$

and collecting the terms multiplying  $\bar{v}_r$  gives Equation 7.

### A.2 Synapse-plus-membrane linearization

Decompose each quantity into its operating point and a small fluctuation,

$$g = \bar{g}_r + \delta g, \quad v = \bar{v}_r + \delta v, \quad s = \frac{r}{1000} + \delta s.$$

Substitution into Equation A1 and cancellation of the stationary terms gives

$$\frac{d\delta g}{dt} = -\delta \frac{g}{\tau_{\text{AMPA}}} + w\delta s. \quad (\text{A3})$$

With Fourier convention  $\frac{d}{dt} \rightarrow i\omega$ ,

$$\delta g(\omega) = \frac{w}{i\omega + \frac{1}{\tau_{\text{AMPA}}}} \delta s(\omega). \quad (\text{A4})$$

Substitute the decompositions into Equation 4. After cancelling Equation A2 and discarding the second-order product  $\delta g \delta v$ ,

$$C \frac{d\delta v}{dt} = -(g_L + \bar{g}_r) \delta v + (E_e - \bar{v}_r) \delta g. \quad (\text{A5})$$

Fourier transformation and substitution of Equation A4 yields Equation 9. Its two denominator factors are the AMPA and membrane low-pass terms; the numerator contains the conductance increment and local excitatory driving force.

### A.3 Finite-window average

Linearizing Equation 5 leaves the average of the voltage fluctuation,

$$\delta z = \frac{1}{T} \int_0^T \delta v(t) dt. \quad (\text{A6})$$

The averaging kernel is  $a_T(t) = \frac{1}{T}$  for  $0 \leq t \leq T$  and zero otherwise. Its Fourier transform is

$$A_T(\omega) = \frac{1}{T} \int_0^T \exp(-i\omega t) dt = \frac{1 - \exp(-i\omega T)}{i\omega T},$$

proving Equation 10. Because averaging follows the membrane response, the transfer functions multiply, proving Equation 11. Using  $1 - \exp(-ix) = 2i \exp(-i\frac{x}{2}) \sin(\frac{x}{2})$  gives

$$|A_T(\omega)| = \left| \frac{\sin(\omega \frac{T}{2})}{\omega \frac{T}{2}} \right|,$$

which becomes Equation 16 after substituting  $\omega = 2\pi \frac{f}{1000}$  and  $T_s = \frac{T}{1000}$ .

### A.4 Poisson spectrum and feature variance

For ideal Poisson events with rate  $\frac{r}{1000}$  per ms, disjoint intervals have independent counts and count variance equals count mean. The centred impulse train therefore has autocovariance

$$R_{\delta s}(\tau) = \left( \frac{r}{1000} \right) \delta(\tau). \quad (\text{A7})$$

Here  $R_{\delta s}(\tau)$  is the input autocovariance at lag  $\tau$ , and  $\delta(\tau)$  is the Dirac delta function.

Fourier transformation of the delta function gives the constant spectrum in Equation 13. A linear time-invariant filter multiplies the input spectrum by squared transfer magnitude, proving Equation 14. Finally, inverse Fourier transformation at zero lag gives

$$\text{Var}(z) = R_z(0) = \frac{1}{2\pi} \int_{-\infty}^{\infty} S_z(\omega) d\omega,$$

which, after substituting Equation 14, proves Equation 15. The result is exact for the stated stationary linearized model but only approximate for the nonlinear, start-from-rest, finite-event simulation.

## References

1. Wolff & Lindner: *Mean, Variance, and Autocorrelation of Subthreshold Potential Fluctuations Driven by Filtered Conductance Shot Noise*. Neural Computation, 2010. doi:10.1162/neco.2009.02-09-958
2. Brigham & Destexhe: *Nonstationary Filtered Shot-Noise Processes and Applications to Neuronal Membranes*. Physical Review E, 2015. doi:10.1103/PhysRevE.91.062102

# Spike-count streaming across input rates

10 August 2026

## 1. Abstract

We asked whether a spiking network could classify a continuous digit stream when each digit arrived at a different strength or remained visible for a different time. We froze networks trained on changing input rates and used their output spikes as class evidence. The classifier worked across a broad range of input strengths once enough spikes arrived. Weak or brief inputs were harder, and some ended before the output produced any evidence. Longer presentations helped, but the experiment cannot separate extra viewing time from extra decision time. It also does not show that the network’s rhythmic activity caused the result.

The main lesson is that the classifier handled changing inputs when each digit produced enough evidence before the decision ended.

## 2. Prospective design and scope

Three PING networks were trained independently across changing input rates, then frozen before evaluation. Within each five-digit stream, the PING network runs continuously: its hidden neuronal state does not reset when the digit changes. Only the output-LIF state and class counts reset, so each digit starts a new decision without restarting the network. The shared design below shows this streaming arrangement.




Figure 111: Planned streaming evaluation. Hidden network state continues across digits, while output evidence resets at each boundary. This blue-grey schematic defines the prospective mechanism and is not measured evidence.

We test whether this readout remains useful across a broad range of input strengths once enough spikes arrive. A narrow preferred rate is the main rival. The fixed-duration evaluation tests rate tolerance, while the duration–rate grid tests shorter matched windows. Chance-level performance would reject useful transfer. Persistent silence at moderate rates would instead identify missing output activity as the limiting failure. Accuracy is summarized across trained networks. Because presentation and decision time change together, the design cannot separate their effects.

The experiment and publication scaffold were committed before execution. The networks, readout, evaluation grid, checkpoint policy, sampling scale, and planned outputs were

fixed. Missing directional thresholds and a formal uncertainty model limit confirmatory interpretation.

### 3. Investigations

#### 3.1 How output spikes become a decision

The first investigation shows how the trained readout forms a decision. At timestep  $t$ , the excitatory spike vector  $\mathbf{s}^{E(t)}$  drives ten learned output-LIF units. For a presentation beginning at  $a$  and ending before  $b$ , class  $c$  accumulates

$$z_{c(u)} = \sum_{t=a}^u s_c^{\text{out}(t)}, \quad a \leq u < b,$$

where  $s_c^{\text{out}(t)}$  is the spike emitted by output unit  $c$ . The final prediction is  $\arg \max_c z_{c(b-1)}$ . If rhythmic bursts deliver useful evidence packets, classes can exchange the lead before one builds a stable margin. Sparse failure should instead produce few or no output spikes.




Figure 112: A correctly classified 200 ms presentation at 5 Hz, selected as the first success in a pre-existing matched stream. The figure explains the readout; it does not estimate accuracy. Red marks the true and winning class.

In this digit-4 presentation, output spikes increment class counts around successive population bursts. Softmax converts those counts into the displayed shares, but it is not a calibrated posterior and does not determine the winner. The trajectory explains the readout and is consistent with bursts delivering packets of class evidence. One selected example cannot show that each cycle improves the decision or that rhythmic packaging causes the aggregate pattern. The next investigation therefore tests the same readout in a changing stream.

### 3.2 Classification in a changing stream

The second investigation changes input rate and presentation duration at digit boundaries while enforcing  $T_{\text{readout}} = T_{\text{presentation}}$ . Boundary resets should prevent class evidence from leaking across labels, although continuing hidden state can shape early activity. Five registered conditions span sparse, dense, short, and matched presentations. This stream is a qualitative stress test, not an accuracy estimate.




Figure 113: A five-digit stream classified by the native output-LIF spike-count readout. Counts reset at each boundary; hidden PING state continues. Thumbnail opacity increases with input rate, and badges show the true and predicted labels.

Three of five presentations were correct. The 0.5 Hz presentation produced no output spikes and failed; the 2 Hz presentation also failed. Presentations at 5, 10, and 25 Hz were correct despite lasting from 25 to 200 ms. The stream verifies matched-window operation and exposes a silent sparse-input failure. Five outcomes cannot estimate reliability.

### 3.3 Rate and duration robustness

The factorial evaluation crosses four matched presentation/readout durations with all eleven training rates. Each condition contains 200 digits for each network. The leading account predicts that accuracy will rise as rate and duration supply more output events, then remain useful across a broad upper-rate region.




Figure 114: Held-out accuracy across matched presentation/readout durations and trained input rates. The right panel fixes duration at 200 ms to separate rate tolerance from integration time.

Mean accuracy increased monotonically with duration: 36.5% at 25 ms, 49% at 50 ms, 60.4% at 100 ms, and 69.1% at 200 ms. Mean output silence fell from 31.1% to 4.8%. Shorter presentations leave less time for both hidden dynamics and evidence accumulation. This design cannot separate those effects.




Figure 115: Input-rate psychometric with presentation and spike-count window fixed at 200 ms. Each rate contains 200 held-out digit presentations for each of three trained seeds.

At 200 ms, mean accuracy rose from 26% at 0.5 Hz to 76.8% at 3 Hz and 87.3% at 7.5 Hz. Across 10–25 Hz, it remained between 83.2% and 88.7%. The dense end did not collapse. At 15 Hz, seed-level accuracy ranged from 87% to 92%. The sparse edge was weaker: at 0.5 Hz, accuracy ranged from 23.5% to 29.5%, with 37.2% silent windows on average.



## 4. Executed methods

### 4.1 Networks and frozen selection

Three PING networks were trained independently on MNIST. Each image presentation sampled one of the eleven registered input rates. A learned projection connected 1024 excitatory cells to ten output-LIF class units, whose spike counts served as logits. Validation accuracy selected one checkpoint per seed. All weights and checkpoints remained fixed during the study.

### 4.2 Streaming evaluation and diagnostics

Input pixels generated independent Bernoulli spikes at 0.1 ms resolution. Each evaluation cell comprised 40 independent five-digit streams per seed, giving 200 decisions. We simulated five streams per batch, with separate neuronal state for each stream. Hidden state continued only within a stream. At every digit boundary, the output-LIF state and counter reset. Each decision therefore used its matched presentation window alone. The factorial evaluation crossed presentations of 25, 50, 100, and 200 ms with input rates from 0.5 to 25 Hz. The fixed-duration psychometric is the 200 ms slice. For each seed and condition, we retained accuracy, output spikes per presentation, silent-window fraction, and excitatory and inhibitory population rates. The plots summarize seed-level accuracy; they do not pool seeds into one nominal replicate.

The primary estimand was condition-level accuracy,

$$A_{d,r,s} = \frac{1}{N} \sum_{i=1}^N 1_{\hat{y}_{i,d,r,s}=y_i},$$

where  $A_{d,r,s}$  is accuracy for duration  $d$ , rate  $r$ , and trained seed  $s$ . Each cell contains  $N = 200$  digits;  $\hat{y}$  is the predicted label and  $y$  is the true label. Output silence is a companion diagnostic. We summarize the three seed-level accuracies rather than treating 600 presentations as independent network replicates.

### 4.3 Illustrations, deviations, and limits

The variable stream used five fixed duration–rate pairs and supports only qualitative interpretation. The single-trial figure shows the first correct presentation in a pre-existing 200 ms, 5 Hz stream, selected to explain a successful readout rather than estimate reliability. All factorial cells completed without a known scientific deviation, retraining, or parameter search. Evaluation used held-out streams and validation-selected classifiers. The study lacks a fixed-rate control, population-level intervals, additional training seeds, an independent stream-bank repeat, and adjusted condition comparisons. Agreement across three networks supports robustness within the tested protocol, not across a broader network population. This is a deployment evaluation rather than an account of final-epoch dynamics.

## 5. Conclusion

Across these three networks, the native matched-window readout worked over a broad part of the trained rate range. At 200 ms, accuracy remained high from moderate through dense rates, weakening the narrow-optimum rival. Longer windows improved accuracy and reduced silence. The weak 0.5 Hz edge points to insufficient output evidence as the sparse-input failure mode.

The study does not explain why variable-rate training works, establish a causal role for PING cycles, or show superiority over the exp048 mean-voltage decoder. That comparison changed both training distribution and readout. A stronger successor should compare fixed-rate and variable-rate training under matched readouts. It should add training seeds, predefine uncertainty and decision thresholds, and manipulate presentation time separately from integration time.

# When does the default PING circuit start to sing?

17 August 2026

## Abstract

The default `snn.components.ping()` circuit is silent at weak drive, then switches abruptly into a strongly rhythmic state near 50 Hz per input channel. The dominant rhythm rises from 14.93 to 27.96 Hz across the active sweep and remains predominantly below the conventional gamma band. One compiled graph produces the entire response curve. No model parameter is tuned between conditions.

## Methods

1. **Author one graph.** A typed 128-channel spike input drives the default PING component, which contains 80 excitatory (E) and 20 inhibitory (I) cells. The timestep is 0.1 ms. Neuron, synapse, delay, initializer, and constraint specifications remain at their component defaults.
2. **Vary only input drive.** Homogeneous Poisson input spans 0 Hz, 25 Hz, 50 Hz, 75 Hz, 100 Hz, 125 Hz, 150 Hz, 200 Hz per channel. Every condition uses the same compiled graph and 5 paired deterministic trials, each lasting 1000 ms. Measurements exclude the first 200 ms.
3. **Resolve the dominant rhythm.** The `default-ping-dominant-rhythm-v1` policy computes a single-trial Welch spectrum from the E-population raster. It searches 5–80 Hz, interpolates the peak between bins, rejects maxima at the band edge, and requires peak power to exceed 3 times the band median. If a peak at half the selected frequency carries at least 30% of its power, the lower frequency is reported. This prevents a strong harmonic from masquerading as the population rhythm.
4. **Score rhythmicity.** The standard `exp054` metric bins the E-population spike count at 1 ms, computes its normalized autocorrelogram, and applies a three-point smoothing kernel. If  $L$  is the first side-lobe height and  $T$  the following trough height, the dimensionless Michelson contrast is  $R = \frac{L-T}{L+T}$ . Silence is reported as  $R = 0$ .
5. **Measure E/I timing separately.** Post-transient population spikes are binned at 1 ms. The lag of the strongest E/I cross-correlation within plus or minus 20 ms is descriptive and does not enter the gamma-resolution rule.




Figure 116: Compiled graph reused at every input condition. A time-by-batch-by-128 spike tensor drives one default PING component with 80 E cells and 20 I cells. Only the input event probability changes across the sweep; the graph and its parameters remain fixed.

## Results

The network is silent through 25 Hz per channel. At 50 Hz it activates, the median rhythmicity score reaches 1, and the dominant rhythm is 14.93 Hz. Rhythmicity therefore appears discontinuously, while the rhythm frequency increases smoothly with drive. The default circuit sings, but under this protocol it mostly sings below gamma.




Figure 117: Response of one fixed default PING graph to homogeneous Poisson drive. Top: mean E and I firing rates in hertz, with standard deviations across 5 paired trials. Middle: median lobe-trough rhythmicity contrast  $R$ , with error bars showing half the interquartile range;  $R = 0$  is flat and  $R$  approaches 1 as periodic structure strengthens. Bottom: median dominant E-population frequency in hertz after subharmonic correction; the grey region marks 5–30 Hz. Rhythmicity switches on abruptly at 50 Hz per channel, while the dominant rhythm increases smoothly from 14.93 Hz.




Figure 118: Single-trial E and I rasters at the three input rates fixed before the primary sweep. Time is in milliseconds; E cells are black, I cells are red, and the dashed vertical line marks the 200 ms transient exclusion. The right labels report input rate per channel and post-transient mean population rates in hertz. The 25 Hz condition is silent, whereas the higher-drive conditions show repeated population volleys.




Figure 119: Mean E-population power spectra at the preselected input rates. Frequency is in hertz and power is normalized to each curve’s maximum for shape comparison; frequency resolution uses the unnormalized single-trial spectra. The grey region marks the former 30–80 Hz gamma-only window. The dominant peaks sit below it, while visible harmonics fall inside it, explaining why a gamma-restricted search gave a misleading frequency curve.

# Can inhibitory recovery tune default PING into gamma?

17 August 2026

## Abstract

At a fixed 100 Hz/channel drive, shortening inhibitory synaptic decay from 16 to 2 ms accelerates the default SNNLANG PING rhythm from 13.81 to 51.48 Hz. Decays of 4 ms and below enter the 30–80 Hz gamma band without weakening the standard rhythmicity score. This experiment varies one public component parameter while preserving the authored circuit, paired inputs, and analysis policy established in exp083.

## Methods

1. **Fix the active operating point.** A typed 128-channel spike input drives 80 excitatory (E) and 20 inhibitory (I) cells at 100 Hz per channel. Each condition reuses the same 5 deterministic input tensors and network seed. Trials last 1000 ms; the first 200 ms are excluded.
2. **Vary inhibitory recovery only.** The public `tau_gaba` argument of `snn.components.ping()` spans 2 ms, 4 ms, 6 ms, 9 ms, 12 ms, 16 ms. The default is 9 ms. Every other neuron, synapse, delay, initializer, and constraint specification remains unchanged.
3. **Apply the registered rhythm analyses.** The `default-ping-dominant-rhythm-v1` estimator reports the dominant E-population rhythm over 5–80 Hz, including its prominence and subharmonic rules. Rhythmicity is the standard autocorrelation lobe-trough contrast  $R$  used in exp083. E/I lag is measured separately from the peak cross-correlation of 1 ms population counts.




Figure 120: Compiled SNNLANG graph at the 9 ms default condition. Across the sweep, only the decay time attached to the I-to-E GABA projection changes. The input tensor, populations, weights, delays, and execution seeds are paired across conditions.

## Results

Inhibitory decay produces a direct test of the textbook recovery-timescale account. The default 9 ms circuit resolves at 21.54 Hz. Faster inhibition shifts the rhythm to 51.48 Hz, while slower inhibition yields 13.81 Hz.






Figure 121: Response to inhibitory synaptic decay at fixed 100 Hz/channel input. Top: mean E and I firing rates with standard deviations across 5 paired trials. Middle: median standard rhythmicity contrast  $R$ , with half-interquartile-range error bars. Bottom: median dominant E-population frequency; the grey region marks 30–80 Hz gamma. The dashed line marks the 9 ms component default.




Figure 122: Single paired-trial E and I rasters at the preselected fast, default, and slow inhibitory decay conditions. Time is in milliseconds; E cells are black, I cells are red, and the dashed vertical line marks the transient exclusion. Right labels give inhibitory decay and the resolved dominant frequency.

## Lowet 2015

19 August 2026

### Abstract

Two gamma rhythms with different frequencies drift out of phase unless coupling corrects the mismatch. Lowet et al. showed that reciprocal excitation can synchronize PING networks through pathways targeting either excitatory or inhibitory neurons [1]. We recreate that setup and separate the two mechanisms. Both pathways alter volley timing, but only E-to-E coupling stops the drift at this operating point. Excitation advances the next E volley; inhibition follows rather than initiating the correction.

### The question

Lowet et al. connected two PING networks through reciprocal E-to-E and E-to-I projections and showed that locking depends on detuning and coupling strength [1]. The two pathways suggest different mechanisms. E-to-E input can advance the target rhythm directly. E-to-I input can recruit inhibition and delay its next volley. Which route actually stops phase drift?

### The system

Each network contains 80 excitatory and 20 inhibitory neurons in a local PING loop. Sparse reciprocal excitation targets both populations through separate pathways.




Figure 123: Two matched PING circuits. Long-range excitation targets either E or I with exact fan-in 8.

Network A receives 300 Hz input and Network B receives 260 Hz. At the demonstration point,  $K_{EE} = 0.08$ ,  $K_{EI} = 0.08$ , and delay  $d = 2$  ms.

## Evidence

### 1. The uncoupled rhythms drift




Figure 124: Both networks sustain gamma rhythms, but their relative phase keeps moving. Network A oscillates at 50.7 Hz and Network B at 46.7 Hz. Their low interval variability confirms regular rhythms. Relative phase wraps 7 times, establishing the drift that coupling must stop.

### 2. The pathways make different corrections

We deliver one coupling-matched probe volley at different phases of Network A's cycle. E-targeted probes advance the next excitatory volley late in the cycle. I-targeted probes delay it only in a narrow window.




Figure 125: Three representative responses: direct advance, no correction, and doublet-mediated delay.




Figure 126: E input advances over a broad late-cycle range. I input delays only from phase 0.1 to 0.14 the lower panels show why.

The I-targeted delay occurs when residual local excitation and the probe jointly push recovered I neurons back across threshold. Earlier probes meet refractory neurons; later probes arrive after the local excitation has faded. The inhibitory correction is therefore strong but difficult to engage.

### 3. Only E-to-E coupling stops the drift

We start four conditions from the same saved state: no coupling, E-to-E only, E-to-I only, and both pathways.




Figure 127: A slope means continued drift; a plateau means phase locking.

No coupling drifts at 4.73 cycles/s. E-to-I alone still drifts at 3.57 cycles/s. E-to-E alone reduces drift to 0.02 cycles/s and locks the rhythms. Both pathways also lock, at 0 cycles/s.

The doublet mechanism exists, but its narrow phase window is insufficient here. Direct excitation captures the drifting rhythms.

#### 4. The first correction begins in E




Figure 128: The first correction runs from arriving excitation to an advanced E volley and then advanced feedback inhibition.

Arriving E-to-E conductance advances Network B's next excitatory volley by 0.9 ms. Feedback inhibition advances with it, so inhibition follows the correction rather than initiating it.

## Methods

1. Run the networks uncoupled for 2 s. Discard 300 ms, detect excitatory volleys, and interpolate phase between them.
2. Measure phase response from one baseline cycle. Sample phases 0.02–0.30 in steps of 0.02 around the abrupt I response and use steps of 0.1 elsewhere. Keep probe strengths and the 2 ms arrival delay fixed. Change only target population and arrival phase.
3. Save the full uncoupled runtime state, then branch into the four coupling conditions. Classify the final 500 ms as locked from phase drift and concentration.
4. Compare no-coupling and E-to-E branches around the first arriving cross-network volley. Measure target E and I activity, returned inhibition, and the next E-volley time.

## Scope

This is one selected operating point, not a claim that E-to-E coupling dominates across delays, detuning, noise, or network realizations. Broader claims require systematic sweeps and repeated runs.



## References

### References

1. Lowet, E., Roberts, M., Hadjipapas, A., Peter, A., van der Eerden, J., and De Weerd, P. (2015). Input-dependent frequency modulation of cortical gamma oscillations shapes spatial synchronization and enables phase coding. doi:10.1371/journal.pcbi.1004072

## Lowet 2017

19 August 2026

### Abstract

In macaque V1, nearby gamma rhythms did not hold one fixed relative-phase position. Their relative phase continued to move, but its velocity slowed near positions where coupling made the two instantaneous frequencies more similar. This phase-dependent slowing concentrated the observed phase differences around those positions despite continuing phase slips [1]. The effect could create recurring windows for communication without permanent synchronization. We reproduced that qualitative regime in one fixed-input PING trajectory by reducing equal reciprocal coupling from 0.08 to 0.06  $\mu\text{S}$ . The networks completed 3 phase slips, but their relative phase remained concentrated around a preferred position. Removing coupling produced 16 slips and an almost uniform phase distribution. This is a controlled demonstration, not a claim about reliability across inputs or seeds.

### Prior work

Lowet et al. (2015) mapped synchronization across detuning and coupling in two 80-E, 20-I PING networks with reciprocal E-to-E and E-to-I fan-in eight [2]. Lowet et al. (2017) found the corresponding signature in macaque V1: coupling reduced instantaneous frequency differences near preferred phases, producing imperfect rather than permanent synchronization [1].

The shared parameter-space axes are uncoupled frequency detuning  $\Delta f$  and measured effective interaction strength  $\varepsilon$ . Mean frequency  $|f|$  sets the timescale; phase noise controls how sharply the rhythms lock.

| Quantity                            | Lowet regime                                                                                          | Our starting point                                             | First move                                       |
|-------------------------------------|-------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------|
| Mean frequency $ f $                | Approximately 30–40 Hz in the illustrated model and macaque conditions                                | 48.7 Hz                                                        | Hold fixed initially                             |
| Detuning $\Delta f$                 | Illustrated macaque examples span approximately 2.8–4.8 Hz                                            | 4 Hz, or 0.082 of $ f $                                        | Hold near the starting value                     |
| Effective interaction $\varepsilon$ | Phase-dependent frequency modulation is approximately 1.6–1.8 Hz in representative macaque conditions | Not measured; the interaction cancels 4 Hz at the locked phase | Describe the correction; fit $\varepsilon$ later |
| Synchronization                     | Representative phase-locking values approximately 0.3–0.5 with phase slips                            | Phase concentration 0.997 with no late slips                   | Weaken coupling first                            |

**Coupling units.** Both models divide total pathway strength across eight afferents. Lowet reports summed conductance density in  $\text{mS}/\text{cm}^2$ ; SNNLANG reports summed absolute conductance in  $\mu\text{S}$ . Normalizing each by target leak conductance places our E-to-E and E-to-I strengths at  $\kappa = 1.6$  and  $0.8$ , within Lowet’s broad sweep but more E-to-E dominated [2]. Here  $\kappa$  is cross-network conductance divided by target leak conductance.

## Methods

**All three methods were run once. The starting values and topology were sourced from exp085. Every coupling condition reused the same saved network state and pre-generated input spike trains.**

1. **Define the starting rhythms.** Each network contains an excitatory population, an inhibitory population, and a local E-to-I-to-E feedback loop. Reciprocal excitation targets both E and I populations with  $K_{EE} = 0.08 \mu\text{S}$ ,  $K_{EI} = 0.08 \mu\text{S}$ , and delay  $d = 2 \text{ ms}$ . Drive Networks A and B at 300 and 260 Hz. Run them without cross-network coupling and confirm regular rhythms near mean frequency 48.7 Hz and detuning 4 Hz. Interpolate phase between consecutive excitatory volleys and calculate their wrapped and unwrapped relative phase. Generates Result 1.




Figure 129: Implemented topology. Networks A and B each contain a local E-to-I-to-E PING loop. Reciprocal projections target E and I populations with independently controlled strengths.

2. **Reduce coupling while everything else stays the same.** Save the network immediately before coupling begins. Replay from that point several times with the same neuron states and the same pre-generated input spike trains after that point. Change only the coupling strength  $K$ : begin at  $0.08 \mu\text{S}$ , then use progressively weaker values down to zero. E-to-E and E-to-I coupling always use the same value. Run one trajectory at each value of  $K$ ; repeated seeds and trials are outside this experiment. For each coupling strength, track the phase gap between the two rhythms. Strong coupling may keep that

gap fixed. Weaker coupling may allow one rhythm to repeatedly gain a full cycle on the other, producing phase slips. We are looking for the intermediate behaviour reported by Lowet et al. (2017): phase slips continue, but the phase gap repeatedly slows near one preferred value, making that value more common [1]. Select one trajectory that shows this pattern. This demonstrates the behaviour once; it does not establish reliability across seeds. Generates Result 2.

The expected and measured coupling regimes are placed together in Result 2.

3. **Relate phase velocity to phase position.** For the selected condition, estimate each network's instantaneous frequency from consecutive excitatory volleys. Relative-phase velocity is  $v_\theta = 2\pi(f_A - f_B)$ , where  $f_A$  and  $f_B$  are the instantaneous frequencies of Networks A and B. Group  $v_\theta$  by wrapped relative-phase position  $\theta$ , and compare the resulting velocity curve with the distribution of  $\theta$ . Intermittent attraction requires continued phase slips, a non-uniform phase distribution, and lower absolute velocity near the distribution's preferred position. Generates Result 3.

The expected signature and its measured counterpart are placed together in Result 3.

## Results

1. **Uncoupled rhythms.**





Figure 130: Both uncoupled networks maintain regular PING rhythms, but Network A runs at 50.6 Hz and Network B at 46.6 Hz. Their relative phase therefore circulates, completing 16 slips with phase concentration 0.028.

## 2. Coupling boundary.

## Expected — schematic



## Observed — measured





Figure 131: Expected coupling regimes above and measured trajectories below. The schematic is qualitative; aligned columns connect each proposed regime to its observation. At  $0.08 \mu\text{S}$ , relative phase remains fixed with concentration  $0.992$ . At  $0.06 \mu\text{S}$ , it completes 3 slips but repeatedly slows near one phase region. With no coupling, it completes 16 slips and approaches uniform drift.

### 3. Intermittent phase attraction.

## Expected — schematic

### Expected intermittent-attraction signature

qualitative schematic



## Observed — measured


Intermediate condition:  $K = 0.060 \mu\text{S}$ 

Figure 132: Expected intermittent-attraction signature above and measured result below. The schematic is qualitative; matching panel positions connect each proposed relationship to its observation. At  $K = 0.06 \mu\text{S}$ , relative phase continues to slip but has concentration 0.785. Its distribution peaks at 1.18 rad and reaches 7.6 times the mean density. The

## References

### References

1. Lowet, E., Roberts, M. J., Peter, A., Gips, B., and De Weerd, P. (2017). A quantitative theory of gamma synchronization in macaque V1. doi:10.7554/eLife.26642
2. Lowet, E., Roberts, M., Hadjipapas, A., Peter, A., van der Eerden, J., and De Weerd, P. (2015). Input-dependent frequency modulation of cortical gamma oscillations shapes spatial synchronization and enables phase coding. doi:10.1371/journal.pcbi.1004072



## Gold-star manuscript figure comparison


22 August 2026

This review compares the manuscript plots retained in both immutable gold-star campaigns. The left column is the historical `legacy-exp022-cc36be1` archive; the right column is the current `ggs-production-composite-20260821-6d9c38eb` publication campaign. A *changed* label means the rendered file bytes differ; it is not by itself a scientific judgement.

|                        |                                                                                |
|------------------------|--------------------------------------------------------------------------------|
| <b>Legacy archive</b>  | <code>r2://pinglab/campaigns/legacy/exp022-cc36be1</code>                      |
| <b>Legacy payload</b>  | <code>ab2b0695dbd62d39e1e7b8f9c99864fe6b22008863615e122b4a77c62dbe4a38</code>  |
| <b>Current archive</b> | <code>r2://pinglab/campaigns/ggs-production-composite-20260821-6d9c38eb</code> |
| <b>Current commit</b>  | <code>6d9c38ebd0d2d9c5bf4a4f59bede9e03e90d86bf</code>                          |
| <b>Current payload</b> | <code>7ef819f466a134762326450e431a1e96af9667e48fc87701ce27efa6a4a244ba</code>  |

### Trained PING versus COBA


`exp025 · results_compound.png · changed`



**Trained PING matches COBA classification accuracy while operating at an order-of-magnitude lower excitatory firing rate.** Both configurations were trained on MNIST by surrogate-gradient descent (§5.4). Top: representative single-trial rasters of the trained networks: COBA fires densely and asynchronously with the inhibitory population silent, whereas PING fires in gamma bands with synchronous inhibitory bursts (red) above excitatory spikes (black). For visualisation, each raster is an extended 400 ms replay of one digit, twice the 200 ms presentation used for training and quantitative evaluation. Bottom left: test accuracy per epoch, both configurations converging to  $\approx 90\%$ . Bottom right: accuracy–rate frontier traced by sweeping the sample-wise hidden-E rate ceiling (§5.4); each marker shows mean hidden-E firing rate (abscissa) and test accuracy (ordinate) across three independent seeds, with standard-error bars. PING lies above and to the left of COBA across the sweep. At the unpenalised operating point (starred), PING reaches  $\approx 90\%$  at  $\approx 16.6$  Hz, against COBA’s  $\approx 91\%$  at  $\approx 114$  Hz. Source: exp025 rate-attractor analysis in exp024.

### Inference-time loop activation


`exp038 · loop_transfer_compound.png · changed`



**Engaging the recurrent loop at inference reproduces the PING firing-rate reduction with no weight update.** COBA networks trained with seeds 42–44 are evaluated with recurrent E→I coupling scaled from  $ei = 0$  to  $ei = 1$ , without retraining. Top: illustrative seed-42 rasters at loop-off and full strength. Bottom left: across-seed mean excitatory (black) and inhibitory (red) rates; excitation falls approximately 14-fold (from  $\approx 112$  to  $\approx 8$  Hz) as inhibition rises to  $\approx 45$  Hz. Bottom right: mean accuracy falls from  $\approx 91\%$  to  $\approx 43\%$  (a  $\approx 48$  pp cost). Shaded bands show sample SD across seeds. The rate gating appears when the loop is wired in, whereas the accuracy loss reflects the absence of a feedforward compensation learned in the presence of the loop. Source: exp038.

## Released-loop training

exp049 · training\_curves.svg · changed




**Releasing the loop weights to gradient descent prunes the rhythm within a single epoch, from every initialisation.** Per-epoch training metrics with the recurrent weights  $W^{EI}, W^{IE}$  made trainable under the Dale's-law clamp, over 50 epochs on MNIST. Lines are the mean of three seeds (42–44); shading is the across-seed range. Conditions differ only in initialisation of the loop weights: canonical PING values (black), zero (red), and  $0.1 \times$  canonical (amber), against a frozen-PING control (grey, dashed). (A) Test accuracy: all conditions overlap at  $\approx 84$ – $91\%$ . (B) Mean excitatory firing rate: the trainable conditions rise

to  $\approx 49\text{--}88\text{ Hz}$  as the loop is dismantled, while the frozen control remains gated near  $17\text{ Hz}$ . (C) Mean inhibitory firing rate: the trainable conditions collapse to  $\approx 0\text{ Hz}$  within a few epochs, while the frozen control's inhibitory rate rises to  $\approx 108\text{ Hz}$  as its readout trains. (D) Lobe–trough rhythmicity contrast: the frozen control holds at  $\approx 1$  while every trainable initialisation drains to  $\approx 0.02\text{--}0.11$ . Source: exp049.

## Rate versus gamma frequency


exp041 · rate\_vs\_fgamma.svg · changed



**Post-training excitatory rate covaries affinely with gamma frequency across a sweep of inhibitory decay kinetics.** Networks were trained from scratch at each of six values of the GABA decay constant  $\tau_{\text{GABA}} \in \{4.5, 6, 9, 12, 18, 27\}\text{ ms}$ . Changing  $\tau_{\text{GABA}}$  alters both the realised gamma frequency and the duration and integrated influence of inhibition (§5.4). Top: mean post-training excitatory firing rate against measured  $f_\gamma$ ; markers are per-condition means over three seeds, with error bars ( $\pm\text{ SD}$ ) on both axes. The linear fit  $r_E = -0.7 + 0.285f_\gamma$  passes through every error bar ( $R^2 = 0.997$ ). Bottom: mean test accuracy declines from  $91.2\%$  at  $\tau_{\text{GABA}} = 4.5\text{ ms}$  to  $81.9\%$  at  $27\text{ ms}$ , a  $9.3$  percentage-point tradeoff. The sweep establishes covariance with realised frequency, not an independent causal effect of frequency alone. Source: exp041.

## Spikes per gamma cycle


exp046 · spikes\_per\_cycle\_distribution.svg · changed



The affine rate law follows from a near-binary per-cycle firing statistic: each excitatory cell contributes at most one spike per gamma cycle. Excitatory spikes were resolved into (cell, cycle) pairs by assigning each spike to the gamma cycle inferred from peaks of the population inhibitory-burst rate (§5.5). Each panel shows the distribution of spikes per pair (0, 1, 2, or  $\geq 3$ ) at one value of  $\tau_{\text{GABA}}$ . Across the sweep,  $P(0) \approx 75\%$ ,  $P(1) \approx 24\%$ , and the multi-spike fraction ( $\geq 2$ ) stays near  $\approx 1\%$ ; pooled over all conditions, 98.85% of pairs contain at most one spike. Source: exp046.

## Spike perturbation robustness


exp037 · perturbation\_curves.svg · changed



The gating is robust to spike deletion but fragile to spike addition, the expected signature of a phase-based code. PING and COBA networks trained with seeds 42–44 are perturbed at inference without retraining. Left: deletion of a random fraction of emitted spikes. PING retains  $\approx 89\%$  mean accuracy through 80% deletion, close to its unperturbed value. Right: addition of Poisson spikes, expressed relative to each population's baseline rate. PING falls toward chance as off-phase spikes disrupt the rhythm; COBA, having no rhythm to protect, is more tolerant to addition. Lines show across-seed means and shaded bands show sample SD. Source: exp037.

## Inhibitory timing perturbations

exp042 · rhythm\_compound.png · changed




sha256:123cb0e3291b

sha256:03760f990e41

**Two inhibitory-jitter manipulations at the same magnitude that hold the mean inhibitory rate fixed drive the excitatory rate in opposite directions, isolating timing from level.** The trained PING inhibitory spike train is perturbed at inference while the mean per-cell inhibitory rate is held constant. Both arms use the same jitter magnitude,  $\sigma = 14$  ms — only the *kind* of jitter differs. Top: single-trial rasters (E black, I red). Bottom: mean excitatory rate (black) and accuracy (red) versus jitter magnitude  $\sigma$ , with the realised mean inhibitory rate overlaid (grey). Left: per-cell jitter smears each burst into a continuous shunt; the excitatory rate falls to  $\approx 0$  Hz (inhibitory rate  $\approx 105$  Hz) and accuracy falls to chance. Right: cycle-coherent jitter displaces whole bursts while preserving within-burst synchrony; the excitatory rate rises from  $\approx 17$  to  $\approx 73$  Hz (inhibitory rate  $\approx 103$  Hz, matched to the left arm) and accuracy holds high. Both arms are read where the realised inhibitory rate is matched to within a few percent; at larger  $\sigma$  the cycle-coherent excitatory rate climbs further, but the finite trial window truncates the most-displaced bursts and realised inhibition falls, so the strict comparison is anchored here. Identical mean inhibition, opposite excitatory outcome: the gate is the phase structure of inhibition, not its level. Source: exp042.

## Integration-timestep invariance

exp044 · dt\_sweep.svg · changed



**The firing-rate reduction is a physical-time property, invariant to the integration timestep over a twentyfold range.** The network was trained and evaluated at matched integration timestep  $\Delta t$  for each value across  $[0.05, 1.0]$  ms (logarithmic abscissa). Left ordinate (black diamonds): post-training mean excitatory rate, confined to a 13.6–20.2 Hz band and non-monotonic in  $\Delta t$ , so finer stepping does not buy a lower rate. Right ordinate (red squares): test accuracy, flat within 2.2 pp (88.2–90.4%). Because both training and inference use the same  $\Delta t$  at each point, the figure tests invariance of the training-plus-inference pipeline, not the generalisation of one trained network to a varied inference step. Source: exp044.

# Decoder transfer in frozen COBA and PING networks

22 August 2026

## 1. Abstract

This exploratory scout asks how much of a frozen MNIST decision survives when its temporal evidence rule changes, and what a later display mapping changes without changing the underlying evidence. The reconstructed hypothesis is that rhythmic PING activity packages class competition into output events that transfer more faithfully than COBA activity from the native mean-voltage decoder to spike-based evidence. The intervention freezes each network and its learned projection while changing only the temporal evidence rule or its later display mapping. The primary estimand is retention of native correct decisions on an outcome-blind example and a balanced 100-image screen. PING output spikes retain substantially more of the native decision than COBA output spikes under the tested decoders, while output mappings alter apparent confidence but not a shared cumulative-count winner. The result clears the escalation gate for a prospective multi-seed study; it is not durable evidence of an architectural effect.

## 2. Design and scope

We compare decoder transfer in canonical COBA and PING networks trained on MNIST. When the learned network and output projection are frozen, how much of the native decision survives changes to temporal evidence  $z$ , and what does a later output mapping  $p$  change without changing the winner? The leading mechanism is that PING rhythms package useful class competition into transferable output events. Simpler rivals include output-rate mismatch, dependence on one trained network of each kind, fixed decoder timescales, and the deterministic convenience sample.

Both networks, their hidden activity, learned output weights, and encoded inputs remain frozen. Native mean-voltage evidence uses the trained non-spiking output. Every spike-based alternative reads one counterfactual output-LIF trajectory driven by the same hidden spikes and weights. All output mappings read the same cumulative-count tensor. PING voting uses detected cycles; COBA uses duration-matched bins. The illustrative MNIST example was chosen without inspecting its outcome, and the screen uses the first ten official-test examples from each digit class.

The interventions separate two stages that should not be conflated. Temporal evidence  $z$  converts output voltages or spikes into the class quantities on which a decision is based; changing  $z$  can therefore change the winner. A later mapping  $p$  transforms one already chosen evidence vector for display. Ordinary and temperature-softened softmax preserve its argmax, while independent sigmoid tests what is lost when classes are no longer normalized against one another. The final screening investigations then ask whether the decoder contrast survives beyond the illustrative trajectory.

The scout stops if decoder transfer is uninformative, requires revision if the intervention is mismatched, and escalates if a COBA–PING contrast survives the balanced screen. Its budget is one illustrative replay plus 100 balanced screening images, with no retraining, hyperparameter search, network-seed sweep, or full-test evaluation.




Figure 133: Shared decoder decomposition. Frozen activity enters a temporal evidence rule  $z$ , then an optional display mapping  $p$ , before the final argmax decision.

No separately frozen prospective plan predates this run. The expectations and gates are reconstructed from the preserved experimental record and outcome-blind selections. They are kept distinct from observations but cannot substitute for prospective registration.

Every planned investigation completed, with no known scientific deviation from the reconstructed design. The evidence remains exploratory.

### 3. Investigations

#### 3.1 Temporal evidence $z$

The first five investigations change how activity becomes decision evidence. They begin with the native mean-voltage reference, then ask whether cumulative, leaky, windowed, or interval-vote summaries of output spikes preserve the same class information.

##### 3.1.1 Running mean voltage

Running mean voltage is the native decoder used to train both frozen networks, so it establishes the reference decision before any output-spike intervention. The true class should finish above its competitors in both networks, although their transient competition may differ before the temporal mean settles. The schematic defines the running mean; its measured mirror follows the true class and strongest competitor.




Figure 134: Native mean-voltage evidence retains subthreshold activity while removing temporal order.

Both native decoders select the true class. COBA settles rapidly, while PING retains more early competition before the true-class mean remains larger. This is the baseline against which later evidence rules are judged.

### 3.1.2 Cumulative spike count

Cumulative count asks whether frozen output spikes preserve the trained decision when every spike remains evidence until reset. Transferable output spikes should allow the true class to accumulate a durable lead; dense, poorly matched output activity should instead obscure class separation. The schematic defines count accumulation, and its measured mirror applies that rule to the shared counterfactual output trajectory.






Figure 135: Cumulative evidence preserves every output spike until reset.

PING eventually gives the true class the largest cumulative count, whereas COBA does not. The contrast indicates different compatibility with the spike-count intervention, not the accuracy either network would achieve if trained with this decoder.

### 3.1.3 Leaky spike count

Leaky evidence tests whether forgetting old spikes reveals recent class competition better than an irreversible cumulative count. Recent PING evidence may remain separable as older spikes decay, whereas leakage cannot help if the counterfactual output rate keeps all classes near a common ceiling. The measured mirror uses the same fixed leak for both networks.




Figure 136: Leaky evidence weights recent output spikes more strongly.

PING retains changing local separation under leakage. COBA remains close to a steady saturated level, so forgetting old evidence does not recover a useful decision.

### 3.1.4 Sliding-window spike count

A finite window makes the decoder's memory boundary explicit and tests whether local rather than accumulated evidence carries the decision. A compatible event representation should show class differences within the fixed window, while saturated windows should erase useful competition. The measured mirror shows the resulting local counts.




Figure 137: Windowed evidence retains spikes for 25 ms, then removes them.

PING’s local competition remains visible as the window moves. COBA windows are nearly full, showing that a memory rule cannot rescue an output event rate poorly matched to it.

### 3.1.5 Cycle or matched-bin voting

Voting tests whether treating rhythmic intervals as discrete evidence packets preserves class information beyond raw burst size. If PING cycles carry structured competition, the true class should win more detected cycles; duration-matched COBA bins provide a non-rhythmic control. The measured mirror accumulates one winner per PING cycle or matched COBA interval.




Figure 138: Cycle or matched-bin evidence gives each interval one class vote.

The PING true class wins more detected cycles and pulls away in cumulative votes. Matched COBA bins favour another class. This is consistent with meaningful rhythmic packets in the selected PING trajectory, but voting alone does not establish their causal importance.

### 3.2 Output mappings $p$

The next three investigations hold cumulative evidence  $z$  fixed and change only its displayed mapping  $p$ . They distinguish genuine changes in evidence from changes in apparent confidence or class competition.

#### 3.2.1 Ordinary softmax

Ordinary softmax separates evidence accumulation from the visual sharpening produced by a normalized output mapping. It should preserve the cumulative-count winner while converting margins into competing class shares, using the same cumulative-count vector as the other output mappings.




Figure 139: Ordinary softmax converts count margins into competing class shares.

Softmax makes PING leader changes appear abrupt and decisive but leaves the cumulative-count winner unchanged. COBA’s different winner is likewise preserved. The plot changes confidence display, not evidence quality.

### 3.2.2 Temperature-softened softmax

Temperature tests whether apparent decisiveness can be reduced without changing accumulated evidence or the winning class. Dividing the same cumulative-count vector by a positive fixed temperature before softmax should preserve every argmax while making competitors easier to see.




Figure 140: Temperature softening exposes competitors while preserving the winner.

Softening exposes more of PING’s competing classes while preserving its leader changes and final winner. The difference from ordinary softmax is entirely presentational.

### 3.2.3 Independent sigmoid

Independent sigmoid removes mutual class competition and tests whether a bounded per-class display is meaningful for non-negative accumulating counts. Because each count is transformed independently rather than normalized across classes, several classes should approach one together and make the final decision tie-dominated.




Figure 141: Independent sigmoid bounds each class separately and removes mutual competition.

All classes saturate near one, so the displayed winner is governed by numerical tie handling rather than useful separation. The failure is specific to applying independent sigmoid directly to cumulative non-negative counts.

### 3.3 Aggregate screening diagnostics

The final three investigations apply the decoder rules to the balanced screen. Accuracy tests whether the contrast persists, decision transitions reveal whether native correct choices are preserved, and class-specific changes show whether failures concentrate in only a few digits.

#### 3.3.1 Balanced-screen accuracy

Aggregate accuracy tests whether the illustrative decoder-transfer contrast immediately collapses across a balanced set of other inputs. A useful signal should survive across digits, although the screen remains descriptive because it contains one trained network of each kind and is not a population estimate. The matrix applies all eight decoder rules to the same first ten official-test examples of every digit.




Figure 142: Decoder-transfer screen. The divider separates temporal evidence rules from mappings of shared cumulative evidence.

COBA’s spike-based rules retain only 10–18% accuracy from a 100% native baseline, whereas PING retains 72–88% from a 96% native baseline. The contrast clears the scout’s cheap aggregate gate without establishing a general architectural effect.

### 3.3.2 Native-decision transitions

Aggregate accuracy alone cannot distinguish preserved native decisions from compensating repairs and new failures. A compatible alternative should preserve most native correct decisions rather than merely exchange one set of errors for another, so the transition plot cross-tabulates every alternative decision against its network’s native decision.




Figure 143: Transitions show whether each alternative preserves, breaks, repairs, or retains a native error.

COBA alternatives break most decisions that its native decoder gets right. PING alternatives preserve substantially more native correctness, with only limited repairs. The contrast is therefore a difference in decision retention, not an artefact of aggregate averaging.

### 3.3.3 Class-specific changes

Per-class changes test whether aggregate decoder loss is confined to the selected digit or one unusually difficult class. A broad incompatibility should affect several digits, whereas a selected-example artefact should remain narrowly concentrated. The heatmap subtracts native class accuracy from each alternative’s class accuracy on the balanced screen.






Figure 144: Class-specific changes show whether aggregate loss is confined to one digit.

COBA’s loss spans nearly every digit and disproportionately collapses to class zero. PING’s smaller losses are distributed rather than confined to the illustrative class. This weakens the selected-example explanation but does not replace a multi-seed full-test study.

## 4. Executed methods

These methods give the complete scientific account of the executed scout and replace the retrospectively reconstructed planned protocol in this rendering.

### 4.1 Shared frozen replay and output intervention

For hidden spike  $s_i^{H(t)}$  and learned output weight  $W_{ic}^{\text{out}}$ , the shared class drive is  $u_{c(t)} = \sum_i W_{ic}^{\text{out}} s_i^{H(t)}$ . The native non-spiking output yields pre-reset voltage  $v_c^{\text{pre}(t)}$ . The counterfactual output leaky integrate-and-fire unit receives the same  $u_{c(t)}$  and yields spike  $s_{c(t)} \in \{0, 1\}$ . The resulting shared input and output trajectories support the temporal-evidence and output-mapping investigations; no network or projection weight is retrained.

### 4.2 Running mean voltage

For class  $c$  at timestep  $t$ ,

$$z_c^{\text{mean}(t)} = \frac{1}{t+1} \sum_{\tau=0}^t v_c^{\text{pre}(\tau)}.$$

The final class is  $\arg \max_c z_c^{\text{mean}(t_{\text{final}})}$ . This is the native baseline for the temporal-evidence comparisons.

### 4.3 Cumulative spike count

Cumulative evidence retains every counterfactual output spike:

$$z_c^{\text{cum}(t)} = \sum_{\tau=0}^t s_{c(\tau)}.$$

This defines the cumulative spike-count trajectory, supplies the fixed evidence vector transformed by the output mappings, and contributes cumulative-count decisions to the aggregate screen.

#### 4.4 Leaky spike count

Leaky evidence retains a fraction  $\lambda$  of earlier evidence and adds the current spike:

$$z_c^{\text{leak}(t)} = \lambda z_c^{\text{leak}(t-1)} + s_{c(t)}, \quad 0 < \lambda < 1.$$

The fixed leak timescale is 25 ms. The same definition is used for the illustrative trajectory and aggregate screen.

#### 4.5 Sliding-window spike count

For a window of  $W$  timesteps,

$$z_c^{\text{win}(t)} = \sum_{\tau=\max(0, t-W+1)}^t s_{c(\tau)}.$$

Here  $W$  corresponds to 25 ms. The same window is used for the illustrative trajectory and aggregate screen.

#### 4.6 Cycle or matched-bin voting

Class spikes  $n_{j,k}$  are counted inside interval  $k$ ; each interval is assigned to its largest count, and votes accumulate as

$$z_c^{\text{vote}(K)} = \sum_{k=1}^K 1_{c=\arg \max_j n_{j,k}}.$$

PING intervals use detected cycles, while COBA intervals use the same durations. The same vote definition is used for the illustrative trajectory and aggregate screen.

#### 4.7 Ordinary softmax

Ordinary softmax applies one normalized exponential to shared cumulative evidence:

$$p_{c(t)} = \frac{\exp(z_c^{\text{cum}(t)})}{\sum_j \exp(z_j^{\text{cum}(t)})}.$$

Its argmax equals the cumulative-count argmax.

#### 4.8 Temperature-softened softmax

Temperature-softened softmax divides the same evidence by fixed temperature  $T = 4$  before normalization:

$$p_{c(t;T)} = \frac{\exp\left(\frac{z_c^{\text{cum}(t)}}{T}\right)}{\sum_j \exp\left(\frac{z_j^{\text{cum}(t)}}{T}\right)}.$$

Positive temperature preserves the argmax.

#### 4.9 Independent sigmoid

Independent sigmoid transforms each cumulative count separately:

$$p_c^{\text{sig}(t)} = \frac{1}{1 + \exp(-z_c^{\text{cum}(t)})}.$$

The scores need not sum to one; numerical ties use the implementation’s default argmax.

#### 4.10 Balanced screen and transition accounting

For  $N = 100$  labelled images with predictions  $\hat{y}_i$ , accuracy is

$$A = \frac{1}{N} \sum_{i=1}^N 1_{\hat{y}_i=y_i}.$$

Each alternative is cross-tabulated against the native decoder as correct-to-correct, correct-to-wrong, wrong-to-correct, or wrong-to-wrong. Per-class change subtracts native class accuracy from alternative class accuracy. The first ten official-test images per class are fixed without outcome inspection.

## 5. Conclusion

The scout supports escalation with revision. Under this frozen-weight intervention, PING output spikes preserve substantially more of the native decision than COBA output spikes, and the contrast survives the cheap balanced screen. Output mappings alone change apparent confidence but cannot repair incompatible evidence.

The strongest unresolved rivals are output-rate mismatch, one-network dependence, fixed decoder timescales, and the deterministic convenience sample. There are no sampling intervals, independent training seeds, or held-out choices of leak, window, and temperature. A prospective multi-seed full-test study should control decoder timescales, measure rate compatibility, and test whether cycle-aware evidence explains transfer beyond cumulative counts. This scout itself remains exploratory.

# What does gamma timing buy?

23 August 2026

## Abstract

Gamma rhythms create periodic windows for neuronal firing and can shape sensory responses and signal transmission [1, 2]. Whether those windows carry an operative code or merely regulate activity remains unresolved. We compare frozen COBA and PING networks trained on rate-Poisson MNIST and change only how much hidden-spike timing is retained. Three measurements follow in order: what timing makes externally decodable, what timing the trained output circuit actually uses, and whether that timing permits decisions with less time or fewer spikes. The analysis varies temporal resolution continuously rather than choosing between a rate code and a temporal code.

## Introduction

A hidden response is a binary array  $H$ , with one row per excitatory neuron and one column per simulation timestep. Entry  $H_{it}$  is one when neuron  $i$  spikes at time  $t$  and zero otherwise. The complete array contains every hidden spike, but a decoder need not read it at full resolution.

Here one number, the bin width  $\Delta$ , decides how much timing survives. Divide the 200 ms presentation into adjacent windows of duration  $\Delta$  and count each neuron’s spikes inside each window:

$$z_{ib}^{\Delta} = \sum_{t \in [b\Delta, (b+1)\Delta)} H_{it}.$$

Here  $i$  identifies a hidden E neuron,  $b$  identifies a time bin, and  $t$  indexes simulation timesteps. At  $\Delta = 200$  ms, each neuron contributes one presentation-wide count and all temporal order disappears. At 50 ms there are four counts per neuron; at 25 ms there are eight; at 5 ms there are forty. Narrower bins preserve finer timing.

This gives the experiment one common control knob:

$$\text{presentation count} \longrightarrow z^{\Delta} \longrightarrow \text{fine timing}.$$

The three questions are deliberately different. An external probe may decode timing that the trained network ignores. The trained readout may use timing without gaining robustness from it. Only the final comparison asks what computational advantage timing provides.

## Shared activity

**Nothing in this experiment has been run.** Every curve below is a qualitative design schematic, not data. Measured figures will replace the schematic curves while preserving their axes and visual language.

Use the canonical COBA and PING final-epoch checkpoints produced by exp022 and characterised by exp025. Freeze every parameter. Present identical MNIST images and identical Poisson input tensors to each paired checkpoint, including every available independently trained network seed. Record the 1,024 hidden E spike trains and the native output state.

External probes use the original training partition for fitting, a fixed validation partition for selection, and the untouched official test partition once for final evaluation. Before accepting any result, a compact validation table must confirm checkpoint provenance, paired trial identity, duration, neuron count, firing rate, native accuracy, and exact reproduction of the unaltered output replay.

## Methods

### 1. Information available at resolution $\Delta$ .

Give an external digit decoder the same hidden activity at successively narrower bin widths:

$$\Delta \in \{200, 100, 50, 25, 20, 10, 5, 2, 1\} \text{ ms.}$$

Fixed bins begin at presentation onset. COBA and PING receive separately fitted probes with identical data splits, optimization, regularisation, initialization count, and matched trainable capacity. A shuffled-label probe must remain at chance.

Gamma alignment is a separate comparison, not another point on the fixed-bin axis. For PING, detect the actual cycle boundaries and count spikes cycle by cycle. Compare that representation with ordinary fixed bins having the same median duration. Equal-duration fixed bins provide the COBA control. If cycle alignment helps, it must beat resolution alone rather than benefiting merely because a gamma cycle is short.




Figure 145: Design schematic for information available. Moving right narrows  $\Delta$  and exposes finer timing. The purple cycle mark tests alignment against a fixed bin of the same duration. These curves are illustrative, not predictions or measurements.

Generates Result 1.

### 2. Information used by the native readout.

An external decoder answers what *could* be read. The native readout answers what the trained network *does* read. Let  $\mathcal{S}_{\Delta(H)}$  denote the response obtained by redistributing each neuron's spikes inside each  $\Delta$ -wide bin.

**Controlled comparison.** Original  $H$  and shuffled  $\mathcal{S}_{\Delta(H)}$  contain exactly the same spike count for every neuron inside every  $\Delta$ -wide window. They differ only in timing finer than  $\Delta$ . At 200 ms, only each neuron's presentation-wide count survives. At smaller  $\Delta$ , progressively finer structure is protected from the shuffle.

Replay  $H$  and  $\mathcal{S}_{\Delta(H)}$  through the same frozen  $W_{\text{out}}$  and exact mem-mean output dynamics from identical initial states. First require intact replay to reproduce the stored native output. Then measure class decisions and true-class logit margins across  $\Delta$ .

Two interventions ask what kind of gamma-relative timing matters. Cycle permutation preserves each complete volley but changes its order. Within-cycle phase shuffling preserves cycle participation but changes fine phase. Duration-matched interventions provide the COBA controls.




Figure 146: Design schematic for native use. A flat trace means presentation counts suffice. A low coarse-resolution score that recovers toward intact replay as  $\Delta$  narrows means the trained output depends on timing at the recovery scale.

Generates Result 2.

### 3. Computational benefit under constraint.

Timing may be unnecessary after a full 200 ms presentation yet useful when the decision must be made earlier or with fewer spikes. Compare intact PING with its presentation-count control  $\mathcal{S}_{200 \text{ ms}}(H)$  at prefixes of 25, 50, 80, 100, 150, and 200 ms.

For the spike-budget comparison, create nested retained-spike fractions by reproducible per-neuron thinning. Apply the same retention mask before temporal redistribution so intact and shuffled conditions retain the same neuron-specific spike counts. COBA receives the same prefix and thinning controls.

Let the timing benefit be

$$\Delta A(c) = A_{\text{intact PING}(c)} - A_{\text{timing-disrupted PING}(c)},$$

where  $A$  is held-out accuracy and  $c$  is the available resource: presentation time or retained-spike fraction. A positive  $\Delta A$  under scarcity means timing makes the existing population code usable with fewer resources; convergence at 200 ms or 100% retained spikes means the advantage is conditional rather than a baseline accuracy difference.




Figure 147: Design schematic for computational benefit. The illustrated positive interaction is a gap between intact and timing-disrupted PING when time or spikes are scarce, followed by convergence when resources are ample. Overlapping PING traces are the registered null.

Generates Result 3.

## Planned Results

### 1. What timing makes decodable.

**Axes.** Bin width  $\Delta$  in milliseconds on the horizontal logarithmic axis, ordered from the 200 ms presentation count toward fine timing; official-test digit accuracy on the vertical axis.

**Traces or marks.** Fixed-window COBA and PING curves, paired network-seed marks, uncertainty across probe initializations, chance control, and a PING gamma-aligned mark beside its duration-matched fixed-window mark.

**Purpose.** Locate the temporal resolution at which additional digit information first becomes externally accessible, and test whether gamma-relative coordinates outperform an ordinary clock.

**Expected observation.** Presentation counts probably retain most information, giving shallow fixed-bin curves. A PING-specific rise would show information beyond counts. A cycle-aligned mark above its matched fixed-bin mark would show a gamma-coordinate advantage.

### 2. What timing the trained output uses.

**Axes.** Preserved bin width  $\Delta$  on the horizontal axis; native-readout accuracy and change in true-class logit margin on paired vertical panels.

**Traces or marks.** COBA and PING replay curves, intact references, cycle-permutation marks, within-cycle-phase marks, and duration-matched COBA controls.

**Purpose.** Distinguish information available to an external observer from temporal structure required by the actual trained output circuit.

**Expected observation.** If counts suffice, even the 200 ms shuffle remains near intact replay. If timing matters, performance begins below intact at coarse  $\Delta$  and recovers when the required temporal scale is preserved. Cycle or phase interventions then identify the gamma-relative component.

### 3. What timing buys.

**Axes.** Available presentation time against accuracy in the left panel; retained-spike fraction against accuracy in the right panel.

**Traces or marks.** Matched COBA, intact PING, and presentation-count-shuffled PING curves with one mark per network seed and resource level. Annotations report decision latency, spikes to stable correct decision, and agreement across independent Poisson realizations.

**Purpose.** Test whether temporal organisation makes the representation readable sooner or with fewer spikes.

**Expected observation.** The positive result is an interaction: intact PING exceeds count-matched disrupted PING under scarcity, then converges as resources become ample.

Overlap throughout is the null result and assigns gamma's demonstrated contribution to regulation and spike economy rather than an additional temporal code.

### Reading the three results together

| Resolution gain | Native replay loss | Constraint interaction | Interpretation                                                                                        |
|-----------------|--------------------|------------------------|-------------------------------------------------------------------------------------------------------|
| No              | No                 | No                     | Timing adds no detected representational or computational benefit; PING regulates activity.           |
| Yes             | No                 | Either                 | Timing is externally decodable but is not an operative code for the trained readout.                  |
| Either          | Yes                | No                     | The readout uses timing under ordinary inference without a demonstrated resource-dependent advantage. |
| Either          | Yes                | Yes                    | PING timing is operative and improves rapid or spike-limited computation.                             |



## References

1. Cardin, J. A., Carlén, M., Meletis, K., Knoblich, U., Zhang, F., Deisseroth, K., Tsai, L.-H., and Moore, C. I. (2009). Driving fast-spiking cells induces gamma rhythm and controls sensory responses. doi:10.1038/nature08002
2. Lewis, C. M., Bosman, C. A., Womelsdorf, T., and Fries, P. (2021). Cortical gamma-band resonance preferentially transmits coherent input. doi:10.1016/j.celrep.2021.109083

# Can a PING cycle be seen as a running engine?

23 August 2026

## Abstract

Pyramidal–interneuron gamma (PING) is often described as alternating excitatory and inhibitory volleys. This scout asks whether the two recurrent conductances form a coherent state portrait of that cycle. Across five simulated trials, the conductance pair repeatedly traced an oriented loop at gamma frequency. The result supports an engine-like visualization of this simulated operating point without claiming that two conductances fully describe the network.

The engine picture shows the rhythm clearly, but it does not contain the whole machine.

## The proposed engine

The frozen scout used one 80-excitatory, 20-inhibitory conductance-based PING network at its active gamma operating point. Five predeclared Poisson input realizations drove the same network. Each simulated trial lasted 500 ms, and the first 100 ms was excluded as settling time.

The engine has two main displayed state variables:

$g_{E(t)}$  = mean conductance of the recurrent E→I projection,

$g_{I(t)}$  = mean conductance of the recurrent I→E projection.

These are separate target-local conductances, not a signed quantity moving between two reservoirs. E spikes increase excitatory conductance onto I cells. I spikes increase inhibitory conductance onto E cells. Each conductance then decays locally. Their ordered rise and fall produces the engine-like cycle.

## 1. Does the conductance pair form a cycle?

A useful engine portrait should return through the same joint states in the same order. The frozen analysis aligned every complete post-transient cycle to its E-population volley, then traced  $(g_E, g_I)$  through time. It measured trajectory orientation, enclosed area, cycle duration, and E-to-I volley lag.

**Expected patterns.** A coherent PING cycle should raise  $g_E$  after an E volley, recruit an I volley, and then raise  $g_I$  while E activity is suppressed. Repeated cycles should traverse a bounded loop in one direction. A collapsed line, inconsistent orientation, or broad cloud would weaken the two-conductance account.

**Planned visual evidence.** The trial nearest the median rhythm frequency supplies five complete cycles. Equal-sized conductance and voltage instruments, simulated traces, volley marks, and a moving phase-plane point share one clock. Screen positions are normalized, but the video reports biological time.

**Simulation result.** The five trials supplied 98 complete cycles: 20, 19, 20, 20, 19 per trial. Every cycle moved counter-clockwise through the conductance plane. The median period was 19.5 ms, or 51.3 Hz. The median signed loop area was  $0.354 \mu S^2$ . The conductance pair therefore forms a coherent cycle at this operating point.

*[Video — view the web edition to play.]*

Figure 148: Simulation result. Five continuous cycles from the representative simulated trial, looped in the web view. The top row groups the conductance family: pistons, time traces, and joint trajectory. The bottom row groups membrane voltage and activity: voltage pistons, voltage traces, and a scrolling raster of 24 sampled inputs, 40 sampled E neurons, and all 20 I neurons. Thin envelopes retain the corresponding population counts. The footer separates biological time from playback rate.

### Comparison videos

Figure 1 is the stable-PING reference. Four matched simulations show what changes when recurrence is removed or input drive moves below and above that operating point. These are simulation results from the same conductance-based cell family, not recordings from biological neurons. Increased input tests a dynamical transition; it does not change a COBA architecture into a PING architecture. In every video, panel 6 shows actual binned spikes from the same fixed neuron sample; its vertical ordering indicates temporal correspondence, not literal particles moving between cells.

*[Video — view the web edition to play.]*

Figure 149: Simulation result. Recurrence-off COBA control at 100 Hz per input channel. Recurrent  $E \rightarrow I$  and  $I \rightarrow E$  weights are zero; feedforward drive and cell parameters remain matched to the PING comparisons.

The control classification was 100 Hz: irregular.

*[Video — view the web edition to play.]*

Figure 150: Simulation result. The recurrent PING graph receives 0, 25, 50, 75, and 100 Hz per input channel. Direct labels report the measured regime at each step; no onset is assumed.

The onset sweep classified its conditions as 0 Hz: silent; 25 Hz: silent; 50 Hz: irregular; 75 Hz: PING; 100 Hz: PING.

*[Video — view the web edition to play.]*

Figure 151: Simulation result. Input to the recurrent PING graph increases through 75, 100, 125, 150, and 200 Hz per channel. The matched panels show whether ordered conductance, voltage, and volley structure persists.

The stronger-drive sweep classified its conditions as 75 Hz: PING; 100 Hz: PING; 125 Hz: PING; 150 Hz: PING; 200 Hz: irregular.

*[Video — view the web edition to play.]*

Figure 152: Simulation result. High input increases through 200, 250, 300, 400, and 500 Hz per channel. Loss of PING, tonic firing, saturation, or continued ordered activity remain distinguishable outcomes.

The high-drive sweep classified its conditions as 200 Hz: irregular; 250 Hz: irregular; 300 Hz: PING; 400 Hz: irregular; 500 Hz: PING.

The exploratory criteria detect onset at 75 Hz/channel and retain PING through 150 Hz/channel. The 200 Hz condition loses period regularity. Higher conditions sit close to the frozen variability threshold and alternate between PING and irregular labels. This scout therefore finds a clear onset but no clean monotonic overdrive boundary.

## Executed methods

### 2.1 Simulation and sampling

1. Simulate 80 excitatory and 20 inhibitory cells with 128 homogeneous Poisson input channels at 100 Hz per channel, a 0.1 ms timestep, and a 2 ms inhibitory decay.
2. Hold the network realization fixed and use input seeds 8300, 8301, 8302, 8303, 8304. Simulate 500 ms per trial and exclude the first 100 ms.
3. Record external-input spikes, E and I population spikes, membrane voltages, recurrent E-to-I AMPA conductance, and recurrent I-to-E GABA conductance at every timestep. This investigation analyzes the spikes and recurrent conductances.

### 2.2 Cycle measurements

1. Compute  $g_{E(t)}$  from the recurrent E→I AMPA projection and  $g_{I(t)}$  from the recurrent I→E GABA projection. Average over batch and target cells only after retaining the full per-cell traces.
2. Detect E volleys from the smoothed population spike count after the transient. Define a complete cycle between consecutive detected E volleys.
3. Compute signed phase-plane area, orientation, period, and E-to-I volley lag from each complete  $(g_E, g_I)$  path.

### 2.3 Visual mapping

1. Select the illustrative trial by the frozen median-frequency rule. Downsample five cycles to 300 display frames; retain native-resolution arrays for every analysis.
2. Keep E and I identity stable across pistons, traces, spikes, and the phase portrait. State biological time and playback rate together.
3. Preserve every spike falling inside a display bin for fixed indices spanning 24 of 128 input channels, 40 of 80 E neurons, and all 20 I neurons. Label the subset directly and retain aggregate count envelopes. Animate every raster against the same fixed  $-100$  to  $0$  ms axis, with the live cursor at zero and past spikes flowing leftward.
4. Render the stable reference as five complete cycles. Render each comparison as a 10-second loop with 300 frames; rate sweeps use equal 100 ms windows per condition.

### 2.4 Comparison conditions

1. Define the COBA control by setting both recurrent weight distributions to zero while preserving feedforward input and cell parameters.
2. Test possible PING onset at 0, 25, 50, 75, and 100 Hz per input channel; stronger-drive PING at 75, 100, 125, 150, and 200 Hz; and possible overdrive at 200, 250, 300, 400, and 500 Hz.
3. Label a condition PING only with at least four complete cycles, a 12.5–33.3 ms median period, period coefficient of variation no greater than 0.20, and at least 80% conductance-loop orientation agreement. Label E rates above 150 Hz per cell as overdriven.

### 2.5 Frozen interpretation gate

1. Stop the engine interpretation if complete cycles do not share a trajectory orientation.
2. Restrict every conclusion to this network realization and operating point.

## Conclusion

The scout passes its coherence gate: all 98 detected cycles formed an oriented conductance loop with a median period of 19.5 ms. The two recurrent conductances therefore support the running-engine visualization at this simulated operating point.

The comparison videos sharpen that interpretation. Recurrent coupling distinguishes the stable engine from the recurrence-off control, and increasing input organizes the recurrent graph into PING by 75 Hz/channel. Stronger input accelerates the rhythm through 150 Hz/channel, but the registered high-drive range does not produce one stable failure boundary.

This bounded result does not establish that the conductance pair is a complete network state or that the same portrait generalizes across network realizations, parameters, or biological gamma rhythms.