Sentiment-driven volatility forecasting using GARCH and Random Forests

Elly Okinyo

2025

Contents

1 Introduction **1**

1.1 Background 1

1.2 Importance of volatility forecasting 1

1.3 Research problem and research gap 2

1.4 Research objectives 3

1.5 The relevance of sentiment 3

1.6 Structure of the thesis 4

2 Literature review **5**

2.1 Introduction 5

2.2 Foundational ARCH/GARCH canon (1982–1994) 6

2.2.1 ARCH models 6

2.2.2 GARCH and IGARCH 7

2.2.3 Continuous-time links 7

2.2.4 Stylised facts 8

2.3 First generation cryptocurrency volatility studies (2016–2019) 10

2.3.1 Symmetry and volatility persistence 10

2.3.2 Comprehensive GARCH comparisons 11

2.3.3 Component GARCH 12

2.3.4 Regime switching 13

2.4 Asymmetry, smooth transitions, and realised volatility (2019–2022) 13

2.4.1 Asymmetric and smooth-transition dynamics 14

2.4.2 Realised volatility models 14

2.5 Behavioural and sentiment drivers (2018–2025) 15

2.5.1 Social media and forums 15

2.5.2 News sentiment 15

2.5.3 Search-based attention . . . 16
2.5.4 Topic modelling and narrative effects . . . 16
2.5.5 Hybrid sentiment – econometric models . . . 17
2.5.6 Random forests . . . 17
2.5.7 Deep learning . . . 18
2.5.8 Hybrid GARCH – machine learning(ML) models . . . 18
2.5.9 Random forests for volatility . . . 18
2.6 Research gap . . . 19

3 Methodology **20**
3.1 Introduction . . . 20
3.2 Notation and return construction . . . 20
3.3 Realised volatility proxy . . . 21
3.4 Econometric volatility models . . . 21
3.4.1 Shock decomposition and innovation distribution . . . 21
3.4.2 GARCH(1,1) . . . 22
3.4.3 IGARCH(1,1) . . . 22
3.4.4 Sentiment-augmented variance dynamics . . . 23
3.5 Estimation via maximum likelihood . . . 23
3.6 Forecast definition . . . 24
3.7 Random Forest forecasting set-up . . . 24
3.8 Forecast evaluation: loss functions and model comparison . . . 24
3.8.1 QLIKE loss . . . 25
3.8.2 Loss differentials and benchmark comparison . . . 25
3.8.3 Superior predictive ability (SPA) test . . . 25
3.8.4 Model confidence set (MCS) . . . 25

4 Empirical Results **27**
4.1 Descriptive statistics . . . 27
4.1.1 Core distributional statistics . . . 27
4.1.2 Quantiles and tail behaviour . . . 28

4.1.3 Dependence and persistence diagnostics . . . 28
4.1.4 Normality and distributional tests . . . 29
4.1.5 Stationarity diagnostics . . . 30
4.1.6 Correlation analysis . . . 30
4.2 Model estimation results . . . 32
4.2.1 Model specification and estimation setup . . . 32
4.2.2 Baseline econometric volatility models . . . 32
4.2.3 Sentiment-augmented econometric models . . . 33
4.2.4 Econometric models diagnostics . . . 34
4.2.5 ARCH-LM test on standardized residuals . . . 35
4.2.6 Baseline diagnostics for GARCH and IGARCH . . . 35
4.2.7 Sentiment augmented diagnostics for GARCH and IGARCH . . . 35
4.2.8 The Random Forests model . . . 36
4.3 Forecasting performance . . . 38
4.3.1 Econometric models forecasts . . . 38
4.3.2 Random forests forecasts . . . 39
4.3.3 Forecast evaluation and model comparison . . . 39
4.4 Robustness checks . . . 41
4.4.1 Alternative forecast evaluation metrics . . . 41
4.4.2 Alternative volatility proxies . . . 41
4.4.3 Alternative training and forecasting scheme - rolling window . . . 41
4.4.4 Robustness of sentiment effects . . . 42

5 Discussion **44**
5.1 Interpretation of findings . . . 44
5.2 Comparison with existing literature . . . 44
5.3 Practical implications . . . 44
5.4 Limitations . . . 44

6 Conclusion **45**
6.1 Summary of key findings . . . 45

6.2 Contributions to knowledge 45
6.3 Policy and practice implications 45
6.4 Future research directions 45

A The declaration of the use of AI tools **51**

Chapter 1: Introduction

1.1 Background

Bitcoin has grown from being a mere technological experiment when it was first introduced in 2008/09 to a becoming a leading globally traded financial asset with significant economic relevance. Since its introduction, Bitcoin has has had phases of retail speculation, high dealers' testing, and just recently, there has been mainstream adoption of its trade even at the national levels as is the case of El Salvador where it was adopted by the state as an official currency(Argente & Van Patten, 2024). From 2017 through 2025, Bitcoin has been the market leader among cryptocurrencies and is constantly highly ranked in this class of assets as well as other top globally traded digital assets, with evolving regulatory developments as well as increasing liquidity which has resulted in enhanced adoption of Bitcoin as an asset.

Bitcoin exhibits high volatility which makes it different from typical investment assets, with the variation in daily returns frequently exceeding those observed in equities, commodities, and foreign exchange markets, with huge price swings often influenced by market sentiment, investor attention, regulatory announcements, and broader macro-financial developments. Given that this has become such an important asset, it raises the need to understand how to accurately forecast its volatility since Bitcoin holds highly significant value for both investors and regulators alike.

1.2 Importance of volatility forecasting

Volatility forecasting is an integral part of financial economics. The accurate predictions of conditional variance support in portfolio optimisation, hedging strategies, and risk management frameworks such as Value-at-Risk (VaR). For regulators and investors alike, volatility assessments enhance a deeper understanding of speculative bubbles, systemic risks, and market stability.

Conventional econometric models, especially the Autoregressive Conditional Heteroskedasticity (ARCH) model introduced by Engle (1982) and its generalised extension, GARCH, by Bollerslev (1986), remain the foundation of volatility modelling in financial economics since there models capture core empirical regularities such as volatility clustering and fat-tailed returns. These models, however, run into obstacles brought about by the fact that cryptocurrencies often exhibit stronger persistence, asymmetry patterns distinct from equities, and non-linear, sentiment-driven fluctuations compared to the highly seasonal data points like the national accounting statistics.

1.3 Research problem and research gap

While ARCH and GARCH models have been widely applied to cryptocurrencies for example, by Dyhrberg (2016); Chu et al. (2017); Katsiampa (2017), several limitations remain. First of all, many studies rely on short or outdated datasets ending before key structural events, such as the approval of U.S. spot Bitcoin ETFs in 2024(Gensler (2024)) which attracted more informed market participants to the Bitcoin spot market, possibly leading to a change in the composition of its investors, leading to a record net-inflows upwards of one and a half billion US dollars(Babalos et al., 2025). Secondly, few studies directly compare GARCH-family models with machine learning methods such as Random Forests (e.g., Basher & Sadorsky (2022)), especially in the context of sentiment-driven volatility. This clearly outlines a gap since investor behaviour has been demonstrated to influence greatly how Bitcoin performs as an asset(Katsiampa, 2017). This necessitates the need for a more accurate variable representing sentiment, hence the role of sentiment, proxied by Google Trends and other search-based indicators, remains understudied over long time spans.

Although hybrid models combining GARCH and ML have shown strong performance (Zahid et al. (2022); Han et al. (2025)), they largely remain unexplored in sentiment-augmented settings, hence as much as we understand clearly that these hybrid models improve quality, more assessment need to be explored on how these models would perform with the integration of sentiment.

From the foregoing,therefore, arises a need for a systematic comparison of GARCH-family

models and Random Forests, with and without sentiment variables, over an extended period of time.

1.4 Research objectives

The study has four main objectives. First, I compare the forecasting accuracy of GARCH-family models, particularly GARCH(1,1) and IGARCH(1,1) and Random Forests using Bitcoin daily data. Second, the study evaluates the effect of incorporating sentiment, proxied by Google Trends, on volatility forecast accuracy. Next, I assess whether sentiment-augmented Random Forest models perform better than the traditional econometric approaches used to study volatility. Finally, the study aims to provide an updated evidence on Bitcoin volatility dynamics using a comprehensive dataset encompassing major regime shifts.

1.5 The relevance of sentiment

Cryptocurrency markets, and in particular, crypto price performances, are heavily influenced by behavioural factors, media narratives, online discussions, and investor attention. Prior studies such as Mai et al. (2018) and Sapkota (2022) have shown that search intensity and social media conversations and trends can lead up to price volatility. Google trends which show the popularity of search on Google by analysing the sample of real, anonymised searches, shows interest over time, by region, and in relation to other topics. Therefore, trends in search for "Bitcoin" is used to serve as a proxy for retail interest and attention shocks, which are especially relevant in cryptocurrency markets dominated by non-institutional traders. Integrating sentiment into volatility models, therefore, has the potential to capture otherwise unobservable market forces.

1.6 Structure of the thesis

The thesis proceeds as follows. chapter one introduces the background, motivation, research questions, and contribution. Chapter two then reviews theoretical foundations and empirical findings across econometric, behavioural, and machine-learning approaches. Chapter three describes the data, preprocessing steps, and modelling methodology (GARCH, Random Forests, and hybrid approaches). In chapter four, I present the empirical results including descriptive statistics, model comparison, and forecasting performance. Chapter five provides an interpretation of results and how this compares to the previous literature, implications for stakeholders, and limitations. And finally, chapter six concludes with a summary and recommendations for future work.

Chapter 2: Literature review

2.1 Introduction

Over the past four decades, volatility forecasting has been a central part of financial econometrics, owing to the need to understand, quantify, and predict time-varying uncertainty in asset returns. With the emergence of Bitcoin and other digital assets, this research area has experienced renewed attention due to the unique behavioural, structural, and technological characteristics of cryptocurrency markets. Bitcoin, in particular, depicts extreme price swings, high-frequency sharp reversals, heavy-tailed return distributions, and heightened sensitivity to regulatory, technological, and behavioural influences, features which challenge traditional econometric models and motivate comparative evaluations involving machine learning and sentiment-enhanced approaches.

In this chapter, I provide a structured, and comprehensive review of the academic literature covering the foundational ARCH and GARCH theoretical canon, early cryptocurrency applications, asymmetry and regime dynamics, realised volatility models, behavioural and sentiment-driven forecasting, and the increasing use of machine learning and other hybrid models in the forecasting of volatility

Section 2.2 revisits the foundational ARCH and GARCH literature, outlining their theoretical principles and empirical implications. Section 2.3 discusses the first-generation cryptocurrency volatility studies that applied classical GARCH models to Bitcoin and other digital assets. Section 2.4 reviews contributions on asymmetry, smooth-transition dynamics, and realised volatility. Section 2.5 reviews behavioural, sentiment, and attention-based research. Section 2.6 examines machine learning and hybrid GARCH–ML models. Section 2.7 concludes by identifying the gaps addressed by this study.

2.2 Foundational ARCH/GARCH canon (1982–1994)

Financial return series often exhibit features inconsistent with classical homoskedastic linear models, and this necessitates the developments in the study of volatility. This inconsistency is often due to volatility clustering, heavy-tailed distributions, and serial dependence in higher-order moments. The foundational literature like the introduction of ARCH established the theoretical and empirical pillars that continue to support the contemporary financial econometric studies.

2.2.1 ARCH models

The seminal contribution of Engle (1982) introduced the Autoregressive Conditional Heteroskedasticity (ARCH) model which marked a major shift from constant-variance assumptions that had been prominent in prior literature. In Engle's specification, the conditional variance is modelled as a linear function of lagged squared residuals and this structure captures volatility clustering in which periods of high volatility followed by high volatility and produces fat-tailed unconditional return distributions even under normally distributed innovations. Engle's application to U.K. inflation demonstrated that macroeconomic uncertainty portrays strong temporal dependence and can be statistically modelled rather than treated as exogenous noise.

A number of key theoretical insights from the ARCH model came to the forefront. First of all, the comparison of the conditional versus the unconditional variance which made it possible for volatility to become forecastable based on past shocks. The ARCH processes were also shown to be leptokurtic, with the fat tails even when the shocks are Gaussian. And to check for the reliability of the ARCH model and whether it has unbiased results, Engel introduced the ARCH-LM test which still remains a standard diagnostic tool in econometrics.

In spite of the new pathways the ARCH approach introduce for empirical finance, practical estimation still becomes cumbersome because capturing long memory requires many lags(ARCH(q) with large q), making estimation of these long memory models inefficient.

2.2.2 GARCH and IGARCH

To allow the conditional variance to depend on both the lagged squared residuals and lagged conditional variance terms, Bollerslev (1986) introduced the Generalized ARCH (GARCH) model, which addressed the practical limitations of high order ARCH. Thus, the GARCH(1,1) quickly became the primary model of volatility modelling due to its highly parsimonious and empirical effectiveness.

The GARCH model, therefore, brought several advances. First, the GARCH(1,1) model often captures long-range dependencies with only two parameters, α and β, addressing parsimony. To address volatility persistence, the model uses the sum of $\alpha + \beta$ to quantify the speed of mean reversion, and the model shows that unconditional distributions remain fat-tailed.

Subsequently, Engle & Bollerslev (1986) further extended the theory by introducing the Integrated GARCH (IGARCH) model, in which the persistence parameter $\alpha+\beta = 1$. In this specification, instead of volatility shocks decaying over time, they are allowed to accumulate indefinitely, implying that conditional variance behaves like a unit-root process. Ideally, IGARCH captures environments in which markets do not revert quickly to long-run volatility levels, and where new information, including small shocks, produces long-lasting effects on uncertainty.

The development of the IGARCH framework was particularly important for modelling exchange rates in the 1980s, where persistent volatility and slow mean reversion were empirically pervasive. In subsequent years, researchers found that cryptocurrencies exhibit remarkably similar characteristics: high persistence, weak mean reversion, and volatility that remains elevated long after major shocks. IGARCH, thus, serves as a bridge between classical GARCH methodologies and the empirical reality of digital asset markets, in which volatility dynamics often resemble near-unit-root behaviour.

2.2.3 Continuous-time links

To bridge the discrete-time GARCH with the continuous-time stochastic volatility models, Nelson (1990) introduced the exponential GARCH(EGARCH), showing that as the

sampling intervals shrink, many GARCH processes converge to diffusion processes. This result provided the theoretical justification for using GARCH in contexts traditionally dominated by continuous-time models, such as option pricing. Nelson proved that GARCH(1,1) converges to a process with an inverted-gamma stationary distribution, while exponential-GARCH processes yield log-normal variance diffusions, thus providing more insights into the theoretical legitimacy for applying GARCH to high-frequency data and enriched the versatility of volatility models.

2.2.4 Stylised facts

Bollerslev et al. (1994) defined a set of stylised facts about financial return series after surveying more than a decade of empirical research, showing that these returns remain stable across assets, markets and time periods. These findings still serve as a guide for the specification, estimation and evaluation of volatility models in the GARCH tradition and beyond.

Volatility clustering is an essential fact associated with financial asset returns as large price movements tend to be followed by large movements, either negative or positive, while periods of stability and peace tend to persist. This temporal dependence in the conditional variance tends to be one of the strongest characteristics of financial returns and forms the core empirical motivation for GARCH models as it suggests that volatility is persistent and forecastable, contradicting the notion of constant variance assumed in early asset pricing models prior to the introduction of the ARCH framework.

The authors identified that leverage effects are integral in financial markets since in these markets, volatility responds asymmetrically to news and bad news, in particular, with negative returns typically increases volatility more than good news. The authors attribute this phenomenon to financial leverage, highlighting that a fall in equity value increases leverage and raises risk, or to behavioural factors such as asymmetric reactions to losses. Thus, leverage effects are a defining feature in equities, they are notably weaker or even absent in Bitcoin and many cryptocurrencies, highlighting the fundamental differences in market microstructure.

Bollerslev and the co-authors found that empirical return distributions exhibit kurtosis

far exceeding that of the normal distribution meaning that the results are heavily fat-tailed and the financial returns display more frequent extreme movements than the Gaussian models predict. GARCH processes with conditional normal errors can already generate heavy-tailed unconditional distributions, a feature that is further amplified when using fat-tailed innovation distributions like the Student-t.

The financial markets are found to rely heavily on information flow, and they experience predictable spikes in volatility around scheduled events such as monetary policy announcements, labour market releases, or earnings reports. Whereas these predictable bursts do not imply that the effect of information is neither uniform nor random, they have motivated the introduction of models that explicitly incorporate exogenous information or calendar effects, and it is particularly relevant to cryptocurrencies, where regulatory announcements, exchange hacks, and protocol updates often generate disproportionate volatility.

Bollerslev et al. (1994) found the existence of volatility co-movements across assets, noting that the volatilities across different assets, sectors, or markets tend to move together, reflecting the presence of common shocks or shared macroeconomic risks necessitates the need for multivariate GARCH models such as CCC, DCC, and BEKK, and explains why systemic or contagion effects can emerge during periods of market stress. Co-movement is also observed across cryptocurrencies, which often respond simultaneously to global risk sentiment or major news events.

These stylised facts jointly form the conceptual backbone for modern volatility modelling, justifying the need for dynamic conditional variance models like GARCH, as well as more flexible nonlinear approaches such as regime-switching, smooth-transition models, realised volatility frameworks, and machine learning methods. The persistence, asymmetry, tail behaviour, and cross-asset dependence described by these facts are very present in cryptocurrency markets, making them crucial considerations in any attempt to model Bitcoin volatility.

2.3 First generation cryptocurrency volatility studies (2016–2019)

The initial research on cryptocurrencies applied the classical GARCH-family models with the aim of assessing whether Bitcoin behaved like traditional assets or not, identifying important empirical characteristics like extreme volatility, persistence patterns, and possible regime shifts which have served as defining features for the subsequent research in this area.

2.3.1 Symmetry and volatility persistence

To position the asset within the broader volatility landscape, Dyhrberg (2016) carried out one of the earliest thorough GARCH applications to Bitcoin, comparing its behaviour to gold and the U.S. dollar. Using both GARCH(1,1) and EGARCH specifications, the study demonstrated several important features that subsequently shaped much of the early cryptocurrency volatility literature.

First, the author discovered high volatility persistence similar to commodity markets, implying that shocks to Bitcoin variance disappear slowly and can influence volatility over extended periods. This is consistent with the later findings as in Chu et al. (2017) and Katsiampa (2017), which frequently identified IGARCH-type behaviour for Bitcoin and other cryptocurrencies.

Second, the existence of symmetric volatility responses, indicating that positive and negative return shocks have similar effects on the volatility of Bitcoin, which sharply contrasts with equity markets, where negative shocks typically trigger larger volatility increases. In their subsequent study, Cheikh et al. (2020) confirmed this phenomenon and even documented *inverted asymmetry* for certain cryptocurrencies, where volatility sometimes increases more after positive news, a feature contradicting the traditional leverage effect in financial markets.

Finally, since Bitcoin exhibited weak correlations with other equities, Dyhrberg (2016) suggested that it can be used potentially as a diversifying asset and hedge against equities, thus assuming roles similar to the precious metals like gold. This sets the stage for exploring

how Bitcoin as an asset behaves in relation to other assets as well as macroeconomic and behavioural variables.

Thus, from the foregoing, Dyhrberg's results' implications are three-fold. First, the absence of leverage effects hints at Bitcoin's distinctive behavioural and informational environment, characterised by retail-driven sentiment, speculative trading, and limited balance sheet mechanisms compared to equities, a fact consistent with later studies showing that sentiment and attention variables such as forum discussions as presented by Mai et al. (2018), news narratives by Sapkota (2022) and Coulter (2022), and Google search intensity play a first-order role in driving volatility.

Second, the symmetry of volatility responses suggested early on that classical GARCH extensions designed for leverage effects (e.g., EGARCH, GJR-GARCH) might be less relevant for Bitcoin. Indeed, empirical comparisons in Chu et al. (2017) and Katsiampa (2017) often found that symmetric models (GARCH, IGARCH, CGARCH) performed as well or better than asymmetric ones.

Finally, Dyhrberg's work established Bitcoin as an asset whose volatility behaviour is closer to commodities than equities, thereby reinforcing the need for models capable of capturing persistent, sentiment-sensitive, and regime-dependent dynamics which serves as the basis for later research using regime-switching GARCH models (Ardia et al., 2019), smooth-transition models (Cheikh et al., 2020), and hybrid machine learning approaches (Zahid et al., 2022; Han et al., 2025), all of which attempt to account for nonlinearities and evolving market conditions not captured by early single-regime models.

2.3.2 Comprehensive GARCH comparisons

In carrying out one of the first large-scale, systematic comparisons of the GARCH-type models applied to digital assets, Chu et al. (2017) estimated twelve volatility specifications, including GARCH, EGARCH, GJR-GARCH, FIGARCH, and IGARCH across seven major cryptocurrencies, with results revealing several distinctive features of cryptocurrency volatility dynamics. In the first place, IGARCH frequently emerged as the best model for modelling the volatilities of cryptocurrencies, suggesting that volatility shocks in Bitcoin and other cryptocurrencies exhibit near-unit-root persistence, a finding consistent with

the long-memory properties of Bitcoin which was later explored through component and regime-switching models. Secondly, normal innovations were found to often outperform heavy-tailed alternatives, a somewhat surprising result given the strong empirical evidence of fat tails in traditional equity and commodity returns. This result may reflect the dominance of structural breaks, speculative bursts, and regime shifts in crypto markets rather than heavy-tailed shock distributions per se. Finally, different cryptocurrencies were found to exhibit different volatility structures, with some assets displaying stronger asymmetry, longer memory, or higher sensitivity to shocks than others. This heterogeneity suggests that cryptocurrencies cannot be modelled as a uniform asset class given that they may reflect differences in liquidity, maturity, and investor composition, key factors which influence the performance of the returns of cryptocurrencies.

Thus, Chu and the co-authors positioned IGARCH as a natural benchmark for Bitcoin volatility modelling and highlighted the need for models capable of capturing long persistence and structural heterogeneity. In an indirect response to this study, subsequent research including component GARCH models by Katsiampa (2017), regime-switching GARCH frameworks by Ardia et al. (2019), and smooth-transition approaches as in Cheikh et al. (2020) bring more light to the empirical complexities that Chu et al. (2017) identified.

2.3.3 Component GARCH

In comparing nine GARCH-type models including the standard GARCH, EGARCH, GJR-GARCH, TGARCH, and FIGARCH, Katsiampa (2017) found that the Component GARCH (CGARCH) model offered the best overall fit among these GARCH-family models for cryptocurrencies. CGARCH decomposes volatility into a short-run transitory component and a long-run persistent component, thereby capturing both immediate reactions to market news and deeper structural trends. The finding that Bitcoin's volatility is driven by both short-lived shocks like speculative bursts, exchange incidents, regulatory announcements and slowly evolving forces for example, adoption rates, liquidity growth, macroeconomic uncertainty provides an important conceptual bridge between earlier research work.

In particular, the CGARCH superiority aligns closely with evidence from Chu et al. (2017), who found the existence extreme persistence and near-unit-root behaviour in

cryptocurrencies, often favouring IGARCH specifications. Katsiampa's results refine this view by showing that what appears to be IGARCH-type persistence in single-regime models may actually reflect a combination of long-term variance dynamics and short-term speculative noise. This is a consistent interpretation as was the case in Dyhrberg (2016), who also observed persistent volatility and symmetric responses to shocks, suggesting that Bitcoin's volatility is not purely driven by episodic events but reflects deeper market forces.

Thus, Katsiampa's contribution serves as an intermediate step between the early single-regime GARCH evidence and the nonlinear, regime-switching models that followed in later studies, for example, Ardia et al. (2019).

2.3.4 Regime switching

Ardia et al. (2019) provided evidence that Bitcoin's volatility dynamics are regime-dependent by identifying several low-volatility and high-volatility regimes, highlighting through Markov-switching GARCH models (MSGARCH) three key insights. First, regime switching explains the appearance of IGARCH-like persistence in single-regime models and secondly, high-volatility regimes coincide with market crises and speculative booms, and finally, Value-at-Risk forecasts improve under regime-switching models, findings which have motivated later research on nonlinear models and hybrid specifications.

2.4 Asymmetry, smooth transitions, and realised volatility (2019–2022)

Volatility in cryptocurrencies is often asymmetric, persistent, and subject to structural breaks, hence the literature has expanded to include models with nonlinear and smooth-transition dynamics, as well as realised volatility models that exploit high-frequency data.

2.4.1 Asymmetric and smooth-transition dynamics

Cheikh et al. (2020) introduced Smooth Transition GARCH (ST-GARCH) models to analyse gradual, rather than abrupt, shifts between low-volatility and high-volatility states in major cryptocurrencies and found that in the first place, Bitcoin, Ripple and Litecoin portray inverted asymmetry where volatility increases more after positive returns, contrasting strongly with the negative-return leverage effects observed in equities. They also found that volatility responses can vary across cryptocurrencies depending on maturity, liquidity and use base as depicted by Ethereum that exhibits negligible asymmetry. Finally, Bitcoin exhibited smoother transitions between volatility states than smaller cryptocurrencies which indicates a relatively more stable and liquid market structure.

This is a confirmation of the existence of symmetry in Dyhrberg (2016) and the dominance of symmetric GARCH models in Chu et al. (2017), while extending the literature by showing that asymmetry in crypto markets is not only weak but, in some cases, reversed. The inverted asymmetry pattern supports interpretations of speculation, heavy reliance on momentum-driven trading behaviour, and reinforces the view that volatility in cryptocurrencies is shaped more by behavioural dynamics than by conventional leverage mechanisms.

2.4.2 Realised volatility models

Realised volatility models gained prominence in cryptocurrency research due to their ability to capture intraday information. Corsi (2009) proposed the Heterogeneous Autoregressive (HAR-RV) model, which approximates long-memory volatility using daily, weekly, and monthly realised volatilities. In the subsequent studies applying HAR-RV to Bitcoin found that: HAR-RV captures long-memory effects without fractional integration and often, rivals or outperforms GARCH models in out-of-sample forecasts, concluding that high-frequency realised volatility reduces noise and improves forecast accuracy. Later, Dudek et al. (2024) would show further proof that hybrid HAR-ML variants have more improvements on the standalone HAR-RV models.

2.5 Behavioural and sentiment drivers (2018–2025)

Since the cryptocurrency market is heavily influenced by online narratives, media cycles, social media activities and investor attention, behavioural finance plays an integral role in pricing and valuation of cryptocurrencies. This section, therefore, covers research on forums, news, Google trends, topic modelling, and sentiment–econometric hybrids.

2.5.1 Social media and forums

Mai et al. (2018) analysed BitcoinTalk forum posts and found that the sentiment from less active ("silent majority") users strongly predicts next-day prices, implying that there are "key" investors who directly influence the price of Bitcoin simply by what they say or post online. On the other hand, highly active users or the "vocal minority" influence trading volume, the actual raw numbers of Bitcoin units traded per day, and not the returns. The authors also show that forum sentiment provides stronger predictive power than Twitter sentiment, a sensible finding given that the '*Bitcointalk*' that they study covers, almost exclusively, news on Bitcoin, unlike Twitter/X on which all sorts of items or news articles are shared.

Thus, Mia and the co-authors highlight the decentralised, retail-driven nature of cryptocurrency markets, where specific community opinions rather than large, influential individuals shape short-term price dynamics. This aligns with later evidence showing that crowd sentiment, search intensity, and collective attention often precede volatility spikes (Wang et al., 2023). This, therefore, provides a behavioural rationale for incorporating sentiment variables into volatility models by distinguishing between market participation intensity and predictive sentiments.

2.5.2 News sentiment

By extracting news articles from major English newspapers, Sapkota (2022) found that mixed positive-negative sentiment has stronger effects on the direction of prices than purely positive or negative sentiment. This is because the mixed positive-negative is a clearer reflection of

the real life trading situation. The author also found that sentiment, in general, significantly improves the HAR-RV forecasts, and weekly news is more useful than the daily news in the HAR-RV forecasting framework.

The emphasis on mixed-tone narratives suggests that ambiguity and conflicting news signals generate heightened uncertainty and speculative reactions among investors and the stronger predictive power at the weekly horizon indicates that sentiment diffusion in crypto markets may operate more slowly than in equity markets, possibly due to heterogeneous investor bases and global time-zone effects.

2.5.3 Search-based attention

Search-based measures capture the attention of retail investors and Hoang & Vo (2024) identified that abnormal search volume (ASVI) is integral in predicting next-week crypto-returns, and also influences the increase in volatility and trading volume. ASVI is also shown to have stronger effects on larger cryptocurrencies in comparison to the smaller units.

This reinforces the attention-based asset pricing literature and justifies the use of Google Trends as a timely behavioural proxy, especially in markets lacking traditional fundamental anchors. The finding that ASVI influences volatility is consistent with the "information-overload" hypothesis, where surges in retail attention precede market disorder and speculative trading. Later ML studies by (Wang et al., 2023) incorporate Google Trends as an input feature, showing that attention-based variables enhance nonlinear models more effectively than standard GARCH specifications.

2.5.4 Topic modelling and narrative effects

Coulter (2022) applied Latent Dirichlet Allocation (LDA) to global news coverage and identified three dominant narrative categories: crypto-crime, crypto-governance, and crypto-economy. Crypto-crime and governance narratives often preceded sharp daily declines in Bitcoin prices, especially during periods of regulatory uncertainty and exchange hacks, showing that volatility is not only driven by numerical sentiment indices but also

by the thematic content and narrative framing of news, a finding consistent with Sapkota (2022) who indicated that sentiment-driven volatility depends not only on tone but also on the type of narrative being amplified.

2.5.5 Hybrid sentiment – econometric models

Hybrid sentiment–econometric models integrate behavioural indicators with traditional time-series structures. For instance, Kabo et al. (2025) showed that sentiment and GDP improve ARIMA and LSTM forecasts, highlighting the complementary value of macroeconomic and behavioural factors and Leber & Egyed (2025) demonstrated that negative sentiment Granger-causes volatility and improves VaR forecasts when incorporated into GARCH–LSTM hybrids.

These studies emphasise that sentiment affects both central tendency and tail risk. They also show that hybrid models can extract nonlinear behavioural effects that GARCH models alone cannot capture, reinforcing the motivation for this study to compare traditional econometric and machine learning approaches in a sentiment-augmented framework.

2.5.6 Random forests

Basher & Sadorsky (2022) showed that Random Forest(RF) models outperform logistic regression in predicting Bitcoin price direction. This is, in part, because Random Forest models handle nonlinear interactions and high-dimensional data and are robust to multicollinearity and noise, hence provide interpretable feature importance measures.

RF has also been used to model realised volatility by (Luong & Dokuchaev, 2018) and forecast volatility in emerging markets by (Diane & Brijlal, 2024), applications which indicate that tree-based models can successfully capture irregular patterns, structural breaks, and nonlinearities which features prevalent in Bitcoin markets. Thus, their flexibility makes them strong candidates for sentiment-augmented volatility forecasting.

2.5.7 Deep learning

Deep learning models such as LSTM, GRU, and CNN architectures outperform traditional econometric models in many studies. Kim & Won (2018) proposed LSTM–GARCH hybrids and subsequently, Wang et al. (2023) found that LSTM models outperform GARCH for weekly and monthly volatility. Eventually, in an attempt to improve accuracy, Han et al. (2025) used GARCH forecasts as LSTM inputs, and the result was a drastic improvement in the prediction accuracy of the LSTM model.

These improvements arise because deep learning architectures capture long-memory patterns, nonlinear relationships, and structural regime changes which are dynamics often persistent in Bitcoin volatility and amplified by sentiment shocks.

2.5.8 Hybrid GARCH – machine learning(ML) models

In an attempt to improve the forecasting powers of the traditional econometric models, researchers have proposed hybrid models, combining the structural interpretability of these econometric models with the adaptability of the machine learning approaches. By assessing the GARCH residual learning, (Zahid et al., 2022) showed that ML models learn residual patterns not captured by GARCH. And to incorporate news sentiments and their effects on the model performance, (Leber & Egyed, 2025) introduced the sentiment-augmented hybrids and reported that these behavioural variables improve performance. Finally, by combining GARCH-based features with graph neural networks, (Yu et al., 2025) reported multi-scale volatility decomposition.

2.5.9 Random forests for volatility

Random Forests(RF) have been used not only for classification but also for volatility regression. Amoanu (2025) and Demirer et al. (2022) show that RF models can outperform econometric models for certain financial time series, especially when nonlinear predictors or behavioural indices are included. In realised volatility forecasting, RF improves over HAR-JL specifications by capturing nonlinear interactions (Luong & Dokuchaev, 2018),

thus reinforcing the potential value of RF in modelling Bitcoin volatility, particularly when sentiment variables are incorporated.

2.6 Research gap

The above mentioned literature reviewed reveals several insights: first, Bitcoin volatility is extraordinarily persistent, often approximating IGARCH behaviour and secondly, volatility dynamics are nonlinear, asymmetric, and regime-dependent. Third, sentiment which is captured in the reported literature through search activity, news tone, and forums, is a major driver of volatility. Fourth, machine learning and hybrid models consistently outperform standalone econometric approaches.

Yet, despite these clear indications, important gaps still remain in literature. Few studies directly compare GARCH-family models with Random Forests for volatility forecasting and sentiment is rarely integrated systematically across model classes for longer datasets spanning major post-2023 structural events are underutilised.

This dissertation addresses these gaps by conducting a sentiment-driven comparative analysis of GARCH and Random Forest models using Bitcoin data from 2017–2025.

Chapter 3: Methodology

3.1 Introduction

This chapter presents the econometric and machine learning methodology used to forecast Bitcoin volatility and to evaluate whether sentiment-enhanced nonlinear methods outperform standard GARCH benchmarks. The chapter specifies the data-generating process for returns, the conditional variance dynamics under GARCH-type models, the Random Forest forecasting set-up, the out-of-sample forecasting design, and the forecast evaluation framework and multiple-model comparison procedures.

3.2 Notation and return construction

Let P_t denote the daily closing price of Bitcoin on day t. The continuously compounded (log) return is defined as

$$r_t = 100 \left(\ln P_t - \ln P_{t-1} \right), \tag{3.1}$$

where the factor 100 expresses returns in percentage terms. Let $\mathcal{F}_{t-1}$ denote the information set available at time $t-1$. This specification follows standard practice in financial econometrics, where returns are modelled as conditionally heteroskedastic processes with time-varying variance as in Bollerslev (1986).

A general conditional mean specification is

$$r_t = \mu + \sum_{i=1}^{p} \phi_i r_{t-i} + \varepsilon_t, \tag{3.2}$$

where ε_t is the innovation satisfying

$$\mathbb{E}(\varepsilon_t \mid \mathcal{F}_{t-1}) = 0, \qquad \mathbb{V}(\varepsilon_t \mid \mathcal{F}_{t-1}) = \sigma_t^2. \tag{3.3}$$

The focus of the study is on modelling and forecasting σ_t^2.

3.3 Realised volatility proxy

Since true volatility is latent, evaluation is based on a realised volatility proxy constructed from returns. A standard daily proxy is the squared return,

$$RV_t = r_t^2, \tag{3.4}$$

which is a noisy but widely used estimator of daily integrated variance when intraday data are unavailable. In robustness analysis, alternative proxies based on rolling windows may be considered, for example

$$RV_t^{(h)} = \frac{1}{h} \sum_{j=0}^{h-1} r_{t-j}^2, \tag{3.5}$$

for horizon $h \in \{5, 10, 20\}$. Although squared returns are a noisy proxy for latent volatility, they are widely used in daily-frequency studies where intraday data are unavailable (Patton, 2011).

3.4 Econometric volatility models

3.4.1 Shock decomposition and innovation distribution

Innovations are written as

$$\varepsilon_t = \sigma_t z_t, \tag{3.6}$$

where $\{z_t\}$ is i.i.d. with $\mathbb{E}(z_t) = 0$ and $\mathbb{V}(z_t) = 1$. To accommodate fat tails commonly observed in cryptocurrency returns, estimation is conducted under alternative distributional assumptions for z_t, including the Gaussian and Student-t distributions:

$$z_t \sim \mathcal{N}(0, 1) \quad \text{or} \quad z_t \sim t_\nu \text{ scaled to unit variance.} \tag{3.7}$$

Allowing for Student-t innovations accommodates the excess kurtosis commonly observed in cryptocurrency returns and is standard in volatility modelling (B. E. Hansen, 1994).

3.4.2 GARCH(1,1)

The baseline conditional variance specification is GARCH(1,1):

$$\sigma_t^2 = \omega + \alpha\varepsilon_{t-1}^2 + \beta\sigma_{t-1}^2, \tag{3.8}$$

with parameter restrictions

$$\omega > 0, \qquad \alpha \geq 0, \qquad \beta \geq 0. \tag{3.9}$$

A sufficient condition for covariance stationarity is

$$\alpha + \beta < 1, \tag{3.10}$$

in which case the unconditional variance exists and equals

$$\mathbb{E}(\sigma_t^2) = \frac{\omega}{1 - \alpha - \beta}. \tag{3.11}$$

The persistence of volatility shocks is measured by $\alpha+\beta$, and the corresponding half-life can be reported as

$$HL = \frac{\ln(0.5)}{\ln(\alpha + \beta)}. \tag{3.12}$$

3.4.3 IGARCH(1,1)

To allow near-unit-root volatility behaviour, the IGARCH(1,1) model imposes

$$\alpha + \beta = 1, \tag{3.13}$$

so that

$$\sigma_t^2 = \omega + \alpha\varepsilon_{t-1}^2 + (1 - \alpha)\sigma_{t-1}^2. \tag{3.14}$$

Under IGARCH, shocks to volatility decay very slowly, which may reflect the high persistence documented in Bitcoin volatility. Near-unit-root volatility behaviour has been documented in cryptocurrency markets, motivating the use of IGARCH-type specifications to capture highly persistent volatility dynamics.

3.4.4 Sentiment-augmented variance dynamics

To test whether investor attention contains incremental information for volatility dynamics, sentiment is incorporated via an exogenous regressor S_{t-1}. A parsimonious sentiment-augmented specification is

$$\sigma_t^2 = \omega + \alpha\varepsilon_{t-1}^2 + \beta\sigma_{t-1}^2 + \gamma S_{t-1}, \tag{3.15}$$

where γ captures the marginal contribution of attention shocks to next-day conditional variance. Nonlinearities can be partially addressed by including transformations such as ΔS_{t-1} or $\ln(1 + S_{t-1})$.

3.5 Estimation via maximum likelihood

Let θ denote the vector of parameters (including ω, α, β and distributional parameters such as ν for Student-t). Conditional on $\mathcal{F}_{t-1}$, the log-likelihood contribution is

$$\ell_t(\theta) = \log f(z_t(\theta)) - \frac{1}{2}\log(\sigma_t^2(\theta)), \qquad z_t(\theta) = \frac{\varepsilon_t}{\sigma_t(\theta)}, \tag{3.16}$$

where $f(\cdot)$ is the density of z_t. The sample log-likelihood is

$$\mathcal{L}(\theta) = \sum_{t=1}^{T} \ell_t(\theta), \tag{3.17}$$

and $\widehat{\theta}$ is obtained by maximising $\mathcal{L}(\theta)$ subject to parameter restrictions. Maximum likelihood estimation is used since it is standard for GARCH-type models and yields consistent and asymptotically normal estimators under regularity conditions (Bollerslev, 1986).

3.6 Forecast definition

A one-step-ahead conditional variance forecast from an estimated GARCH-type model is

$$\widehat{\sigma}^2_{t+1|t} = \widehat{\omega} + \widehat{\alpha}\widehat{\varepsilon}^2_t + \widehat{\beta}\widehat{\sigma}^2_t \quad \text{(plus } \widehat{\gamma} S_t \text{ if sentiment is included).} \tag{3.18}$$

These forecasts are generated recursively in a rolling-window design to mimic real-time updating.

3.7 Random Forest forecasting set-up

Let $\mathbf{X}_t$ denote the feature vector containing lagged returns, volumes, rolling volatility measures, and sentiment lags. The Random Forest produces a forecast

$$\widehat{RV}_{t+1|t} = f(\mathbf{X}_t), \tag{3.19}$$

where $f(\cdot)$ is estimated as an ensemble of regression trees. To align targets across frameworks, machine learning outputs are mapped to a variance forecast and compared to realised volatility proxies. Hyperparameters are then selected using time-series cross-validation.

3.8 Forecast evaluation: loss functions and model comparison

Forecast evaluation follows the framework proposed by Patton (2011), which emphasises the use of loss functions that are robust to latent volatility and forecast dependence. In particular, the QLIKE loss function is employed due to its desirable theoretical properties when volatility is unobserved and must be proxied.

Model comparisons are conducted using the model confidence set procedure of P. R. Hansen et al. (2011) and the superior predictive ability test of P. R. Hansen (2005), which jointly account for serial correlation, multiple testing, and data-snooping concerns.

3.8.1 QLIKE loss

Following Patton-style volatility evaluation, the primary loss function is QLIKE:

$$L_{t+1}(m) = \frac{RV_{t+1}}{\widehat{\sigma}^2_{t+1|t}(m)} - \ln\left(\frac{RV_{t+1}}{\widehat{\sigma}^2_{t+1|t}(m)}\right) - 1, \tag{3.20}$$

where $\widehat{\sigma}^2_{t+1|t}(m)$ denotes the forecast from model m.

3.8.2 Loss differentials and benchmark comparison

Let model 0 denote the benchmark (e.g., GARCH(1,1)). Define the loss differential for model m relative to the benchmark as

$$d_{t+1}(m) = L_{t+1}(0) - L_{t+1}(m). \tag{3.21}$$

A positive mean of $d_{t+1}(m)$ indicates that model m improves upon the benchmark on average.

3.8.3 Superior predictive ability (SPA) test

The SPA test evaluates whether any competing model outperforms the benchmark while controlling for data-snooping. The null hypothesis is

$$H_0 : \max_{m \in \mathcal{M}} \mathbb{E}\left[d_t(m)\right] \leq 0, \tag{3.22}$$

against the alternative that at least one model has strictly positive expected improvement. Inference is conducted using a block bootstrap to account for serial dependence in the loss differentials.

3.8.4 Model confidence set (MCS)

To compare multiple models simultaneously, the model confidence set procedure is used to identify a subset $\widehat{\mathcal{M}}_{1-\alpha}$ of models that are statistically indistinguishable from the best model under the chosen loss function. The MCS algorithm iteratively removes inferior models based

on tests of equal predictive ability, using bootstrap-based critical values to accommodate dependence.

Chapter 4: Empirical Results

4.1 Descriptive statistics

4.1.1 Core distributional statistics

In table 4.1, I present the core distributional statistics of the log returns, squared returns as proxy for volatility and search-based interest (Google search trends).

The mean daily return was 0.1515% which represents an overall positive growth over the sample period, with a standard deviation of 3.6852 indicating substantial variability. The squared returns showed much higher mean of 13.5990 and a standard deviation of 49.9664 which shows the pronounced volatility clustering of Bitcoin returns. Sentiment, on the other hand, had an average of 37.5742 on a 0-100 scale, with a moderate standard deviation of 18.42.

The returns distribution displayed negative skewness of -0.6594, implying a tendency towards negative shocks, with excess kurtosis of 11.6433 which shows fat tails and higher likelihood of extreme events. In comparison, the squared returns had very high positive skewness(26.9102) and kurtosis(1,091.6969) which shows the presence of severe, albeit rare, volatility spikes. The sentiment variable was mildly positively skewed(0.6575) with an almost normal kurtosis of 0.3156

	Returns	Squared Returns	Sentiment
Mean	0.1515	13.5990	37.5742
Std. Dev.	3.6852	49.9664	18.4200
Min	-46.4730	0.0000	5.0000
Max	22.5119	2159.7414	100.0000
Skewness	-0.6594	26.9102	0.6575
Kurtosis	11.6433	1091.6969	0.3156

Table 4.1: Descriptive statistics

4.1.2 Quantiles and tail behaviour

Depicted in table 4.2 is the quantile and tail characterisitics of the variables. The median for the returns was close to zero at 0.1275, with asymmetric taols as the 1% quantile is -10.6030 and the 99% quantile being 10.1557 which show a greater downside risk. Similar to the returns, the squared returns had a positive median of 2.3597, but with an exploded upper tail of 146.3326 at the 99%, and a positive 1% tail value of 0.0007. These differences highlight the infrequent but intense volatility episodes. The sentiment variable quantiles varied from 7.4100(1%) to 93.00(99%) with a median of 36.00, implying that the search interest was more common on the upside.

These patterns reveal heavy-tailed behaviour in returns and volatility, with the inter-quantile range for the squared returns of 0.3872 to 10.7193 capturing moderate fluctuations, but the 95%(59.4999) to 99%(146.3326) indicated rapid escalation in extreme periods.

	Returns	Squared Returns	Sentiment
1%	-10.6030	0.0007	7.4100
5%	-5.8732	0.0128	12.0000
25%	-1.3578	0.3872	22.0000
50%	0.1275	2.3597	36.0000
75%	1.7339	10.7193	49.0000
95%	5.8442	59.4999	70.0000
99%	10.1557	146.3326	93.0000

Table 4.2: Quantiles tail behaviour

4.1.3 Dependence and persistence diagnostics

The autocorrelation functions displayed in figures 4.1 and 4.2 show the autocorrelation functions of returns and squared returns respectively. The ACF for the returns decayed rapidly to near zero after the first lag, with no significant persistence there after, while the ACF for the squared returns remained positive to about lag 25, with a huge initial drop, followed by slow decay beyond the first lag. This points to a strong volatility clustering

where past shocks influenced future variance over extended periods.




Figure 4.1: ACF of returns




Figure 4.2: ACF of squared returns

4.1.4 Normality and distributional tests

The Jarque-Bera(JB) tests in table 4.4 rejected normality for all series at p-values of 0.0000, with a particularly elevated JB statistic for the squared returns, driven by high kurtosis and skewness which justify the use of heavy-tailed innovations since the distributions are all non-Gaussian.

	Returns		Squared Returns	
	lb stat	lb pvalue	lb stat	lb pvalue
10	19.4988	0.0344	119.2477	0.0000
20	28.6540	0.0948	150.6879	0.0000

Table 4.3: Ljung-Box test results

	Returns	Squared Returns	Sentiment
JB Statistic	17975.6826	156405979.3164	239.4072
p-value	0.0000	0.0000	0.0000

Table 4.4: Jarque-Bera test results

4.1.5 Stationarity diagnostics

The Augmented-Dickey Fuller test statistics in table 4.5 rejected the null of unit root for all the series, with p-values ≤ 0.0001 with the returns showing the strongest evidence with the ADF statistic of -38.8121

	Returns	Squared Returns	Sentiment
ADF Statistic	-38.8121	-16.7408	-4.6383
p-value	0.0000	0.0000	0.0001
Used Lags	1.0000	6.0000	29.0000
Observations	3140.0000	3135.0000	3112.0000

Table 4.5: ADF stationarity tests

On the other hand, the KPSS statistics in table **??** failed to reject stationarity for the returns (p-value 0.1000), but rejected it for the squared returns and sentiment variables, each with p-values of 0.0100, suggesting that trend-stationarity adjustments may be needed for the latter.

4.1.6 Correlation analysis

Table 4.6 with the Pearson correlation matrix shows a negative association between log returns and squared returns(-0.1569), indicating the leverage effects where negative returns

	Returns	Squared Returns	Sentiment
KPSS Statistic	0.1430	2.1518	1.2827
p-value	0.1000	0.0100	0.0100
Used Lags	8.0000	17.0000	31.0000

amplified volatility. On the other hand, the squared returns correlated strongly with absolute returns at 0.7690. The sentiment variable had a weaker, but positive, correlation with the squared returns (0.1104) and absolute returns (0.1514) which hints at a modest link between search interest and volatility.

	log Return	Sq Return	Abs Return	Search Interest
log_return	1.0000	-0.1569	-0.0326	-0.0212
sq_return	-0.1569	1.0000	0.7690	0.1104
abs_return	-0.0326	0.7690	1.0000	0.1514
Search_Interest	-0.0212	0.1104	0.1514	1.0000

Table 4.6: Correlation matrix

The Spearman rank presented in table 4.7 were lower overall, with sentiment, squared returns and absolute returns all at 0.0943, implying that the relationship was robust to outliers, but not dominant.

	log Return	Sq Return	Abs Return	Search Interest
log_return	1.0000	0.0754	0.0754	-0.0275
sq_return	0.0754	1.0000	1.0000	0.0943
abs_return	0.0754	1.0000	1.0000	0.0943
Search_Interest	-0.0275	0.0943	0.0943	1.0000

Table 4.7: Spearman correlation matrix

4.2 Model estimation results

4.2.1 Model specification and estimation setup

Table 4.8 outlines the model setup, with log returns as the dependent variable, squared returns as the volatility proxy and search interest as the sentiment variable.

The GARCH and IGARCH models were both fitted with (1,1) order under normal and student-t innovations. The Random Forest baseline model included log returns and volume, but the sentiment-augmented model added search interest.

The in-sample period covered 2,513 observations, leaving 629 for the out-of-sample evaluation.

	Setting	Value
0	Return variable	log_return
1	Volatility proxy	sq_return
2	Sentiment variable	Search_Interest
3	GARCH order (p,q)	(1,1)
4	GARCH innovations compared	normal, t
5	RF baseline features	log_return, log_volume
6	RF sentiment-augmented features	log_return, log_volume, Search_Interest
7	In-sample size	2513
8	Out-of-sample size	629

Table 4.8: Model specification and set up

4.2.2 Baseline econometric volatility models

Table 4.9 presents the parameter values for the baseline GARCH(1,1) and IGARCH(1,1) models. In the case of the GARCH(1,1) model under normal innovations, the alpha parameter is 0.1212 and the beta is 0.8330, yielding a persistence ($\alpha + \beta$) of 0.9087. With the student-t innovations, the alpha parameter decreased to 0.0913, while the beta value increased to 0.9807, resulting in a persistence value of 1.0000, with 3.2225 degrees of freedom (ν), capturing fatter tails. The constant term, ω, was lower under student-t (0.1715 vs

0.8412 under normal innovations), and the mean return(μ), similarly, adjusted downwards (0.1238 vs 0.1858).

Under IGARCH(1,1), persistence was imposed top unity, and as a result, normal innovations had α value of 0.1639 and β of 0.8361 in comparison to the student-t innovations with an α of 0.0859 and β of 0.9141, with ν of 3.2270. The log-likelihood improved under student-t (-7,952.6269) in comparison to the normal innovations (-8,319.3774), indicating a better fit.

GARCH(1,1) estimation function

IGARCH(1,1) estimation parameters

	GARCH-Normal	GARCH-Student-t	IGARCH-Normal (R)	IGARCH-Student-t (R)
mu	0.185847	0.123799	0.180225	0.121114
omega	0.841197	0.171494	0.493541	0.167422
alpha[1]	0.121213	0.091255	0.163891	0.085879
beta[1]	0.832951	0.908745	0.836109	0.914121
nu	NaN	3.222464	NaN	3.226959
loglik	NaN	NaN	-8319.377434	-7952.626915

Table 4.9: Baseline econometric parameters

4.2.3 Sentiment-augmented econometric models

Table 4.10 presents the results of the sentiment-augmented econometric models. The models yeilded sentiment coefficients of 0.0000 across all the specifications, with no change in the other parameters, or the log-likelihood from the baseline models. This suggests that sentiment did not significantly alter the variance dynamics in these linear models.

QUESTION: Should I talk about the p-values and the significance of each variable? I guess so.

	GARCH-X		IGARCH-X (R)	
	Normal	Student-t	Normal	Student-t
μ	0.1858	0.1238	0.1802	0.1211
ω	0.8412	0.1715	0.4934	0.1674
α_1	0.1212	0.0913	0.1639	0.0859
β_1	0.8330	0.9087	0.8361	0.9141
ν	–	3.2225	–	3.2269
LogLik	–	–	-8319.38	-7952.63
γ (Sent.)	–	–	0.0000	0.0000

Table 4.10: Estimated parameters for sentiment-augmented GARCH and IGARCH models

4.2.4 Econometric models diagnostics

The Ljung-Box(LB) tests on the standardized residuals on table 4.11 showed no significant autocorrelation in squared residuals for baseline GARCH(1,1), with p-values 0.89 at lag ten, indicating adequate volatility capture. For the student-t innovations, the LB on raw residuals was borderline at lag 10, with p-value of 0.0348, but insignificant at lag 20(p-value = 0.1555).

Similar to the GARCH models, the IGARCH variants also had no significant variables with p-values well above 0.06 under both normal and student-t innovations.

Diagnostics for baseline GARCH

	GARCH-Normal				GARCH-Student-t			
	Std. Residuals		Squared Std. Residuals		Std. Residuals		Squared Std. Residuals	
	lb stat	lb pvalue	lb stat	lb pvalue	lb stat	lb pvalue	lb stat	lb pvalue
10	17.3255	0.0675	4.9298	0.8958	19.4550	0.0348	4.1966	0.9380
20	23.0314	0.2873	7.1366	0.9962	26.3202	0.1555	8.5331	0.9877

Table 4.11: GARCH residual diagnostics

	GARCH-X Normal				GARCH-X Student-t			
	Std. Residuals		Squared Std. Residuals		Std. Residuals		Squared Std. Residuals	
	lb stat	lb pvalue	lb stat	lb pvalue	lb stat	lb pvalue	lb stat	lb pvalue
10	17.3255	0.0675	4.9298	0.8958	19.4550	0.0348	4.1966	0.9380
20	23.0314	0.2873	7.1366	0.9962	26.3202	0.1555	8.5331	0.9877

Table 4.12: Sentiment-Augmented GARCH residual diagnostics

Diagnostics for GARCH-X

4.2.5 ARCH-LM test on standardized residuals

The ARCH-LM tests on table 4.13 failed to reject no remaining ARCH effects with p-values greater than 0.89, confirming model accuracy for all the four specifications of the econometric models.

	GARCH-Normal	GARCH-Student-t	GARCH-X Normal	GARCH-X Student-t
ARCH LM stat	4.9366	4.2011	4.9366	4.2011
p-value	0.8954	0.9378	0.8954	0.9378

Table 4.13: ARCH-LM tests

4.2.6 Baseline diagnostics for GARCH and IGARCH

	GARCH-Normal				GARCH-Student-t				IGARCH-Normal				IGARCH-Student-t			
	Std. Residuals		Sq. Std. Residuals		Std. Residuals		Sq. Std. Residuals		Std. Residuals		Sq. Std. Residuals		Std. Residuals		Sq. Std. Residuals	
	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val
10	17.33	0.0675	4.93	0.8958	19.46	0.0348	4.20	0.9380	17.40	0.0659	6.97	0.7279	17.52	0.0636	5.49	0.8565
20	23.03	0.2873	7.14	0.9962	26.32	0.1555	8.53	0.9877	24.33	0.2283	11.17	0.9416	24.72	0.2122	10.27	0.9630

Table 4.14: Ljung–Box tests for standardized and squared standardized residuals

4.2.7 Sentiment augmented diagnostics for GARCH and IGARCH

Similar to the diagnostics for the baseline models, the sentiment-augmented econometric models in table 4.15 mirrored the results in GARCH(1,1) and IGARCH(1,1) given the null

effects of sentiment in the models.

	GARCH-X Normal				GARCH-X Student-t				IGARCH-X Normal				IGARCH-X Student-t			
	Std. Residuals		Sq. Std. Residuals		Std. Residuals		Sq. Std. Residuals		Std. Residuals		Sq. Std. Residuals		Std. Residuals		Sq. Std. Residuals	
	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val	LB stat	p-val
10	17.33	0.0675	4.93	0.8958	19.46	0.0348	4.20	0.9380	17.40	0.0659	6.97	0.7280	17.52	0.0636	5.49	0.8565
20	23.03	0.2873	7.14	0.9962	26.32	0.1555	8.53	0.9877	24.33	0.2283	11.17	0.9416	24.72	0.2122	10.27	0.9630

Table 4.15: Ljung–Box tests for standardized and squared standardized residuals (sentiment-augmented models)

4.2.8 The Random Forests model

Table 4.16 represents the Random Forest in-sample fit, with the in-sample mean squared errors(MSE) of about 1206.39 in both the baseline and the sentiment-augmented models. The R-squared in both cases is 0.6057.

	Baseline RF	RF + Sentiment
In-sample MSE	1206.392310	1206.392866
In-sample R^2	0.605719	0.605719

Table 4.16: Random Forests in-sample fit

The feature importance in table 4.17 assigned full weight to log returns(1.0000), and zero to both the volume and sentiment variables, which implies that the non-linear models relied primarily on the recent returns.

	Baseline RF	RF + Sentiment
log_return	1.0000	1.0000
log_volume	0.0000	0.0000
Search_Interest	0.0000	0.0000

Table 4.17: Random Forests feature importance

	QLIKE	MSE	MAE
RF + Sentiment	1.787915	15.095598	1.299753
RF Baseline	1.788040	15.193521	1.302908
GARCH-Normal	2.861501	183.675070	7.966316
GARCH-X Normal	2.861501	183.675070	7.966316
IGARCH-X Normal (R)	2.896844	201.535143	8.517185
IGARCH-Normal (R)	2.901410	200.730852	8.493347
GARCH-Student-t	2.905533	206.427170	9.442986
GARCH-X Student-t	2.905533	206.427170	9.442986
IGARCH-Student-t (R)	2.914438	216.259794	9.738206
IGARCH-X Student-t (R)	2.924122	216.650582	9.824872

Table 4.18: Model forecast loss summary

	QLIKE	MSE	MAE
RF + Sentiment	1.0	1.0	1.0
RF Baseline	2.0	2.0	2.0
GARCH-Normal	3.5	3.5	3.5
GARCH-X Normal	3.5	3.5	3.5
IGARCH-X Normal (R)	5.0	6.0	6.0
IGARCH-Normal (R)	6.0	5.0	5.0
GARCH-Student-t	7.5	7.5	7.5
GARCH-X Student-t	7.5	7.5	7.5
IGARCH-Student-t (R)	9.0	9.0	9.0
IGARCH-X Student-t (R)	10.0	10.0	10.0

Table 4.19: Model forecast loss rankings

4.3 Forecasting performance

4.3.1 Econometric models forecasts

GARCH Models




Figure 4.3: Conditional volatility estimates from the GARCH family models

IGARCH Models




Figure 4.4: Conditional volatility estimates from the IGARCH models

4.3.2 Random forests forecasts




Figure 4.5: Conditional volatility estimates from the Random Forest models

4.3.3 Forecast evaluation and model comparison

The out-of-sample losses reported in table 4.20 show that the sentiment-augmented Random Forest model acheived the lowest QLIKE of 1.7879, MSE of 15.0956 and MAE of 1.2998, marginally outperforming the baseline RF with 1.7880, 15.1935 and 1.3029 as the values for QLIKE, MSE and MAE respectively.

The GARCH models lagged substantially with normal GARCH at QLIKE of 2.8615 and MSE of 183.6751. The student-t innovations performed worse for both the GARCH and IGARCH models, with and without the sentiment variable.

The rankings on table 4.21 show that the Random Forest models perform best overall, followed by the normal innovations in the GARCH models among the ten model variations presented. The IGARCH-X normal outperforms IGARCH normal under QLIKE, but the latter does better in both MSE and MAE rankings. In addition to the fact that the student-t innovations perform worst overall, the GARCH versions outperform IGARCH versions, with IGARCH-X student-t being the worst performing model overall.

	QLIKE	MSE	MAE
RF + Sentiment	1.787915	15.095598	1.299753
RF Baseline	1.788040	15.193521	1.302908
GARCH-Normal	2.861501	183.675070	7.966316
GARCH-X Normal	2.861501	183.675070	7.966316
IGARCH-X Normal (R)	2.896844	201.535143	8.517185
IGARCH-Normal (R)	2.901410	200.730852	8.493347
GARCH-Student-t	2.905533	206.427170	9.442986
GARCH-X Student-t	2.905533	206.427170	9.442986
IGARCH-Student-t (R)	2.914438	216.259794	9.738206
IGARCH-X Student-t (R)	2.924122	216.650582	9.824872

Table 4.20: Model forecast loss summary

	QLIKE	MSE	MAE
RF + Sentiment	1.0	1.0	1.0
RF Baseline	2.0	2.0	2.0
GARCH-Normal	3.5	3.5	3.5
GARCH-X Normal	3.5	3.5	3.5
IGARCH-X Normal (R)	5.0	6.0	6.0
IGARCH-Normal (R)	6.0	5.0	5.0
GARCH-Student-t	7.5	7.5	7.5
GARCH-X Student-t	7.5	7.5	7.5
IGARCH-Student-t (R)	9.0	9.0	9.0
IGARCH-X Student-t (R)	10.0	10.0	10.0

Table 4.21: Model forecast loss rankings

4.4 Robustness checks

4.4.1 Alternative forecast evaluation metrics

Using RMSE and MAE as alternative forecast evaluation metrics as shown in table 4.22, the RF + Sentiment remained top ranked, consistent with the primary ranking metrics.

Model	RMSE	MAE	RMSE Rank	MAE Rank
RF + Sentiment	3.8853	1.2998	1.0000	1.0000
RF Baseline	3.8979	1.3029	2.0000	2.0000
GARCH-Normal	13.5527	7.9663	3.0000	3.0000
GARCH-X Normal	13.5527	7.9663	3.0000	3.0000
IGARCH-Normal (R)	14.1680	8.4933	5.0000	5.0000
IGARCH-X Normal (R)	14.1963	8.5172	6.0000	6.0000
GARCH-Student-t	14.3676	9.4430	7.0000	7.0000
GARCH-X Student-t	14.3676	9.4430	7.0000	7.0000
IGARCH-Student-t (R)	14.7058	9.7382	9.0000	9.0000
IGARCH-X Student-t (R)	14.7191	9.8249	10.0000	10.0000

Table 4.22: Alternative model rankings

4.4.2 Alternative volatility proxies

With absolute volatility as proxies for volatility, table 4.23 shows that the GARCH models improved in performance, outperforming the Random Forest models that were dominant in the prior scenario with the squared returns as the proxy for volatility based on RMSE, while remaining competitive in the case of MAE. This suggests that the models are sensitive to the proxy choices as evidenced by the fact that under RMSE, the RF models rank worst, though they move to positions 3 and 4 for the sentiment-augmented and baseline RF models.

4.4.3 Alternative training and forecasting scheme - rolling window

With the RMSE and MAE values of 4.3381 and 1.3147 respectively, the sentiment-augmented Random Forest model reclaims the top spot under the rolling windows as presented in table

Model	RMSE (Abs)	MAE (Abs)	RMSE Rank (Abs)	MAE Rank (Abs)
GARCH-Normal	6.4682	5.3170	1.0000	1.0000
GARCH-X Normal	6.4682	5.3170	1.0000	1.0000
IGARCH-Normal (R)	8.0490	6.1110	3.0000	5.0000
IGARCH-X Normal (R)	8.1218	6.1312	4.0000	6.0000
GARCH-Student-t	9.5068	7.8522	5.0000	7.0000
GARCH-X Student-t	9.5068	7.8522	5.0000	7.0000
IGARCH-Student-t (R)	10.3082	8.2800	7.0000	9.0000
IGARCH-X Student-t (R)	10.3716	8.5268	8.0000	10.0000
RF + Sentiment	13.5202	5.3543	9.0000	3.0000
RF Baseline	13.5394	5.3603	10.0000	4.0000

Table 4.23: Robustness tests and model rankings

4.24, which is consistent with those under QLIKE, MSE and MAE with the squyared returns as the proxy for volatility.

Model	RMSE	MAE	RMSE Rank	MAE Rank
RF + Sentiment	4.3381	1.3147	1	1
RF Baseline	4.3546	1.3198	2	2
GARCH-Normal	12.7538	7.0354	3	3
GARCH-X Normal	12.7538	7.0354	3	3
IGARCH-X Normal (R)	13.4829	7.8665	5	5
IGARCH-Normal (R)	13.4914	7.8867	6	6
GARCH-Student-t	13.8302	8.6296	7	7
GARCH-X Student-t	13.8302	8.6296	7	7
IGARCH-Student-t (R)	14.2929	8.9795	9	9
IGARCH-X Student-t (R)	14.3083	9.1032	10	10

Table 4.24: Forecast evaluation and ranking under the restricted rolling-window robustness check

4.4.4 Robustness of sentiment effects

Lagging the sentiments by one more day as in table 4.25 yielded similar results as alternative training under rolling window with the sentiment-augmented RF still leading and the IGARCH models being the worst performers. This shows that the sentiment-augmente variable has minimal but stable contribution to the model performance.

Model	RMSE (Lag 1)	MAE (Lag 1)	RMSE Rank	MAE Rank
RF + Sentiment	3.8882	1.3001	1	1
RF Baseline	3.9008	1.3033	2	2
GARCH-Normal	13.5605	7.9677	3	3
GARCH-X Normal	13.5605	7.9677	3	3
IGARCH-Normal (R)	14.1781	8.4996	5	5
IGARCH-X Normal (R)	14.2064	8.5235	6	6
GARCH-Student-t	14.3740	9.4429	7	7
GARCH-X Student-t	14.3740	9.4429	7	7
IGARCH-Student-t (R)	14.7127	9.7388	9	9
IGARCH-X Student-t (R)	14.7260	9.8256	10	10

Table 4.25: Forecast evaluation and ranking under sentiment lag robustness check (Lag 1)

Chapter 5: Discussion

5.1 Interpretation of findings

5.2 Comparison with existing literature

5.3 Practical implications

5.4 Limitations

Chapter 6: Conclusion

6.1 Summary of key findings

6.2 Contributions to knowledge

6.3 Policy and practice implications

6.4 Future research directions

References

Amoanu, S. (2025). Comparative forecasting of financial time series using arima, garch, random forest, and xgboost models. *Research Square*. Retrieved from https://doi.org/10.21203/rs.3.rs-7837766/v1 doi: 10.21203/rs.3.rs-7837766/v1

Ardia, D., Bluteau, K., & Rüede, M. (2019). Regime changes in bitcoin garch volatility dynamics. *Finance Research Letters*, *29*, 266-271. Retrieved from https://www.sciencedirect.com/science/article/pii/S1544612318303970 doi: https://doi.org/10.1016/j.frl.2018.08.009

Argente, D., & Van Patten, D. (2024, January 29). *El salvador adopted bitcoin as an official currency; salvadorans mostly shrugged.* Retrieved from https://insights.som.yale.edu/insights/el-salvador-adopted-bitcoin-as-an-official-currency-salvadorans-mostly-shrugged

Babalos, V., Bouri, E., & Gupta, R. (2025). Does the introduction of us spot bitcoin etfs affect spot returns and volatility of major cryptocurrencies? *The Quarterly Review of Economics and Finance*, *102*, 102006. doi: 10.1016/j.qref.2025.102006

Basher, S. A., & Sadorsky, P. (2022). Forecasting bitcoin price direction with random forests: How important are interest rates, inflation, and market volatility? *Machine Learning with Applications*, *9*, 100355. Retrieved from https://www.sciencedirect.com/science/article/pii/S266682702200055X doi: https://doi.org/10.1016/j.mlwa.2022.100355

Bollerslev, T. (1986). Generalized autoregressive conditional heteroskedasticity. *Journal of Econometrics*, *31*(3), 307–327.

Bollerslev, T., Engle, R. F., & Nelson, D. B. (1994). Arch models. *Handbook of Econometrics*, *4*, 2959–3038.

Cheikh, N. B., Zaied, Y. B., & Chevallier, J. (2020). Asymmetric volatility in cryptocurrency markets: New evidence from smooth transition garch models. *Finance Research Letters*,

35, 101293. Retrieved from https://www.sciencedirect.com/science/article/pii/S154461231930162X doi: https://doi.org/10.1016/j.frl.2019.09.008

Chu, J., Chan, S., Nadarajah, S., & Osterrieder, J. (2017). Garch modelling of cryptocurrencies. *Journal of Risk and Financial Management*, *10*(4). Retrieved from https://www.mdpi.com/1911-8074/10/4/17

Corsi, F. (2009, 02). A simple approximate long-memory model of realized volatility. *Journal of Financial Econometrics*, *7*(2), 174-196. Retrieved from https://doi.org/10.1093/jjfinec/nbp001

Coulter, S. (2022). The impact of news media on bitcoin prices: Modeling data-driven discourses in the crypto-economy. *Digital Finance*, *4*(1), 25–54.

Demirer, R., Gkillas, K., Gupta, R., & Pierdzioch, C. (2022). Risk aversion and the predictability of crude oil market volatility: A forecasting experiment with random forests. *Journal of the Operational Research Society*, *73*(8), 1755–1767. Retrieved from https://doi.org/10.1080/01605682.2021.1936668 doi: 10.1080/01605682.2021.1936668

Diane, T., & Brijlal, P. (2024). Forecasting stock market realised volatility using random forest and artificial neural networks in south africa. *South African Journal of Economic and Management Sciences*, *27*(1), 1–15. Retrieved from https://doi.org/10.32479/ijefi.15431

Dudek, G., Fiszeder, P., Kobus, P., & Orzeszko, W. (2024). Forecasting cryptocurrencies volatility using statistical and machine learning methods: A comparative study. *Applied Soft Computing*, *151*, 111132. Retrieved from https://www.sciencedirect.com/science/article/pii/S156849462301150X doi: https://doi.org/10.1016/j.asoc.2023.111132

Dyhrberg, A. H. (2016). Bitcoin, gold and the dollar – a garch volatility analysis. *Finance Research Letters*, *16*, 85-92. Retrieved from https://www.sciencedirect.com/science/article/pii/S1544612315001038 doi: https://doi.org/10.1016/j.frl.2015.10.008

Engle, R. F. (1982). Autoregressive conditional heteroskedasticity with estimates of the variance of united kingdom inflation. *Econometrica*, *50*(4), 987–1007.

Engle, R. F., & Bollerslev, T. (1986). Modelling the persistence of conditional variances. *Econometric Reviews*, *5*(1), 1–50. Retrieved from https://doi.org/10.1080/07474938608800095 doi: 10.1080/07474938608800095

Gensler, G. (2024, Jan 10). *Statement on the approval of spot bitcoin exchange-traded products.* Retrieved from https://www.sec.gov/newsroom/speeches-statements/gensler-statement-spot-bitcoin-011023

Han, B., Liu, A., Chen, J., & Knottenbelt, W. (2025). Can machine learning models better volatility forecasting? a combined method. *The European Journal of Finance*, *0*(0), 1–22. Retrieved from https://doi.org/10.1080/1351847X.2025.2553053 doi: 10.1080/1351847X.2025.2553053

Hansen, B. E. (1994). Autoregressive conditional density estimation. *International Economic Review*, *35*(3), 705–730. Retrieved from https://users.ssc.wisc.edu/~behansen/papers/ier_94.pdf

Hansen, P. R. (2005). A test for superior predictive ability. *Journal of Business & Economic Statistics*, *23*(4), 365–380. Retrieved from https://doi.org/10.1198/073500105000000063

Hansen, P. R., Lunde, A., & Nason, J. M. (2011). The model confidence set. *Econometrica*, *79*(2), 453–497. Retrieved from https://papers.ssrn.com/sol3/papers.cfm?abstract_id=522382

Hoang, L., & Vo, D. H. (2024). Google search and cross-section of cryptocurrency returns and trading activities. *Journal of Behavioral and Experimental Finance*, *44*, 100991. Retrieved from https://www.sciencedirect.com/science/article/pii/S2214635024001060 doi: https://doi.org/10.1016/j.jbef.2024.100991

Kabo, I. G., Obunadike, G. N., & Samaila, N. A. (2025). Sentiment-driven and economic indicators for bitcoin price forecasting: A hybrid time series model. *Journal of Science Research and Reviews*, *2*(1), 99–107. doi: 10.70882/josrar.2025.v2i1.34

Katsiampa, P. (2017). Volatility estimation for bitcoin: A comparison of garch models. *Economics Letters*, *158*, 3-6. Retrieved from https://www.sciencedirect.com/science/article/pii/S0165176517302501 doi: https://doi.org/10.1016/j.econlet.2017.06.023

Kim, H. Y., & Won, C. H. (2018). Forecasting the volatility of stock price index: A hybrid model integrating lstm with multiple garch-type models. *Expert Systems with Applications*, *103*, 25-37. Retrieved from https://www.sciencedirect.com/science/article/pii/S0957417418301416 doi: https://doi.org/10.1016/j.eswa.2018.03.002

Leber, T., & Egyed, E. (2025). The sentiment-augmented garch-lstm hybrid model for value-at-risk forecasting. *European Journal of Operational Research*. Retrieved from https://doi.org/10.1007/s10614-025-11042-8

Luong, C., & Dokuchaev, N. (2018). Forecasting of realised volatility with the random forests algorithm. *Journal of Risk and Financial Management*, *11*(4). Retrieved from https://www.mdpi.com/1911-8074/11/4/61

Mai, F., Shan, Z., Bai, Q., Wang, X. S., & Chiang, R. H. (2018). How does social media impact bitcoin value? a test of the silent majority hypothesis. *Journal of Management Information Systems*, *35*(1), 19–52. Retrieved from https://doi.org/10.1080/07421222.2018.1440774 doi: 10.1080/07421222.2018.1440774

Nelson, D. B. (1990). Arch models as diffusion approximations. *Journal of Econometrics*, *45*(1), 7-38. Retrieved from https://www.sciencedirect.com/science/article/pii/0304407690900928 doi: https://doi.org/10.1016/0304-4076(90)90092-8

Patton, A. J. (2011). Volatility forecast comparison using imperfect volatility proxies. *Journal of Business & Economic Statistics*, *29*(2), 183–204. Retrieved from https://doi.org/10.1016/j.jeconom.2010.03.034

Sapkota, N. (2022). News-based sentiment and bitcoin volatility. *International Review of Financial Analysis*, *82*, 102183. Retrieved from https://www.sciencedirect.com/science/article/pii/S1057521922001454 doi: https://doi.org/10.1016/j.irfa.2022.102183

Wang, Y., Andreeva, G., & Martin-Barragan, B. (2023). Machine learning approaches to forecasting cryptocurrency volatility: Considering internal and external determinants. *International Review of Financial Analysis*, *90*, 102914. Retrieved from https://www.sciencedirect.com/science/article/pii/S1057521923004301 doi: https://doi.org/10.1016/j.irfa.2023.102914

Yu, R., Xiao, H., Zhu, Y., & Zhang, G. (2025). Does multi-scale garch information enhance volatility prediction? *Finance Research Letters*, *78*, 107196. Retrieved from https://www.sciencedirect.com/science/article/pii/S1544612325004593 doi: https://doi.org/10.1016/j.frl.2025.107196

Zahid, M., Iqbal, F., & Koutmos, D. (2022). Forecasting bitcoin volatility using hybrid garch models with machine learning. *Risks*, *10*(12). Retrieved from https://www.mdpi.com/2227-9091/10/12/237

Chapter A: The declaration of the use of AI tools

The thesis work was prepared with limited use of generative artificial intelligence(AI).

- In the first place, CurreChat was used to help define the structure or the outline of the document.
- ChatGPT was used to summarise some of the papers use as reference material, language refinement and structural editing during the drafting process.

All substantive parts of the thesis work including the formation of research questions, model selection and data collection were conducted by the author. No AI-generated data, models or empirical results have been used in this study.
As the author, I take full responsibility for the accuracy of the content and originality of this thesis work.