

FREE SAMPLE / 2026 EDITION

NETWORK SECURITY ASSESSMENT

Executive & Technical Sample Report

ASSESS -> REMEDIATE -> VALIDATE -> PROVE

Fictional organization and synthetic technical evidence. This sample demonstrates reporting structure, risk reasoning, remediation depth, and validation methodology. No real customer or production environment is represented.

weownit.net / Network & Security Consulting

Risk-informed security engineering · Architecture · Remediation · Validation

Executive assessment summary

From technical findings to business risk and validated remediation.

ASSESSMENT CONCLUSION

The synthetic environment shows common weaknesses in management-plane protection, network segmentation, privileged access, and security visibility. The principal concern is the combination of broad reachability, privileged exposure, and incomplete monitoring.

BUSINESS RISK

A compromised user workstation could create a path toward privileged network control. Excessive east-west access also increases lateral-movement opportunity, while incomplete logging can reduce detection and investigation capability.

OUTCOME

The sample shows how weownit.net connects evidence to business impact, remediation ownership, validation criteria, and residual risk - rather than stopping at a list of technical findings.

Business context & critical assets

Security decisions start with what the organization depends on.

CONTEXT

ACME Manufacturing is a fictional 250-user organization with a headquarters, two branches, business-critical ERP, internal application services, remote connectivity, and centralized network administration.

CRITICAL ASSETS

Internet edge firewall; management network; ERP and application servers; branch VPN connectivity; centralized security logging; privileged administrative identities.

SECURITY OBJECTIVES

Protect connectivity availability, integrity of privileged configuration, confidentiality of business data, segmentation between trust zones, and accountability of administrative actions.

Scope, assumptions & methodology

A repeatable assessment model for risk-informed security engineering.

SCOPE

Architecture, trust boundaries, administrative exposure, segmentation, firewall policy, logging, privileged access, configuration backup, and recovery readiness.

METHOD


CONTEXT -> ASSESS -> ANALYZE -> PRIORITIZE -> REMEDIATE -> VALIDATE -> PROVE

EVIDENCE CONFIDENCE

This sample uses SYNTHETIC / INFERRED evidence. In a real engagement, evidence is classified as Observed, Confirmed, Inferred, or Not Tested.

Architecture & trust boundaries

Where lower-trust zones can reach privileged control.



TRUST ZONES

Internet / User / Server / Management / Security Management / Branch VPN

KEY OBSERVATION

The user network can reach administrative HTTPS/SSH services on the edge firewall. This weakens the trust boundary and creates an unnecessary path from a lower-trust workstation segment to privileged security control.

TARGET STATE

Administrative access originates only from the management zone or an explicitly approved remote-administration path, protected by MFA, named accounts, least privilege, and centralized audit logging.

Risk register & prioritization

Prioritize risk scenarios, not isolated settings.

R-01 - MANAGEMENT-PLANE EXPOSURE

Likelihood 4/5 | Impact 5/5 | Inherent risk: CRITICAL | Target residual risk: LOW

R-02 - EXCESSIVE EAST-WEST ACCESS

Likelihood 4/5 | Impact 4/5 | Inherent risk: HIGH | Target residual risk: MEDIUM

R-03 - INCOMPLETE SECURITY LOGGING

Likelihood 3/5 | Impact 4/5 | Inherent risk: HIGH | Target residual risk: LOW

R-04 - PRIVILEGED ACCESS WITHOUT MFA

Likelihood 3/5 | Impact 5/5 | Inherent risk: HIGH | Target residual risk: LOW

1	2	3	4	5
2	4	6	8	10
3	6	9	12	15
4	8	12	16	
5	10	15	20	25

F-001 - Management plane reachable from the user zone

Detailed finding - HIGH / PRIORITY 1

ATTACK PATH

Compromised workstation -> User network -> Firewall management -> Privileged control

AFFECTED ASSET

Edge firewall / management plane.

OBSERVATION

Administrative HTTPS and SSH services are reachable from the general corporate user network rather than only through the dedicated management path.

THREAT SCENARIO

A compromised workstation could establish connectivity to the firewall management plane. Combined with credential compromise or another authentication weakness, this creates a credible path toward privileged control.

ILLUSTRATIVE EVIDENCE

Source 10.20.10.25 (USER) -> 10.20.100.1. TCP/443 REACHABLE; TCP/22 REACHABLE. Evidence type: SYNTHETIC.

POTENTIAL IMPACT

Unauthorized firewall policy, routing, VPN, or logging changes; service disruption; loss of control integrity.

F-001 - Control strategy & validation

Prevent, limit, detect, recover - then prove the result.

ATTACK PATH

Compromised workstation -> User network -> Firewall management -> Privileged control

PREVENT

Dedicated management network; approved administrative sources; MFA for privileged access; named administrator accounts.

LIMIT

Role-based administration; least privilege; required management protocols only; VPN/OOB administration where appropriate.

DETECT

Administrative login logging; failed-authentication monitoring; configuration-change audit trail; centralized security telemetry.

RECOVER

Validated configuration backup; emergency access path; documented rollback procedure; clear recovery ownership.

IMPLEMENTATION RISK

MEDIUM - restricting management access before confirming alternate administrative connectivity can cause lockout. Verify console/OOB access first.

VALIDATION EVIDENCE

Approved admin -> HTTPS ALLOW; USER -> HTTPS/SSH BLOCK; Internet -> management BLOCK; MFA REQUIRED; configuration changes LOGGED.

EXPECTED RESIDUAL RISK

LOW when management sources are restricted, MFA and named accounts are enforced, privileged actions are logged, and negative-path testing is successful.

F-002 - Excessive east-west network access

Detailed finding - HIGH / PRIORITY 1

OBSERVATION

A broad User-to-Server security policy permits more services than are required for normal business operation.

CURRENT STATE

USER -> SERVER: broad / any-style access.

VALIDATION

Positive test for required application flows plus negative tests for database and management services. Review denied-traffic logs.

THREAT SCENARIO

A compromised workstation can probe or connect to internal services unrelated to the user's business function, increasing the number of reachable targets and potential blast radius.

TARGET STATE

USER -> APP: required business services only. USER -> DB/MGMT: blocked unless explicitly justified.

RESIDUAL RISK

MEDIUM after least-privilege policy and monitoring, subject to application dependencies and formally approved exceptions.

Remediation roadmap & closure evidence

Turn findings into owned, measurable, and verifiable work.

0-7 DAYS

Contain privileged exposure: restrict firewall management reachability, verify emergency access, enforce MFA, and assign accountable owners.

0-30 DAYS

Reduce unnecessary trust: replace broad user-to-server access with approved application flows and validate dependencies before enforcement.

30-60 DAYS

Strengthen visibility and recovery: centralize security telemetry, verify audit retention, test configuration restore, and document recovery ownership.

CLOSURE CRITERIA

OPEN -> REMEDIATION PLANNED -> IMPLEMENTED -> VALIDATION REQUIRED -> VERIFIED -> CLOSED.

EVIDENCE PACK

Relevant configuration extract, approved change, positive and negative tests, audit evidence, residual-risk statement, and owner acceptance.

CLIENT OUTCOME

Executive assessment summary + technical findings register + risk-prioritized remediation backlog + architecture observations + validation plan + reusable closure evidence.