

## TECHNICAL SPECIFICATION

HOT ROLLED COILED (HRC)

HRC.25.045-THP-(SAE1012)

| No | Item                            | Specification                                                                                                                                           |                                                     |
|----|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| 1  | Steel Grade                     | SAE1012                                                                                                                                                 |                                                     |
| 2  | Standard                        | J403:2024                                                                                                                                               |                                                     |
| 3  | Width (mm)                      | <1300                                                                                                                                                   |                                                     |
| 4  | Width tolerance (mm)            | +0/+20mm(aming +8/+12mm,not include 20m each head and tail end )                                                                                        |                                                     |
| 5  | Thickness (mm)                  | W < 1300                                                                                                                                                | 1.20±5.00                                           |
| 6  | Thickness tolerance (mm)        | ±0.09                                                                                                                                                   |                                                     |
|    | Beyond thickness tolerance      | The thickness tolerances shall apply to any point, but it is not less than 40mm from edge of hot rolled coil and not include 20m each head and tail end |                                                     |
| 7  | Chemical composition (%)        | C                                                                                                                                                       | 0.10-0.15 ✓                                         |
|    |                                 | Mn                                                                                                                                                      | 0.30-0.60 ✓                                         |
|    |                                 | P                                                                                                                                                       | ≤0.02 ✓                                             |
|    |                                 | S                                                                                                                                                       | ≤0.025 ✓                                            |
|    |                                 | Si                                                                                                                                                      | ≤0.03 ✓                                             |
|    |                                 | Cu                                                                                                                                                      | ≤0.06 ✓                                             |
|    |                                 | Cr;Ni                                                                                                                                                   | ≤0.06 ✓                                             |
|    |                                 | B                                                                                                                                                       | -                                                   |
|    |                                 | N                                                                                                                                                       | -                                                   |
| 8  | Mechanical properties           | Al (Als)                                                                                                                                                | 200-600 ppm ✓                                       |
|    |                                 | Yield strength (MPa)                                                                                                                                    | Min 300 ✓                                           |
|    |                                 | Tensile strength (MPa)                                                                                                                                  | 400-580 ✓                                           |
|    |                                 | Elongation (%)                                                                                                                                          | ≥21 ✓                                               |
|    |                                 | Tbend                                                                                                                                                   | 1T ✓                                                |
|    |                                 | Impact test (J)                                                                                                                                         | -                                                   |
|    |                                 |                                                                                                                                                         |                                                     |
| 9  | Camber                          | 5mm/2000m length of strip, not include 20m each head and tail end ✓                                                                                     |                                                     |
| 10 | Crown                           | ≤80μm at the point 40mm from edge and not include 20m each head and tail end ✓                                                                          |                                                     |
| 11 | Wedge                           | ≤50μm at the point 40mm from edge and not include 20m each head and tail end ✓                                                                          |                                                     |
| 12 | High spot                       | ≤20μm ✓                                                                                                                                                 |                                                     |
| 13 | Coil ID                         | 762 (-20/+20) mm ✓                                                                                                                                      |                                                     |
| 14 | Coil OD                         | Max 2000mm ✓                                                                                                                                            |                                                     |
| 15 | Fishtail/ Tongue                | Non skin-pass                                                                                                                                           | Max 500mm each end ✓                                |
|    |                                 | Skin-passed                                                                                                                                             | None                                                |
| 16 | Edge condition                  | Mill edge; free from crack, saw tooth, bavia, ...                                                                                                       |                                                     |
| 17 | Flatness tolerance              | Non skin-pass                                                                                                                                           | Max 20mm (not include 20m each head and tail end) ✓ |
|    |                                 | Skin-passed                                                                                                                                             | Max 9mm (not include 15m each head and tail end) ✓  |
| 18 | Telescope                       | Non skin-pass                                                                                                                                           | Max 50mm ✓                                          |
|    |                                 | Skin-passed                                                                                                                                             | Max 30mm ✓                                          |
| 19 | Defect                          | Free from crack, hole, rolled in scale & sliver... (not include 20m each head and tail end)<br>No coil break except 20m head and 20m tail end           |                                                     |
| 20 | Packing                         | As mill's standard                                                                                                                                      |                                                     |
| 21 | Label                           | As mill's standard                                                                                                                                      |                                                     |
| 22 | Coild Weigh                     | W: 1200 ÷ 1299                                                                                                                                          | 23 ÷ 25 ton (aming 24-25 ton) ✓                     |
| 23 | Grain size                      | 08-10 (according to ASTM E112)                                                                                                                          |                                                     |
| 24 | Non - Metallic Inclusion        | ≤ Level 2 (according to ISO 4967)                                                                                                                       |                                                     |
| 25 | Finishing mill temperature (°C) | aiming ≤ 900 (±20°C)                                                                                                                                    |                                                     |
| 26 | Coiling temperature (°C)        | Coiling temperature 620 (+-20) °C min ✓                                                                                                                 |                                                     |

THP

HPDQ

Ngô Quang Hồng



OS2511166999

