

# Metadata Management Tool Non-Distributed Dependencies

## Dependencies

As of December 3, 2015 11:23am

### 95 total

- 82 MIT
- 2 ruby
- 2 Apache 2.0
- 1 ISC
- 1 GPL2, ruby
- 1 BSD
- 1 Artistic 2.0, GPL-2, MIT
- 1 GNU GPL v2, MIT, Perl Artistic v2
- 1 LGPL-2.1+
- 1 LGPLv2.1+
- 1 New BSD
- 1 GPLv2+, Ruby 1.8

The listed dependencies are required to run Metadata Mangement Tool but need not be distributed with the Metadata Mangement Tool source code in source or binary form.

## actionmailer v4.2.1

MIT whitelisted ✓

### Email composition, delivery, and receiving framework (part of Rails).

Email on Rails. Compose, deliver, receive, and test emails using the familiar controller/view pattern. First-class support for multipart email and attachments.

#### actionmailer is required by:

rails, web-console

#### actionmailer relies on:

actionpack, actionview, activejob, mail, rails-dom-testing

## actionpack v4.2.1

MIT whitelisted ✓

### Web-flow and rendering framework putting the VC in MVC (part of Rails).

Web apps on Rails. Simple, battle-tested conventions for building and testing MVC web applications. Works with any Rack-compatible server.

#### actionpack is required by:

actionview, actionmailer, railties, kaminari, sprockets-rails, rails, rspec-rails

#### actionpack relies on:

activesupport, rack, rack-test, rails-html-sanitizer, rails-dom-testing, actionview, activemodel

## actionview v4.2.1

MIT whitelisted ✓

## Rendering framework putting the V in MVC (part of Rails).

Simple, battle-tested conventions and helpers for building web pages.

### actionview is required by:

actionpack, actionmailer, railties, rails

### actionview relies on:

activesupport, builder, erubis, rails-html-sanitizer, rails-dom-testing, actionpack, activemodel

## activejob v4.2.1

MIT whitelisted ✓

### Job framework with pluggable queues.

Declare job classes that can be run by a variety of queueing backends.

### activejob is required by:

actionmailer, rails

### activejob relies on:

activesupport, globalid

## activemodel v4.2.1

MIT whitelisted ✓

### A toolkit for building modeling frameworks (part of Rails).

A toolkit for building modeling frameworks like Active Record. Rich support for attributes, callbacks, validations, serialization, internationalization, and testing.

### activemodel is required by:

actionview, actionpack, activerecord, rails, web-console

### activemodel relies on:

activesupport, builder

## activerecord v4.2.1

MIT whitelisted ✓

### Object-relational mapper framework (part of Rails).

Databases on Rails. Build a persistent domain model by mapping database tables to Ruby classes. Strong conventions for associations, validations, aggregations, migrations, and testing come baked-in.

### activerecord is required by:

database\_cleaner, factory\_girl, rails, web-console

### activerecord relies on:

activesupport, activemodel, arel

## activesupport v4.2.1

MIT whitelisted ✓

### A toolkit of support libraries and Ruby core extensions extracted from the Rails framework.

A toolkit of support libraries and Ruby core extensions extracted from the Rails framework. Rich support for multibyte strings, internationalization, time zones, and testing.

### activesupport is required by:

rails-deprecated\_sanitizer, rails-dom-testing, actionview, actionpack, globalid, activejob, activemodel, activerecord, carmen, railties, factory\_girl, jbuilder, kaminari, sprockets-rails, rails, rspec-rails

### activesupport relies on:

i18n, json, tzinfo, minitest, thread\_safe

## addressable v2.3.8

Apache 2.0 whitelisted ✓

## URI Implementation

Addressable is a replacement for the URI implementation that is part of Ruby's standard library. It more closely conforms to the relevant RFCs and adds support for IRIs and URI templates.

### addressable is required by:

launchy, json-schema

### addressable relies on:

rake, rspec, rspec-its, launchy

## arel v6.0.0

MIT whitelisted ✓

### Arel Really Exasperates Logicians Arel is a SQL AST manager for Ruby

Arel Really Exasperates Logicians Arel is a SQL AST manager for Ruby. It 1. Simplifies the generation of complex SQL queries 2. Adapts to various RDBMSes It is intended to be a framework framework; that is, you can build your own ORM with it, focusing on innovative object and collection modeling as opposed to database compatibility and query generation.

### arel is required by:

activerecord

### arel relies on:

minitest, rdoc, rake

## awrence v0.1.0 (default)

MIT whitelisted ✓

### Camelize your snake keys when working with JSON APIs

Have you ever needed to automatically convert Ruby-style snake\_case to CamelCase or camelBack hash keys? Awrence to the rescue. This gem recursively converts all snake\_case keys in a hash structure to camelBack.

### awrence relies on:

minitest, yard, rdoc, bundler, jeweler

## binding\_of\_caller v0.7.2

MIT whitelisted ✓

### Retrieve the binding of a method's caller. Can also retrieve bindings even further up the stack.

Retrieve the binding of a method's caller. Can also retrieve bindings even further up the stack.

### binding\_of\_caller is required by:

web-console

### binding\_of\_caller relies on:

debug\_inspector, bacon, rake

## bourbon v4.2.3 (default)

MIT whitelisted ✓

### A simple and lightweight mixin library for Sass

Bourbon is a library of pure Sass mixins that are designed to be simple and easy to use. No configuration required. The mixins aim to be as vanilla as possible, meaning they should be as close to the original CSS syntax as possible.

### bourbon is required by:

neat

### bourbon relies on:

sass, thor, aruba, css\_parser, rake, rspec, scss-lint

## builder v3.2.2

MIT whitelisted ✓

### Builders for Markup.

Builder provides a number of builder objects that make creating structured data simple to do. Currently the following builder objects are supported: \* XML Markup \* XML Events

**builder is required by:**

actionview, activemodel, rack\_session\_access, tilt, rspec\_junit\_formatter

## bundler v1.10.5

MIT whitelisted ✓

### The best way to manage your application's dependencies

Bundler manages an application's dependencies through its entire life, across many machines, systematically and repeatably

**bundler is required by:**

rails-deprecated\_sanitizer, rails-dom-testing, rails-html-sanitizer, mail, awrence, thor, byebug, cliver, database\_cleaner, figaro, multi\_json, jshint, json-schema, kaminari, multi\_xml, neat, rails, rspec-support, sdock, simplecov-html, simplecov, uglifier

**bundler relies on:**

mustache, rake, rdiscount, ronn, rspec

## byebug v5.0.0 (development, test)

BSD whitelisted ✓

### Ruby 2.0 fast debugger - base + CLI

Byebug is a Ruby 2 debugger. It's implemented using the Ruby 2 TracePoint C API for execution control and the Debug Inspector C API for call stack navigation. The core component provides support that front-ends can build on. It provides breakpoint handling and bindings for stack frames among other things and it comes with an easy to use command line interface.

**byebug relies on:**

columnize, bundler

## capybara v2.4.4 (test)

MIT whitelisted ✓

### Capybara aims to simplify the process of integration testing Rack applications, such as Rails, Sinatra or Merb

Capybara is an integration testing tool for rack based web applications. It simulates how a user would interact with a website

**capybara is required by:**

capybara-screenshot, kaminari, poltergeist

**capybara relies on:**

nokogiri, mime-types, rack, rack-test, xpath, selenium-webdriver, sinatra, rspec, launchy, yard, fuubar, cucumber, rake, pry

## capybara-screenshot v1.0.9 (test)

MIT whitelisted ✓

### Automatically create snapshots when Cucumber steps fail with Capybara and Rails

When a Cucumber step fails, it is useful to create a screenshot image and HTML file of the current page

**capybara-screenshot relies on:**

capybara, launchy, rspec, timecop, cucumber, aruba, sinatra, test-unit, spinach, minitest

## carmen v1.0.2 (default)

MIT whitelisted ✓

### A collection of geographic region data for Ruby

Includes data from the Debian iso-data project.

**carmen relies on:**

minitest, nokogiri, rake, i18n, activesupport

## cliver v0.3.2

MIT whitelisted ✓

### Cross-platform version constraints for cli tools

Assertions for command-line dependencies

**cliver is required by:**

poltergeist

**cliver relies on:**

bundler, rake, rspec, ruby-appraiser-reek, ruby-appraiser-rubocop, yard

## coffee-rails v4.1.0 (default)

MIT whitelisted ✓

### CoffeeScript adapter for the Rails asset pipeline.

CoffeeScript adapter for the Rails asset pipeline.

**coffee-rails relies on:**

coffee-script, railties

## coffee-script v2.4.1

MIT whitelisted ✓

### Ruby CoffeeScript Compiler

Ruby CoffeeScript is a bridge to the JS CoffeeScript compiler.

**coffee-script is required by:**

coffee-rails, poltergeist, tilt, sprockets

**coffee-script relies on:**

coffee-script-source, execjs, json, rake

## coffee-script-source v1.9.1.1

MIT whitelisted ✓

### The CoffeeScript Compiler

CoffeeScript is a little language that compiles into JavaScript. Underneath all of those embarrassing braces and semicolons, JavaScript has always had a gorgeous object model at its heart. CoffeeScript is an attempt to expose the good parts of JavaScript in a simple way.

**coffee-script-source is required by:**

coffee-script, sprockets

## columnize v0.9.0

ruby, GPL2 whitelisted ✓

### Module to format an Array as an Array of String aligned in columns

In showing a long lists, sometimes one would prefer to see the value arranged aligned in columns. Some examples include listing methods of an object or debugger commands. See Examples in the rdoc documentation for examples.

**columnize is required by:**

byebug

**columnize relies on:**

rdoc, rake

## database\_cleaner v1.4.1 (default)

MIT whitelisted ✓

### Strategies for cleaning databases. Can be used to ensure a clean state for testing.

Strategies for cleaning databases. Can be used to ensure a clean state for testing.

**database\_cleaner is required by:**

kaminari

**database\_cleaner relies on:**

rake, ruby-debug, ruby-debug19, bundler, json\_pure, activerecord-mysql2-adapter, activerecord, datamapper, dm-migrations, dm-sqlite-adapter, mongoid, tzinfo, mongo\_ext, bson\_ext, mongoid-tree, mongo\_mapper, moped, neo4j-core, couch\_potato, sequel, mysql, mysql2, pg, ohm, guard-

## debug\_inspector v0.0.2

MIT whitelisted ✓

### A Ruby wrapper for the MRI 2.0 debug\_inspector API

A Ruby wrapper for the MRI 2.0 debug\_inspector API

#### debug\_inspector is required by:

binding\_of\_caller

## diff-lcs v1.2.5

MIT, Perl Artistic v2, GNU GPL v2 whitelisted ✓

### Diff::LCS computes the difference between two Enumerable sequences using the McIlroy-Hunt longest common subsequence (LCS) algorithm

Diff::LCS computes the difference between two Enumerable sequences using the McIlroy-Hunt longest common subsequence (LCS) algorithm. It includes utilities to create a simple HTML diff output format and a standard diff-like tool. This is release 1.2.4, fixing a bug introduced after diff-lcs 1.1.3 that did not properly prune common sequences at the beginning of a comparison set. Thanks to Paul Kunysch for fixing this issue. Coincident with the release of diff-lcs 1.2.3, we reported an issue with Rubinius in 1.9 mode ([{{rubinius/rubinius#2268}}](https://github.com/rubinius/rubinius/issues/2268)) [<https://github.com/rubinius/rubinius/issues/2268>]. We are happy to report that this issue has been resolved.

#### diff-lcs is required by:

rspec-expectations, rspec-mocks

#### diff-lcs relies on:

rubyforge, rdoc, hoe-bundler, hoe-doofus, hoe-gemspec2, hoe-git, hoe-rubygems, hoe-travis, rake, rspec, hoe

## docile v1.1.5

MIT whitelisted ✓

### Docile keeps your Ruby DSLs tame and well-behaved

Docile turns any Ruby object into a DSL. Especially useful with the Builder pattern.

#### docile is required by:

simplecov

#### docile relies on:

rake, rspec, yard, redcarpet, github-markup, coveralls

## erubis v2.7.0

MIT whitelisted ✓

### a fast and extensible eRuby implementation which supports multi-language

Erubis is an implementation of eRuby and has the following features: \* Very fast, almost three times faster than ERB and about 10% faster than eruby. \* Multi-language support (Ruby/PHP/C/Java/Scheme/Perl/Javascript) \* Auto escaping support \* Auto trimming spaces around '<% %>' \* Embedded pattern changeable (default '<% %>') \* Enable to handle Processing Instructions (PI) as embedded pattern (ex. '') \* Context object available and easy to combine eRuby template with YAML datafile \* Print statement available \* Easy to extend and customize in subclass \* Ruby on Rails support

#### erubis is required by:

actionview, tilt

## execjs v2.5.2

MIT whitelisted ✓

### Run JavaScript code from Ruby

ExecJS lets you run JavaScript code from Ruby.

#### execjs is required by:

coffee-script, jshint, sprockets, uglifier

#### execjs relies on:

rake

## factory\_girl v4.5.0

MIT whitelisted ✓

**factory\_girl provides a framework and DSL for defining and using model instance factories.**

factory\_girl provides a framework and DSL for defining and using factories - less error-prone, more explicit, and all-around easier to work with than fixtures.

**factory\_girl is required by:**

factory\_girl\_rails

**factory\_girl relies on:**

activesupport, rspec, cucumber, timecop, simplecov, aruba, mocha, bourne, appraisal, activerecord, sqlite3, yard

## factory\_girl\_rails v4.5.0 (development, test)

MIT whitelisted ✓

**factory\_girl\_rails provides integration between factory\_girl and rails 3**

factory\_girl\_rails provides integration between factory\_girl and rails 3 (currently just automatic factory definition loading)

**factory\_girl\_rails relies on:**

railties, factory\_girl

## faraday v0.8.9 (default)

MIT whitelisted ✓

**HTTP/REST API client library.**

**faraday is required by:**

faraday\_middleware

**faraday relies on:**

multipart-post, rake, simplecov

## faraday\_middleware v0.9.0 (default)

MIT whitelisted ✓

**Various middleware for Faraday**

Various middleware for Faraday

**faraday\_middleware relies on:**

faraday, multi\_xml, rake, hashie, rash, rspec, simple\_oauth, rack-cache

## figaro v1.1.1 (default)

MIT whitelisted ✓

**Simple Rails app configuration**

Simple, Heroku-friendly Rails app configuration using ENV and a single YAML file

**figaro relies on:**

thor, bundler, rake

## globalid v0.3.5

MIT whitelisted ✓

**Refer to any model with a URI: gid://app/class/id**

URIs for your models makes it easy to pass references around.

**globalid is required by:**

activejob

**globalid relies on:**

activesupport, rake

MIT whitelisted ✓

## hike v1.2.3

### Find files in a set of paths

A Ruby library for finding files in a set of paths.

#### hike is required by:

sprockets

#### hike relies on:

rake

## i18n v0.7.0

MIT whitelisted ✓

### New wave Internationalization support for Ruby

New wave Internationalization support for Ruby.

#### i18n is required by:

activesupport, carmen

## jbuilder v2.2.16 (default)

MIT whitelisted ✓

### Create JSON structures via a Builder-style DSL

#### jbuilder relies on:

activesupport, multi\_json

## jquery-rails v4.0.3 (default)

MIT whitelisted ✓

### Use jQuery with Rails 4+

This gem provides jQuery and the jQuery-ujs driver for your Rails 4+ application.

#### jquery-rails relies on:

railties, thor, rails-dom-testing

## jshint v1.4.0 (development, test)

MIT whitelisted ✓

### Ensures your JavaScript code adheres to best practices

It achieves this by linting your code through a library called JSHint which catches most code smells, and ensures code consistency

#### jshint relies on:

therubyracer, execjs, multi\_json, bundler, railties, rake, rspec, yard

## json v1.8.3

ruby whitelisted ✓

### JSON Implementation for Ruby

This is a JSON implementation as a Ruby extension in C.

#### json is required by:

activesupport, loofah, coffee-script, sprockets, sdoc, simplecov, uglifier

#### json relies on:

permutation, sdoc

## json-schema v2.5.1 (default)

MIT whitelisted ✓

### Ruby JSON Schema Validator

json-schema relies on:



rake, minitest, webmock, bundler, addressable

## kaminari v0.16.3 (default)

MIT whitelisted ✓

### A pagination engine plugin for Rails 3+ and other modern frameworks

Kaminari is a Scope & Engine based, clean, powerful, agnostic, customizable and sophisticated paginator for Rails 3+

#### kaminari relies on:

activesupport, actionpack, bundler, rake, tzinfo, rspec, rr, capybara, database\_cleaner, rdoc

## kgio v2.9.3

LGPL-2.1+ whitelisted ✓

### kinder, gentler I/O for Ruby

kgio provides non-blocking I/O methods for Ruby without raising exceptions on EAGAIN and EINPROGRESS. It is intended for use with the Unicorn and Rainbows! Rack servers, but may be used by other applications (that run on Unix-like platforms).

#### kgio is required by:

unicorn

#### kgio relies on:

olddoc, test-unit

## launchy v2.4.3 (test)

ISC whitelisted ✓

### Launchy is helper class for launching cross-platform applications in a fire and forget manner.

Launchy is helper class for launching cross-platform applications in a fire and forget manner. There are application concepts (browser, email client, etc) that are common across all platforms, and they may be launched differently on each platform. Launchy is here to make a common approach to launching external application from within ruby programs.

#### launchy is required by:

addressable, capybara, capybara-screenshot, poltergeist

#### launchy relies on:

addressable, rake, minitest, rdoc

## libv8 v3.16.14.11

MIT whitelisted ✓

### Distribution of the V8 JavaScript engine

Distributes the V8 JavaScript engine in binary and source forms in order to support fast builds of The Ruby Racer

#### libv8 is required by:

therubyracer

#### libv8 relies on:

rake, rake-compiler, rspec, rspec-spies

## loofah v2.0.2

MIT whitelisted ✓

### Loofah is a general library for manipulating and transforming HTML/XML documents and fragments

Loofah is a general library for manipulating and transforming HTML/XML documents and fragments. It's built on top of Nokogiri and libxml2, so it's fast and has a nice API. Loofah excels at HTML sanitization (XSS prevention). It includes some nice HTML sanitizers, which are based on HTML5lib's whitelist, so it most likely won't make your codes less secure. (These statements have not been evaluated by Netexperts.) ActiveRecord extensions for sanitization are available in the 'loofah-activerecord' gem (see <https://github.com/flavorjones/loofah-activerecord>).

#### loofah is required by:

rails-html-sanitizer

#### loofah relies on:

nokogiri, rdoc, rake, minitest, rr, json, hoe-gemspec, hoe-debugging, hoe-bundler, hoe-git, hoe

**Mail provides a nice Ruby DSL for making, sending and reading emails.**

A really Ruby Mail handler.

**mail is required by:**

actionmailer

**mail relies on:**

mime-types, bundler, rake, rspec, rdoc

**The mime-types library provides a library and registry for information about MIME content type definitions**

The mime-types library provides a library and registry for information about MIME content type definitions. It can be used to determine defined filename extensions for MIME types, or to use filename extensions to look up the likely MIME type definitions. MIME content types are used in MIME-compliant communications, as in e-mail or HTTP traffic, to indicate the type of content which is transmitted. The mime-types library provides the ability for detailed information about MIME entities (provided as an enumerable collection of MIME::Type objects) to be determined and used. There are many types defined by RFCs and vendors, so the list is long but by definition incomplete; don't hesitate to add additional type definitions. MIME type definitions found in mime-types are from RFCs, W3C recommendations, the {IANA Media Types registry} [https://www.iana.org/assignments/media-types/media-types.xhtml], and user contributions. It conforms to RFCs 2045 and 2231. This is release 2.6 with two new experimental features. The first new feature is a new default registry storage format that greatly reduces the initial memory use of the mime-types library. This feature is enabled by requiring +mime/types/columnar+ instead of +mime/types+ with a small performance cost and no change in \*total\* memory use if certain methods are called (see {Columnar Store}[#columnar-store] for more details). The second new feature is a logger interface that conforms to the expectations of an ActiveSupport::Logger so that warnings can be written to an application's log rather than the default location for +warn+. This interface may be used for other logging purposes in the future. mime-types 2.6 is the last planned version of mime-types 2.x, so deprecation warnings are no longer cached but provided every time the method is called. mime-types 2.6 supports Ruby 1.9.2 or later.

**mime-types is required by:**

mail, capybara

**mime-types relies on:**

minitest, rdoc, hoe-doofus, hoe-gemspec2, hoe-git, hoe-rubygems, hoe-travis, minitest-autotest, minitest-focus, rake, simplecov, coveralls, hoe

**Simplistic port-like solution for developers**

Simplistic port-like solution for developers. It provides a standard and simplified way to compile against dependency libraries without messing up your system.

**mini\_portile is required by:**

nokogiri, sqlite3

**minitest provides a complete suite of testing facilities supporting TDD, BDD, mocking, and benchmarking**

minitest provides a complete suite of testing facilities supporting TDD, BDD, mocking, and benchmarking. "I had a class with Jim Weirich on testing last week and we were allowed to choose our testing frameworks. Kirk Haines and I were paired up and we cracked open the code for a few test frameworks... I MUST say that minitest is \*very\* readable / understandable compared to the 'other two' options we looked at. Nicely done and thank you for helping us keep our mental sanity." -- Wayne E. Seguin minitest/unit is a small and incredibly fast unit testing framework. It provides a rich set of assertions to make your tests clean and readable. minitest/spec is a functionally complete spec engine. It hooks onto minitest/unit and seamlessly bridges test assertions over to spec expectations. minitest/benchmark is an awesome way to assert the performance of your algorithms in a repeatable manner. Now you can assert that your newb co-worker doesn't replace your linear algorithm with an exponential one! minitest/mock by Steven Baker, is a beautifully tiny mock (and stub) object framework. minitest/pride shows pride in testing and adds coloring to your test output. I guess it is an example of how to write IO pipes too. :P minitest/unit is meant to have a clean implementation for language implementors that need a minimal set of methods to bootstrap a working test suite. For example, there is no magic involved for test-case discovery. "Again, I can't praise enough the idea of a testing/specing framework that I can actually read in full in one sitting!" -- Piotr Sztokowski Comparing to rspec: rspec is a testing DSL. minitest is ruby. -- Adam Hawkins, "Bow Before MiniTest" minitest doesn't reinvent anything that ruby already provides, like: classes, modules, inheritance, methods. This means you only have to learn ruby to use minitest and all of your regular OO practices like extract-method refactorings still apply.

**minitest is required by:**

thread\_safe, activesupport, nokogiri, rails-dom-testing, loofah, rails-html-sanitizer, mime-types, arel, awrence, sass, launchy, capybara-screenshot, carmen, json-schema, rspec-core, rspec-expectations, rspec-mocks, sdock, sqlite3

**minitest relies on:**

rdoc, hoe

## multi\_json v1.11.0

MIT whitelisted ✓

### A common interface to multiple JSON libraries.

A common interface to multiple JSON libraries, including Oj, Yajl, the JSON gem (with C-extensions), the pure-Ruby JSON gem, NSJSONSerialization, gson.rb, JrJackson, and OkJson.

**multi\_json is required by:**

builder, jshint, poltergeist, sprockets

**multi\_json relies on:**

bundler

## multi\_xml v0.5.5 (default)

MIT whitelisted ✓

### A generic swappable back-end for XML parsing

Provides swappable XML backends utilizing LibXML, Nokogiri, Ox, or REXML.

**multi\_xml is required by:**

faraday\_middleware

**multi\_xml relies on:**

bundler

## multipart-post v1.2.0

MIT whitelisted ✓

### A multipart form post accessory for Net::HTTP.

Use with Net::HTTP to do multipart form posts. IO values that have #content\_type, #original\_filename, and #local\_path will be posted as a binary file.

**multipart-post is required by:**

faraday

## neat v1.7.2 (default)

MIT whitelisted ✓

### A lightweight, semantic grid framework built with Bourbon

Neat is a fluid grid framework built with Bourbon with the aim of being easy enough to use out of the box and flexible enough to customize down the road.

**neat relies on:**

sass, bourbon, aruba, rake, css\_parser, rspec, rdoc, bundler, rb-fsevent, scss-lint

## nokogiri v1.6.6.2

MIT whitelisted ✓

### Nokogiri (鋸) is an HTML, XML, SAX, and Reader parser

Nokogiri (鋸) is an HTML, XML, SAX, and Reader parser. Among Nokogiri's many features is the ability to search documents via XPath or CSS3 selectors. XML is like violence - if it doesn't solve your problems, you are not using enough of it.

**nokogiri is required by:**

rails-dom-testing, loofah, xpath, capybara, carmen, tilt, rspec-core, rspec\_junit\_formatter

**nokogiri relies on:**

mini\_portile, rdoc, hoe-bundler, hoe-debugging, hoe-gemspec, hoe-git, minitest, rake, rake-compiler, racc, rexical, hoe

## poltergeist v1.6.0 (test)

MIT whitelisted ✓

### PhantomJS driver for Capybara

Poltergeist is a driver for Capybara that allows you to run your tests on a headless WebKit browser, provided by PhantomJS.

#### poltergeist relies on:

capybara, websocket-driver, multi\_json, cliver, launchy, rspec, sinatra, rake, image\_size, pdf-reader, coffee-script, guard-coffeescript, rspec-rerun

## rack v1.6.4

MIT whitelisted ✓

### a modular Ruby webserver interface

Rack provides a minimal, modular and adaptable interface for developing web applications in Ruby. By wrapping HTTP requests and responses in the simplest way possible, it unifies and distills the API for web servers, web frameworks, and software in between (the so-called middleware) into a single method call. Also see <http://rack.github.io/>.

#### rack is required by:

rack-test, actionpack, capybara, rack\_session\_access, sprockets, raindrops, unicorn

#### rack relies on:

bacon, rake

## rack-test v0.6.3

MIT whitelisted ✓

### Simple testing API built on Rack

Rack::Test is a small, simple testing API for Rack apps. It can be used on its own or as a reusable starting point for Web frameworks and testing libraries to build on. Most of its initial functionality is an extraction of Merb 1.0's request helpers feature.

#### rack-test is required by:

actionpack, capybara, sprockets

#### rack-test relies on:

rack

## rack\_session\_access v0.1.1 (test)

MIT whitelisted ✓

### Rack middleware that provides access to rack.session environment

#### rack\_session\_access relies on:

rack, builder

## rails v4.2.1 (default)

MIT whitelisted ✓

### Full-stack web application framework.

Ruby on Rails is a full-stack web framework optimized for programmer happiness and sustainable productivity. It encourages beautiful code by favoring convention over configuration.

#### rails relies on:

activesupport, actionpack, actionview, activemodel, activerecord, actionmailer, activejob, railties, bundler, sprockets-rails

## rails-deprecated\_sanitizer v1.0.3

MIT whitelisted ✓

### Deprecated sanitizer API extracted from Action View.

#### rails-deprecated\_sanitizer is required by:

rails-dom-testing

#### rails-deprecated\_sanitizer relies on:

activesupport, bundler, rake

## rails-dom-testing v1.0.6

MIT whitelisted ✓

### Dom and Selector assertions for Rails applications

This gem can compare doms and assert certain elements exists in doms using Nokogiri.

#### rails-dom-testing is required by:

rails-html-sanitizer, actionview, actionpack, actionmailer, jquery-rails

#### rails-dom-testing relies on:

nokogiri, activesupport, rails-deprecated\_sanitizer, bundler, rake, minitest

## rails-html-sanitizer v1.0.2

MIT whitelisted ✓

### This gem is responsible to sanitize HTML fragments in Rails applications.

HTML sanitization for Rails applications

#### rails-html-sanitizer is required by:

actionview, actionpack

#### rails-html-sanitizer relies on:

loofah, bundler, rake, minitest, rails-dom-testing

## railties v4.2.1

MIT whitelisted ✓

### Tools for creating, working with, and running Rails applications.

Rails internals: application bootup, plugins, generators, and rake tasks.

#### railties is required by:

coffee-rails, factory\_girl\_rails, jquery-rails, jshint, sprockets-rails, rails, rspec-rails, sass-rails, web-console

#### railties relies on:

activesupport, actionpack, rake, thor, actionview

## raindrops v0.13.0

LGPLv2.1+ whitelisted ✓

### real-time stats for preforking Rack servers

Raindrops is a real-time stats toolkit to show statistics for Rack HTTP servers. It is designed for preforking servers such as Rainbows! and Unicorn, but should support any Rack HTTP server under Ruby 2.0, 1.9, 1.8 and Rubinius on platforms supporting POSIX shared memory. It may also be used as a generic scoreboard for sharing atomic counters across multiple processes.

#### raindrops is required by:

unicorn

#### raindrops relies on:

aggregate, io-extra, posix\_mq, rack, unicorn, wrongdoc

## rake v10.4.2

MIT whitelisted ✓

### This rake is bundled with Ruby

#### rake is required by:

thread\_safe, nokogiri, rails-deprecated\_sanitizer, rails-dom-testing, loofah, rails-html-sanitizer, rack, globalid, mime-types, mail, arel, addressable, binding\_of\_caller, bourbon, bundler, columnize, xpath, capybara, launchy, carmen, cliver, execjs, coffee-script, railties, database\_cleaner, diff-lcs, docile, faraday, faraday\_middleware, figaro, hike, libv8, jshint, json-schema, kaminari, neat, poltergeist, sprockets, sprockets-rails, rspec-support, rspec-core, rspec-expectations, rspec-mocks, rspec-rails, sdock, uglifier

## rdoc v4.2.0

ruby whitelisted ✓

### This rdoc is bundled with Ruby

**rdoc is required by:**

minitest, nokogiri, loofah, mime-types, mail, arel, awrence, columnize, launchy, diff-lcs, kaminari, neat, tilt, sdoc, sqlite3, uglifier

## ref v2.0.0

MIT whitelisted ✓

### Library that implements weak, soft, and strong references in Ruby.

Library that implements weak, soft, and strong references in Ruby that work across multiple runtimes (MRI, Jruby and Rubinius). Also includes implementation of maps/hashtables that use references and a reference queue.

**ref is required by:**

therubyracer

## rspec-core v3.2.3

MIT whitelisted ✓

### rspec-core-3.2.3

BDD for Ruby. RSpec runner and example groups.

**rspec-core is required by:**

rspec-rails, rspec\_junit\_formatter

**rspec-core relies on:**

rspec-support, rake, cucumber, minitest, aruba, nokogiri, coderay, mocha, rr, flexmock

## rspec-expectations v3.2.1

MIT whitelisted ✓

### rspec-expectations-3.2.1

rspec-expectations provides a simple, readable API to express expected outcomes of a code example.

**rspec-expectations is required by:**

rspec-rails

**rspec-expectations relies on:**

rspec-support, diff-lcs, rake, cucumber, aruba, minitest

## rspec-mocks v3.2.1

MIT whitelisted ✓

### rspec-mocks-3.2.1

RSpec's 'test double' framework, with support for stubbing and mocking

**rspec-mocks is required by:**

rspec-rails

**rspec-mocks relies on:**

rspec-support, diff-lcs, rake, cucumber, aruba, minitest

## rspec-rails v3.2.3 (development, test)

MIT whitelisted ✓

### rspec-rails-3.2.3

RSpec for Rails

**rspec-rails relies on:**

activesupport, actionpack, railties, rspec-core, rspec-expectations, rspec-mocks, rspec-support, rake, cucumber, aruba, ammeter

## rspec-support v3.2.2

MIT whitelisted ✓

### rspec-support-3.2.2

Support utilities for RSpec gems

**rspec-support is required by:**

rspec-core, rspec-expectations, rspec-mocks, rspec-rails

**rspec-support relies on:**

bundler, rake

## rspec\_junit\_formatter v0.2.3 (test)

MIT whitelisted ✓

### RSpec JUnit XML formatter

RSpec results that Hudson can read.

**rspec\_junit\_formatter relies on:**

rspec-core, builder, nokogiri

## sass v3.4.14

MIT whitelisted ✓

### A powerful but elegant CSS compiler that makes CSS fun again.

Sass makes CSS fun again. Sass is an extension of CSS3, adding nested rules, variables, mixins, selector inheritance, and more. It's translated to well-formatted, standard CSS using the command line tool or a web-framework plugin.

**sass is required by:**

bourbon, neat, tilt, sprockets, sprockets-rails, sass-rails

**sass relies on:**

yard, maruku, minitest

## sass-rails v5.0.3 (default)

MIT whitelisted ✓

### Sass adapter for the Rails asset pipeline.

Sass adapter for the Rails asset pipeline.

**sass-rails relies on:**

railties, sass, sprockets-rails, sprockets, tilt, sqlite3

## sdoc v0.4.1 (doc)

MIT whitelisted ✓

### rdoc html with javascript search index.

rdoc generator html with javascript search index.

**sdoc is required by:**

json

**sdoc relies on:**

rdoc, json, bundler, rake, minitest

## simplecov v0.10.0 (test)

MIT whitelisted ✓

### Code coverage for Ruby 1.9+ with a powerful configuration library and automatic merging of coverage across test suites

Code coverage for Ruby 1.9+ with a powerful configuration library and automatic merging of coverage across test suites

**simplecov is required by:**

mime-types, factory\_girl, faraday

**simplecov relies on:**

json, simplecov-html, docile, bundler

MIT whitelisted ✓

## simplecov-html v0.10.0

### Default HTML formatter for SimpleCov code coverage tool for ruby 1.9+

Default HTML formatter for SimpleCov code coverage tool for ruby 1.9+

#### simplecov-html is required by:

simplecov

#### simplecov-html relies on:

bundler

## sprockets v2.12.4 (default)

MIT whitelisted ✓

### Rack-based asset packaging system

Sprockets is a Rack-based asset packaging system that concatenates and serves JavaScript, CoffeeScript, CSS, LESS, Sass, and SCSS.

#### sprockets is required by:

sprockets-rails, sass-rails

#### sprockets relies on:

hike, multi\_json, rack, tilt, closure-compiler, coffee-script, coffee-script-source, eco, ejs, execjs, json, rack-test, rake, sass, uglifier, yui-compressor

## sprockets-rails v2.3.1

MIT whitelisted ✓

### Sprockets Rails integration

#### sprockets-rails is required by:

rails, sass-rails, web-console

#### sprockets-rails relies on:

sprockets, actionpack, activesupport, railties, rake, sass, uglifier

## sqlite3 v1.3.10 (development, test)

New BSD whitelisted ✓

### This module allows Ruby programs to interface with the SQLite3 database engine (<http://www.sqlite.org>)

This module allows Ruby programs to interface with the SQLite3 database engine (<http://www.sqlite.org>). You must have the SQLite engine installed in order to build this module. Note that this module is only compatible with SQLite 3.6.16 or newer.

#### sqlite3 is required by:

factory\_girl, sass-rails

#### sqlite3 relies on:

minitest, rdoc, rake-compiler, mini\_portile, hoe-bundler, hoe

## therubyracer v0.12.2 (default)

MIT whitelisted ✓

### Embed the V8 JavaScript interpreter into Ruby

Call JavaScript code and manipulate JavaScript objects from Ruby. Call Ruby code and manipulate Ruby objects from JavaScript.

#### therubyracer is required by:

jshint

#### therubyracer relies on:

ref, libv8

## thor v0.19.1

MIT whitelisted ✓

Thor is a toolkit for building powerful command-line interfaces.



Thor is a toolkit for building powerful command-line interfaces.

**thor is required by:**

bourbon, railties, figaro, jquery-rails

**thor relies on:**

bundler

## thread\_safe v0.3.5

Apache 2.0 whitelisted ✓

### A collection of data structures and utilities to make thread-safe programming in Ruby easier

Thread-safe collections and utilities for Ruby

**thread\_safe is required by:**

tzinfo, activesupport

**thread\_safe relies on:**

atomic, rake, minitest

## tilt v1.4.1

MIT whitelisted ✓

### Generic interface to multiple Ruby template engines

Generic interface to multiple Ruby template engines

**tilt is required by:**

sprockets, sass-rails

**tilt relies on:**

asciidoctor, RedCloth, bluecloth, builder, coffee-script, contest, creole, erubis, haml, kramdown, less, liquid, markaby, maruku, nokogiri, radius, rdiscount, rdoc, redcarpet, sass, wikicloth, yajl-ruby, rdoc

## tzinfo v1.2.2

MIT whitelisted ✓

### Daylight savings aware timezone library

TZInfo provides daylight savings aware transformations between times in different time zones.

**tzinfo is required by:**

activesupport, database\_cleaner, kaminari

**tzinfo relies on:**

thread\_safe

## uglifyer v2.7.1 (default)

MIT whitelisted ✓

### Ruby wrapper for UglifyJS JavaScript compressor

Uglifier minifies JavaScript files by wrapping UglifyJS to be accessible in Ruby

**uglifyer is required by:**

sprockets, sprockets-rails

**uglifyer relies on:**

execjs, json, rspec, rake, bundler, rdoc, source\_map

## unicorn v4.9.0 (default)

GPLv2+, Ruby 1.8 manually approved ✓

2015-12-03 —

### Rack HTTP server for fast clients and Unix

Unicorn is an HTTP server for Rack applications designed to only serve fast clients on low-latency, high-bandwidth connections and take advantage of features in Unix/Linux-like kernels. Slow clients should only be served by placing a reverse proxy capable of fully buffering both the request and response in between Unicorn and slow clients.

**unicorn is required by:**

raindrops

**unicorn relies on:**

rack, kgio, raindrops, test-unit, olddoc

**vcr** v2.9.3 (development, test)

MIT whitelisted ✓

**Record your test suite's HTTP interactions and replay them during future test runs for fast, deterministic, accurate tests.**

VCR provides a simple API to record and replay your test suite's HTTP interactions. It works with a variety of HTTP client libraries, HTTP stubbing libraries and testing frameworks.

**web-console** v2.1.2 (development, test)

MIT whitelisted ✓

**A debugging tool for your Ruby on Rails applications.**

**web-console relies on:**

railties, activemodel, sprockets-rails, binding\_of\_caller, actionmailer, activerecord

**websocket-driver** v0.5.4

MIT whitelisted ✓

**WebSocket protocol handler with pluggable I/O**

**websocket-driver is required by:**

poltergeist

**websocket-driver relies on:**

websocket-extensions, eventmachine, permessage\_deflate, rake-compiler, rspec

**websocket-extensions** v0.1.2

MIT whitelisted ✓

**Generic extension manager for WebSocket connections**

**websocket-extensions is required by:**

websocket-driver

**websocket-extensions relies on:**

rspec

**xpath** v2.0.0

MIT whitelisted ✓

**Generate XPath expressions from Ruby**

XPath is a Ruby DSL for generating XPath expressions

**xpath is required by:**

capbara

**xpath relies on:**

nokogiri, rspec, yard, rake