

OpenWhisk Package Specification

Version 0.8, Working Draft 07

Notational Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#).

The OpenWhisk specification is licensed under [The Apache License, Version 2.0](#).

Introduction

OpenWhisk™ is an open source, distributed Serverless computing project. Specifically, it is able to execute application logic (*Actions*) in response to events (*Triggers*) from external sources (*Feeds*) governed by simple conditional logic (*Rules*) around the event data.

It provides a programming model for registering and managing *Actions*, *Triggers* and *Rules* supported by a REST-based Command Line Interface (CLI) along with tooling to support packaging and catalog services.

The project includes a catalog of built-in system and utility *Actions* and *Feeds*, along with a robust set of samples that demonstrate how to integrate OpenWhisk with various external service providers (e.g., GitHub, Slack, etc.) along with several platform and run-time Software Development Kits (SDKs).

The code for the Actions, along with any support services implementing *Feeds*, are packaged according to this specification to be compatible with the OpenWhisk catalog and its tooling. It also serves as a means for architects and developers to model OpenWhisk package Actions as part of full, event-driven services and applications providing the necessary information for artifact and data type validation along with package management operations.

Compatibility

This specification is intended to be compatible with the following specifications:

- *OpenWhisk API which is defined as an OpenAPI document:*
 - <https://raw.githubusercontent.com/openwhisk/openwhisk/master/core/controller/src/main/resources/whiskswagger.json>
- *OpenAPI Specification when defining REST APIs and parameters:*
 - <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/2.0.md>

36 Revision History

Version	Date	Notes
0.8.1	2016-11-03	Initial public point draft, Working Draft 01
0.8.2	2016-12-12	Working Draft 02, Add. Use cases, examples
0.8.3	2017-02-02	Working Draft 03, Add use cases, examples, \$ notation
0.8.4	2017-04-18	Working Draft 04, Support JSON parameter type; Clarify use of Parameter single-line grammar and inferred types. Add support for API Gateway mappings. Add support for Web Actions
0.8.5	2017-04-21	Add support for “dependencies”, that is allow automatic deployment of other OpenWhisk packages (from GitHub) that the current package declares as a dependency.
0.8.6	2017-07-25	Clarified requirements for \$ dollar notation. Updated conceptual Manifest/Deployment File processing images.
0.8.7	2017-08-24	Added explicit Application entity and grammar. Added API listing to Package entity. Cleaned up pseudo-grammar which contained various uses of credentials in places not intended. Fixed Polygon Tracking example (indentation incorrect).

37

38	Table of Contents
39	<i>Introduction</i> 1
40	Compatibility 1
41	Revision History 2
42	<i>Programming Model</i> 4
43	OpenWhisk Entities 4
44	<i>Package processing</i> 5
45	Conceptual Package creation and publishing 5
46	Conceptual tooling integration and deployment 6
47	Conceptual representation 7
48	Composition 7
49	Namespacing 7
50	Entity Names 8
51	Cardinality 8
52	A single trigger can be configured to invoke multiple Actions.Definitions 8
53	<i>Specification</i> 9
54	YAML Types 9
55	OpenWhisk Types 10
56	Schema 11
57	Extended Schema 26
58	Package Artifacts 30
59	Normative References 33
60	<i>Non-normative References</i> 33
61	Scenarios and Use cases 34
62	<i>Usage Scenarios</i> 34
63	<i>Schema Use Cases</i> 35
64	“Hello world” 35
65	Basic Trigger and Rule 36
66	Github feed 37
67	Github feed advanced 38
68	RSS Package 39
69	Polygon Tracking 40
70	MQTT Package (tailored for Watson IoT) 43
71	Check deposit processing with optical character recognition 45
72	Event Sources 50
73	<i>Curated Feeds</i> 50
74	Alarms 50
75	Cloudant 51
76	<i>Public Sources</i> 51
77	GitHub WebHook 51
78	Other Considerations 52
79	<i>Tooling interaction</i> 52
80	Using package manifest directly from GitHub 52
81	Using package manifest in archive (e.g., ZIP) file 52
82	<i>Simplification of WebHook Integration</i> 52
83	<i>Enablement of Debugging for DevOps</i> 52

84 **Programming Model**

85 **OpenWhisk Entities**

86 OpenWhisk uses the following entities to describe its programming model:

87 **Action**

88 A stateless, relatively short-running function invoked as an event handler.

89 *Note: Typically, an Action's run time is on the order of seconds or even milliseconds, but usually*
90 *well under the defaulted maximum of 5 minutes.*

91 **Trigger**

92 The name for a class of events. Triggers represent the events (and their data) themselves without
93 any concept of how they were generated.

94 **Rule**

95 A mapping from a Trigger to an Action which may contain simple conditional logic. OpenWhisk
96 evaluates incoming events (that belong to a Trigger) and invokes the assigned Action (event
97 handler).

98
99 *Note: Rule conditional logic can be described relative to the event data and the target Action*
100 *input parameters.*

101
102 *Note: In a pub-sub system, a trigger could be viewed as a message topic.*

103 **Event Source**

104 An Event Source is the descriptor (edge) for an Event Producer (or provider). It describes the
105 Event Format(s) produced, as well as any configuration and subscription capabilities.

106 **Feed**

107 A Feed is an optional service that allows control operations (e.g., configure, start, stop, pause,
108 resume, etc.) and configuration of Events coming from an Event Source.

109
110 *Note: The terms Feed and Trigger are often used interchangeably conversationally (since they*
111 *both represent a class of events); however, we make this distinction.*

112 **Package**

113 A named, shared collection of Actions and Feeds. The goal of this specification is to describe
114 OpenWhisk packages and their component entities and resources to enable an open-ecosystem.

115
116 *Note: Not all actions must belong to packages.*
117 *Note: Designed as a first-class entity within the OpenWhisk platform to be used by tooling such*
118 *as catalogs (repositories), associated package managers, installers, etc.*

119


Package processing

This document defines two file artifacts that are used to deploy Packages to a target OpenWhisk platform; these include:

- **Package Manifest file**: Contains the Package definition along with any included Action, Trigger or Rule definitions that comprise the package. This file includes the schema of input and output data to each entity for validation purposes.
- **Deployment file**: Contains the values and bindings used configure a Package to a target OpenWhisk platform provider's environment and supply input parameter values for Packages, Actions and Triggers. This can include Namespace bindings, security and policy information.

Conceptual Package creation and publishing


The following diagram illustrates how a developer would create OpenWhisk code artifacts and associate a Package Manifest file that describes them for deployment and reuse.



Conceptual tooling integration and deployment

The following diagram illustrates how Package manifests can be leveraged by developer tooling to integrate OpenWhisk Serverless functions.


1. Developer **searches** and **discovers** OpenWhisk packages described by the **Package Manifest** in one or more Catalogs, that can:
 - Help analyze, augment and annotate application information and data.
 - Add value added functionality to a base application or workflow.
2. Imports Open **Package Manifest Files** and related code and artifacts into development tooling, including:
 - Project and Application (source code) Repositories
 - Integrated Development Environments (IDEs)
 - Cloud-based design, workflow and application workspaces.
3. Creates OpenWhisk **Deployment Files** for one or more target OpenWhisk enabled Clouds, with
 - Parameter values for desired target environment
 - Appropriate Credentials and configurations for chosen Event Sources and Feeds.
4. Deploys **Packages** (i.e., Actions, Triggers, Feeds, etc.) to OpenWhisk enabled Clouds, using,
 - **Package Manifest** and **Deployment File(s)**.



Notes

- Deployment Files are optional. Deployment can be fully accomplished with simply the Manifest File.

139 Conceptual representation



140

141 Composition

142 Action Sequence

143 An Action that is a sequenced composition of 2 or more existing Actions. The Action Sequence
144 can be viewed as a named pipe where OpenWhisk can automatically take the output of a first
145 Action 'A' in a declared sequence and provides it as input to the next Action 'B' in the sequence
146 and so on until the sequence completes.

147

148 *Note: This composition technique allows the reuse of existing action implementations treating*
149 *them as "building blocks" for other Actions.*

150 Namespacing

151 Every OpenWhisk entity (i.e., Actions, Feeds, Triggers), including packages, belongs in a
152 namespace.

153 The fully qualified name of any entity has the format:

154 /`<namespaceName>`[/`<packageName>`]/`<entityName>`

155

156 The namespace is typically provided at bind-time by the user deploying the package to their
157 chosen OpenWhisk platform provider.

158

159 *Note: The `/whisk.system` namespace is reserved for entities that are distributed with the*
160 *OpenWhisk system.*

161 **Entity Names**

162 The names of all entities, including actions, triggers, rules, packages, and namespaces, are a
163 sequence of characters that follow the following format:

- 164 • The first character SHALL be an alphanumeric character, a digit, or an underscore.
- 165 • The subsequent characters MAY be alphanumeric, digits, spaces, or any of the following:
166 `_`, `@`, `.`, `-`
- 167 • The last character SHALL NOT be a space.

168 More precisely, a name must match the following regular expression (expressed with Java
169 metacharacter syntax):

170 `\A([\w]|[\w][\w@.-]*[\w@.-])+\z`

171 **Cardinality**

172 *Trigger to Action*

173 A single trigger can be configured to invoke multiple Actions.**Definitions**

174 *Activation*

175 An invocation or “run” of an action results in an activation record that is identified by a unique
176 activation ID. The term Activation is short-hand for the creation of this record and its
177 information.

178 *Repository*

179 A location that provides storage for sets of files, as well as the history of changes made to those
180 files.

181 *Project*

182 A description of a software application which enables management of its design,
183 implementation, source control, monitoring and testing.

184 *Application*

185 A computer program designed to perform a group of coordinated functions, tasks, or activities
186 to achieve some result or user benefit.

187

[Cloud] Service

Any resource, including a functional task, that is provided over the Internet. This includes delivery models such as *Platform as a Service* (PaaS), *Infrastructure as a Service* (IaaS), as well as *Serverless*.

Specification

This specification utilizes the [YAML language](#), a superset of JSON, which supports key features for packaging descriptors and configuration information such as built-in data types, complex data types, anchors (relational information), files, comments and can embed other data formats such as JSON and XML easily.

YAML Types

Many of the types we use in this profile are *built-in* types from the [YAML 1.2 specification](#) (i.e., those identified by the “tag:yaml.org,2002” version tag).

The following table declares the valid YAML type URIs and aliases that SHALL be used when defining parameters or properties within an OpenWhisk package manifest:

Type Name	Type URI	Notes
string	tag:yaml.org,2002:str (default)	Default type if no type provided
integer	tag:yaml.org,2002:int	Signed. Includes large integers (i.e., long type)
float	tag:yaml.org,2002:float	Signed. Includes large floating point values (i.e., double type)
boolean	tag:yaml.org,2002:bool	This specification uses lowercase ‘true’ and lowercase ‘false’
timestamp	tag:yaml.org,2002:timestamp (see YAML-TS-1.1)	ISO 8601 compatible.
null	tag:yaml.org,2002:null	Different meaning than an empty string, map, list, etc.
version	tag:maven.apache.org:version (see Maven version)	Typically found in modern tooling (i.e., “package@version” or “package:version” format).
string256	long length strings (e.g., descriptions)	A string type limited to 256 characters.
string64	medium length strings (e.g., abstracts, hover text)	A string type limited to 64 characters.
string16	short length strings (e.g., small form-factor list displays)	A string type limited to 16 characters.

Requirements

- The ‘string’ type SHALL be the default type when not specified on a parameter or property declaration.
- All ‘boolean’ values SHALL be lowercased (i.e., ‘true’ or ‘false’).

OpenWhisk Types

In addition to the YAML built-in types, OpenWhisk supports the types listed in the table below. A complete description of each of these types is provided below.

Type Name	Description	Notes
json	The parameter value represents a JavaScript Object Notation (JSON) data object.	The deploy tool will validate the corresponding parameter value against JSON schema. Note: The implied schema for JSON is the JSON Schema (see http://json-schema.org/).
scalar-unit	Convenience type for declaring common scalars that have an associated unit. For example, "10 msec.", "2 Gb", etc.)	See description below.
schema	The parameter itself is an OpenAPI Specification v2.0 Schema Object (in YAML format) with self-defining schema.	The schema declaration follows the OpenAPI v2.0 specification for Schema Objects (YAML format).. Specifically, see https://github.com/OAI/OpenAPI-Specification/blob/master/versions/2.0.md#schemaObject
object	The parameter itself is an object with the associated defined Parameters (schemas).	Parameters of this type would include a declaration of its constituting Parameter schema.

scalar-unit types

Scalar-unit types can be used to define scalar values along with a unit from the list of recognized units (a subset of GNU units) provided below.

Grammar

```
<scalar> <unit>
```

In the above grammar, the pseudo values that appear in angle brackets have the following meaning:

- `scalar`: is a required scalar value (e.g., integer).
- `unit`: is a required unit value. The unit value **MUST** be type-compatible with the scalar value.

Requirements

- Whitespace: any number of spaces (including zero or none) **SHALL** be allowed between the scalar value and the unit value.
- It **SHALL** be considered an error if either the scalar or unit portion is missing on a property or attribute declaration derived from any scalar-unit type.

226 *Recognized units for sizes (i.e., scalar-unit.size)*

Unit	Description
B	byte
kB	kilobyte (1000 bytes)
MB	megabyte (1000000 bytes)
GB	gigabyte (1000000000 bytes)
TB	terabyte (1000000000000 bytes)

227 *Recognized units for times (i.e., scalar-unit.time)*

Unit	Description
d	days
h	hours
m	minutes
s	seconds
ms	milliseconds
us	microseconds

228 *Object type example*

229 The Object type allows for complex objects to be declared as parameters with an optional validateable
230 schema.

```
inputs:
  person:
    type: object
    parameters:
```

231

232 **Schema**

233 This section defines all the essential schema used to describe OpenWhisk packages within a
234 manifest.

235 *General Requirements*

- 236
- All field names in this specification SHALL be case sensitive.

237 *map schema*

238 The Map schema is used to define maps of key values within OpenWhisk entities.

239 *Single-line grammar*

```
{ <key_1>: <value_1>, ..., <key_n>: <value_n> }
```

240 *Multi-line grammar*

```
# Where 'key_n' is a type <string> and 'value_n' is type <any>.
<key_1>: <value_1>
...
<key_n>: <value_n>
```

241 *Examples*

242 *Single-line*

```
alert_levels: { "high": "red", "medium": "yellow", "low": green }
```

243 *Multi-line*

```
alert_levels:
  "high": "red"
  "medium": "yellow"
  "low": green
```

244

245 *Parameter schema*

246 The Parameter schema is used to define input and/or output data to be used by OpenWhisk
247 entities for the purposes of validation.

248 *Fields*

Key Name	Required	Value Type	Default	Description
type	no	<any>	string	Optional valid type name or the parameter's value for validation purposes. By default, the type is string .
description	no	string256	N/A	Optional description of the Parameter.
value	no	<any>	N/A	The optional user supplied value for the parameter. Note: this is not the default value, but an explicit declaration which allows simple usage of the Manifest file without a Deployment file..
required	no	boolean	true	Optional indicator to declare the parameter as required (i.e., true) or optional (i.e., false).
default	no	<any>	N/A	Optional default value for the optional parameters. This value MUST be type compatible with the value declared on the parameter's type field.
status	no	string	supported	Optional status of the parameter (e.g., deprecated , experimental). By default a parameter is without a declared status is considered supported.
schema	no	<schema>	N/A	The optional schema if the 'type' key has the value 'schema'. The value would include a Schema Object (in YAML) as defined by the OpenAPI Specification v2.0 . This object is based upon the JSON Schema Specification .

Key Name	Required	Value Type	Default	Description
properties	no	<list of Parameter schema>	N/A	The optional properties if the 'type' key has the value 'object'. Its value is a listing of Parameter schema from this specification.

Requirements

- The "schema" key's value MUST be compatible with the value provided on both the "type" and "value" keys; otherwise, it is considered an error.

Notes

- The "type" key acknowledges some popular schema (e.g., JSON) to use when validating the value of the parameter. In the future additional (schema) types may be added for convenience.

Grammar

Single-line

```
<parameterName>: <YAML type> | scalar-unit | json
```

- Where <YAML type> is inferred to be a YAML type as shown in the YAML Types section above (e.g., string, integer, float, boolean, etc.).
- If you wish the parser to validate against a different schema, then the multi-line grammar MUST be used where the value would be supplied on the keyname "value" and the type (e.g., json) and/or schema (e.g., OpenAPI) can be supplied

Multi-line

```
<parameterName>:
  type: <any>
  description: <string>
  required: <boolean>
  default: <any>
  status: <string>
  schema: <OpenAPI Schema Object>
```

Status values

Status Value	Description
supported (default)	Indicates the parameter is supported. This is the implied default status value for all parameters.
experimental	Indicates the parameter MAY be removed or changed in future versions.
deprecated	Indicates the parameter is no longer supported in the current version and MAY be ignored.

Shared schema for all Entities

The entity schema contains fields that are common to all OpenWhisk entities (e.g., Actions, Triggers, Rules, etc.).

268 *Fields*

Key Name	Required	Value Type	Default	Description
version	yes	version	N/A	The required version for the Entity.
description	no	string256	N/A	The optional description for the Entity.
displayName	no	string16	N/A	This is the optional name that will be displayed on small form-factor devices.
annotations	no	TBD	N/A	The optional annotations for the Entity.
inputs	no	list of parameter	N/A	The optional ordered list inputs to the Entity.
outputs	no	list of parameter	N/A	The optional outputs from the Entity.

269 *Grammar*

```
version: <version>
description: <string>
annotations: <map of <string>>
inputs: <list of <parameter>>
outputs: <list of <parameter>>
```

270 *Requirements*

- Version values for all entities SHALL be provided.
- Non-required fields MAY be stored as “annotations” within the OpenWhisk framework after they have been used for processing.
- Description string values SHALL be limited to 256 characters.
- DisplayName string values SHALL be limited to 16 characters.
- The lists of inputs and outputs MAY also be described as ordered lists (using the YAML ‘-‘ dash convention).
- Annotations MAY be ignored by target consumers of the Manifest file as they are considered data non-essential to the deployment of management of OpenWhisk entities themselves.
 - Target consumers MAY preserve (persist) these values, but are not required to.
- For any OpenWhisk Entity, the maximum size of all Annotations SHALL be (TBD) characters.

282 *Notes*

- Input and output parameters are implemented as JSON Objects within the OpenWhisk framework.
- Several, non-normative Annotation keynames and allowed values for (principally for User Interface (UI) design) may be defined below for optional usage.

286 *Action entity*

287 The Action entity schema contains the necessary information to deploy an OpenWhisk function
288 and define its deployment configurations, inputs and outputs.

Key Name	Required	Value Type	Default	Description
function	yes	string	N/A	Required source location (path inclusive) of the Action code either <ul style="list-style-type: none"> • Relative to the Package manifest file. • Relative to the specified Repository.
runtime	no	string	N/A	The required runtime name (and optional version) that the Action code requires for an execution environment. <i>Note: May be optional if tooling allowed to make assumptions about file extensions.</i>
limits	no	map of <limit keys and values>	N/A	Optional map of limit keys and their values. <i>See section “Valid limit keys” below for a listing of recognized keys and values.</i>
feed	no	boolean	false	Optional indicator that the Action supports the required parameters (and operations) to be run as a Feed Action.
web-export	no	boolean	false	Optionally, turns the Action into a “ web actions ” causing it to return HTTP content without use of an API Gateway.

290 *Requirements*

- 291 • The Action name (i.e., <actionName> MUST be less than or equal to 256 characters.
- 292 • The Action entity schema includes all general [Entity Schema](#) fields in addition to any fields declared
- 293 above.
- 294 • Supplying a runtime name without a version indicates that OpenWhisk SHOULD use the most
- 295 current version.
- 296 • Supplying a runtime *major version* without a *minor version* (et al.) indicates OpenWhisk SHOULD use
- 297 the most current *minor version*.
- 298 • Unrecognized limit keys (and their values) SHALL be ignored.
- 299 • Invalid values for known limit keys SHALL result in an error.
- 300 • If the Feed is a Feed Action (i.e., the feed key’s value is set to true), it MUST support the following
- 301 parameters:
- 302 • **lifecycleEvent**: one of 'CREATE', 'DELETE', 'PAUSE', or 'UNPAUSE'
- 303 o These operation names MAY be supplied in lowercase (i.e., ‘create’, ‘delete’, ‘pause’, etc.).
- 304 • **triggerName**: the fully-qualified name of the trigger which contains events produced from this
- 305 feed.
- 306 • **authKey**: the Basic auth. credentials of the OpenWhisk user who owns the trigger just
- 307 mentioned.

308 *Notes*

- 309 • The maximum code size for an Action currently must be less than 48 MB.
- 310 • The maximum payload size for an Action (i.e., POST content length or size) currently must be less
- 311 than 1 MB.
- 312 • The maximum parameter size for an Action currently must be less than 1 MB.

Valid Runtime names

The following runtime values are currently supported by the OpenWhisk platform.

Each of these runtimes also include additional built-in packages (or libraries) that have been determined be useful for Actions surveyed and tested by the OpenWhisk platform. These packages may vary by OpenWhisk release; details on runtimes and their package conventions and default package (or libraries) here:

Runtime name	Supported versions	Default	Description
nodejs	nodejs@6, nodejs@5	nodejs@6	Node.js runtime.
java	java@8	java@8	Java language runtime.
python	python@2.7	python@2.7	Python language runtime.
swift	swift@3, swift@2	swift@3	Swift language runtime.
language:default	N/A	N/A	Permit the OpenWhisk platform to select the correct default language runtime.

Please note, if no value for runtime is supplied, the value 'language:default' will be assumed.

Recognized File extensions

Although it is best practice to provide a runtime value when declaring an Action, it is not required. In those cases, that a runtime is not provided, the package tooling will attempt to derive the correct runtime based upon the the file extension for the Action's function (source code file). The following file extensions are recognized and will be run on the latest version of corresponding Runtime listed below:

File extension	Runtime used	Description
.js	nodejs	Node.js runtime.
.java	java	Java language runtime.
.py	python	Python language runtime.
.swift	swift	Swift language runtime.

Valid Limit keys

Limit Keyname	Allowed values	Default value	Valid Range	Description
timeout	scalar-unit.time	60000 ms	[100 ms, 300000 ms]	The per-invocation Action timeout. Default unit is assumed to be milliseconds (ms).
memorySize	scalar-unit.size	256 MB	[128 MB, 512 MB]	The per-Action memory. Default unit is assumed to be in megabytes (MB).
logSize	scalar-unit.size	10 MB	[0 MB, 10 MB]	The action log size. Default unit is assumed to be in megabytes (MB).

Limit Keyname	Allowed values	Default value	Valid Range	Description
concurrentActivations	integer	1000	See description	The maximum number of concurrent Action activations allowed (per-namespace). <i>Note: This value is not changeable via APIs at this time.</i>
userInvocationRate	integer	5000	See description	The maximum number of Action invocations allowed per user, per minute. <i>Note: This value is not changeable via APIs at this time.</i>
codeSize	scalar-unit.size	48 MB	See description	The maximum size of the Action code. <i>Note: This value is not changeable via APIs at this time.</i>
parameterSize	scalar-unit.size	1 MB	See description	The maximum size <i>Note: This value is not changeable via APIs at this time.</i>

Notes

The default values and ranges for limit configurations reflect the defaults for the OpenWhisk platform (open source code). These values may be changed over time to reflect the open source community consensus.

Web Actions

OpenWhisk can turn any Action into a “web action” causing it to return HTTP content without use of an API Gateway. Simply supply a supported “type” extension to indicate which content type is to be returned and identified in the HTTP header (e.g., `.json`, `.html`, `.text` or `.http`).

Return values from the Action’s function are used to construct the HTTP response. The following response parameters are supported in the response object.

1. `headers`: a JSON object where the keys are header-names and the values are string values for those headers (default is no headers).
2. `code`: a valid HTTP status code (default is 200 OK).
3. `body`: a string which is either plain text or a base64 encoded string (for binary data).

Grammar

```
# Note: the optional [.<type>] grammar is used for naming Web Actions.
<actionName>[.<type>]:
  <Entity schema> # Common to all OpenWhisk Entities
  function: <string>
  runtime: <name>[@<[range of ]version>]
  limits:
    <list of limit key-values>
```

```
feed: <boolean> # default: false
```

345 *Example*

```
my_awesome_action:
  version: 1.0
  description: An awesome action written for node.js
  function: src/js/action.js
  runtime: nodejs@>0.12<6.0
  inputs:
    not_awesome_input_value:
      description: Some input string that is boring
      type: string
  outputs:
    awesome_output_value:
      description: Impressive output string
      type: string
  limits:
    memorySize: 512 kB
    logSize: 5 MB
```

346 *Trigger entity*

347 The Trigger entity schema contains the necessary information to describe the stream of events
348 that it represents. For more information see: “[Creating Triggers and Rules](#)”.

349 *Fields*

Key Name	Required	Value Type	Default	Description
feed	no	string	N/A	The optional name of the Feed associated with the Trigger.
events	no	list of Event	N/A	The optional list of valid Event schema the trigger supports. OpenWhisk would validate incoming Event data for conformance against any Event schema declared under this key. Note: This feature is not supported at this time. This is viewed as a possible feature that may be implemented along with configurable options for handling of invalid events.

350

351 *Requirements*

- 352
- The Trigger name (i.e., <triggerName> MUST be less than or equal to 256 characters.
 - The Trigger entity schema includes all general [Entity Schema](#) fields in addition to any fields declared above.
- 353
- 354

355 *Notes*

- 356
- The Trigger entity within the OpenWhisk programming model is considered outside the scope of the Package (although there are discussions about changing this in the future). This means that Trigger and API information will not be returned when using the OpenWhisk Package API:
- 357
- 358
- 359
- `wsk package list <package name>`
- 360
- However, it may be obtained using the Trigger API:

361 • wsk trigger list -v

362 *Grammar*

```
<triggerName>:
  <Entity schema> # Common to all OpenWhisk Entities
  feed: my_feed
```

363 *Rule entity*

364 The Rule entity schema contains the information necessary to associates one trigger with one
365 action, with every firing of the trigger causing the corresponding action to be invoked with the
366 trigger event as input. For more information see: “[Creating Triggers and Rules](#)”.

367 *Fields*

Key Name	Required	Value Type	Default	Description
trigger	yes	string	N/A	Required name of the Trigger the Rule applies to.
action	yes	string	N/A	Required name of the Action the Rule applies to.
rule	no	regex	true	The optional regular expression that determines if the Action is fired. Note: In this version of the specification, only the expression “true” is currently supported.

368 *Requirements*

- 369 • The Rule name (i.e., <ruleName>) MUST be less than or equal to 256 characters.
- 370 • The Rule entity schema includes all general [Entity Schema](#) fields in addition to any fields declared
- 371 above.

372 *Grammar*

```
<ruleName>:
  <Entity schema> # Common to all OpenWhisk Entities
  trigger: <string>
  action: <string>
  rule: <regex> # “true” supported at this time
```

373 *Example*

```
my_rule:
  desription: Enable events for my Action
  trigger: my_trigger
  action: my_action
```

374 [Composition entity](#)

375 The Composition entity schema contains information to declare compositions of OpenWhisk
376 Actions. Currently, this includes Action Sequences where Actions can be composed of two or
377 more existing Actions.

378 [Fields](#)

Key Name	Required	Value Type	Default	Description
type	no	string	sequence	The optional type of Action composition. <i>Note: currently only 'sequence' is supported.</i>
inputs	no	list of parameter	N/A	The optional list of parameters for the Action composition (e.g., Action Sequence).
sequence	no	ordered list of Action (names)	N/A	The optional expression that describes the connections between the Actions that comprise the Action sequence composition.
parameterMappings	no	TBD	N/A	The optional expression that describes the mappings of parameter (names and values) between the outputs of one Action to the inputs of another Action. Note: Currently, mappings are not supported and JSON objects are passed between each Action in a sequence. At this time, it is assumed that the Actions in a sequence are designed to work together with no output to input mappings being performed by the OpenWhisk platform.

379 [Requirements](#)

- 380 • The Composition name (i.e., <compositionName> MUST be less than or equal to 256 characters.
- 381 • The Composition entity schema includes all general [Entity Schema](#) fields in addition to any fields
- 382 declared above.

383 [Grammar](#)

```
<compositionName>:  
  <Entity schema> # Common to all OpenWhisk Entities  
  type: <string>  
  inputs: <list of parameters>  
  sequence:  
    - <order list of action names>  
  parameterMappings:  
    # TBD. This is a future use case.
```

384 [Example](#)

```
my_action_sequence:  
  type: sequence  
  sequence:  
    - action_1  
    - action_2
```

```

- action_3
inputs:
  simple_input_string: string
outputs:
  annotated_output_string: string

```

Feed entity

The OpenWhisk Feed entity schema contains the information necessary to reference a configurable service that works with an existing network accessible service to produce events on its behalf thereby acting as an Event Source.

These are standalone services unto themselves which the OpenWhisk platform does not currently deploy and run from an OpenWhisk Package. At this time, the Package Manifest simply provides the information to access, configure and manage (via lifecycle operations) the Feed service that is already running elsewhere.

Fields

Key Name	Required	Value Type	Default	Description
location	no	string	N/A	The URL for the Feed service which can be used by the OpenWhisk platform or registration and configuration.
credential	no	string	N/A	Contains either: <ul style="list-style-type: none"> A credential string. The optional name of a credential (e.g., token) that must be used to access the Feed service. Note: this would be defined elsewhere, perhaps as an input parameter to the Package.
operations	no	list of operations	N/A	The list of operations (i.e., APIs) the Feed supports on the URL provided described, by default, using the OpenAPI (f.k.a. "Swagger") specification schema.
operation_type	no	openwhisk openapi@<version>	openwhisk	The specification format for the operation definitions.
action	no	string	N/A	The optional name of the Action if this is a Feed Action, that is, the Feed service implementation is an OpenWhisk Action.

Requirements

- The Feed name (i.e., <FeedName> MUST be less than or equal to 256 characters.
- The Feed entity schema includes all general [Entity Schema](#) fields in addition to any fields declared above.
- If the action field is set, the corresponding Action definition and function (code) MUST be a valid Feed Action.
- The location and credential SHOULD be supplied if the Feed is not a Feed action from the Deployment File.
- Operation names in manifests MAY be lower or upper cased (e.g., "create" or "CREATE").

404 *Grammar*

```
<feedName>:
  <Entity schema> # Common to all OpenWhisk Entities
  location: <string>
  credential: <Credential>
  operations:
    <list of operations>
  action: <string>
```

405 *Example*

406 The following example shows the mandatory operations for Feed Actions.

407

```
my_feed:
  description: A simple event feed
  location: https://my.company.com/services/eventHub
  credential: my_credential
  operations:
    # Note: operation names in manifests MAY be lower or upper cased.
    create | CREATE:
      inputs:
        <parameters>
    delete | DELETE:
      inputs:
        <parameters>
    pause | PAUSE:
      inputs:
        <parameters>
    unpause | UNPAUSE:
      inputs:
        <parameters>
    # Additional, optional operations
    ...
```

408 *Discussion*

409 For a description of types of Feeds and why they exist, please see
410 <https://github.com/openwhisk/openwhisk/blob/master/docs/feeds.md>.

411 *Feed Actions*

412 OpenWhisk supports an open API, where any user can expose an event producer service as a
413 **feed** in a **package**. This section describes architectural and implementation options for providing
414 your own feed.

415 *Feed actions and Lifecycle Operations*

416 The *feed action* is a normal OpenWhisk *action*, but it should accept the following parameters:

- 417 • **lifecycleEvent**: one of 'CREATE', 'DELETE', 'PAUSE', or 'UNPAUSE'
- 418 • **triggerName**: the fully-qualified name of the trigger which contains events produced from this feed.
- 419 • **authKey**: the Basic auth. credentials of the OpenWhisk user who owns the trigger just mentioned

420 The feed action can also accept any other parameters it needs to manage the feed. For example,
421 the Cloudant changes feed action expects to receive parameters including 'dbname', 'username',
422 etc.

423 *API entity*

424 This entity allows manifests to link Actions to be made available as HTTP-based API endpoints
425 as supported by the API Gateway service of OpenWhisk.

426 This entity declaration is intended to provide grammar for the experimental API (*see*
427 <https://github.com/apache/incubator-openwhisk/blob/master/docs/apigateway.md> and shown
428 using a "book club" example:

429 *Example*

```
$ wsk api create -n "Book Club" /club /books get getBooks
$ wsk api create /club /books post postBooks
$ wsk api create /club /books put putBooks
$ wsk api create /club /books delete deleteBooks
```

430 the above would translate to the following grammars in the pkg. spec. to a new-top level
431 keyname "apis" in the manifest:

432 *Full Grammar*

```
apis:  # new top-level key for defining groups of named APIs
  <API name>:  # descriptive name
    <description>: <string>  # optional, description
    basepath: <string>  # optional, shared basepath
    path: <string>  # optional, shared path
    actions:
      <action name>:
        verb: get | post | put | delete
      ...
```

433 *Example: Full Grammar*

```
apis:
  book-club:
    description: Book Club
    basepath: /club
    path: /books
    actions:
      getBooks:
        verb: get
      postBooks:
        verb: post
      putBooks:
        verb: put
      deleteBooks:
        verb: delete
```

434 *Simple Grammar*

```
apis:
  <API name>:                # descriptive name
    description: <string>    # optional, description
    <basepath>:              # shared basepath
      <path>:
        <action name>: <verb>
        ...
      ...
```

435 *Note*

- 436 • The ‘basepath’ and ‘path’ are required in Simple Grammar; whereas these are optional
437 components in the full grammar.

438 *Example: Simplified Grammar*

439 A somewhat simplified grammar is also supported that allows single-line definition of Actions
440 (names) along with their HTTP verbs.

```
apis:
  book-club:
    club:
      books:
        getBooks: get
        postBooks: post
        putBooks: put
        deleteBooks: delete
      members:
        listMembers: get
```

442 *Requirements*

- 443 • The API entity’s name (i.e., <API Name>) MUST be less than or equal to 256 characters.

444 *Notes*

- 445 • The API entity within the OpenWhisk programming model is considered outside the scope of the
446 Package. This means that API information will not be returned when using the OpenWhisk Package
447 API:
- 448 • `wsk package list <package name>`
- 449 • However, it may be obtained using the Trigger API:
- 450 • `wsk api list -v`

451 *Package entity*

452 The Package entity schema is used to define an OpenWhisk package within a manifest.

453 *Fields*

Key Name	Required	Value Type	Default	Description
license	yes	string	unlicensed	The required value that indicates the type of license the Package is governed by.

Key Name	Required	Value Type	Default	Description
credential	no	string	N/A	The optional Credential used for all entities within the Package. The value is either: Contains either: <ul style="list-style-type: none"> A credential string. The optional name of a credential (e.g., token) that is defined elsewhere.
dependencies	no	list of Dependency	N/A	The optional list of external OpenWhisk packages the manifest needs deployed before it can be deployed.
repositories	no	list of Repository	N/A	The optional list of external repositories that contain functions and other artifacts that can be found by tooling.
actions	no	list of Action	N/A	Optional list of OpenWhisk Action entity definitions.
triggers	no	list of Trigger	N/A	Optional list of OpenWhisk Trigger entity definitions.
rules	no	list of Rule	N/A	Optional list of OpenWhisk Rule entity definitions.
feeds	no	list of Feed	N/A	Optional list of OpenWhisk Feed entity definitions.
compositions	no	list of Composition	N/A	Optional list of OpenWhisk Composition entity definitions.
apis	no	list of API	N/A	Optional list of API entity definitions.

Requirements

- The Package name MUST be less than or equal to 256 characters.
- The Package entity schema includes all general [Entity Schema](#) fields in addition to any fields declared above.
- A valid Package license value MUST be one of the [Linux SPDX](#) license values; for example: Apache-2.0 or GPL-2.0+, or the value 'unlicensed'.
- Multiple (mixed) licenses MAY be described using [NPM SPDX license syntax](#).
- A valid Package entity MUST have one or more valid Actions defined.

Notes

- The Trigger and API entities within the OpenWhisk programming model are considered outside the scope of the Package. This means that Trigger and API information will not be returned when using the OpenWhisk Package API:

```
wsk package list <package name>
```
- However, their information may be retrieved using respectively:

```
wsk trigger list -v
```

```
wsk api list -v
```

Grammar

```
<packageName>:
  <Entity schema> # Common to all OpenWhisk Entities
```

```
license: <string>
repositories: <list of repository>
actions: <list of actions>
triggers: <list of triggers>
rules: <list of rules>
feeds: <list of feeds>
compositions: <list of compositions>
apis: <list of API>
```

471 *Example*

```
my_whisk_package:
  description: A complete package for my awesome action to be deployed
  version: 1.2.0
  license: Apache-2.0
  actions:
    my_awesome_action:
      <Action schema>
  triggers:
    trigger_for_awesome_action:
      <Trigger schema>
  rules:
    rule_for_awesome_action:
      <Rule schema>
```

472 *Extended Schema*

473 *Dependencies*

474 The dependencies section allows you to declare other OpenWhisk packages that your application
475 or project (manifest) are dependent on. A Dependency is used to declare these other packages
476 which deployment tools can use to automate installation of these pre-requisites.

477 *Fields*

Key Name	Required	Value Type	Default	Description
location	yes	string	N/A	The required location of the package.
version	yes	version	N/A	The required version of the package.
inputs	no	various	N/A	The optional Inputs to the package.

478 *Requirements*

- 479 • No additional requirements.

480 *Notes*

- 481 • The 'version' parameter is currently used to specify a branch in GitHub and defaults to "master", this
482 behavior may change in upcoming releases of the specification.

483 *Grammar*

```
<package_name>:
  location: <GitHub URL> |
  version: 1.0.1
  inputs:
    <list of inputs>
```

484 *Example*

```
dependencies:
  status_update:
    location: github.com/myrepo/statusupdate
    version: 1.0.
  database pkg:
    location: /whisk.system/couchdb
  inputs:
    dbname: MyAppDB
```

485

486 *Repository*

487 A repository defines a named external repository which contains (Action) code or other artifacts
488 package processors can access during deployment.

489 *Fields*

Key Name	Required	Value Type	Default	Description
url	yes	string	N/A	Required URL for the Repository.
description	no	string256	N/A	Optional description for the Repository.
credential	no	string	N/A	Optional name of a Credential defined in the Package that can be used to access the Repository.

490

491 *Requirements*

- 492 • The Repository name (i.e., <repositoryName> MUST be less than or equal to 256 characters.
493 • Description string values SHALL be limited to 256 characters.

494 *Grammar*

495 *Single-line (no credential)*

```
<repositoryName>: <repository_address>
```

496 *Multi-line*

```
<repositoryName>:
  description: <string256>
  url: <string>
  credential: <Credential>
```

497 *Example*

```
my_code_repo:
  description: My project's code repository in GitHub
  url: https://github.com/openwhisk/openwhisk-package-rss
```

498

499 *Credential*

500 A Credential is used to define credentials used to access network accessible resources. Fields

Key Name	Required	Value Type	Default	Description
protocol	no	string	N/A	Optional protocol name used to indicate the authorization protocol to be used with the Credential's token and other values.
tokenType	yes	string	password	Required token type used to indicate the type (format) of the token string within the supported types allowed by the protocol.
token	yes	string	N/A	Required token used as a credential for authorization or access to a networked resource.
description	no	string256	N/A	Optional description for the Credential.
keys	no	map of string	N/A	Optional list of protocol-specific keys or assertions.

501

502 *Requirements*

- 503
- The Credential name (i.e., <credentialName> MUST be less than or equal to 256 characters.
- 504
- Description string values SHALL be limited to 256 characters.

505 *Valid protocol values*

Protocol Value	Valid Token Type Values	Description
plain	N/A	Basic (plain text) username-password (no standard).
http	basic_auth	HTTP Basic Authentication Protocol.
xauth	X-Auth-Token	HTTP Extended Authentication Protocol (base-64 encoded Tokens).
oauth	bearer	Oauth 2.0 Protocol
ssh	identifier	SSH Keypair protocol (e.g., as used in OpenStack)

506

507 *Grammar*

```
Credential:
  type: Object
  properties:
    protocol:
      type: string
      required: false
```

```

tokenType:
  type: string
  default: password
token:
  type: string
keys:
  type: map
  required: false
  entry_schema:
    type: string
user:
  type: string
  required: false

```

508 *Notes*

- 509 • The use of transparent user names (IDs) or passwords are not considered best practice.

510 *Examples*

511 *Plain username-password (no standardized protocol)*

```

inputs:
  my_credential:
    type: Credential
    properties:
      user: my_username
      token: my_password

```

512 *HTTP Basic access authentication*

```

inputs:
  my_credential:
    type: Credential
    description: Basic auth. where <username>:<password> are a single string
    properties:
      protocol: http
      token_type: basic_auth
      # Note: this would be base64 encoded before transmission by any impl.
      token: myusername:mypassword

```

513 *X-Auth-Token*

```

inputs:
  my_credential:
    type: Credential
    description: X-Auth-Token, encoded in Base64
    properties:
      protocol: xauth
      token_type: X-Auth-Token
      # token encoded in Base64
      token: 604bbe45ac7143a79e14f3158df67091

```

514 *OAuth bearer token*

```
inputs:
  my_credential:
    type: Credential
    properties:
      protocol: oauth2
      token_type: bearer
      # token encoded in Base64
      token: 8ao9nE2DEjr1zCsicWMpBC
```

515 *SSH Keypair*

```
inputs:
  my_ssh_keypair:
    type: Credential
    properties:
      protocol: ssh
      token_type: identifier
      # token is a reference (ID) to an existing keypair (already installed)
      token: <keypair_id>
```

516

517 **Package Artifacts**

518 *Package Manifest File*

519 The Package Manifest file is the primary OpenWhisk Entity used to describe an OpenWhisk
520 Package and all necessary **schema** and **file** information needed for deployment. It contains the
521 *Package entity schema* described above.

522 *Deployment File*

523 The Deployment file is used in conjunction with a corresponding Package Manifest file to
524 provide configuration information (e.g., input parameters, authorization credentials, etc.) needed
525 to deploy, configure and run an OpenWhisk Package for a target Cloud environment.
526 Fields

527

528 The manifest and Deployment files are comprised of the following entities:

529 *Application*

530 An optional, top-level key that describes a set of related Packages that together comprise a
531 higher-order application.

532 *Fields*

Key Name	Required	Value Type	Default	Description
name	no	string256	N/A	The optional name of the application.
namespace	no	string	N/A	The optional namespace for the application (and default namespace for its packages where not specified).

Key Name	Required	Value Type	Default	Description
credential	no	string		The optional credential for the application (and default credential for its packages where not specified).
packages	yes	list of package	N/A	The required list of one or more packages.

Grammar

```

application:
  name: <string256>
  namespace: <string>
  credential: <string>
  packages:
    <list of package>

```

Requirements

- The keys under the application key (e.g., name, namespace, credential and packages) are only used in a manifest or deployment file if the optional application key is used.

Notes

- Currently, the OpenWhisk platform does not recognize the Application entity as part of the programming model; it exists as a higher order grouping concept only in this specification. Therefore there is no data stored within OpenWhisk for the Application entity,

Example

```

application:
  name: greetings
  namespace: /mycompany/greetings/
  credential: 1234-5678-90abcdef-0000
  packages:
    helloworld:
      inputs:
        city: Boston
      actions:
        hello:
          inputs: # input bindings
            personName: Paul
    ...

```

Notes

- Note: A common use would be to associate a namespace (i.e., a target namespace binding) or credential to a application and all included packages automatically inherit that namespace (if applied at that level) unless otherwise provided (similar to style inheritance in CSS).*

549 • *The application name would be treated as metadata, perhaps stored in the annotations for the*
550 *contained entities.*

551 *Setting values using (\$) dollar notation*

552 In the Deployment file, a parameter value may be set from the local execution environment by
553 using the dollar (\$) notation to denote names of local environment variables which supply the
554 value to be inserted at execution time.

555 *Syntax*

```
<parameter>: $<local environment variable name>
```

556 *Example*

```
...
  inputs:
    userName: $DEFAULT_USERNAME
```

557 *Requirements*

558 • Processors or tooling that encounter (\$) Dollar notation and are unable to locate the value in the
559 execution environment SHOULD resolve the value to be the default value for the type (e.g., an empty
560 string for type string).

561 *Notes*

562 • Processors or tooling that encounter (\$) Dollar notation for values should attempt to locate the
563 corresponding named variables set into the local execution environment (e.g., where the tool was
564 invoked) and assign its value to the named input parameter for the OpenWhisk entity.

565 • This specification does not currently consider using this notation for other than simple data types
566 (i.e., we support this mechanism for values such as strings, integers, floats, etc.) at this time.

567 Normative References

568

Tag	Description
RFC2119	S. Bradner, <i>Key words for use in RFCs to Indicate Requirement Levels</i> , http://www.ietf.org/rfc/rfc2119.txt , IETF RFC 2119, March 1997.
YAML-1.2	YAML, Version 1.2, 3rd Edition, Patched at 2009-10-01, Oren Ben-Kiki, Clark Evans, Ingy döt Net http://www.yaml.org/spec/1.2/spec.html
YAML-TS-1.1	Timestamp Language-Independent Type for YAML Version 1.1, Working Draft 2005-01-18, http://yaml.org/type/timestamp.html
Maven-Version	The version type is defined with the Apache Maven project's policy draft: https://cwiki.apache.org/confluence/display/MAVEN/Version+number+policy
OpenAPI-2.0	The OpenAPI (f.k.a. "Swagger") specification for defining REST APIs as JSON. https://github.com/OAI/OpenAPI-Specification/blob/master/versions/2.0.md
Linux-SPDX	Linux Foundation, SPDX License list https://spdx.org/licenses/
NPM-SPDX-Syntax	Node Package Manager (NPM) SPDX License Expression Syntax https://www.npmjs.com/package/spdx

569 Non-normative References

570

Tag	Description
OpenWhisk-API	OpenWhisk REST API which is defined as an OpenAPI document. https://raw.githubusercontent.com/openwhisk/openwhisk/master/core/controller/src/main/resources/whiskswagger.json
GNU-units	Size-type units are based upon a subset of those defined by GNU at http://www.gnu.org/software/parted/manual/html_node/unit.html
RFC 6838	Mime Type definitions in compliance with RFC 6838 .
RFC 7231	HTTP 1.1. status codes are described in compliance with RFC 7231 .
IANA-Status-Codes	HTTP Status codes as defined in the IANA Status Code Registry .
JSON Schema Specification	The built-in parameter type "json" references this specification. http://json-schema.org/

571 Scenarios and Use cases

572 Usage Scenarios

573 *User background*

574

575 The following assumptions about the users referenced in the usage scenarios:

- 576 • Experienced developer; knows Java, Node, SQL, REST principles and basic DevOps processes; uses
- 577 IDEs to develop code locally.
- 578 • Limited exposure to Serverless, but interested in trying new technologies that might improve
- 579 productivity.

580 *Scenario 1: Clone and Create*

581 Deploy an OpenWhisk app (project, set of entities, package, ...) discovered on github. The developer...

- 582 1. discovers an interesting git repo containing an OpenWhisk app (project, set of entities,
- 583 package, ...)
- 584 2. clones the repo to local disk.
- 585 3. He pushes (deploys) it into one of his OpenWhisk namespaces
- 586 4. He checks out the app's behavior using OpenWhisk CLI or OpenWhisk UI

587 *Notes*

- 588 • while this scenario allows to use the manifest file as a "black box" the manifest format
- 589 can influence the user experience of a developer trying to read it and understand what it
- 590 does

591 *Scenario 2: Pushing Updates with versioning*

592 Change a cloned repo that he previously pushed into one of his namespaces. The developer...

- 593 1. changes the local repo by editing code and adding and changing entity specifications
- 594 using local tools (editors, IDEs, ...).
- 595 2. bumps version number for package.
- 596 3. pushes his updates into the namespace so that the existing entities are changed
- 597 accordingly.

598 *Scenario 3: Start New Repo with Manifest*

599 Start a new OpenWhisk app (project, set of entities) from scratch. The developer...

- 600 1. code files for the actions (e.g. *action1.js*, *action2.js*, *action3.js*)
- 601 2. creates a *LICENSE.txt* file

3. Creates a **Manifest File** that specifies the set of OpenWhisk entities and their relations (e.g. *manifest.yml*). It also references the LICENSE.txt file.
4. initializes and uploads the set of files as a new git repo.

Notes:

- Creating the initial manifest file should be supported by providing an empty template with syntax examples and other helpful comments

Scenario 4: Export into Repository

Share an existing OpenWhisk app (project, set of entities) with others so that they can deploy and change it for their purposes. The developer...

1. exports a defined set of entities (a whole namespace?) into a set of files that includes code files, and generated manifest, LICENSE.txt and README files.
2. initializes and uploads the set of files as a new git repo.
Example: `git init ...` etc.

Scenario 5: Discovery and Import from object store

Discover an OpenWhisk package (manifest) co-located with data in an Object storage service. This package would include a description of the Actions, Triggers, Rules and Event Sources (or Feeds) necessary to interact with data it is associated with directly from the Object storage repository; thus allowing anyone with access to the data an immediate way to interact and use the data via the OpenWhisk Serverless platform.

Schema Use Cases

“Hello world”

“Hello world” is a simple use case which will accept a string parameter and return a “Hello world” if the parameter is null or “Hello + <string>” if the string parameter is not null.

Manifest Files

Example 1: No parameter descriptions

```
helloworld:
  version: 1.0
  license: Apache-2.0
  actions:
    hello:
      version: 1.0
      function: src/hello/hello.js
      inputs:
        personName: string
```

```
    outputs:
      greeting_string: string
```

Defaults discussion

This specification places an emphasis on simplicity for the casual developer who may wish to hand-code a Manifest and/or Deployment File; however, it also provides a robust optional schema that can be advantaged when integrating with larger application projects using design and development tooling such as IDEs.

In the above example, please note the following intelligent defaults would be applied by a deployment tooling authored using this speification:

- The runtime (i.e., runtime: nodejs) is found from the .js extension on the Action function's filename.

Example 2: with parameter descriptions

```
helloworld:
  version: 1.0
  license: Apache-2.0
  actions:
    hello:
      version: 1.0
      function: src/hello/hello.js
      runtime: nodejs@6
      inputs:
        personName:
          type: string
          description: input person name
      outputs:
        greeting_string:
          type: string
          description: output greeting string
```

Basic Trigger and Rule

This use case will demonstrate how rules and triggers are configured in manifest and deployment file. It will use the previous “helloworld” action, create a rule to associate a trigger with it.

Manifest File

```
helloRules:
  version: 1.0
  license: Apache-2.0
  actions:
    hello:
      version: 1.0
      function: src/hello/hello.js
      runtime: nodejs
      inputs:
        personName: string
      outputs:
```

```

    greeting_string: string

  triggers:
    locationUpdate:
      inputs:
        name: string
        place: string

  rules:
    myRule:
      trigger: locationUpdate
      action: hello

```

643 **Deployment File**

```

packages:
  helloRules:
    triggers:
      locationUpdate:
        inputs:
          name: Henry
          place: Washington, D.C.

```

644

645 **Github feed**

646 This use case will install a feed to fire a trigger when there is activity in a specified GitHub
 647 repository.

648 **Manifest File**

```

git_webhook:
  version: 1.0
  license: Apache-2.0
  feeds:
    webhook_feed:
      version: 1.0
      function: github/webhook.js
      runtime: nodejs@6
      inputs:
        username:
          type: string
          description: github username
        repository:
          type: string
          description: url of github repository
      accessToken:
        type: string
        description: GitHub personal access token
      events:
        type: string
        description: the github event type

```

```
triggers:
  webhook_trigger:
    action: webhook_feed
```

649 **Deployment File**

```
packages:
  git_webhook:
    triggers:
      webhook_trigger:
        inputs:
          username: daisy
          repository: https://github.com/openwhisk/wsktool.git
          accessToken:
          events: push
```

650

651 **Github feed advanced**

652 This use case use the Github feed to create a trigger. When there is any push event happened, it
653 will send a notification email.

654 **Manifest File**

```
git_webhook:
  version: 1.0
  license: Apache-2.0
  action:
    emailNotifier:
      version: 1.0
      function: src/sendemail.js
      runtime: nodejs
      inputs:
        email: string
        title: string
  rules:
    githubNotifier:
      trigger: webhook_trigger
      action: emailNotifier
```

655 **Deployment File**


```
packages:
  git_webhook:
    feeds:
      webhook_feed:
        inputs:
          email: daisy@company.com
          title: Github Push Notification
```

656

RSS Package

The RSS package provides RSS/ATOM feeds which can receive events when a new feed item is available. It also defines a trigger to listen to a specific RSS feed. It describes the OpenWhisk package repositied here:

<https://github.com/openwhisk/openwhisk-package-rss>.



Manifest File

with inline values (no Deployment File)

This example makes use of in-line "values" where the developer does not intend to use a separate Deployment file:

```
rss:
  version: 1.0
  license: Apache-2
  description: RSS Feed package
  inputs:
    provider_endpoint:
      value: http://localhost:8080/rss
      type: string
      description: Feed provider endpoint

  feeds:
    rss_feed:
      version: 1.0
      function: feeds/feed.js
      runtime: nodejs@6
      inputs:
        url:
          type: string
          description: url to RSS feed
          value: http://rss.nytimes.com/services/xml/rss/nyt/HomePage.xml
        pollingInterval:
          type: string
          description: Interval at which polling is performed
          value: 2h
```

```
    filter:
      type: string
      description: Comma separated list of keywords to filter on

  triggers:
    rss_trigger:
      action: rss_feed
```

668

669 **Deployment File**

670 Alternatively, a Deployment File could have provided the same values (bindings) in this way:

```
packages:
  rss:
    inputs:
      provider_endpoint: http://localhost:8080/rss

  feeds:
    rss_feed:
      inputs:
        url: http://rss.nytimes.com/services/xml/rss/nyt/HomePage.xml
        pollingInterval: 2h
```

671

672 Using such a deployment file, allows for more flexibility and the resulting Manifest file would
673 not have needed any **'value'** fields.

674 **Polygon Tracking**

675 This use case describes a microservice composition using Cloudant and a Push Notification
676 service to enable location tracking for a mobile application. The composition uses Cloudant to
677 store polygons that describe regions of interests, and the latest known location of a mobile user.
678 When either the polygon set or location set gets updated, we use the Cloudant Geo capabilities to
679 quickly determine if the new item satisfies a geo query like “is covered by” or “is contained in”.
680 If so, a push notification is sent to the user.

681 **Manifest File:**

```
application:
  name: PolygonTracking
  namespace: polytrack

packages:
  polytrack:

    triggers:
      pointUpdate:
        <feed>

      polygonUpdate:
        <feed>
```



```
actions:
  superpush:
    inputs:
      appId: string
      appSecret: string

  pointGeoQuery:
    inputs:
      username: string
      password: string
      host: string
      dbName: string
      ddoc: string
      iName: string
      relation: string
    outputs:
      cloudantResp: json

  createPushParamsFromPointUpdate:
    <mapper>

  polygonGeoQuery:
    inputs:
      username: string
      password: string
      host: string
      dbName: string
      ddoc: string
      iName: string
      relation: string
    outputs:
      cloudantResp: json

  createPushParamsFromPolygonUpdate:
    <mapper>

Rules:
  whenPointUpdate:
    trigger:
      pointUpdate
    action:
      handlePointUpdate
  whenPolygonUpdate:
    trigger:
      polygonUpdate
    action:
      handlePolygonUpdate

Composition:
  handlePolygonUpdate:
    sequence:
      createGeoQueryFromPolygonUpdate, polygonGeoQuery, createPushParamsFromPolygonUpdate, superpush
```

```

application:
  name: PolygonTracking
  namespace: polytrack

packages:

  myCloudant:
    <bind to Cloudant at whisk.system/Cloudant>

  polytrack:
    credential: ABDCF
    inputs:
      PUSHAPPID=12345
      PUSHAPPSECRET=987654
      COVEREDBY='covered_by'
      COVERS='covers'
      DESIGNDOC='geodd'
      GEOIDX='geoidx'
      CLOUDANT_username=myname
      CLOUDANT_password=myspassword
      CLOUDANT_host=myhost.cloudant.com
      POLYDB=weatherpolygons
      USERLOCDB=userlocation

    triggers:
      pointUpdate:
        <feed>
        inputs:
          dbname: $USERLOCALDB
          includeDoc: true
      polygonUpdate:
        <feed>
        inputs:
          dbname: $USERLOCDB
          includeDoc: true

    actions:
      superpush:
        inputs:
          appId: $PUSHAPPID
          appSecret: $PUSHAPPSECRET
      pointGeoQuery:
        inputs:
          designDoc: $DESIGNDOC
          indexName: $GEOIDX
          relation: $COVEREDBY
          username: $CLOUDANT_username
          password: $CLOUDANT_password

```


```

    host: $CLOUDANT_host
    dbName: $POLYDB
  polygonGeoQuery:
    inputs:
      designDoc: $DESIGNDoc
      indexName: $GEOIDX
      relation: $COVERS
      username: $CLOUDANT_username
      password: $CLOUDANT_password
      host: $CLOUDANT_host
      dbName: $POLYDB

```

MQTT Package (tailored for Watson IoT)

The MQTT package that integrates with Watson IoT provides message topic feeds which can receive events when a message is published. It also defines a trigger to listen to a specific MQTT topic. It describes the OpenWhisk package reposited here: <https://github.com/krook/openwhisk-package-mqtt-watson>.



Manifest File

with inline values (no Deployment File)

This example makes use of in-line “values” where the developer does not intend to use a separate Deployment file:

```

mqtt_watson:
  version: 1.0
  license: Apache-2
  description: MQTT Feed package for Watson IoT
  inputs:
    provider_endpoint:
      value: http://localhost:8080/mqtt-watson

```

```

    type: string
    description: Feed provider endpoint

feeds:
  mqtt_watson_feed:
    version: 1.0
    function: feeds/feed-action.js
    runtime: nodejs@6
    inputs:
      url:
        type: string
        description: URL to Watson IoT MQTT feed
        value: ssl://a-123xyz.messaging.internetofthings.ibmcloud.com:8883
      topic:
        type: string
        description: Topic subscription
        value: iot-2/type/+/id/+/evt/+/fmt/json
      apiKey:
        type: string
        description: Watson IoT API key
        value: a-123xyz
      apiToken:
        type: string
        description: Watson IoT API token
        value: +-derpbog
      client:
        type: string
        description: Application client id
        value: a:12e45g:mqttapp

triggers:
  mqtt_watson_trigger:
    action: mqtt_watson_feed

```

696

697 *Deployment File*

698 Alternatively, a Deployment File could have provided the same values (bindings) in this way:

```

packages:
  mqtt_watson:
    inputs:
      provider_endpoint: http://localhost:8080/mqtt-watson

feeds:
  mqtt_watson_feed:
    inputs:
      url: ssl://a-123xyz.messaging.internetofthings.ibmcloud.com:8883
      topic: iot-2/type/+/id/+/evt/+/fmt/json
      apiKey: a-123xyz
      apiToken: +-derpbog
      client: a:12e45g:mqttapp

```


699

Using such a deployment file, allows for more flexibility and the resulting Manifest file would not have needed any 'value' fields.

Check deposit processing with optical character recognition

This use case demonstrates an event-driven architecture that processes the deposit of checks to a bank account using optical character recognition. It relies on Cloudant and SoftLayer Object Storage. On premises, it could use CouchDB and OpenStack Swift. Other storage services could include FileNet or Cleversafe. Tesseract provides the OCR library.

This application uses a set of actions and triggers linked by rules to process images that are added to an object storage service. When new checks are detected a workflow downloads, resizes, archives, and reads the checks then it invokes an external system to handle the transaction.



```

application:
  name: OpenChecks
  namespace: openchecks

packages:
  openchecks:

  triggers:
    poll-for-incoming-checks:
      inputs:
        cron: string
        maxTriggers: integer

    check-ready-to-scan:
      inputs:
        dbname: string
        includDocs: boolean

    check-ready-for-deposit:
      inputs:
        dbname: string
        includDocs: boolean

  actions:
    find-new-checks:
      inputs:
        CLOUDANT_USER: string
        CLOUDANT_PASS: string
        SWIFT_USER_ID: string
        SWIFT_PASSWORD: string
        SWIFT_PROJECT_ID: string
        SWIFT_REGION_NAME: string
        SWIFT_INCOMING_CONTAINER_NAME: string
        CURRENT_NAMESPACE: string

    save-check-images:
      inputs:
        CLOUDANT_USER: string
        CLOUDANT_PASS: string
        CLOUDANT_ARCHIVED_DATABASE: string
        CLOUDANT_AUDITED_DATABASE: string
        SWIFT_USER_ID: string
        SWIFT_PASSWORD: string
        SWIFT_PROJECT_ID: string
        SWIFT_REGION_NAME: string
        SWIFT_INCOMING_CONTAINER_NAME: string

    parse-check-data:
      inputs:
        CLOUDANT_USER: string
        CLOUDANT_PASS: string
        CLOUDANT_AUDITED_DATABASE: string
        CLOUDANT_PARSED_DATABASE: string

```

```

    CURRENT_NAMESPACE: string

record-check-deposit:
  inputs:
    CLOUDANT_USER: string
    CLOUDANT_PASS: string
    CLOUDANT_PARSED_DATABASE: string
    CLOUDANT_PROCESSED_DATABASE: string
    CURRENT_NAMESPACE: string
    SENDGRID_API_KEY: string
    SENDGRID_FROM_ADDRESS: string

parse-check-with-ocr:
  inputs:
    CLOUDANT_USER: string
    CLOUDANT_PASS: string
    CLOUDANT_AUDITED_DATABASE: string
    id: string
  outputs:
    result: JSON

rules:
  fetch-checks:
    trigger:
      poll-for-incoming-checks
    action:
      find-new-checks
  scan-checks:
    trigger:
      check-ready-to-scan
    action:
      parse-check-data
  deposit-checks:
    trigger:
      check-ready-for-deposit
    action:
      record-check-deposit

```

716 *Deployment File:*

```

application:
  name: OpenChecks
  namespace: openchecks

packages:

  myCloudant:
    <bind to Cloudant at whisk.system/Cloudant>

  openchecks:
    credential: ABDCF
    inputs:
      XXX=YYY

```

```
triggers:
  poll-for-incoming-checks:
    <feed>
    inputs:
      cron: */20 * * * * *
      maxTriggers: 90
  check-ready-to-scan:
    <feed>
    inputs:
      dbname: audit
      includeDoc: true
  check-ready-for-deposit:
    <feed>
    inputs:
      dbname: parsed
      includeDoc: true

actions:
  find-new-checks:
    inputs:
      CLOUDANT_USER: 123abc
      CLOUDANT_PASS: 123abc
      SWIFT_USER_ID: 123abc
      SWIFT_PASSWORD: 123abc
      SWIFT_PROJECT_ID: 123abc
      SWIFT_REGION_NAME: northeast
      SWIFT_INCOMING_CONTAINER_NAME: incoming
      CURRENT_NAMESPACE: user_dev
  save-check-images:
    inputs:
      CLOUDANT_USER: 123abc
      CLOUDANT_PASS: 123abc
      CLOUDANT_ARCHIVED_DATABASE: archived
      CLOUDANT_AUDITED_DATABASE: audited
      SWIFT_USER_ID: 123abc
      SWIFT_PASSWORD: 123abc
      SWIFT_PROJECT_ID: 123abc
      SWIFT_REGION_NAME: northeast
      SWIFT_INCOMING_CONTAINER_NAME: container_name
  parse-check-data:
    inputs:
      CLOUDANT_USER: 123abc
      CLOUDANT_PASS: 123abc
      CLOUDANT_AUDITED_DATABASE: audited
      CLOUDANT_PARSED_DATABASE: parsed
      CURRENT_NAMESPACE: user_dev
  record-check-deposit:
    inputs:
```



```
    CLOUDANT_USER: 123abc
    CLOUDANT_PASS: 123abc
    CLOUDANT_PARSED_DATABASE: parsed
    CLOUDANT_PROCESSED_DATABASE: processed
    CURRENT_NAMESPACE: user_dev
    SENDGRID_API_KEY: 123abc
    SENDGRID_FROM_ADDRESS: user@example.org
  parse-check-with-ocr:
    inputs:
      CLOUDANT_USER: 123abc
      CLOUDANT_PASS: 123abc
      CLOUDANT_AUDITED_DATABASE: audited
      id: 123abc
```

Event Sources

OpenWhisk is designed to work with any Event Source, either directly via published APIs from the Event Source's service or indirectly through Feed services that act as an Event Source on behalf of a service. This section documents some of these Event Sources and/or Feeds using this specification's schema.

Curated Feeds

The following Feeds are supported by the OpenWhisk platform within the IBM Bluemix Cloud platform. They are referenced by the term "curated" since they are maintained alongside the OpenWhisk open source code to guarantee compatibility. More information on curated feeds can be found here: <https://github.com/openwhisk/openwhisk/blob/master/docs/catalog.md>.

Alarms

The `/whisk.system/alarms` package can be used to fire a trigger at a specified frequency. This is useful for setting up recurring jobs or tasks, such as invoking a system backup action every hour.

Package Manifest

The "alarms" Package Manifest would appear as follows:

```
# shared system package providing the alarms feed action
alarms:
  version: 1.0
  license: Apache-2
  description: Alarms and periodic utility

  actions:
    alarm:
      function: action/alarm.js
      description: Fire trigger when alarm occurs
      feed: true
      inputs:
        package_endpoint:
          type: string
          description: The alarm provider endpoint with port
        cron:
          type: string
          description: UNIX crontab syntax for firing trigger in
            Coordinated Universal Time (UTC).
          required: true
        trigger_payload:
          type: object
          description: The payload to pass to the Trigger, varies
          required: false
        maxTriggers:
          type: integer
          default: 1000
          required: false
```

```
feeds:
  location: TBD
  credential: TBD
  operations:
    CREATE:
      TBD
    DELETE:
      TBD
  action: alarm
```

735
736

737 **Cloudant**

738 The `/whisk.system/cloudant` package enables you to work with a Cloudant database. It
739 includes the following actions and feeds.

740 *Package Manifest*

741 The “cloudant” Package Manifest would appear as follows:

TBD

742 **Public Sources**

743 The following examples are Event Sources that can provide event data to OpenWhisk. We
744 describe them here using this specification’s schema.

745 **GitHub WebHook**

746 Note: the GitHub WebHook is documented here: <https://developer.github.com/webhooks/>.

747

748 A sample description of the GitHub Event Source and its “create hook” API would appear as follows:

TBD

749

Other Considerations

Tooling interaction

Using package manifest directly from GitHub

GitHub is an acknowledged as a popular repository for open source projects which may include OpenWhisk Packages along with code for Actions and Feeds. It is easily envisioned that the Package Manifest will commonly reference GitHub as a source for these artifacts; this specification will consider Github as being covered by the general Catalog use case.

Using package manifest in archive (e.g., ZIP) file

Compressed packaging, including popular ZIP tools, is a common occurrence for popular distribution of code which we envision will work well with OpenWhisk Packages; however, at this time, there is no formal description of its use or interaction. We leave this for future consideration.

Simplification of WebHook Integration

Using RESTify

One possible instance of a lightweight framework to build REST APIs in Nodejs to export WebHook functionality. See <https://www.npmjs.com/package/restify> RESTify (over Express) provides help in the areas of versioning, error handling (retry, abort) and content-negotiation. It also provides built in DTrace probes that identify application performance problems.

Enablement of Debugging for DevOps

Isolating and debugging “bad” Actions using (local) Docker

Simulate Inputs at time of an Action failure/error condition, isolate it and run it in a “debug” mode.

Considerations include, but are not limited to:

- Isolation on separate “debug” container
- Recreates “inputs” at time of failure
- Possibly recreates message queue state
- Provides additional stacktrace output
- Provides means to enable “debug” trace output
- Connectivity to “other” debug tooling

Using software debugging (LLDB) frameworks

This is a topic for future use cases and integrations. Specifically, working with LLDB frameworks will be considered. See <http://lldb.llvm.org/>.

Appendices

OpenWhisk Entity Names

Entity Name Tests

Note that Java `/w` matches “word characters” (not just alphanumerics) such as `'_'` (underscore).

Against Java Regex: `\A([\w]/[\w][\w@.-]*[\w@.-]+\z`

Test String	matches()	n [start(n), end(n)] group(n)	Notes
"a"	true	0: [0,1] a 1: [0,1] a	Shortest Alpha
"1"	true	0: [0,1] 1 1: [0,1] 1	Shortest Numeric
"_1"	true	0: [0,2] _1 1: [0,2] _1	Underscore at beginning
"aAbBcCzZ"	true	0: [0,8] aAbBcCzZ 1: [0,8] aAbBcCzZ	All Alphas
"1234567890"	true	0: [0,10] 1234567890 1: [0,10] 1234567890	All Numerics
"1 2 a Z 9 0"	true	0: [0,11] 1 2 a Z 9 0 1: [0,11] 1 2 a Z 9 0	AlphaNumerics with spaces
"09 @@ _ 4m .. -- aZ"	true	0: [0,23] 09 @@ _ 4m .. -- aZ 1: [0,23] 09 @@ _ 4m .. -- aZ	Multiples of all possible allowed characters.
"Name includes a short domain name is a@b.c"	true	0: [0,42] Name includes a short domain name is a@b.c 1: [0,42] Name includes a short domain name is a@b.c	Sentence-style name with embedded domain name
"_"	true	0: [0,1] _ 1: [0,1] _	Underscore only
"_."	true	0: [0,2] _. 1: [0,2] _.	Underscore, dot only
"_.-@"	true	0: [0,4] _.-@ 1: [0,4] _.-@	Underscore, all special characters only (no spaces)
"___"	true	0: [0,3] ___ 1: [0,3] ___	3 underscores only
a+b	false	N/A	Invalid '+' character
@a	TBD		
-a	TBD		

792 *Against Java Regex: \A([\w][\w@ .-]*[\w@.-]+\z*

Test String	matches()	Notes
TBD		

793

794 **Acknowledgements**

795 Thanks to the following individuals who have contributed to the contents:

796

797 Castro, Paul

798 Guo, Ying Chun

799 Krook, Daniel

800 Linnemeier, Micah

801 Liu, David

802 Mitchell, Nick

803 Ortelt, Thomas

804 Rutkowski, Matt

805 Santana, Carlos

806 Villard, Lionel