RESONIK

Roadmap

What each release of the free ATS Mini firmware brings · 12 November 2026

Released · In testing · Planned · Ideas

v2.45-r1

6 Nov 2026

Released

The basics for listeners and hams

- CW mode with the true CW frequency
- IARU Region 1 band plan on the scale, automatic LSB/USB
- Dual clock (local and UTC), named time zones
- Reliable clock sync at power-on
- Battery time remaining
- Automatic attenuation for strong AM stations
- Browser installer and Wi-Fi updates from RESONIK
- RESONIK boot screen and About

v2.45-r2

8 Nov 2026

Released

New menu and station tools

- New default menu: six categories of coloured tiles
- Full-screen settings pages
- NCDXF/IARU beacon tracker
- Memory scan, stops on signals
- Signal logger to a CSV file
- Propagation data from hamqsl.com
- CAT control from a PC (Kenwood TS-480)
- EiBi schedules with days, language and target
- Knob setting: 20 or 30 clicks
- Persian user manual (PDF)

v2.45-r3

testing now

In testing

Decoders and smarter tuning

- CW decoder: Morse to text, full screen or as a strip
- FT8 decoder with waterfall and message list
- Band scanner that holds on signals
- Band Plan Auto: mode, filter and step set per band segment
- Plan areas: Region 1, UAE and Iran
- FT4 decoder on the FT8 page
- FT8/FT4 decode even without the clock set
- Performance setting: up to 3 times faster processor
- Frequency lock: the knob sets the volume instead
- Wi-Fi power setting for boards that reset
- Fixes from other ats-mini forks

CW, FT8 and FT4 decoding use the speaker line wired to GPIO11 on V4/V4B boards.

Continued on the next page

RESONIK

Roadmap (continued)

v2.45-r4
next

Planned

More decoding and a better view of the band

- RTTY decoder
- Scan as a waterfall, blue to yellow
- Status page: ESP32 temperature, memory, uptime, last restart reason, restart
- Propagation map with the day/night line
- Web Control: the radio's screen live in the browser, with remote knob and buttons
- Backup and restore of all settings from the web page
- Setup wizard at first start: time zone, Wi-Fi, knob, plan area
- Wi-Fi set up on the radio: network scan and on-screen keyboard
- Number pad to type a frequency
- Auto-store: scan the band and fill a station list
- Country of each FT8 station
- Battery shown as icon, volts or percent

v2.45-r5
after R4

Planned

Maps and images

- FT8 station map with country flags, distance and bearing
- EiBi transmitter location, distance and bearing
- SSTV picture decoder

Later
under study

Ideas

Ideas

- Automatic mode detection from the received audio (experimental)
- New ats-mini versions merged in as they are released
- Your suggestions: send them in the Telegram group or on GitHub

Not possible
on this radio

Noise reduction and sound effects

The sound goes from the receiver chip straight to the speaker, so the processor can decode signals but cannot change what you hear. For a cleaner sound use a narrower Bandwidth, SoftMute, AVC or Squelch.