FunctX XQuery Functions

Below is an alphabetical list of all available functions. You can also see a list of functions by category.

FunctX XQuery Function Library

functx:add-attributes	Adds attributes to XML elements
functx:add-months	Adds months to a date
functx:add-or-update-attributes	Adds attributes to XML elements
functx:all-whitespace	Whether a value is all whitespace or a zero-length string
functx:are-distinct-values	Whether all the values in a sequence are distinct
functx:atomic-type	The built-in type of an atomic value
functx:avg-empty-is-zero	The average, counting "empty" values as zero
functx:between-exclusive	Whether a value is between two provided values
functx:between-inclusive	Whether a value is between two provided values, or equal to one of them
functx:camel-case-to-words	Turns a camelCase string into space-separated words
functx:capitalize-first	Capitalizes the first character of a string
functx:change-element-names-deep	Changes the names of elements in an XML fragment
functx:change-element-ns-deep	Changes the namespace of XML elements and its descendants
functx:change-element-ns	Changes the namespace of XML elements
functx:chars	Converts a string to a sequence of characters
functx:contains-any-of	Whether a string contains any of a sequence of strings
functx:contains-case-insensitive	Whether one string contains another, without regard to case
functx:contains-word	Whether one string contains another, as a separate word
functx:copy-attributes	Copies attributes from one element to another
functx:date	Construct a date from a year, month and day
functx:dateTime	Construct a date/time from individual components
functx:day-in-year	The day of the year (a number between 1 and 366)
functx:day-of-week-abbrev-en	The abbreviated day of the week, from a date, in English
functx:day-of-week-name-en	The name of the day of the week, from a date, in English
functx:day-of-week	The day of the week, from a date

Google

Web xqueryfunctions.com

Search

Need XQuery Help?

DATYPIC

Training | Development

Recommended Reading:

XQuery

functx:dayTimeDuration	Construct a dayTimeDuration from a number of days, hours, etc.
functx:days-in-month	Number of days in the month
functx:depth-of-node	The depth (level) of a node in an XML tree
functx:distinct-attribute-names	The distinct names of all attributes in an XML fragment
functx:distinct-deep	The XML nodes with distinct values, taking into account attributes and descendants
functx:distinct-element-names	The distinct names of all elements in an XML fragment
functx:distinct-element-paths	The distinct paths of all descendant elements in an XML fragment
functx:distinct-nodes	The distinct XML nodes in a sequence (by node identity)
functx:duration-from-timezone	Converts a timezone like "-05:00" or "Z" into xs:dayTimeDuration
functx:dynamic-path	Dynamically evaluates a simple XPath path
functx:escape-for-regex	Escapes regex special characters
functx:exclusive-or	Whether one (and only one) of two boolean values is true
functx:first-day-of-month	The first day of the month of a date
functx:first-day-of-year	The first day of the year of a date
functx:first-node	The XML node in a sequence that appears first in document order
functx:follows-not-descendant	Whether an XML node follows another without being its descendant
functx:format-as-title-en	Moves title words like "the" and "a" to the end of strings
functx:fragment-from-uri	Returns the fragment from a URI
functx:get-matches-and-non-matches	Splits a string into matching and non-matching regions
functx:get-matches	Return the matching regions of a string
functx:has-element-only-content	Whether an element has element-only content
functx:has-empty-content	Whether an element has empty content
functx:has-mixed-content	Whether an element has mixed content
functx:has-simple-content	Whether an element has simple content
functx:id-from-element	Gets the ID of an XML element
functx:id-untyped	Gets XML element(s) that have an attribute with a particular value
functx:if-absent	The first argument if it is not empty, otherwise the second argument
functx:if-empty	The first argument if it is not blank, otherwise the second argument
functx:index-of-deep-equal-node	The position of a node in a sequence, based on contents and attributes
functx:index-of-match-first	The first position of a matching substring
functx:index-of-node	The position of a node in a

	sequence, based on node identity
functx:index-of-string-first	The first position of a substring
functx:index-of-string-last	The last position of a substring
functx:index-of-string	The position(s) of a substring
functx:insert-string	Inserts a string at a specified position
functx:is-a-number	Whether a value is numeric
functx:is-absolute-uri	Whether a URI is absolute
functx:is-ancestor	Whether an XML node is an ancestor of another node
functx:is-descendant	Whether an XML node is a descendant of another node
functx:is-leap-year	Whether a date falls in a leap year
functx:is-node-among-descendants-deep-equal	Whether an XML node is among the descendants of a sequence, based on contents and attributes
functx:is-node-among-descendants	Whether an XML node is among the descendants of a sequence, based on node identity
functx:is-node-in-sequence-deep-equal	Whether an XML node is in a sequence, based on contents and attributes
functx:is-node-in-sequence	Whether an XML node is in a sequence, based on node identity
functx:is-value-in-sequence	Whether an atomic value appears in a sequence
functx:last-day-of-month	The last day of the month of a date
functx:last-day-of-year	The last day of the month of a date
functx:last-node	The XML node in a sequence that is last in document order
functx:leaf-elements	All XML elements that don't have any child elements
functx:left-trim	Trims leading whitespace
functx:line-count	The number of lines
functx:lines	Split a string into separate lines
functx:max-depth	The maximum depth of elements in an XML tree
functx:max-determine-type	The maximum value in a sequence, figuring out its type (numeric or string)
functx:max-line-length	The maximum line length
functx:max-node	The XML node whose typed value is the maximum
functx:max-string	The maximum of a sequence of values, treating them like strings
functx:min-determine-type	The minimum value in a sequence, figuring out its type (numeric or string)
functx:min-node	The XML node whose typed value is the minimum
functx:min-non-empty-string	The minimum of a sequence of strings, ignoring "empty" values
functx:min-string	The minimum of a sequence of values, treating them like strings
functx:mmddyyyy-to-date	Converts a string with format MMDDYYYY (with any delimiters) to a date

functx:month-abbrev-en	The month of a date as an abbreviated word (Jan, Feb, etc.)
functx:month-name-en	The month of a date as a word (January, February, etc.)
functx:name-test	Whether a name matches a list of names or name wildcards
functx:namespaces-in-use	A list of namespaces used in element/attribute names in an XML fragment
functx:next-day	The next day
functx:node-kind	The XML node kind (element, attribute, text, etc.)
functx:non-distinct-values	Returns any values that appear more than once in a sequence
functx:number-of-matches	The number of regions that match a pattern
functx:open-ref-document	Resolves a relative URI and references it, returning an XML document
functx:ordinal-number-en	Reformats a number as an ordinal number, e.g. 1st, 2nd, 3rd.
functx:pad-integer-to-length	Pads an integer to a desired length by adding leading zeros
functx:pad-string-to-length	Pads a string to a desired length
functx:path-to-node-with-pos	A unique path to an XML node (or sequence of nodes)
functx:path-to-node	A path to an XML node (or sequence of nodes)
functx:precedes-not-ancestor	Whether an XML node precedes another without being its ancestor
functx:previous-day	The previous day
functx:remove-attributes-deep	Removes attributes from an XML fragment, based on name
functx:remove-attributes	Removes attributes from an XML element, based on name
functx:remove-elements-deep	Removes descendant elements from an XML node, based on name
functx:remove-elements-not-contents	Removes descendant XML elements but keeps their content
functx:remove-elements	Removes child elements from an XML node, based on name
functx:repeat-string	Repeats a string a given number of times
functx:replace-beginning	Replaces the beginning of a string, up to a matched pattern
functx:replace-element-values	Updates the content of one or more elements
functx:replace-first	Replaces the first match of a pattern
functx:replace-multi	Performs multiple replacements, using pairs of replace parameters
functx:reverse-string	Reverses the order of characters
functx:right-trim	Trims trailing whitespace
functx:scheme-from-uri	Returns the scheme from a URI
functx:sequence-deep-equal	Whether two sequences have the same XML node content and/or values

functx:sequence-node-equal-any-order	Whether two sequences contain the same XML nodes, regardless of order
functx:sequence-node-equal	Whether two sequences contain the same XML nodes, in the same order
functx:sequence-type	The sequence type that represents a sequence of nodes or values
functx:siblings-same-name	The siblings of an XML element that have the same name
functx:siblings	The siblings of an XML node
functx:sort-as-numeric	Sorts a sequence of numeric values or nodes
functx:sort-case-insensitive	Sorts a sequence of values or nodes regardless of capitalization
functx:sort-document-order	Sorts a sequence of nodes in document order
functx:sort	Sorts a sequence of values or nodes
functx:substring-after-if-contains	Performs substring-after, returning the entire string if it does not contain the delimiter
functx:substring-after-last-match	The substring after the last text that matches a regex
functx:substring-after-last	The substring after the last occurrence of a delimiter
functx:substring-after-match	The substring after the first text that matches a regex
functx:substring-before-if-contains	Performs substring-before, returning the entire string if it does not contain the delimiter
functx:substring-before-last-match	The substring after the first text that matches a regex
functx:substring-before-last	The substring before the last occurrence of a delimiter
functx:substring-before-match	The substring before the last text that matches a regex
functx:time	Construct a time from an hour, minute and second
functx:timezone-from-duration	Converts an xs:dayTimeDuration into a timezone like "-05:00" or "Z"
functx:total-days-from-duration	The total number of days in a dayTimeDuration
functx:total-hours-from-duration	The total number of hours in a dayTimeDuration
functx:total-minutes-from-duration	The total number of minutes in a dayTimeDuration
functx:total-months-from-duration	The total number of months in a yearMonthDuration
functx:total-seconds-from-duration	The total number of seconds in a dayTimeDuration
functx:total-years-from-duration	The total number of years in a yearMonthDuration
functx:trim	Trims leading and trailing whitespace
functx:update-attributes	Updates the attribute value of an XML element
functx:value-except	The values in one sequence that aren't in another sequence
functx:value-intersect	The intersection of two sequences of values

functx:value-union	The union of two sequences of values
functx:word-count	The number of words
functx:words-to-camel-case	Turns a string of words into camelCase
functx:wrap-values-in-elements	Wraps a sequence of atomic values in XML elements
functx:yearMonthDuration	Construct a yearMonthDuration from a number of years and months

Built-In Functions

fn:QName	Constructs a QName from a namespace and local part
fn:abs	The absolute value
fn:adjust-date-to-timezone	Adjusts a date to a specific timezone, or no timezone
fn:adjust-dateTime-to-timezone	Adjusts a dateTime to a specific timezone, or no timezone
fn:adjust-time-to-timezone	Adjusts a time to a specific timezone, or no timezone
fn:avg	The average of a sequence of values
fn:base-uri	The base URI of a node
fn:boolean	The effective boolean value of a sequence
fn:ceiling	Rounds up to the next highest integer
fn:codepoint-equal	Whether two strings have the same Unicode code points
fn:codepoints-to-string	Creates a string from a sequence of Unicode code points
fn:collection	Opens a collection
fn:compare	Compares two strings
fn:concat	Concatenates two or more strings
fn:contains	Whether one string contains another
fn:count	The number of items in a sequence
fn:current-date	The current date
fn:current-dateTime	The current date/time
fn:current-time	The current time
fn:data	The atomic value of a node
fn:dateTime	Construct a dateTime from a date and time
fn:day-from-date	The day portion of a date
fn:day-from-dateTime	The day portion of a date/time
fn:days-from-duration	The number of days in a duration
fn:deep-equal	Whether two nodes have the same content and attributes
fn:default-collation	The default collation
fn:distinct-values	The distinct atomic values in a sequence
fn:doc-available	Whether a document is available
fn:doc	Opens a document based on a URI
fn:document-uri	The URI of a document
fn:empty	Whether a value is the empty sequence
fn:encode-for-uri	Encodes reserved characters for use in the path of a URI
fn:ends-with	Whether one string ends with another

fn:error	Raises a custom error
fn:escape-html-uri	Escapes all characters except printable ASCII characters
fn:exactly-one	Returns a sequence if it contains exactly one item, otherwise errors
fn:exists	Whether an argument is the empty sequence
fn:false	The boolean value false
fn:floor	Rounds down to the next lowest integer
fn:hours-from-dateTime	The hour portion of a date/time
fn:hours-from-duration	The hours in a duration
fn:hours-from-time	The hour portion of a time
fn:id	Retrieves elements by their ID
fn:idref	Retrieves elements that refer to other elements based on ID
fn:implicit-timezone	The implicit timezone set by the processor
fn:in-scope-prefixes	The prefixes that are in scope for an element
fn:index-of	The position(s) of an atomic value within a sequence
fn:insert-before	Inserts a new item into a sequence
fn:iri-to-uri	Converts an IRI into a URI
fn:lang	Tests the language of a node
fn:last	The size of the current context
fn:local-name-from-QName	The local part of a QName
fn:local-name	The local part of a node's name
fn:lower-case	Converts to lower case
fn:matches	Whether a string matches a regular expression
fn:max	The maximum of a sequence of values
fn:min	The minimum of a sequence of values
fn:minutes-from-dateTime	The minute portion of a date/time
fn:minutes-from-duration	The number of minutes in a duration
fn:minutes-from-time	The minute portion of a time
fn:month-from-date	The month portion of a date
fn:month-from-dateTime	The month portion of a date/time
fn:months-from-duration	The number of months in a duration
fn:name	The qualified name of a node, as a string
fn:namespace-uri-for-prefix	The namespace associated with a prefix, in the scope of an element
fn:namespace-uri-from-QName	The namespace part of a QName
fn:namespace-uri	The namespace URI of a node
fn:nilled	Whether an element is nilled (has xsi:nil="true")
fn:node-name	The qualified name of a node, as a QName
fn:normalize-space	Normalizes whitespace

fn:normalize-unicode	Normalizes according to a Unicode normalization form
fn:not	Negates a boolean value
fn:number	Converts a value or a node to a number
fn:one-or-more	Returns a sequence if it contains one or more items, otherwise errors
fn:position	The current context position
fn:prefix-from-QName	The prefix portion of a QName
fn:remove	Removes an item from a sequence
fn:replace	Replaces parts of a string that match a regular expression
fn:resolve-QName	Resolves a QName based on the in-scope namespaces of an element
fn:resolve-uri	Resolves a relative URI to a base URI, returning an absolute URI
fn:reverse	Reverses the order of a sequence
fn:root	The root of the tree that contains the argument
fn:round-half-to-even	Rounds a numeric value, rounding even halfs to the nearest even number
fn:round	Rounds a numeric value
fn:seconds-from-dateTime	The seconds portion of a date/time
fn:seconds-from-duration	The number of seconds in a duration
fn:seconds-from-time	The seconds portion of a time
fn:starts-with	Whether one string starts with another
fn:static-base-uri	The base URI from the static context
fn:string-join	Concatenates a sequence of strings using an optional separator
fn:string-length	The length of a string
fn:string-to-codepoints	Creates a sequence of Unicode code points from a string
fn:string	Converts a value or a node to string
fn:subsequence	A portion of a sequence based on a starting point and length
fn:substring-after	The substring after the first occurrence of a delimiter
fn:substring-before	The substring before the first occurrence of a delimiter
fn:substring	A substring based on a starting point and optional length
fn:sum	The sum of values in a sequence
fn:timezone-from-date	The timezone portion of a date
fn:timezone-from-dateTime	The timezone portion of a date/time
fn:timezone-from-time	The timezone portion of a time
fn:tokenize	Splits a string based on a regular expression
fn:trace	Reports tracing information in an implementation-defined way
fn:translate	Replaces individual characters
fn:true	The boolean value true
fn:unordered	Indicates that order is not significant, to

	improve performance
fn:upper-case	Converts to upper case
fn:year-from-date	The year portion of a date
fn:year-from-dateTime	The year portion of a date/time
fn:years-from-duration	The number of years in a duration
fn:zero-or-one	Returns a sequence if it contains zero or one items, otherwise errors

---

© Copyright 2006-2018 Datypic.
Syntax highlighting by xmlspectrum.
Please report errors or comments to contrib@functx.com.