Estimation of Object Location in Small Enclosed Spaces Using Convolutional Neural Networks and Acoustic Echoes

Esteban Padilla Padilla
Instituto Tecnológico de Costa Rica
San José, Costa Rica
estebanpadi@estudiantec.cr

Kervin Sánchez Herrera
Instituto Tecnológico de Costa Rica
San José, Costa Rica
ksanchez@itcr.ac.cr

***Abstract*—Robotic perception must be robust when machines are deployed to operate and interact safely with humans in complex environments. Acoustic perception of geometry and enclosed spaces represents a promising modality to complement and enhance traditional optical sensing. This work investigates the use of acoustic sensing and Convolutional Neural Networks (CNNs) to estimate the spatial location of an object inside a confined environment. An experimental measurement box was built, equipped with a robotic arm to position a cube at controlled coordinates and orientations, and instrumented with a speaker and a four-microphone array to capture the acoustic response. A dataset of acoustic recordings was collected covering a wide range of cube positions and orientations. Spectrograms were generated from the audio signals and used as input to a modified ResNet-18 architecture designed for both classification and regression tasks.**

The model achieved high accuracy in classifying cube location regions, whereas orientation classification proved significantly more challenging. For coordinate estimation, three independent regression networks were trained to predict the X, Y, and Z positions of the cube, and the estimation error for each coordinate is reported and analyzed. Overall, the findings demonstrate that acoustic perception combined with CNN-based inference can effectively estimate object location in confined spaces, offering a low-cost alternative to optical sensors.

***Index Terms*—Audio, Room Impulse Response, CNN, Log-Mel spectrogram, location estimation.**

I. Introduction

Robots are expected to operate in a wide variety of environments. To achieve this, they must be equipped with situational awareness and sufficient autonomy to make appropriate decisions. Computer vision seeks to provide machines with an interpretable representation of the surrounding world. By processing images and videos, robots can detect objects, infer geometry, and extract textures, materials, and other scene features. Although visual analysis allows a machine to build rich internal models of its environment, this does not imply that perception is complete.

Robotic perception enables a machine to understand its surroundings well enough to interact safely with the world [1]. Achieving such understanding requires techniques beyond computer vision in order to obtain a more comprehensive sensory experience of the environment. Acoustic sensing and analysis can significantly enhance robotic perception by following an approach similar to that found in nature. Animals that rely on binaural acoustic perception can analyze their environment to detect the source of a sound and direct their visual attention toward that region. Moreover, this capability is not merely an extension of vision; in certain conditions, animals can depend almost entirely on acoustic information. This is the case of echolocation, employed by bats, birds, dolphins, and whales. By interpreting the echoes of acoustic chirps, these animals gain spatial awareness of their surroundings and can navigate complex environments [2].

Traditional computer vision techniques that use cameras and LiDARs provide high-fidelity information to navigation systems; however, their reliability degrades in environments with poor illumination or in the presence of dust, smoke, or fog [3]. Another important consideration is the cost of sensing hardware. In this regard, acoustic perception offers a significant advantage due to the low cost of commercial electret and MEMS microphones, which are considerably cheaper than optical cameras and LiDAR units. This makes acoustic sensing an attractive alternative to traditional sensors.

Recent advances in machine learning, such as those presented in [3]–[5], have demonstrated the strong potential of neural networks to infer spatial and geometric information about surrounding objects solely from the analysis of acoustic echoes in the audible spectrum. Within the context of Industry 4.0, the manufacturing sector is rapidly increasing its adoption of automation and intelligent monitoring technologies. This trend has created a relevant application domain for acoustic-based methods, particularly in the supervision of machinery operating on production floors, where robotic arms and computer numerical control actuators manipulate objects within confined spaces [6].

In such conditions, acoustic sensing provides valuable insight into the overall system state due to the nature of the Room Impulse Response (RIR), which acts as a transfer function encoding information about the environment configuration. The acoustic response of a room can be leveraged together with artificial neural networks—such as convolutional neural networks or recurrent neural networks—to learn meaningful representations of room echoes and identify spatial

characteristics and object properties. Consequently, acoustic perception combined with neural network-based inference can significantly enhance the perceptual capabilities of machinery operating in complex environments.

This paper presents the results of using acoustic sensing and CNNs to estimate the spatial location of an object inside a confined environment. Section II reviews related work on Room Impulse Responses (RIRs), room classification, geometry estimation, and acoustic-based shape recognition. Section III describes the construction of the measurement box, the robotic arm mechanism, and the microphone-speaker configuration, and also details the procedure used to collect the dataset. Section IV presents the experimental results and their corresponding analysis. Finally, Section V summarizes the main conclusions of the study and outlines several directions for future research.

II. Related Work

For an enclosed space, the Room Impulse Response (RIR) provides a unique representation of its geometry and materials. Audio signals such as music or speech recorded in indoor environments inherently contain this echo information, which can be used to identify the room in which the recording was performed. This idea is explored in [7], where the authors developed a machine learning system capable of classifying rooms from reverberant audio samples, achieving an accuracy of 85%. Similarly, the work in [8] employed RIR and speech data to train a model that infers room volume from single-microphone recordings. Using this inferred volume, the model classified rooms into three categories: small, large, or hall, with an accuracy of 85.8%. In [9], microphone arrays were used to analyze RIRs and estimate room geometry by leveraging properties of Euclidean distance matrices. The authors demonstrated that, under certain conditions, first-order echoes provide a unique description of the geometry of convex polyhedral rooms. An indoor positioning device based on RIR "fingerprints" is presented in [10], where room identification accuracy ranged from 65% for living rooms to 95% for bathrooms. The dataset introduced in [11] includes RIR samples recorded with people standing and moving inside the rooms. The authors showed the potential of applying machine learning techniques to this dataset for tasks such as human localization, identification, and detection.

Acoustic perception of object shapes is investigated in [12], where the authors propose the use of acoustic standing waves to recognize the size and shape of target objects. By analyzing the distance spectrum profile generated by interference between transmitted and reflected sounds, In [12] are estimated the dimensions of a rectangular board measuring 1.2 m × 0.9 m with a mean absolute error of 0.0194 m, demonstrating that the spectrum profile encodes geometric information that can be used to infer object shape. The approach presented in [4] resulted in the development of the BatVision system, which perceives deep spatial layouts by analyzing echoes recorded by two microphones acting as artificial ears. A dataset of paired acoustic chirps and depth images was collected using mobile robots, and an adversarial discriminator was trained to generate depth maps from audio signals. BatVision successfully predicted detailed indoor scenes and obstacles with an L1 loss as low as 0.072, in some cases outperforming stereo-vision-based depth mapping.

Building upon BatVision, the CatChatter system presented in [3] reports two main contributions. First, an improved version of BatVision was developed by removing an input encoder that processed acoustic spectrograms before reaching the adversarial discriminator; this encoder caused spatial information loss, reducing the inference capability of the U-Net. Second, a new system was introduced that uses LiDAR to generate 360-degree depth images and increases acoustic perception from two microphones to four, enabling echo capture from all directions. The results are comparable to those reported in [4], but the prediction field—due to the 360-degree depth information and additional microphones—was four times larger than that obtained with the stereo-vision and two-microphone configuration.

Acoustic sensing for detecting basic shapes and deformations is explored in [5], where the work identify and monitor small hollow objects from the inside. Deformations were introduced by altering object dimensions or blocking portions of the interior. A square-wave sound signal was emitted inside the objects, and a four-microphone array recorded the resulting echoes. Acoustic features were extracted from these signals and used to train a classifier capable of identifying object shape with 80% accuracy, detecting the presence of deformation with 100% accuracy, and localizing the deformation with 90% accuracy.

III. Methodology


To collect the acoustic response of an enclosed space while the position of an internal object is modified, an experimental box was constructed to generate the acoustic-location dataset used for training the CNN responsible for estimating the object's location inside the enclosure.

A. Experimental configuration

The experimental container is a cubic box with sides of 1 m and a volume close to $1\,\mathrm{m}^3$. The concept is shown in Figure 1(a). Three of its six walls are made of porcelain tiles with a thickness of 1 cm, one wall and the floor are made of solid concrete, and the remaining wall used for observation is made of acrylic with a thickness of 0.5 cm. The clear acrylic sheet allows direct observation of the movement mechanism inside the box. Unlike the other walls, which are permanently bonded, this acrylic wall can be removed to provide access to the interior of the measurement box.

The movement mechanism inside the box consists of a robotic arm mounted at the center of the floor. The arm has four degrees of freedom (DOF) and is used to move and change the position and orientation of a cube with a side length of 20 cm attached to its end. The cube is made of plastic, with walls 2 mm thick. For the measurements, a mono speaker is placed at the center of one wall to generate the

acoustic stimulus inside the system. On the opposite wall, four capacitive microphones are positioned 15 cm away from each corner to capture the acoustic response of the measurement box. The implementation of the measurement box was built inside a storage room and is shown in Figure 1(b).






Fig. 1: Measure box: (a) Conceptual sketch for the acoustic measurement box, and (b) actual implementation for the data acquisition task.

B. The Audio-Location Dataset

The dataset was collected over twenty-six recording sessions. In each session, the robotic arm maintained a fixed angular value at its base and positioned the cube at specific coordinates and orientations. The initial orientation of the cube was set such that its sides were parallel to the measurement box walls. The variables modified during each measurement were the cube's location and orientation. For each location, nine different orientations were recorded. After completing these nine measurements, the robotic arm lowered the cube by decreasing its position along the Z axis, and the recording process was repeated for the new location. This procedure continued until the cube reached the bottom of the measurement box.

Audio from four channels was recorded. The acoustic signal was emitted four times, and the response was captured one microphone at a time. Each recording session consisted of 270 recordings, each containing four channels. A change of 10 degrees in the base of the robotic arm defined each recording session, producing a cylindrical envelope for the measurement area.

The coordinates of each measurement, obtained from the robotic arm, are shown in Fig. 2. Each blue column in the three-dimensional plot corresponds to one recording session, and each point represents one of the nine orientations captured at that location. The total number of sessions was limited by the rotational constraint of the robotic arm's base, which allowed only 270 degrees of movement.




Fig. 2: Scatter plot of cube locations for each recording in the dataset for one of the folds, the blue columns represent the 26 sessions, and each point in the column represents the nine orientations captured at that location. The distribution of training and test points are pesentend in blue and red respectively.

The source audio signal was obtained by extracting an arbitrary 0.3-second segment from an acoustic melody. The spectrum of the signal has a bandwidth of up to 10 kHz, with the highest-magnitude components concentrated at low frequencies. Before reproducing the source signal, the recording process is initialized by opening the capture window for one

second. This procedure is repeated four times, once for each microphone. After completing the four recordings, the cube is moved to a new orientation until all nine possible orientations are covered, and then it is moved to a new location.

Because the recording start time is affected by the operating system scheduler, the signals from the four channels are aligned by exploiting the fact that the source-to-microphone distance is identical for each channel. Therefore, the magnitude of the direct sound can be used as a reference for alignment.

Second, a signal-integrity validation is performed to divide each recording into its main body and tail (reverberation segment). From the main segment, the signal power is computed, and from the tail, its duration is extracted. Signals whose power and tail length fall within predefined limits are considered valid and included in the dataset.

To train a CNN on the dataset, a Log-Mel transformation is applied to the audio signals to obtain spectrograms that can be used as input to the network. This results in four Log-Mel spectrogram images of 570×370 pixels for each location-orientation pair, as shown in Figure 3.




Fig. 3: Log-Mel spectograms correspondig of the four channels of signals captured at session 1, location X=22.8, Y=-0.94 , Z=-9.43 and orientation 50 degrees.

C. CNN Architecture for Estimation

The model architecture selected for the task of classifying and estimating the cube's location and orientation inside the measurement box was the ResNet-18 network, chosen for its robustness, simplicity, and suitability for inference in resource-constrained environments [13]. Two modifications were applied to the standard network structure. First, the input layer was extended to accept a stack of four RGB images, one corresponding to each channel. Second, for the regression task, the softmax output layer was replaced with a single output feature using a sigmoid activation function.

The collected dataset consists of 7020 samples, each composed of four images, one per channel. For training and validation, a five-fold approach was used. The dataset was split using an 80:20 ratio; as an example, Fig. 2 shows the training and test points for Fold 1, represented in blue and red, respectively. Training was performed for 40 epochs for both the classification and regression networks. The complete data-processing pipeline is shown in Figure 4.




Fig. 4: Diagram of the audio data processing pipe for the estimator.

IV. Results

A. Classification by Location and Orientation

First, the ability to classify the recordings in the database according to their location and orientation was evaluated. For the location-classification task, the 26 distinct session labels were used to train the CNN. The objective of this experiment was to determine whether, after training, the network could correctly classify in which session each recording was performed. After training, the network achieved an accuracy higher than 99% on the test sets across the five folds.

For the orientation-classification task, the dataset containing the nine distinct label values was used to train the network. The training procedure was identical to that of the location task, using 40 epochs. After training, the network achieved an accuracy no higher than 27.07% across the five folds, exhibiting a substantial number of misclassifications across the different orientations.

B. Location Estimation

To estimate the location along the X, Y, and Z coordinates, three independent networks were trained. In all cases, the standard ResNet output layer was replaced with a single sigmoid function to enable regression instead of classification. Additionally, the loss function was changed from cross-entropy, which is used for classification, to the MSE loss, since it operates on real-valued outputs and computes the squared error between the predicted and actual values, making it suitable for regression.

The networks were trained for 40 epochs and subsequently evaluated on each test set for the corresponding fold. Figure 5 shows the resulting histograms and density curves for the estimation errors produced by each CNN for its respective coordinate in Fold 1. From Figure 5, it can be observed that the

error histograms for X, Y, and Z are approximately symmetric around zero and resemble a normal distribution. The errors are concentrated between approximately -2 cm and 2 cm, with a few outliers beyond this range. The Z coordinate shows a wider spread of errors compared to X and Y, indicating that the network has more difficulty estimating the Z position of the cube in certain scenarios. Similar behavior is observed for the other folds.




Fig. 5: Histograms of the estimation errors for each coordinate with the test set after training.

The means and standard deviations for the histograms in Fig. 5 are presented in Table I. The three coordinates exhibit mean values close to zero, indicating that the estimations are unbiased. The standard deviation for X and Y is similar, approximately 0.8 cm, while the Z coordinate has a higher standard deviation of 1.05 cm, indicating that Z estimates are more dispersed. In all three cases, the standard deviation is below 2 cm. Considering 2σ as an evaluation metric, 95.44% of the total estimations fall below 1.56 cm of error in the X dimension, 1.42 cm in the Y dimension, and 2.11 cm in the Z dimension.

Variable	Mean (cm)	Sample SD (cm)
Error x	0.0590	0.7869
Error y	0.3232	0.7112
Error z	-0.1000	1.0577

TABLE I: Mean and standard deviation for the three coordinates X,Y and Z

Fig. 6 shows the boxplots for the three distributions. It can be observed that the estimation error is similar across the coordinates when outliers are excluded from the analysis. For the three boxes, the median is close to zero; the interquartile ranges are comparable for X and Y, while Z has a larger interquartile range. The whiskers represent 1.5 times the interquartile range, and outliers are shown as points beyond the whiskers.




Fig. 6: Box-plot of estimation error for the three coordinates X, Y and Z

The Mean Absolute Error (MAE) for the coordinates across the five folds is presented in table II, can be observed that the mean of the MAE for the five folds is less than 1cm for the three coordinates, having the lower values on Y and the higher on Z. Also the table III contains the mean of percentage of samples with estimation within an error range, From the table the percentages for Z are lower than the X and Y, but still arround of 92% the error are below $\pm 2cm$ for the Z coordinate.

To understand how the error relates to the cube's location inside the box, Fig. 7 shows the absolute error as a function of the three spatial coordinates for all points in the dataset that were included in the test set for each five-fold run. To facilitate visualization, error values are represented using a color scale, where blue indicates low error and red indicates high error. Outliers above 5 cm are shown in red, indicating

TABLE II: Mean Absolute Error (MAE) Across Folds for X, Y, and Z Coordinates

Folds	**MAE X (cm)**	**MAE Y (cm)**	**MAE Z (cm)**
Fold 1	0.6019	0.5029	1.3013
Fold 2	0.5231	0.4467	0.5549
Fold 3	0.5569	0.4069	0.8829
Fold 4	0.5764	0.3836	1.0473
Fold 5	0.5062	0.3144	0.7316
Mean $\pm$ SD	**0.5529 $\pm$ 0.0384**	**0.4109 $\pm$ 0.0706**	**0.9036 $\pm$ 0.2847**

TABLE III: Mean percentage of samples with estimation errors within specific ranges across 5 folds

	Five-Fold Mean (%)		
Error Range (cm)	X	Y	Z
$(-1, 1)$	87.69	92.90	64.44
$(-2, 2)$	97.83	98.32	91.98
$(-3, 3)$	99.05	99.52	97.97
$(-4, 4)$	99.42	99.69	99.45

a significantly higher error than the majority of the data. The plots show that the error is relatively uniformly distributed across the three dimensions, without clear hotspots or regions of higher misprediction. The absence of a strong pattern in the 3D error distribution suggests that the network's performance is relatively consistent across different locations inside the box. In regions where the test set contains points close together but the training set has a lower density, the error tends to be similar to that of nearby points, indicating that the network generalizes well in those areas.

To analyze the response of the networks along the three coordinates in more detail, the absolute estimation error as a function of the X, Y, and Z coordinates is plotted in Fig. 8. The estimation error is shown as a function of each coordinate while the other two coordinates vary but are not the focus of the analysis. X and Y exhibit a similar sample distribution along their respective axes, because the cube motion during data collection was circular in the X-Y plane, resulting in more points at the extremes of the axes. For Z, the cube was sampled more uniformly along the axis, with a similar density of points across the range. These plots show that, for all three coordinates, the magnitude of the estimation error increases toward both ends of the axis, being more pronounced in X and Y. This effect may be explained by the limited number of training samples in those regions. At the extremes, the network must learn the regression mapping using samples from only one side of the range, which makes the learning process more difficult.




Fig. 7: Absolute value of the error estimation for the three networks as function of the three coordinates X, Y and Z




Fig. 8: Estimation errors along the three coordinates X, Y and Z as function of the corresponding coordinate value.

V. Conclusion and Future Work

The experiments presented in this work demonstrate that, from the acoustic response recorded by an array of microphones, it is possible to locate an object within a confined space. Regarding the classification task based on the acoustic response, the results show that identifying whether an object is positioned within a particular region of the measurement box is a relatively straightforward task for a CNN trained on Log-Mel spectrograms. In contrast, the network exhibited poor performance when attempting to classify the specific orientation of the cube.

For the task of estimating the cube's position in a Cartesian coordinate system, the results indicate that the estimator behaves similarly across the three coordinates, although the estimation error varies slightly along each axis. The error distributions are approximately normal, with the Y coordinate achieving the lowest MAE, followed by X and then Z. The estimators for the three coordinates were capable of determining the cube's position within an error range of approximately ± 2 cm for a large number of points in the space.

This work did not consider the individual contribution of each channel; therefore, future research should explore the influence of each microphone on the overall estimation performance. Additionally, due to the motion restriction of the robotic arm, the X and Y samples were not uniformly distributed. It would therefore be valuable to include data augmentation or additional sampling to assess its impact on estimation performance in underrepresented regions. Finally, in the present work the estimation of coordinates was performed by independent networks; it would be interesting to evaluate a multi-head network that estimates the three coordinates simultaneously.

References

[1] L. Gionfrida, C. Wang, L. Gan, M. Chli, and L. Carlone, "Computer and robot vision: Past, present, and future [tc spotlight]," *IEEE Robotics and Automation Magazine*, vol. 31, no. 3, pp. 211–215, 2024.

[2] B. wildlife. (2025) What exactly is echolocation and how does it work? the incredible adaptation that allows animals to 'see' and communicate in the dark. [Online]. Available: https://www.discoverwildlife.com/animal-facts/what-is-echolocation

[3] E. Tracy and N. Kottege, "Catchatter: Acoustic perception for mobile robots," *IEEE Robotics and Automation Letters*, vol. 6, no. 4, pp. 7209–7216, 2021.

[4] A. Brunetto, S. Hornauer, S. X. Yu, and F. Moutarde, "The audio-visual batvision dataset for research on sight and sound," in *2023 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. IEEE, Oct. 2023, p. 1–8. [Online]. Available: http://dx.doi.org/10.1109/IROS55552.2023.10341715

[5] M. Rothstein, Z. Liu, and I. Bashima, "Echosense: Acoustic sensing for enclosed structure monitoring and recognition," in *2023 IEEE MIT Undergraduate Research Technology Conference (URTC)*, 2023, pp. 1–6.

[6] mordorintelligence. (2025) Usa maintenance repair & operations industry size & share analysis - growth trends & forecasts (2025 - 2030). [Online]. Available: https://www.mordorintelligence.com/industry-reports/united-states-maintenance-repair-and-operations-mro-market

[7] N. Peters, H. Lei, and G. Friedland, "Name that room: room identification using acoustic features in a recording," in *hola*, ser. MM '12. New York, NY, USA: Association for Computing Machinery, 2012, p. 841–844. [Online]. Available: https://doi.org/10.1145/2393347.2396326

[8] J. Bitterman, D. Levi, H. H. Diamandi, S. Gannot, and T. Rosenwein, "Revrir: Joint reverberant speech and room impulse response embedding using contrastive learning with application to room shape classification," 2024. [Online]. Available: https://arxiv.org/abs/2406.03120

[9] I. Dokmanić, R. Parhizkar, A. Walther, Y. M. Lu, and M. Vetterli, "Acoustic echoes reveal room shape," *Proceedings of the National Academy of Sciences*, vol. 110, no. 30, pp. 12 186–12 191, 2013. [Online]. Available: https://www.pnas.org/doi/abs/10.1073/pnas.1221464110

[10] T. A. Leticia Jaén, Fernando J. Álvarez and J. J. García, "Groom-level indoor positioning based on acoustic impulse response identification," *International Conference on Indoor Positioning and Indoor Navigation*, September 2017.

[11] M. Wang, S. Clarke, J.-H. Wang, R. Gao, and J. Wu, "Soundcam: A dataset for finding humans using room acoustics," 2024. [Online]. Available: https://arxiv.org/abs/2311.03517

[12] T. Manabe, R. Fukunaga, K. Nakatsuma, and M. Kumon, "Object surface recognition using microphone array by acoustic standing wave," in *2022 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2022, pp. 9274–9279.

[13] R. K. Bhogal and A. Singh, "A comprehensive review of resnet-18: Architecture and applications," in *Advances in Data-Driven Computing and Intelligent Systems*, J. C. Bansal, S. Saha, C. A. C. Coello, and H. Rathore, Eds. Singapore: Springer Nature Singapore, 2025, pp. 595–607.