## **Start application**

```
Prerequisitives:

- Java SE 8
- Maven

In Windows powershel:
```

mvn clean package; java -jar .\target\Jabber-0.0.1-SNAPSHOT.jar
\_.

In linux:

mvn clean package && java -jar ./target/Jabber-0.0.1-SNAPSHOT.jar

# Add message

Adding new message by user.

• URL

/:username/messages

Method:

POST

URL Params

#### Required:

```
username=[string]
```

• Data Params

```
{"messageText"="Message text example"}
```

- Success Response:
  - o **Code:** 204

**Content:** None

- Error Response:
  - o Code: 404 BAD REQUEST

Content: { error : "Invalid operation. Message to long." }

# List massages(wall)

List all user messages.

• URL

/:username/messages

• Method:

GET

URL Params

#### Required:

```
username=[string]
```

• Data Params

None

- Success Response:
  - o **Code:** 200

```
Content: [{"postingDate":"2018-02-20T09:38:27.204","creator":"user1","messageText":"Second example message."},{"postingDate":"2018-02-20T09:38:14.284","creator":"user1","messageText":"First example message."}]
```

- Error Response:
  - o **Code:** 404 BAD REQUEST

```
Content: { error : "User user1 not found." }
```

### Follow user

Follow user

• URL

/:username1/followee/:username2

• Method:

POST

URL Params

#### Required:

```
username1=[string]
username2=[string]
```

Data Params

None

• Success Response:

Code: 204Content: None

• Error Response:

o Code: 404 BAD REQUEST

Content: { error : "User user1 not found." }

### List followee massages(wall)

List all messages of followed ussers.

• URL

/:username/followee/messages

• Method:

GET

URL Params

#### Required:

username=[string]

• Data Params

None

- Success Response:
  - o **Code:** 200

```
Content: [{"postingDate":"2018-02-20T09:49:47.131","creator":"user2","messageText":"Second example message."},{"postingDate":"2018-02-20T09:49:35.271","creator":"user2","messageText":"First example message."}]
```

- Error Response:
  - o **Code:** 404 BAD REQUEST

```
Content: { error : "User user1 not found." }
```