SRE
Reference Guide

SRE-DOCS-200

October 2026

Version 2.0.0

Preface

Table of Contents

- **[CLI]** **sre** - *The main click's group to accumulate all the CLI commands*
  - **[Group]** **customer** - *Manages Syndicate Rule Engine Customer Entities*
    - **[Group]** **rabbitmq** - *Manages RabbitMQ configuration for a customer*
      - [Command] `add`
      - [Command] `describe`
    - [Command] `describe`
    - [Command] `get_excluded_rules`
    - [Command] `set_excluded_rules`
  - **[Group]** **integrations** - *Manages Integrations*
    - **[Group]** **chronicle** - *Manages chronicle integrations*
      - [Command] `activate`
      - [Command] `add`
      - [Command] `deactivate`
      - [Command] `delete`
      - [Command] `describe`
      - [Command] `get_activation`
    - **[Group]** **dojo** - *Manages defect dojo integrations*
      - [Command] `activate`
      - [Command] `add`
      - [Command] `deactivate`
      - [Command] `delete`
      - [Command] `describe`
      - [Command] `get_activation`
      - [Command] `update`
    - **[Group]** **event** - *Manages integrations for events*
      - **[Group]** **sources** - *Manages event sources for integrations*
        - [Command] `add`
        - [Command] `delete`
        - [Command] `describe`
        - [Command] `update`
    - **[Group]** **mcp** - *Manages MCP integrations*
      - **[Group]** **auth** - *Manages MCP JWT auth configuration*
        - [Command] `add`
        - [Command] `delete`
        - [Command] `describe`
        - [Command] `update`
    - **[Group]** **re** - *Manages Rule engine integration (self integration for Maestro)*
      - [Command] `add`
      - [Command] `describe`
  - **[Group]** **job** - *Manages jobs*
    - **[Group]** **scan** - *Submits a job to scan Cloud or K8S account*
      - [Command] `aws`
      - [Command] `azure`
      - [Command] `gcp`
      - [Command] `k8s`

        - **[Group] scheduled** - *Manages Job submit action*
            - [Command] `add`
            - [Command] `delete`
            - [Command] `describe`
            - [Command] `update`
        - [Command] `describe`
        - [Command] `resume`
        - [Command] `submit`
        - [Command] `submit_k8s`
        - [Command] `terminate`
    - **[Group] license** - *Manages License Entities*
        - [Command] `activate`
        - [Command] `add`
        - [Command] `deactivate`
        - [Command] `delete`
        - [Command] `describe`
        - [Command] `get_activation`
        - [Command] `sync`
        - [Command] `update_activation`
    - **[Group] metadata** - *Manages locally stored metadata*
        - [Command] `update`
    - **[Group] metrics** - *Manages Scan and Tenant Metrics*
        - [Command] `update`
    - **[Group] platform** - *Manages K8S platforms*
        - **[Group] k8s** - *Manages kubernetes platforms*
            - [Command] `create`
            - [Command] `delete`
            - [Command] `describe`
            - [Command] `update`
    - **[Group] policy** - *Manages Entities*
        - [Command] `add`
        - [Command] `delete`
        - [Command] `describe`
        - [Command] `update`
    - **[Group] report** - *Manages reports*
        - **[Group] compliance** - *Describes compliance reports*
            - [Command] `accumulated`
            - [Command] `jobs`
        - **[Group] details** - *Describes detailed undigested reports*
            - [Command] `jobs`
        - **[Group] digests** - *Describes summaries of job reports*
            - [Command] `jobs`
        - **[Group] errors** - *Describes error reports*
            - [Command] `jobs`
        - **[Group] findings** - *Describes findings reports*
            - [Command] `jobs`
        - **[Group] push** - *Pushes job reports to SIEMs*

        - [Command] `chronicle`
        - [Command] `dojo`
    - **[Group] questionnaire** - *Describes standard questionnaire reports*
        - [Command] `accumulated`
        - [Command] `jobs`
    - **[Group] raw** - *Fetches raw report*
        - [Command] `latest`
    - **[Group] resource** - *Generate resource reports*
        - [Command] `job`
        - [Command] `jobs`
        - [Command] `latest`
        - [Command] `platform_latest`
    - **[Group] rules** - *Describes rule reports of jobs*
        - [Command] `accumulated`
        - [Command] `jobs`
    - [Command] `status`
- **[Group] resource** - *Manages resources*
    - **[Group] exception** - *Manages resource exception*
        - [Command] `add`
        - [Command] `delete`
        - [Command] `describe`
        - [Command] `update`
    - [Command] `describe`
    - [Command] `describe_platform`
- **[Group] role** - *Manages Role Entity*
    - [Command] `add`
    - [Command] `delete`
    - [Command] `describe`
    - [Command] `update`
- **[Group] rule** - *Manages Rule Entity*
    - [Command] `delete`
    - [Command] `describe`
    - [Command] `update`
- **[Group] ruleset** - *Manages Customer rulesets*
    - [Command] `add`
    - [Command] `delete`
    - [Command] `describe`
    - [Command] `release`
    - [Command] `update`
- **[Group] rulesource** - *Manages Rule Source entity*
    - [Command] `add`
    - [Command] `delete`
    - [Command] `describe`
    - [Command] `sync`
    - [Command] `update`
- **[Group] service** - *Manages Services*
    - **[Group] operations** - *Manages Service Operations*

        - [Command] `status`
- **[Group]** **setting** - *Manages Settings*
    - **[Group]** **lm** - *Manages License Manager Setting(s)*
        - **[Group]** **client** - *Manages License Manager Client data*
            - [Command] `add`
            - [Command] `delete`
            - [Command] `describe`
            - [Command] `update`
        - **[Group]** **config** - *Manages License Manager Config data*
            - [Command] `add`
            - [Command] `delete`
            - [Command] `describe`
            - [Command] `update`
    - **[Group]** **mail** - *Manages Mail configuration*
        - [Command] `add`
        - [Command] `delete`
        - [Command] `describe`
    - **[Group]** **report** - *Manages Syndicate Rule Engine configuration*
        - [Command] `disable_sending`
        - [Command] `enable_sending`
- **[Group]** **tenant** - *Manages Tenant Entity*
    - **[Group]** **credentials** - *Allows to bind existing credentials applications to tenants*
        - [Command] `describe`
        - [Command] `get_linked_tenants`
        - [Command] `link`
        - [Command] `unlink`
    - [Command] `active_licenses`
    - [Command] `describe`
    - [Command] `get_excluded_rules`
    - [Command] `set_excluded_rules`
- **[Group]** **users** - *Manages Rule Engine users. Only for system customer*
    - [Command] `change_password`
    - [Command] `create`
    - [Command] `delete`
    - [Command] `describe`
    - [Command] `update`
- [Command] `cleanup` - *Removes all the configuration data related to the tool*
- [Command] `configure` - *Configures sre tool to work with Syndicate Rule Engine*
- [Command] `health_check` - *Checks SRE components availability*
- [Command] `login` - *Authenticates user to work with Syndicate Rule Engine*
- [Command] `show_config` - *Returns the cli configuration*
- [Command] `whoami` - *Returns information about the current user*

Detailed Command Reference

Group: sre

Description:

The main click's group to accumulate all the CLI commands

Usage:

```
sre [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--version	flag	✗	False	Show the version and exit.

↑ Back to Table of Contents

Group: sre customer

Description:

Manages Syndicate Rule Engine Customer Entities

Usage:

```
sre customer
```

↑ Back to Table of Contents

Group: sre customer rabbitmq

Description:

Manages RabbitMQ configuration for a customer

Usage:

```
sre customer rabbitmq
```

↑ Back to Table of Contents

Command: sre customer rabbitmq add

Description:

Creates rabbitMQ configuration for your customer

Usage:

```
sre customer rabbitmq add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--maestro_user, -mr	string	✓	-	Maestro user
--rabbit_exchange, -re	string	✗	-	Rabbit exchange
--request_queue, -req	string	✓	-	Request queue

Option	Type	Req	Default	Description
--response_queue, -res	string	✓	-	Response queue
--sdk_access_key, -sak	string	✓	-	SDK Access key
--connection_url, -url	string	✓	-	Rabbit connection url
--sdk_secret_key, -ssk	string	✓	-	SDK Secret key
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre customer rabbitmq describe

Description:

Describes rabbitMQ configuration for your customer

Usage:

```
sre customer rabbitmq describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre customer describe

Description:

Describes your user's customer

Usage:

```
sre customer describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre customer get_excluded_rules

Description:

Returns excluded rules for a customer

Usage:

```
sre customer get_excluded_rules [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre customer set_excluded_rules

Description:

Excludes rules for a customer

Usage:

```
sre customer set_excluded_rules [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rules, -r	string	✗	-	Rules that you want to exclude for a customer. They will be excluded for each tenant [multiple]
--empty	flag	✗	False	Whether to reset the list of excluded rules
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre integrations

Description:

Manages Integrations

Usage:

```
sre integrations
```

↑ Back to Table of Contents

Group: sre integrations chronicle

Description:

Manages chronicle integrations

Usage:

```
sre integrations chronicle
```

↑ Back to Table of Contents

Command: sre integrations chronicle activate

Description:

Activates a concrete Chronicle integration for a specific set of tenants. Each activation overrides the existing one

Usage:

```
sre integrations chronicle activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of Chronicle integration
--tenant_name, -tn	string	✗	-	Name of related tenant [multiple]
--all_tenants	flag	✗	False	Whether to activate integration for all tenants
--clouds, -c	choice	✗	-	Tenant clouds to activate this dojo for. Can be specific together with –all_tenants flag [multiple]. Available choices: AWS, AZURE, GOOGLE, KUBERNETES
--exclude_tenant, -et	string	✗	-	Tenants to exclude for this integration. Can be specified together with –all_tenants flag [multiple]
--send_after_job, -saj	flag	✗	False	Specify this flag to send results to dojo after each job automatically
--convert_to, -ct	choice	✗	EVENTS	The way Rule engine findings will be converted before sending to Chronicle. Available choices: EVENTS, ENTITIES
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations chronicle add

Description:

Adds Chronicle integration

Usage:

```
sre integrations chronicle add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--url, -u	string	✓	-	Base url for Google Chronicle integration (https://region.googleapis.com
--description, -d	string	✓	-	Human-readable description of this installation
--credentials_application_id, -cai	string	✓	-	Id of application with google credentials
--instance_customer_id, -ici	string	✓	-	Customer id of Chronicle instance
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations chronicle deactivate

Description:

Deactivates a concrete Chronicle integration for a specific set of tenants

Usage:

```
sre integrations chronicle deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of Chronicle integration
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations chronicle delete

Description:

Deletes Chronicle integration

Usage:

```
sre integrations chronicle delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of Chronicle integration
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations chronicle describe

Description:

Describes Chronicle integration

Usage:

```
sre integrations chronicle describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✗	-	Id of Chronicle integration
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations chronicle get_activation

Description:

Returns a Chronicle activation

Usage:

```
sre integrations chronicle get_activation [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of Chronicle integration
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre integrations dojo

Description:

Manages defect dojo integrations

Usage:

```
sre integrations dojo
```

↑ Back to Table of Contents

Command: sre integrations dojo activate

Description:

Activates a concrete dojo integration for a specific set of tenants. Each activation overrides the existing one

Usage:

```
sre integrations dojo activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of dojo integration
--tenant_name, -tn	string	✗	-	Name of related tenant [multiple]
--all_tenants	flag	✗	False	Whether to activate integration for all tenants
--clouds, -c	choice	✗	-	Tenant clouds to activate this dojo for. Can be specific together with –all_tenants flag [multiple]. Available choices: AWS, AZURE, GOOGLE, KUBERNETES
--exclude_tenant, -et	string	✗	-	Tenants to exclude for this integration. Can be specified together with –all_tenants flag [multiple]
--scan_type, -st	choice	✗	Generic Findings ...	Defect Dojo scan type. Generic Findings Import can be used with open source DefectDojo whereas Cloud Custodian Scan - with EPAM's fork. Available choices: Generic Findings Import, Cloud Custodian Scan
--send_after_job, -saj	flag	✗	False	Specify this flag to send results to dojo after each job automatically
--product_type	string	✗	Rule Engine	Product type to create in Dojo, "Rule Engine" is used by default. "tenant_name", "customer_name" and "job_id" can be used as generic placeholders inside curly brackets
--product	string	✗	{tenant_name}	Product name to create in Dojo, "{tenant_name}" is used by default
--engagement	string	✗	Rule-Engine Main	Engagement name to create in Dojo. "Rule-Engine Main" is used by default
--test	string	✗	{job_id}	Test name to create in Dojo, "{job_id}" is used by default
--attachment	choice	✗	-	What type of file with resources to attach to each finding. If not provided, no files will be attached, resources will be displayed in description. Available choices: json, xlsx, csv
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file

Option	Type	Req	Default	Description
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations dojo add

Description:

Adds dojo integration

Usage:

```
sre integrations dojo add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--url, -u	string	✓	-	Url to defect dojo installation. With API prefix (http://127.0.0.1:8080/api/v2
--api_key, -ak	string	✓	-	Defect dojo api key
--description, -d	string	✓	-	Human-readable description of this installation
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations dojo deactivate

Description:

Deactivates a concrete dojo integration for a specific set of tenants

Usage:

```
sre integrations dojo deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of dojo integration
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations dojo delete

Description:

Deletes Dojo integration

Usage:

```
sre integrations dojo delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of dojo integration
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations dojo describe

Description:

Describes Dojo integration

Usage:

```
sre integrations dojo describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✗	-	Id of dojo integration
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations dojo get_activation

Description:

Returns a dojo activation

Usage:

```
sre integrations dojo get_activation [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of dojo integration
--json	flag	✗	False	Response as a JSON

Option	Type	Req	Default	Description
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations dojo update

Description:

Update a dojo activation.

Usage:

```
sre integrations dojo update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--integration_id, -id	string	✓	-	Id of dojo integration
--tenant_name, -tn	string	✗	-	Tenants to include for this integration [multiple]
--exclude_tenant, -et	string	✗	-	Tenants to exclude for this integration. [multiple]
--clouds, -c	choice	✗	-	Tenant clouds to activate this dojo for. Can be specific if –all_tenants flag is on at this integration [multiple]. Available choices: AWS, AZURE, GOOGLE, KUBERNETES
--scan_type, -st	choice	✗	-	Defect Dojo scan type. Generic Findings Import can be used with open source DefectDojo whereas Cloud Custodian Scan - with EPAM's fork. Available choices: Generic Findings Import, Cloud Custodian Scan
--send_after_job, -saj	choice	✗	-	Enter "yes" or "not" to toggle the flag to send results to the dojo after each job automatically. Available choices: yes, not
--product_type	string	✗	-	Product type to update in Dojo. "tenant_name", "customer_name" and "job_id" can be used as generic placeholders inside curly brackets
--product	string	✗	-	Product name to update in Dojo.
--engagement	string	✗	-	Engagement name to update in Dojo.
--test	string	✗	-	Test name to create in Dojo.
--attachment	choice	✗	-	What type of file with resources to attach to each finding. If not provided, no files will be attached, resources will be displayed in description. Available choices: json, xlsx, csv
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre integrations event

Description:

Manages integrations for events

Usage:

```
sre integrations event
```

↑ Back to Table of Contents

Group: sre integrations event sources

Description:

Manages event sources for integrations

Usage:

```
sre integrations event sources
```

↑ Back to Table of Contents

Command: sre integrations event sources add

Description:

Creates an SQS event source configuration.

Usage:

```
sre integrations event sources add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--queue_url, -qu	string	✓	-	SQS queue URL
--region, -r	string	✓	-	AWS region
--enabled, -e	boolean	✗	True	Param to enable or disable the event source temporarily
--aws_access_key_id	string	✗	-	AWS access key (optional)
--aws_secret_access_key	string	✗	-	AWS secret key (optional)
--aws_session_token	string	✗	-	AWS session token for temporary creds (optional)
--role_arn, -ra	string	✗	-	IAM role ARN to assume for SQS access (optional, uses instance profile as base)
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations event sources delete

Description:

Deletes an event source by ID

Usage:

```
sre integrations event sources delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--event_source_id, -esid	string	✓	-	Event source ID
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations event sources describe

Description:

Lists SQS event sources or describes one by event_source_id.

Usage:

```
sre integrations event sources describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--event_source_id, -esid	string	✗	-	Event source ID. If provided, describes a specific event source.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations event sources update

Description:

Updates an SQS event source configuration.

Usage:

```
sre integrations event sources update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--event_source_id, -esid	string	✓	-	Event source ID to update
--queue_url, -qu	string	✗	-	SQS queue URL
--region, -r	string	✗	-	AWS region

Option	Type	Req	Default	Description
--enabled, -e	boolean	✗	-	Param to enable or disable the event source temporarily
--role_arn, -ra	string	✗	-	IAM role ARN to assume for SQS access
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre integrations mcp

Description:

Manages MCP integrations

Usage:

```
sre integrations mcp
```

↑ Back to Table of Contents

Group: sre integrations mcp auth

Description:

Manages MCP JWT auth configuration

Usage:

```
sre integrations mcp auth
```

↑ Back to Table of Contents

Command: sre integrations mcp auth add

Description:

Adds MCP JWT auth configuration. Only one configuration is allowed.

Usage:

```
sre integrations mcp auth add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--jwt, -j	string	✓	-	JWT verification key. If not provided, will be prompted for securely
--algorithm, -alg	string	✗	RS256	JWT signing algorithm
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations mcp auth delete

Description:

Removes current MCP JWT auth configuration

Usage:

```
sre integrations mcp auth delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations mcp auth describe

Description:

Describes current MCP JWT auth configuration

Usage:

```
sre integrations mcp auth describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations mcp auth update

Description:

Updates existing MCP JWT auth configuration

Usage:

```
sre integrations mcp auth update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--jwt, -j	string	✗	-	JWT verification key. Use –prompt_jwt instead of this option to enter the key securely without exposing it in the command

Option	Type	Req	Default	Description
--prompt_jwt, -pj	flag	✗	False	Prompt for the JWT verification key securely (input hidden) instead of passing it via –jwt
--algorithm, -alg	string	✗	-	JWT signing algorithm
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre integrations re

Description:

Manages Rule engine integration (self integration for Maestro)

Usage:

```
sre integrations re
```

↑ Back to Table of Contents

Command: sre integrations re add

Description:

Adds self integration

Usage:

```
sre integrations re add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✗	-	Name of related tenant [multiple]
--all_tenants	flag	✗	False	Whether to activate integration for all tenants
--clouds, -c	choice	✗	-	Tenant clouds to activate the service for. Can be specified together with –all_tenants flag [multiple]. Available choices: AWS, AZURE, GOOGLE, KUBERNETES
--exclude_tenant, -et	string	✗	-	Tenants to exclude for this integration. Can be specified together with –all_tenants flag [multiple]
--description, -d	string	✓	-	Human-readable description of this installation
--username, -u	string	✓	-	Username to set to the application
--password, -p	string	✓	-	Password to set to application
--url, -U	string	✗	-	Url to SRE installation
--auto_resolve_access, -ara	flag	✗	False	If specified, SRE will try to resolve access automatically. Otherwise you must specify url
--results_storage, -rs	string	✗	-	S3 bucket name were to store EC2 recommendations

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre integrations re describe

Description:

Describes self integration

Usage:

```
sre integrations re describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre job

Description:

Manages jobs

Usage:

```
sre job
```

↑ Back to Table of Contents

Group: sre job scan

Description:

Submits a job to scan Cloud or K8S account

Usage:

```
sre job scan
```

↑ Back to Table of Contents

Command: sre job scan aws

Description:

Submit a job to scan an AWS tenant.

Usage:

```
sre job scan aws [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available by license rulesets will be used [multiple]
--region, -r	string	✗	-	Regions to scan. If not specified, all active regions will be used [multiple]
--rules_to_scan	string	✗	-	Rules that must be scanned. Ruleset must contain them. You can specify some subpart of rule names. SRE will try to resolve the full names: aws-002 -> ecc-aws-002-encryption… Also you can specify some part that is common to multiple rules. All the them will be resolved: postgresql -> [ecc-aws-001-postgresql…, ecc-aws-002-postgresql…]. This CLI param can accept both raw rule names and path to file with JSON list of rules [multiple]
--license_key, -lk	string	✗	-	License key to utilize for this job in case an ambiguous situation occurs
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is

Option	Type	Req	Default	Description
				configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--access_key_id	string	✗	-	AWS access key
--secret_access_key	string	✗	-	AWS secret key
--session_token	string	✗	-	AWS session token
--resolve_local_credentials	flag	✗	False	Flag to resolve credentials that can be found in the cli session
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job scan azure

Description:

Submit a job to scan an Azure tenant.

Usage:

```
sre job scan azure [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available by license rulesets will be used [multiple]
--region, -r	string	✗	-	Regions to scan. If not specified, all active regions will be used [multiple]
--rules_to_scan	string	✗	-	Rules that must be scanned. Ruleset must contain them. You can specify some subpart of rule names. SRE will try to resolve the full names: aws-002 -> ecc-aws-002-encryption… Also you can specify some part that is common to multiple rules. All the them will be resolved: postgresql -> [ecc-aws-001-postgresql…, ecc-aws-002-postgresql…]. This CLI param can accept both raw rule names and path to file with JSON list of rules [multiple]
--license_key, -lk	string	✗	-	License key to utilize for this job in case an ambiguous situation occurs
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be

Option	Type	Req	Default	Description
				used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--subscription_id	string	✗	-	Azure subscription id
--tenant_id	string	✗	-	Azure tenant id
--client_id	string	✗	-	Azure client id
--client_secret	string	✗	-	Azure client secret
--resolve_local_credentials	flag	✗	False	Flag to resolve credentials that can be found in the cli session
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job scan gcp

Description:

Submit a job to scan a Google Cloud tenant.

Usage:

```
sre job scan gcp [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available by license rulesets will be used [multiple]
--region, -r	string	✗	-	Regions to scan. If not specified, all active regions will be used [multiple]
--rules_to_scan	string	✗	-	Rules that must be scanned. Ruleset must contain them. You can specify some subpart of rule names. SRE will try to resolve the full names: aws-002 -> ecc-aws-002-encryption… Also you can specify some part that is common to multiple rules. All the them will be resolved: postgresql -> [ecc-aws-001-postgresql…, ecc-aws-002-postgresql…]. This CLI param can accept both raw rule names and path to file with JSON list of rules [multiple]
--license_key, -lk	string	✗	-	License key to utilize for this job in case an ambiguous

Option	Type	Req	Default	Description
				situation occurs
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--application_credentials_path	string	✗	-	Path to file with google credentials
--resolve_local_credentials	flag	✗	False	Flag to resolve credentials that can be found in the cli session
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job scan k8s

Description:

Submit a job to scan a Kubernetes cluster.

Usage:

```
sre job scan k8s [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
-pid, --platform_id	string	✓	-	-
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available by license rulesets will be used [multiple]
--license_key, -lk	string	✗	-	License key to utilize for this job in case an ambiguous situation occurs
--token, -t	string	✗	-	Short-lived token to perform k8s scan with
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly

Option	Type	Req	Default	Description
				brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Group: sre job scheduled

Description:

Manages Job submit action

Usage:

```
sre job scheduled
```

↑ Back to Table of Contents

Command: sre job scheduled add

Description:

Registers a scheduled job

Usage:

```
sre job scheduled add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✗	-	Name of related tenant
--schedule, -sch	string	✓	-	Cron or Rate, 20 minutes expression: “cron(0 20 * * *)“. One execution per two hours:”rate(2 hours)”
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available rulesets will be used [multiple]
--description, -d	string	✓	-	Description for this scheduled job entry
--region, -r	string	✗	-	Regions to scan. If not specified, all active regions will be used [multiple]
--name, -n	string	✗	-	Name for the scheduled job. Must be unique. If not given, will be generated automatically
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job scheduled delete

Description:

Removes a scheduled job

Usage:

```
sre job scheduled delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Scheduled job name to remove
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job scheduled describe

Description:

Describes registered scheduled jobs

Usage:

```
sre job scheduled describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✗	-	Scheduled job name to describe
--tenant_name, -tn	string	✗	-	Name of related tenant
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job scheduled update

Description:

Updates an existing scheduled job

Usage:

```
sre job scheduled update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Scheduled job name to update
--schedule, -sch	string	✗	-	Cron or Rate expression: cron(0 20 * * *), rate(2 minutes)
--enabled, -e	boolean	✗	-	Param to enable or disable the job temporarily
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job describe

Description:

Describes Scans

Usage:

```
sre job describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✗	-	Job id to describe
--tenant_name, -tn	string	✗	-	Name of related tenant
--status, -s	choice	✗	-	Status to query jobs by. Available choices: SUBMITTED, PENDING, RUNNABLE, STARTING, RUNNING, FAILED, SUCCEEDED, INTERRUPTED
--from_date, -from	string	✗	-	Query jobs from this date. Accepts date ISO string. Example: 2026-09-13
--to_date, -to	string	✗	-	Query jobs till this date. Accepts date ISO string. Example: 2026-11-12
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job resume

Description:

Resubmits a standard scan job that has partial progress stored in S3/DynamoDB.

Usage:

```
sre job resume [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Job id to resume (checkpoint required; INTERRUPTED, FAILED, or stale RUNNING)
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job submit

Description:

Submits a job to scan either AWS, AZURE or GOOGLE account

Usage:

```
sre job submit [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available by license rulesets will be used [multiple]
--region, -r	string	✗	-	Regions to scan. If not specified, all active regions will be used [multiple]
--rules_to_scan	string	✗	-	Rules that must be scanned. Ruleset must contain them. You can specify some subpart of rule names. SRE will try to resolve the full names: aws-002 -> ecc-aws-002-encryption… Also you can specify some part that is common to multiple rules. All the them will be resolved: postgresql -> [ecc-aws-001-postgresql…, ecc-aws-002-postgresql…]. This CLI param can accept both raw rule names and path to file with JSON list of rules [multiple]
--license_key, -lk	string	✗	-	License key to utilize for this job in case an ambiguous situation occurs
--aws_access_key_id	string	✗	-	AWS access key
--aws_secret_access_key	string	✗	-	AWS secret key
--aws_session_token	string	✗	-	AWS session token
--azure_subscription_id	string	✗	-	Azure subscription id
--azure_tenant_id	string	✗	-	Azure tenant id
--azure_client_id	string	✗	-	Azure client id
--azure_client_secret	string	✗	-	Azure client secret
--	string	✗	-	Path to file with google credentials

Option	Type	Req	Default	Description
google_application_credentials_path				
--resolve_local_credentials	flag	✗	False	Flag to resolve credentials that can be found in the cli session
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job submit_k8s

Description:

Submits a job for kubernetes cluster

Usage:

```
sre job submit_k8s [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
-pid, --platform_id	string	✓	-	-
--ruleset, -rs	string	✗	-	Rulesets to scan. If not specified, all available by license rulesets will be used [multiple]
--license_key, -lk	string	✗	-	License key to utilize for this job in case an ambiguous situation occurs
--token, -t	string	✗	-	Short-lived token to perform k8s scan with
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly

Option	Type	Req	Default	Description
				brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre job terminate

Description:

Terminates Scan

Usage:

```
sre job terminate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Job id to terminate
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Group: sre license

Description:

Manages License Entities

Usage:

```
sre license
```

↑ Back to Table of Contents

Command: sre license activate

Description:

Activates a concrete license for a specific set of tenants. Each activation overrides the existing one

Usage:

```
sre license activate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✓	-	License key
--tenant_name, -tn	string	✗	-	Name of related tenant [multiple]
--all_tenants	flag	✗	False	Whether to activate integration for all tenants
--clouds, -c	choice	✗	-	Tenant clouds to activate this license for. Can be specific together with –all_tenants flag [multiple]. Available choices: AWS, AZURE, GOOGLE, KUBERNETES
--exclude_tenant, -et	string	✗	-	Tenants to exclude for this integration. Can be specified together with –all_tenants flag [multiple]
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license add

Description:

Adds a license from License Manager to the system. After performing this action licensed rulesets will appear and will be ready to use

Usage:

```
sre license add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_license_key, -tlk	string	✓	-	License key to create
--json	flag	✗	False	Response as a JSON

Option	Type	Req	Default	Description
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license deactivate

Description:

Deactivates a concrete license for a specific set of tenants

Usage:

```
sre license deactivate [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✓	-	License key
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license delete

Description:

Deletes Licenses

Usage:

```
sre license delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✓	-	License key to delete
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license describe

Description:

Describes licenses

Usage:

```
sre license describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✗	-	License key to describe
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license get_activation

Description:

Returns license activation

Usage:

```
sre license get_activation [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✓	-	License key
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license sync

Description:

Synchronizes Licenses

Usage:

```
sre license sync [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✓	-	License key to synchronize
--overwrite_rulesets, -or	flag	✗	False	Overwrite existing rulesets in S3 even if they already exist
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file

Option	Type	Req	Default	Description
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre license update_activation

Description:

Allows to add and remove specific tenants from the activation

Usage:

```
sre license update_activation [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--license_key, -lk	string	✓	-	License key
--add_tenant, -at	string	✗	-	Tenants to activate [multiple]
--exclude_tenant, -et	string	✗	-	Tenants to deactivate [multiple]
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre metadata

Description:

Manages locally stored metadata

Usage:

```
sre metadata
```

↑ Back to Table of Contents

Command: sre metadata update

Description:

Triggers a complete synchronization with License Manager for all customers.

This updates: - Rule metadata (severity, category, MITRE mappings, standards, remediation) - License information (description, allowance, event_driven settings, validity dates) - Rulesets (downloads compiled ruleset files from License Manager to S3) - Ruleset metadata in DB (versions, license associations)

Usage:

```
sre metadata update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre metrics

Description:

Manages Scan and Tenant Metrics

Usage:

```
sre metrics
```

↑ Back to Table of Contents

Command: sre metrics update

Description:

Triggers a metrics update for Syndicate Rule Engine reports. Report data will contain data up to the time when the trigger was executed

Usage:

```
sre metrics update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre platform

Description:

Manages K8S platforms

Usage:

```
sre platform
```

↑ Back to Table of Contents

Group: sre platform k8s

Description:

Manages kubernetes platforms

Usage:

```
sre platform k8s
```

↑ Back to Table of Contents

Command: sre platform k8s create

Description:

Register a new K8S Platform within a tenant. Note: insecure_skip_tls_verify is automatically enabled if certificate_authority is not provided.

Usage:

```
sre platform k8s create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
-n, --name	string	✓	-	Cluster name
-t, --type	choice	✓	-	Cluster type. Available choices: SELF_MANAGED, EKS, AKS, GKS
-r, --region	string	✗	-	Cluster region in case the cluster is bound to a cloud
-d, --description	string	✓	-	K8s platform description
-e, --endpoint	string	✗	-	K8s endpoint
-ca, --certificate_authority	string	✗	-	Certificate authority base64 encoded string
-T, --token	string	✗	-	Long lived token. Short-lived tokens will be generated base on this one
--insecure_skip_tls_verify	flag	✗	False	Skip TLS certificate verification. Auto-enabled if –certificate_authority is not provided
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre platform k8s delete

Description:

Deregister a platform

Usage:

```
sre platform k8s delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
-pid, --platform_id	string	✓	-	Platform id
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre platform k8s describe

Description:

List registered K8S platforms

Usage:

```
sre platform k8s describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✗	-	Name of related tenant
--event_driven_enabled, -ede	boolean	✗	-	Optional filter by event-driven status
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre platform k8s update

Description:

Update K8S platform event-driven settings.

Usage:

```
sre platform k8s update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
-pid, --platform_id	string	✓	-	Platform id
--event_driven_enabled, -ede	boolean	✓	-	Enable or disable event-driven for this platform
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre policy

Description:

Manages Entities

Usage:

```
sre policy
```

↑ Back to Table of Contents

Command: sre policy add

Description:

Creates a policy for a customer

Usage:

```
sre policy add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Policy name to create
--permission, -p	string	✗	-	List of permissions to attach to the policy [multiple]
--path_to_permissions, -path	string	✗	-	Local path to .json file that contains list of permissions to attach to the policy
--permissions_admin, -admin	flag	✗	False	Whether to add all permissions to this policy
--effect, -ef	choice	✓	-	That this policy will do. Available choices: allow, deny
--tenant, -t	string	✓	-	Permission will be allowed or denied for these tenants. Specify tenant name. '*' to allow or deny for all tenants [multiple]
--description, -d	string	✓	-	Description for this policy
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre policy delete

Description:

Deletes a policy of a customer

Usage:

```
sre policy delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Policy name to delete
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre policy describe

Description:

Describes policies of a customer

Usage:

```
sre policy describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✗	-	Policy name to describe.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre policy update

Description:

Updates permission-list within a policy

Usage:

```
sre policy update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	-
--attach_permission, -ap	string	✗	-	Names of permissions to attach to the policy [multiple]
--detach_permission, -dp	string	✗	-	Names of permissions to detach from the policy [multiple]
--effect, -ef	choice	✗	-	That this policy will do. Available choices: allow, deny
--add_tenant, -at	string	✗	-	Add these tenants. Specify tenant name [multiple]
--remove_tenant, -rt	string	✗	-	Remove these tenants. Specify tenant name [multiple]
--description, -d	string	✗	-	Description for this policy

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report

Description:

Manages reports

Usage:

```
sre report
```

↑ Back to Table of Contents

Group: sre report compliance

Description:

Describes compliance reports

Usage:

```
sre report compliance
```

↑ Back to Table of Contents

Command: sre report compliance accumulated

Description:

Describes tenant-specific compliance report

Usage:

```
sre report compliance accumulated [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--format, -ft	choice	✗	json	Format of the file behind the presigned reference. Available choices: json, xlsx
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report compliance jobs

Description:

Describes job compliance reports

Usage:

```
sre report compliance jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Unique job identifier
--format, -ft	choice	✗	json	Format of the file behind the presigned reference. Available choices: json, xlsx
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report details

Description:

Describes detailed undigested reports

Usage:

```
sre report details
```

↑ Back to Table of Contents

Command: sre report details jobs

Description:

Describes detailed reports of jobs

Usage:

```
sre report details jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✗	-	Unique job identifier
--job_type, -jt	choice	✗	-	Specify type of jobs to retrieve (manual type is deprecated and it will be removed). The option is applicable only with --tenant_name [multiple]. Available choices: manual, reactive, scheduled, standard
--tenant_name, -tn	string	✗	-	Name of related tenant
--from_date, -from	isoparse	✗	-	Generate report FROM date. ISO 8601 format. Example: 2026-11-12T00:00:00
--to_date, -to	isoparse	✗	-	Generate report TILL date. ISO 8601 format. Example: 2026-11-12T00:00:00
--obfuscated	flag	✗	False	Whether to obfuscate the data and return also a dictionary
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file

Option	Type	Req	Default	Description
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report digests

Description:

Describes summaries of job reports

Usage:

```
sre report digests
```

↑ Back to Table of Contents

Command: sre report digests jobs

Description:

Describes summary reports of jobs

Usage:

```
sre report digests jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✗	-	Unique job identifier
--job_type, -jt	choice	✗	-	Specify type of jobs to retrieve (manual type is deprecated and it will be removed). The option is applicable only with --tenant_name [multiple]. Available choices: manual, reactive, scheduled, standard
--tenant_name, -tn	string	✗	-	Name of related tenant
--from_date, -from	isoparse	✗	-	Generate report FROM date. ISO 8601 format. Example: 2026-11-12T00:00:00
--to_date, -to	isoparse	✗	-	Generate report TILL date. ISO 8601 format. Example: 2026-11-12T00:00:00
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report errors

Description:

Describes error reports

Usage:

```
sre report errors
```

↑ Back to Table of Contents

Command: sre report errors jobs

Description:

Describes errors report of a specific job

Usage:

```
sre report errors jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Unique job identifier
--error_type, -et	choice	✗	-	Available choices: SKIPPED, ACCESS, CREDENTIALS, CLIENT, INTERNAL
--format, -ft	choice	✗	json	Format of the file behind the presigned reference. Available choices: json, xlsx
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report findings

Description:

Describes findings reports

Usage:

```
sre report findings
```

↑ Back to Table of Contents

Command: sre report findings jobs

Description:

Describes detailed reports of jobs

Usage:

```
sre report findings jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✗	-	Unique job identifier
--job_type, -jt	choice	✗	-	Specify type of jobs to retrieve (manual type is deprecated and it will be removed). The option is applicable only with --tenant_name [multiple]. Available

Option	Type	Req	Default	Description
				choices: manual, reactive, scheduled, standard
--tenant_name, -tn	string	✗	-	Name of related tenant
--from_date, -from	isoparse	✗	-	Generate report FROM date. ISO 8601 format. Example: 2026-11-12T00:00:00
--to_date, -to	isoparse	✗	-	Generate report TILL date. ISO 8601 format. Example: 2026-11-12T00:00:00
--obfuscated	flag	✗	False	Whether to obfuscate the data and return also a dictionary
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report push

Description:

Pushes job reports to SIEMs

Usage:

```
sre report push
```

↑ Back to Table of Contents

Command: sre report push chronicle

Description:

Pushes job detailed report(s) to the Google Chronicle

Usage:

```
sre report push chronicle [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Job id to push
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report push dojo

Description:

Pushes job detailed report(s) to the Dojo SIEM

Usage:

```
sre report push dojo [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✗	-	Unique job identifier. Required if neither --to_date or --from_date are set.
--job_type, -jt	choice	✗	-	Specify type of jobs to retrieve (manual type is deprecated and it will be removed). The option is applicable only with --tenant_name [multiple]. Available choices: manual, reactive, scheduled, standard
--from_date, -from	isoparse	✗	-	Generate report FROM date. ISO 8601 format. Example: 2026-11-12T00:00:00
--to_date, -to	isoparse	✗	-	Generate report TILL date. ISO 8601 format. Example: 2026-11-12T00:00:00
--tenant_name, -tn	string	✗	-	Name of related tenant
--dojo_product, -dp	string	✗	-	Defect Dojo product name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_engagement, -de	string	✗	-	Defect Dojo engagement name to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--dojo_test, -dt	string	✗	-	Defect Dojo test title to which the results will be uploaded in case Defect Dojo integration is configured. “tenant_name”, “customer_name” and “job_id” can be used as generic placeholders inside curly brackets
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report questionnaire

Description:

Describes standard questionnaire reports

Usage:

```
sre report questionnaire
```

↑ Back to Table of Contents

Command: sre report questionnaire accumulated

Description:

Returns a presigned url to a tenant standard questionnaire xlsx file

Usage:

```
sre report questionnaire accumulated [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--standard, -s	string	✓	-	Full name of the standard, i.e. “CIS Controls v7”
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report questionnaire jobs

Description:

Returns a presigned url to a job standard questionnaire xlsx file

Usage:

```
sre report questionnaire jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Unique job identifier
--standard, -s	string	✓	-	Full name of the standard, i.e. “CIS Controls v7”
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer’s behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report raw

Description:

Fetches raw report

Usage:

```
sre report raw
```

↑ Back to Table of Contents

Command: sre report raw latest

Description:

Returns latest raw report

Usage:

```
sre report raw latest [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--obfuscated	flag	✗	False	Whether to obfuscate the data and return also a dictionary
--meta	flag	✗	False	Whether to return rules meta as well
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report resource

Description:

Generate resource reports

Usage:

```
sre report resource
```

↑ Back to Table of Contents

Command: sre report resource job

Description:

Resource report for concrete job

Usage:

```
sre report resource job [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Unique job identifier
--resource_type, -rt	string	✗	-	Resource type to filter the result (lambda, s3, …)
--region, -r	string	✗	-	Region to filter the result by. Specify "global" for region-independent resources
--full, -f	flag	✗	False	Whether to return full resource data
--exact_match, -em	boolean	✗	True	Whether to match the identifier exactly or allow partial match
--search_by_all, -sba	flag	✗	False	If specified, all the fields will be checked

Option	Type	Req	Default	Description
--href, -hf	flag	✗	False	Whether to return raw data or URL to the data
--obfuscated	flag	✗	False	Whether to obfuscate the data and return also a dictionary
--id	string	✗	-	Resource identifier
--name	string	✗	-	Resource name
--arn	string	✗	-	Resource arn, only for aws
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report resource jobs

Description:

Resource report for tenant jobs

Usage:

```
sre report resource jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--job_type, -jt	choice	✗	-	Specify type of jobs to retrieve (manual type is deprecated and it will be removed). The option is applicable only with --tenant_name [multiple]. Available choices: manual, reactive, scheduled, standard
--from_date, -from	isoparse	✗	-	Generate report FROM date. ISO 8601 format. Example: 2026-11-12T00:00:00
--to_date, -to	isoparse	✗	-	Generate report TILL date. ISO 8601 format. Example: 2026-11-12T00:00:00
--resource_type, -rt	string	✗	-	Resource type to filter the result (lambda, s3, …)
--region, -r	string	✗	-	Region to filter the result by. Specify "global" for region-independent resources
--full, -f	flag	✗	False	Whether to return full resource data
--exact_match, -em	boolean	✗	True	Whether to match the identifier exactly or allow partial match
--search_by_all, -sba	flag	✗	False	If specified, all the fields will be checked
--id	string	✗	-	Resource identifier
--name	string	✗	-	Resource name
--arn	string	✗	-	Resource arn, only for aws
--json	flag	✗	False	Response as a JSON

Option	Type	Req	Default	Description
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report resource latest

Description:

Resource report for tenant

Usage:

```
sre report resource latest [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--resource_type, -rt	string	✗	-	Resource type to filter the result (lambda, s3, …)
--region, -r	string	✗	-	Region to filter the result by. Specify "global" for region-independent resources
--full, -f	flag	✗	False	Whether to return full resource data
--exact_match, -em	boolean	✗	True	Whether to match the identifier exactly or allow partial match
--search_by_all, -sba	flag	✗	False	If specified, all the fields will be checked
--format, -ft	choice	✗	-	Report format. Available choices: json, xlsx
--href, -hf	flag	✗	False	Whether to return raw data or URL to the data
--obfuscated	flag	✗	False	Whether to obfuscate the data and return also a dictionary
--id	string	✗	-	Resource identifier
--name	string	✗	-	Resource name
--arn	string	✗	-	Resource arn, only for aws
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report resource platform_latest

Description:

Resource report for platform

Usage:

```
sre report resource platform_latest [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--platform_id, -pid	string	✓	-	Platform id
--resource_type, -rt	string	✗	-	Resource type to filter the result (lambda, s3, …)
--full, -f	flag	✗	False	Whether to return full resource data
--exact_match, -em	boolean	✗	True	Whether to match the identifier exactly or allow partial match
--search_by_all, -sba	flag	✗	False	If specified, all the fields will be checked
--format, -ft	choice	✗	-	Report format. Available choices: json, xlsx
--href, -hf	flag	✗	False	Whether to return raw data or URL to the data
--obfuscated	flag	✗	False	Whether to obfuscate the data and return also a dictionary
--id	string	✗	-	Resource identifier
--name	string	✗	-	Resource name
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre report rules

Description:

Describes rule reports of jobs

Usage:

```
sre report rules
```

↑ Back to Table of Contents

Command: sre report rules accumulated

Description:

Describes tenant-specific rule statistic reports, based on relevant jobs

Usage:

```
sre report rules accumulated [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--from_date, -from	isoparse	✗	-	Generate report FROM date. ISO 8601 format. Example: 2026-11-12T00:00:00
--to_date, -to	isoparse	✗	-	Generate report TILL date. ISO 8601 format. Example: 2026-11-12T00:00:00

Option	Type	Req	Default	Description
--job_type, -jt	choice	✗	-	Specify type of jobs to retrieve (manual type is deprecated and it will be removed). The option is applicable only with --tenant_name [multiple]. Available choices: manual, reactive, scheduled, standard
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report rules jobs

Description:

Describes job-specific rule statistic reports

Usage:

```
sre report rules jobs [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Unique job identifier
--format, -ft	choice	✗	json	Format of the file behind the presigned reference. Available choices: json, xlsx
--href, -hf	flag	✗	False	Return presigned URL instead of inline payload
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre report status

Description:

Retrieves report status by its ID

Usage:

```
sre report status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--job_id, -id	string	✓	-	Report job type
--full, -f	flag	✗	False	Flag to list all attempts related to specified ID
--json	flag	✗	False	Response as a JSON

Option	Type	Req	Default	Description
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre resource

Description:

Manages resources

Usage:

```
sre resource
```

↑ Back to Table of Contents

Group: sre resource exception

Description:

Manages resource exception

Usage:

```
sre resource exception
```

↑ Back to Table of Contents

Command: sre resource exception add

Description:

Creates a new resource exception to exclude resources from rule execution.

Three types of exceptions are supported: 1. Resource-specific: requires –resource_id, –resource_type, and –location 2. ARN-based: requires –arn 3. Tag-based: requires –tags_filters

All exception types require –tenant_name and –expire_at

Usage:

```
sre resource exception add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--expire_at, -exp	isoparse	✓	-	Date and time when this exception should expire. ISO 8601 format. Example: 2026-11-12T00:00:00
--resource_id, -resid	string	✗	-	Resource ID (required with resource_type and location for resource-specific exception)
--resource_type, -rt	string	✗	-	Resource type (e.g., aws.ec2, azure.vm) - required with resource_id and location
--location, -loc	string	✗	-	Location/region (required with resource_id and resource_type)
--arn	string	✗	-	Amazon Resource Name for ARN-based exception (cannot be combined with other filters)
--tags_filters, -tf	string	✗	-	Tag filters in format “key=value” for tag-based exception (cannot be combined with other filters) [multiple]
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file

Option	Type	Req	Default	Description
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre resource exception delete

Description:

Deletes a resource exception by its ID

Usage:

```
sre resource exception delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--exception_id, -exid	string	✓	-	The resource exception ID to delete
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre resource exception describe

Description:

Retrieves resource exception(s) with optional filtering and pagination.

Can retrieve either: - A specific resource exception by ID (when –exception_id is provided) - A filtered list of resource exceptions (when using other filter options)

Usage:

```
sre resource exception describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--exception_id, -exid	string	✗	-	Resource exception ID. If provided, other filters are ignored
--tenant_name, -tn	string	✗	-	Name of related tenant
--resource_type, -rt	string	✗	-	Resource type to filter the results (e.g., aws.ec2, azure.vm)
--location, -loc	string	✗	-	Location/region to filter the results
--resource_id, -resid	string	✗	-	Resource ID to filter the results
--arn	string	✗	-	Amazon Resource Name (ARN) of a specific AWS resource to filter the results

Option	Type	Req	Default	Description
--tags_filters, -tf	string	✗	-	Tag filters to apply to the results (e.g., key=value) [multiple]
--include_expired, -ie	flag	✗	False	Determines whether to include expired exceptions in the results
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre resource exception update

Description:

Updates an existing resource exception.

The update replaces the entire exception configuration. You must provide the complete exception type configuration (not just the fields to update).

Three types of exceptions are supported: 1. Resource-specific: requires –resource_id, –resource_type, and –location 2. ARN-based: requires –arn 3. Tag-based: requires –tags_filters

All exception types require –exception_id, –tenant_name and –expire_at

Usage:

```
sre resource exception update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--exception_id, -exid	string	✓	-	The resource exception ID to update
--tenant_name, -tn	string	✓	-	Name of related tenant
--resource_id, -resid	string	✗	-	Resource ID (required with resource_type and location for resource-specific exception)
--resource_type, -rt	string	✗	-	Resource type (e.g., aws.ec2, azure.vm) - required with resource_id and location
--location, -loc	string	✗	-	Location/region (required with resource_id and resource_type)
--arn	string	✗	-	Amazon Resource Name for ARN-based exception (cannot be combined with other filters)
--tags_filters, -tf	string	✗	-	Tag filters in format "key=value" for tag-based exception (cannot be combined with other filters) [multiple]
--expire_at, -exp	isoparse	✓	-	Date and time when this exception should expire. ISO 8601 format. Example: 2026-11-12T00:00:00
--json	flag	✗	False	Response as a JSON

Option	Type	Req	Default	Description
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre resource describe

Description:

Retrieves cloud resource(s) with optional filtering and pagination.

Can retrieve either: - A specific AWS resource by ARN (when –arn is provided) - A filtered list of resources (when using other filter options)

Use `sre resource describe_platform` to browse the collected inventory of one specific K8S platform.

Usage:

```
sre resource describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--arn	string	✗	-	Amazon Resource Name (ARN) of a specific AWS resource. If provided, other filters are ignored
--tenant_name, -tn	string	✗	-	Name of related tenant
--resource_type, -rt	string	✗	-	Resource type to filter the results (e.g., aws.ec2, azure.vm)
--location, -loc	string	✗	-	Location/region to filter the results
--resource_id, -resid	string	✗	-	Resource ID to filter the results
--name, -n	string	✗	-	Resource name to filter the results
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre resource describe_platform

Description:

Retrieves the collected inventory of one K8S platform.

Only KUBERNETES resources are returned. They have no location because Kubernetes has no regions, but they do have a namespace.

Usage:

```
sre resource describe_platform [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--platform_id, -pid	string	✓	-	K8S platform id to get the collected inventory of
--resource_type, -rt	string	✗	-	K8S resource type to filter the results, with or without the cloud prefix (e.g., k8s.pod, pod)
--resource_id, -resid	string	✗	-	Resource ID to filter the results
--name, -n	string	✗	-	Resource name to filter the results
--namespace, -ns	string	✗	-	K8S namespace to filter the results
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre role

Description:

Manages Role Entity

Usage:

```
sre role
```

↑ Back to Table of Contents

Command: sre role add

Description:

Creates the Role entity with the given name from Customer with the given id

Usage:

```
sre role add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Role name
--policies, -p	string	✓	-	List of policies to attach to the role [multiple]
--expiration, -e	string	✗	-	Expiration date in ISO 8601 format (e.g. 2026-11-12). If no timezone (tz) is specified, it will be interpreted as UTC.
--description, -d	string	✓	-	Description for the created role
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre role delete

Description:

Deletes customers role

Usage:

```
sre role delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Role name to delete
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file

Option	Type	Req	Default	Description
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre role describe

Description:

Describes roles for the given customer

Usage:

```
sre role describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✗	-	Role name to describe.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre role update

Description:

Updates role configuration

Usage:

```
sre role update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Role name to modify
--attach_policy, -a	string	✗	-	List of policies to attach to the role [multiple]
--detach_policy, -dp	string	✗	-	List of policies to detach from role [multiple]
--expiration, -e	string	✗	-	Expiration date in ISO 8601 format (e.g. 2026-11-12). If no timezone (tz) is specified, it will be interpreted as UTC.
--description, -d	string	✗	-	Description for the created role
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre rule

Description:

Manages Rule Entity

Usage:

```
sre rule
```

↑ Back to Table of Contents

Command: sre rule delete

Description:

Deletes rules within your customer

Usage:

```
sre rule delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rule_name, -r	string	✗	-	Rule id to delete
--cloud, -c	choice	✗	-	Delete only rules of specific cloud. Available choices: AWS, AZURE, GCP, KUBERNETES
--git_project_id, -pid	string	✗	-	Project id of git repo to delete rules
--git_ref, -gr	string	✗	-	Branch of git repo to delete rules
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre rule describe

Description:

Describes rules within your customer

Usage:

```
sre rule describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rule_name, -r	string	✗	-	Rule id to describe
--cloud, -c	choice	✗	-	Display only rules of specific cloud.. Available choices: AWS, AZURE, GCP, KUBERNETES
--git_project_id, -pid	string	✗	-	Project id of git repo to build a ruleset

Option	Type	Req	Default	Description
--git_ref, -gr	string	✗	-	Branch of git repo to build a ruleset
--rule_source_id, -rsid	string	✗	-	The id of rule source object the rule must belong to
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre rule update

Description:

Pulls the latest versions of rules within your customer

Usage:

```
sre rule update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rule_source_id, -rsid	string	✗	-	Unique rule-source identifier.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre ruleset

Description:

Manages Customer rulesets

Usage:

```
sre ruleset
```

↑ Back to Table of Contents

Command: sre ruleset add

Description:

Creates Customers ruleset

Usage:

```
sre ruleset add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Ruleset name
--cloud, -c	choice	✓	-	Ruleset cloud. Available choices: AWS, AZURE, GCP, KUBERNETES
--version, -v	string	✗	-	Ruleset version to create. If not specified, will be resolved automatically based on the previous ruleset with the same name or based on rulesource of type GITHUB_RELEASE
--rule, -r	string	✗	-	Rule ids to attach to the ruleset. Multiple ids can be specified [multiple]
--exclude_rule, -er	string	✗	-	Rules to exclude from the ruleset [multiple]
--rule_source_id, -rsid	string	✗	-	The id of rule source object to use rules from
--git_project_id, -pid	string	✗	-	Project id of git repo to build a ruleset
--git_ref, -gr	string	✗	-	Branch of git repo to build a ruleset
--platform	choice	✗	-	Platform for k8s [multiple]. Available choices: kubernetes, openshift, kubernetes and openshift
--category	string	✗	-	Rules category to use [multiple]
--service_section	string	✗	-	Rules service section to use [multiple]
--source	string	✗	-	Rules source to use [multiple]
--description, -d	string	✓	-	Human-readable description of the ruleset
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre ruleset delete

Description:

Deletes Customer ruleset. For successful deletion, the ruleset must be inactive

Usage:

```
sre ruleset delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Ruleset name
--version, -v	string	✓	-	Ruleset version to remove. Specify * to remove all the versions of a specific ruleset
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre ruleset describe

Description:

Describes Customer rulesets

Usage:

```
sre ruleset describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✗	-	Ruleset name
--version, -v	string	✗	-	Ruleset version
--cloud, -c	choice	✗	-	Cloud name to filter rulesets. Available choices: AWS, AZURE, GCP, KUBERNETES
--get_rules, -r	flag	✗	False	If specified, ruleset's rules ids will be returned. MAKE SURE to use '–json' flag to get a clear output
--licensed, -ls	boolean	✗	-	If True, only licensed rule-sets are returned. If False, only standard rule-sets
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre ruleset release

Description:

Released a specific version of ruleset

Usage:

```
sre ruleset release [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Ruleset name
--version, -v	string	✗	-	Ruleset version to release. Specify * to release all the versions of a specific ruleset. If not specified, the latest version is released
--display_name, -dn	string	✓	-	Ruleset display name
--description, -d	string	✓	-	Ruleset description
--overwrite, -o	flag	✗	False	Determines whether to overwrite an existing ruleset version
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre ruleset update

Description:

Updates Customers ruleset

Usage:

```
sre ruleset update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--name, -n	string	✓	-	Ruleset name
--version, -v	string	✗	-	Ruleset version to update. If not specified, the latest version will be updated
--new_version, -nv	string	✓	-	New version for the updated ruleset
--attach_rules, -ar	string	✗	-	Rule ids to attach to the ruleset. Multiple values allowed [multiple]
--detach_rules, -dr	string	✗	-	Rule ids to detach from the ruleset. Multiple values allowed [multiple]
--force, -f	flag	✗	False	If specified the new version of ruleset will be created even if there are no changes
--description, -d	string	✗	-	Human-readable description of the ruleset

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre rulesource

Description:

Manages Rule Source entity

Usage:

```
sre rulesource
```

↑ Back to Table of Contents

Command: sre rulesource add

Description:

Creates rule source

Usage:

```
sre rulesource add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--git_project_id, -gpid	string	✓	-	GitLab project id or GitHub owner/repo
--type, -t	choice	✗	-	Rule source type. Available choices: GITHUB, GITLAB, GITHUB_RELEASE
--git_url, -gurl	string	✗	-	API endpoint of a Git-based platform
--git_ref, -gref	string	✗	main	Name of the branch to grab rules from
--git_rules_prefix, -gprefix	string	✗	/	Rules path prefix
--git_access_secret, -gsecret	string	✗	-	Secret token to access the repository
--description, -d	string	✓	-	Human-readable description of the repo
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre rulesource delete

Description:

Deletes rule source

Usage:

```
sre rulesource delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rule_source_id, -rsid	string	✓	-	Unique rule-source identifier.

Option	Type	Req	Default	Description
--delete_rules, -dr	flag	✗	False	Whether to remove all rules belonging to this rule source
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre rulesource describe

Description:

Describes rule source

Usage:

```
sre rulesource describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rule_source_id, -rsid	string	✗	-	Unique rule-source identifier.
--git_project_id, -gpid	string	✗	-	GitLab project id or GitHub owner/repo
--type, -t	choice	✗	-	Rule source type. Available choices: GITHUB, GITLAB, GITHUB_RELEASE
--has_secret, -hs	boolean	✗	-	Specify whether returned rule sources should have secrets
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre rulesource sync

Description:

Updates rules for this rule source

Usage:

```
sre rulesource sync [OPTIONS]
```

Options:

Option	Type	Req	Default	Description

Option	Type	Req	Default	Description
--rule_source_id, -rsid	string	✓	-	Unique rule-source identifier.
--force, -f	flag	✗	False	Force sync even if the rule source is already SYNCING.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre rulesource update

Description:

Updates rule source

Usage:

```
sre rulesource update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--rule_source_id, -rsid	string	✓	-	Unique rule-source identifier.
--git_project_id, -gpid	string	✗	-	GitLab project id or GitHub owner/repo
--type, -t	choice	✗	-	Rule source type. Available choices: GITHUB, GITLAB, GITHUB_RELEASE
--git_url, -gurl	string	✗	-	API endpoint of a Git-based platform
--git_ref, -gref	string	✗	-	Name of the branch to grab rules from
--git_rules_prefix, -gprefix	string	✗	-	Rules path prefix
--git_access_secret, -gsecret	string	✗	-	Secret token to access the repository
--description, -d	string	✗	-	Human-readable description of the repo
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre service

Description:

Manages Services

Usage:

```
sre service
```

↑ Back to Table of Contents

Group: sre service operations

Description:

Manages Service Operations

Usage:

```
sre service operations
```

↑ Back to Table of Contents

Command: sre service operations status

Description:

Execution status of the specified service operation

Usage:

```
sre service operations status [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--operation, -op	choice	✓	-	Service operation type to check status for. Available choices: metrics_update, metadata_update, push_dojo
--from_date, -from	string	✗	-	Query statuses from this date. Example: 2026-09-13
--to_date, -to	string	✗	-	Query statuses till this date. Example: 2026-10-13
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre setting

Description:

Manages Settings

Usage:

```
sre setting
```

↑ Back to Table of Contents

Group: sre setting lm

Description:

Manages License Manager Setting(s)

Usage:

```
sre setting lm
```

↑ Back to Table of Contents

Group: sre setting lm client

Description:

Manages License Manager Client data

Usage:

```
sre setting lm client
```

↑ Back to Table of Contents

Command: sre setting lm client add

Description:

Adds License Manager provided client-key data

Usage:

```
sre setting lm client add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key_id, -kid	string	✓	-	Key-id granted by the License Manager
--algorithm, -alg	string	✓	ECC:p521_DSS_SHA:256	Algorithm granted by the License Manager
--private_key, -prk	string	✓	-	Private-key granted by the License Manager
--b64encoded, -b64	flag	✗	False	Specify whether the private is b64encoded
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting lm client delete

Description:

Removes current License Manager client-key data

Usage:

```
sre setting lm client delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--key_id, -kid	string	✓	-	Key-id granted by the License Manager
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting lm client describe

Description:

Describes current License Manager client-key data

Usage:

```
sre setting lm client describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting lm client update

Description:

Updates License Manager provided client-key data

Usage:

```
sre setting lm client update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description

Option	Type	Req	Default	Description
--key_id, -kid	string	✗	-	Key-id granted by the License Manager
--algorithm, -alg	string	✓	ECC:p521_DSS_SHA:256	Algorithm granted by the License Manager
--private_key, -prk	string	✓	-	Private-key granted by the License Manager
--b64encoded, -b64	flag	✗	False	Specify whether the private is b64encoded
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre setting lm config

Description:

Manages License Manager Config data

Usage:

```
sre setting lm config
```

↑ Back to Table of Contents

Command: sre setting lm config add

Description:

Adds License Manager access configuration data

Usage:

```
sre setting lm config add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--host, -h	string	✓	-	License Manager host. You can specify the full url here
--port, -p	integer	✗	-	License Manager port
--protocol, -pr	choice	✗	-	License manager protocol. Available choices: HTTP, HTTPS
--stage, -st	string	✗	-	Path prefix
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting lm config delete

Description:

Removes current License Manager access configuration data

Usage:

```
sre setting lm config delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting lm config describe

Description:

Describes current License Manager access configuration data

Usage:

```
sre setting lm config describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting lm config update

Description:

Updates License Manager access configuration data

Usage:

```
sre setting lm config update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--host, -h	string	✗	-	License Manager host. You can specify the full url here
--port, -p	integer	✗	-	License Manager port

Option	Type	Req	Default	Description
--protocol, -pr	choice	✗	-	License manager protocol. Available choices: HTTP, HTTPS
--stage, -st	string	✗	-	Path prefix
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre setting mail

Description:

Manages Mail configuration

Usage:

```
sre setting mail
```

↑ Back to Table of Contents

Command: sre setting mail add

Description:

Creates Mail configuration

Usage:

```
sre setting mail add [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username, -u	string	✓	-	Username of mail account
--password, -pd	string	✓	-	Password of mail account
--password_label, -pl	string	✓	-	Name of the parameter to store password under
--host, -h	string	✓	-	Host of a mail server
--port, -pt	integer	✓	-	Port of a mail server
--use_tls, -tls	flag	✗	False	Specify to whether utilize TLS
--sender_name, -s	string	✗	-	Name to specify as the sender of email(s). Defaults to '–username'
--emails_per_session, -eps	integer	✗	1	Amount of emails to send per session
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting mail delete

Description:

Deletes Mail configuration

Usage:

```
sre setting mail delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting mail describe

Description:

Describes Mail configuration

Usage:

```
sre setting mail describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--display_password, -dp	flag	✗	False	Specify to whether display a configured password.
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre setting report

Description:

Manages Syndicate Rule Engine configuration

Usage:

```
sre setting report
```

↑ Back to Table of Contents

Command: sre setting report disable_sending

Description:

Disables Syndicate Rule Engine report sending mechanism

Usage:

```
sre setting report disable_sending [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre setting report enable_sending

Description:

Enables Syndicate Rule Engine report sending mechanism

Usage:

```
sre setting report enable_sending [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre tenant

Description:

Manages Tenant Entity

Usage:

```
sre tenant
```

↑ Back to Table of Contents

Group: sre tenant credentials

Description:

Allows to bind existing credentials applications to tenants

Usage:

```
sre tenant credentials
```

↑ Back to Table of Contents

Command: sre tenant credentials describe

Description:

Lists all available applications with credentials

Usage:

```
sre tenant credentials describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--cloud, -c	choice	✗	-	Cloud to describe credentials by. Available choices: AWS, AZURE, GOOGLE
--application_id, -aid	string	✗	-	Application id to describe a concrete credentials item
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant credentials get_linked_tenants

Description:

Returns all the tenants the credentials is linked to

Usage:

```
sre tenant credentials get_linked_tenants [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	✓	-	Application id to describe a concrete credentials item
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant credentials link

Description:

Links credentials to a specific set of tenants.

Usage:

```
sre tenant credentials link [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	✓	-	Application id to describe a concrete credentials item
--tenant_name, -tn	string	✗	-	Name of related tenant [multiple]
--all_tenants	flag	✗	False	Whether to activate integration for all tenants
--exclude_tenant, -et	string	✗	-	Tenants to exclude for this integration. Can be specified together with –all_tenants flag [multiple]
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant credentials unlink

Description:

Unlinks credentials from tenants

Usage:

```
sre tenant credentials unlink [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--application_id, -aid	string	✓	-	Application id to describe a concrete credentials item
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file

Option	Type	Req	Default	Description
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant active_licenses

Description:

Gets tenant active licenses

Usage:

```
sre tenant active_licenses [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--limit, -l	integer (1 to 50)	✗	1	Number of records to show
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant describe

Description:

Describes tenants within your customer

Usage:

```
sre tenant describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✗	-	Name of related tenant
--account_number, -acc	string	✗	-	Cloud native account identifier
--active, -act	boolean	✗	-	Type of tenants to return
--cloud, -c	choice	✗	-	Specific cloud to describe tenants. Available choices: AZURE, YANDEX, GOOGLE, AWS, OPEN_STACK, CSA, HARDWARE, ENTERPRISE, EXOSCALE, WORKSPACE, AOS, VSPHERE, VMWARE, NUTANIX
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON

Option	Type	Req	Default	Description
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant get_excluded_rules

Description:

Returns excluded rules for a tenant

Usage:

```
sre tenant get_excluded_rules [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre tenant set_excluded_rules

Description:

Excludes rules for a tenant

Usage:

```
sre tenant set_excluded_rules [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--tenant_name, -tn	string	✓	-	Name of related tenant
--rules, -r	string	✗	-	Rules that you want to exclude for a tenant [multiple]
--empty	flag	✗	False	Whether to reset the list of excluded rules
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Group: sre users

Description:

Manages Rule Engine users. Only for system customer

Usage:

```
sre users
```

↑ Back to Table of Contents

Command: sre users change_password

Description:

Changes password for your user

Usage:

```
sre users change_password [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--password, -p	string	✓	-	New password for your user
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre users create

Description:

Creates a new user

Usage:

```
sre users create [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username	string	✓	-	Username to create user
--password, -p	string	✓	-	New user password
--role_name, -rn	string	✓	-	Role to assign to this user. It should exist inside the customer
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre users delete

Description:

Removes an existing user

Usage:

```
sre users delete [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username	string	✓	-	Username to delete user
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre users describe

Description:

Describes users

Usage:

```
sre users describe [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username	string	✗	-	Username to describe a specific user
--limit, -l	integer (1 to 50)	✗	10	Number of records to show
--next_token, -nt	string	✗	-	Token to start record-pagination from
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre users update

Description:

Updates some user's attributes

Usage:

```
sre users update [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username	string	✓	-	Username to update user
--password, -p	string	✗	-	New user password
--role_name, -rn	string	✗	-	Role to assign to this user. It should exist inside the customer
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre cleanup

Description:

Removes all the configuration data related to the tool

Usage:

```
sre cleanup [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--confirm	flag	✗	False	Confirms the action
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre configure

Description:

Configures sre tool to work with Syndicate Rule Engine

Usage:

```
sre configure [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--api_link, -api	string	✗	-	Link to the Syndicate Rule Engine host
--items_per_column, -ipc	integer (≥ 0)	✗	-	Specify how many items per table. Set 0 to disable the limitation
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre health_check

Description:

Checks SRE components availability

Usage:

```
sre health_check [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--identifier, -id	string	✗	-	Concrete check id to retrieve
--status, -st	choice	✗	-	Filter checks by status. Available choices: OK, UNKNOWN, NOT_OK
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre login

Description:

Authenticates user to work with Syndicate Rule Engine

Usage:

```
sre login [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--username, -u	string	✓	-	Your username
--password, -p	string	✓	-	Your password
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre show_config

Description:

Returns the cli configuration

Usage:

```
sre show_config [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Command: sre whoami

Description:

Returns information about the current user

Usage:

```
sre whoami [OPTIONS]
```

Options:

Option	Type	Req	Default	Description
--json	flag	✗	False	Response as a JSON
--verbose	flag	✗	False	Save detailed information to the log file
--customer_id, -cid	string	✗	-	Hidden customer option to make a request on other customer's behalf. Only for system customer

↑ Back to Table of Contents

Version History

Version	Date	Summary

View Changelog: https://github.com/epam/syndicate-rule-engine/blob/main/CHANGELOG.md

Documentation generated for: **sre.EXE, version 5.22.0**