

n8n Integration Endpoints

Provides endpoints used by n8n to:

1. [Upload booking documents](#)
2. [Update booking status to 'documents uploaded'](#)
3. [Lookup user by email and booking IDs](#)

POST /api/v1/integrations/bookings/{ID}/documents

- Description: Upload one or more documents for a booking.
- Auth: Protected
- Path parameters:
 - ID (string) — booking ID
- Headers:
 - Content-Type: multipart/form-data
 - x-api-token: string — API token used by n8n to authenticate requests
- Request body:
 - The payload is sent as multipart/form-data with the following form fields:
 - documents: file(s) to be uploaded. Provide one or more files by repeating the documents field.
 - type: integer enum value representing the document type (e.g., driving license). This value applies to all uploaded files.
 - Example curl:

```
curl -X POST "https://<HOST>/api/v1/integrations/bookings/<BOC
--header 'Content-Type: multipart/form-data' \
--header 'x-api-token: <TOKEN>' \
--form "type=41" \
--form "documents=@/path/to/file1.pdf" \
--form "documents=@/path/to/file2.png"
```

- Staging host: hq-api.staging.instacar.dev
- Max upload size for multipart uploads: 20 MB (api.MaxUploadFileSize). (Confirm whether this limit is per-file or per-request.)
- Success response:
 - 200 OK with empty body. (Confirm whether the API returns 200 OK or 204 No Content.)
- Error responses:
 - 400 Bad Request for malformed multipart form or invalid files.

- 401 Unauthorized if the x-api-token header is missing or invalid.
- 500 Internal Server Error on processing/upload failure.

PATCH /api/v1/integrations/bookings/{ID}

- Description: Patch booking fields (used by n8n to change booking status).
- Auth: Protected
- Path parameters:
 - ID (string) — booking ID
- Headers:
 - Content-Type: application/json
 - x-api-token: string — API token used by n8n to authenticate requests
- Request body:
 - status (integer, required): booking status. Example: 3 — documents uploaded.
 - Example curl:

```
curl --request PATCH \
  --url https://<HOST>/api/v1/integrations/bookings/<BOOKING_ID> \
  --header 'Content-Type: application/json' \
  --header 'x-api-token: <TOKEN>' \
  --data '{"status":3}'
```

- Staging host: hq-api.staging.instacar.dev
- Success response:
 - 200 OK with empty body. (Confirm whether the API returns 200 OK or 204 No Content.)
- Error responses:
 - 400 Bad Request for invalid JSON payload.
 - 401 Unauthorized if the x-api-token header is missing or invalid.
 - 500 Internal Server Error on update failure.

POST /api/v1/integrations/users

- Description: Fetch user details by email and return only booking IDs from the request that are valid for that user.
- Auth: Protected
- Headers:
 - Content-Type: application/json
 - x-api-token: string — API token used by n8n to authenticate requests
- Request body:
 - email (string, required): user email to lookup.

- bookingIds (array of strings, required): booking IDs to validate against the user.
- Example curl:

```
curl --request POST \
  --url https://<HOST>/api/v1/integrations/users \
  --header 'Content-Type: application/json' \
  --header 'x-api-token: <TOKEN>' \
  --data '{"email":"john.doe@example.com","bookingIds":["BOOKI
```

- Staging host: hq-api.staging.instacar.dev
- Success response:
 - 200 OK with JSON body:

```
{
  "data": {
    "id": "U-AB999TEST",
    "firstName": "John ",
    "lastName": "Doe",
    "bookingIds": [
      "BOOKING_ID_1",
      "BOOKING_ID_2"
    ]
  }
}
```

- Error responses:
 - 400 Bad Request for invalid JSON payload or validation errors.
 - 401 Unauthorized if the x-api-token header is missing or invalid.
 - 500 Internal Server Error on lookup/transformation failure.