

EntraID (OIDC/JWT) Authentication for Claude Desktop

Version 2. This guide supersedes the previous revision of this document. If you set up JWT auth against an earlier version of this guide, re-run through the steps below in full — the claims configuration surface has changed and the two approaches should not be mixed.


Configures Claude Desktop to authenticate against this self-hosted AIGW Gateway (although this process works with the SaaS AIGW offering too) using Microsoft EntraID as the OIDC identity provider, with JWT bearer tokens validated by the gateway. User and workspace assignment is driven entirely by **Entra security groups**, so adding or moving a user is a group-membership change — no per-user policy edits.

Prerequisites

- This repo's `docker-compose.yml` stack running
 - `JWT_ENABLED: ON`
- An EntraID tenant with permissions to register applications and manage Enterprise Application properties (Application Administrator or Cloud Application Administrator)
- `openssl` installed locally (for generating the token-signing certificate in step 3)
- Claude Desktop installed, with the Developer menu enabled (step 1 below)


1. Enable the Developer menu in Claude Desktop

The 3rd-party provider / OIDC configuration UI referenced in step 9 lives behind Claude Desktop's Developer menu, which is hidden by default. Enable it before continuing (Help → Troubleshooting → Enable Developer Mode, or the equivalent toggle for your Claude Desktop version).




2. Register the application

In the [Entra Admin Center](#), go to **App registrations** → **New registration**.



- **Name:** something identifiable, e.g. `aigw-jwt-app`
- **Supported account types:** Single tenant
- **Redirect URI:** add the **loopback port Claude Desktop will use** (`http://localhost:8080` in this example) — platform type "Web"



Register an application

*** Name**
The user-facing display name for this application (this can be changed later).

Supported account types
Choose the account types that can use this application or access this API
 [Help me choose](#)

Redirect URI (optional)
We'll return the authentication response to this URI after successfully authenticating the user. Providing this now is optional and it can be changed later, but a value is required for most authentication scenarios.

Register an app you're working on here. Integrate gallery apps and other apps from outside your organization by adding from [Enterprise applications](#).


Note the **Application (client) ID** and **Directory (tenant) ID** from the app's Overview page — both are needed throughout this guide, and the tenant ID doubles as part of the **OIDC Issuer URL**:
`https://login.microsoftonline.com/<tenant-id>/v2.0.`

3. Generate and upload a token-signing certificate

Customizing claims on this app (step 6) requires a certificate — Entra signs tokens with a custom key once you add custom claims, instead of the default Microsoft key. Generate a self-signed certificate and upload the public half:

```
openssl req -x509 -newkey rsa:2048 \  
-keyout key.pem -out cert.pem \  
-days 365 -nodes \  
-subj "/CN=PortkeyTokenSigningKey"
```

In **App registrations** → **your app** → **Certificates & secrets** → **Certificates** → **Upload certificate**, upload **cert.pem** (the public key only — never upload or share **key.pem**).



Upload certificate

✓ Upload Completed for cert.pem
1.12 KiB | "Streaming upload"

Upload a certificate (public key) with one of the following file types: .cer, .pem, .cert *

cert.pem

Description

Enter a description for this certificate

The screenshot shows the Microsoft Azure portal interface. At the top, the navigation bar includes the Microsoft Azure logo and a search bar. Below the navigation bar, the breadcrumb trail reads 'Home > MSFT | App registrations > aigw-jwt-app'. The main heading is 'aigw-jwt-app | Certificates & secrets'. On the left, a sidebar menu lists various options: Overview, Quickstart, Integration assistant, Diagnose and solve problems, Manage (expanded), Branding & properties, Authentication (Preview), Certificates & secrets (selected), Token configuration, API permissions, Expose an API, App roles, Owners, Roles and administrators, and Manifest. The main content area features a search bar, a 'Got feedback?' link, and a message: 'Got a second to give us some feedback? →'. Below this, a text block explains that credentials enable confidential applications to identify themselves to the authentication service. Another message states: 'Application registration certificates, secrets and federated credentials can be found in the tabs below.' The 'Certificates (1)' tab is active, showing a table of certificates. The table has columns for Thumbprint, Description, Start date, and Expires. One certificate is listed with a thumbprint of DA3491AE646C99900F2BA45A89B3F..., a description of CN=PortkeyTokenSigningKey, a start date of 10/2/2026, and an expiration date of 10/1/2028. An 'Upload certificate' link is also visible.

Microsoft Azure

Search resources, services, and docs (G+)

Home > MSFT | App registrations > aigw-jwt-app

aigw-jwt-app | Certificates & secrets

Search

Got feedback?

Overview

Quickstart

Integration assistant

Diagnose and solve problems

Manage

Branding & properties

Authentication (Preview)

Certificates & secrets

Token configuration

API permissions

Expose an API

App roles

Owners

Roles and administrators

Manifest

Support + Troubleshooting

Got a second to give us some feedback? →

Credentials enable confidential applications to identify themselves to the authentication service when receiving tokens at a web address (scheme). For a higher level of assurance, we recommend using a certificate (instead of a client secret) as a credential.

Application registration certificates, secrets and federated credentials can be found in the tabs below.

Certificates (1) Client secrets (0) Federated credentials (0)

Certificates can be used as secrets to prove the application's identity when requesting a token. Also can be referred to as public key

Upload certificate

Thumbprint	Description	Start date	Expires
DA3491AE646C99900F2BA45A89B3F...	CN=PortkeyTokenSigningKey	10/2/2026	10/1/2028

Keep `key.pem` safe — treat it like any other private key material. It is not consumed by the gateway or by Claude; it only needs to exist so the certificate it backs is valid.

4. Patch the manifest

In the app's **Manifest** tab, set two fields under `"api"`:

```
"api": {
  "acceptMappedClaims": true,
  "requestedAccessTokenVersion": 2,
  ...
}
```

Microsoft Azure

Q Si

Home > MSFT | App registrations > aigw-jwt-app

aigw-jwt-app | Manifest

✦ ...

Search

◊ <<

Refresh

Got feedback?

Overview

Quickstart

Integration assistant

Diagnose and solve problems

Manage

Branding & properties

Authentication (Preview)

Certificates & secrets

Token configuration

API permissions

Expose an API

App roles

Owners

Roles and administrators

Manifest

An app manifest is a JSON representation of an app registration. The Microsoft system will automatically update the other one for them to match.

Microsoft Graph App Manifest (New)

AAD Graph App Manifest (Depr

See [Understanding the Microsoft Graph application manifest](#) to learn how to ec

Save Discard Download Upload

23 "samlMetadataUrl": null,

24 "defaultRedirectUri": null,

25 "certification": null,

26 "optionalClaims": null,

27 "requestSignatureVerification": null,

28 "addIns": [],

29 "api": {

30 "acceptMappedClaims": true,

31 "knownClientApplications": [],

32 "requestedAccessTokenVersion": null,

33 "oauth2PermissionScopes": [],

34 "preAuthorizedApplications": []

35 },

36 "appRoles": [],

37 "info": {

38 "logoUrl": null,

39 "name": "aigw-jwt-app",

40 "signInUrl": null,

41 "tags": [],

42 "webUrl": null,

43 "isHidden": false,

44 "isDefaultOnly": false,

45 "isPublic": false,

46 "isSinglePage": false,

47 "isWebApplication": false,

48 "isMobileApplication": false,

49 "isNativeApplication": false,

50 "isDesktopApplication": false,

51 "isWebResource": false,

52 "isNativeResource": false,

53 "isDesktopResource": false,

54 "isWebResourceOnly": false,

55 "isNativeResourceOnly": false,

56 "isDesktopResourceOnly": false,

57 "isWebResourceAndNativeResource": false,

58 "isNativeResourceAndDesktopResource": false,

59 "isDesktopResourceAndWebResource": false,

60 "isWebResourceAndDesktopResourceAndNativeResource": false,

61 "isNativeResourceAndDesktopResourceAndWebResource": false,

62 "isDesktopResourceAndWebResourceAndNativeResource": false,

63 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResource": false,

64 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResource": false,

65 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResource": false,

66 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResource": false,

67 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResource": false,

68 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

69 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResource": false,

70 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

71 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResource": false,

72 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

73 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResource": false,

74 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

75 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResource": false,

76 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

77 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResource": false,

78 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

79 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResource": false,

80 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResource": false,

81 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResource": false,

82 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

83 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResource": false,

84 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

85 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

86 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

87 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

88 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

89 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

90 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

91 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

92 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

93 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

94 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

95 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

96 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,


97 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

98 "isDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

99 "isWebResourceAndDesktopResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

100 "isNativeResourceAndDesktopResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndWebResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResourceAndNativeResource": false,

5 / 14



Microsoft Azure

Home > MSFT | App registrations > aigw-jwt-app

aigw-jwt-app | Manifest

Search Refresh Got feedback?

Overview

Quickstart

Integration assistant

Diagnose and solve problems

Manage

- Branding & properties
- Authentication (Preview)
- Certificates & secrets
- Token configuration
- API permissions
- Expose an API
- App roles
- Owners
- Roles and administrators
- Manifest**

An app manifest is a JSON representation of an app registration. The Microsoft system will automatically update the other one for them to match.

Microsoft Graph App Manifest (New) AAD Graph App Manifest

See [Understanding the Microsoft Graph application manifest](#) to learn how

Save Discard Download Upload

```
23 "samlMetadataUrl": null,
24 "defaultRedirectUri": null,
25 "certification": null,
26 "optionalClaims": null,
27 "requestSignatureVerification": null,
28 "addIns": [],
29 "api": {
30   "acceptMappedClaims": true,
31   "knownClientApplications": [],
32   "requestedAccessTokenVersion": 2,
33   "oauth2PermissionScopes": [],
34   "preAuthorizedApplications": []
35 },
36 "appRoles": [],
37 "info": {
38   "logoUrl": null,
39   "marketingUrl": null,
```

- `requestedAccessTokenVersion: 2` — without this, EntraID issues v1.0 tokens whose issuer (<https://sts.windows.net/<tenant-id>/>) won't match the v2.0 issuer URL used in step 9, causing authentication to fail.
- `acceptMappedClaims: true` — required for the app to emit the custom claims configured in step 6.

Click **Save**.

5. Restrict and assign access via the Enterprise Application

In the [Entra Admin Center](#), go to **Enterprise applications** → **All applications** and search for your app by name — the App Registration above automatically has a matching Enterprise Application (service principal).

Home

> Enterprise applications

Enterprise applications | All applications

MSFT

+ New application

Refresh

Download (Export)

Preview info

Columns

Preview features

Go

> Overview

> Manage

All applications

Private Network connectors

User settings

App launchers

Custom authentication extensions

View, filter, and search applications in your organization that are set up to use your Microsoft Entra tenant as their Identity Provider.

The list of applications that are maintained by your organization are in [application registrations](#).

aigw

Application type == Enterprise Applications

Apply

1 application found

Name	Object ID	Application ID	Homepage URL	Created on
A aigw-jwt-app	4c8ff76a-c68a-42a9-8dd3-...	c5490456-8e83-4df6-a979-...		10/2/2026

5a. Require assignment

Under **Properties**, set **Assignment required?** to **Yes**. This is what makes group membership meaningful – without it, any user in the tenant can sign in and get a token regardless of group assignment below.

Home

> Enterprise applications | All applications

> aigw-jwt-app

aigw-jwt-app | Properties

Enterprise Application

Got feedback?

Overview

Deployment Plan

Diagnose and solve problems

> Manage

Properties

Owners

Roles and administrators

Users and groups

Single sign-on

Provisioning

Application proxy

Self-service

Custom security attributes

> Security

> Activity

> Help

View and manage application settings for your organization. Editing properties like display information, user sign-in settings, and user visibility settings requires Global Administrator, Cloud Application Administrator, Application Administrator roles. [Learn more](#).

If this application resides in your tenant, you can manage additional properties on the [application registration](#).

Activation status

Activated

Enabled for users to sign-in?

Yes No

Name *

aigw-jwt-app

Homepage URL

Logo

A

Select a file

Application ID

c5490456-8e83-4df6-a979-9ed2b4dd84a5

Object ID

4c8ff76a-c68a-42a9-8dd3-7832df6b03a4

Assignment required?

Yes No

Visible to users?

Yes No

5b. Assign the groups that should have access

Under **Users and groups** → **Add user/group**, assign the security group(s) whose members should be able to use this gateway (e.g. **AIRS Group**). Only members of an assigned group can sign in once assignment is required.

Home > Enterprise applications | All applications > aigw-jwt-app

aigw-jwt-app | Users and groups

Enterprise Application

◊ << + Add user/group ✎ Edit assignment 🗑️ Remo

- Overview
- Deployment Plan
- Diagnose and solve problems
- Manage
 - Properties
 - Owners
 - Roles and administrators
 - Users and groups**

The application will not appear for assigned users with

Assign users and groups to app-roles for your application

First 200 shown, search all users & groups

Display name

No application assignments found

Home > Enterprise applications | All applications > aigw-jwt-app | Users and groups

Add Assignment

MSFT

Users and groups

None Selected

Select a role

Default Access

Users and groups

Try changing or adding filters if you don't see what you're looking for.

Search

AIRS Group

1 result found

All Users Agents' user accounts Groups

	Name	Type	Details
☒	AG AIRS Group	Group	

Onboarding a new user: add them to the appropriate Entra group. No app registration change, no policy edit, no restart — their next sign-in picks up access and claims automatically. This is the mechanism for allocating users "on the fly."

6. Configure claims

Still on the Enterprise Application, go to **Single sign-on** → **OIDC-based Sign-on** → **Attributes & Claims** → **Edit**.

Home > Enterprise applications | All applications > aigw-jwt-app

aigw-jwt-app | OIDC-based Sign-on

...

Enterprise Application

Overview

Deployment Plan

Diagnose and solve problems

Manage

- Properties
- Owners
- Roles and administrators
- Users and groups
- Single sign-on
- Provisioning
- Application proxy
- Self-service
- Custom security attributes

OIDC Applications require custom signing keys to customize claims. Please check the security considerations before customizing the claims for the application. [Learn more](#)

This application uses OpenID Connect and OAuth. This protocol simplifies application configuration, has easy-to-use SDKs, and enables your application to use MS Graph. [Learn more](#)

Because this application uses OpenID Connect and OAuth, most single sign-on configuration is already complete. [Learn more about application and service principal objects in Microsoft Entra](#)

1

Configure application properties

[Go to application](#)

Please go to aigw-jwt-app in the App registrations experience to edit properties such as reply URLs, identifiers, optional claims, among others. Your account should have the required permissions (Global Administrator, Cloud Application Administrator, Application Administrator, or owner of the application object). [Learn more about admin roles in Microsoft Entra](#)

2

Attributes & Claims

[Edit](#)

This application does not have any JWT-based claims configured. Click on edit to start configuring claims.

Add the claims the gateway needs as **Additional claims** (use **+ Add new claim**, source = typed constant value, not an attribute):

Claim name	Value	Purpose
portkey_oid	Your deployment's ORGANISATIONS_TO_SYNC UUID	Org routing — the gateway rejects tokens missing this
portkey_workspace	A workspace slug, e.g. ws- main-a-997260	Workspace routing
scopes	e.g. completions.write	Overrides JWT_LOCAL_AUTH_DEFAULT_SCOPES explicitly

9 / 14

Attributes & Claims

...

+

Add new claim

+

Add a group claim

≡

Columns

🗨

Got feedback?

i

OIDC Applications require custom signing keys to customize claims. Please check the security considerations before customizing the claims for the application. [Learn more.](#)

Required claim

Claim name	Type	Value
No claims configured		

Additional claims

Claim name	Type	Value
portkey_oid	JWT	"95cb67bf-6fb5-4581-ac... ...
portkey_workspace	JWT	"ws-main-a-997260" ...
scopes	JWT	"completions.write" ...

****NOTE: **** You can choose to leave out the portkey_workspace and leverage SCIM group assignment to allocate the workspace. Upon authentication the gateway will scan for valid users based on the UPN or email and assign them to the appropiate workspace.

Group-based claim values (multi-team / multi-workspace)

If different teams need different values — different workspaces, or extra metadata — don't hardcode a single value. Instead, add **claim conditions** scoped to a group, with a distinct value per group. For example, a **metadata** claim that varies by team:

Manage claim

...

💾

Save

✕

Discard changes

🗨

Got feedback?

Name *

metadata

Namespace

Enter a namespace URI

Choose name format

Source

●

Attribute

○

Transformation

○

Directory schema extension

Source attribute

Select from drop down or type a constant

Claim conditions

Returns the claim only if all the conditions below are met.

i

Multiple conditions can be applied to a claim. When adding conditions, order of operation is important. [Read the documentation](#) for more information.

User type	Scoped Groups	Source	Value
Members	1 groups	Attribute	"{ \"environment\": \"production\", \"team\": \"backend\" }"
Members	1 groups	Attribute	"{ \"environment\": \"production\", \"team\": \"frontend\" }"
Select from drop down	Select groups	Select claim condition source.	
Advanced SAML claims options			

With this in place, the same claim resolves differently depending on which group signs in — this is how `portkey_workspace` itself can also be made group-dependent for a multi-workspace deployment: add one claim condition row per group, each with its own value, instead of a single static value in the table above.

Click **Save**.

7. Get the Application (client) ID

From either the App Registration's Overview or the Enterprise Application's Overview — they share the same **Application ID**.

Home > Enterprise applications | All applications

aigw-jwt-app | Overview
Enterprise Application

Overview

- Deployment Plan
- Diagnose and solve problems
- Manage
 - Properties
 - Owners
 - Roles and administrators
 - Users and groups

Properties

Name ⓘ
aigw-jwt-app

Application ID ⓘ
c5490456-8e83-4df6-a9... Copied

Object ID ⓘ
4c8ff76a-c68a-42a9-8dd...

Getting Started

8. Configure the Vertex integration

In the AIGW control plane, add an integration for `@vertex` and select the models you want available through this gateway.

9. Create an AIGW config


Create a config that routes to the Vertex integration, e.g.:

```
{
  "retry": {
    "attempts": 3
  },
  "cache": {
    "mode": "simple"
  },
  "provider": "@vertex"
}
```

Save it and note the generated **config ID** — it's used in step 11.

10. Enable JWT Authentication

Enable JWT Authentication in the AIGW control plane and point it at your EntraID app (tenant ID from step 2).



11. Configure the 3rd-party (OIDC) provider in Claude Desktop

In Claude Desktop's Developer menu, add a 3rd-party provider pointing at the local hybrid gateway container, with OIDC authentication:

Field	Value
Base URL	This gateway's URL (e.g. <code>http://localhost:8787</code>)
Client ID	The Application (client) ID from step 7
Issuer URL	The EntraID tenant issuer URL from step 2
Bearer token type	ID Token
Scopes	<code>openid profile email offline_access</code>
Redirect port	<code>8080</code> (must match the redirect URI registered in step 2)

Sample configuration:

```
{
  "inferenceGatewayBaseUrl": "http://127.0.0.1:8787",
  "inferenceCustomHeaders": "[redacted]",
  "inferenceGatewayOidcAuthFlow": "browser",
  "inferenceGatewayOidc": {
    "clientId": "c5490456-8e83-4df6-a979-9ed2b4dd84a5",
    "issuer": "https://login.microsoftonline.com/<TenantID>/v2.0",
    "bearerTokenType": "id_token",
    "scopes": "openid profile email offline_access",
```

```

    "appendOfflineAccess": true,
    "redirectPort": 8080
  },
  "chatTabEnabled": true,
  "modelDiscoveryEnabled": true,
  "inferenceModels": [],
  "inferenceProvider": "gateway",
  "inferenceCredentialKind": "interactive"
}

```

Finally, add a custom header so every request carries the AIGW config from step 9:

```
x-portkey-config: <config-id>
```

Verifying it works

1. In Claude Desktop, trigger the OIDC login flow for the provider you just added — it should open a browser to EntraID, authenticate, and redirect back to `localhost:8080`.
2. Send a message through Claude Desktop using this provider.
3. Decode the resulting token at jwt.ms or via `cut/base64/python3 -m json.tool` and confirm `portkey_oid`, `portkey_workspace`, and `scopes` are present and correct for the signed-in user's group:

```

{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "dgvSDvK8A5KyKypw1dAwTXD3CA"
}.{
  "aud": "c5490456-8e83-4df6-a979-9ed2b4dd84a5",
  "iss": "https://login.microsoftonline.com/934a04e7-6fbf-4142-83bc-4cecbacabbfb/v2.0",
  "iat": 1790933662,
  "nbf": 1790933662,
  "exp": 1790938281,
  "aio":
"AaQAW/8eAAAAgotN7qRTX3JqtzD9Fy95jPx8esfvrJGS0Z0vD3goN8CajYH4uLMva001mxKNmumKAvcMqMAKQLu690f2GmkhB6rAsFI620zJW35xi9nNPbcy
tyZ/dgW/Yk2P9goNqGQLQ9aSzmgNp5VYjUmVEYGE9oQlh2XbgftM7yyeWaFYgQU+qGeqqgLzC/GZrI4dnPbAJJrbZj4JJdbPFPg2aLA==",
  "azp": "04b07795-8ddb-461a-bbee-02f9e1bf7b46",
  "azpacr": "0",
  "name": "Marc Gollop",
  "oid": "b473cc00-77d1-4b47-8b66-f5e94f786e11",
  "preferred_username": "mgollop@sase-au.io",
  "rh": "1.AUoA5wRKk79vQkGDvEzsusq7-1YEScWDjvZNqXme0rTdhKUAABxKAA.",
  "scp": "user_impersonation",
  "sid": "008df00a-a519-6980-2f87-11414b2be80c",
  "sub": "xw_xuxN6sDvBlaXjjwVIYs74rWtTLbMf9RPe7o13-R0",
  "tid": "934a04e7-6fbf-4142-83bc-4cecbacabbfb",
  "uti": "uH7GNP2v40yLrUHHh10AA",
  "ver": "2.0",
  "xms_ftd": "u4Dd4k_JiHeDBsIJeoTwn2Sb67nnkoeVa0cKBpCpJbQBamFwYw5LYXN0LWRzbXM",
  "portkey_oid": "95cb67bf-6fb5-4581-ac72-db32e2bb7f2c",
  "portkey_workspace": "ws-main-a-997260",
  "scopes": "completions.write",
  "metadata": "{
    \"environment\": \"production\",
    \"team\": \"frontend\"
  }"
}.[Signature]

```

A user in a different group gets different claim values from the same app, with no per-user configuration:

```
{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "dgvSDvK8A5KyKypw1dAwTXD3CA"
}, {
  "aud": "c5490456-8e83-4df6-a979-9ed2b4dd84a5",
  "iss": "https://login.microsoftonline.com/934a04e7-6fbf-4142-83bc-4cecbacabbfb/v2.0",
  "iat": 1790933925,
  "nbf": 1790933925,
  "exp": 1790939576,
  "aio":
"AVQAAq/8eAAAAUsoWXhkSuprACsNybu4m3tk7LVCcNYXWfDYcS+WvJzwcW4WqTzjdwB6iFTM2D9TfSkT+k371tVadsFfUH0oI8jtivZNDtE5FjSS7SndbBI="
,
  "azp": "04b07795-8ddb-461a-bbee-02f9e1bf7b46",
  "azpacr": "0",
  "name": "AIRS Demo User",
  "oid": "c604bcbe-43cb-475a-ae1e-e4ea4ae88b23",
  "preferred_username": "airsdemo@sase-au.io",
  "rh": "1.AUoA5wRKK79vQkGDvEzsusq7-1YEScWDjvZNqXme0rTdhKUAALxKAA.",
  "scp": "user_impersonation",
  "sid": "0098ec8a-ccb3-c990-a152-fe8883135204",
  "sub": "dNznM-MXrQo7wFnwvBk0EPtCisM7A4GgV7gTk4vfsEk",
  "tid": "934a04e7-6fbf-4142-83bc-4cecbacabbfb",
  "uti": "zxHH55QJzUKXaM2fMwxkAA",
  "ver": "2.0",
  "xms_ftd": "iY6Dv_sUx5yRxK_2mQj0g2KbNdH0tcVIX-1ynU3yuzMBamFwYw5LYXN0LWRzbXM",
  "portkey_oid": "95cb67bf-6fb5-4581-ac72-db32e2bb7f2c",
  "portkey_workspace": "ws-main-a-997260",
  "scopes": "completions.write",
  "metadata": "{ \"environment\": \"production\", \"team\": \"backend\" }"
}.[Signature]
```

4. Confirm requests are landing in AIGW's control plane logs/analytics for the mapped workspace.



SCM-Logs

Troubleshooting

- **User can sign in but gets no/wrong `portkey_workspace`** — they're not a member of any group referenced by a claim condition in step 6. Add them to the correct group.
- **User can't sign in at all** — confirm **Assignment required?** is **Yes** (step 5a) and the user is a member of an assigned group (step 5b).
- **Claims don't appear in the token** — claims must be added under **Enterprise Applications → your app → Single sign-on → Attributes & Claims**, not under the App Registration's **Token configuration** tab — these are two different systems and only the former supports the group-conditioned values used here. Also confirm the certificate from step 3 is uploaded; Entra silently ignores custom claims without a signing certificate.
- **401 Unauthorized** — verify **JWT_ENABLED: ON** and **JWT_LOCAL_AUTH_DEFAULT_SCOPES** are set on the gateway (see [docker-compose.yml](#)), and that the ID token actually contains **portkey_oid** and **scopes** (decode it at [jwt.ms](#)).
- **Org/workspace not resolved** — double check **portkey_oid** in the token matches this deployment's **ORGANISATIONS_TO_SYNC** env var exactly.
- **Redirect fails / stuck on EntraID** — confirm the redirect URI registered in EntraID (step 2) exactly matches the redirect port configured in Claude Desktop (step 11), including **`http://localhost:<port>`**.
- **Authentication fails right after setup with an issuer mismatch** — confirm **requestedAccessTokenVersion: 2** was saved in the manifest (step 4); a v1.0 token's issuer won't match the v2.0 issuer URL configured in step 11.