

DOCKER NETWORKING TIPS

Load Balance Options

Presenter's Name: Sreenivas Makam

Associated Youtube video:

<https://youtu.be/aQmPqrHleJU>

About me

- ❑ Senior Engineering Manager at Cisco Systems Data Center group
- ❑ Author of “Mastering CoreOS” <https://www.packtpub.com/networking-and-servers/mastering-coreos/>)
- ❑ Docker Captain(<https://www.docker.com/community/docker-captains>)
- ❑ Blog: <https://sreeninet.wordpress.com/>
- ❑ Projects: <https://github.com/smakam>
- ❑ LinkedIn: <https://in.linkedin.com/in/sreenivasmakam>
- ❑ Twitter: @srmakam



What is Service Discovery?

- ❑ Allows micro services running as containers to discover each other automatically.
- ❑ Components of Service Discovery
 - Health check – Identify healthy service
 - DNS – Maintain service name to IP mapping
- ❑ Load balancer uses Service discovery database.
- ❑ Standalone Service discovery software examples – Consul, etcd

Service Discovery in Docker

- ❑ Service discovery is provided by DNS server available in Docker engine.
- ❑ For unmanaged containers, container name resolves to container IP. Alias names can be also be used.
- ❑ For services using service IP(endpoint mode=vip), service name resolves to service IP which in turn forwards the request to containers. In this case, ipvs based L4 load balancing is done.
- ❑ For services using direct DNS(endpoint mode=dnsrr), service name directly resolves to container IP. In this case, DNS round robin load balancing is done.
- ❑ Service Discovery is network scoped. Only containers in same network can discover each other.


What is Load balancing?

- ❑ L4 Load balancer does load balancing based on L3 and L4 fields.
- ❑ L7 Load balancer uses URL fields to load balance.
- ❑ Load balancer also supports advanced features like SSL/TLS termination, Content based routing, Access control and authorization, Rewrites and redirects, sticky session
- ❑ Example Load balancers are nginx, haproxy, traefik, ELB in AWS.

Load balancing in Docker


- ❑ For unmanaged containers, load balancing is done using simple round robin load balancing. Using aliases, a single alias can load balance to multiple unmanaged containers .
- ❑ Docker takes care of load balancing internal services to the containers associated with the services.
- ❑ For services using service IP(endpoint mode=vip), ipvs and iptables are used to load balance. This provides L4 based load balancing. Ipvs is Linux kernel load balancing feature.
- ❑ For services using direct DNS(endpoint mode=dnsrr), DNS round robin balancing is used.
- ❑ For services exposed externally, Docker uses routing mesh to expose the service on all Swarm nodes. Routing mesh uses “ingress” network to connect all nodes.
- ❑ For HTTP based load balancing, HRM(HTTP Routing mesh) can be used. This is supported only with Docker EE.
- ❑ Docker can also integrate with external load balancers like nginx, haproxy, traefik as well as cloud load balancers like ELB.

Internal Load balancer




Example: <https://github.com/smakam/docker/tree/master/loadbalance/internal>

Internal Load balancer - Details




Example: <https://github.com/smakam/docker/tree/master/loadbalance/internal>

Ingress Load balancer




Example: <https://github.com/smakam/docker/tree/master/loadbalance/ingress>

Ingress Load balancer - Details




Example: <https://github.com/smakam/docker/tree/master/loadbalance/ingress>

Proxy Load balancer



Example: <https://github.com/smakam/docker/tree/master/loadbalance/proxy>

L7 Load balancer



Example: <https://github.com/smakam/docker/tree/master/loadbalance/traefik>

References

- ❑ [White paper on Docker networking](#)
- ❑ [HRM and UCP White paper](#)
- ❑ [Docker blogs by me](#)
- ❑ [Docker Networking – common issues and troubleshooting techniques](#)