

Databricks Feature Store

Python API

Databricks FeatureStoreClient

```
class databricks.feature_store.client.FeatureStoreClient(feature_store_uri: Optional[str] = None, model_registry_uri: Optional[str] = None)
```

Bases: [object](#)

Client for interacting with the Databricks Feature Store.

```
create_table(name: str, primary_keys: Union[str, List[str]], df: Optional[pyspark.sql.dataframe.DataFrame] = None, *, timestamp_keys: Union[str, List[str], None] = None, partition_columns: Union[str, List[str], None] = None, schema: Optional[pyspark.sql.types.StructType] = None, description: Optional[str] = None, tags: Optional[Dict[str, str]] = None, **kwargs) → databricks.feature_store.entities.feature_table.FeatureTable
```

Create and return a feature table with the given name and primary keys.

The returned feature table has the given name and primary keys. Uses the provided **schema** or the inferred schema of the provided **df**. If **df** is provided, this data will be saved in a Delta table. Supported data types for features are: **IntegerType**, **LongType**, **FloatType**, **DoubleType**, **StringType**, **BooleanType**, **DateType**, **TimestampType**, **ShortType**, **ArrayType**, **MapType**, and **BinaryType**, and **DecimalType**.

- Parameters:**
- **name** – A feature table name of the form `<database_name>.<table_name>`, for example `dev.user_features`.
 - **primary_keys** – The feature table's primary keys. If multiple columns are required, specify a list of column names, for example `['customer_id', 'region']`.
 - **df** – Data to insert into this feature table. The schema of **df** will be used as the feature table schema.
 - **timestamp_keys** –
Columns containing the event time associated with feature value.
Timestamp keys and primary keys of the feature table uniquely identify the feature value for an entity at a point in time.

Note

Experimental: This argument may change or be removed in a future release without warning.

- **partition_columns** –
Columns used to partition the feature table. If a list is provided, column ordering in the list will be used for partitioning.

Note

When choosing partition columns for your feature table, use columns that do not have a high cardinality. An ideal strategy would be such that you expect data in each partition to be at least 1 GB. The most commonly used partition column is a **date**.

Additional info: [Choosing the right partition columns for Delta tables](#)

- **schema** – Feature table schema. Either **schema** or **df** must be provided.
- **description** – Description of the feature table.
- **tags** –
Tags to associate with the feature table.

Note

Available starting with Databricks Runtime 10.5 for ML.

Other Parameters:

- **path** (**Optional[str]**) – Path in a supported filesystem. Defaults to the database location.

```
register_table(* , delta_table: str, primary_keys: Union[str, List[str]], timestamp_keys: Union[str, List[str], None] = None, description: Optional[str] = None, tags: Optional[Dict[str, str]] = None) → databricks.feature_store.entities.feature_table.FeatureTable
```

Register an existing Delta table as a feature table with the given primary keys.

The returned feature table has the same name as the Delta table.

Note

Available starting with Databricks Runtime 10.4 for ML.

- Parameters:
- **name** – A Delta table name of the form `<database_name>.<table_name>`, for example `dev.user_features`. The table must exist in the metastore.
 - **primary_keys** – The Delta table's primary keys. If multiple columns are required, specify a list of column names, for example `['customer_id', 'region']`.
 - **timestamp_keys** – Columns containing the event time associated with feature value. Together, the timestamp keys and primary keys uniquely identify the feature value at a point in time.
 - **description** – Description of the feature table.
 - **tags** – Tags to associate with the feature table.

Note

Available starting with Databricks Runtime 10.5 for ML.

Returns: A **FeatureTable** object.

```
get_table(name: str) → databricks.feature_store.entities.feature_table.FeatureTable
```

Get a feature table's metadata.

Parameters: **name** – A feature table name of the form `<database_name>.<table_name>`, for example `dev.user_features`.

```
drop_table(name: str) → None
```

Note

Experimental: This method may change or be removed in a future release without warning.

Delete the specified feature table. This API also drops the underlying Delta table.

Note

Available starting with Databricks Runtime 10.5 for ML.

Parameters: **name** – The feature table name of the form **<database_name>.<table_name>**, for example **dev.user_features**.

Note

Deleting a feature table can lead to unexpected failures in upstream producers and downstream consumers (models, endpoints, and scheduled jobs). You must delete any existing published online stores separately.

read_table(*name: str, **kwargs*) → pyspark.sql.dataframe.DataFrame

Read the contents of a feature table.

Parameters: **name** – A feature table name of the form **<database_name>.<table_name>**, for example **dev.user_features**.

Returns: The feature table contents, or an exception will be raised if this feature table does not exist.

write_table(*name: str, df: pyspark.sql.dataframe.DataFrame, mode: str = 'merge', checkpoint_location: Optional[str] = None, trigger: Dict[str, Any] = {'processingTime': '5 seconds'}*) → Optional[pyspark.sql.streaming.StreamingQuery]

Writes to a feature table.

If the input **DataFrame** is streaming, will create a write stream.

- Parameters:**
- **name** – A feature table name of the form `<database_name>.<table_name>`, for example `dev.user_features`. Raises an exception if this feature table does not exist.
 - **df** – Spark `DataFrame` with feature data. Raises an exception if the schema does not match that of the feature table.
 - **mode** –
Two supported write modes:
 - **"overwrite"** updates the whole table.
 - **"merge"** will upsert the rows in **df** into the feature table. If **df** contains columns not present in the feature table, these columns will be added as new features.
 - **checkpoint_location** – Sets the Structured Streaming `checkpointLocation` option. By setting a **checkpoint_location**, Spark Structured Streaming will store progress information and intermediate state, enabling recovery after failures. This parameter is only supported when the argument **df** is a streaming `DataFrame`.
 - **trigger** – If **df.isStreaming**, **trigger** defines the timing of stream data processing, the dictionary will be unpacked and passed to `DataStreamWriter.trigger` as arguments. For example, **trigger={'once': True}** will result in a call to `DataStreamWriter.trigger(once=True)`.

Returns: If **df.isStreaming**, returns a PySpark `StreamingQuery`. `None` otherwise.

```
add_data_sources(* , feature_table_name: str, source_names: Union[str, List[str]],  
source_type: str = 'custom') → None
```

Note

Experimental: This method may change or be removed in a future release without warning.

Add data sources to the feature table.

- Parameters:**
- **feature_table_name** – The feature table name.
 - **source_names** – Data source names. For multiple sources, specify a list. If a data source name already exists, it is ignored.
 - **source_type** – One of the following:
 - **"table"** : Table in format <database_name>.<table_name> and is stored in the metastore (eg Hive).
 - **"path"** : Path, eg in the Databricks File System (DBFS).
 - **"custom"** : Manually added data source, neither a table nor a path.

```
delete_data_sources(* , feature_table_name: str, source_names: Union[str, List[str]]) → None
```

Note

Experimental: This method may change or be removed in a future release without warning.

Delete data sources from the feature table.

Note

Data sources of all types (table, path, custom) that match the source names will be deleted.

- Parameters:**
- **feature_table_name** – The feature table name.
 - **source_names** – Data source names. For multiple sources, specify a list. If a data source name does not exist, it is ignored.

```
publish_table(name: str, online_store: databricks.feature_store.online_store_spec.online_store_spec.OnlineStoreSpec, *, filter_condition: Optional[str] = None, mode: str = 'merge', streaming: bool = False, checkpoint_location: Optional[str] = None, trigger: Dict[str, Any] = {'processingTime': '5 minutes'}, features: Union[str, List[str], None] = None) → Optional[pyspark.sql.streaming.StreamingQuery]
```

Publish a feature table to an online store.

- Parameters:
- **name** – Name of the feature table.
 - **online_store** – Specification of the online store.
 - **filter_condition** – A SQL expression using feature table columns that filters feature rows prior to publishing to the online store. For example, `"dt > '2020-09-10'"`. This is analogous to running `df.filter` or a **WHERE** condition in SQL on a feature table prior to publishing.
 - **mode** –
Specifies the behavior when data already exists in this feature table in the online store. If **"overwrite"** mode is used, existing data is replaced by the new data. If **"merge"** mode is used, the new data will be merged in, under these conditions:
 - If a key exists in the online table but not the offline table, the row in the online table is unmodified.
 - If a key exists in the offline table but not the online table, the offline table row is inserted into the online table.
 - If a key exists in both the offline and the online tables, the online table row will be updated.
 - **streaming** – If **True**, streams data to the online store.
 - **checkpoint_location** – Sets the Structured Streaming **checkpointLocation** option. By setting a **checkpoint_location**, Spark Structured Streaming will store progress information and intermediate state, enabling recovery after failures. This parameter is only supported when **streaming=True**.
 - **trigger** – If **streaming=True**, **trigger** defines the timing of stream data processing. The dictionary will be unpacked and passed to **DataStreamWriter.trigger** as arguments. For example, **trigger={'once': True}** will result in a call to **DataStreamWriter.trigger(once=True)**.
 - **features** –
Specifies the feature column(s) to be published to the online store. The selected features must be a superset of existing online store features. Primary key columns and timestamp key columns will always be published.

Note

This parameter is only supported when **mode="merge"**. When **features** is not set, the whole feature table will be published.

Returns: If **streaming=True**, returns a PySpark **StreamingQuery**, **None** otherwise.

```
create_training_set(df: pyspark.sql.dataframe.DataFrame, feature_lookups:
List[databricks.feature_store.entities.feature_lookup.FeatureLookup], label: Union[str, List[str],
None], exclude_columns: List[str] = []) → databricks.feature_store.training_set.TrainingSet
```

Create a **TrainingSet**.

- Parameters:
- **df** – The **DataFrame** used to join features into.
 - **feature_lookups** – List of features to join into the **DataFrame**.
 - **label** – Names of column(s) in **DataFrame** that contain training set labels.
To create a training set without a label field, i.e. for unsupervised training set, specify label = None.
 - **exclude_columns** – Names of the columns to drop from the **TrainingSet DataFrame**.

Returns: A **TrainingSet** object.

```
log_model(model: Any, artifact_path: str, *, flavor: module, training_set:
databricks.feature_store.training_set.TrainingSet, registered_model_name: Optional[str] =
None, await_registration_for: int = 300, **kwargs)
```

Log an MLflow model packaged with feature lookup information.

Note

The **DataFrame** returned by **TrainingSet.load_df()** must be used to train the model. If it has been modified (for example data normalization, add a column, and similar), these modifications will not be applied at inference time, leading to training-serving skew.

- Parameters:
- **model** – Model to be saved. This model must be capable of being saved by **flavor.save_model**. See the [MLflow Model API](#).
 - **artifact_path** – Run-relative artifact path.
 - **flavor** – MLflow module to use to log the model. **flavor** should have type **ModuleType**. The module must have a method **save_model**, and must support the **python_function** flavor. For example, **mlflow.sklearn**, **mlflow.xgboost**, and similar.
 - **training_set** – The **TrainingSet** used to train this model.
 - **registered_model_name** –

Note

Experimental: This argument may change or be removed in a future release without warning.

If given, create a model version under **registered_model_name**, also creating a registered model if one with the given name does not exist.

- **await_registration_for** – Number of seconds to wait for the model version to finish being created and is in **READY** status. By default, the function waits for five minutes. Specify **0** or **None** to skip waiting.

Returns: **None**

```
score_batch(model_uri: str, df: pyspark.sql.dataframe.DataFrame, result_type: str = 'double')  
→ pyspark.sql.dataframe.DataFrame
```

Evaluate the model on the provided **DataFrame**.

Additional features required for model evaluation will be automatically retrieved from **Feature Store**.

The model must have been logged with **FeatureStoreClient.log_model()**, which packages the model with feature metadata. Unless present in **df**, these features will be looked up from **Feature Store** and joined with **df** prior to scoring the model.

If a feature is included in **df**, the provided feature values will be used rather than those stored in **Feature Store**.

For example, if a model is trained on two features **account_creation_date** and **num_lifetime_purchases**, as in:

```

feature_lookups = [
    FeatureLookup(
        table_name = 'trust_and_safety.customer_features',
        feature_name = 'account_creation_date',
        lookup_key = 'customer_id',
    ),
    FeatureLookup(
        table_name = 'trust_and_safety.customer_features',
        feature_name = 'num_lifetime_purchases',
        lookup_key = 'customer_id'
    ),
]

with mlflow.start_run():
    training_set = fs.create_training_set(
        df,
        feature_lookups = feature_lookups,
        label = 'is_banned',
        exclude_columns = ['customer_id']
    )
    ...
    fs.log_model(
        model,
        "model",
        flavor=mlflow.sklearn,
        training_set=training_set,
        registered_model_name="example_model"
    )

```

Then at inference time, the caller of `FeatureStoreClient.score_batch()` must pass a `DataFrame` that includes `customer_id`, the `lookup_key` specified in the `FeatureLookups` of the `training_set`. If the `DataFrame` contains a column `account_creation_date`, the values of this column will be used in lieu of those in `Feature Store`. As in:

```

# batch_df has columns ['customer_id', 'account_creation_date']
predictions = fs.score_batch(
    'models:/example_model/1',
    batch_df
)

```

Parameters: • **model_uri** –

The location, in URI format, of the MLflow model logged using `FeatureStoreClient.log_model()`. One of:

- **runs:** /<mlflow_run_id>/run-relative/path/to/model
- **models:** /<model_name>/<model_version>
- **models:** /<model_name>/<stage>

For more information about URI schemes, see [Referencing Artifacts](#).

• **df** –

The **DataFrame** to score the model on. **Feature Store** features will be joined with **df** prior to scoring the model. **df** must:

1. Contain columns for lookup keys required to join feature data from Feature Store, as specified in the **feature_spec.yaml** artifact.
2. Contain columns for all source keys required to score the model, as specified in the **feature_spec.yaml** artifact.
3. Not contain a column **prediction**, which is reserved for the model's predictions. **df** may contain additional columns.

• **result_type** – The return type of the model. See `mlflow.pyfunc.spark_udf()` **result_type**.

Returns:

A **DataFrame** containing:

1. All columns of **df**.
2. All feature values retrieved from Feature Store.
3. A column **prediction** containing the output of the model.

set_feature_table_tag(**, table_name: str, key: str, value: str*) → None

Create or update a tag associated with the feature table. If the tag with the corresponding key already exists, its value will be overwritten with the new value.

Note

Available starting with Databricks Runtime 10.5 for ML.

Parameters:

- **table_name** – the feature table name
- **key** – tag key
- **value** – tag value

`delete_feature_table_tag(*, table_name: str, key: str) → None`

Delete the tag associated with the feature table. Deleting a non-existent tag will emit a warning.

Note

Available starting with Databricks Runtime 10.5 for ML.

Parameters:

- **`table_name`** – the feature table name.
- **`key`** – the tag key to delete.

Feature Lookup

class

`databricks.feature_store.entities.feature_lookup.FeatureLookup`(*`table_name: str, lookup_key: Union[str, List[str]], *, feature_names: Union[str, List[str], None] = None, rename_outputs: Optional[Dict[str, str]] = None, timestamp_lookup_key: Union[str, List[str], None] = None, **kwargs`*)

Bases:

`databricks.feature_store.entities._feature_store_object._FeatureStoreObject`

Value class used to specify a feature to use in a **`TrainingSet`**.

- Parameters:
- **table_name** – Feature table name.
 - **lookup_key** – Key to use when joining this feature table with the `DataFrame` passed to `FeatureStoreClient.create_training_set()`. The **lookup_key** must be the columns in the `DataFrame` passed to `FeatureStoreClient.create_training_set()`. The type of **lookup_key** columns in that `DataFrame` must match the type of the primary key of the feature table referenced in this `FeatureLookup`.
 - **feature_names** – A single feature name, a list of feature names, or `None` to lookup all features (excluding primary keys) in the feature table at the time that the training set is created. If your model requires primary keys as features, you can declare them as independent `FeatureLookups`.
 - **rename_outputs** – If provided, renames features in the `TrainingSet` returned by of `FeatureStoreClient.create_training_set`.
 - **timestamp_lookup_key** – Key to use when performing point-in-time lookup on this feature table with the `DataFrame` passed to `FeatureStoreClient.create_training_set()`. The **timestamp_lookup_key** must be the columns in the `DataFrame` passed to `FeatureStoreClient.create_training_set()`. The type of **timestamp_lookup_key** columns in that `DataFrame` must match the type of the timestamp key of the feature table referenced in this `FeatureLookup`.

Note

Experimental: This argument may change or be removed in a future release without warning.

- **feature_name** – Feature name. **Deprecated** as of 0.3.4 [Databricks Runtime for ML 9.1]. Use **feature_names**.
- **output_name** – If provided, rename this feature in the output of `FeatureStoreClient.create_training_set`. **Deprecated** as of 0.3.4 [Databricks Runtime for ML 9.1]. Use **rename_outputs**.

```
__init__(table_name: str, lookup_key: Union[str, List[str]], *, feature_names: Union[str, List[str], None] = None, rename_outputs: Optional[Dict[str, str]] = None, timestamp_lookup_key: Union[str, List[str], None] = None, **kwargs)
```

Initialize a `FeatureLookup` object.

table_name

The table name to use in this `FeatureLookup`.

lookup_key

The lookup key(s) to use in this FeatureLookup.

feature_name

The feature name to use in this FeatureLookup. **Deprecated** as of 0.3.4 [Databricks Runtime for ML 9.1]. Use **feature_names**.

output_name

The output name to use in this FeatureLookup. **Deprecated** as of 0.3.4 [Databricks Runtime for ML 9.1]. Use **feature_names**.

Training Set

```
class databricks.feature_store.training_set.TrainingSet(feature_spec: databricks.feature_store.entities.feature_spec.FeatureSpec, df: pyspark.sql.dataframe.DataFrame, labels: List[str], feature_table_metadata_map: Dict[str, databricks.feature_store.entities.feature_table.FeatureTable], feature_table_data_map: Dict[str, pyspark.sql.dataframe.DataFrame])
```

Bases: **object**

Class that defines **TrainingSet** objects.

Note

The **TrainingSet** constructor should not be called directly. Instead, call **FeatureStoreClient.create_training_set**.

load_df() → `pyspark.sql.dataframe.DataFrame`

Load a **DataFrame**.

Return a **DataFrame** for training.

The returned **DataFrame** has columns specified in the **feature_spec** and **labels** parameters provided in **FeatureStoreClient.create_training_set**.

Returns: A **DataFrame** for training

Feature Table

Classes

```
class databricks.feature_store.entities.feature_table.FeatureTable(name,
table_id, description, primary_keys, partition_columns, features, creation_timestamp=None,
online_stores=[], notebook_producers=[], job_producers=[], table_data_sources=[],
path_data_sources=[], custom_data_sources=[], timestamp_keys=[], tags=None)
```

Value class describing one feature table.

This will typically not be instantiated directly, instead the

FeatureStoreClient.create_table will create **FeatureTable** objects.

Online Store Spec

```
class
databricks.feature_store.online_store_spec.AmazonRdsMySQLSpec(hostname:
str, port: int, user: Optional[str] = None, password: Optional[str] = None, database_name:
Optional[str] = None, table_name: Optional[str] = None, driver_name: Optional[str] = None,
read_secret_prefix: Optional[str] = None, write_secret_prefix: Optional[str] = None)
```

Bases:

databricks.feature_store.online_store_spec.online_store_spec.OnlineStoreSpec

Class that defines and creates **AmazonRdsMySQLSpec** objects.

This **OnlineStoreSpec** implementation is intended for publishing features to Amazon RDS MySQL and Aurora (MySQL-compatible edition).

See **OnlineStoreSpec** documentation for more usage information, including parameter descriptions.

- Parameters:
- **hostname** – Hostname to access online store.
 - **port** – Port number to access online store.
 - **user** – Username that has access to the online store.
 - **password** – Password to access the online store.
 - **database_name** – Database name.
 - **table_name** – Table name.
 - **driver_name** – Name of custom JDBC driver to access the online store.
 - **read_secret_prefix** – Prefix for read secret.
 - **write_secret_prefix** – Prefix for write secret.

hostname

Hostname to access the online store.

port

Port number to access the online store.

database_name

Database name.

cloud

Define the cloud property for the data store.

store_type

Define the data store type property.

auth_type()

Publish Auth type.

```
class databricks.feature_store.online_store_spec.AzureMySQLSpec(hostname: str, port: int, user: Optional[str] = None, password: Optional[str] = None, database_name: Optional[str] = None, table_name: Optional[str] = None, driver_name: Optional[str] = None, read_secret_prefix: Optional[str] = None, write_secret_prefix: Optional[str] = None)
```

Bases:

```
databricks.feature_store.online_store_spec.online_store_spec.OnlineStoreSpec
```

Define the **AzureMySQLSpec** class.

This **OnlineStoreSpec** implementation is intended for publishing features to Azure Database for MySQL.

See **OnlineStoreSpec** documentation for more usage information, including parameter descriptions.

- Parameters:
- **hostname** – Hostname to access online store.
 - **port** – Port number to access online store.
 - **user** – Username that has access to the online store.
 - **password** – Password to access the online store.
 - **database_name** – Database name.
 - **table_name** – Table name.
 - **driver_name** – Name of custom JDBC driver to access the online store.
 - **read_secret_prefix** – Prefix for read secret.
 - **write_secret_prefix** – Prefix for write secret.

hostname

Hostname to access the online store.

port

Port number to access the online store.

database_name

Database name.

cloud

Define the cloud the future store runs.

store_type

Define the data store type.

auth_type()

Publish Auth type.

class

databricks.feature_store.online_store_spec.AzureSqlServerSpec(*hostname: str, port: int, user: Optional[str] = None, password: Optional[str] = None, database_name: Optional[str] = None, table_name: Optional[str] = None, driver_name: Optional[str] = None, read_secret_prefix: Optional[str] = None, write_secret_prefix: Optional[str] = None*)

Bases:

databricks.feature_store.online_store_spec.online_store_spec.OfflineStoreSpec

This **OnlineStoreSpec** implementation is intended for publishing features to Azure SQL Database (SQL Server).

The spec supports SQL Server 2019 and newer.

See **OnlineStoreSpec** documentation for more usage information, including parameter descriptions.

- Parameters:
- **hostname** – Hostname to access online store.
 - **port** – Port number to access online store.
 - **user** – Username that has access to the online store.
 - **password** – Password to access the online store.
 - **database_name** – Database name.
 - **table_name** – Table name.
 - **driver_name** – Name of custom JDBC driver to access the online store.
 - **read_secret_prefix** – Prefix for read secret.
 - **write_secret_prefix** – Prefix for write secret.

hostname

Hostname to access the online store.

port

Port number to access the online store.

database_name

Database name.

cloud

Define the cloud the future store runs.

store_type

Define the data store type.

auth_type()

Publish Auth type.

```
class databricks.feature_store.online_store_spec.AmazonDynamoDBSpec(*,  
region: Optional[str], access_key_id: Optional[str] = None, secret_access_key: Optional[str] = None,  
session_token: Optional[str] = None, table_name: Optional[str] = None, read_secret_prefix:  
Optional[str] = None, write_secret_prefix: Optional[str] = None, ttl: Optional[datetime.timedelta] =  
None)
```

Bases:

databricks.feature_store.online_store_spec.online_store_spec.OnlineStoreSpec

This **OnlineStoreSpec** implementation is intended for publishing features to Amazon DynamoDB.

If **table_name** is not provided, **FeatureStoreClient.publish_table** will use the offline store's database and table name combined as the online table name.

To use a different table name in the online store, provide a value for the **table_name** argument.

The expected read or write secrets for DynamoDB for a given **{prefix}** string are **\${prefix}-access-key-id**, **\${prefix}-secret-access-key**, and **\${prefix}-session-token**.

If none of the `access_key_id`, `secret_access_key`, and `write_secret_prefix` are passed, the instance profile attached to the cluster will be used to write to DynamoDB.

Note

AmazonDynamoDBSpec is available starting with Databricks Runtime 10.4 for ML.

Instance profile based writes are available starting with Databricks Runtime 10.5 for ML.

- Parameters:
- **region** – Region to access online store.
 - **access_key_id** – Access key ID that has access to the online store.
 - **secret_access_key** – Secret access key to access the online store.
 - **session_token** – Session token to access the online store.
 - **table_name** – Table name.
 - **read_secret_prefix** – Prefix for read secret.
 - **write_secret_prefix** – Prefix for write secret.
 - **ttl** – The time to live for data published to the online store. This attribute is only applicable when publishing time series feature tables. If the time to live is specified for a time series table, `FeatureStoreClient.publish_table()` will publish a window of data instead of the latest snapshot.

access_key_id

Access key ID that has access to the online store. Property will be empty if **write_secret_prefix** or the instance profile attached to the cluster are intended to be used.

secret_access_key

Secret access key to access the online store. Property will be empty if **write_secret_prefix** or the instance profile attached to the cluster are intended to be used.

session_token

Session token to access the online store. Property will be empty if **write_secret_prefix** or the instance profile attached to the cluster are intended to be used.

cloud

Define the cloud property for the data store.

store_type

Define the data store type.

region

Region to access the online store.

ttl

Time to live attribute for the online store.

auth_type()

Publish Auth type.

```
class databricks.feature_store.online_store_spec.AzureCosmosDBSpec(*,  
account_uri: str, database_name: Optional[str] = None, container_name: Optional[str] = None,  
read_secret_prefix: Optional[str] = None, write_secret_prefix: str)
```

Bases:

```
databricks.feature_store.online_store_spec.online_store_spec.OnlineStoreSpec
```

This **OnlineStoreSpec** implementation is intended for publishing features to Azure Cosmos DB.

If **database_name** and **container_name** are not provided, **FeatureStoreClient.publish_table** will use the offline store's database and table name as the Cosmos DB database and container name.

The expected read or write secret for Cosmos DB for a given **{prefix}** string is **`\${prefix}-authorization-key`**.

The authorization key can be either the Cosmos DB account primary or secondary key.

Note

Available starting with Databricks Runtime 11.1 for ML.

Parameters:

- **account_uri** – URI of the Cosmos DB account.
- **database_name** – Database name.
- **container_name** – Container name.
- **read_secret_prefix** – Prefix for read secret.
- **write_secret_prefix** – Prefix for write secret.

account_uri

Account URI of the online store.

database_name

Database name.

container_name

Container name.

cloud

Define the cloud property for the data store.

store_type

Define the data store type.

auth_type()

Publish Auth type.

```
class databricks.feature_store.online_store_spec.OnlineStoreSpec(_type,
hostname: [<class 'str'>, None] = None, port: [<class 'int'>, None] = None, user: Optional[str] = None,
password: Optional[str] = None, database_name: Optional[str] = None, table_name: Optional[str] =
None, driver_name: Optional[str] = None, read_secret_prefix: Optional[str] = None,
write_secret_prefix: Optional[str] = None, _internal_properties: Optional[Dict[str, str]] = None)
```

Bases: **abc.ABC**

Parent class for all types of **OnlineStoreSpec** objects.

Abstract base class for classes that specify the online store to publish to.

If **database_name** and **table_name** are not provided, **FeatureStoreClient.publish_table** will use the offline store's database and table names.

To use a different database and table name in the online store, provide values for both **database_name** and **table_name** arguments.

The JDBC driver can be customized with the optional **driver_name** argument. Otherwise, a default is used.

Strings in the primary key should not exceed 100 characters.

The online database should already exist.

Note

It is strongly suggested (but not required), to provide read-only database credentials via the **read_secret_prefix** in order to grant the least amount of database access privileges to the served model. When providing a **read_secret_prefix**, the secrets must exist in the scope name using the expected format, otherwise **publish_table** will return an error.

- Parameters:**
- **hostname** – Hostname to access online store. The database hostname cannot be changed. Subsequent publish calls to the same online store must provide the same hostname.
 - **port** – Port number to access online store. The database port cannot be changed. Subsequent publish calls to the same online store must provide the same port.
 - **user** – Username that has write access to the online store, or **None** if using **write_secret_prefix**.
 - **password** – Password to access the online store, or **None** if using **write_secret_prefix**.
 - **database_name** – Database name.
 - **table_name** – Table name.
 - **driver_name** – Name of custom JDBC driver to access the online store.
 - **read_secret_prefix** –
The secret scope name and secret key name prefix where read-only online store credentials are stored. These credentials will be used during online feature serving to connect to the online store from the served model. The format of this parameter should be **`${scope-name}/${prefix}`**, which is the name of the secret scope, followed by a **`/`**, followed by the secret key name prefix. The scope passed in must contain the following keys and corresponding values:
 - **`${prefix}-user`** where **`${prefix}`** is the value passed into this function. For example if this function is called with **`datascience/staging`**, the **`datascience`** secret scope should contain the secret named **`staging-user`**, which points to a secret value with the database username for the online store.
 - **`${prefix}-password`** where **`${prefix}`** is the value passed into this function. For example if this function is called with **`datascience/staging`**, the **`datascience`** secret scope should contain the secret named **`staging-password`**, which points to a secret value with the database password for the online store.Once the **read_secret_prefix** is set for an online store, it cannot be changed.

- **write_secret_prefix** –

The secret scope name and secret key name prefix where read-write online store credentials are stored. These credentials will be used to connect to the online store to publish features. If **user** and **password** are passed, this field must be **None**, or an exception will be raised. The format of this parameter should be **`${scope-name}/${prefix}`**, which is the name of the secret scope, followed by a **`/`**, followed by the secret key name prefix. The scope passed in must contain the following keys and corresponding values:

- **`${prefix}-user`** where **`${prefix}`** is the value passed into this function. For example if this function is called with **`datascience/staging`**, the **`datascience`** secret scope should contain the secret named **`staging-user`**, which points to a secret value with the database username for the online store.
- **`${prefix}-password`** where **`${prefix}`** is the value passed into this function. For example if this function is called with **`datascience/staging`**, the **`datascience`** secret scope should contain the secret named **`staging-password`**, which points to a secret value with the database password for the online store.

type

Type of the online store.

table_name

Table name.

user

Username that has access to the online store.

Property will be empty if **`write_secret_prefix`** argument was used.

password

Password to access the online store.

Property will be empty if **`write_secret_prefix`** argument was used.

driver

Name of the custom JDBC driver to access the online store.

read_secret_prefix

Prefix for read access to online store.

Name of the secret scope and prefix that contains the username and password to access the online store with read-only credentials.

See the **read_secret_prefix** parameter description for details.

write_secret_prefix

Secret prefix that contains online store login info.

Name of the secret scope and prefix that contains the username and password to access the online store with read/write credentials. See the **write_secret_prefix** parameter description for details.

cloud

Cloud provider where this online store is located.

store_type

Store type.

auth_type()

Publish Auth type.