Formal Verification in Scala

Ramon Boss, Anna Doukmak

June 11, 2019

Formal verification components //TODO: or concept

Process of verification //TODO: change the title

Formal verification components //TODO: or concept

Process of verification //TODO: change the title

Stainless

- Pure Scala code
- Imperative features
- Formal specification with pre- and postcondition
- Outcomes of verification: valid, invalid, unknown

Properties to verify

- Bitcoin-S project
- No Inflation Property
- Addition with Zero Property

Formal verification components //TODO: or concept

Process of verification //TODO: change the title

Verifying No Inflation Property

- Validation of a transaction with checkTransaction
- Integration of Stainless
- Adjusting the property
- Bug in checkTransaction

Verifying No Inflation Property

- Validation of a transaction with checkTransaction
- Integration of Stainless
- Adjusting the property
- Bug in checkTransaction

Bugfix

```
▼ 6 ■■■■■ core-test/src/test/scala/org/bitcoins/core/protocol/transaction/TransactionTest.scala &
   213
            00 -294,6 +294,12 00 class TransactionTest extends FlatSpec with MustMatchers (
                it must "check transaction with two out point referencing the same tx with different indexes" in {
                  val hex = "0200000002924942b0b7c12ece0dc8100d74a1cd29acd6cfc60698bfc3f07d83890eec20b6000000006a47304402202831
                  val btx = BaseTransaction.fromHex(hex)
                  ScriptInterpreter.checkTransaction(btx) must be(true)
                private def findInput(
                    outPoint: TransactionOutPoint): Option((TransactionInput, Int)) = {
   SIS
∨ 4 ■■■■ core/src/main/scala/org/bitcoins/core/script/interpreter/ScriptInterpreter.scala €
   213
           00 -779,8 +779,8 00 sealed abstract class ScriptInterpreter {
                    outputValues.fold(CurrencyUnits.zero)(_ + _)
                  val allOutputsValidMonevRange = validMonevRange(totalSpentByOutputs)
                  val prevOutputTxIds = transaction.inputs.map(_.previousOutput.txId)
                  val noDuplicateInputs = prevOutputTxIds.distinct.size == prevOutputTxIds.size
                  val prevOutputs = transaction.inputs.map( .previousOutput)
                  val noDuplicateInputs = prevOutputs.distinct.size == prevOutputs.size
                  val isValidScriptSiqForCoinbaseTx = transaction.isCoinbase match (
                    case true =>
   SIR
```

Verifying Addition with Zero

- Datatype Satoshis
- Method for verification

```
+(c: CurrencyUnit): CurrencyUnit
```

• Rewriting 2 classes into Pure Scala

Rewriting the code

Formal specification

```
override def +(c: CurrencyUnit): CurrencyUnit = {
   require(c.satoshis == Satoshis.zero)
   Satoshis(satoshis.underlying + c.satoshis.
        underlying)
} ensuring(res => res.satoshis == this.satoshis)
```

Formal verification components //TODO: or concept

Process of verification $//\mathsf{TODO}$: change the title

Output of Stainless

```
| Warning | The 23 native interface is not voxilable, falling back onto sat-23.
| Info | Checking caches 'cast correctness' V for underlying 69930...
| Info | Checking caches 'cast correctness' V for underlying 69930...
| Info | Cache hit: 'cast correctness' V for inv 69930...
| Info | Cache hit: 'cast correctness' V for inv 69930...
| Info | Cache hit: 'cast correctness' V for inv 69930...
| Info | Cache hit: 'cast correctness' V for underlying 69930...
| Info | Cache hit: 'cast correctness' V for underlying 69930...
| Info | Cache hit: 'cast correctness' V for underlying 69930...
| Info | Cache hit: 'cast correctness' V for underlying 69930...
| Info | Cache hit: 'cast correctness' V for underlying 69930...
| Info | Cache hit: 'precond. (call checkmedicthiss, underlying thiss) + u ...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:11...
| Checking caches 'precond. (call checkmedicthiss, underlying fints) + u...) V for * 822:
```