

Project 14

Contour Placement for PUMA 560

Format: Group of two students; simulation-based project.

Prerequisites: Full-pose inverse kinematics, shoulder–elbow–wrist classification, singularities, and path continuation.

Motivation

A contour may be geometrically small and entirely reachable yet fail from every admissible initial posture at a particular placement. Translating or rotating the task changes the IK trajectories and their margins. This project connects task placement to the global branch structure of a specific noncuspidal industrial robot.

Task

Overall objectives. Map where a fixed full-pose contour can be executed by PUMA 560, identify which initial shoulder–elbow–wrist classes survive, and explain feasibility boundaries through singularities and joint limits.

- **Validate the PUMA full-pose model.** Use the supplied D–H model and analytical IK; implement signed shoulder–elbow–wrist classification. Verify forward pose closure and document joint limits and base/tool transforms. Keep all mathematical branches distinct before physical filtering.
- **Define a contour and placement family.** Specify one closed contour with a smooth or explicitly segmented orientation schedule. Place the complete pose sequence using $T'_k = T_\Delta T_k$, including orientation. Explore two translation coordinates on a small grid and compare two fixed orientations of the whole contour.
- **Continue every admissible initial class.** For each placement, enumerate initial IKs and lift the full-pose path from every valid one. Track class identity, position/orientation residuals, joint limits, and arm and wrist regularity. Never repair a failed branch by jumping to another configuration at the next sample.
- **Produce branch-specific placement maps.** For each initial class, plot complete-path feasibility against the two placement coordinates. Distinguish unreachable poses, branch termination, joint-limit violations, and singularity-margin failures. Compare surviving trajectories by joint travel and minimum margins.
- **Explain the boundaries geometrically.** Select two neighboring placements with different outcomes. Plot the PUMA arm determinant in (q_2, q_3) , overlay the wrist-center IK trajectory, and relate its workspace image to arm IK-count regions. Diagnose wrist failures using the full Jacobian rather than the reduced position plot alone.

Specifics and scope

Use one contour, a 5×5 translation grid, and two fixed placement rotations; locally refine only one boundary. Begin with about 150 samples per contour. Choose a justified characteristic length for the mixed pose Jacobian and use the same thresholds throughout. This is kinematic placement analysis; cycle-time optimization and collision-checker development are not required.

Check both translation and orientation residuals for every claimed full-pose IK. Document angle periodicity and limits, Jacobian conventions, and any scaling used for singular values. State all fixed coordinates in reduced plots; a two-dimensional slice does not show the entire 6R singular set. Refine decisive transitions, and distinguish sampled evidence from a continuous-path guarantee. Collision freedom is not implied by these kinematic checks.

Expected outcome

Understand how task placement changes the feasible global IK choices for PUMA. Deliver the contour and placement transforms, eight class-labelled feasibility maps per placement orientation, and two detailed explanations connecting placement boundaries to joint-space and workspace structure.

Submit reproducible code, model parameters and test data, the required plots, a concise 5–6-page report, and a short simulation demonstration. Explain both successful cases and failures; conclusions must follow the numerical and geometric evidence rather than an expected outcome.

Resources

The PUMA 560 robot description (URDF) and visualization meshes (STL) will be provided to students, together with its D–H parameter set and analytical full-pose IK. Confirm joint offsets, physical joint limits, and the selected terminal frame when importing the model. Check the signed shoulder–elbow–wrist classification against the returned configurations.

Implement forward kinematics, Jacobian evaluation, and continuous branch tracking using the supplied model and IK. Validate poses independently using transforms composed from the URDF, and visualize trajectories with the supplied meshes. A position-only wrist-center solution is insufficient: include orientation and the fixed tool transform in every full-pose check.