FieldProof

Software pays for a fresh physical check.

The device signs its answer. The buyer verifies who answered and whether the answer is still fresh.



Working prototype: ESP32-C6 and Solana Devnet.

01 / A device signature authenticates a claim. It does not establish physical truth.

A remote inspection before a decision

Target workflow

An operator pays someone to check a physical fact at another site.

Its software lacks a reliable answer from an existing API.

FieldProof proposal

Commission one check from a device already on site.

Get a new answer tied to that request.

Value test: does the check replace a manual check or change a costly decision?

What the prototype does

1. Request a check

The buyer fixes the contact question, device key, price, and ten-second age limit.

2. Pay the operator

Solana x402 settles 0.001 test USDC before measurement.

3. Measure and sign

The ESP32 reads the physical input and signs a new answer for this request.

4. Verify and decide

The buyer verifies the source, request, signature, and age before its next action.

The evidence has limits

The buyer can verify

This approved device signed the answer to this request.

An old answer fails the age policy. An edited answer fails signature verification.

The physical demonstration

Release or hold BOOT. The contact changes between OPEN and CLOSED.

The contact does not prove contents, safety, or completed work.

peaq's role and the next test

Solana: demonstrated

Bounded Devnet payment and an original device-signed answer.

The public replay preserves the October 11 transaction and capture time.

peaq: live integration pending

A machine identity binds the offered service to its device key.

An activity record links a completed check to payment and evidence.

Next: one authorized operator, one repeated question, and a comparison with its current process.