	Porte moyeu arrière plaque de frein							
	POINT	X	Υ		POINT	X	Y	
	1	69,772	-20,133		20	60,864	-28,538	
	2	47,974	-27,741		21	53,435	-31,131	-
	3	44,660	-31,847		22	49,126	-36,469	
	4	39,350	-74,743	-	23	43,877	-78,876	
	5	32,403	-73,883	12	24	42,775	-78,740	le coordonnées usinage (à placer)
	7	36,681 30,071	-39,324 -33,989		25 26	28,107 27,005	-76,924	9 (1 /
	8		-39,654	-	27	30,433	-49,093	
	9		-40,833		28	21,841	-42,158	
	10		-38,349		29	15,488	-44,375	
	11	-26,276	-42,566		30	-11,004	-45,694	
	12		-74,769		31	-14,282	-44,904	
	13	-37,399	-73,868		32	-22,250	-50,387	
	14		-39,850		33	-25,955	-78,929	1
	15		-34,346		34	-27,056	-78,786	
	16	-64,360	-27,702		35	-41,713	-76,884	
					36	-42,814	-76,741	
16					37	-38,692	-44,996	2
-					38	-43,617	-37,840	20
					39	-54,661	-35,180	3
		15						7
39	38	37 35 00005,88	14	32 +	9			8 29 28 27 26 25 24 23

