TRUCK FEATURES





STANDARD EQUIPMENT:

BYD Iron-Phosphate Technology
Battery 80V 270Ah (21.6 kWh)
Single AC drive
4-way valve
Mechanical lever
TFT display
Cornering speed reduction
OPS (Operator Presence Sensor)
Regenerative braking system
Clear-view masts
Charger 80V 100A
Upprade charging gun

OPTIONAL EQUIPMENT:

1-hour fast-charging solution
Charger 80V 200A
Battery 80V 420Ah/540Ah
Synchronised steering control
Blue light
Panoramic mirror
Rear working light
LED lights
Multiple masts variants

Official WeChat

Official Website

ISO 9001
ISO 14001
OHSAS 18001

BYD Forklift

BYD Industrial Park, Shenzhen, Guangdong, China
Tel: +86 400 6298 666 **E-mail:** forklift@byd.com
04-21/KS/V1 www.bydforklift.com

BYD Forklift



The BYD EL30/35/38-PRO is a highly developed forklift truck which boasts advanced features and extreme operational capability whilst minimising the effect on the environment thanks to its patented BYD Iron-Phosphate Battery Technology. The efficient, emission-free BYD EL30/35/38-PRO fits into BYD's existing range to offer a powerful option for those seeking to optimise their material handling fleet, particularly in intensive warehouse operations where its short charge times offer high levels of availability.

EL30/35/38-PRO

3.0/3.5/3.8-Tonne Forklift Truck

CHANGE YOUR MIND
NOT YOUR BATTERY

Lithium | 5 YRS 10,000 HRS Battery Warranty | BYD Iron-Phosphate

EL30/35/38-PRO TECHNICAL SPECIFICATIONS

Identification	1.1	Manufacturer			BYD	BYD	BYD
	1.2	Model			EL30-PRO	EL35-PRO	EL38-PRO
	1.3	Drive			Electric	Electric	Electric
	1.4	Operator type			Seat	Seat	Seat
	1.5	Rated capacity	Q	kg	3000	3500	3800
	1.6	Load centre	c	mm	500	500	500
	1.8	Load distance, centre of drive axle to fork	x	mm	485	485	485
	1.9	Wheelbase	y	mm	1770	1770	1770
Weight	2.1	Service weight		kg	4500	4820	4960
	2.2	Axle load, with load, front/rear		kg	6915/660	7680/715	8055/780
	2.3	Axle load, without load, front/rear		kg	2360/2140	2675/2145	2905/2055
Wheels, Chassis	3.1	Tyres			SE	SE	SE
	3.2	Tyre size, front		mm	21x9-9	21x9-9	21x9-9
	3.3	Tyre size, rear		mm	6.5-10	6.5-10	6.5-10
	3.5	Wheels, number front rear (x=driven wheels)			2x/2	2x/2	2x/2
	3.6	Track width, front	b10	mm	1030	1030	1030
	3.7	Track width, rear	b11	mm	946	946	946
Basic Dimensions	4.1	Tilt of mast/fork carriage forward/backward	a/b	deg	5/8	5/8	5/8
	4.2	Height, mast lowered	h1	mm	2105	2105	2120
	4.3	Free lift	h2	mm	130	130	130
	4.4	Lift height	h3	mm	3000	3000	3000
	4.5	Height, mast extended	h4	mm	4250	4250	4250
	4.7	Height of overhead guard	h6	mm	2215	2215	2245
	4.8	Seat height	h7	mm	1260	1260	1260
	4.12	Coupling height	h10	mm	390	390	390
	4.19	Overall length	l1	mm	3790	3790	3890
	4.20	Length to face of forks	l2	mm	2720	2720	2820
	4.21	Overall width	b1	mm	1270	1270	1270
	4.22	Fork dimensions	s/e/l	mm	45/125/1070	50/125/1070	50/150/1070
	4.23	Fork carriage ISO 2328, class/type A, B			3A	3A	3A
	4.24	Fork carriage width	b3	mm	1100	1100	1100
	4.31	Ground clearance, with load, below mast	m1	mm	120	120	135
	4.32	Ground clearance, centre of wheelbase	m2	mm	140	140	140
	4.33	Aisle width for pallets 1000x1200 crossways	Ast	mm	4105	4105	4205
	4.34	Aisle width for pallets 800x1200 lengthways	Ast	mm	4305	4305	4405
	4.35	Turning radius	Wa	mm	2440	2440	2440
Performance Data	5.1	Travel speed, with/without load		Km/h	16/18	16/18	16/18
	5.2	Lift speed, with/without load		mm/s	380/450	380/450	380/450
	5.3	Lowering speed, with/without load		mm/s	550/450	550/450	550/450
	5.6	Max. drawbar pull, with/without load		KN	15/11	15/11	15/11
	5.8	Max. gradeability, with/without load		%	18/20	18/20	18/20
	5.10	Service brake		s	Mech./Hydr.	Mech./Hydr.	Mech./Hydr.
Motor	6.1	Drive motor rating S2 60 min.		kW	21.5	21.5	21.5
	6.2	Lift motor rating at S3 15%		kW	24	24	24
	6.4	Battery voltage, nominal capacity K5		V/Ah	80/270Ah	80/270Ah	80/270Ah
	6.5	Battery weight		kg	485	485	485
Other	8.1	Type of drive control			AC	AC	AC
	8.2	Operating pressure for attachments		Mpa	18	18	18
	8.4	Sound level at the driver's ear		dB(A)	<75	<75	<75
	8.5	Towing coupling, type			PIN	PIN	PIN

*BYD reserves the right to alter and modify the design, features and technical parameters of its products at any given time and without pre-advice, as products are subject to ongoing and continuous development.


MAST SPECIFICATIONS

h3 Lifting Height (mm) h2 Full Free Lift Height (mm) (Load Backrest 950mm) h1 Height, Mast Fully Lowered (mm)
h4 Height, Mast Fully Extended (mm) (Load Backrest 950mm) α Tilt Forward β Tilt Backward

Mast Specifications (mm)	h3	h2	h1	h4	α	β	Residual Capacity (kg) (without attachment) @500MM		
							EL30-PRO	EL35-PRO	EL38-PRO
2-stage standard Mast	3000	130	2125	4000	5°	8°	3000	3500	3800
	3300	130	2275	4300	5°	8°	3000	3500	3800
	3500	130	2375	4500	5°	8°	3000	3500	3700
	4000	130	2625	5000	5°	8°	2778	3275	3459
	4500	130	2925	5500	5°	6°	2641	3125	3301
	5000	130	3225	6000	5°	6°	2373	2721	2976
2-stage FFL Mast	3000	1175	2125	4000	5°	8°	3000	3500	3800
	3300	1325	2275	4300	5°	8°	3000	3500	3800
	3500	1425	2375	4500	5°	8°	3000	3500	3700
	4000	1675	2625	5000	5°	8°	2778	3275	3459
3-stage with single FFL Mast	4000	1075	2025	5000	5°	6°	2778	3275	3459
	4500	1240	2190	5500	5°	6°	2641	3125	3301
	4800	1340	2290	5800	5°	6°	2516	2992	3162
	5000	1410	2360	6000	5°	6°	2373	2721	2976
	5500	1575	2525	6500	5°	4.5°	2196	2539	2785
	6000	1740	2690	7000	5°	4.5°	2087	2419	2551

LOADING CAPACITY


CAPACITY CHART



CAPACITY CHART



CAPACITY CHART



Model	Voltage \ Capacity	270Ah	420Ah	540Ah
EL30-PRO	80V	●	○	○
EL35-PRO		●	○	○
EL38-PRO		●	○	○
Charger	380VAC	DC80V100A		
		DC80V200A		
	480VAC	DC80V100A		
		DC80V200A		

Remark: "●" standard equipment, "○" optional equipment.

