

l3erw-disambig^{*}

Erwann Rogard[†]

Released 2018/05/20

Abstract

L^AT_EX3 package to add a prefix to the names of commands created using `\NewDocumentCommand`, so as to prevent conflicts with external commands.

1 Usage

<code>\disambigset</code>	<code>\disambigset{<prefix>}</code>
---------------------------	---

See Listing 1

<code>\disambignewcmd</code>	<code>\disambignewcmd{<cs>}{<pars>}{<code>}</code>
------------------------------	--

<code>\disambignewcmd*</code>	Analogues of <code>\NewDocumentCommand</code> and <code>\RenewDocumentCommand</code> See Listing 2
-------------------------------	---

<code>\disambignewenv</code>	<code>\disambignewenv{<cs>}{<pars>}{<code1>}{<code2>}</code>
------------------------------	--

<code>\disambignewenv*</code>	Analogues of <code>\NewDocumentEnvironment</code> and <code>\RenewDocumentEnvironment</code> See Listing 3
-------------------------------	---

Listing 1

Input

```
\disambigset{my}
```

Output

Listing 2

Input

```
\disambignewcmd{foo}{m}{#1~world!}  
\noindent\myfoo{Hello}  
\disambignewcmd*{foo}{m}{#1~universe!}  
\myfoo{Hello}
```

Output

```
Hello world!  
Hello universe!
```

^{*}This file describes version v0.1, last revised 2018/05/20.

[†]firstname dot lastname AusTria gmail dot com

Listing 3

Input

```
\disambignewenv{bar}{}{\textrightarrow}{\textleftarrow}
\begin{mybar}
  Hello~world
\end{mybar}
\disambignewenv*{bar}{}{>}{<}
\\ \begin{mybar}
  Hello~world
\end{mybar}
```

Output

```
→ Hello world ←
> Hello world <
```

2 Implementation

```
1 \NeedsTeXFormat{LaTeX2e}
2 \RequirePackage{expl3}[2018/02/21]
3 \RequirePackage{xparse}[2018/02/21]
4 \ExplSyntaxOn
5 \tl_new:N \__erw_disambig_tl
6 \keys_define:nn { erw_disambig }
7 {
8   disambig .tl_set:N = \__erw_disambig_tl,
9   disambig .initial:n = erw
10 }
11 \cs_set:Npn \__erw_disambig:NN #1 #2 {#1{#2}}
12 \cs_generate_variant:Nn \__erw_disambig:NN { Nc }
13 \NewDocumentCommand{\disambignewcmd}{ s m m m }
14 {
15   \IfBooleanTF{#1}
16     {\__erw_disambig:Nc{\RenewDocumentCommand}}
17     {\__erw_disambig:Nc{\NewDocumentCommand}}
18     {\__erw_disambig_tl #2}
19     {#3}
20     {#4}
21 }
22 \NewDocumentCommand{\disambignewenv}{ s m m m m }
23 {
24   \IfBooleanTF{#1}
25     {\RenewDocumentEnvironment}
26     {\NewDocumentEnvironment}
27     {\__erw_disambig_tl #2}
28     {#3}
29     {#4}
30     {#5}
31 }
32 \NewDocumentCommand{\disambigset}{ m }
33 {
34   \keys_set:nn { erw_disambig }
```

```
35 {  
36     disambig={#1}  
37 }  
38 }  
39 %\ProcessKeysOptions{ erw_disambig }  
40 \ExplSyntaxOff
```