SYSTEM OF WORKING

"system of working" means the system adopted for the time being

For the working of trains on any portion of a railway.

"All trains working between stations shall be worked on one of the following system, namely –

(a) The Absolute Block System,

(b) The Automatic Block System,

(c) The Following Trains System,

(d) The Pilot Guard System,

(e) The Train–staff and Ticket System,

(f) The One Train Only System,

ESSENTIALS OF THE ABSOLUTE BLOCK SYSTEM-

(1) Where trains are worked on the absolute block system-

(a) No any train shall be allowed to leave a block station unless line clear has been received from the block station in advance,and

(b) On double lines such line clear shall not be given unless the line is clear,not only upto the first stop signal at the block station at which such line clear is given but also for an adequate distance beyond it;

(c) On single lines such line clear shall not be given unless the line is clear of trains running in the same direction, not only upto the first stop signal at the block station at which such line clear is given,but also for an adequate distance beyond it, and is clear of trains running in the direction towards the block station to which such line clear is given.

(2) Unless otherwise directed by approved special instructions,the adequate distance referred to in clauses(b) and (c) of sub-rule (1) shall not be less than-

(a) 400 metres in case of multiple-aspect lower quadrant signalling or two-aspect colour light signalling, and

(b) 180 metres in case of multiple-aspect signalling or modified lower quadrant signalling.

ESSENTIALS OF THE AUTOMATIC BLOCK SYSTEM ON SINGLE LINE.-

(1) Where trains on a single line are worked on the Automatic Block System,-

(a) The line shall be provided with continuous track circuiting or axle counters,

(b) The direction of the traffic shall be established only after Line Clear has been obtained from the block station in advance,

(c) A train shall be started from one block station to another only after the direction of traffic has been established,

(d) It shall not be possible to obtain Line Clear unless the line is clear,at the block station from which Line Clear is obtained, not only upto the first stop signal but also for an adequate distance beyond it,

(e) The line between two adjacent block stations may,where required,divided into or more automatic block signalling sections by provision of stop signals,

(f) After the direction of traffic has been established, movement of trains into,through and out of each automatic block signalling section shall be controlled by the concerned Automatic Stop signal and the said Automatic Stop signal shall not assume 'off' position unless the line is clear upto the next Automatic Stop signal: provided further that where the next stop signal is a Manual Stop signal,the line is clear for an adequate distance beyond it,and

(g) All Stop signals against the direction of traffic shall be at 'on'.

(2) Unless otherwise directed by approved special instructions, the adequate distance shall not be less than 180 metres.

ESSENTIALS OF THE AUTOMATIC BLOCK SYSTEM ON DOUBLE LINE-

(1) Where trains on a double line are worked on the Automatic block system,-

(a) The line shall be provided with continuous track circuiting or axle counters,

(b) The line between two adjacent block stations may, when required, be divided into a series of automatic block signalling sections each of which is the portion of the running line between two consecutive stop signal, and

(c) The track circuits or axle counters shall so control the stop signal governing the entry into an automatic block signalling section that-

(i) The signal shall not assume on 'off' aspect unless the line is clear not only upto the next stop signal in advance but also for an adequate distance beyond it,and

(ii) The signal is automatically placed to'on' as soon as it is passed by the train.

(2) Unless otherwise directed by approved special instructions adequate distance referred to in sub-clause(i) of clause (c) of sub-rule (1) shall not be less than 120 metres.

ESSENTIALS OF THE ONE TRAIN ONLY SYSTEM-

Where trains are worked on the train only system,only one train shall be on the section on which this system is in force,at one and the same time.

Trains may be worked on the one train only system,only on short terminal branches on the single line.

Procedure in case of accident or disablement on the one train only system.-

(1) (a) If the train becomes disabled and requires assistance or if an accident occurs which renders it impossible for the train to proceed, the train shall be protected in accordance with the provisions of Rule 6.03 in the direction from which assitance, if necessary, is being obtaind.

(b) The Guard of the train shall convey advice of the not able to proceed, to the Station Master of the station from which assitance can best be obtained, and if it is necessary for such Guard to proceed to such station,he shall instruct the Driver in writing to keep the train stationary until his return,and obtain his written acknowledgement.

(2) (a) Such SM,if he is not the SM of the base station,shall communicate this information to the SM of the base station. On receipt of such information, the SM of the base station may allow another engine to enter the line.

(b) The engine so sent shall either be accompanied by the guard of the disabled train who shall explain to the Driver where and under what circumstances the disabled train is situated.

(3) The Guard of the disabled train shall be responsible for the safe and proper working of the line until the disabled train has been moved and any other engine sent to the assitance of the disabled train has been returned to the base station. If there is no guard of disabled train, the fireman or the assistant driver shall performed the duties of the guard.

THANK YOU !

A.K. RAM
INSTRUCTOR, TRANS.
MDZRTI, BHULI