क्षेत्रीय रेल प्रशिक्षण संस्थान, भूली

ZONAL RAILWAY TRAINING INSTITUTE, BHULI

SHUNTING

Dhananjay Kumar Singh
INSTRUCTOR
ZRTI/Bhuli

SHUNTING

Shunting means the movement of a vehicle or vehicles with or without an engine on of any engine on any other self-propelled vehicle for the purpose of attaching, detaching with the train transfer on for any other purpose.

SHUNTING

TYPES OF SHUNTING-

1. Hand shunting
2. Flat Shunting
3. Loose shunting/ Hump shunting
4. Fly shunting

SHUNTING

1) **Hand shunting:** **Movement of vehicles from one place to another by employing manual labour is called hand shunting.**
2) **Flat Shunting:** **When vehicles are shunted by continuous forward and backward movements the locomotive remaining attached to the vehicles, it is known as flat shunting.**

SHUNTING

3) **Loose shunting:** means pushing of vehicles by an engine and allowing them to run forward with the engine un-attached. When this type of shunting performed in hump yard then it is called Hump Shunting.
4) **Fly shunting:** It is a shunt movement in which two or more vehicles are given a push by an engine and or separated the points by the smart reversal of points within the vehicles in order to send them on to different lines.

SHUNTING

GENERAL RULES OF SHUNTING:

1) Shunting should be done as per SWR.
2) Outer, Home and LSS should not be used for shunting.
3) Starter(if not interlocked with Advance Starter), Shunt Signal, Calling on and hand signal is used for shunting.
4) Loco pilot should be given shunting order-T/806.
5) White light should not be used for shunting at night.
6) If there is any level crossing is in shunting zone then it must be closed.
7) All points over which train will pass should be correctly set and facing point should be correctly locked.

SHUNTING

8) **Shunting must be performed under the supervision of properly authorized operating staff. It is performed only by the engine driver on the instruction of Station Master, Yard Master, Shunting Master, Guard (In case of road side station) or whoever may be in charge of shunting operation.**
9) **Maximum speed of shunting should not exceed 15 kmph.**
10) **Maximum speed of shunting of wagons loaded with Dangerous/ Explosive/ Inflammable goods should not exceed 8 kmph.**
11) **Impact speed of 5 NBOX wagon should not exceed 2.5 kmph.**
12) **Impact speed of 1 BOX wagon should not exceed 5 kmph.**

SHUNTING

13) **While attaching engines to the passenger train, the engine should be stopped at 20 meter away from the train and there after coupled carefully. It is the responsibility of SM and Guard to inform the passengers about the shunting.**

14) **Loose shunting of or against empty or loaded oil tank wagons, trucks loaded with heavy machinery, cranes, loaded explosive vans, livestock wagons, wagons labelled 'not to be loose shunted', coaching vehicles etc., is prohibited.**

15) **Coaching vehicles with passenger speed is restricted to 5-8kmph.**



- **Dhananjay Kumar Singh**
- **INSTRUCTOR**
- **ZRTI/Bhuli**