```
/*
  Computer Networks Laboratory (Lab) 15CSL77
  10. Write a program for congestion control using Leaky bucket algorithm.
*/

/* Network layer

   Varialbe traffic rate

   Match rate of output link/line

   Remove burstiness or jitter
*/

/* MTU (Maximum Transmission Unit) for Ethernet is 1500 bytes.
*/

/* Multiple approaches -

   Assume packet size is fixed
   Fixed packet size, variable number or packets,
     hence bucket capacity expressed in number of packets
   or
   Variable packet size, hence bucket capacity in terms of size of packets
*/

/* Compare to Dam, compare water to packets
     Water from catchment area - Inflow of packets into bucket
     Assume if overflow water is not sent downstream
       Then use / open spillway, main Gate - for overflow
                drop packets
     And constant outgoing flow rate - Bottom outlet
                Bucket, output, leak rate
*/

/* The leaky bucket consists of a finite queue

   When a packet arrives,
     if there is room on the queue
         Appended to the queue
     else
         Discard the packet as no space in bucket

   Assume leak rate is one packe every second, then
   At every clock tick one packet is transmitted
       Unless the queue is empty, called
*/

/*
   Router A to B
   A has queue so link to B does not get congested
   A is restricting its output

   A sends, fails, retries, instead match the capacity of A to B link

   A limits to match B
*/

/* Queue, enqueue, dequeue, isFull
   Circular queue
*/

/* Read parameters of the bucket:

   1. Read Bucket(Queue) Size, bucketSize or queueSize
      Size in terms of packets it can hold

   2. Read output rate, bucketRate
      In terms of packets Sent/output(dequeued) from bucket(queue)
```

```
   Read number of times to simulate, time

   for t  ← 0 to time

     Simulate flow into bucket, incoming traffic

     Read number of incoming packets, numberOfIncomingPackets

     Read content of incoming packets, contentOfIncomingPacket[]

     Now add to bucket

     for packet p in numberOfIncomingPackets

        if bucket(queue) not full
          enqueue( contentOfIncomingPacket[p] )

        else
          packet p discarded

     Adding to bucket complete, now simulate flow out of bucket

     for  t  ← 0 to bucketRate                      Leaky bucket
       outgoingPacket = dequeue( contentOfIncomingPacket )
       print outgoingPacket transmitted
*/

/* Queue
   Queue size/capacity, front, rear, present/current size/capacity
*/

#include <stdio.h>    // Bucket == Queue
#include <stdlib.h>   // For random function
#include <time.h>     // For time function

int main()            // Assume packets have fixed size, and
 {                    //   Bucket size == number packets bucket can hold
   int bucketSize;             // Maximum number of packets the bucket can hold
   int totalPacketsInBucket=0; // Keeps count of total number of packets in bucket
   int bucket[100];   // Array for bucket/queue, assume it would be big enough
   int front = 0;           // Front of bucket/queue
   int rear = -1;           // Rear of bucket/queue
   int leakRate;            // Packets let out of bucket per second
   int timeInstances;       // Unit time instances the network traffic is simulated
   // Variable name changed from time to timeInstance,
   //   because function name is also time
   int numberOfInComingPacketsAtTimeT;
   int i;
   int j;
   int k;

   srand ( time(NULL) ); // Initialize seed for random number generation

   printf("\n Assume maximum packets the bucket can hold is bucket size.");
   bucketSize = ( rand() % 5 ) + 1 ;  // Limiting bucket size from 1 to 5
   printf("\n Randomly selected bucket size = %d \n", bucketSize);

   printf("\n Assume packets the bucket leaks out every time unit is leak rate");
   leakRate  = ( rand() % 5 ) + 1 ;  // Limiting leak rate from 1 to 5
   printf("\n Randomly selected leak rate = %d \n", leakRate);

   timeInstances = ( rand() % 5 ) + 1 ;  // Limiting time instances from 1 to 5
   printf("\n Randomly selected time instances to simulate = %d \n",
                                                    timeInstances);

   printf("\n Leaky bucket: ");
   for( i=0; i<timeInstances; i++ )
```

```
    {
      printf("\n\n Time t = %d\n ", i); // limiting numberOfInComingPacketsAtTimeT
      numberOfInComingPacketsAtTimeT = rand() % 10; //  from 0 to 9

      printf("\n     Number of in coming packets at time %d = %d Packets \n", i,
                                    numberOfInComingPacketsAtTimeT);

      // If OpenMP (Open Multi-Processing) omp.h is used, and threading is enabled
      //     then, both enqueuing and dequeuing can be done simultaneously
      //     which resembles real life inflow and outflow of packets from bucket

      for( j=0; j<numberOfInComingPacketsAtTimeT; j++ )        // Add to bucket
       {
        if( totalPacketsInBucket < bucketSize ) // If space in bucket, then
         { // Read the content and enqueue in bucket, content is to differentiate
           bucket[++rear] = rand() % 100; //  packets, add packet to rear of queue
           totalPacketsInBucket++;        // Increment number of packets in bucket
           printf("\n       Randomly assigned content of incoming packets = %d\n",
                                                              bucket[rear]);
         }
        else
         { // totalPacketsInBucket == bucketSize, cannot add packet into bucket
           printf("\n       Bucket Overflow, drop the packet\n");
         }
       }

      printf("\n\n     Outgoing packets at time t = %d are \n", i);
      for( j=0; j<leakRate; j++ ) // Remove leakRate number of packets from bucket
       {
        if( totalPacketsInBucket == 0 )
         {
           printf("\n       Bucket empty, underflow, no packets to leak out\n");
         }
        else
         { // Remove from front of bucket/queue; Increment front
           printf("\n       Packet with content %d leaked out\n",bucket[front++]);
           totalPacketsInBucket--;    // and decrement number of packets in bucket
         }
       }
    }

   return 0;
 }

// improve implementation with Circular Queue
/* circular queue
   front = -1
   rear = -1

   full if ( front == 0 && rear == size-1 ) or ( rear == (front-1)%(size-1) )

   empty if ( front == -1 ) or ( rear+1 % size == front )

   enqueue
     if front == -1 , front = 0
     queue[ rear+1 % size ] = value

   dequeue
     queue[front]
     front = front+1 % size

   display queue
*/

/* Textbook:
   Behrouz Forouzon - Data Communications and Networking, McGraw Hill Edition
   Andrew S. Tanenbaum - Computer Networks
*/
```

```
/* Output:

Assume maximum packets the bucket can hold is bucket size.
Randomly selected bucket size = 4

Assume packets the bucket leaks out every time unit is leak rate
Randomly selected leak rate = 4

Randomly selected time instances to simulate = 4
Leaky bucket:

Time t = 0

    Number of in coming packets at time 0 = 0 Packets

    Outgoing packets at time t = 0 are

      Bucket empty, underflow, no packets to leak out

      Bucket empty, underflow, no packets to leak out

      Bucket empty, underflow, no packets to leak out

      Bucket empty, underflow, no packets to leak out

Time t = 1

    Number of in coming packets at time 1 = 2 Packets

      Randomly assigned content of incoming packets = 71

      Randomly assigned content of incoming packets = 40


    Outgoing packets at time t = 1 are

      Packet with content 71 leaked out

      Packet with content 40 leaked out

      Bucket empty, underflow, no packets to leak out

      Bucket empty, underflow, no packets to leak out

Time t = 2

    Number of in coming packets at time 2 = 9 Packets

      Randomly assigned content of incoming packets = 51

      Randomly assigned content of incoming packets = 73

      Randomly assigned content of incoming packets = 65

      Randomly assigned content of incoming packets = 65

      Bucket Overflow, drop the packet

      Bucket Overflow, drop the packet

      Bucket Overflow, drop the packet

      Bucket Overflow, drop the packet

      Bucket Overflow, drop the packet

    Outgoing packets at time t = 2 are

      Packet with content 51 leaked out
```

```
      Packet with content 73 leaked out
      Packet with content 65 leaked out
      Packet with content 65 leaked out
Time t = 3
    Number of in coming packets at time 3 = 2 Packets
      Randomly assigned content of incoming packets = 35
      Randomly assigned content of incoming packets = 93

    Outgoing packets at time t = 3 are
      Packet with content 35 leaked out
      Packet with content 93 leaked out
      Bucket empty, underflow, no packets to leak out
      Bucket empty, underflow, no packets to leak out
*/
```