

```

<?php
/* 2. Demonstrating the various forms to concatenate multiple strings
Develop program(s) to demonstrate concatenation of strings:
    (i) Strings represented with literals
        (single quote or double quote)
    (ii) Strings as variables
    (iii) Multiple strings represented with literals
        (single quote or double quote) and variables
    (iv) Strings and string variables containing single
        quotes as part string contents
    (v) Strings containing HTML segments having elements
        with attributes

    2_str_concat.php
*/
// Strings, content enclosed (start and end with same type of)
//     either in single ' or double " quotes
//         'content'         "content"

// single quote strings, as good as string constant literals
//     as is, no interpretation, no substitution of variable values

// double quote strings, variables and escape sequences are expanded

// string concatenation operator, dot operator      .

echo "<br />";
//(i) Strings represented with literals (single quote or double quote)

echo 'Ashok' . "Kumar"; // there is a . inbetween 'Ashok' and "Kumar"

echo "<br />";
// (ii) Strings as variables
$name = 'Ashok';           // variable name begins with a $
$lname = "Kumar";         // and type decided on context
echo $name . $lname;      // there is a . inbetween $name and $lname

echo "<br />";
// (iii) Multiple strings represented with literals
//         (single quote or double quote) and variables
$age = 25;

echo "Ashok Kumar is " . $age . ' years old'; // . used to concatenate
// concat string and integer, same operator, different operand type
// polymorphism, in this context operator overloading

echo "<br />";
// (iv) Strings and string variables containing single
//     quotes as part string contents
//                                     // either
echo $name . "'s age is " . $age;    // enclose in double quotes ""
// to avoid ambiguity , OR
echo $name . "'s age is ' . $age;    // escape ' with backslash \
// observe escape identification, change in color

echo "<br />";
//(v) Strings containing HTML segments having elements with attributes

echo '<a href="https://www.google.com"> Google </a>'; // a, link element
// OR
echo '<a href="https://www.google.com"> Google </a>'; // like in (iv)
// <element attribute = "value" />, since "" encloses value,
// enclose entire element in single quote ' , or escape using \
// '<element attribute = "value" />'

?>

```

```
<!--  
For more on , please check ,  
  Strings  
    https://www.php.net/manual/en/language.types.string.php  
  String Operators  
    https://www.php.net/manual/en/language.operators.string.php  
  String Functions  
    https://www.php.net/manual/en/ref.strings.php  
<a>: The Anchor element  
    https://developer.mozilla.org/en-US/docs/Web/HTML/Reference/Elements/a  
-->
```