

Troubleshooting Azure Active Directory Sync

Last updated by | Erik Ralston | Aug 4, 2022 at 7:04 AM PDT

This article is a guide to trying to gather information on why AAD sync may not be returning desired values. It is intended to isolate the process of gathering data from AAD by investigating it via MS Graph directly rather than relying purely on the integration with Soundbite.

Microsoft Graph Explorer

[Microsoft Graph Explorer \(https://developer.microsoft.com/en-us/graph/graph-explorer\)](https://developer.microsoft.com/en-us/graph/graph-explorer)  is a standalone tool offered by Microsoft to understand how integration via API can extract data from your M365 tenant. It enables developers to experiment with their own data and it can be used to understand what Soundbite extracts from your system.

These instructions will guide you through how to make an example response from MS Graph Explorer to share with [Soundbite Support \(Support@Soundbite.Freshdesk.Com\)](mailto:Support@Soundbite.Freshdesk.Com).

Logging In

In order to use [Microsoft Graph Explorer](https://developer.microsoft.com/en-us/graph/graph-explorer) , you must have some AAD admin capabilities turned on. For some organizations, these are available on an individual basis, but most users will have to be assigned AAD admins in order to follow these instructions.

First, head over to: <https://developer.microsoft.com/en-us/graph/graph-explorer> 

You will need to **Sign In** using the button on the top-left of the interface (underlined green below):

← → ↻ ⬆️ <https://developer.microsoft.com/en-us/graph/graph-explorer>

 Microsoft Graph Solutions ▾ Graph Explorer Get Started ▾ Docs ▾ Changelog

Graph Explorer

Authentication

i You are currently using a sample account. Sign in to access your own data. ...

 Sign in to Graph Explorer

 Sample queries  Resources  History

 Search sample queries

i See more queries in the [Microsoft Graph API Reference docs](#).

▾ Getting Started (8)

 GET my profile

 GET my profile (beta)

GET ▾ v1.0 ▾

▶ Request body  Request headers  Modify permissions

i When you use Microsoft Graph APIs, you agree to the [Microsoft APIs](#)

◀ Response preview  Response headers  Code snippet

You will see an interaction to grant access and you should accept it:

Let this app access your info? - Google Chrome

https://account.live.com/Consent/Update?mkt=EN-US&uiflavor=web...

 Microsoft

erik.ralston@gmail.com

 Let this app access your info?

 

Graph Explorer needs your permission to:

-  **Read your profile**
Graph Explorer will be able to read your profile.
-  **Maintain access to data you have given Graph Explorer access to**
Allows Graph Explorer to see and update the data you gave it access to, even when you are not currently using the app. This does not give Graph Explorer any additional permissions.

Accepting these permissions means that you allow this app to use your data as specified in their [terms of service](#) and [privacy statement](#). You can change these permissions at <https://microsoft.com/consent>. [Show details](#)

https://account.live.com/Consent/Update?mkt=EN-US&uiflavor=web&id=293577...

When you are successfully signed in, you will see your user information on the top-left corner where the sign-in button used to be:

The screenshot shows the Microsoft Graph Explorer web application. At the top, the browser address bar displays the URL `https://developer.microsoft.com/en-us/graph/graph-explorer`. The Microsoft logo and navigation links (Microsoft Graph, Solutions, Graph Explorer, Get Started, Docs, More) are visible in the header. The main interface has a dark theme. On the left sidebar, the title "Graph Explorer" is shown. Below it is a user profile for Erik Ralston with the email `erik@soundbite...`. Further down is a "Sample queries" section with a search bar labeled "Search sample queries" and a link to "See more queries in the Microsoft Graph API Reference docs." The main content area on the right has a top bar with a "GET" method selector, a "v1.0" version selector, a URL input field containing `https://graph.microsoft.com/v1...`, a "Run query" button, and an information icon. Below this, there are four tabs: "Request body" (selected), "Request headers", "Modify permissions (Preview)", and "Access token". The "Request body" tab is currently active, showing a large empty text area for the query.

Making a Query

To test your ability to query, you can run the default query:

```
https://graph.microsoft.com/v1.0/me
```

This should return values for you as a current user matching your profile:

← → ↺ 🏠 <https://developer.microsoft.com/en-us/graph/graph-explorer>

 Microsoft Graph Solutions ▾ Graph Explorer Get Started ▾ Docs ▾ Changelog More ▾ All Microsoft ▾

Graph Explorer

 Erik Ralston
erik@soundbite.ai

 Sample queries ...

 Search sample queries

 See more queries in the [Microsoft Graph API Reference docs](#).

▾ Getting Started (8)

-  GET my profile
-  GET my profile (beta)
-  GET my photo
-  GET my mail
-  GET all the items in my drive
-  GET items trending around...
-  GET my manager

GET ▾ v1.0 ▾ <https://graph.microsoft.com/v1.0/me> ⓘ Run query 

➤ Request body  Request headers  Modify permissions (Preview)  Access token

ⓘ When you use Microsoft Graph APIs, you agree to the [Microsoft APIs Terms of Use](#). View the [Microsoft Privacy Statement](#). X

✓ OK - 200 - 183ms X

↶ Response preview  Response headers  Code snippets  Toolkit component • ...

```
{
  "@odata.context": "https://graph.microsoft.com/v1.0/$metadata#users/$entity",
  "businessPhones": [
    "0-123-456-7890"
  ],
  "displayName": "Erik Ralston",
  "givenName": "Erik",
  "jobTitle": "Co-Founder & Chief Technology Officer",
  "mail": "erik@soundbite.ai",
  "mobilePhone": "509-312-9058",
  "officeLocation": null,
  "preferredLanguage": "en-US",
  "surname": "Ralston",
  "userPrincipalName": "erik@soundbite.ai",
  "id": "b2be56fb-0b86-44c6-b0ab-8a00e90c61be"
}
```


These are the default attributes for your user and this is very close to what Soundbite uses to query for data.

Querying Like Soundbite

The following is a sequence of queries reflecting the information Soundbite is capable of finding in your AAD instance. Running each of them should inform us as to whether or not your unique directory is giving Soundbite the required information for each user.

For each query, copy it from this document, paste it into the query textbox (highlighted), set the GET/POST keyword in the selector, and look for responses in the "Response Preview" window (highlighted). Missing fields or mismatches with the given format should be screenshotted (most easily done in Windows with the Windows+Shift+S interaction), which will then allow you to please e-mail any differences with commentary to [Soundbite Support \(Support@Soundbite.Freshdesk.Com\)](mailto:Support@Soundbite.Freshdesk.Com).

Querying Groups

To query for the initial list of groups:

```
GET https://graph.microsoft.com/v1.0/groups?
$select=id,deletedDateTime,displayName&$filter=groupTypes/any(groupType: groupType eq 'Unified')
```

Which yields a list of groups by ID and name:

```
{
  "@odata.context": "https://graph.microsoft.com/v1.0/$metadata#groups(id,deletedDateTime,displayName)",
  "value": [
    {
      "id": "5342c6a4-e19e-4bd6-b4cd-e02eeb9a13eb", // Group ID
      "deletedDateTime": null,
      "displayName": "Soundbite"
    },
    // Further items redacted
  ]
}
```

Querying All Groups

The all groups query is the broadest group-based query, finding the list of all groups by name in AAD. These will then be brought into Soundbite:

```
GET https://graph.microsoft.com/v1.0/groups/
```

Querying Users

```
GET https://graph.microsoft.com/v1.0/users?$select=id,mail,deletedDateTime&$filter=userType eq 'Member' or
userType eq 'Guest'
```

```
{
  "@odata.context": "https://graph.microsoft.com/v1.0/$metadata#users(id,mail,deletedDateTime)",
  "value": [
    {
      "id": "b2be56fb-0b86-44c6-b0ab-8a00e90c61be", // User ID
      "mail": "erik@soundbite.ai",
      "deletedDateTime": null
    },
    // Additional items redacted
    ...
  ]
}
```