

COMMERCIAL LED AREA LIGHT

ARL 150–240W Area Light

Selectable color temperature and steady, even output define the ARL 150–240W Area Light. Built for pole or wall mounting over parking lots, loading areas, and site perimeters, its shoebox housing is engineered for continuous outdoor duty and simplifies stocking across a property. Field-selectable color temperature lets installers match the light to the site without carrying multiple SKUs — dependable, code-ready area lighting for commercial and municipal sites.

FINISH OPTIONS

Bronze DV2



PRODUCT DETAILS

FAMILY

ARL

PRODUCT TYPE

LED Area / Flood Light

MATERIAL

Die-cast aluminum

LENS / DIFFUSER

Full-cutoff · Type III optic

MOUNTING

Pole (slip-fitter) or wall arm

LOCATION RATING

Wet

CERTIFICATIONS

ETL Listed (Wet)

ELECTRICAL / PERFORMANCE

WATTAGE

150 / 200 / 240W selectable

LUMENS

Up to 21,000 lm

CCT

3000K / 4000K / 5000K selectable

CRI

80 CRI

INPUT VOLTAGE

120–277V (universal)

IP RATING

IP65

CONTROL

Integral photocell · 0–10V dimming

INSTALLATION

INSTALLATION

Slip-fitter / arm · pole or wall

WIRING

Hardwired

ORDERING

	FINISH	CODE	WATTAGE	LUMENS	WIDTH	HEIGHT	SKU	PART #
	● Bronze	DV2	150 / 200 / 240W selectable	Up to 21,000 lm	13.97"	2.51"	3490005	ARL-150T240W-3CCT-DV2-PC-T3-BZ
	● Bronze	DV3	150 / 200 / 240W selectable	Up to 21,000 lm	13.97"	2.51"	3490001	ARL-150T240W-3CCT-DV3-PC-T3-BZ

ORDER CODE

Order code: ARL-150T240W-3CCT-[DV2 / DV3]-PC-T3-BZ — Bronze. LED, 150 / 200 / 240W selectable (max 240W), Up to 21,000 lm, 3-CCT selectable, 80 CRI. 120–277V, 0–10V dimmable, integral photocell, Type III optic. Wet-rated, IP65, ETL Listed. DV2 & DV3 driver options.