

COMMERCIAL LED AREA LIGHT

ARL 200–300W Area Light

High-output light spreads across the site from the ARL 200–300W Area Light, the highest-wattage option in the ARL family. Its rugged shoebox housing mounts to a pole or wall and is engineered for continuous outdoor duty, while field-selectable color temperature simplifies spec and stocking across a large property. Built for wide parking fields, distribution yards, and large lot perimeters that need serious output — dependable, code-ready area lighting that pays back through lower maintenance.

FINISH OPTIONS

Bronze DV2



PRODUCT DETAILS

FAMILY

ARL

PRODUCT TYPE

LED Area / Flood Light

MATERIAL

Die-cast aluminum

LENS / DIFFUSER

Full-cutoff · Type III optic

MOUNTING

Pole (slip-fitter) or wall arm

LOCATION RATING

Wet

CERTIFICATIONS

ETL Listed (Wet)

ELECTRICAL / PERFORMANCE

WATTAGE

200 / 240 / 300W selectable

LUMENS

Up to 26,500 lm

CCT

3000K / 4000K / 5000K selectable

CRI

80 CRI

INPUT VOLTAGE

120–277V (universal)

IP RATING

IP65

CONTROL

Integral photocell · 0–10V dimming

INSTALLATION

INSTALLATION

Slip-fitter / arm · pole or wall

WIRING

Hardwired

ORDERING

	FINISH	CODE	WATTAGE	LUMENS	WIDTH	HEIGHT	SKU	PART #
	● Bronze	DV2	200 / 240 / 300W selectable	Up to 26,500 lm	13.97"	2.51"	3490003	ARL-200T300W-3CCT-DV2-PC-T3-BZ
	● Bronze	DV3	200 / 240 / 300W selectable	Up to 26,500 lm	13.97"	2.51"	3490004	ARL-200T300W-3CCT-DV3-PC-T3-BZ

ORDER CODE

Order code: ARL-200T300W-3CCT-[DV2 / DV3]-PC-T3-BZ — Bronze, LED, 200 / 240 / 300W selectable (max 300W), Up to 26,500 lm, 3-CCT selectable, 80 CRI. 120–277V, 0–10V dimmable, integral photocell, Type III optic. Wet-rated, IP65, ETL Listed. DV2 & DV3 driver options.