

COMMERCIAL FLOOD

FusionX Flood Light

Bright, wide-beam output from the FusionX Flood Light covers a yard, sign, facade, or building perimeter in even, consistent light. The compact 15W and 28W models are field-selectable across five color temperatures, so one SKU covers multiple spec requirements and cuts stocking complexity, while the higher-output 50W and 80W models add smooth 0–10V dimming to tie into building controls at a fixed 4000K. All install in minutes with standard hardware and run efficiently against higher-wattage legacy floods — a full ladder of output from a small entry up to a large facility perimeter.

FINISH OPTIONS ● Bronze BZ



PRODUCT	FusionX Flood Light
LOCATION	—
DATE	—
PART #	FSNX15-5CCT-BZ
NOTES	—



PRODUCT DETAILS

FAMILY
FusionX

PRODUCT TYPE
Single-Head LED Flood

MATERIAL
Die-cast aluminum · tempered-glass lens

LENS / DIFFUSER
Tempered glass

MOUNTING
Wall / eave · adjustable knuckle

LOCATION RATING
Wet

CERTIFICATIONS
ETL Listed (Wet)

ELECTRICAL / PERFORMANCE

INPUT VOLTAGE
120V

IP RATING
IP65

INSTALLATION

INSTALLATION
Surface-mount · wall or eave

WIRING
Hardwired (120V)

MODELS & ORDERING

	WATTAGE	LUMENS	CCT	SKU	PART #
	15W	1,320 lm	Selectable 5CCT	3770001	FSNX15-5CCT-BZ
	28W	2,500 lm	Selectable 5CCT	3770002	FSNX28-5CCT-BZ
	50W	4,400 lm	4000K	3770005	FSNX50-PC-4K-BZ

All dimensions are nominal and in inches unless noted. Specifications and finishes subject to change without notice. © 2026 Eran Group.