

LED WALL PACK

PowerwallX LED Wall Pack

Bright, even light covers a loading dock, perimeter wall, or building entrance with the PowerwallX LED Wall Pack. A rugged die-cast aluminum housing delivers dependable output while cutting energy against older HID wall packs, and it mounts easily to a standard junction box for years of low-maintenance exterior duty. The 50W and 80W models add a dusk-to-dawn photocell, and the 80W dims on 0–10V for curfew or occupancy control. Three power classes cover a doorway up to a full facility perimeter, in Bronze.

FINISH OPTIONS ● Bronze BZ



PRODUCT	PowerwallX LED Wall Pack
LOCATION	—
DATE	—
PART #	PRWX[28/50/80]-...-BZ
NOTES	—



28W



80W · PC

PRODUCT DETAILS

FAMILY
PowerwallX
PRODUCT TYPE
LED Architectural Wall Pack
MATERIAL
Die-cast aluminum
LENS / DIFFUSER
Polycarbonate
MOUNTING
Wall · J-box
LOCATION RATING
Wet
CERTIFICATIONS
ETL Listed (Wet)

ELECTRICAL / PERFORMANCE

WATTAGE
28 – 80W
CCT
4000K
CRI
80 CRI
INPUT VOLTAGE
120–277V
IP RATING
IP65
CONTROL
Dusk-to-dawn photocell (50/80W)

INSTALLATION

INSTALLATION
Surface · wall J-box
WIRING
Hardwired

WATTAGES & ORDERING

	WATTAGE	LUMENS	CCT	SKU	PART #
	28W	2,800 lm	4000K	3830003	PRWX28-H-4K-BZ
	50W	5,000 lm	4000K	3830005	PRWX50-H-PC-4K-BZ
	80W	—	4000K	3830006	PRWX80-H-PC-4K-BZ

ORDER CODE Order code / SKU: PRWX28-H-4K-BZ (3830003, 28W, 2,800 lm) · PRWX50-H-PC-4K-BZ (3830005, 50W, 5,000 lm, photocell) · PRWX80-H-PC-4K-BZ (3830006, 80W, photocell)
All dimensions are nominal and in inches unless noted. Specifications and finishes subject to change without notice. © 2026 Eran Group.