

SURFACE / FLUSH MOUNT

SFMDC Globe Surface Mount

Bright, even light spreads from the compact opal-glass globe of the SFMDC Surface Mount, built for closets, hallways, laundry rooms, and everyday utility spaces. Its low-profile globe mounts flush to almost any ceiling in minutes with no bulky housing, and a standard medium-base A19 socket keeps bulbs easy to source. The opal shade diffuses a warm, even glow for grooming or general tasks, in Brushed Nickel or Black.

FINISH OPTIONS ● Brushed Nickel BN ● Black BK



Brushed Nickel



Black

PRODUCT DETAILS

FAMILY
SFMDC
PRODUCT TYPE
Opal-Globe Flush / Surface Mount
MATERIAL
Opal glass globe · metal
MOUNTING
Ceiling · Flush (hardwired)
LOCATION RATING
Dry
CERTIFICATIONS
ETL Listed

LIGHT SOURCE

BASE / SOCKET
Medium (E26)
BULB TYPE
A19
NO. OF BULBS
1
BULB INCLUDED
Not included (sold separately)
MAX WATTAGE
Up to 60W / socket
INPUT VOLTAGE
120V

INSTALLATION

INSTALLATION
Hardwired · ceiling J-box (flush)
CANOPY / BACKPLATE
Integral · matches finish
CHAIN LENGTH
Flush (no chain)

FINISHES & ORDERING

	FINISH	DIAMETER	HEIGHT	SKU	PART #
	● Brushed Nickel	7.6"	5.25"	102-12500040-1	DC421-5-BN
	● Black	7.6"	5.25"	102-12500040-2	DC421-5-BK

ORDER CODE Order code / SKU: DC421-5-BN Brushed Nickel (102-12500040-1) · DC421-5-BK Black (102-12500040-2). 7.6" opal globe × 5.25" H, one medium E26 / A19 socket, bulb sold separately, dry-rated, ETL Listed. ⚠ Built as socketed (ceiling_chandelier) per the PIM spec block — not integrated LED. ⚠ Spec conflict: block cites '(1) 15W E26/A19' while the summary reads '500 lm / 6W max'; SKUs use a non-standard 102-... format — confirm.