

VAPOR-TIGHT LIGHT

Vapor Vapor-Tight LED Linear

High-output, sealed light from the Vapor Vapor-Tight LED Linear covers warehouse bays, garages, and wash-down areas in even, consistent coverage. A gasketed housing shrugs off dust, moisture, and washdown conditions, while field-selectable wattage and color temperature let one SKU adapt to a facility's spec instead of stocking multiple options. Smooth 0–10V dimming and universal 120–277V input tie it into building controls — 2, 4, and 8-foot runs for tight utility rooms up to full industrial corridors.

FINISH OPTIONS

Gray GR



PRODUCT	Vapor Vapor-Tight LED Linear
LOCATION	—
DATE	—
PART #	VPT[2/4/8]-...-GR
NOTES	—



PRODUCT DETAILS

FAMILY
Vapor

PRODUCT TYPE
Sealed Vapor-Tight LED Linear

MATERIAL
Sealed polycarbonate housing · gasketed

MOUNTING
Surface / suspended

LOCATION RATING
Wet (washdown)

CERTIFICATIONS
ETL Listed

LIGHT SOURCE (LED)

LIGHT SOURCE
Integrated LED

LUMENS
2,700 – 8,000 lm

CCT
Selectable 3CCT

CRI
80 CRI

DIMMABLE
0–10V

INPUT VOLTAGE
120–277V

INSTALLATION

INSTALLATION
Surface / chain / suspended

SIZES & ORDERING

	SIZE	WATTAGE	LUMENS	CCT	SKU	PART #
	2-ft	20/25/30W	2,700 lm	Sel. 3CCT	3900003	VPT2-20T30W-3CCT-DV2-GR
	4-ft	40/50/60W	5,300 lm	Sel. 3CCT	3900001	VPT4-40T60W-3CCT-DV2-GR
	8-ft	60/75/90W	8,000 lm	Sel. 3CCT	3900002	VPT8-60T90W-3CCT-DV2-GR

ORDER CODE Order code / SKU: VPT2 (3900003, 20–30W, 2,700 lm) · VPT4 (3900001, 40–60W, 5,300 lm) · VPT8 (3900002, 60–90W, 8,000 lm), Gray. Selectable wattage + 3CCT, 80 CRI, 0–10V dimmable, 120–277V, IP-rated wet/washdown, ETL Listed.