





# **VERTICAL HOLLOW SHAFT MOTOR**







**Product Line of Kirloskar Electric** 

AC & DC Motors | Generators | Transformers | Switchgear | Drives | DG Sets | Projects | Engineering









Vertical Hollow Shaft (VHS) induction motors from Kirloskar Electric are well known globally, since five decades. The demand for underground source of water (for irrigation, domestic and drinking purpose) is ever increasing. This demand is being met by the use of deep well vertical turbine pumps which are driven by vertical hollow shaft motors.

#### **APPLICATIONS**

VHS motors are specially designed to drive vertical turbine pumps and the motors are well suited for the application due to the ease of installation and maintenance, permanent shaft alignment, well protected construction, high thrust capability and compact & rugged design.



FRAME	2 POLE	4 POLE	6 POLE	
• SVH160	15	15	11	
• SVH180	37	30	18.5	
• SVH200	55	45	30	
• SVH250	-	100	55	
• SVH280	-	135	90	
• SVH315	-	250	160	

### **OPERATIONAL FEATURES**

The rotation in the WNR type (non-reversible) motor is only in one direction. The standard direction of rotation is anti-clockwise looking from the top of the motor. This is achieved by means of a non-reversible ratchet (NRR) which prevents the reverse rotation of the motor due to the back flow of water in to the well when the motor is switched off. The NRR also prevents reverse rotation due to the accidental phase reversal which would tend to unscrew the pump shaft. An added protection is incorporated in frames SVH250, SVH280 & SVH315 in the form of a "Pin arrangment" in the clutch to take care of the accidental up thrust of the pump shaft.



## **SPECIFICATIONS**

<ul> <li>Voltage (V)</li> </ul>	: 415V+/-10%, 3 Phase AC			
• Frequency (Hz)	: 50Hz +/- 5%			
• Combined V & F variation: +/-10%				
<ul> <li>Insulation</li> </ul>	: Class F			
• Duty	: S1-continuous			
• Ambient	: 0 to 50°C			
Temperature Rise	: Class B			
<ul> <li>Atmosphere</li> </ul>	: Safe area			
<ul> <li>Altitude</li> </ul>	: <1000m above mean sea level.			
• Enclosure	: IP23/1C01, (IP21 for frames SVH 160, SVH 180, SVH 200)			
Mounting	: IM 3239HS			
• Direction of Rotation	: ACW looking from top. With UVW phase sequence			

## KIRLOSKAR ELECTRIC CO. LTD.

Regd. Office: PB. No. 5555, Malleswaram West, Bangalore 560 055 | Tel: 080-23374865 | Fax: 080-23377706 Email: enq@hub.vrkec.com | www.kirloskar-electric.com

