



THREE PHASE AC

**MOTORS - CAGE, SPDP** 





AC & DC Motors | Generators | Transformers | Switchgear | Drives | DG Sets | Projects | Engineering







### **FEATURES**

- Foot / Flange mounting with single shaft extension
- Class 'F' insulation, Class 'B' Temperature Rise
- · Cast Iron body
- Cast Iron end covers
- Optimum fan design for better cooling and minimum energy consumption
- Rigidly sealed Terminal Box at RHS when viewed from Drive End
- EC grade aluminum die- cast rotors
- Suitable for flexible direct coupling or belt drives with high load GD2
- Suitable for DOL / STAR-DELTA Starting
- Bi-directional rotation

## **COMPLIES TO**

<ul> <li>Specifications</li> </ul>	:	IS: 325
General Requirements	:	BS: 4999
Rating & Performance	:	IEC: 34-1
Dimensions, foot mounted IS	:	1231
Dimensions, flange mounted	:	IS: 2223

#### **APPLICATIONS**

- Pumps
- Compressors
- Machine Tools
- Textiles
- Fans
- Crushers
- Material Handling
- Cranes

# When you order please furnish

- Application
- Mounting
- Input supply condition & % variation
- Load GD2
- · Method of power transmission



### WE CAN ALSO SUPPLY

- · Foot or flange mounting with double shaft extensions
- · Motors for high inertia load
- Supply voltages 220/380/400/440/660 V
- Supply frequency: 50 / 60Hz
- Motors to suit for customized duty cycle
- Thermister and anti condensation heaters
- Multi speed motors
- Dual voltage motors
- IP 22 / 23 protection

#### **SPECIFICATIONS**

<ul> <li>Input Voltage (V)</li> </ul>	: 415V+/-10%, 3 Ph AC
<ul> <li>Frequency (Hz)</li> </ul>	: 50+/-5%
<ul> <li>Insulation</li> </ul>	: F
• Duty	: S1
<ul> <li>Protection</li> </ul>	: IP 21
• Enclosure	: IC 01
Ambient	: 0 to 50 <sup>0</sup> C
• Rating	: 15 - 135 kW
Frame size	: 180 - 280

# KIRLOSKAR ELECTRIC CO. LTD.

Regd. Office: PB. No. 5555, Malleswaram West, Bangalore 560 055 | Tel: 080-23374865 | Fax: 080-23377706 Email: enq@hub.vrkec.com | www.kirloskar-electric.com

