TÜRK STANDARDLARI ENSTİTÜSÜ
TÜRK STANDARDLARINA UYGUNLUK BELGESİ
TURKISH STANDARDS INSTITUTION
CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS

Markanın Tarifesi — Description of the Mark

TSE — TSE — I-II-III

BELGE KAPSAMI (006237-TSE-03/04nolu belge devamı) : GERSAN ELEKTRİK TİC.VE SAN.A.Ş.
İLGİLİ TÜRK STANDARDI/RELATED TURKISH STANDARD: TS EN 61439-6 / 18.03.2015

MODEL : GGD COMPACT 500 A, GGD COMPACT 630 A MODEL Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 50/55 (WITH SILICONE) PHASE: 3P+N+E+PE In: 500 A, 630 A Icw: 25 kA (1 SC)/53 kA AL BRAID SECTIONS: 500 mm^2 , E SECTIONS: 500 mm^2 , PE SECTIONS: 1200 mm^2
MODEL : GGD COMPACT 800 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 50/55 (WITH SILICONE) PHASE: 3P+N+E+PE In: 800 A Icw: 30 kA (1 SC)/60kA AL BRAID SECTIONS: 600 mm^2 , E SECTIONS: 600 mm^2 , PE SECTIONS: 1200 mm^2
MODEL : GGD COMPACT 1000 A MODEL Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 50/55 (WITH SILICONE) PHASE: 3P+N+E+PE In: 1000 A Icw: 40 kA (1 SC)/80 kA AL BRAID SECTIONS: 700 mm^2 , E SECTIONS 700 mm^2 , PE SECTIONS: 1200 mm^2
MODEL : GS-A COMPACT 500 A , GS-A COMPACT 630 A , GS-A COMPACT 800 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 500 A , 630 A , 800 A Icw: 50 kA (1 SC)/110 kAUimp: 8 kV AL BRAID SECTIONS: 330 mm^2 , E SECTIONS: 165 mm^2 , PE SECTIONS: 1304 mm^2
MODEL : GS-A COMPACT 1000 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 1000 A Icw: 50 kA (1 SC)/110 kA Uimp: 8 kV AL BRAID SECTIONS: 450 mm^2 , E SECTIONS 225 mm^2 , PE SECTIONS: 1450 mm^2
MODEL : GS-A COMPACT 1250 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 1250 A Icw: 65 kA (1 SC)/150 kA Uimp: 8 kV AL BRAID SECTIONS: 660 mm^2 , E SECTIONS: 330 mm^2 , PE SECTIONS: 2256 mm^2
MODEL : GS-A COMPACT 1600 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 1600 A Icw: 80 kA (1 SC)/175 kA Uimp: 8 kV AL BRAID SECTIONS: 1040 mm^2 , E SECTIONS: 520 mm^2 , PE SECTIONS: 2944 mm^2
MODEL : GS-A COMPACT 2000 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 2000 A Icw: 80 kA (1 SC)/175 kA Uimp: 8 kV AL BRAID SECTIONS: 1080 mm^2 , E SECTIONS: 540 mm^2 , PE SECTIONS: 2600 mm^2
MODEL : GS-A COMPACT 2500 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 2500 A Icw: 100 kA (1 SC)/220 kA Uimp: 8 kV AL BRAID SECTIONS: 1320 mm^2 , E SECTIONS: 660 mm^2 , PE SECTIONS: 4580 mm^2
MODEL : GS-A COMPACT 3200 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 3200 A Icw: 120 kA (1 SC)/264 kA Uimp: 8 kV AL BRAID SECTIONS: 2080 mm^2 , E SECTIONS: 1040 mm^2 , PE SECTIONS: 4688 mm^2
MODEL : GS-A COMPACT 4000 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 4000 A Icw: 150 kA (1 SC)/330 kA Uimp: 8 kV AL BRAID SECTIONS: 2160 mm^2 , E SECTIONS: 1080 mm^2 , PE SECTIONS: 5208 mm^2
MODEL : GS-A COMPACT 5000 A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 5000 A Icw: 150 kA (1 SC)/330 kA Uimp: 8 kV AL BRAID SECTIONS: 3240 mm^2 , E SECTIONS: 1620 mm^2 , PE SECTIONS: 7810 mm^2
MODEL : GS-C COMPACT 500 A , GS-C COMPACT 630 A , GS-C COMPACT 800 A , GS-C COMPACT 1000A Ue: 1000 V Ui: 1000 V FREQUENCY: 50 HZ IP: 55 / X8 (WITH RESIN) PHASE: 3P+N+E+PE In: 500 A , 630 A , 800 A , 1000 A Icw: 50 kA (1 SC)/110 kA Uimp: 8 kV CU BRAID SECTIONS: 330 mm^2 , E SECTIONS: 165 mm^2 , PE

e-imzalıdır-signed

29.09.2022

On Behalf Of The Head Of Certification Center
SOYDAN CERAN

ELECTROTECHNICAL SECTOR MANAGER