

SINE-O-TRON 3000®

Reference Manual

Einros Computer Inc.

Einros Computer Inc.

If you are having trouble starting your SINE-O-TRON 3000[®], please ensure the CD-ROM drive is correctly installed in your host computer, eject the SINE-O-TRON 3000[®] CD-ROM and restart your computer. If you continue to have problems, please contact the manufacturer of your host computer for further support.

If you are having trouble with the audio of your SINE-O-TRON 3000[®], please ensure you have correctly set up the audio components of the virtual computer as described in Section 6.2.

If the display of your SINE-O-TRON 3000[®] is flashing it is likely that an error has occurred. Please refer to Table 12.1 and Table 12.2 to troubleshoot the issue.

Table 12.1

<i>Frequency</i>	<i>Phase</i>	<i>Code</i>
0.02 Hz	90°	1
0.1 Hz	270°	2
0.01 Hz	180°	3
0.2 Hz	270°	4
1 Hz	0°	5
0.05 Hz	120°	6
2 Hz	45°	7
0.005 Hz	0°	8
0.5 Hz	320°	9

Table 12.2

<i>Code</i>	<i>Solution</i>
00001	Type "exit", then shutdown the SINE-O-TRON 3000 [®] and restart the host computer.
00004	Type "psmem"
00005	Type "reboot"
00014	Type "runtests"
00023	Type "sighup"
00409	Type "cancel"
00837	Type "opendesktop"
01057	Type "killx"
01289	Type "cancelall"
02456	Type "startx"
04108	Type "reinstall"
06208	Type "clear"
09870	Type "killall"
10360	Type "reroll"
13802	Type "del"
14289	Type "exit", then shutdown the SINE-O-TRON 3000 [®] and restart the host computer.
19850	Type "reboot"