HYDROSTATIC INTERNAL PRESSURE TESTER

DESCRIPTION

The internal pressure creep test is a test procedure for determining the strength of thermoplastic pipes. The specimens are subjected to a constant hydrostatic internal pressure at a constant ambient temperature either for a specified period or until they fail. The test duration is subject to the tension generated by the internal pressureand the temperature. It combines the tester's exceptional reliability with simple operation without making any compromises with respect to precision and flexibility.

Accessories

Simple and safe operation

- Convenient operation and clear visualisation via integrated touch display

Reliable test results

- Microprocessor-controlled, with automatic failure and leakage detection
- Precision pressure transducer incl. pressure gauge for test pres sures up to 60 bar and system pressure up to 130 bar
- Water disruption detection system

Reliable test results

- High-quality unit components guarantee high reliability, a long service life and low maintenance costs
- Extendable up to 20 station on request

State of the art technology

- Interface to BTLogger® Windows based datalogger software for reporting and visiualisation.

HYDROSTATIC INTERNAL PRESSURE TESTER

Standards
ISO 1167
ASTM D 1598
ASTM D 1599

Basic cabinets

		T011630V1P	T011630V2P	T011630V3P	T011630V4P	T011630V5P	T011630V6P
Pressure range up to	bar	100	100	100	100	100	100
Integrated high-pressure pump		●	●	●	●	●	●
Pump capacity	l/min	10	14	14	14	14	14
Second system pressure		-	-	-	-	-	-
Stainless steel pressure reservoir		●	●	●	●	●	●
Max. number of stations		4	8	12	16	20	28
Integrated control unit via 5.7” touch-screen		●					
Integrated control unit via 12.1” touch-screen		○	●	●	●	●	●
Compatibility with BTLogger®		From version 3.x					
Simple Burst Test		Avaliable in 1 test line only					
CE conformity		●					
Width	mm	900					
Depth	mm	900					
Height	mm	1700					
Weight (with 12 stations)	kg	250					
Voltage data		**230/400 V, 50/60 Hz (other voltages on request)**					

● included ○ available / optional □ eligible - not available

POLİNAR PLASTİK MAKİNE ve KALIP SANAYİ
TİCARET LİMİTED ŞİRKETİ
İkitelli O.S.B Eskoop San. Sit. D Blok
No: 34 Başakşehir / İSTANBUL - TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.polinar.com.tr

PTE (POLİNAR TEST EQUIPMENT)
İkitelli O.S.B. Eskoop San. Sit.
D Blok No.34 Başakşehir
İstanbul / TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.pte.com.tr

POLINAR GmbH
THE ICON VIENNA, Tower 24
Wiedner Gürtel 13 1100
Vienna AUSTRIA

Phone : +43 (0) 1 253535 4044
Fax : +43 (0) 1 253535 4044
Mobile : +43 676 5983869
E-Mail : office@polinar.at

www.polinar.at