TEST OVEN for PIPE TESTING

DESCRIPTION

The internal pressure creep test is a test procedure for determining the strength of thermoplastic pipes. The samples are subjected to a constant hydrostatic internal pressure at a constant ambient temperature either for a specified period or until they fail. The test duration is subject to the tension generated by the internal pressure and the temperature. The PTE test ovens are specially designed for testing thermoplastic pipes and fittings. The high reliability, long service life of the materials used and the constant temperatures in the test oven with respect to both volume and time provide particularly reliable test conditions. The efficient use of energy with low servicing and maintenance costs guarantees efficient longterm operation. There are a wide range of connection options, enabling the ovens to be flexibly adapted to various operating conditions.

Accessories

Easy and safe operation

- Sliding rack system enables the individual connections to be fitted more easily outside the oven
- Doors locked with safety switches and retrieval of the test pressure before doors are released

Reliable test results

- Constant test temperatures thanks to highly-efficient water circulation and precise temperature control in the inner chamber

Lasting efficiency

- High-quality stainless steel test oven (1.4571)
- High-quality oven insulation and insulated doors for minimum energy loss
- High-quality unit components guarantee high reliability, a long service life and low maintenance costs

State of the art technology

- Extremely accurate temperature control in the entire inner chamber thanks to exceptionally high performance circulating air system
- Interface to Polinar®

TEST OVEN for PIPE TESTING

Standards
ISO 1167
ASTM D 1598
ASTM D 1599

Versions

		T1101V1D TEST OVEN	T1101V2D ETUV OVEN	T1101V3D MUFFLE FUTNACE
Temperature range	°C	5/150	5/250	1100
Regulating accuracy	°C	±0.2	±0.2	±1
Temperature control		•	•	•
Inner chamber material		AISI 304	AISI 304	AISI 304
Power requirement of tubular furnace	kW	1,5	3,5	3,0
CE conformity		•	•	•
Permissible ambient temperature	°C	+5 to +40	+5 to +40	+5 to +40
Permissible relative humidity		Max.70	Max.70	Max.70
Width (internal/external)	mm	800/900	550/850	170/370
Depth (internal/external)	mm	600/700	500/700	220/520
Height (internal/external)	mm	750/850	900/1100	170/550
Voltage data		**220/380V. 50/60 Hz**		

● included ○ available / optional □ eligible - not available

POLİNAR PLASTİK MAKİNE ve KALIP SANAYİ
TİCARET LİMİTED ŞİRKETİ
İkitelli O.S.B Eskoop San. Sit. D Blok
No: 34 Başakşehir / İSTANBUL - TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.polinar.com.tr

PTE (POLİNAR TEST EQUIPMENT)
İkitelli O.S.B. Eskoop San. Sit.
D Blok No.34 Başakşehir
İstanbul / TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.pte.com.tr

POLINAR GmbH
THE ICON VIENNA, Tower 24
Wiedner Gürtel 13 1100
Vienna AUSTRIA

Phone : +43 (0) 1 253535 4044
Fax : +43 (0) 1 253535 4044
Mobile : +43 676 5983869
E-Mail : office@polinar.at

www.polinar.at