CNC MILLING MACHINE for TEST BARS

DESCRIPTION

The test bar milling machine enables bar-shaped plastic samples to be produced for tension, pressure, bending and flexural impact tests in accordance with a wide range of standards. The CNC milling machine is a table-top unit with electrically locking protective doors. Pre-configured machining programs for all common bar shapes and visualisation via touch screen display makes it very easy to operate the milling machine. Up to five test bars can be produced in one milling process. The all-round enclosure ensures safety at the workstation during the milling process. A swarf extraction system ensure the workstation remains clean.

Accessories

Simple and safe operation

- Pre-configured machining programs protective doors with safety lock
- Clean workstation thanks to machine enclosure delivered with workbench

Reliable test results

- Test bars milled in accordance with standards
- CNC-controlled positioning of the axes
- Machined areas cooled with compressed air

Lasting efficiency

- High-quality unit components guarantee high reliability, a long service life and low maintenance costs

CNC MILLING MACHINE for TEST BARS

Standards	
ISO 179/180	ISO 16770
ISO 527	ASTM D 638
ISO 6259	ASTM D 1822

Versions

		T081V1P
Milling table with mechanical clamping device		●
- Clamping range for blanks small		Max. thickness 30 mm Max. length 220 mm
- Clamping range for blanks big		Max. thickness 90 mm Max. length 250 mm
- Number of test bars		Max. 2/5
Milling table with pneumatic clamping device		●
Rotational speed of spindle		Between 3000 and 18000 per minute
Hard metal milling cutter Ø 12-16 mm (subject to standard)		●
Diamond milling cutter		○
Industrial vacuum cleaner		○
Milling program		Can be selected acc. to EN, ISO, ASTM, etc.
CE conformity		●
Permissible ambient temperature	°C	+5 to +30
Permissible relative humidity		Max. 70%, non-condensing
Noise emission		85 dB(A) during the milling process
Width (milling table)	mm	500
Depth (milling table)	mm	300
Width	mm	900
Depth	mm	900
Height	mm	1700
Weight	kg	450
Voltage data		**3 ph 380/400 VAC 230 V, 50 Hz (other voltages on request)**

● included ○ available / optional □ eligible - not available

POLİNAR PLASTİK MAKİNE ve KALIP SANAYİ
TİCARET LİMİTED ŞİRKETİ
İkitelli O.S.B Eskoop San. Sit. D Blok
No: 34 Başakşehir / İSTANBUL - TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.polinar.com.tr

PTE (POLİNAR TEST EQUIPMENT)
İkitelli O.S.B. Eskoop San. Sit.
D Blok No.34 Başakşehir
İstanbul / TURKEY

Phone : +90 212 549 88 20 – 21
Fax : +90 212 549 88 19
E-Mail : info@polinar.com.tr

www.pte.com.tr

POLINAR GmbH
THE ICON VIENNA, Tower 24
Wiedner Gürtel 13 1100
Vienna AUSTRIA

Phone : +43 (0) 1 253535 4044
Fax : +43 (0) 1 253535 4044
Mobile : +43 676 5983869
E-Mail : office@polinar.at

www.polinar.at